

86 9606 041-3
RTMP's copy

DIEHL · GLAESER HITL & PARTNER

Patentanwalte · Flüggenstraße 13 · D-8000 München 19

Patentanwälte · European Patent Attorneys
MÜNCHEN · HAMBURG

Kanzlei/Office München
Flüggenstraße 13 · D-8000 München 19

Dr. Hermann O. Th. Diehl · Diplom-Physiker
Joachim W. Glaeser · Diplom-Ingenieur
Dr. Elmar Hittl · Diplom-Chemiker
Erich Burger · Diplom-Ingenieur

May 8, 1990 D/We
S 5209-EP

SEIKO EPSON CORPORATION
No. 4-1, Nishi-Shinjuku
2-chome, Shinjuku-ku
T O K Y O JAPAN

IMAGE FORMING DEVICE

Telefon
Telephone
(089) 17 70 61-63
(089) 1 78 43 00

Fernschreiber
Telex
5 215 145 zeus d

Telekopierer
Facsimile
(089) 1 78 40 33
(089) 1 78 40 34

Reuschebank
München
Kto.-Nr. 3 525 100
BLZ 700 303 00

Postgto
München
Kto.-Nr. 948 54-507
BLZ 700 100 20




IMAGE FORMING DEVICE

REPLACED SHEETS		SG
☒ Description	: paged1..... to paged9.....	
☒ Claim(s)	: paged10..... to paged-.....	
☒ Drawing(s)	: pagedX 1/4..... to pagedX 1/4.....	
☒ Abstract	: paged11..... to paged-.....	
DATE OF RECEIPT		

This invention relates to an image forming device.

To print a sentence created by an external device such as a host computer using a printer and the like, a general operation is that code signals for specifying characters used in the sentence are transferred to the printer through a cable and that the transferred code signals are converted into font data by the printer.

To this end, the code signals and the kinds of character are specified by the national standard. Taking European characters as an example, many countries assign common codes to main characters, but there are no common codes for characters and symbols unique to one particular language.

Thus, when there is no common standard in the relationship between characters and their character codes, it is necessary for a manufacturer of printers to prepare data serving to tie a set of code signals modified for its

particular end user to a set of characters; or it is sometimes desired that the character codes be changed by the user.

Although it is possible to make such a change on the set of character codes by entering a new set of character codes from an external entry means and storing them in a storage means with the printer started, once the printer has been turned off, the stored data is lost and it is necessary to enter the lost character code data once again at the restart of the printer. This complicates the printing operation.

The present invention has been made in consideration of the above problem and has as an object the provision of an image forming device allowing a specific set of character codes to be prepared for use in printing automatically at the start of a printer once a required set of symbols are once called by an ID and registered. This object is solved by the image forming device of independent claim 1. Further advantageous features of the invention are evident from the dependent claims and the following description and drawings. The claims are intended to be understood as a non-limiting first approach of defining the invention in general terms.

The image forming device of the present invention is capable of determining the relationship between a character code that specifies the kind of character and a character that corresponds to the character code in a printer and the like.

The invention provides an image forming device, which comprises: first storage means for storing a set of symbols in which a character and a code of a font to be used for image processing is tied by an ID; second storage means for storing said ID on a nonvolatile basis; and means for reading said set of symbols based on said ID by accessing said second storage means at a start time.



Fig. 1 is a block diagram showing an embodiment of an image forming device according to the present invention;

Fig. 2 is a schematic showing an embodiment of a circuit for storing character code correspondence data;

Fig. 3 is a schematic representation showing an example of a set of symbols;

Fig. 4 is a front view showing an embodiment of a panel screen;

Fig. 5 is a flow chart showing an operation of the device shown in Fig. 1;

Figs. 6a and 6b are diagrams showing examples of a menu screen in the symbol set registration mode and in the symbol set selection mode, respectively;

Fig. 7 is a schematic representation showing data to be stored in a symbol set storing circuit; and

Fig. 8 is a diagram showing the relationship between the character codes and the characters after a set of symbols has been changed.

Fig. 1 shows an embodiment of the present invention. In the figure, reference numeral 1 designates a character code correspondence data storage circuit, which has, as shown in Fig. 2, a number column 20 and a character column 21 and stores



data in which each of characters "A," "B," "C," "D," "E," ... is affixed by each of character numbers "1," "2," "3," "4," "5," As shown in Fig. 3, a character number column 22 and a character code column 23 are further arranged, by which a character code is made to correspond with a character through a character number; i.e., each character code "41h," "42h," "43h," "44h" ... is tied with each character number "1," "2," "3," "4," ... in correspondence, thereby allowing each character to be read based on the character code.

Returning to Fig. 1, reference numeral 2 designates a microcomputer comprising a central processing unit (CPU) 3, a read only memory (ROM) 4, and a random access memory (RAM) 5. This microcomputer 2 is operated based on a program such as shown by a flow chart (described later). Reference numeral 6 designates a panel for registering or selecting a set of characters, and, as shown in Fig. 4, it is arranged together with a symbol set registration key 11 for selecting a mode of registering a set of symbols, a symbol set selection key 12 for selecting the registered set of symbols, a symbol save key 13 for entering a command for storing a set of symbols to be registered upon definition of such a set of symbols, an online key 14 for selecting the printing mode, cursor movement keys 15, 16, 17, and 18 for selecting menu items, and a display unit 19 made of, e.g., a liquid crystal display.

This Sheet Has Been Replaced



Returning to Fig. 1 again, reference numeral 7 designates a menu screen data storage circuit, which is constructed so that it will store data for displaying a menu for making various entries and selections from the key or keys on the panel 6.

Reference numeral 8 designates the symbol set storage circuit comprising a nonvolatile storage element such as a RAM backed up by a battery or an electrically erasable ROM. The symbol set storage circuit is constructed so that it will store a set of symbols entered from the panel.

Reference numeral 9 designates an ID storage circuit comprising a nonvolatile storage element such as a RAM backed up by a battery or an electrically erasable ROM. The ID storage circuit is constructed so that it will store the ID of a selected set of symbols.

An operation of the device thus constructed will be described with reference to the flow chart shown in Fig. 5.

When the printer is powered (Step 50) and the printing mode is selected by the online key 14 (Step 53'), the microcomputer 2 accesses the ID storage circuit 9 to read ID data (Step 54'). It then accesses the symbol set storage circuit 8 to read symbol set data registered therein.


In this case, since there is no registered set of symbols, data in the character code correspondence data storage circuit 1 are developed in a work area (Steps 55' and 56'). That

is, characters are produced based on the character code-character correspondence data (Fig. 3) stored in the character code correspondence storage circuit 1; i.e., "A" in correspondence with the character code "41h," "B" to the character code "42h," and "C" to the character code "43h," and so on.

When printing data is entered under this condition (Step 57'), each character is applied to a character pattern generating device 10 to convert it to bit pattern data that is printable.

On the other hand, to change the correspondence between the character and the character code, the symbol set registration key 11 of the panel 6 is pressed (Step 51). As a result, a symbol set registration start command is received by the microcomputer 2, which then gets ready for accepting a new set of symbols and causes the display unit 19 to display a screen prompting the entry of an ID such as shown by part (I) of Fig. 6a.

When a number or symbol, e.g. "1," is entered by operating the ten key or the like under this condition, the microcomputer 2 causes the display unit 19 to display the ID "1" just entered. When the symbol save key 14 is subsequently pressed, the microcomputer 2 temporarily stores the ID "1" in a buffer or the like (Step 53). Then, when the cursor movement key 18 is pressed, the microcomputer 2 causes the display unit



19 to display a screen prompting the entry of a minimum value of a character code to be registered such as shown by part (II) of Fig. 6 (a) (Step 54). When the character code to be changed, e.g. "4lh," is entered from the ten key under this condition, and the symbol save key 14 is pressed, this is temporarily stored in the buffer or the like (Step 55).

After the minimum code has been stored, the microcomputer 2 causes the display unit 19 to display a screen prompting the entry of a maximum value of a character code to be changed (part III of Fig. 6a) (Step 56). When the maximum value of the character code to be changed, e.g. "45h," is entered and the symbol set save key 14 is pressed under this condition, the microcomputer 2 temporarily stores the maximum code in the buffer or the like (Step 57).

Subsequently, the microcomputer 2 causes the display unit 19 to display a screen requesting the input of the correspondence between the code to be changed and the character (part IV of Fig. 6a) (Step 58). The character numbers are entered in the order of array; i.e., "5," "4," "3," "2," and "1," under this condition (Step 58). Upon entry of the character numbers of the characters whose character codes are to be changed (Steps 59 and 60), the symbol set save key 14 is pressed (Step 61). Then, the microcomputer 2 stores the set of symbols just registered in the symbol set storage circuit 8 (Step 62). Accordingly, the data causing the character code

This Sheet Has Been Replaced



"41h" to correspond with the character number "5," the character code "42h" with the character number "4," the character code "43h" with the character number "3," the character code "44h" with the character number "2," and the character code "45h" with the character number "1" are stored in the symbol set storage circuit 8.

In case of registering another set of symbols, an ID that is different from the ID already registered is used. Thus, the set of symbols with the new ID will be registered in the symbol set storage circuit 8 as an independent set of symbols (areas II and III of Fig. 7).

In the case where a character code system different from that (Fig. 3) stored in the character code correspondence storage circuit 1, the symbol set selection key 12 is pressed (Step 52¹) so that the microcomputer 2 will cause a screen prompting the entry of an ID such as shown by part I of Fig. 6b to be displayed (Step 63). The ID now registered in the symbol set storage circuit 8, i.e. "1" in this case, is displayed on the display unit 19 and the symbol set save key 14 is pressed. If a plurality of IDs are registered, the microcomputer 2 causes each ID to be sequentially displayed every time the cursor movement key is pressed.

The microcomputer 2 then stores the ID "1" in the ID storage circuit 9 (Step 64) and moves to the printing mode (Step 53¹).



The microcomputer 2, under this condition, accesses the ID storage circuit 9 to read the ID "1" therein registered (Step 54'), accesses the symbol set storage circuit 8 to read the symbol set data registered with the ID "1" (Step 55'), and develop the read data in the work area.

Accordingly, it is possible to produce the characters based on the definition of the changed character codes as shown in Fig. 8.

If an ID has been registered in the ID storage circuit 9 by the previously described steps and the printing mode has been specified by the online key 13, the microcomputer 2, upon turning the power on, accesses the ID storage circuit 9 and automatically develops the new character-character code correspondence by the Steps 54' to 56'.

In the above embodiment, although a set of undefined characters and their codes are defined by grouping them with a minimum character code and a maximum character code, it goes without saying that the same effects will be obtained by defining the data on a single character basis.

This Sheet Has Been Replaced



CLAIMS:

1. An image forming device, comprising:
first storage means (8) for storing a set of symbols in which a character and a code of a font to be used for image processing is tied by an ID;
second storage means (9) for storing said ID on a nonvolatile basis; and
means (2) for reading said set of symbols based on said ID by accessing said second storage means (9) at a start time.
2. An image forming device as claimed in claim 1, wherein said first and second storage means comprise an electrically erasable read only memory, respectively.
3. An image forming device as claimed in claim 1, wherein said first and second storage means comprise a random access memory backed up by a battery, respectively.

This Sheet Has Been Replaced

