

VEHICLE REAR SIDE VIDEO MONITORING SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a vehicle rear side video monitoring system and more particularly, to such a vehicle rear side video monitoring system, which uses a CMOS image pickup device to pick up the image of the scene behind the vehicle under the illumination of a high brightness LED.

2. Description of Related Art

Due to limited parking space and a big number of cars, it is difficult to park a car in a city. Therefore, it is important to move the car backward rapidly and to park the car on the side of a road safely. According to the designs of conventional cars, the driver has a visual dead angle corresponding to the two opposite lateral sides and the rear side of the body of the car. Further, a car may be equipped with a soundproof structure around the driver's seat, and the driver may be unable to hear abnormal noises before occurrence of an accident when driving the car. In this case, a traffic accident may happen.

Further, a car may be equipped with a CCD (Charge-coupled Device) camera for picking up the image of the scene behind the car. However, a CCD camera is quite expensive, not popularly accepted by car owners. Further, a CCD camera has a bulky size and heavy weight, and is not easy to install. When a CCD camera is used and installed in the rear side of a car, it may fail easily upon heavy vibration of the rear side of the car.

Therefore, it is desirable to provide a vehicle rear side video monitoring system that eliminates the aforesaid drawbacks.

SUMMARY OF THE INVENTION

The present invention provides a vehicle rear side video monitoring system installed in a motor vehicle. The vehicle rear side video monitoring system comprises a CMOS (Comprehensive Metal Oxide Semiconductor) image pickup device, at least one high brightness LED, a display unit, and a controller. The CMOS image pickup device is installed in a specific position of a rear side of the motor vehicle and adapted to pick up and process an image of the scene behind the motor vehicle and to output a corresponding video signal. The at least one high brightness LED is installed in an another specific position of the rear side of the motor vehicle near the specific position. The display unit is mounted inside the motor vehicle. The controller is electrically connected to the CMOS image pickup device, the at least one high brightness LED, and the display unit, wherein the controller controls the at least one high brightness LED to give off light when controlling the CMOS image pickup device to pick up and process the image of the scene behind the motor vehicle, and controls the display unit to display the image of the scene behind the motor vehicle.

Because the system uses a CMOS image pickup device with a high brightness LED, the cost of the parts is less expensive. Further, because the CMOS image pickup device and the high brightness LED have a small size and a light weight, they can easily be installed in the rear side of the motor vehicle for a long service without failure.

The at least one high brightness LED each can be a high brightness white light LED or other color of high brightness LED, and can be installed in the license housing at the rear side of the motor vehicle above the license plate or another suitable location.

5 The CMOS image pickup device is preferably installed in a rear bumper of the motor vehicle. The CMOS image pickup device can also be installed in the rearview mirror or any other suitable location of the motor vehicle where the CMOS image pickup device can pick up the image of the scene behind the motor vehicle clearly.

10 The display unit can be a LCD, CRT monitor, head-up display, or any of a variety of suitable display devices.

 The vehicle rear side video monitoring system further comprises a starting device electrically connected to the controller and controllable to output a starting signal to the controller, the controller fetches the starting
15 signal to accordingly drive the at least one high brightness LED to give off light. The starting device can be a reverse gear transmission device of the motor vehicle, a photo sensor, an electronic clock, a wireless receiver, or any of a variety of other equivalent means capable of driving the controller to start the at least one high brightness LED and the CMOS image pickup
20 device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a system block diagram of a vehicle rear side video monitoring system according to the present invention.

FIG. 2 is a schematic drawing showing an installation example of

the vehicle rear side video monitoring system according to the present invention.

FIG. 3 is a sectional view in an enlarged scale of a part of FIG. 2, showing the positioning of the CMOS image pickup device and the high
5 brightness LED in the rear side of the car.

FIG. 4 is a schematic drawing showing a Head-up Display installed in the instrument panel of the car and operated according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

10 Referring to FIGS. 1 and 2, a vehicle rear side video monitoring system is shown installed in the rear side of a car **1**, comprising a CMOS (Comprehensive Metal Oxide Semiconductor) image pickup device **11**, a high brightness LED (light emitting diode) **12**, a display unit **13**, and a controller **14**. The controller **14** controls the high brightness LED **12** to give
15 off light, the CMOS image pickup device **11** to pick up and process the image **S** of the scene behind the car **1**, and the display unit **13** to display the processed image **S**.

Because the CMOS image pickup device **11** and the high brightness LED **12** are compact, they can easily be installed in the limited space at the
20 rear side of the car **1**. Further, the cost of these two parts is relatively lower to a conventional CCD camera, thereby highly competitive in the market. Further, these two parts are light in weight, not easy to be damaged upon vibration. Comparing to conventional CCD cameras, the invention is more durable in use.

According to this embodiment, the display unit **13** is a LCD (liquid crystal display) **131**. Further, the CMOS image pickup device **11** comprises an image pickup lens installed in the rear bumper **101** of the car **1** and adapted to pick up the image **S** of the scene behind the car **1** for processing
5 by the CMOS image pickup device **11**, causing the CMOS image pickup device **11** outputs a corresponding video signal **M**. The image pickup lens of the CMOS image pickup device **11** is most preferably installed in the rear bumper **101** of the car **1** around the center area **L1** to pick up the image **S** of the scene behind the car **1** clearly, preventing incomplete rear side image
10 due to dead angle around the border area of the rear side of the car **1**. Alternatively, the CMOS image pickup device **11** can be installed in the rearview mirror **102** at the left/right side of the car **1**.

Because the invention uses the CMOS image pickup device **11** to pick up images, a relatively higher surrounding illumination is needed so
15 that a high quality of the image **S** of the scene behind the car **1** can be obtained. Therefore, the invention uses the aforesaid high brightness LED **12** to provide sufficient illumination. According to this embodiment, the high brightness LED **12** is a high brightness white light LED for the advantage of low color difference.

20 The high brightness LED **12** is preferably installed in the center area of the rear side of the car **1** adjacent to the rear bumper **101**, for example, in the license light housing **12** at the rear side of the car **1** above the license plate **103**, as shown in FIG. 3, where the high brightness LED **12** is well protected against weather and can effectively enhance the exposure of the

CMOS image pickup device **11** to pick up the image **S** of the scene behind the car **1**. Alternatively, the high brightness LED **12** can be installed in the rear bumper, left/right rearview mirror, below the rear cowling, or any other suitable location at the car **1** where the high brightness LED **12** can be well
5 protected against weather.

The vehicle rear side video monitoring system further comprises a starting device **10** adapted to controls on/off of the high brightness LED **12**. The starting device **10** is electrically connected to the controller **14** and adapted to output a starting signal **A** to the controller **14**. Upon receipt of the
10 starting signal **A** from the starting device **10**, the controller **14** immediately turns on the high brightness LED **12**. Different starting devices may be used to drive the controller **14** to turn on/off the high brightness LED **12** subject to different conditions. For example, in FIGS. 1 and 4, the starting device **10** is the reverse gear transmission device **15**, and the starting signal **A** is a
15 reverse shift signal **A1**. When the driver operating the reverse gear transmission device **15** to reverse the moving direction of the car **1**, the reverse gear transmission device **15** outputs a reverse shift signal **A1** to the controller **14**, causing the controller **14** to turn on the high brightness LED **12** and to drive the CMOS image pickup device **11** to pick up the image **S** of
20 the scene behind the car **1**. At this time, the high brightness LED **12** provides sufficient illumination to the CMOS image pickup device **11**, enabling the CMOS image pickup device **11** to pick up the image **S** of the scene behind the car **1** clearly. The image **S** will then be displayed on the LCD **131** subject to the control of the controller **14**.

Further, as shown in FIG. 4, the image **S** can be displayed through a Head-up Display **132**, which is installed in the instrument panel **105** near the front side and adapted to project images onto the front windshield **106**.

Referring to FIG. 1 again, the starting device **10** can be a photo sensor **16** adapted to detect the intensity of the surrounding light. When the intensity of the surrounding light is below a predetermined level (lumen), the photo sensor **16** outputs a low illumination signal **A2** to the controller **14**, causing the controller **14** to turn on the high brightness LED **12** and to drive the CMOS image pickup device **11** to pick up the image **S** of the scene behind the car **1**.

Referring to FIG. 1 again, the starting device **10** can be an electronic clock **17**, which has the alarm function for enabling the user to set the alarm time. When the set time is up, the electronic clock **17** outputs an alarm signal **A3**. For example, the owner of the car **1** can set the electronic clock **17** to output the alarm signal **A3** to the controller **14** at a particular time within the nighttime period from PM6:00 through AM6:00, causing the controller **14** to turn on the high brightness LED **12** and to drive the CMOS image pickup device **11** to pick up the image **S** of the scene behind the car **1**. The aforesaid particular time can be provided by the electronic clock **17** itself, or by an on-vehicle time counting or time signal means, for example, satellite signal containing a satellite time signal from an on-vehicle GPS (Global Positioning System).

Further, the owner of the car can use a remote controller **182** to send a wireless signal **A4** to a wireless receiver **181**, causing the wireless

receiver **181** to transmit the wireless signal **A4** to the starting device **10** and then the controller **14** for controlling the operation of the high brightness LED **12**.

Except the aforesaid various different forms of the starting device
5 **10**, the starting device **10** can be as simple as a single push button, audio switch, or their combination. One single button or switch is sufficient for controlling the high brightness LED **12** to give off light and the CMOS image pickup device **11** to pick up the image **S** of the scene behind the car **1**.

Although the present invention has been explained in relation to its
10 preferred embodiment, it is to be understood that many other possible modifications and variations can be made without departing from the spirit and scope of the invention as hereinafter claimed.

WHAT IS CLAIMED IS:

1. A vehicle rear side video monitoring system installed in a motor vehicle, comprising:

a CMOS (Comprehensive Metal Oxide Semiconductor) image pickup device installed in a specific position of a rear side of said motor vehicle and adapted to pick up and process an image of the scene behind said motor vehicle and to output a corresponding video signal;

at least one high brightness LED (light emitting diode) installed in an another specific position of the rear side of said motor vehicle near said specific position;

a display unit mounted inside said motor vehicle; and

a controller electrically connected to said CMOS image pickup device, said at least one high brightness LED, and said display unit, wherein said controller controls said at least one high brightness LED to give off light when controlling said CMOS image pickup device to pick up and process the image of the scene behind said motor vehicle, and controls said display unit to display the image of the scene behind said motor vehicle.

2. The vehicle rear side video monitoring system as claimed in claim 1, wherein said at least one high brightness LED includes a high brightness white light LED.

3. The vehicle rear side video monitoring system as claimed in claim 1, further comprising a starting device electrically connected to said controller and controllable to output a starting signal to said controller, said controller fetches said starting signal to accordingly drive said at least one

high brightness LED to give off light.

4. The vehicle rear side video monitoring system as claimed in claim 3, wherein said starting device is a reverse gear transmission device; said starting signal is a reverse shift signal produced by said reverse gear
5 transmission device when in a reverse gear shift thereof.

5. The vehicle rear side video monitoring system as claimed in claim 3, wherein said starting device comprises a photo sensor; said starting signal is a low illumination signal produced by said photo sensor when in low illuminations.

10 6. The vehicle rear side video monitoring system as claimed in claim 3, wherein said starting device comprises an electronic clock; said starting signal is an alarm signal produced by said electronic clock.

7. The vehicle rear side video monitoring system as claimed in claim 3, wherein said starting device comprises a wireless receiver, and a
15 remote controller; said starting signal is a wireless signal produced by said remote controller.

8. The vehicle rear side video monitoring system as claimed in claim 1, wherein said CMOS image pickup device is installed in a rear bumper of said motor vehicle.

20 9. The vehicle rear side video monitoring system as claimed in claim 1, wherein said CMOS image pickup device is installed in one rearview side-mirror of said motor vehicle.

10. The vehicle rear side video monitoring system as claimed in claim 1, wherein said at least one high brightness LED is installed in a

license light housing at the rear side of said motor vehicle adjacent to a license plate.

11. The vehicle rear side video monitoring system as claimed in claim 1, wherein said display unit comprises an LCD (liquid crystal
5 display).

12. The vehicle rear side video monitoring system as claimed in claim 11, wherein said display unit comprises a head-up display installed in an instrument panel of said motor vehicle and facing to a front windshield of said motor vehicle.

10