

Description

The present invention relates to an outlet device for coin payout hoppers used in gaming machines coin exchangers or the like.

Hitherto, there is a coin payout hopper as described in U.S. Patent No. 4,437,478 comprising a hopper for storing coins, a rotary disc rotatably mounted within said hopper at an angle to the horizontal, a plurality of delivery pins spaced in the peripheral direction of the rotary disc, a delivery knife for guiding coins at the upper delivery portion to a discharge chute.

Some coin payout hoppers of the type mentioned above are provided with an outlet device which comprises an outlet chute for receiving coins discharged from the discharge chute of the coin payout hopper and an escalator which is connected to the outlet chute at the lower end thereof and upwardly extended from the outlet chute for transferring coins to a coin tray which is elevated from the hopper as described in U.S. Patent No. 4,518,001.

The escalator is in the form of an elongated trough composed of front and back side plates and a pair of edge plates interposed between the side edges of the side plates respectively to define an upwardly extending straight coin guide passage adapted for pushing up coins in single edge-to-edge file or stack in the trough to the upper outlet end thereof by mutual thrust of coins pushed into the outlet chute, for example, by means of the delivery pins of the coin payout hopper.

In the conventional outlet device, as shown in Figs. 9 and 10, the outlet chute 1 is composed of front and back side plates 7 and 8 and edge plates 11 and 12 interposed between the side plates to define a curved coin guiding passage 4 extending from a lower inlet 3 receiving coins 2 from a discharge chute of a payout hopper to an upper outlet 5 connected to the lower end of an elevator 6. The curved coin guiding passage has a depth between the front and back plates greater than the thickness of the coins, but less than twice the thickness of the coins and a width between the edge plates also greater than the diameter of the coins. The width of the curved coin guiding passage is defined by the opposed coin guiding edge faces 9 and 10 of the edge plates 11 and 12 positioned in the outer and inner sides in relation to a center of curvature of the curved guiding passage 4, respectively. The front side plate 7 in the case shown in Figs. 9 and 10 is divided to an inner front side plate 7A and an outer front side plate 7B which are spaced to define a window 13 extending along the curved coin passage 4. The inner and outer front side plates 7A and 7B are rigidly secured to the back side plate 8 together with the

edge plates 11 and 12 by means of screws 14 and 15. The outer and inner front side plates 7A and 7B have extensions 7a and 7b beyond the coin guiding edge face 9 and 10 of the edge plate 11 and 12 respectively to provide gutters for engaging with the outer peripheral portion of the coins to retain the coins in the curved guiding passage and to prevent the coins from dropping out of the passage. Thus, the outlet chute 1 receives coins 2 pushed in the lower inlet 3 in the horizontal direction as shown by an arrow "A" and guides their in single edge-to-edge file in the curved guiding passage 4 defined by the front side plate 8, a pair of the edge plates 11 and 12 and both the front side plates 7A and 7B towards the upper outlet 5 in the vertical direction as shown by an arrow "B" by mutual thrust of coins.

Such a conventional outlet device as mentioned above has drawbacks such that a deformed coin can be jammed in the guiding passage by outwardly or inwardly pushing by an edge of the adjacent coin slipping behind or in front of the deformed coin against the side plates to stop up the coins in the guiding passage. Particularly, when the height of the escalator is higher the weight of coins subjected to the coins in the curved guiding passage is larger, as the result the tendency of jamming by the deformed coin is increased. Accordingly, not only the height of the escalator is limited, but also the efficiency of payout is decreased.

An object of the invention is to remove the drawbacks mentioned above and to provide an outlet device having a high lift and a high efficiency without jamming of coins.

According to the present invention, the outlet device for coin payout hoppers comprises an outlet chute having a curved coin guiding passage for upwardly guiding coins pushed in at a lower inlet in the horizontal direction towards an upper outlet in the vertical direction and an escalator connected to the outlet chute at the lower end thereof and composed of opposite side plates and edge plates interposed between the side edges of the side plates to define a coin guide passage upwardly extending from the upper outlet of the curved guiding passage of the outlet chute, characterized in that said outlet chute comprises a back side plate and a pair of inner and outer edge plates secured to the opposite edge portions of the back side plate such as to define an open curved coin guiding passage by exposing at least one of the opposed coin guiding edge faces of the inner and outer edge plate and such as to space the opposed coin guiding edge faces of the edge plates from each other by a distance corresponding to a diameter of the coin to be handled and a front side plate covering only the inner edge plate positioned in the

inner side in relation to a center of curvature of the curved coin guiding passage and having an extension protruded beyond the inner coin guiding edge face of the inner edge plate, at least the edge face of the outer edge plate positioned in the outer side in relation to the center of curvature being inclined to the back side plate at an angle θ . The above mentioned arrangement of the outlet chute permits a deformed coin to drop out of the curved guiding passage otherwise when the deformed coin is, for example, outwardly pushed by the edge of the adjacent coin slipping behind or in front of the deformed coin, this deformed coin is jammed against the side plates to clog the guiding passage.

In an embodiment of the invention for more effectively dropping out the deformed coin from the curved guiding passage of the outlet chute to completely prevent any slightly deformed coins from passing into the guiding passage of the elevator composed of the front and back plates and a pair of the edge plates. In this embodiment, the outlet chute comprises a back side plate and a pair of inner and outer edge plates secured to the opposite edge portions of the back side plate such as to define an open curved coin guiding passage by exposing at least one of the opposed coin guiding edge faces of the inner and outer edge plate and wherein each of said edge plates has a coin guiding edge face inclined to the back side plate. The outer guide plate is rigidly fixed to the back side plate, while the inner edge plate is rotatably pivoted to the back side plate at the inner end thereof and is connected to the fixed outer guide plate by means of tension spring secured to the outer portion of the movable inner edge plate.

In a further embodiment of the invention for enabling to increase the coin lifting height of the escalator wherein the front side plate having a window is provided with means for holding coins at their pushed up position in the trough to prevent the coins from descending when the feeding out operation of the payout hopper is stopped. The coin holding means includes a ball retaining gutter having a sloped guide wall extending along the trough at an acute angle α such as 8-15° to the front side plate and a coin holding ball which is vertically movably retained in the ball retaining gutter and protrudes from the opening of the ball retaining gutter into the coin guiding passage to contact the side surface of the coin in the coin guiding passage, thereby to hold the coin by wedging effect of the ball moved downwardly in the tapered guide gutter when the coin tends to descend in the coin guiding passage.

In a further embodiment of the invention for efficiently feeding out the coins from the upper end outlet of coin guiding passage of the escalator comprising an upper end outlet upwardly opened

at the top end of the coin guiding passage, a coin pushing out roller provided at an upper end of a supporting lever pivoted at the one side of the passage and resiliently urged toward the center of the upper end outlet, means for latching the roller supporting lever in the closed position of the roller, an electromagnetic solenoid for releasing the latching means upon operating the payout hopper, and a counter actuated by the roller supporting lever.

Fig. 1 is an elevational view of a first embodiment of the outlet chute of the outlet device according to the present invention;

Fig. 2 is a cross-sectional view taken on the line II - II in Fig. 1;

Fig. 3 is a schematic perspective view illustrating a coin payout hopper provided with the outlet chute shown in Fig. 1 according to the invention;

Fig. 4 is an enlarged elevational view of a portion of the escalator shown in Fig. 3 illustrating coin holding means;

Fig. 5 is a cross-sectional view taken on the line V - V in Fig. 4;

Fig. 6 is a cross-sectional view taken on the line VI - VI in Fig. 4;

Fig. 7 is an enlarged elevational view of the upper end portion of the escalator shown in Fig. 3;

Fig. 8 is an elevational view of a second embodiment of the outlet chute;

Fig. 9 is an elevational view of a conventional outlet chute; and

Fig. 10 is a cross-sectional view taken on the line X - X in Fig. 9.

The present invention will be more fully described with reference to Figs. 1-8.

Referring to Figs. 1 and 2 illustrating the first embodiment, an outlet chute 1 of an outlet device is generally arranged such as to receive coins 2 pushed in a lower inlet 3 in the horizontal direction as shown by an arrow "A" from a coin payout hopper and guide the coins in single edge-to-edge file in a curved coin guiding passage 4 to convert the coin in the vertical direction towards an upper outlet 5 as shown by an arrow "B". The upper outlet 5 is connected to the lower end of an escalator of the outlet device.

As shown in Fig. 2, an outer edge plate 11 which has an outer coin guiding edge face 9 positioned at the outer side in relation to a center of curvature of the curved coin guiding passage 4 is fixedly secured to a back side plate 8 by means of screws 14 and an inner edge plate 12 which has an inner coin guiding edge face 10 positioned at the inner side in relation to the center of curvature of the curved coin guiding passage 4 is fixedly secured to the back side plate 8 together with an inner front side plate 7A by means of a screw 15. The

inner front side plate 7A has an extension 7a protruded beyond the inner edge face 10.

The outer edge face 9 is inclined to the back side plate 8 at an acute angle θ of about 70° without any means for preventing the coins from dropping out of the curved coin guide passage.

Referring to Fig. 3 illustrating a coin payout hopper provided with the outlet chute 1, an escalator 6 is connected to the upper outlet 5 of the outlet chute at the lower end thereof. The escalator 6 is provided with coin retaining means 17 on the front side plate 18 having a window 19. The coin holding means 17 includes a coin holding ball 20 which is vertically movably retained in a ball retaining gutter 21 of ball retainer. As shown in Figs. 5 and 6, the ball retaining gutter 21 has a sloped guide wall 23 extending along the longitudinal direction of the escalator at an angle α such as $8-15^\circ$, preferably 10° to the surface "a" of the front side plate 18 to define a ball retaining space which is downwardly constricted.

The coin holding means 17 provided along the escalator permits coins 2 in the coin guiding passage 22 of the escalator 6 to move upwardly when the coins 2 are pushed up by coins discharged from the coin payout hopper since the coin holding ball 20 is also pushed up by the ascending coins and retained in the upper wide portion in the tapered space within the ball retaining gutter 21. While the coins are held in the pushed up position in the coin guiding passage 22 by the coin holding ball 20 when the operation of the coin payout hopper is stopped, since the coin holding ball drops in the tapered ball retaining space which is downwardly restricted and a wedging effect is applied to the coin by the coin holding ball 20 to prevent the coin from descending in the coin guiding passage.

It is understood that the coins are held at their pushed up positions in the coin guiding by the coin holding ball 20 so that a downward thrust caused by the weight of coins above the coin held by the coin holding ball is supported by the coin holding ball, as the result the upward thrust required for pushing up the coins in the coin guiding passage is decreased and the tendency of jamming coins in the coin guiding passages of the escalator and of dropping coins out of the outlet chute is remarkably decreased so that it is possible to make higher the coin lifting height of the escalator than that of the conventional escalator without jamming of coins.

Referring to Fig. 7 illustrating the upper end portion of the escalator, an upper end outlet 25 is upwardly opened at the top end of the coin guiding passage 22 of the escalator 6 such as to discharge coins to an inlet 26 of a coin tray. A coin pushing out roller 27 is provided at an upper end 28a of a supporting lever 28 which is pivoted at a pivot pin

29 on a side plate 30 secured to the upper end portion of the escalator. The coin pushing out roller 27 is normally positioned in the center of the upper end outlet 25 by resiliently urging the upper end 28a of the supporting lever 28 toward the center of the upper end of the escalator by means of a spring 31 and locking the supporting lever 28 by a latch lever 32 engaging with the lower end 28b of the supporting lever 28 at one end 32a by a spring 33 which can be connected to the other end 32b. The supporting lever 28 is pivoted at a pivot pin 34 to the side plate 30 and connected to an actuating rod 35 of an electromagnetic solenoid 36 by means of a pin 37 such as to release the engagement of the lower end 28b and the engaging end 32a upon energizing of the solenoid 36 to permit a coin pushed up in the coin guiding passage 22 to displace the pushing up roller 27 from the center position shown by a solid line to a side position shown by a dotted line against force of the spring 31 and then pass through the upper end outlet 25 between the pushing up roller 27 and a fixed roller 38. When the coin is discharged through the upper end outlet 25, the roller supporting lever 28 is angularly moved about the pivot pin 29 and then a proximity switch 39 of a coin counter is actuated by an arm 40 of the lever 28.

Referring to Fig. 8 illustrating a second embodiment of the outlet chute 1. In this embodiment, the outlet chute 1 is composed of a back side plate 8 and a pair of outer and inner edge plates 11 and 45 each of which has an edge face 9, 46 inclined to the back side plate 8. The outer edge plate 11 is fixedly secured to the back side plate 8, while the inner edge plate 45 is rotatably pivoted to the back side plate 8 at the inner end by a pivot pin 47. The movable inner edge plate 11 is connected to the fixed outer guide plate 11 by at least one spring 48 which is connected between a pin 49 on the outer edge plate 11 and a pin 50 on the inner edge plate 45 to contact the edge of the coin 2 in the curved coin guiding passage 4 with both sloped edge faces 9 and 46 of the outer and inner edge plates 11 and 45. Preferably, the thickness of at least the outer guide plate is thinner than that of the coin to be handled.

Claims

1. An outlet device for coin payout hoppers comprising an outlet chute (1) having a curved coin guiding passage (4) for upwardly guiding coins pushed in at a lower inlet (3) in the horizontal direction towards an upper outlet (5) and an escalator (6) connected to the outlet chute (1) at the lower end thereof and composed of front and back side plates and a pair of edge plates interposed between the side edges of the side



inner front side plate 7A has an extension 7a protruded beyond the inner edge face 10.

The outer edge face 9 is inclined to the back side plate 8 at an acute angle θ of about 70° without any means for preventing the coins from dropping out of the curved coin guide passage.

Referring to Fig. 3 illustrating a coin payout hopper provided with the outlet chute 1, an escalator 6 is connected to the upper outlet 5 of the outlet chute at the lower end thereof. The escalator 6 is provided with coin retaining means 17 on the front side plate 18 having a window 19. The coin holding means 17 includes a coin holding ball 20 which is vertically movably retained in a ball retaining gutter 21 of ball retainer. As shown in Figs. 5 and 6, the ball retaining gutter 21 has a sloped guide wall 23 extending along the longitudinal direction of the escalator at an angle α such as $8-15^\circ$, preferably 10° to the surface "a" of the front side plate 18 to define a ball retaining space which is downwardly constricted.

The coin holding means 17 provided along the escalator permits coins 2 in the coin guiding passage 22 of the escalator 6 to move upwardly when the coins 2 are pushed up by coins discharged from the coin payout hopper since the coin holding ball 20 is also pushed up by the ascending coins and retained in the upper wide portion in the tapered space within the ball retaining gutter 21. While the coins are held in the pushed up position in the coin guiding passage 22 by the coin holding ball 20 when the operation of the coin payout hopper is stopped, since the coin holding ball drops in the tapered ball retaining space which is downwardly restricted and a wedging effect is applied to the coin by the coin holding ball 20 to prevent the coin from descending in the coin guiding passage.

It is understood that the coins are held at their pushed up positions in the coin guiding by the coin holding ball 20 so that a downward thrust caused by the weight of coins above the coin held by the coin holding ball is supported by the coin holding ball, as the result the upward thrust required for pushing up the coins in the coin guiding passage is decreased and the tendency of jamming coins in the coin guiding passages of the escalator and of dropping coins out of the outlet chute is remarkably decreased so that it is possible to make higher the coin lifting height of the escalator than that of the conventional escalator without jamming of coins.

Referring to Fig. 7 illustrating the upper end portion of the escalator, an upper end outlet 25 is upwardly opened at the top end of the coin guiding passage 22 of the escalator 6 such as to discharge coins to an inlet 26 of a coin tray. A coin pushing out roller 27 is provided at an upper end 28a of a supporting lever 28 which is pivoted at a pivot pin

29 on a side plate 30 secured to the upper end portion of the escalator. The coin pushing out roller 27 is normally positioned in the center of the upper end outlet 25 by resiliently urging the upper end 28a of the supporting lever 28 toward the center of the upper end of the escalator by means of a spring 31 and locking the supporting lever 28 by a latch lever 32 engaging with the lower end 28b of the supporting lever 28 at one end 32a by a spring 33 which can be connected to the other end 32b. The supporting lever 28 is pivoted at a pivot pin 34 to the side plate 30 and connected to an actuating rod 35 of an electromagnetic solenoid 36 by means of a pin 37 such as to release the engagement of the lower end 28b and the engaging end 32a upon energizing of the solenoid 36 to permit a coin pushed up in the coin guiding passage 22 to displace the pushing up roller 27 from the center position shown by a solid line to a side position shown by a dotted line against force of the spring 31 and then pass through the upper end outlet 25 between the pushing up roller 27 and a fixed roller 38. When the coin is discharged through the upper end outlet 25, the roller supporting lever 28 is angularly moved about the pivot pin 29 and then a proximity switch 39 of a coin counter is actuated by an arm 40 of the lever 28.

Referring to Fig. 8 illustrating a second embodiment of the outlet chute 1. In this embodiment, the outlet chute 1 is composed of a back side plate 8 and a pair of outer and inner edge plates 11 and 45 each of which has an edge face 9, 46 inclined to the back side plate 8. The outer edge plate 11 is fixedly secured to the back side plate 8, while the inner edge plate 45 is rotatably pivoted to the back side plate 8 at the inner end by a pivot pin 47. The movable inner edge plate 11 is connected to the fixed outer guide plate 11 by at least one spring 48 which is connected between a pin 49 on the outer edge plate 11 and a pin 50 on the inner edge plate 45 to contact the edge of the coin 2 in the curved coin guiding passage 4 with both sloped edge faces 9 and 46 of the outer and inner edge plates 11 and 45. Preferably, the thickness of at least the outer guide plate is thinner than that of the coin to be handled.

Claims

1. An outlet device for coin payout hoppers comprising an outlet chute (1) having a curved coin guiding passage (4) for upwardly guiding coins pushed in at a lower inlet (3) in the horizontal direction towards an upper outlet (5) and an escalator (6) connected to the outlet chute (1) at the lower end thereof and composed of front and back side plates and a pair of edge plates interposed between the side edges of the side



plates to define a coin guiding passage (22) upwardly extending from the upper outlet (5) of the curved coin guiding passage (4) of the outlet chute (1), characterised in that said outlet chute (1) comprises a back side plate (8) and a pair of inner and outer edge plates (11, 12) secured to the opposite edge portions of the back side plate (8) such as to define an open curved coin guiding passage (4) by exposing at least one of the opposed coin guiding edge faces (9,10) of the inner and outer edge plate and such as to space the opposed coin guiding edge faces (9, 10) of the edge plates (11, 12) from each other by a distance corresponding to a diameter of the coin to be handled, and a front side plate covering only the inner edge plate (7A) positioned in the inner side in relation to a center of curvature of the curved coin guiding passage and having an extension (7a) protruded beyond the inner coin guiding edge face (10) of the inner edge plate (12), at least the edge face (9) of the outer edge plate (11) positioned in the outer side in relation to the center of curvature of the curved coin guiding passage (4) being inclined to the back side plate (8) at an angle θ

2. An outlet device for coin payout hoppers comprising an outlet chute (1) having a curved coin guiding passage (4) for upwardly guiding coins pushed in at a lower inlet (3) in the horizontal direction towards an upper outlet (5) and an escalator (6) connected to the outlet chute (1) at the lower end thereof and composed of front and back side plates and a pair of edge plates interposed between the side edges of the side plates to define a coin guiding passage (22) upwardly extending from the upper outlet (5) of the curved coin guiding passage (4) of the outlet chute (1), characterised in that said outlet chute (1) comprises a back side plate (8) and a pair of inner and outer edge plates (11, 12) secured to the opposite edge portions of the back side plate (8) such as to define an open curved coin guiding passage (4) by exposing at least one of the opposed coin guiding edge faces (9, 10) of the inner and outer edge plate and wherein each of said edge plates (11, 12) has a coin guiding edge face (9, 10) inclined to the back side plate (8), the outer edge plate being rigidly fixed to the back side plate (8), while the inner edge plate (45) is rotatably pivoted to the back side plate (8) at the inner end thereof and is connected to the fixed outer edge plate (11) by means of tension spring (48) secured to the outer portion of the movable inner edge plate (45).

3. A device according to either one of claims 1 and 2 wherein said escalator comprises means for holding coins (17) including a ball retaining gutter (21) having a sloped guide wall (23) extending along the trough at an acute angle α and such as 8-15° to the front side plate (18) and a coin holding ball (20) which is vertically movably retained in the ball retaining gutter (21) and protrudes from the opening of the ball retaining gutter and an opening (19) in the front side plate (18) into the coin guiding passage (22) to contact the side surface of the coin in the coin guiding passage (22), thereby to hold the coin by wedging effect of the ball moved downwardly in the tapered guide gutter (21) when the coin tends to descend in the coin guiding passage.
4. A device according to either one of claims 1 and 2 wherein said escalator comprises an upper end outlet (25) upwardly opened at the top end of the coin guiding passage (22), a coin pushing out roller (27) provided at an upper end of a supporting lever (28) pivoted at the one side of the passage and resiliently urged toward the center of the upper end outlet (25), means for latching (32) the roller supporting lever (28) in the closed position of the roller, an electromagnetic solenoid (36) for releasing the latching means (32) upon operating the payout hopper, and a counter (39) actuated by the roller supporting lever.

Patentansprüche

1. Ausgabevorrichtung für Münzauszahlbehälter, umfassend einen Ausgabeschacht (1) mit einem gekrümmten Münzleitdurchgang (4) für Aufwärtsführung von an einem unteren Einlaß (schlitz) (3) in der waagerechten Richtung eingeschobenen Münzen zu einem oberen Auslaß (6) und eine am unteren Ende mit dem Ausgabeschacht (1) verbundene Steig- oder Stufenbahn (6), bestehend aus vorderen und hinteren Seitenplatten sowie einem Paar von zwischen die Seitenränder der Seitenplatten eingefügten Randplatten zur Festlegung eines Münzleitdurchgangs (22), der vom oberen Auslaß (5) des gekrümmten Münzleitdurchgangs (4) des Ausgabeschachts (1) aufwärts verläuft, dadurch gekennzeichnet, daß der Ausgabeschacht (1) eine hintere Seitenplatte (8) und ein Paar innerer und äußerer Randplatten (11, 12), die an den gegenüberliegenden Randabschnitten der hinteren Seitenplatte (8) so befestigt sind, daß ein offener gekrümmter Münzleitdurchgang (4) festgelegt ist, indem mindestens eine der gegenüberliegenden Münzlei-



randflächen (9, 10) von innerer und äußerer Randplatte freigelegt ist, und daß die gegenüberliegenden Münzleitrandflächen (9, 10) der Randplatten (11, 12) in einem Abstand entsprechend einem Durchmesser der zu behandelnden Münze voneinander angeordnet sind, und eine vordere Seitenplatte aufweist, die nur die innere Randplatte (7A) bedeckt, welche in bezug auf ein Krümmungszentrum des gekrümmten Münzleitdurchgangs an der Innenseite angeordnet ist und einen über die innere Münzleitrandfläche (10) der inneren Randplatte (12) hinaus vorstehenden Fortsatz (7a) aufweist, wobei zumindest die Randfläche (9) der in bezug auf das Krümmungszentrum des gekrümmten Münzleitdurchgangs (4) an der Außenseite positionierten äußeren Randplatte (11) unter einem Winkel θ zur hinteren Seitenplatte (8) geneigt ist.

2. Ausgabevorrichtung für Münzauszahlbehälter, umfassend einen Ausgabeschacht (1) mit einem gekrümmten Münzleitdurchgang (4) für Aufwärtsführung von an einem unteren Einlaß (schlitz) (3) in der waagerechten Richtung eingeschobenen Münzen zu einem oberen Auslaß (6) und eine am unteren Ende mit dem Ausgabeschacht (1) verbundene Steig- oder Stufenbahn (6), bestehend aus vorderen und hinteren Seitenplatten sowie einem Paar von zwischen die Seitenränder der Seitenplatten eingefügten Randplatten zur Festlegung eines Münzleitdurchgangs (22), der vom oberen Auslaß (5) des gekrümmten Münzleitdurchgangs (4) des Ausgabeschachts (1) aufwärts verläuft, dadurch gekennzeichnet, daß der Ausgabeschacht (1) eine hintere Seitenplatte (8) und ein Paar innerer und äußerer Randplatten (11, 12), die an den gegenüberliegenden Randabschnitten der hinteren Seitenplatte (8) so befestigt sind, daß ein offener gekrümmter Münzleitdurchgang (4) festgelegt ist, indem mindestens eine der gegenüberliegenden Münzleitrandflächen (9, 10) von innerer und äußerer Randplatte freigelegt ist, aufweist und daß jede der Randplatten (11, 12) eine zur hinteren Seitenplatte (8) geneigte Münzleitrandfläche (9, 10) aufweist, wobei die äußere Randplatte starr an der hinteren Seitenplatte (8) befestigt ist, während die innere Randplatte (45) an ihrem Innenende dreh- oder schwenkbar an der hinteren Seitenplatte (8) angebracht und mittels einer Zugfeder (48), die am Außenabschnitt der bewegbaren inneren Randplatte (45) befestigt ist, mit der festen äußeren Randplatte (11) verbunden ist.

3. Vorrichtung nach einem der Ansprüche 1 und 2, wobei die Steig- oder Stufenbahn ein Mittel zum Halten von Münzen (17) mit einer Kugel- (zurück)halterinne (21) mit einer abfallenden Leitwand (23), die längs der Mulde oder Rinne unter einem spitzen Winkel α von z.B. $8 - 15^\circ$ zur vorderen Seitenplatte (18) verläuft, und mit einer Münzhaltekegel (20) aufweist, welche lotrecht verschiebbar in der Kugelhalterinne (21) (zurück)gehalten ist und aus der Öffnung der Kugelhalterinne sowie einer Öffnung (19) in der vorderen Seitenplatte (18) in den Münzleitdurchgang (22) vorsteht, um sich an die Seitenfläche der Münze im Münzleitdurchgang (22) anzulegen und damit die Münze mittels der Keilwirkung der Kugel, die sich in der sich verjüngenden (verengenden) Leitrinne (21) abwärts verlagert, wenn die Münze zu einem Absinken im Münzleitdurchgang neigt, zu halten.

4. Vorrichtung nach einem der Ansprüche 1 und 2, wobei die Steig- oder Stufenbahn einen sich am oberen Ende des Münzleitdurchgangs (22) aufwärts öffnenden oberen Endauslaß (25), eine Münzausstoßrolle (27) an einem oberen Ende eines Traghebels (28), der an der einen Seite des Durchgangs angelenkt und elastisch in Richtung auf das Zentrum oder die Mitte des oberen Endauslasses (25) gedrängt ist, ein Mittel zum Sperren (32) des Rollentraghebels (28) in der Schließstellung der Rolle, ein elektromagnetisches Solenoid (36) zum Auslösen des Sperrmittels (32) bei Betätigung des Auszahlbehälters und einen durch den Rollentraghebel betätigten Zähler (39) umfaßt.

Revendications

1. Dispositif de sortie pour des trémies distributrices de pièces de monnaie, comportant une goulotte de sortie (1) avant un passage de guidage incurvé (4) de pièces de monnaie pour guider vers le haut des pièces de monnaie poussées dans une entrée inférieure (3) dans une direction horizontale vers une sortie supérieure (5) et un élévateur (6) raccordé à la goulotte de sortie (1) à son extrémité inférieure et constitué par des plaques latérales avant et arrière et par une paire de plaques de tranche interposées entre les bords latéraux des plaques latérales pour définir un passage de guidage de pièces de monnaie (22) vers le haut s'étendant depuis la sortie supérieure (5) du passage de guidage incurvé (4) de pièces de monnaie de la goulotte de sortie (1), caractérisé en ce que ladite goulotte de sortie (1) comporte une plaque latérale arrière (8) et une



- paire de plaques de tranche intérieure et extérieure (11, 12) fixées aux parties de tranche opposées de la plaque latérale arrière (8) de manière à définir un passage de guidage de pièces, incurvé et ouvert (4), en exposant au moins une des faces de tranche de guidage de pièces opposées (9, 10) des plaques de tranche intérieure et extérieure et de manière à espacer les faces de tranche de guidage de pièces de monnaie opposées (9, 10) des plaques de tranche (11, 12) l'une de l'autre d'une distance correspondant au diamètre de la pièce devant être manipulée, et une plaque de tranche avant ne recouvrant que la plaque de tranche intérieure (7A) positionnée sur le côté intérieur par rapport au centre de courbure du passage de guidage incurvé de la pièce et comportant un prolongement (7a) en saillie au-delà de la face de tranche de guidage de pièces de monnaie intérieure (10) de la plaque de tranche intérieure (12), au moins la face de tranche (9) de la plaque de tranche extérieure (11) positionnée sur le côté extérieur par rapport au centre de courbure du passage de guidage incurvé (4) de pièces de monnaie étant inclinée vers la plaque latérale arrière (8) d'un angle θ .
2. Dispositif de sortie pour trémies distributrices de pièces de monnaie, comportant une goulotte de sortie (1) ayant un passage de guidage incurvé (4) de pièces de monnaie pour guider vers le haut des pièces de monnaie poussées dans une entrée inférieure (3) suivant une direction horizontale vers une sortie supérieure (5) et un élévateur (6) raccordé à la goulotte de sortie (1) à son extrémité inférieure, et constitué de plaques latérales avant et arrière et d'une paire de plaques de tranche interposées entre les tranches latérales des plaques de tranche pour définir un passage de guidage de pièces de monnaie (22) s'étendant vers le haut depuis la sortie supérieure (5) du passage de guidage incurvé (4) de pièces de monnaie de la goulotte de sortie (1), caractérisé en ce que ladite goulotte de sortie (1) comporte une plaque latérale arrière (8) et une paire de plaques de tranche intérieure et extérieure (11, 12) fixées aux parties de bord opposées de la plaque latérale arrière (8) de manière à définir un passage de guidage incurvé ouvert (4) de pièces de monnaie en exposant une au moins des faces de tranche de guidage de pièces de monnaie opposées (9, 10) de la plaque de tranche intérieure et extérieure et dans lequel chacune desdites plaques de tranche (11, 12) comporte une face de tranche de guidage de pièces de monnaie (9, 10) inclinée vers la plaque arrière (8), la plaque de tranche extérieure étant fixée de façon rigide à la plaque latérale arrière (8) alors que la plaque de tranche intérieure (45) est articulée à la plaque latérale arrière (8) à son extrémité intérieure et est connectée à une plaque de tranche extérieure fixe (11) au moyen d'un ressort de tension (48) fixé à la partie extérieure de la plaque de tranche intérieure mobile (45).
3. Dispositif selon l'une quelconque des revendications 1 et 2, dans lequel ledit élévateur comporte des moyens de retenue de pièces (17) comprenant une encoche de retenue d'une bille (21) ayant une paroi de guidage inclinée (23) s'étendant le long de la gouttière suivant un angle aigu α tel que de 8 à 15 degrés par rapport à la plaque latérale avant (18) et une bille de retenue de pièces de monnaie (20) dont le déplacement vertical est empêché dans l'encoche de retenue de bille (21) et qui est en saillie depuis l'ouverture de l'encoche de retenue de bille, et une ouverture (19) formée dans la plaque latérale avant à l'intérieur du passage de guidage (22) de pièces de monnaie pour mettre en contact la surface de tranche de la pièce de monnaie dans le passage de guidage (22) de pièces de monnaie, maintenant ainsi la pièce de monnaie, la bille déplacée vers le bas dans l'encoche de guidage effilée (21) coïncant la pièce de monnaie lorsque la pièce de monnaie tend à descendre dans le passage de guidage de pièces de monnaie.
4. Dispositif selon l'une quelconque des revendications 1 et 2, dans lequel ledit élévateur comporte une sortie d'extrémité supérieure (25) ouverte vers le haut à l'extrémité supérieure du passage de guidage (22) de pièces de monnaie, un galet d'éjection de pièces de monnaie (27) étant prévu à une extrémité supérieure d'un levier support (28) articulé à une extrémité du passage et poussé de façon élastique vers le centre de la sortie d'extrémité supérieure (25), un moyen de verrouillage (32) du levier support de galet (28) en position de blocage de ce galet, un solénoïde électromagnétique (36) destiné à libérer le moyen de verrouillage (32) lors du fonctionnement de la trémie distributrice et un compteur (39) actionné par le levier support du galet.