Claims

What is claimed is

1. An enclosure comprising:

a plurality of panel sections rotatably coupled together, each of the plurality of panel sections comprising an upper frame component extending parallel to a bottom frame component; and

a panel of razor wire mesh extending between the upper frame component and the bottom frame component, wherein the panel of razor wire mesh includes a first plurality of razor wire strands arranged across a second plurality of razor wire strands.

2. The enclosure of claim 1, further comprising a hinge coupling together a set of adjacent upper frame components of the plurality of panel sections.

3. The enclosure of claim 1, the panel of razor wire mesh having a generally rectangular configuration.

4. The enclosure of claim 1, wherein the plurality of panel sections are collapsed in a first configuration and expanded in a second configuration.

5. The enclosure of claim 4, wherein each of the plurality of panel sections extends parallel to one another along different planes in the first configuration.

6. The enclosure of claim 4, wherein each of the plurality of panel sections extends parallel to one another along a same plane in the second configuration.

7. The enclosure of claim 4, wherein each of the plurality of panel sections extends parallel to one another in a side-by-side arrangement when the plurality of panels of razor wire are collapsed in the first configuration.

8. The enclosure of claim 2, wherein the hinge comprises:

a plate; and

a first pin and a second pin coupled to the plate, wherein the first pin is directly coupled to a first upper frame component of the plurality of panel sections, and wherein the second pin is directly coupled to a second upper frame component of the plurality of panel sections.

9. A razor wire barrier comprising:

a first upper frame component rotatably coupled to a second upper frame component;

a first bottom frame component extending parallel to the first upper frame component and a second bottom frame component extending parallel to the second upper frame component;

a first panel of razor wire mesh directly coupled to and extending between the first upper frame component and the first bottom frame component; and

a second panel of razor wire mesh directly coupled to and extending between the second upper frame component and the second bottom frame component, wherein each of the first and second panels of razor wire mesh includes a first plurality of razor wire strands arranged across a second plurality of razor wire strands.

10. The razor wire barrier of claim 9, further comprising a hinge coupling the first upper frame component to the second upper frame component.

11. The razor wire barrier of claim 10, the hinge comprising:

a plate; and

a first pin and a second pin coupled to the plate, wherein the first pin is directly coupled to the first upper frame component, and wherein the second pin is directly coupled to the second upper frame component.

12. The razor wire barrier of claim 10, wherein the hinge permits the first panel of razor wire mesh and the second panel of razor wire mesh to move between a collapsed configuration and an expanded configuration.

13. The razor wire barrier of claim 12, wherein the first panel of razor wire mesh and the second panel of razor wire mesh extend parallel to one another along different planes in the collapsed configuration.

14. The razor wire barrier of claim 12, wherein the first panel of razor wire mesh and the second panel of razor wire mesh form a substantially accordion shape in the expanded configuration.

15. A method of operating a barrier comprising:

providing a plurality of panel sections rotatably coupled together, each of the plurality of panel sections comprising an upper frame component extending parallel to a bottom frame component;

providing a panel of razor wire mesh coupled to and extending between the upper and bottom frame components of each of the plurality of panel sections; and

moving the plurality of panel sections between a first configuration and a second configuration, wherein in the first configuration the plurality of panel sections are collapsed, and wherein in the second configuration the plurality of panel sections are expanded.

16. The method of claim 15, further comprising coupling together the upper frame component of a first panel section of the plurality of panel sections to an adjacent upper frame component of a second panel section of the plurality of panel sections using a hinge.

17. The method of claim 15, further comprising orienting each of the plurality of panel sections parallel to one another along different planes when the plurality of panel sections are in the first configuration.

18. The method of claim 15, further comprising expanding the plurality of panel sections in an accordion motion.