

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 May 2002 (02.05.2002)

PCT

(10) International Publication Number
WO 02/34433 A2

(51) International Patent Classification⁷: **B22D 17/20**, 17/00

(21) International Application Number: PCT/CA01/01279

(22) International Filing Date:
7 September 2001 (07.09.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/697,101 26 October 2000 (26.10.2000) US

(71) Applicant: **HUSKY INJECTION MOLDING SYSTEMS LTD.** [CA/CA]; AMC/IPS Department, 500 Queen Street South, Bolton, Ontario L7E 5S5 (CA).

(72) Inventors: **KESTLE, Martin, R.**; RR 3, Site 16, P.O. Box 7, Everett, Ontario L0J 1M0 (CA). **MANDA, Jan, Marius**; 132 Anndale Drive, Toronto, Ontario M2N 2X8 (CA).

(74) Agent: **SMITH, Derek, K.W.**; Husky Injection Molding Systems Ltd., AMC/IPS Department, 500 Queen Street South, Bolton, Ontario L7E 5S5 (CA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVED INJECTION NOZZLE FOR A METALLIC MATERIAL INJECTION-MOLDING MACHINE



(57) Abstract: In metallic material injection molding machines, the connection between the injection nozzle and the sprue bushing has tended to leak metallic material. To overcome this problem, the nozzle has been modified to have a projecting portion or spigot that extends into a mating portion of the sprue bushing to form a seal between the respective portion walls. The nozzle and sprue bushing can move axially with respect to one another without loss of sealing whereas with the prior designs any separation between confronting annular surfaces on the sprue bushing and the nozzle would result in a loss of sealing and leakage.



WO 02/34433 A2