



(51) International Patent Classification:

G01R 31/36 (2006.01) *G01R 19/00* (2006.01)
H01M 10/48 (2006.01) *G01K 5/00* (2006.01)

(21) International Application Number:

PCT/US2013/038407

(22) International Filing Date:

26 April 2013 (26.04.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/639,712 27 April 2012 (27.04.2012) US

(71) Applicants: CALIFORNIA INSTITUTE OF TECHNOLOGY [US/US]; 1200 East California Boulevard, MC201-85, Pasadena, California 91125 (US). CENTRE NATIONAL DE LA RECHERCHE SCIENTIFIQUE (C.N.R.S.) [FR/FR]; 3 rue Michel-Ange, Cedex 16, F-75794 Paris (FR). NANYANG TECHNOLOGICAL UNIVERSITY [SG/SG]; 50 Nanyang Avenue, Singapore 639798 (SG).

(72) Inventors; and

(71) Applicants (for US only): YAZAMI, Rachid [FR/SG]; 12 Kensington Park Drive 04-01, Singapore 557325 (SG).

TAN, Cher Ming [SG/SG]; 46 Choa Chu Kang St. 64, #08-21, Singapore 689106 (SG).

(74) Agents: GIANOLA, Adam J. et al.; Lathrop & Gage LLP, 4845 Pearl East Circle, Suite 201, Boulder, Colorado 80301 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) Title: AN IMBEDDED CHIP FOR BATTERY APPLICATIONS




Figure 4

(57) Abstract: Provided are methods, systems and devices for thermodynamically evaluating electrochemical systems and components thereof, including electrochemical cells such as batteries. The present systems and methods are capable of monitoring selected electrochemical cell conditions, such as temperature, open circuit voltage and/or composition, and carrying out measurements of a number of cell parameters, including open circuit voltage, time and temperature, with accuracies large enough to allow for precise determination of thermodynamic state functions and materials properties relating to the composition, phase, states of charge, health and safety and electrochemical properties of electrodes and electrolytes in an electrochemical cell. Thermodynamic measurement systems of the present invention are highly versatile and provide information for predicting a wide range of performance attributes for virtually any electrochemical system having an electrode pair.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

24 April 2014