

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 September 2004 (23.09.2004)

PCT

(10) International Publication Number
WO 2004/081428 A2

- (51) International Patent Classification⁷: **F16K**
- (21) International Application Number:
PCT/US2004/006990
- (22) International Filing Date: 8 March 2004 (08.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/452,772 7 March 2003 (07.03.2003) US
60/481,904 16 January 2004 (16.01.2004) US
- (71) Applicant (for all designated States except US):
SWAGELOK COMPANY [US/US]; 29500 Solon
Road, Solon, Ohio 44139 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **DELISIO, Carmen**


J, [US/US]; 7783 Rutland Drive, Mentor, Ohio 44060 (US). **BROWNE, Ronnie** [US/US]; 9277 Shady Lake Drive, Streetsboro, Ohio 44241 (US). **STEDMAN, David** [US/US]; 6338 Bryson Drive, Mentor, Ohio 44060 (US). **TIMKO, Jared** [US/US]; 7850 Champaign Drive, Mentor, Ohio 44060 (US). **SCHEFFEL, Gary** [US/US]; 8384 State Route 43, Streetsboro, Ohio 44241 (US).

(74) Agent: **MCKNIGHT, Douglas, B.**; Calfee, Halter & Griswold LLP, 800 Superior Avenue, Suite 1400, Cleveland, OH 44114 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Continued on next page]

(54) Title: VALVE WITH ADJUSTABLE STOP



(57) Abstract: An adjustable mechanism for a valve or actuator is provided. The adjustable mechanism cooperates with one or more pistons, which in turn cooperates with a valve element to limit the axial displacement of the valve element relative to the valve seat. The adjustable mechanism can be adjusted axially, thereby providing a greater or lesser distance for the piston and diaphragm to travel. Embodiments incorporating the adjustable mechanism include a trickle valve, an on/off valve and a mixing valve. The adjustable mechanism also provides to the adjustment of the piston stroke to match or closely mirror the stroke of the valve element.

WO 2004/081428 A2



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.