

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
31 January 2002 (31.01.2002)

PCT

(10) International Publication Number
WO 02/08051 A2

(51) International Patent Classification⁷: **B63B 1/34**, 1/38

(21) International Application Number: PCT/US01/22274

(22) International Filing Date: 17 July 2001 (17.07.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/621,611 21 July 2000 (21.07.2000) US

(71) Applicant: **CORTANA CORPORATION** [US/US];
Suite 200, 520 N. Washington Street, Falls Church, VA
22046 (US).

(71) Applicant and

(72) Inventor: **MOORE, Kenneth, J.** [US/US]; 616 Walker
Hill Lane, Great Falls, VA 22066 (US).

(72) Inventors: **RYAN, Thomas, D.**; 1936 Valleywood Road,
McLean, VA 22102 (US). **GORBAN, Vladimir, A.**;

Zakrevskogo Street, Apartment 147, Kiev 02212 (UA).
BABENKO, Victor, V.; fl. 57, Malishko Street, 13A,
Kiev, 253206 (UA).


(74) Agent: **ARNOLD, Bruce, Y.**; P.O. Box 585, Great Falls,
VA 22066 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR INCREASING THE EFFECTIVENESS AND EFFICIENCY OF MULTIPLE BOUNDARY LAYER CONTROL TECHNIQUES



(57) Abstract: In an apparatus and method for ejecting an additive for significantly reducing the drag of a first fluid moving relative to a wall, a drag-reducing substance is conditioned by causing a second fluid (5), which includes the drag-reducing substance as a dispersed solid, liquid or gas, to flow through a nozzle (13). The second fluid is then passed by a vortex chamber (4) prior to ejection of the second fluid into the first fluid via an aperture that includes a Coanda surface (8) on a portion thereof. Additional techniques are also disclosed which increase the effectiveness and efficiency of ejecting a drag-reducing substance into a fluid that is moving relative to a wall, and which thus enable multiple layer to be established without the undesirable disruption of the boundary layer and without the rapid diffusion of the additives across the boundary layer that occur in prior art ejection techniques.



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.