METHOD AND SYSTEM FOR MEASURING PARAMETERS OF AUTONOMIC DYSFUNCTION TESTS

FIELD OF THE INVENTION

The invention relates to a method for measuring parameters of autonomic dysfunction tests and a system for performing same. The method is particularly related to the equipment used.

BACKGROUND TO THE INVENTION

The following discussion of the background to the invention is intended to facilitate an understanding of the present invention. However, it should be appreciated that the discussion is not an acknowledgment or admission that any of the material referred to was published, known or part of the common general knowledge in any jurisdiction as at the priority date of the application.

Autonomic dysfunction is presently detected through monitoring the blood pressure and the heart rate changes of a patient through five distinct tests, namely:

- While the patient performs the Valsalva manoeuvre;
- While the patient repeats lying down and standing up (this may be performed by way of a tilt-table);
- While the patient's hand is maintained in a sustained handgrip;
- While the patient undertakes a set exercise regime; and
- While the patient's hand is immersed in cold water.

Existing methods for obtaining blood pressure and heart rate readings during these tests commonly sees the patient being monitored by two or more devices. For example, blood pressure may be measured using a sphygmomanometer or other non-invasive systems, while heart rate is almost universally monitored by way of an electrocardiogram ("**ECG**").

These devices are expensive, and, in some cases, may cause additional discomfort to the patient. The use of multiple monitoring devices also may prolong the assessment due to the requirement to calibrate each device separately.

A further problem of the present testing regime for autonomic dysfunction is that there is no integration between the monitoring devices. A side effect of this is that multiple machines, of varying accuracy, have been developed to handle one or more of the tests mentioned above. The results of each such machine then have to be weighted as part of the autonomic dysfunction diagnosis.

An additional side effect to the requirement for multiple machines is that the patient undergoes periods of delay while he or she is disconnected from one monitoring device and hooked up to the next – thereby increasing the overall time necessary to obtain test results.

While the above are problematic in themselves, the use of the ECG during the autonomic dysfunction testing regime introduces further uncertainty into the tests. This is due to the fact that it has been shown that while electrical signals may be sent to the heart, these electrical signals do not always translate into the mechanical motion that is a heart beat. Accordingly, this electrical-mechanical dissociation result in the heart beat as determined by the ECG may not be an accurate reflection of the true heart beat of a patient.

Another drawback to the present testing systems is that the monitoring devices are only capable of qualitatively indicating whether a patient suffers from autonomic dysfunction. There is no way by which the degree or amount of autonomic dysfunction can be quantified using such systems.

It is therefore an object of the present invention to provide a method and system that alleviates, at least in part, one or more of the problems of the prior art mentioned above.

SUMMARY OF THE INVENTION

Throughout this document, unless otherwise indicated to the contrary, the terms "comprising", "consisting of", and the like, are to be construed as non-exhaustive, or in other words, as meaning "including, but not limited to".

Additionally, in the context of the remainder of the specification, "beat-to-beat blood pressure" refers to the actual blood pressure assessed on each beat of a patient's heart. It is not a reference to any system which takes an average or uses some other statistical or processing technique to provide a value for each beat of the patient's heart as determined from a period of time longer than one beat of the patient's heart.

The applicant has discovered that the existing understanding that multiple devices are required to assess autonomic dysfunction parameters is in error. This discovery stems from the realisation that a device capable of measuring the beat-to-beat blood pressure of a patient can use the resulting blood pressure waveform data to determine the patient's heart rate. In doing so, as blood pressure is related to the mechanical movement of the heart (ie. heart beats), the potential for error in heart beat calculation latent in ECG systems is avoided. This discovery thus allows for real time measurements of parameters of autonomic dysfunction during performance of the autonomic dysfunction tests through seamless connection with the test system.

In accordance with a first aspect of the invention there is a method for measuring parameters of autonomic dysfunction tests comprising:

obtaining beat-to-beat blood pressure measurements from a patient during the performance of each of at least one autonomic dysfunction test;

calculating variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements for each of the at least one autonomic dysfunction tests;

summing the variant blood pressure values calculated for each autonomic dysfunction test; and

summing the variant heart rate values calculated for each autonomic dysfunction test.

The step of calculating variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements, preferably includes the sub step of calculating the heart rate according to the formula:

$$hr = 60/d$$

where:

hr is the heart rate of the patient; and

d is the duration of the blood pressure waveform in seconds.

The calculated variant heart rate may be adjusted to factor in the sampling rate of the beat-to-beat blood pressure monitoring device.

The variant blood pressure and heart rate values may be alternatively calculated with reference to a

comparison between the blood pressure measurement taken from the patient against a normal blood pressure measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient;

comparison between the calculated heart rate measurement against a normal heart rate measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient.

Ideally, the variant blood pressure measurement is the absolute value of the blood pressure measurement taken from the patient minus the normal blood pressure measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient, the absolute value multiplied by a constant. Similarly, ideally, the variant heart rate is the absolute value of the heart rate measurement taken from the patient minus the normal heart rate measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient, the absolute value multiplied by a constant.

The normal blood pressure measurement is a percentage change in blood pressure of a person without autonomic dysfunction measured during an autonomic dysfunction test preferably determined according to the formula:

$$NBP = (RBP_{ref} - BBP_{ref})/BBP_{ref}$$

where:

NBP is the percentage change in blood pressure of the person without autonomic dysfunction measured during the autonomic dysfunction test; the person of a similar profile as the patient referenced from the external database for the test concerned;

RBP_{ref} is the blood pressure response of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed; AND

BBP_{ref} is the resting blood pressure of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed.

The actual blood pressure measurement is the actual percentage change in blood pressure of the patient measured during the autonomic dysfunction test, preferably determined according to the formula:

$$ABP = (RBP_{patient} - BBP_{patient})/BBP_{patient}$$

where:

ABP is the actual percentage change in blood pressure of the patient during the autonomic dysfunction test concerned;

$RBP_{patient}$ is the blood pressure response of the patient for the autonomic dysfunction test being performed; AND

$BBP_{patient}$ is the resting blood pressure response of the patient as expected for the autonomic dysfunction test being performed.

The normal heart rate measurement is the percentage change in heart rate of a person without autonomic dysfunction measured during an autonomic dysfunction test, preferably determined according to the formula:

$$NHR = (RHR_{ref} - BHR_{ref})/BHR_{ref}$$

where:

NHR is the percentage change in heart rate of the person without autonomic dysfunction measured during the autonomic dysfunction test; the person of a

similar profile as the patient as referenced from the external database for the test concerned;

RHR_{ref} is the heart rate response of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed; AND

BHR_{ref} is the resting heart rate of a person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed.

The actual heart rate measurement is the actual percentage change in heart rate of a patient measured during the autonomic dysfunction test determined according to the formula:

$$AHR = (RHR_{patient} - BHR_{patient})/BHR_{patient}$$

where:

AHR is the actual percentage change in heart rate of the patient measured during the autonomic dysfunction test concerned;

$RHR_{patient}$ is the heart rate response of the patient for the autonomic dysfunction test being performed; AND

$BHR_{patient}$ is the resting heart rate of the patient as expected for the autonomic dysfunction test being performed.

The variant blood pressure values and/or the variant heart rate response value may be weighted prior to summation.

The at least one autonomic dysfunction test is at least one of the following:

having the patient perform the Valsalva manoeuvre;

having the patient repeatedly lying down and standing up;

having the patient's hand maintained in a sustained handgrip;

having the patient undertake a set exercise regime; and/or

having the patient's hand immersed in cold water.

Each test is ideally performed for a predetermined length of time.

In accordance with a second aspect of the invention there is a system for measuring parameters of autonomic dysfunction tests comprising:

a beat-to-beat blood pressure monitoring device; and

a processing unit,

where the beat-to-beat blood pressure monitoring device is operable to obtain beat-to-beat blood pressure measurements from a patient during the performance of each of at least one autonomic dysfunction test and calculate variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements for each of the at least one autonomic dysfunction tests, the calculated variant blood pressure and heart rate values being communicated to the processing unit where the variant blood pressure values for each autonomic dysfunction test is summed and the variant heart rate values calculated for each autonomic dysfunction test are summed.

In accordance with a third aspect of the invention, being a variant on the second aspect of the invention, there is a system for measuring parameters of autonomic dysfunction tests comprising:

a beat-to-beat blood pressure monitoring device; and

a processing unit,

where the beat-to-beat blood pressure monitoring device is operable to obtain beat-to-beat blood pressure measurements from a patient during the performance of each of at least one autonomic dysfunction test and communicate the measurements to the processing unit, the processing unit thereafter operable to calculate variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements for each of the at least one autonomic dysfunction tests, the processing unit thereafter also operable to sum the variant blood pressure values for each autonomic dysfunction test and sum the variant heart rate values calculated for each autonomic dysfunction test.

Preferably, the heart rate is calculated according to the formula:

$$hr = 60/d$$

where:

hr is the heart rate of the patient; and

d is the duration of the blood pressure waveform in seconds.

The calculated heart rate may be adjusted to factor in the sampling rate of the beat-to-beat blood pressure monitoring device.

The blood pressure measurement taken from the patient is, ideally, compared against a normal blood pressure measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient in determining the variant blood pressure measurement. Similarly, the calculated heart rate measurement is compared against a normal heart rate measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient in determining the variant heart rate measurement.

The variant blood pressure measurement is, preferably, the absolute value of the blood pressure measurement taken from the patient minus the normal blood pressure measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient, the absolute value multiplied by a constant. The variant heart rate is the absolute value of the heart rate measurement taken from the patient minus the normal heart rate measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient, the absolute value multiplied by a constant.

Preferably, the normal blood pressure measurement is a percentage change in blood pressure of a person without autonomic dysfunction measured during an autonomic dysfunction test determined according to the formula:

$$NBP = (RBP_{ref} - BBP_{ref})/BBP_{ref}$$

where:

NBP is the percentage change in blood pressure of the person without autonomic dysfunction measured during the autonomic dysfunction test; the

person of a similar profile as the patient referenced from the external database for the test concerned;

RBP_{ref} is the blood pressure response of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed; AND

BBP_{ref} is the resting blood pressure of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed.

Preferably, the actual blood pressure measurement is the actual percentage change in blood pressure of the patient measured during the autonomic dysfunction test, determined according to the formula:

$$ABP = (RBP_{patient} - BBP_{patient})/BBP_{patient}$$

where:

ABP is the actual percentage change in blood pressure of the patient during the autonomic dysfunction test concerned;

$RBP_{patient}$ is the blood pressure response of the patient for the autonomic dysfunction test being performed; AND

$BBP_{patient}$ is the resting blood pressure response of the patient as expected for the autonomic dysfunction test being performed.

Preferably, the normal heart rate measurement is the percentage change in heart rate of a person without autonomic dysfunction measured during an autonomic dysfunction test determined according to the formula:

$$NHR = (RHR_{ref} - BHR_{ref})/BHR_{ref}$$

where:

NHR is the percentage change in heart rate of the person without autonomic dysfunction measured during the autonomic dysfunction test; the person of a similar profile as the patient as referenced from the external database for the test concerned;

RHR_{ref} is the heart rate response of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed; AND

BHR_{ref} is the resting heart rate of a person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed.

Preferably, the actual heart rate measurement is a percentage change in heart rate of the patient measured during the autonomic dysfunction test as determined according to the formula:

$$AHR = (RHR_{patient} - BHR_{patient})/BHR_{patient}$$

where:

AHR is the actual percentage change in heart rate of the patient measured during the autonomic dysfunction test concerned;

$RHR_{patient}$ is the heart rate response of the patient for the autonomic dysfunction test being performed; AND

$BHR_{patient}$ is the resting heart rate of the patient as expected for the autonomic dysfunction test being performed.

The variant blood pressure values determined for each autonomic dysfunction test may be weighted before summation. Similarly, the variant heart rate values determined for each autonomic dysfunction test may be weighted before summation.

The at least one autonomic dysfunction test is at least one of the following:

having the patient perform the Valsalva manoeuvre;

having the patient repeatedly lying down and standing up;

having the patient's hand maintained in a sustained handgrip;

having the patient undertake a set exercise regime; and/or

having the patient's hand immersed in cold water.

Each of the at least one autonomic dysfunction test is performed for a predetermined length of time.

Preferably, the beat-to-beat blood pressure monitoring device is a non-invasive blood pressure monitoring service.

Communication of measurements between the beat-to-beat blood pressure monitoring device and the processing unit may be by way of wired or wireless means.

The record of the person without autonomic dysfunction having a similar profile as the patient preferably include information in respect of at least one of the following attributes: age; sex; about the same health profile; ethnicity, and about the same medication regime.

In accordance with a fourth aspect of the invention there is a computer readable medium having software stored thereon that, when executed by an appropriate processor, performs a method for measuring parameters of autonomic dysfunction tests according to the first aspect of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a flow chart of the method for the measurement of parameters of autonomic dysfunction tests in accordance to the first embodiment of the invention.

Figure 2 is an illustration of a series of beat-to-beat blood pressure waveform cycles.

Figure 3 is a system setup for the measurement of parameters of autonomic dysfunction tests .

PREFERRED EMBODIMENTS OF THE INVENTION

In accordance with a first embodiment of the invention there is a system 10 for measuring parameters of autonomic dysfunction tests of a patient 16 comprising:

- a non-invasive, beat-to-beat blood pressure monitoring device 12; and

- an autonomic dysfunction analysis device 14

The non-invasive, beat-to-beat blood pressure monitoring device 12 is ideally the BPro™ device available from HealthSTATS International Pte Ltd of Singapore.

The autonomic dysfunction analysis device 14, in this embodiment, takes the form of a notebook computer 18. The notebook computer 18 is in data communication with the non-invasive, beat-to-beat blood pressure monitoring device 12 by way of a Universal Serial Bus ("**USB**") cable 20.

A hard drive of the notebook computer 18 has software recorded thereon such that, when the software is executed, obtains data from the non-invasive, beat-to-beat blood pressure monitoring device 12 and is able to analyse the autonomic dysfunction parameters as required. The software also has reference to a database. In this embodiment, the database is an external database. Each record in the external database includes the expected blood pressure and heart rate profiles for a "normal" patient segregated according to age and sex. In determining whether the patient 16 has autonomic dysfunction, comparison will be made with a 'normal' person having a similar profile, where they are about the same age and sex.

The system 10 will now be described in more detail in the context of its intended operation.

Medical personnel 22, such as a doctor or a nurse, attaches the non-invasive blood pressure monitoring device 12 to the patient 16 at a location where the patient's 16 blood pressure can be measured. The non-invasive blood pressure monitoring device 12 is also connected to the notebook computer 18. The medical personnel 22 then executes the software stored on the hard drive (if not already operating) to control the testing regime to follow.

Prior to commencement of the autonomic dysfunction tests, the non-invasive blood pressure monitoring device 12 is calibrated to capture bio-data about the patient 16. As such a calibration would be known to the person skilled in the art, it will not be described in more detail here. In addition to calibration, the resting beat-to-beat blood pressure measurement of the patient 16 is obtained. (Step 110) Beat-to-beat blood

pressure measurements are taken by the non-invasive blood pressure monitoring device 12 from at least this point forward.

The patient 16 is then subjected, to each test one after the other in the set of autonomic dysfunction tests of the prior art while wearing the non-invasive blood pressure monitoring device 12. (Step 120) For the sake of clarity, these tests are:

- having the patient perform the Valsalva manoeuvre;
- having the patient repeatedly lying down and standing up;
- having the patient's hand maintained in a sustained handgrip;
- having the patient undertake a set exercise regime; and
- having the patient's hand immersed in cold water.

All throughout this testing regime, beat-to-beat blood pressure data is being accumulated by the non-invasive blood pressure monitoring device 12 and relayed back to the notebook computer 18 by way of the USB cable 20. This information is then stored in a blood pressure database and also recorded on the hard drive of the notebook computer 18. (Step 130)

As part of each test, the software executing on the notebook computer 18 indicates to the medical personnel 22 the test to be performed prior to commencement. Similarly, the software indicates the exact time that the test is to commence as well as the exact time that the test is to finish. In this manner, each test is performed for a predetermined length of time – typically between twenty second and five minutes as required by the standard protocols of the country in which the test is being performed.

The expected consequences of each test, and how they relate to whether a patient may suffer from autonomic dysfunction, are as follows:

The Valsalva Manoeuvre. The normal physiological response consists of four phases: an initial pressure rise phase, a reduced venous return and compensation phase, a pressure release phase and a return of cardiac output phase. If there is little or no variation in heart rate throughout the four phases of the test, the test is indicative that the patient suffers from autonomic dysfunction.

Repeated Transience Between Standing Position and Lying Position. If there is a difference in the systolic blood pressure of the patient between standing and lying positions of greater than 30mmHg and a resultant increase in heart rate, the test is indicative that the patient suffers from autonomic dysfunction.

Sustained Handgrip. If a related increase in heart rate and systolic blood pressure is evident, the test is not indicative that the patient suffers from autonomic dysfunction.

Exercise Regime. If the heart rate and blood pressure do not elevate to a sustained plateau pattern, the test is indicative that the patient suffers from autonomic dysfunction.

Placement of Hand in Cold Water. If the test shows that the patient does not show a sudden and sharp increase in both heart rate and blood pressure which settles over time (heart rate settling first), the test is indicative that the patient suffers from autonomic dysfunction.

At the end of each test, the notebook computer 18 reviews the results obtained against a set of criteria aimed at determining whether the test has been conducted properly and are of sufficient quality for analysis. (Step 140) Such criteria include identifying any stray values. If the results do not meet these criteria the software indicates to the medical personnel 22 that the test should be repeated (Step 135). Other criteria aimed at determining whether the test has been conducted properly and is of sufficient quality for analysis can not be assessed by the notebook computer 18. Accordingly, mechanisms are also provided to allow the medical personnel 22 to manually indicate that a test should be repeated.

If the results meet the criteria, the software operates to direct the medical personnel to perform the next test in the testing regime. Of course, if the last test meets the criteria, the software operates to perform the analysis as described (Step 145).

Once all of the information has been obtained from the non-invasive blood pressure monitoring device 12, the software operates to determine the duration of each blood pressure waveform. (Step 150) In this embodiment, this is achieved by analysing the data as a whole and determining the lowest point (L) in each waveform cycle as illustrated graphically in Figure 2.

With the duration of each blood pressure waveform determined, it is possible to determine the heart rate of the patient at the time the waveform was obtained by the equation:

$$hr = 60/d$$

where *hr* is the heart rate and *d* is the duration of the blood pressure waveform in seconds.

This then means that a blood pressure reading and a heart rate measurement is available at any time during testing.

With the blood pressure and heart rate values during each test able to be referenced, the software compares the heart rate and blood pressure profiles to those stored in the external database for a person falling into a similar age range as the patient who is also of a similar sex. (Step 160) From this comparison, a numerical assessment of autonomic dysfunction for the test is calculated according to the following formulas:

$hrad_{test}$ = |NHR – AHR| x 100%; and

$bpad_{test}$ =|NBP – ABP| x 100%

where:

NHR is the percentage change in heart rate of a person without autonomic dysfunction of a similar sex and age as referenced from the external database for the test concerned; The formula for calculating the NHR value is set out in more detail below.

AHR is the actual percentage change in heart rate of the patient during the test concerned. The formula for calculating the AHR value is set out in more detail below.

NBP is the percentage change in blood pressure of a person without autonomic dysfunction of a similar sex and age as referenced form the external database for the test concerned. The formula for calculating the NBP value is set out in more detail below; and

ABP is the actual percentage change in blood pressure of the patient during the test concerned. The formula for calculating the ABP value is set out in more detail below.

In each case the absolute difference between the two values (EHR and AHR; EBP and ABP) as the extent of the variation is of primary importance. The direction of the variation is considered essentially immaterial.

As mentioned above, the NHR, AHR, NBP and ABP are calculated values. The formula for each value is as follows:

$$NHR = (RHR_{ref} - BHR_{ref})/BHR_{ref}$$

$$AHR = (RHR_{patient} - BHR_{patient})/BHR_{patient}$$

$$NBP = (RBP_{ref} - BBP_{ref})/BBP_{ref}$$

$$ABP = (RBP_{patient} - BBP_{patient})/BBP_{patient}$$

Where

RHR_{ref} is the heart rate response of a person of the same sex and age as referenced from the external database for the test concerned. The measurement for RHR_{ref} varies for different autonomic dysfunction tests conducted. For example, RHR_{ref} for the Exercise Regime test and sustained handgrip test is taken to be the maximum heart rate measured during the conduct of the tests. For the Valsalva Manoeuvre test, RHR_{ref} is taken to be the sum of the minimum, maximum and/or the 1st derivate at different phases of the test. The expected RHR_{ref} for the remaining tests would be known to the person skilled in the art.

BHR_{ref} is the resting heart rate of a person of a similar sex and age as referenced from the external database for the test concerned.

$RHR_{patient}$ is the heart rate response of the patient for a similar description above.

$BHR_{patient}$ is the resting heart rate of the patient.

RBP_{ref} is the blood pressure response of a person of a similar sex and age as referenced from the external database for the test concerned. The measurement for RBP_{ref} varies for different autonomic dysfunction tests conducted and is

known to a person skilled in the art. For example, RBP_{ref} for the Exercise Regime test and sustained handgrip test is taken to be the maximum systolic blood pressure values measured during the conduct of the tests. Again, the expected RBP_{ref} value for the remaining tests would be known to the person skilled in the art.

BBP_{ref} is the resting blood pressure of a person of a similar sex and age as referenced from the external database for the test concerned.

$RBP_{patient}$ is the blood pressure response of the patient for a similar description above.

$BBP_{patient}$ is the resting blood pressure of the patient.

The final quantitative assessment of autonomic dysfunction parameters is then expressed as the sum total of the $hrad_{test}$ and $bpad_{test}$ values for each test. (Step 170) This value then may be graphed to show how the patient's trend of autonomic function and if there is any worsening/improvement in his condition. (Step 180)

It should be appreciated by the person skilled in the art that the above invention is not limited to the embodiment described. In particular, the following modifications and improvements may be made without departing from the scope of the present invention:

- The beat-to-beat blood pressure monitoring device 12 need not be non-invasive. While a non-invasive system is preferable for the comfort of the patient, the invention as described could just as easily be adapted for use with an invasive beat-to-beat blood pressure monitoring device 12.
- The beat-to-beat blood pressure monitoring device 12 may have separate processing circuits or software that allows for calculation of the heart rate as described above. In this situation, the beat-to-beat blood pressure monitoring device 12 may provide the heart rate and beat-to-beat blood pressure data to the autonomic dysfunction analysis device 14. This then alleviates the autonomic dysfunction analysis device14 of the need to calculate the heart rate itself.
- The beat-to-beat blood pressure monitoring device 12 and autonomic dysfunction analysis device 14 may be integrated into a single device.

- The software may allow for the medical personnel 22 to override the assessment of the test measurements against the set criteria. In this manner, the medical personnel can force the system to repeat any test he or she deems necessary to repeat.
- In situations where the beat-to-beat blood pressure monitoring device 12 physically connects to the autonomic dysfunction analysis device14, the method of connection can be by means other than USB cable 20. For instance, connection can be achieved by way of a Fire wire cable or serial cable.
- Wireless connection between the beat-to-beat blood pressure monitoring device 12 and the autonomic dysfunction analysis device14 may be by way of infrared or wireless radio.
- The autonomic dysfunction analysis device 14 need not be a notebook computer 18. It can just as easily be a dedicated device or desktop computer, or a terminal attached to a computer network.
- While it is preferable that an analysis is performed during all the full set of tests, it is possible for a similar to be based on the results of one or more of the tests rather than the full test set.
- A start/stop button may be provided on the beat-to-beat blood pressure monitoring device 12 as a means of indicating the commencement and finishing of each test as directed by the medical personnel 22.
- The non-invasive beat-to-beat blood pressure monitoring device 12 need not be connected to the notebook computer 18 during testing. Instead, the non-invasive beat-to-beat blood pressure monitoring device 12 may have storage means for storing blood pressure measurements. These measurements can then be transferred form the storage means to the notebook computer 18 upon subsequent linkup following completion of the last test.
- In yet a further alternative arrangement, the system may continuously monitor the blood pressure of the patient during the testing regime. In this arrangement, measurements relating to particular tests may be determined by filtering out those measurements considered indicative of the rest heartbeat of the patient.

- In addition to the heart rate and blood pressure response to each test, the settling time or response time may be used to provide an indication on whether a patient is suffering from autonomic dysfunction
- Ideally, the non-invasive blood pressure monitoring device is positioned adjacent to an artery.
- The software may be implemented as an electronic circuit or may be externally stored relative to the autonomic dysfunction analysis device 14.
- As the sampling rate of the beat-to-beat blood pressure monitoring device 12 may impact on the calculated heart rate, the formula used to determine the calculated heart rate may be amended to factor in the influence of such a sampling rate.
- The calculated values hrad and bpad may be further corrected to account for co-existing conditions that may influence such values. An example is to correct the values to account for the patient taking beta-blockers.
- Each record held by the external database may be further segregated according to ethnicity with the NHR and NBP values being correlated on the basis of ethnicity in addition to age and sex. Even further segregation of records held in the external database can be made with reference to any other relevant health profile as would be known to the person skilled in the art.
- The RBP_{ref}, RHR_{ref}, BBP_{ref} and BHR_{ref} values may be determined by averaging the relevant blood pressure measurements and heart rates of a 'normal' person found in the external database.
- The blood pressure response and heart rate response to an autonomic dysfunction test for a 'normal' person may be a range of values bounded by a upper and lower limits.
- The hrad and bpad values may be weighted according to the significance of the test providing such values. In this respect, it is noted that higher weightings could be applied to the Valsalva manoeuvre and cold water tests due to the observation that indications of autonomic dysfunction only show up in these tests when the disease is more pronounced.

It should be further appreciated by the person skilled in the art that the above modifications and improvements, where not mutually exclusive, can be combined to form yet further embodiments considered within the scope of the present invention.

WE CLAIM:

1. A method for measuring parameters of autonomic dysfunction tests comprising:

   obtaining beat-to-beat blood pressure measurements from a patient during the performance of each of at least one autonomic dysfunction test;

   calculating variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements for each of the at least one autonomic dysfunction tests;

   summing the variant blood pressure values calculated for each autonomic dysfunction test; and

   summing the variant heart rate values calculated for each autonomic dysfunction test.

2. A method according to claim 1, where the step of calculating variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements, includes the sub step of calculating the heart rate according to the formula:

$$hr = 60/d$$

   where:

   hr is the heart rate of the patient; and

   d is the duration of the blood pressure waveform in seconds.

3. A method according to claim 2, where the sub step of calculating the heart rate is adjusted to factor in the sampling rate of the beat-to-beat blood pressure monitoring device.

4. A method according to any one of claims 1 to 3, where the step of calculating variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements includes the sub steps of:

   comparing the blood pressure measurement taken from the patient against a normal blood pressure measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient;

comparing the calculated heart rate measurement against a normal heart rate measurement stored in a record representing a person without autonomic dysfunction having a similar profile as the patient.

5. A method according to claim 4, where the variant blood pressure measurement is the absolute value of the blood pressure measurement taken from the patient minus the normal blood pressure measurement stored in a record representing a person having a similar profile as the patient, the absolute value multiplied by a constant.

6. A method according to claim 4 or claim 5, where the variant heart rate is the absolute value of the heart rate measurement taken from the patient minus the normal heart rate measurement stored in a record representing a person having a similar profile as the patient, the absolute value multiplied by a constant.

7. A method according to claim 5, where the normal blood pressure measurement is the percentage change in blood pressure of a person without autonomic dysfunction measured during an autonomic dysfunction test, determined according to the formula:

$$NBP = (RBP_{ref} - BBP_{ref})/BBP_{ref}$$

where:

NBP is the percentage change in blood pressure of the person without autonomic dysfunction measured during the autonomic dysfunction test; the person of a similar profile as the patient referenced from the external database for the test concerned;

RBP_{ref} is the blood pressure response of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed; AND

BBP_{ref} is the resting blood pressure of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed.

8. A method according to claim 5 or claim 7, where the actual blood pressure measurement is the actual percentage change in blood pressure of the patient

measured during the autonomic dysfunction test determined according to the formula:

$$ABP = (RBP_{patient} - BBP_{patient})/BBP_{patient}$$

where:

ABP is the actual percentage change in blood pressure of the patient during the autonomic dysfunction test concerned;

$RBP_{patient}$ is the blood pressure response of the patient for the autonomic dysfunction test being performed; AND

$BBP_{patient}$ is the resting blood pressure response of the patient as expected for the autonomic dysfunction test being performed.

9. A method according to claim 6, where the normal heart rate measurement is the percentage change in heart rate of a person without autonomic dysfunction measured during an autonomic dysfunction test, determined according to the formula:

$$NHR = (RHR_{ref} - BHR_{ref})/BHR_{ref}$$

where:

NHR is the percentage change in heart rate of the person without autonomic dysfunction measured during the autonomic dysfunction test; the person of a similar profile as the patient as referenced from the external database for the test concerned;

RHR_{ref} is the heart rate response of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed; AND

BHR_{ref} is the resting heart rate of a person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed.

10. A method according to claim 6 or claim 9, where the actual heart rate measurement is the actual percentage change in heart rate of the patient measured during the autonomic dysfunction test, determined according to the formula:

$$AHR = (RHR_{patient} - BHR_{patient})/BHR_{patient}$$

where:

AHR is the actual percentage change in heart rate of the patient measured during the autonomic dysfunction test concerned;

$RHR_{patient}$ is the heart rate response of the patient for the autonomic dysfunction test being performed; AND

$BHR_{patient}$ is the resting heart rate of the patient as expected for the autonomic dysfunction test being performed.

11. A method according to any preceding claim including the further step of weighting the variant blood pressure values prior to summation.

12. A method according to any preceding claim including the further step of weighting the heart rate response values prior to summation.

13. A method according to any preceding claim, where the at least one autonomic dysfunction test is at least one of the following:

having the patient perform the Valsalva manoeuvre;

having the patient repeatedly lying down and standing up;

having the patient's hand maintained in a sustained handgrip;

having the patient undertake a set exercise regime; and/or

having the patient's hand immersed in cold water.

14. A method according to any preceding claim, where each of the at least one autonomic dysfunction test is performed for a predetermined length of time.

15. A system for measuring parameters of autonomic dysfunction tests comprising:

a beat-to-beat blood pressure monitoring device; and

a processing unit,

where the beat-to-beat blood pressure monitoring device is operable to obtain beat-to-beat blood pressure measurements from a patient during the performance of each of at least one autonomic dysfunction test and calculate variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements for each of the at least one autonomic dysfunction tests, the calculated variant blood pressure and heart rate values being communicated to the processing unit where the variant blood pressure values for each autonomic dysfunction test is summed and the variant heart rate values calculated for each autonomic dysfunction test are summed.

16. A system for measuring parameters of autonomic dysfunction tests comprising:

a beat-to-beat blood pressure monitoring device; and

a processing unit,

where the beat-to-beat blood pressure monitoring device is operable to obtain beat-to-beat blood pressure measurements from a patient during the performance of each of at least one autonomic dysfunction test and communicate the measurements to the processing unit, the processing unit thereafter operable to calculate variant blood pressure and heart rate values from the beat-to-beat blood pressure measurements for each of the at least one autonomic dysfunction tests, the processing unit thereafter also operable to sum the variant blood pressure values for each autonomic dysfunction test and sum the variant heart rate values calculated for each autonomic dysfunction test.

17. A system according to claim 15 or claim 16, where the heart rate is calculated according to the formula:

$$hr = 60/d$$

where:

hr is the heart rate of the patient; and

d is the duration of the blood pressure waveform in seconds.

18. A system according to claim 17, where the calculated heart rate is adjusted to factor in the sampling rate of the beat-to-beat blood pressure monitoring device.

19. A system according to any one of claims 15 to 18, where:

the blood pressure measurement taken from the patient is compared against an normal blood pressure measurement stored in a record representing a person having a similar profile as the patient in determining the variant blood pressure measurement;

the calculated heart rate measurement is compared against an normal heart rate measurement stored in a record representing a person having a similar profile as the patient in determining the variant heart rate measurement.

20. A system according to claim 19, where the variant blood pressure measurement is the absolute value of the blood pressure measurement taken from the patient minus the normal blood pressure measurement stored in a record representing a person having a similar profile as the patient, the absolute value multiplied by a constant.

21. A system according to claim 19, where the variant heart rate is the absolute value of the heart rate measurement taken from the patient minus the normal heart rate measurement stored in a record representing a person having a similar profile as the patient, the absolute value multiplied by a constant.

22. A system according to claim 20, where the normal blood pressure measurement is a percentage change in blood pressure of a person without autonomic dysfunction measured during an autonomic dysfunction test determined according to the formula:

$$NBP = (RBP_{ref} - BBP_{ref})/BBP_{ref}$$

where:

NBP is the percentage change in blood pressure of the person without autonomic dysfunction measured during the autonomic dysfunction test; the person of a similar profile as the patient referenced from the external database for the test concerned;

RBP_{ref} is the blood pressure response of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed; AND

BBP_{ref} is the resting blood pressure of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed.

23. A system according to claim 20 or claim 22, where the actual blood pressure measurement is the actual percentage change in blood pressure of the patient during an autonomic dysfunction test, determined according to the formula:

$$ABP = (RBP_{patient} - BBP_{patient})/BBP_{patient}$$

where:

ABP is the actual percentage change in blood pressure of the patient during the autonomic dysfunction test concerned;

$RBP_{patient}$ is the blood pressure response of the patient for the autonomic dysfunction test being performed; AND

$BBP_{patient}$ is the resting blood pressure response of the patient as expected for the autonomic dysfunction test being performed.

24. A system according to claim 21, where the normal heart rate measurement is the percentage change in heart rate of a person without autonomic dysfunction, determined according to the formula:

$$NHR = (RHR_{ref} - BHR_{ref})/BHR_{ref}$$

where:

NHR is the percentage change in heart rate of the person without autonomic dysfunction measured during the autonomic dysfunction test; the person of a similar profile as the patient as referenced from the external database for the test concerned;

RHR_{ref} is the heart rate response of the person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed; AND

BHR_{ref} is the resting heart rate of a person without autonomic dysfunction; the person of a similar profile as the patient as expected for the autonomic dysfunction test being performed.

25. A system according to claim 21 or claim 24, where the actual heart rate measurement is the actual percentage change in heart rate of the patient measured during the autonomic dysfunction test determined according to the formula:

$$AHR = (RHR_{patient} - BHR_{patient})/BHR_{patient}$$

where:

AHR is the actual percentage change in heart rate of the patient measured during the autonomic dysfunction test concerned;

$RHR_{patient}$ is the heart rate response of the patient for the autonomic dysfunction test being performed; AND

$BHR_{patient}$ is the resting heart rate of the patient as expected for the autonomic dysfunction test being performed.

26. A system according to any one of claims 15 to 25, where the variant blood pressure values determined for each autonomic dysfunction test are weighted before summation.

27. A system according to any one of claims 15 to 26, where the variant heart rate values determined for each autonomic dysfunction test are weighted before summation.

28. A system according to any one of claims 15 to 27, where the at least one autonomic dysfunction test is at least one of the following:

having the patient perform the Valsalva manoeuvre;

having the patient repeatedly lying down and standing up;

having the patient's hand maintained in a sustained handgrip;

having the patient undertake a set exercise regime; and/or

having the patient's hand immersed in cold water.

29. A system according to any one of claims 15 to 28, where each of the at least one autonomic dysfunction test is performed for a predetermined length of time.

30. A system according to any one of claims 15 to 29, where the beat-to-beat blood pressure monitoring device is a non-invasive blood pressure monitoring service.

31. A system according to any one of claims 15 to 30, where communication of measurements between the beat-to-beat blood pressure monitoring device and the processing unit is by way of wireless means.

32. A system according to any one of claims 15 to 31, where the record of the person having a similar profile as the patient include information in respect of at least one of the following attributes: age; sex; health profile; ethnicity.

33. A computer readable medium having software stored thereon that, when executed by an appropriate processor, performs a method for measuring parameters of autonomic dysfunction tests according to any one of claims 1 to 14.