

HEAT EXCHANGER

TECHNICAL FIELD

The present invention relates to a heat
5 exchanger. More particularly, the invention relates to a
heat exchanger suitable for use in air conditioners,
refrigerators, ice makers and the like.

BACKGROUND ART

10 Conventionally, there has been a heat exchanger
formed by dividing perforated fins, which have perforations
formed therein, at their perforations. More specifically,
this heat exchanger is formed by inserting heat transfer
tubes into insertion holes of a perforated fin and then
15 separating the fin at the perforations so that two heat
exchangers are formed.

The conventional heat exchanger shown above, in
which the fins can be separated at the places of the
perforations, is easy to manufacture, having an advantage
20 that heat exchangers of different dimensions can be easily
manufactured by separating the fins at the perforations or
not separating the fins at the perforations but leaving the
perforations as they are.

However, the above conventional heat exchanger,
25 while having an advantage of easiness in changing

dimensional settings of the fins, has a problem that because, in division of the fins, burrs are formed on an outer edge of the heat exchanger formed by dividing the perforated fins at the perforations and corresponding to places of the fins where the perforations have been separated, condensed water (dew drop water) generated on the fins during the use of the heat exchanger may scatter from the fins along the burrs. In particular, when the conventional heat exchanger is used as a heat exchanger on the indoor side of an air conditioner, the condensed water may be scattered indoors by air blows, giving rise to a serious problem.

Further, in the conventional heat exchanger, since the edge on which the burrs are present is positioned at an outer edge of the heat exchanger, there is another problem that the appearance of the heat exchanger is impaired.

SUMMARY OF THE INVENTION

Accordingly, one embodiment of the present invention provides a heat exchanger which is easy to change in dimensional settings of its fins and which is less liable to scattering of condensed water from the fins and moreover which is kept from impairment of its appearance.

One aspect of the present invention provides a heat exchanger in an indoor unit of an air conditioner comprising: a first heat exchanger section having plate-shaped first fins, and a plurality of first heat transfer tubes inserted through the first fins so as to extend along a thicknesswise direction of the first fins; and a second heat exchanger section having plate-shaped second fins, and a plurality of second heat transfer tubes inserted through the second fins so as to extend along a thicknesswise direction of the second fins, wherein a plurality of burrs are present at specified intervals on edges of the first fins and/or the second fins, and the first heat exchanger section and the second heat exchanger section are so positioned that edges of the first fins or the second fins on which the burrs are present are in contact with or opposition to the other edges of the first fins or the second fins, where all the edges having the burrs present thereon are positioned on an inner side and never positioned on an outer side of the heat exchanger.

In the heat exchanger of this invention, edges with burrs present thereon in the first fins or the second fins are so positioned as to be in contact with or opposition to the other edges of the first fins or the second fins, and the edges with the burrs present thereon are positioned inside. Therefore, burrs are present only on the edges that are in contact with or opposition to the second fins, and not on the other edges, among all the edges

of the first fins, and moreover burrs are present only on the edges that are in contact with or opposition to the first fins, and not on the other edges, among all the edges of the second fins.

5 Consequently, even if condensed water has scattered from the edges having the burrs thereon, the scattered condensed water can be received by the edges that are in contact with or opposition to the edges having the burrs thereon. Thus, since condensed water can be prevented
10 from scattering outside along with winds, the heat exchanger of the invention, even when used as a heat exchanger on the indoor side of an air conditioner, can be kept from indoor scattering of the condensed water mixed in winds.

 Also, in the heat exchanger of this invention,
15 edges with burrs present thereon in the first fins or the second fins are so positioned as to be in contact with or opposition to the other edges of the first fins or the second fins, and the edges with the burrs present thereon are positioned inside. Therefore, burrs are present only on
20 the edges that are in contact with or opposition to the second fins, and not on the other edges, among all the edges of the first fins, and moreover burrs are present only on the edges that are in contact with or opposition to the first fins, and not on the other edges, among all the edges
25 of the second fins. Since the edges having the burrs

thereon are never positioned on the outer side of the heat exchanger, the heat exchanger can be kept from impairment of its appearance.

Also, in the heat exchanger of this invention,
5 edges with burrs present thereon in the first fins or the second fins are so positioned as to be in contact with or opposition to the other edges of the first fins or the second fins, and the edges with the burrs present thereon are positioned inside. Therefore, even if condensed water
10 has scattered from the edges having the burrs thereon, the scattered condensed water can be received by the edges that are in contact with or opposition to the edges having the burrs thereon. Thus, since condensed water can be prevented from scattering outside along with winds, the heat exchanger
15 of the invention, even when used as a heat exchanger on the indoor side of an air conditioner, can be kept from indoor scattering of the condensed water mixed in winds.

Further, in the heat exchanger of this invention, since the edges having the burrs thereon are never
20 positioned on the outer side of the heat exchanger, the heat exchanger can be kept from impairment of its appearance.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not intended to limit the present invention, and wherein:

Fig. 1 is a schematic sectional view of an air conditioner which uses a heat exchanger according to one embodiment of the present invention;

Fig. 2 is a view showing part of a perforated fin used to form a first fin included in the heat exchanger of the embodiment;

Fig. 3A is a view showing manufacturing process of a first portion or a second portion of the first fins included in the heat exchanger of the embodiment;

Fig. 3B is a view showing manufacturing process of a first portion or a second portion of the first fins included in the heat exchanger of the embodiment;

Fig. 3C is a view showing manufacturing process of a first portion or a second portion of the first fins included in the heat exchanger of the embodiment;

DETAILED DESCRIPTION OF THE INVENTION

Hereinbelow, the present invention will be described in detail by embodiments thereof illustrated in the accompanying drawings.

Fig. 1 is a schematic sectional view of an air conditioner which uses a heat exchanger according to one embodiment of the invention. In Fig. 1, reference numeral 1 denotes a blower fan, and 2 denotes a heat exchanger. In
5 Fig. 1, a casing or the like in which the blower fan 1 and the heat exchanger 2 are housed is omitted for simplicity's sake.

This air conditioner is so designed that the blower fan 1 is rotated to blow out air, which serves as a
10 heat transfer medium sucked in via the heat exchanger 2, through an unshown blowoff opening.

The heat exchanger 2 has an auxiliary heat exchanger 8 as an example of a first heat exchanger section, and a main heat exchanger 9 as an example of a second heat
15 exchanger section.

The auxiliary heat exchanger 8 has sheet-like first fins 10, and unshown first heat transfer tubes. The first fin 10, as shown in Fig. 1, has a generally long-and-narrow rectangular-shaped surface. The first fin 10 is
20 provided in plurality so as to be disposed at specified intervals along a thicknesswise direction of the first fin 10 (a direction perpendicular to the drawing sheet of Fig. 1).

The first fin 10 is composed of a first portion 11
25 having a long-and-narrow rectangular-shaped surface, and a

second portion 12 generally identical in shape to the first portion 11. In the first portion 11 are formed 1-row, 8-stage through holes 18 for insertion of heat transfer tubes. Similarly, 1-row, 8-stage through holes 19 for insertion of heat transfer tubes are formed in the second portion 12. Further, burrs 14 are formed at specified intervals on a longitudinal one-side edge of the first portion 11, while burrs 15 are formed at specified intervals on a longitudinal one-side edge of the second portion 12.

10 The first heat transfer tubes are inserted into the 1-row, 8-stage through holes 18 of the first portion 11 for insertion of heat transfer tubes, as well as into the 1-row, 8-stage through holes 19 of the second portion 12 for insertion of heat transfer tubes. More specifically, the first heat transfer tubes are so placed as to run through a plurality of first fins 10 arrayed at specified intervals in a thicknesswise direction of the first fins.

20 One corner at longitudinal one end of the first portion 11 on which the burrs 14 are formed, and one corner at longitudinal one end of the second portion 12 on which the burrs 15 are formed, are in proximity to each other. The second portion 12 is so positioned so as to adjoin the longitudinal one end of the first portion 11. The second portion 12 is so positioned as to be slightly inclined with respect to the first portion 11.

The main heat exchanger 9 has sheet-like second fins 20 and unshown second heat transfer tubes. The second fin 20, as shown in Fig. 1, has a generally long-and-narrow rectangular-shaped surface. The second fin 20 is provided in plurality so as to be disposed at specified intervals along a thicknesswise direction of the second fin 20 (a direction perpendicular to the drawing sheet of Fig. 1).

The second fin 20 is composed of a first portion 21 having a long-and-narrow rectangular-shaped surface, and a second portion 22 generally identical in shape to the first portion 21. In the first portion 21 are formed 2-row, 8-stage through holes 28 for insertion of heat transfer tubes. Similarly, 2-row, 8-stage through holes 29 for insertion of heat transfer tubes are formed in the second portion 22. The first portion 21 of the second fin 20, the second portion 22 of the second fin 20, the first portion 11 of the first fin 10, and the second portion 12 of the first fin 10 are generally equal in longitudinal length to one another.

The second portion 22 is so positioned as to adjoin longitudinal one end of the first portion 21. Also, the second portion 22 is so positioned as to be slightly inclined with respect to the first portion 21. One corner at longitudinal one end of the first portion 21 and one

corner at longitudinal one end of the second portion 22 are in contact with each other.

5 The second heat transfer tubes are inserted into the 2-row, 8-stage through holes 28 of the first portion 21 for insertion of heat transfer tubes, as well as into the 2-row, 8-stage through holes 29 of the second portion 22 for insertion of heat transfer tubes. More specifically, the second heat transfer tubes are so placed as to run through a plurality of second fins 20 arrayed at specified intervals in a thicknesswise direction of the second fins.

Also, as shown in Fig. 1, one-side edges 26, 27 of the main heat exchanger 9, which is long and narrow and bent at one place, are so positioned as to be in contact with one-side edges 16, 17 of the long-and-narrow, bent-at-one-place auxiliary heat exchanger 8 on one side on which the burrs 14, 15 are formed. More specifically, one edge 26 of the first portion 21 of the second fin 20 is in contact with the edge 16 of the first portion 11 of the first fin 10 on which the burrs 14 are present, while one edge 27 of the second portion 22 of the second fin 20 is in contact with the edge 17 of the second portion 12 of the first fin 10 on which the burrs 15 are present.

25 The edges 16, 17 having the burrs thereon are positioned inside, so that no burrs are present at outside edges of the heat exchanger. That is, burrs are

present neither on an outer-side edge 30 of the first portion 11 of the first fin 10 nor on an outer-side edge 31 of the second portion 12 of the first fin 10. Also, burrs are present neither on an outer-side edge 40 of the first portion 21 of the second fin 20 nor on an outer-side edge 41 of the second portion 22 of the second fin 20.

Fig. 2 is a view showing part of a perforated fin 50 used to form the first fin 10.

Referring to Fig. 2, reference numeral 18 denotes insertion holes for heat transfer tubes, and 52 denotes perforations (slits). Reference character DP denotes a distance between the through holes 18 adjacent to each other along a direction generally parallel to a direction in which the perforation extends, SL2 denotes a length of a perforation (slit), and SL1 denotes a connection part of the perforations.

The perforated fin 50 is formed of a plate member having a generally rectangular-shaped surface. The perforations 52 are formed at a generally widthwise center of the perforated fin 50. The perforations 52 extend generally parallel to the longitudinal direction of the perforated fin 50. The first fin 10 shown in Fig. 1 is formed by dividing the perforated fin 50 at its portion where the perforations are formed. From the perforated fin 50 shown in Fig. 2, two first portions 11 of the first fin

10 are formed, or two second portions 12 of the first fin 10 are formed, or one first portion 11 and one second portion 12 of the first fin 10 are formed.

5 There is a relationship shown by the following Equation (1) among DP, SL2 and SL1. The size of the connection part SL1 of the perforations is limited to a range shown by the following Equation (2). Limiting the size of the connection part SL1 of the perforations to the range shown by Equation (2) prevents the perforated fins 10 from becoming lower in strength than a specified strength, and also allows the perforated fins to be easily divided at the perforation.

$$SL2 = DP - SL1 \quad \dots(1)$$

$$0.15 \text{ (mm)} < SL1 < 0.5 \text{ (mm)} \quad \dots(2)$$

15 Figs. 3A to 3C are views showing manufacturing process of the first portions 11 or the second portions 12 of the first fins shown in Fig. 1. A method for manufacturing the first portions 11 or the second portions 12 shown in Fig. 1 are described below with reference to 20 Figs. 3A to 3C. In Fig. 3A, reference numeral 50 denotes the perforated fin shown in Fig. 2. In the perforated fin 50, whereas the heat transfer tube insertion holes 18 are actually disposed in a staggered arrangement as shown in Fig. 2, the insertion holes are disposed in a lattice

arrangement for simplicity in Figs. 3A to 3C (actually, in a staggered arrangement).

First, a plurality of above-described perforated fins 50 of the same configuration are disposed at equal intervals along the thicknesswise direction of the perforated fins 50 so that the perforated fins 50 are piled up. Then, in this state, pins or other rod-like members (not shown) are inserted through some (two or more) of a plurality of heat transfer tube insertion holes 18 that are formed at the same positions of the plurality of piled-up perforated fins 50, so as to extend through the plurality of piled-up perforated fins 50. Thus, the state in which the plurality of perforated fins 50 shown in Fig. 1 are piled up is maintained.

Next, a force is applied along a direction shown by arrow α in Fig. 3B. More specifically, a force is applied in such a direction that two parts of the perforated fins 50 shown in Fig. 3A bordered by a line on which the perforations are formed are separated away from each other. This force is exerted, for example, by applying a force along the widthwise direction of the perforated fins 50 in such a way that one part on one side bordered by the perforations of the perforated fins 50 is fixed while the other part bordered by the perforations is separated from the above-mentioned one side. Then, a force

is applied to the perforated fins 50 in the direction shown by the arrow α in Fig. 3B so that the perforated fins 50 are divided into two by the line on which the perforations are formed as shown in Fig. 3B, by which the first portions
5 11 (or second portions 12) are formed.

As a result of the formation of the first portions 11 by such a method, the manufacturing cost for the first portions 11 (or second portions 12) can be reduced. Also, burrs 14 are formed at places of the first
10 portions 11 corresponding to the connection parts of the perforations of the perforated fins 50 as shown in Fig. 3C. However, with an arrangement that the edge of one fin with burrs present thereon is positioned so as to be in contact with or opposition to the edge of another fin, and that the
15 edge with burrs present thereon is positioned inside, as in the heat exchanger of the embodiment shown in Fig. 1, such problems as scattering of condensed water or degradation of the appearance can be solved.

In the heat exchanger of this embodiment, the
20 edges 16, 17 having the burrs 14, 15 present thereon and formed on one side of the first fins 10 are placed in contact with the edges 26, 27 of the second fins 20, and the edges 16, 17 having the burrs 14, 15 and formed in the heat exchanger are positioned inside. Therefore, the burrs
25 14, 15 are present only on the edges 16, 17 that are in

contact with or opposition to the second fins 20, and not on the edges 30, 31, among the edges 16, 17, 30, 31 of the first fins 10, and moreover the burrs 14, 15 are present only on the edges 26, 27 that are in contact with or
5 opposition to the first fins 10, and not on the edges 40, 41, among the edges 26, 27, 40, 41 of the second fins 20.

Consequently, even if condensed water has scattered from the edges 16, 17 having the burrs 14, 15 present thereon, the scattered condensed water can be
10 received by the edges 26, 27 in contact with or opposition to the edges 16, 17 having the burrs 14, 15 present thereon. Thus, since condensed water can be prevented from scattering outward along with winds, the heat exchanger of the embodiment, even when used as a heat exchanger on the
15 indoor side of an air conditioner, can be kept from indoor scattering of the condensed water mixed in winds.

Also, in the heat exchanger of this embodiment, no burrs are present on the edges 30, 31 other than the edges 16, 17 that are in contact with or opposition to the
20 second fins 20 among the edges 16, 17, 30, 31 of the first fins 10, and moreover no burrs are present on the edges 40, 41 other than the edges 26, 27 that are in contact with or opposition to the first fins 10 among the edges 26, 27, 40, 41 of the second fins 20. Therefore, the burrs 14, 15
25 having burrs present thereon are never positioned on the

outer side of the heat exchanger. Thus, according to the heat exchanger of this embodiment, the appearance of the heat exchanger is not impaired.

In the heat exchanger of this embodiment, burrs
5 are formed on the edges 16, 17 being in contact with the second fins 20 among the edges 16, 17, 30, 31 of the first fins 10. However, in this invention, burrs may also be formed on edges of the first fins that are opposed to the second fins with a specified distance provided between the
10 first fins and the second fins.

Also, in the heat exchanger of this embodiment, burrs are formed only on the edges 16, 17 that are in contact with the second fins 20 among the edges 16, 17, 30, 31 of the first fins 10. However, in this invention, it is
15 also possible that burrs are formed on edges of the first fins that are in contact with or opposition to the second fins while burrs are formed on edges of the second fins that are in contact with or opposition to the first fins. Furthermore, it is also possible that burrs are formed only
20 on edges of the second fins that are in contact with the first fins.

Also, in the heat exchanger of this embodiment, 1-row, 16-stage insertion holes for heat transfer tubes are formed in the first fins 10, and moreover 2-row, 16-stage
25 insertion holes are formed in the second fins 20. However,

in this invention, the arrangement of the insertion holes for heat transfer tubes to be formed in the first fins is not necessarily limited to the 1-row, 16-stage arrangement, and any arrangement may be adopted. Similarly, the
5 insertion holes for heat transfer tube to be formed in the second fins are not necessarily limited to the 2-row, 16-stage arrangement, and any arrangement may be adopted.

Also, in the heat exchanger of this embodiment, the insertion holes 28 are provided in a staggered
10 arrangement in the second fin 20. However, in the fins of this invention, the insertion holes may be provided either in a staggered arrangement or in a lattice arrangement or in any other arrangement.

Further, in the heat exchanger of this
15 embodiment, the first fin 10 of the auxiliary heat exchanger 8 serving as the first heat exchanger section is composed of two portions, the first portion 11 and the second portion 12, while the second fin 20 of the main heat exchanger 9 serving as the second heat exchanger section is
20 composed of two portions, the first portion 21 and the second portion 22. However, for this invention, it is also possible that at least one of the first fin and the second fin is made up of one portion or three or more portions.

Further, in the heat exchanger of this
25 embodiment, two heat exchanger sections (auxiliary

exchanger 8 and main heat exchanger 9) are so positioned that their edges are in contact with each other, and burrs are disposed on the inner side. However, in this invention, it is of course possible that three or more heat
5 exchanger sections are positioned so that edges of adjacent heat exchanger sections are in contact with or opposition to each other, where burrs are formed only in the inner side.

Embodiments of the invention being thus
10 described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of
15 the following claims.

CLAIMS

1. A heat exchanger in an indoor unit of an air conditioner comprising:

a first heat exchanger section having plate-shaped first fins, and a plurality of first heat transfer tubes inserted through the first fins so as to extend along a thicknesswise direction of the first fins; and

a second heat exchanger section having plate-shaped second fins, and a plurality of second heat transfer tubes inserted through the second fins so as to extend along a thicknesswise direction of the second fins, wherein

a plurality of burrs are present at specified intervals on edges of the first fins and/or the second fins, and

the first heat exchanger section and the second heat exchanger section are so positioned that edges of the first fins or the second fins on which the burrs are present are in contact with or opposition to the other edges of the first fins or the second fins, where all the edges having the burrs present thereon are positioned on an inner side and never positioned on an outer side of the heat exchanger.

2. The heat exchanger in the indoor unit of the air conditioner as claimed in Claim 1, wherein

when the burrs are present on the first fins, a clearance between the adjacent burrs is equal to a clearance between adjacent insertion holes for the first heat transfer tubes, and

when the burrs are present on the second fins, a clearance between the adjacent burrs is equal to a clearance between adjacent insertion holes for the second heat transfer tubes.

ABSTRACT

A heat exchanger includes an auxiliary heat exchanger 8, which has plate-shaped first fins 10 and a plurality of first heat transfer tubes, and a main heat exchanger 9 which
5 has plate-shaped second fins 20 and a plurality of second heat transfer tubes. A plurality of burrs 14, 15 are present at specified intervals on edges 16, 17 of the first fins 10. The auxiliary heat exchanger 8 and the main heat
10 exchanger 9 are so positioned that the edges 16, 17 of the first fins 10 on which the burrs 14, 15 are present are in contact with edges 26, 27 of the second fins 20, and the edges 16, 17 having the burrs 14, 15 present thereon are positioned on the inner side.