

METHODS, SYSTEMS, AND MEDIA FOR DETECTING SPOOFING IN MOBILE AUTHENTICATION

CROSS-REFERENCE

[0001] This application claims the benefit of U.S. Provisional Patent Application No. 62/560,038, filed September 18, 2017, which is incorporated herein by reference in its entirety.

BACKGROUND

[0002] “Spoofing” a security system is generally defined as an act of masquerading as an authenticated user, by submitting false data. In this case, methods of liveness detection may be employed to determine whether a biometric modality, such as a face, a palm (palm print), a finger (fingerprint), or an ear, carries the unique structural qualities of the original three-dimensional biometric modality, or is-a two-dimensional replicate.

SUMMARY

[0003] Many current technologies for optical recognition of identity can be easily spoofed or hacked. In the case of facial recognition on mobile devices, for example, it is common for the facial recognition algorithms to be tricked into accepting a fake representation of a user’s face, as presented via an image of the user’s face on the front-facing video screen of another mobile device, or as presented via a print-out of the user’s face on paper, among other methods of identity spoofing. Moreover, biometric implementations such as the facial recognition algorithm described in this example, providing identity management on mobile devices, are a regular feature of mobile devices across the world, and there is a current unmet need for an automated authentication technology for optical recognition of identity, while maintaining immunity to spoofing attempts.

[0004] In a first aspect, the present disclosure provides a mobile device comprising: a front-facing camera, a front-facing screen, at least one processor, a memory, an operating system configured to perform executable instructions, and a computer program including instructions executable by the at least one processor to run an application for detecting spoofing of a 3D object, using a 2D representation of the 3D object, in a mobile object authentication process, the application comprising: a) a software module capturing, via the front-facing camera, i) a first image data of the 3D object while displaying, via the front-facing screen, a first authentication pattern, the first authentication pattern comprising a plurality of first authentication pattern regions, wherein at least one of the first authentication pattern regions varies from another first authentication pattern region in at least one of: brightness, position, size, shape, and color over time causing a first variance of lighting effects, wherein the first image data comprises a first set of highlights and shadows on the 3D object over

time; and ii) a second image data of the 3D object while displaying, via the front-facing screen, the second authentication pattern after displaying the first authentication pattern, wherein the second authentication pattern is different from the first authentication pattern, the second authentication pattern comprising a plurality of second authentication pattern regions, wherein at least one of the second authentication pattern regions varies from another second authentication pattern regions in at least one of brightness, position, size, shape, and color causing a second variance of lighting effects, wherein the second image data comprises a second set of highlights and shadows on the 3D object over time; b) a software module calculating a difference between the first set of highlights and shadows and the second set of highlights and shadows to determine a current spatial characteristic of the 3D object; and c) a software module determining if spoofing of the 3D object, using the 2D representation, is attempted in the mobile authentication process by

comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object.

[0005] In some embodiments, the 3D object comprises a face, a palm (palm print), a finger (fingerprint), or an ear. In some embodiments, the 2D representation comprises a photograph of the 3D object. In some embodiments, the image data comprises a plurality of photographs of the 3D object. In some embodiments, the image data comprises a video of the 3D object. In some embodiments, the authentication pattern comprises a plurality of images. In some embodiments, the authentication pattern comprises a video. In some embodiments, the plurality of regions are arranged in two or more vertical or horizontal bands in the authentication pattern. In some embodiments, the plurality of regions are arranged in a horizontal band across the top or bottom of the screen, or in a vertical band across the left or right side of the screen in the authentication pattern. In some embodiments, the authentication pattern comprises variation of at least one region in at least one of: brightness, position, size, shape, and color to form a regular pulse or a random pulse in the authentication pattern. In some embodiments, at least one of the regions varies in position over time to form a translation or rotation of the region in the authentication pattern. In some embodiments, at least one of the regions varies in size over time to form a contraction or expansion of the region in the authentication pattern. In some embodiments, the application further comprises a software module receiving a request to authenticate the 3D object. In some embodiments, the application further comprises a software module instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the image data. In some embodiments, the variation of at least one region in at least one of: brightness, position, size, shape, and color encode information in the authentication pattern.

[0006] In a second aspect, the present disclosure provides a system for detecting spoofing of a 3D object, using a 2D representation of the 3D object, in a mobile object authentication process, the system comprising: a mobile device comprising a front-facing camera, a front-facing screen, at least one processor, a memory; and a server comprising at least one processor and a memory: the mobile device configured to: a) capture, via the front-facing camera, i) a first image data of the 3D object while displaying, via the front-facing screen, a first authentication pattern comprising a plurality of first authentication pattern regions, wherein at least one of the first authentication regions varies from another first authentication pattern region in at least one of: brightness, position, size, shape, and color over time causing a first variance of lighting effects, wherein the first image data comprises a first set of highlights and shadows on the 3D object over time; ii) a second image data of the 3D object while displaying, via the front-facing screen, the second authentication pattern after displaying

the first authentication pattern, wherein the second authentication pattern is different from the first authentication pattern, the second authentication pattern comprising a plurality of second authentication pattern regions, wherein at least one of the second authentication pattern regions varies from another second authentication pattern regions in at least one of brightness, position, size, shape, and color causing a second variance of lighting effects, wherein the second image data comprises a second set of highlights and shadows on the 3D object over time; and b) transmit the first image data and the second image data to the server; the server configured to: a) receive the first image data and the second image from the mobile device; b) calculate a difference between the first set of highlights and shadows and the second set of highlights and shadows to determine a current spatial characteristic of the 3D object; c) determine if spoofing of the 3D object, using a 2D

representation of the 3D object, is attempted in the mobile authentication process by comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object; and d) transmit a spoofing result to the mobile device.

[0007] In some embodiments, the 3D object comprises a face, a palm (palm print), a finger (fingerprint), or an ear. In some embodiments, the 2D representation comprises a photograph of the 3D object. In some embodiments, the image data comprises a plurality of photographs of the 3D object. In some embodiments, the image data comprises a video of the 3D object. In some embodiments, the authentication pattern comprises a plurality of images. In some embodiments, the authentication pattern comprises a video. In some embodiments, the plurality of regions are arranged in two or more vertical or horizontal bands in the authentication pattern. In some embodiments, the plurality of regions are arranged in a horizontal band across the top or bottom of the screen, or in a vertical band across the left or right side of the screen in the authentication pattern. In some embodiments, the authentication pattern comprises variation of at least one region in at least one of: brightness, position, size, shape, and color to form a regular pulse or a random pulse in the authentication pattern. In some embodiments, at least one of the regions varies in position over time to form a translation or rotation of the region in the authentication pattern. In some embodiments, at least one of the regions varies in size over time to form a contraction or expansion of the region in the authentication pattern. In some embodiments, the application further comprises a software module receiving a request to authenticate the 3D object. In some embodiments, the application further comprises a software module instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the image data. In some embodiments, the variation of at least one region in at least one of: brightness, position, size, shape, and color encode information in the authentication pattern.

[0008] In a third aspect, the present disclosure provides a method of detecting spoofing of a 3D object, using a 2D representation of the 3D object, in a mobile object authentication process, the method comprising: a) capturing, via a front-facing camera of a mobile device, i) a first image data of the 3D object while displaying, via a front-facing screen of the mobile device, a first authentication pattern, the first authentication pattern comprising a plurality of first authentication pattern regions, wherein at least one of the first authentication pattern regions varies from another first authentication pattern region in at least one of: brightness, position, size, shape, and color over time causing a first variance of lighting effectsm wherein the first image data comprises a first set of highlights and shadows on the 3D object over time; and ii) a second image data of the 3D object while displaying, via the front-facing screen, the second authentication pattern after displaying the first authentication pattern,

wherein the second authentication pattern is different from the first authentication pattern, the second authentication pattern comprising a plurality of second authentication pattern regions, wherein at least one of the second authentication pattern regions varies from another second authentication pattern regions in at least one of brightness, position, size, shape, and color causing a second variance of lighting effects, wherein the second image data comprises a second set of highlights and shadows on the 3D object over time; b) calculating a difference between the first set of highlights and shadows and the second set of highlights and shadows to determine a current spatial characteristic of the 3D object; and c) determining if spoofing of the 3D object, using the 2D representation, is attempted in the mobile authentication process by comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object.

[0009] In some embodiments, the 3D object comprises a face, a palm (palm print), a finger (fingerprint), or an ear. In some embodiments, the 2D representation comprises a photograph of the 3D object. In some embodiments, the image data comprises a plurality of photographs of the 3D object. In some embodiments, the image data comprises a video of the 3D object. In some embodiments, the authentication pattern comprises a plurality of images. In some embodiments, the authentication pattern comprises a video. In some embodiments, the plurality of regions are arranged in two or more vertical or horizontal bands in the authentication pattern. In some embodiments, the plurality of regions are arranged in a horizontal band across the top or bottom of the screen, or in a vertical band across the left or right side of the screen in the authentication pattern. In some embodiments, the authentication pattern comprises variation of at least one region in at least one of: brightness, position, size, shape, and color, to form a regular pulse or a random pulse in the authentication pattern. In some embodiments, at least one of the regions varies in position over time to form a translation or rotation of the region in the authentication pattern. In some embodiments, at least one of the regions varies in size over time to form a contraction or expansion of the region in the authentication pattern. In some embodiments, further comprising receiving a request to authenticate the 3D object. In some embodiments, further comprising instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the image data. In some embodiments, the variation of at least one region in at least one of: brightness, position, size, shape, and color, encode information in the authentication pattern.

[0010] An embodiment provided herein is a mobile device comprising: a front-facing camera, a front-facing screen, at least one processor, a memory, an operating system configured to perform executable instructions, and a computer program including instructions executable by the at least one processor to run an application for recognizing a class or a within-class identity of a 3D object, solely or in combination with other mobile processes of object detection and identity recognition, the application comprising: a software module capturing, via the front-facing camera, image data of the 3D object while displaying, via the front-facing screen, an identification pattern comprising a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object over time; a software module using the image data and the identification pattern to determine a current spatial characteristic of the 3D object; and a software module determining the class, or the within-class identity of the 3D object, solely or in combination with other mobile processes of object detection and identity recognition by comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object.

[0011] In some embodiments, the 3D object comprises a face, a palm (palm print), a finger (fingerprint), or an ear. In some embodiments, the image data comprises a plurality of photographs of the 3D object. In some embodiments, the image data comprises a video of the 3D object. In some embodiments, the identification pattern comprises a plurality of images. In some embodiments, the identification pattern comprises a video. In some embodiments, the plurality of regions are arranged in two or more vertical or horizontal bands in the identification pattern. In some embodiments, the plurality of regions are arranged in a horizontal band across the top or bottom of the screen, or in a vertical band across the left or right side of the screen in the identification pattern. In some embodiments, the identification pattern comprises variation of at least one region in at least one of: brightness, position, size, shape, and color to form a regular pulse or a random pulse in the identification pattern. In some embodiments, at least one of the regions varies in position over time to form a translation or rotation of the region in the identification pattern. In some embodiments, at least one of the regions varies in size over time to form a contraction or expansion of the region in the identification pattern. In some embodiments, the application further comprises a software module receiving a request to recognize the class, or the within-class identity of the 3D object. In some embodiments, the application further comprises a software module instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the image data. In some embodiments, the variation of at least one region in at least one of: brightness, position, size, shape, and color encode information in the identification pattern.

[0012] Another embodiment provided herein is a system for recognizing a class or a within-class identity of a 3D object, solely or in combination with other mobile processes of object detection and identity recognition, the system comprising: a mobile device comprising a front-facing camera, a front-facing screen, at least one processor, a memory; and a server comprising at least one processor and a memory: the mobile device configured to: capture, via the front-facing camera, image data of the 3D object while displaying, via the front-facing screen, an identification pattern comprising a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object over time; and transmit the image data and the identification pattern to the server; the server configured to: receive the image data and the identification pattern from the mobile device; use the image data and the identification pattern to determine a current spatial characteristic of the 3D object; determine the class, or the within-class identity of the 3D object, solely or in combination with other mobile processes of object detection and identity recognition , by comparing the current spatial

characteristic of the 3D object with a stored reference spatial characteristic of the 3D object; and transmit the class, or the within-class identity of the 3D object to the mobile device.

[0013] In some embodiments, the 3D object comprises a face, a palm (palm print), a finger (fingerprint), or an ear. In some embodiments, the image data comprises a plurality of photographs of the 3D object. In some embodiments, the image data comprises a video of the 3D object. In some embodiments, the identification pattern comprises a plurality of images. In some embodiments, the identification pattern comprises a video. In some embodiments, the plurality of regions are arranged in two or more vertical or horizontal bands in the identification pattern. In some embodiments, the plurality of regions are arranged in a horizontal band across the top or bottom of the screen, or in a vertical band across the left or right side of the screen in the identification pattern. In some embodiments, the identification pattern comprises variation of at least one region in at least one of: brightness, position, size, shape, and color to form a regular pulse or a random pulse in the identification pattern. In some embodiments, at least one of the regions varies in position over time to form a translation or rotation of the region in the identification pattern. In some embodiments, at least one of the regions varies in size over time to form a contraction or expansion of the region in the identification pattern. In some embodiments, the application further comprises a software module receiving a request to determine a class or within-class identity of the 3D object. In some embodiments, the application further comprises a software module instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the image data. In some embodiments, the variation of at least one region in at least one of: brightness, position, size, shape, and color encode information in the identification pattern.

[0014] Yet another embodiment provided herein is a method of recognizing a class or within-class identity of a 3D object, solely or in combination with other mobile processes of object detection and identity recognition, the method comprising: capturing, via a front-facing camera of a mobile device, image data of the 3D object while displaying, via a front-facing screen of the mobile device, an identification pattern comprising a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object over time; using the image data and the identification pattern to determine a current spatial characteristic of the 3D object; and determining the class, or the within-class identity of a 3D object of the 3D object, solely or in combination with other mobile processes of object detection and identity recognition, by comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object.

[0015] In some embodiments, the 3D object comprises a face, a palm (palm print), a finger (fingerprint), or an ear. In some embodiments, the image data comprises a plurality of photographs of the 3D object. In some embodiments, the image data comprises a video of the 3D object. In some embodiments, the identification pattern comprises a plurality of images. In some embodiments, the identification pattern comprises a video. In some embodiments, the plurality of regions are arranged in two or more vertical or horizontal bands in the identification pattern. In some embodiments, the plurality of regions are arranged in a horizontal band across the top or bottom of the screen, or in a vertical band across the left or right side of the screen in the identification pattern. In some embodiments, the identification pattern comprises variation of at least one region in at least one of: brightness, position, size, shape, and color, to form a regular pulse or a random pulse in the identification pattern. In some embodiments, at least one of the regions varies in position over time to form a translation or rotation of the region in the identification pattern. In some embodiments, at least one of the regions varies in size over time to form a contraction or expansion of the region in the identification pattern. In some embodiments, further comprising receiving a request to recognize a class or within-class identity of the 3D object. In some embodiments, further comprising instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the image data. In some embodiments, the variation of at least one region in at least one of: brightness, position, size, shape, and color, encode information in the identification pattern.

[0016] In some embodiments, the plurality of regions comprises 2 regions to 50 regions. In some embodiments, the plurality of regions comprises at least 2 regions. In some embodiments, the plurality of regions comprises at most 50 regions. In some embodiments, the plurality of regions comprises 2 regions to 3 regions, 2 regions to 4 regions, 2 regions to 5 regions, 2 regions to 10 regions, 2 regions to 15 regions, 2 regions to 20 regions, 2 regions to 25 regions, 2 regions to 30 regions, 2 regions to 35 regions, 2 regions to 40 regions, 2 regions to 50 regions, 3 regions to 4 regions, 3 regions to 5 regions, 3 regions to 10 regions, 3 regions to 15 regions, 3 regions to 20 regions, 3 regions to 25 regions, 3 regions to 30 regions, 3 regions to 35 regions, 3 regions to 40 regions, 3 regions to 50 regions, 4 regions to 5 regions, 4 regions to 10 regions, 4 regions to 15 regions, 4 regions to 20 regions, 4 regions to 25 regions, 4 regions to 30 regions, 4 regions to 35 regions, 4 regions to 40 regions, 4 regions to 50 regions, 5 regions to 10 regions, 5 regions to 15 regions, 5 regions to 20 regions, 5 regions to 25 regions, 5 regions to 30 regions, 5 regions to 35 regions, 5 regions to 40 regions, 5 regions to 50 regions, 10 regions to 15 regions, 10 regions to 20 regions, 10 regions to 25 regions, 10 regions to 30 regions, 10 regions to 35 regions, 10 regions to 40 regions, 10 regions to 50 regions, 15 regions to 20 regions, 15 regions to 25 regions, 15 regions to 30 regions, 15 regions to 35 regions, 15 regions to 40 regions, 15 regions

to 50 regions, 20 regions to 25 regions, 20 regions to 30 regions, 20 regions to 35 regions, 20 regions to 40 regions, 20 regions to 50 regions, 25 regions to 30 regions, 25 regions to 35 regions, 25 regions to 40 regions, 25 regions to 50 regions, 30 regions to 35 regions, 30 regions to 40 regions, 30 regions to 50 regions, 35 regions to 40 regions, 35 regions to 50 regions, or 40 regions to 50 regions. In some embodiments, the plurality of regions comprises 2 regions, 3 regions, 4 regions, 5 regions, 10 regions, 15 regions, 20 regions, 25 regions, 30 regions, 35 regions, 40 regions, 50 regions, or more, including increments therein.

[0017] In some embodiments, a region comprises a percentage of the area of the screen of the mobile device of 0 % to 99 %. In some embodiments, a region comprises a percentage of the area of the screen of the mobile device of at least 0%. In some embodiments, a region comprises a percentage of the area of the screen of the mobile device of at most 99%. In some embodiments, a region comprises a percentage of the area of the screen of the mobile device of 0% to 1%, 0% to 10%, 0% to 20%, 0% to 30%, 0% to 40%, 0% to 50%, 0% to 60%, 0% to 70%, 0% to 80%, 0% to 90%, 0% to 99%, 1% to 10%, 1% to 20%, 1% to 30%, 1% to 40%, 1% to 50%, 1% to 60%, 1% to 70%, 1% to 80%, 1% to 90%, 1% to 99%, 10% to 20%, 10% to 30%, 10% to 40%, 10% to 50%, 10% to 60%, 10% to 70%, 10% to 80%, 10% to 90%, 10% to 99%, 20% to 30%, 20% to 40%, 20% to 50%, 20% to 60%, 20% to 70%, 20% to 80%, 20% to 90%, 20% to 99%, 30% to 40%, 30% to 50%, 30% to 60%, 30% to 70%, 30% to 80%, 30% to 90%, 30% to 99%, 40% to 50%, 40% to 60%, 40% to 70%, 40% to 80%, 40% to 90%, 40% to 99%, 50% to 60%, 50% to 70%, 50% to 80%, 50% to 90%, 50% to 99%, 60% to 70%, 60% to 80%, 60% to 90%, 60% to 99%, 70% to 80%, 70% to 90%, 70% to 99%, 80% to 90%, 80% to 99%, or 90% to 99%. In some embodiments, a region comprises a percentage of the area of the screen of the mobile device of 0%, 1%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 99%.

[0018] In some embodiments, a region exhibits a percentage of the mobile device's brightness capability of 0 % to 100 %. In some embodiments, a region exhibits a percentage of the mobile device's brightness capability of at least 0 %. In some embodiments, a region exhibits a percentage of the mobile device's brightness capability of at most 100 %. In some embodiments, a region exhibits a percentage of the mobile device's brightness capability of 0% to 1%, 0% to 10%, 0% to 20%, 0% to 30%, 0% to 40%, 0% to 50%, 0% to 60%, 0% to 70%, 0% to 80%, 0% to 90%, 0% to 100%, 1% to 10%, 1% to 20%, 1% to 30%, 1% to 40%, 1% to 50%, 1% to 60%, 1% to 70%, 1% to 80%, 1% to 90%, 1% to 100%, 10% to 20%, 10% to 30%, 10% to 40%, 10% to 50%, 10% to 60%, 10% to 70%, 10% to 80%, 10% to 90%, 10% to 100%, 20% to 30%, 20% to 40%, 20% to 50%, 20% to 60%, 20% to 70%, 20% to 80%, 20% to 90%, 20% to 100%, 30% to 40%, 30% to 50%, 30% to 60%, 30% to 70%, 30% to 80%, 30% to 90%, 30% to 100%, 40% to 50%, 40% to 60%, 40% to 70%, 40% to 80%, 40% to 90%, 40% to 100%, 50% to 60%, 5 %

to 70%, 50% to 80%, 50% to 90%, 50% to 100%, 60% to 70%, 60% to 80%, 60% to 90%, 60% to 100%, 70% to 80%, 70% to 90%, 70% to 100%, 80% to 90%, 80% to 100%, or 90% to 100%. In some embodiments, a region exhibits a percentage of the mobile device's brightness capability of 0%, 1%, 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, or 100%, including increments therein.

[0019] In some embodiments, a region exhibits a shape comprising a circle, an oval, an arch, an ellipse, a triangle, a square, a polygon, an amorphous shape, or any combination thereof. In some embodiments, a region exhibits a color comprising alice blue, antique white, aqua, aquamarine, azure, beige, bisque, black, blanched almond, blue, blue violet, brown, burly wood, cadet blue, chartreuse, chocolate, coral, cornflower blue, cornsilk, crimson, cyan, dark blue, dark cyan, dark golden rod, dark gray, dark grey, dark green, dark khaki, dark magenta, dark olive green, dark orange, dark orchid, dark red, dark salmon, dark sea green, dark slate blue, dark slate gray, dark turquoise, dark violet, deep pink, deep sky blue, dim grey, dodger blue, fire brick, floral white, forest green, fuchsia, gainsboro, ghost white, gold, golden rod, gray, green, green yellow, honey dew, hot pink, indian red, indigo, ivory, khaki, lavender, lavender blush, lawn green, lemon chiffon, light blue, light coral, light cyan, light goldenrod yellow, light grey, light green, light pink, light salmon, light sea green, light sky blue, light slate gray, light slate grey, light steel blue, light yellow, lime, lime green, linen, magenta, maroon, medium aqua marine, medium blue, medium orchid, medium purple, medium sea green, medium slate blue, medium spring green, medium turquoise, medium violet red, midnight blue, mint cream, misty rose, moccasin, navajo white, navy, old lace, olive, olive drab, orange, orange red, orchid, pale golden rod, pale green, pale turquoise, pale violet red, papaya whip, peach puff, peru, pink, plum, powder blue, purple, rebecca purple, red, rosy brown, royal blue, saddle brown, salmon, sandy brown, sea green, sea shell, sienna, silver, sky blue, slate blue, slate grey, snow, spring green, steel blue, tan, teal, thistle, tomato, turquoise, violet, wheat, white, white smoke, yellow, yellow green, or any combination thereof.

[0020] In some embodiments, the number of images in the authentication pattern is 2 to 10,000. In some embodiments, the number of images in the authentication pattern is at least 2. In some embodiments, the number of images in the authentication pattern is at most 10,000. In some embodiments, the number of images in the authentication pattern is 2 to 5, 2 to 10, 2 to 20, 2 to 50, 2 to 100, 2 to 200, 2 to 500, 2 to 1,000, 2 to 2,000, 2 to 5,000, 2 to 10,000, 5 to 10, 5 to 20, 5 to 50, 5 to 100, 5 to 200, 5 to 500, 5 to 1,000, 5 to 2,000, 5 to 5,000, 5 to 10,000, 10 to 20, 10 to 50, 10 to 100, 10 to 200, 10 to 500, 10 to 1,000, 10 to 2,000, 10 to 5,000, 10 to 10,000, 20 to 50, 20 to 100, 20 to 200, 20 to 500, 20 to 1,000, 20 to 2,000, 20 to 5,000, 20 to 10,000, 50 to 100, 50 to 200, 50 to 500, 50 to 1,000, 50 to 2,000, 50 to 5,000, 50 to 10,000, 100 to 200, 100 to 500,

100 to 1,000, 100 to 2,000, 100 to 5,000, 100 to 10,000, 200 to 500, 200 to 1,000, 200 to 2,000, 200 to 5,000, 200 to 10,000, 500 to 1,000, 500 to 2,000, 500 to 5,000, 500 to 10,000, 1,000 to 2,000, 1,000 to 5,000, 1,000 to 10,000, 2,000 to 5,000, 2,000 to 10,000, or 5,000 to 10,000. In some embodiments, the number of images in the authentication pattern is 2, 5, 10, 20, 50, 100, 200, 500, 1,000, 2,000, 5,000, or 10,000, including increments therein.

[0021] In some embodiments, the number of photographs of the 3D object that comprise the image data is 2 to 10,000. In some embodiments, the number of photographs of the 3D object that comprise the image data is at least 2. In some embodiments, the number of photographs of the 3D object that comprise the image data is at most 10,000. In some embodiments, the number of photographs of the 3D object that comprise the image data is 2 to 5, 2 to 10, 2 to 20, 2 to 50, 2 to 100, 2 to 200, 2 to 500, 2 to 1,000, 2 to 2,000, 2 to 5,000, 2 to 10,000, 5 to 10, 5 to 20, 5 to 50, 5 to 100, 5 to 200, 5 to 500, 5 to 1,000, 5 to 2,000, 5 to 5,000, 5 to 10,000, 10 to 20, 10 to 50, 10 to 100, 10 to 200, 10 to 500, 10 to 1,000, 10 to 2,000, 10 to 5,000, 10 to 10,000, 20 to 50, 20 to 100, 20 to 200, 20 to 500, 20 to 1,000, 20 to 2,000, 20 to 5,000, 20 to 10,000, 50 to 100, 50 to 200, 50 to 500, 50 to 1,000, 50 to 2,000, 50 to 5,000, 50 to 10,000, 100 to 200, 100 to 500, 100 to 1,000, 100 to 2,000, 100 to 5,000, 100 to 10,000, 200 to 500, 200 to 1,000, 200 to 2,000, 200 to 5,000, 200 to 10,000, 500 to 1,000, 500 to 2,000, 500 to 5,000, 500 to 10,000, 1,000 to 2,000, 1,000 to 5,000, 1,000 to 10,000, 2,000 to 5,000, 2,000 to 10,000, or 5,000 to 10,000. In some embodiments, the number of photographs of the 3D object that comprise the image data is 2, 5, 10, 20, 50, 100, 200, 500, 1,000, 2,000, 5,000, or 10,000, including increments therein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] A better understanding of the features and advantages of the present subject matter will be obtained by reference to the following detailed description that sets forth illustrative embodiments and the accompanying drawings of which:

[0023] **Fig. 1** shows an illustration of an exemplary device for detecting spoofing of a 3D object, using a 2D representation, in a mobile object authentication process;

[0024] **Fig. 2A** shows an illustration of a first exemplary image of an authentication pattern comprising two horizontally arrayed regions;

[0025] **Fig. 2B** shows an illustration of a second exemplary image of an authentication pattern comprising two vertically arrayed regions;

[0026] **Fig. 2C** shows an illustration of a third exemplary image of an authentication pattern comprising four horizontally arrayed regions;

[0027] **Fig. 2D** shows an illustration of a fourth exemplary image of an authentication pattern comprising four vertically arrayed regions;

[0028] **Fig. 2E** shows an illustration of a fifth exemplary image of an authentication pattern comprising three regions arranged in vertical bands;

[0029] **Fig. 2F** shows an illustration of a sixth exemplary image of an authentication pattern comprising three regions arranged in horizontal bands;

[0030] **Fig. 2G** shows an illustration of a seventh exemplary image of an authentication pattern comprising a plurality of horizontally arrayed regions;

[0031] **Fig. 2H** shows an illustration of a eighth exemplary image of an authentication pattern comprising a plurality of vertically arrayed regions;

[0032] **Fig. 3A** shows an illustration of an exemplary first authentication pattern comprising a rotation of a region;

[0033] **Fig. 3B** shows an illustration of an exemplary second authentication pattern comprising a rotation of a plurality of regions;

[0034] **Fig. 4A** shows an illustration of an exemplary first image data, displaying the highlights and shadows on an object resulting from the authentication image in **Fig. 2A**;

[0035] **Fig. 4B** shows an illustration of an exemplary first image data, displaying the highlights and shadows on an object resulting from the authentication image in **Fig. 2B**;

[0036] **Fig. 5A** shows an illustration of an exemplary first image data, displaying the highlights and shadows on a human face resulting from the authentication image in **Fig. 2A**;

[0037] **Fig. 5B** shows an illustration of an exemplary first image data, displaying the highlights and shadows on a human face resulting from the authentication image in **Fig. 2B**;

[0038] **Fig. 6A** shows a top view illustration of the exemplary authentication image in **Fig. 2E** causing a variance of lighting effects which create highlights and shadows on a human face;

[0039] **Fig. 6B** shows a top view illustration of the exemplary authentication image in **Fig. 2F** causing a variance of lighting effects which create highlights and shadows on a human face;

[0040] **Fig. 6C** shows top view illustrations of the exemplary authentication images in **Figs. 2E** and **2F** causing a variance of lighting effects which create highlights and shadows on a human face;

[0041] **Fig. 6D** shows front view illustrations of the exemplary authentication images in **Figs. 2E** and **2F** causing a variance of lighting effects which create highlights and shadows on a human face;

[0042] **Fig. 7A** shows illustrations of exemplary highlights and shadows on a human face as a result of brightness applied from a variety of directions;

[0043] **Fig. 7B** shows exemplary pictures of highlights and shadows on a human face as a result of brightness applied from a variety of directions;

[0044] **Fig. 8** shows a non-limiting schematic diagram of a digital processing device; in this

case, a device with one or more CPUs, a memory, a communication interface, and a display;

[0045] **Fig. 9** shows a non-limiting schematic diagram of a web/mobile application provision system; in this case, a system providing browser-based and/or native mobile user interfaces; and

[0046] **Fig. 10** shows a non-limiting schematic diagram of a cloud-based web/mobile application provision system; in this case, a system comprising an elastically load balanced, auto-scaling web server and application server resources as well synchronously replicated databases.

DETAILED DESCRIPTION OF THE DRAWINGS

Terms and definitions

[0047] Unless otherwise defined, all technical terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs.

[0048] As used herein, the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise. Any reference to “or” herein is intended to encompass “and/or” unless otherwise stated.

[0049] As used herein, the term “about” refers to an amount that is near the stated amount by 10%, 5%, or 1%, including increments therein.

[0050] As used herein, the term “front-facing camera” refers to a feature of cameras, mobile phones, smartphones, tablets and similar mobile devices that allows a user to take self-portrait, photograph, or video while looking at the display of the device.

[0051] As used herein, the term “3D” refers to having a length, a breadth, and a depth.

[0052] As used herein, the term “2D” refers to having a length and a breadth, a length and a depth, or a breadth and a depth, of much greater magnitude in relation to any third dimension of the object as to the 3D object for which it is presented as a spoof.

[0053] While preferred embodiments of the present subject matter have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the disclosure. It should be understood that various alternatives to the embodiments of the subject matter described herein may be employed in practicing the disclosure.

Devices for detecting spoofing of a 3D object

[0054] Provided herein, per **Fig. 1**, is a mobile device **110** for detecting spoofing of a 3D object **101** comprising a front-facing screen **111**, and a front-facing camera **112**; at least one processor; a memory, an operating system configured to perform executable instructions; and a computer program including instructions executable by the at least one processor to run an application for

detecting spoofing of a 3D object **101**, using a 2D representation, in a mobile object authentication process. In some embodiments, the application comprises: a software module capturing, via the front-facing camera **112**, image data of the 3D object **101** while displaying, via the front-facing screen **111**, an authentication pattern comprising a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object **101** over time. In some embodiments, the mobile device **110** further comprises a software module using the image data and the authentication pattern to determine a current spatial characteristic of the 3D object **101**, and a software module determining if spoofing of the 3D object **101**, using a 2D representation, is attempted in the mobile authentication process, by comparing the current spatial characteristic of the 3D object **101** with a stored reference spatial characteristic of the 3D object **101**.

[0055] In some embodiments, the 3D object **101** comprises a face, a palm (palm print), a finger (fingerprint), or an ear. In some embodiments, the 3D object **101** comprises a human face. In some embodiments, the 2D representation comprises a photograph of the 3D object **101**. In some embodiments, the image data comprises a plurality of photographs of the 3D object **101**. In some embodiments, the image data comprises a video of the 3D object **101**. In some embodiments, the authentication pattern comprises a plurality of images. In some embodiments, the authentication pattern comprises a video. In some embodiments, the plurality of regions is arranged in two or more vertical or horizontal bands in the authentication pattern. In some embodiments, the plurality of regions are arranged in a horizontal band across the top or bottom of the screen, or in a vertical band across the left or right side of the screen in the authentication pattern. In some embodiments, the authentication pattern comprises variation of at least one region in at least one of: brightness, position, size, shape, and color to form a regular pulse or a random pulse in the authentication pattern. In some embodiments, at least one of the regions varies in position over time to form a translation or rotation of the region in the authentication pattern. In some embodiments, at least one of the regions varies in size over time to form a contraction or expansion of the region in the authentication pattern. In some embodiments, the application further comprises a software module receiving a request to authenticate the 3D object **101**. In some embodiments, the application further comprises a software module instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the image data. In some embodiments, the variation of at least one region in at least one of: brightness, position, size, shape, and color encode information in the authentication pattern.

Authentication Patterns

[0056] **Figs. 2A to 2H**, shows illustrations of exemplary images of the plurality of images which comprises the authentication pattern, wherein the authentication pattern comprises a plurality of regions that differ in brightness, color, or any combination thereof.

[0057] In some embodiments, per **Fig. 2A**, the plurality of regions comprises a high brightness region **231** and a low brightness region **232**, that are arranged in two vertical bands. In some embodiments, per **Fig. 2B**, the plurality of regions comprises a high brightness region **231** and a low brightness region **232**, that are arranged in two horizontal bands. In some embodiments, the high brightness region **231** is displayed on the left, right, top or bottom of the low brightness region **232**. In some embodiments, per **Fig. 2C**, the plurality of regions comprises two high brightness regions **231** and two low brightness regions **232** that are arranged in four alternating vertical bands. In some embodiments, per **Fig. 2D**, the plurality of regions comprises two high brightness regions **231** and two low brightness regions **232** that are arranged in four alternating horizontal bands. In some embodiments, per **Fig. 2G**, the plurality of regions comprises a plurality of high brightness regions **231** and a plurality of low brightness regions **232** that are arranged in alternating horizontal, or vertical, bands.

[0058] In some embodiments, per **Fig. 2E**, the plurality of regions comprises two horizontal bands of high brightness regions **231** across the top and bottom of the screen, and a single horizontal band of a low brightness region **232** across the middle of the screen. In some embodiments, per **Fig. 2F**, the plurality of regions comprises vertical or horizontal bands of high brightness regions **231** along the left and right sides of the screen, and a single vertical band of a low brightness region **232** along the middle of the screen. In some embodiments, per **Fig. 2G**, the plurality of regions comprises a plurality of randomly shaped and positioned, high brightness regions **231** and low brightness regions **232**.

[0059] In some embodiments the authentication pattern comprises a variation of at least one region in at least one of: brightness, position, size, shape, and color to form a regular pulse or a random pulse. In some embodiments, per **Figs. 3A and 3B**, at least one of the high brightness regions **331** and low brightness regions **332** vary in position over time to form a translation or rotation of the region in the authentication pattern. In some embodiments, at least one of the regions varies in size over time, to form a contraction or expansion of the region in the authentication pattern.

Methods for detecting spoofing of a 3D object

[0060] Provided herein, per **Figs. 4A and 4B** is a method of detecting spoofing of a 3D object **410**, using a 2D representation **420a, 420b**, in a mobile object authentication process, the method comprising: capturing, via a front-facing camera of a mobile device, image data of the

3D object **410** while displaying, via a front-facing screen of the mobile device, an authentication pattern comprising a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object **410** over time; using the image data and the authentication pattern to determine a current spatial characteristic of the 3D object **410**; and determining if spoofing of the 3D object **410**, using a 2D representation **420a**, **420b**, is attempted in the mobile authentication process by comparing the current spatial characteristic of the 3D object **410** with a stored reference spatial characteristic of the 3D object **410**.

[0061] In some embodiments an authentication pattern comprises a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object **410** over time, per **Figs 4A** and **4B**. In some embodiments the authentication pattern comprises a plurality of images. In the case wherein the regions in an image of the authentication pattern comprise a single high brightness region displayed on the left side of the front-facing-screen, and a low high brightness region displayed on the right side of the front-facing-screen, as per **Fig. 2A**, the highlights and shadows on the 3D object **410**, are seen in the exemplary 2D representation **420a** in **Fig 4A**. In the case wherein the regions in an image of the authentication pattern comprise a single high brightness region displayed on the bottom of the front-facing-screen, and a low high brightness region displayed on the top of the front-facing-screen, as per **Fig. 2B**, the highlights and shadows on the 3D object **410**, are seen in the exemplary 2D representation **420b** in **Fig 4B**.

[0062] The differences between the 2D representations **420a**, **420b** of the 3D object **410**, may be used to determine a spatial characteristic of the 3D object **410**, and to determine if spoofing of the 3D object **410**, using a 2D representation **420a**, **420b**, is attempted in the mobile authentication process, by comparing the current spatial characteristic of the 3D object **410** with a stored reference spatial characteristic of the 3D object **410**.

[0063] Once a current spatial characteristic of the 3D object **410** from the image data and the authentication pattern is determined to match a stored reference spatial characteristic of the 3D object **410**, an access may be granted if no spoofing is detected, or block access to the user if spoofing is detected. An authority may additionally be alerted with information related to the time, location, device, account, or any combination thereof associated with the spoofing attempt.

[0064] In some embodiments, the authentication pattern comprises a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object **410** over time, and wherein the variation of at least one region in at least one of:

brightness, position, size, shape, and color, encodes information in the authentication pattern. In some embodiments, the encoded information comprises encoded information corresponding to the user, the object, the authentication attempt, or any combination thereof. In some embodiments, determination that highlights and shadows on the 3D object **410**, captured by the 2D representation **420a**, **420b**, correlate with the information encoded within the authentication pattern, serves as an additional factor of authentication and/or security.

[0065] In some embodiments, per **Figs. 5A** and **5B**, the object comprises a human face **510** wherein the front-facing camera captures the 2D representation **520a**, **520b** of the human face **510** to detect spoofing. In some embodiments, per **Fig. 5A**, the authentication pattern comprises a plurality of images, wherein each image of the authentication pattern comprises a plurality of regions, and wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object **510** over time. In the case wherein the plurality of regions in the authentication pattern comprises a single low brightness region displayed on the left side of the front-facing-screen, and a single high brightness region displayed on the right side of the front-facing-screen, as per **Fig. 2A**, the highlights and shadows on the human face **510**, are seen in the exemplary 2D representation **520a** in **Fig 5A**. In the case wherein the plurality of regions in the authentication pattern comprises a single low brightness region displayed on the top side of the front-facing-screen, and a single high brightness region displayed on the bottom side of the front-facing-screen, as per **Fig. 2B**, the highlights and shadows on the human face **510**, are seen in the exemplary 2D representation **520b** in **Fig 5B**.

[0066] The differences between the 2D representations **520a**, **520b** of the human face **510**, may be used to determine a spatial characteristic of the human face **510**, and to determine if spoofing of the human face **510**, using a 2D representation **520a**, **520b**, is attempted in the mobile authentication process by comparing the current spatial characteristic of the human face **510** with a stored reference spatial characteristic of the human face **510**.

[0067] Once a current spatial characteristic of the human face **510** from the image data and the authentication pattern is determined to match a stored reference spatial characteristic of the human face **510**, an access may be granted if no spoofing is detected, or block access to the user if spoofing is detected. An authority may additionally be alerted with information related to the time, location, device, account, or any combination thereof associated with the spoofing attempt.

[0068] In some embodiments, per **Figs. 6A**, **6B**, and **6C**, the object comprises a human face **610** and the front-facing camera captures the 2D representation of the human face **610** to detect spoofing. In some embodiments, the authentication pattern comprises a plurality of images, wherein an image comprises a plurality of regions, and wherein at least one of the regions varies

in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the human face **610** over time. It can be seen, per **Fig. 6A**, that an image of a first authentication pattern **620a** comprising a two high brightness regions **601** displayed along the top and bottom of the front-facing-screen, and a single low brightness region **602** displayed along the middle of the front-facing-screen, as per **Fig. 2E** casts certain highlights and shadows on the human face **610**. By contrast, an image of a second authentication pattern **620b**, per **Fig. 6B**, comprising a two high brightness regions **601** displayed along the left and right sides of the front-facing-screen, and a single low brightness region **602** displayed along a middle band of the front-facing-screen, as per **Fig. 2F** casts different highlights and shadows on the human face **610**.

[0069] The differences between the 2D representations captured of the human face **610**, while the front-facing-screen displays the first authentication image **620a** and while the front-facing-screen displays the second authentication image **620b**, may be used to determine a current spatial characteristic of the human face **610**, and to determine if spoofing of the human face **610**, using a 2D representation, is attempted in the mobile authentication process by comparing the current spatial characteristic of the human face **610** with a stored reference spatial characteristic of the human face **610**.

[0070] Per **Fig 6D**, it can be seen that if the object is in fact a human face **610**, and if the authentication pattern comprises high brightness regions across the top and bottom of the screen and the single horizontal band of a low brightness region in the middle of the screen, as per **Fig. 2E**, the spatial characteristic of the human face **610** should exhibit highlights on the top of the head of the human face **610**, and on the chin of the human face **610**. Per **Fig 6D**, it can also be seen that if the object is in fact a human face **610**, and if the authentication pattern comprises high brightness regions across the left and right sides of the screen and the single horizontal band of a low brightness region across the middle of the screen, as per **Fig. 2F**, the spatial characteristic of the human face **610** should exhibit highlights on the left and right sides of the head of the human face **610**.

[0071] Once a current spatial characteristic of the human face **610** from the image data and the authentication pattern is determined to match a stored reference spatial characteristic of the human face **610**, an access may be granted if no spoofing is detected, or block access to the user if spoofing is detected. An authority may additionally be alerted with information related to the time, location, device, account, or any combination thereof associated with the spoofing attempt.

Systems for detecting spoofing of a 3D object

[0072] Provided herein is a system for detecting spoofing of a 3D object, using a 2D representation, in a mobile object authentication process, the system comprising: a mobile

device comprising a front-facing camera, a front-facing screen, at least one processor, a memory; and a server comprising at least one processor and a memory: the mobile device configured to: capture, via the front-facing camera, image data of the 3D object while displaying, via the front-facing screen, an authentication pattern comprising a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the 3D object over time; and transmit the image data and the authentication pattern to the server; the server configured to: receive the image data and the authentication pattern from the mobile device; use the image data and the authentication pattern to determine a current spatial characteristic of the 3D object; determine if spoofing of the 3D object, using a 2D representation, is attempted in the mobile authentication process by comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object; and transmit a result spoofing result to the mobile device.

Digital processing device

[0073] In some embodiments, the platforms, systems, media, and methods described herein include a digital processing device, or use of the same. In further embodiments, the digital processing device includes one or more hardware central processing units (CPUs) or general purpose graphics processing units (GPGPUs) that carry out the device's functions. In still further embodiments, the digital processing device further comprises an operating system configured to perform executable instructions. In some embodiments, the digital processing device is optionally connected to a computer network. In further embodiments, the digital processing device is optionally connected to the Internet such that it accesses the World Wide Web. In still further embodiments, the digital processing device is optionally connected to a cloud computing infrastructure. In other embodiments, the digital processing device is optionally connected to an intranet. In other embodiments, the digital processing device is optionally connected to a data storage device.

[0074] In accordance with the description herein, suitable digital processing devices include, by way of non-limiting examples, server computers, desktop computers, laptop computers, notebook computers, sub-notebook computers, netbook computers, netpad computers, set-top computers, media streaming devices, handheld computers, Internet appliances, mobile smartphones, tablet computers, personal digital assistants, video game consoles, and vehicles. Those of skill in the art will recognize that many smartphones are suitable for use in the system described herein. Those of skill in the art will also recognize that select televisions, video players, and digital music players with optional computer network connectivity are suitable for use in the system described herein. Suitable tablet computers include those with booklet, slate,

and convertible configurations, known to those of skill in the art.

[0075] In some embodiments, the digital processing device includes an operating system configured to perform executable instructions. The operating system is, for example, software, including programs and data, which manages the device's hardware and provides services for execution of applications. Those of skill in the art will recognize that suitable server operating systems include, by way of non-limiting examples, FreeBSD, OpenBSD, NetBSD[®], Linux, Apple[®] Mac OS X Server[®], Oracle[®] Solaris[®], Windows Server[®], and Novell[®] NetWare[®]. Those of skill in the art will recognize that suitable personal computer operating systems include, by way of non-limiting examples, Microsoft[®] Windows[®], Apple[®] Mac OS X[®], UNIX[®], and UNIX-like operating systems such as GNU/Linux[®]. In some embodiments, the operating system is provided by cloud computing. Those of skill in the art will also recognize that suitable mobile smart phone operating systems include, by way of non-limiting examples, Nokia[®] Symbian[®] OS, Apple[®] iOS[®], Research In Motion[®] BlackBerry OS[®], Google[®] Android[®], Microsoft[®] Windows Phone[®] OS, Microsoft[®] Windows Mobile[®] OS, Linux[®], and Palm[®] WebOS[®]. Those of skill in the art will also recognize that suitable media streaming device operating systems include, by way of non-limiting examples, Apple TV[®], Roku[®], Boxee[®], Google TV[®], Google Chromecast[®], Amazon Fire[®], and Samsung[®] HomeSync[®]. Those of skill in the art will also recognize that suitable video game console operating systems include, by way of non-limiting examples, Sony[®] PS3[®], Sony[®] PS4[®], Microsoft[®] Xbox 360[®], Microsoft Xbox One, Nintendo[®] Wii[®], Nintendo[®] Wii U[®], and Ouya[®].

[0076] In some embodiments, the device includes a storage and/or memory device. The storage and/or memory device is one or more physical apparatuses used to store data or programs on a temporary or permanent basis. In some embodiments, the device is volatile memory and requires power to maintain stored information. In some embodiments, the device is non-volatile memory and retains stored information when the digital processing device is not powered. In further embodiments, the non-volatile memory comprises flash memory. In some embodiments, the non-volatile memory comprises dynamic random-access memory (DRAM). In some embodiments, the non-volatile memory comprises ferroelectric random access memory (FRAM). In some embodiments, the non-volatile memory comprises phase-change random access memory (PRAM). In other embodiments, the device is a storage device including, by way of non-limiting examples, CD-ROMs, DVDs, flash memory devices, magnetic disk drives, magnetic tapes drives, optical disk drives, and cloud computing based storage. In further embodiments, the storage and/or memory device is a combination of devices such as those disclosed herein.

[0077] In some embodiments, the digital processing device includes a display to send visual

information to a user. In some embodiments, the display is a liquid crystal display (LCD). In further embodiments, the display is a thin film transistor liquid crystal display (TFT-LCD). In some embodiments, the display is an organic light emitting diode (OLED) display. In various further embodiments, on OLED display is a passive-matrix OLED (PMOLED) or active-matrix OLED (AMOLED) display. In some embodiments, the display is a plasma display. In other embodiments, the display is a video projector. In yet other embodiments, the display is a head-mounted display in communication with the digital processing device, such as a VR headset. In further embodiments, suitable VR headsets include, by way of non-limiting examples, HTC Vive, Oculus Rift, Samsung Gear VR, Microsoft HoloLens, Razer OSVR, FOVE VR, Zeiss VR One, Avegant Glyph, Freefly VR headset, and the like. In still further embodiments, the display is a combination of devices such as those disclosed herein.

[0078] In some embodiments, the digital processing device includes an input device to receive information from a user. In some embodiments, the input device is a keyboard. In some embodiments, the input device is a pointing device including, by way of non-limiting examples, a mouse, trackball, track pad, joystick, game controller, or stylus. In some embodiments, the input device is a touch screen or a multi-touch screen. In other embodiments, the input device is a microphone to capture voice or other sound input. In other embodiments, the input device is a video camera or other sensor to capture motion or visual input. In further embodiments, the input device is a Kinect, Leap Motion, or the like. In still further embodiments, the input device is a combination of devices such as those disclosed herein.

[0079] Referring to **Fig. 8**, in a particular embodiment, an exemplary digital processing device **801** is programmed or otherwise configured to detect spoofing of a 3D object, using a 2D representation, in a mobile object authentication process. The digital processing device **801** can regulate various aspects of detecting spoofing of a 3D object of the present disclosure, such as, for example, capturing, via a front-facing camera of a mobile device, image data of the 3D object while displaying, via a front-facing screen of the mobile device, an authentication pattern; using the image data and the authentication pattern to determine a current spatial characteristic of the 3D object; determining if spoofing of the 3D object, using a 2D representation, is attempted in the mobile authentication process by comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object; or transmit image data and authentication pattern to a server. In this embodiment, the digital processing device **801** includes a central processing unit (CPU, also “processor” and “computer processor” herein) **805**, which can be a single core or multi core processor, or a plurality of processors for parallel processing. The digital processing device **801** also includes memory or memory location **810** (e.g., random-access memory, read-only memory, flash memory), electronic storage unit **815**

(e.g., hard disk), communication interface **820** (e.g., network adapter) for communicating with one or more other systems, and peripheral devices **825**, such as cache, other memory, data storage and/or electronic display adapters. The memory **810**, storage unit **815**, interface **820** and peripheral devices **825** are in communication with the CPU **805** through a communication bus (solid lines), such as a motherboard. The storage unit **815** can be a data storage unit (or data repository) for storing data. The digital processing device **801** can be operatively coupled to a computer network (“network”) **830** with the aid of the communication interface **820**. The network **830** can be the Internet, an internet and/or extranet, or an intranet and/or extranet that is in communication with the Internet. The network **830** in some cases is a telecommunication and/or data network. The network **830** can include one or more computer servers, which can enable distributed computing, such as cloud computing. The network **830**, in some cases with the aid of the device **801**, can implement a peer-to-peer network, which may enable devices coupled to the device **801** to behave as a client or a server.

[0080] Continuing to refer to **Fig. 8**, the CPU **805** can execute a sequence of machine-readable instructions, which can be embodied in a program or software. The instructions may be stored in a memory location, such as the memory **810**. The instructions can be directed to the CPU **805**, which can subsequently program or otherwise configure the CPU **805** to implement methods of the present disclosure. Examples of operations performed by the CPU **805** can include fetch, decode, execute, and write back. The CPU **805** can be part of a circuit, such as an integrated circuit. One or more other components of the device **801** can be included in the circuit. In some cases, the circuit is an application specific integrated circuit (ASIC) or a field programmable gate array (FPGA).

[0081] Continuing to refer to **Fig. 8**, the storage unit **815** can store files, such as drivers, libraries and saved programs. The storage unit **815** can store user data, e.g., user preferences and user programs. The digital processing device **801** in some cases can include one or more additional data storage units that are external, such as located on a remote server that is in communication through an intranet or the Internet.

[0082] Continuing to refer to **Fig. 8**, the digital processing device **801** can communicate with one or more remote computer systems through the network **830**. For instance, the device **801** can communicate with a remote computer system of a user. Examples of remote computer systems include personal computers (e.g., portable PC), slate or tablet PCs (e.g., Apple[®] iPad, Samsung[®] Galaxy Tab), telephones, Smart phones (e.g., Apple[®] iPhone, Android-enabled device, Blackberry[®]), or personal digital assistants.

[0083] Methods as described herein can be implemented by way of machine (e.g., computer processor) executable code stored on an electronic storage location of the digital processing

device **801**, such as, for example, on the memory **810** or electronic storage unit **815**. The machine executable or machine readable code can be provided in the form of software. During use, the code can be executed by the processor **805**. In some cases, the code can be retrieved from the storage unit **815** and stored on the memory **810** for ready access by the processor **805**. In some situations, the electronic storage unit **815** can be precluded, and machine-executable instructions are stored on memory **810**.

Non-transitory computer readable storage medium

[0084] In some embodiments, the platforms, systems, media, and methods disclosed herein include one or more non-transitory computer readable storage media encoded with a program including instructions executable by the operating system of an optionally networked digital processing device. In further embodiments, a computer readable storage medium is a tangible component of a digital processing device. In still further embodiments, a computer readable storage medium is optionally removable from a digital processing device. In some embodiments, a computer readable storage medium includes, by way of non-limiting examples, CD-ROMs, DVDs, flash memory devices, solid state memory, magnetic disk drives, magnetic tape drives, optical disk drives, cloud computing systems and services, and the like. In some cases, the program and instructions are permanently, substantially permanently, semi-permanently, or non-transitorily encoded on the media.

Computer program

[0085] In some embodiments, the platforms, systems, media, and methods disclosed herein include at least one computer program, or use of the same. A computer program includes a sequence of instructions, executable in the digital processing device's CPU, written to perform a specified task. Computer readable instructions may be implemented as program modules, such as functions, objects, Application Programming Interfaces (APIs), data structures, and the like, that perform particular tasks or implement particular abstract data types. In light of the disclosure provided herein, those of skill in the art will recognize that a computer program may be written in various versions of various languages.

[0086] The functionality of the computer readable instructions may be combined or distributed as desired in various environments. In some embodiments, a computer program comprises one sequence of instructions. In some embodiments, a computer program comprises a plurality of sequences of instructions. In some embodiments, a computer program is provided from one location. In other embodiments, a computer program is provided from a plurality of locations. In various embodiments, a computer program includes one or more software modules. In various embodiments, a computer program includes, in part or in whole, one or more web applications,

one or more mobile applications, one or more standalone applications, one or more web browser plug-ins, extensions, add-ins, or add-ons, or combinations thereof.

Web application

[0087] In some embodiments, a computer program includes a web application. In light of the disclosure provided herein, those of skill in the art will recognize that a web application, in various embodiments, utilizes one or more software frameworks and one or more database systems. In some embodiments, a web application is created upon a software framework such as Microsoft® .NET or Ruby on Rails (RoR). In some embodiments, a web application utilizes one or more database systems including, by way of non-limiting examples, relational, non-relational, object oriented, associative, and XML database systems. In further embodiments, suitable relational database systems include, by way of non-limiting examples, Microsoft® SQL Server, MySQL™, and Oracle®. Those of skill in the art will also recognize that a web application, in various embodiments, is written in one or more versions of one or more languages. A web application may be written in one or more markup languages, presentation definition languages, client-side scripting languages, server-side coding languages, database query languages, or combinations thereof. In some embodiments, a web application is written to some extent in a markup language such as Hypertext Markup Language (HTML), Extensible Hypertext Markup Language (XHTML), or eXtensible Markup Language (XML). In some embodiments, a web application is written to some extent in a presentation definition language such as Cascading Style Sheets (CSS). In some embodiments, a web application is written to some extent in a client-side scripting language such as Asynchronous JavaScript and XML (AJAX), Flash® ActionScript, JavaScript, or Silverlight®. In some embodiments, a web application is written to some extent in a server-side coding language such as Active Server Pages (ASP), ColdFusion®, Perl, Java™, JavaServer Pages (JSP), Hypertext Preprocessor (PHP), Python™, Ruby, Tcl, Smalltalk, WebDNA®, or Groovy. In some embodiments, a web application is written to some extent in a database query language such as Structured Query Language (SQL). In some embodiments, a web application integrates enterprise server products such as IBM® Lotus Domino®. In some embodiments, a web application includes a media player element. In various further embodiments, a media player element utilizes one or more of many suitable multimedia technologies including, by way of non-limiting examples, Adobe® Flash®, HTML 5, Apple® QuickTime®, Microsoft® Silverlight®, Java™, and Unity®.

[0088] Referring to **Fig. 9**, in a particular embodiment, an application provision system comprises one or more databases **900** accessed by a relational database management system (RDBMS) **910**. Suitable RDBMSs include Firebird, MySQL, PostgreSQL, SQLite, Oracle Database, Microsoft SQL Server, IBM DB2, IBM Informix, SAP Sybase, SAP Sybase,

Teradata, and the like. In this embodiment, the application provision system further comprises one or more application servers **920** (such as Java servers, .NET servers, PHP servers, and the like) and one or more web servers **930** (such as Apache, IIS, GWS and the like). The web server(s) optionally expose one or more web services via application programming interfaces (APIs) **940**. Via a network, such as the Internet, the system provides browser-based and/or mobile native user interfaces.

[0089] Referring to **Fig. 10**, in a particular embodiment, an application provision system alternatively has a distributed, cloud-based architecture **1000** and comprises elastically load balanced, auto-scaling web server resources **1010** and application server resources **1020** as well as synchronously replicated databases **1030**.

Mobile application

[0090] In some embodiments, a computer program includes a mobile application provided to a mobile digital processing device. In some embodiments, the mobile application is provided to a mobile digital processing device at the time it is manufactured. In other embodiments, the mobile application is provided to a mobile digital processing device via the computer network described herein.

[0091] In view of the disclosure provided herein, a mobile application is created by techniques known to those of skill in the art using hardware, languages, and development environments known to the art. Those of skill in the art will recognize that mobile applications are written in several languages. Suitable programming languages include, by way of non-limiting examples, C, C++, C#, Objective-C, Java™, Javascript, Pascal, Object Pascal, Python™, Ruby, VB.NET, WML, and XHTML/HTML with or without CSS, or combinations thereof.

[0092] Suitable mobile application development environments are available from several sources. Commercially available development environments include, by way of non-limiting examples, AirplaySDK, alcheMo, Appcelerator®, Celsius, Bedrock, Flash Lite, .NET Compact Framework, Rhomobile, and WorkLight Mobile Platform. Other development environments are available without cost including, by way of non-limiting examples, Lazarus, MobiFlex, MoSync, and Phonegap. Also, mobile device manufacturers distribute software developer kits including, by way of non-limiting examples, iPhone and iPad (iOS) SDK, Android™ SDK, BlackBerry® SDK, BREW SDK, Palm® OS SDK, Symbian SDK, webOS SDK, and Windows® Mobile SDK.

[0093] Those of skill in the art will recognize that several commercial forums are available for distribution of mobile applications including, by way of non-limiting examples, Apple® App Store, Google® Play, Chrome WebStore, BlackBerry® App World, App Store for Palm devices,

App Catalog for webOS, Windows[®] Marketplace for Mobile, Ovi Store for Nokia[®] devices, Samsung[®] Apps, and Nintendo[®] DSi Shop.

Software modules

[0094] In some embodiments, the platforms, systems, media, and methods disclosed herein include software, server, and/or database modules, or use of the same. In view of the disclosure provided herein, software modules are created by techniques known to those of skill in the art using machines, software, and languages known to the art. The software modules disclosed herein are implemented in a multitude of ways. In various embodiments, a software module comprises a file, a section of code, a programming object, a programming structure, or combinations thereof. In further various embodiments, a software module comprises a plurality of files, a plurality of sections of code, a plurality of programming objects, a plurality of programming structures, or combinations thereof. In various embodiments, the one or more software modules comprise, by way of non-limiting examples, a web application, a mobile application, and a standalone application. In some embodiments, software modules are in one computer program or application. In other embodiments, software modules are in more than one computer program or application. In some embodiments, software modules are hosted on one machine. In other embodiments, software modules are hosted on more than one machine. In further embodiments, software modules are hosted on cloud computing platforms. In some embodiments, software modules are hosted on one or more machines in one location. In other embodiments, software modules are hosted on one or more machines in more than one location.

Databases

[0095] In some embodiments, the platforms, systems, media, and methods disclosed herein include one or more databases, or use of the same. In view of the disclosure provided herein, those of skill in the art will recognize that many databases are suitable for storage and retrieval of spatial characteristics of a 3D object. In various embodiments, suitable databases include, by way of non-limiting examples, relational databases, non-relational databases, object oriented databases, object databases, entity-relationship model databases, associative databases, and XML databases. Further non-limiting examples include SQL, PostgreSQL, MySQL, Oracle, DB2, and Sybase. In some embodiments, a database is internet-based. In further embodiments, a database is web-based. In still further embodiments, a database is cloud computing-based. In other embodiments, a database is based on one or more local computer storage devices.

EXAMPLES

[0096] The following illustrative examples are representative of embodiments of the software applications, systems, and methods described herein and are not meant to be limiting in any

way.

Example 1 – Authentication of a User

[0097] A user attempts to access a banking application on their mobile device. To grant access to the banking account of the user, the application prompts the user to position their mobile device such that the screen of the mobile device points towards their face.

[0098] The application then captures a first image data of the user, via the front-facing camera, while simultaneously displaying a first an authentication pattern image on the screen of the mobile device comprising a high brightness region and a low brightness region, that are arranged in two vertical bands. The application then captures a second image data of the user, via the front-facing camera, while simultaneously displaying a second authentication pattern image on the screen of the mobile device comprising a high brightness region and a low brightness region that are arranged in two horizontal bands. The application then captures a third image data of the user, via the front-facing camera, while simultaneously displaying a third authentication pattern image on the screen of the mobile device comprising two high brightness regions and two low brightness regions that are arranged in four alternating vertical bands. The application then captures a fourth image data of the user, via the front-facing camera, while simultaneously displaying a fourth authentication pattern image on the screen of the mobile device comprising two high brightness regions and two low brightness regions that are arranged in four alternating horizontal bands. The application then captures a fifth image data of the user, via the front-facing camera, while simultaneously displaying a fifth authentication pattern image on the screen of the mobile device comprising a plurality of high brightness regions and a plurality of low brightness regions that are arranged in alternating horizontal bands. The application then captures a sixth image data of the user, via the front-facing camera, while simultaneously displaying a sixth authentication pattern image on the screen of the mobile device comprising a plurality of high brightness regions and a plurality of low brightness regions that are arranged in alternating vertical bands. The application then captures a seventh image data of the user, via the front-facing camera, while simultaneously displaying a seventh authentication pattern image on the screen of the mobile device comprising two horizontal bands of high brightness regions across the top and bottom of the screen, and a single horizontal band of a low brightness region across the middle of the screen. The application then captures an eighth image data of the user, via the front-facing camera, while simultaneously displaying an eighth authentication pattern image on the screen of the mobile device comprising vertical bands of high brightness regions along the left and right sides of the screen, and a single vertical band of a low brightness region along the middle of the screen. The application then captures a ninth image data of the user, via the front-facing camera, while simultaneously displaying a ninth authentication pattern image on

the screen of the mobile device comprising a plurality of randomly shaped and positioned, high brightness regions and low brightness regions. The application then further captures additional image data of the user, via the front-facing camera, while simultaneously displaying a video authentication pattern on the screen of the mobile device comprising a circular high brightness region moving clockwise in an elliptical pattern, with a background comprising a low brightness region.

[0099] Once the mobile device determines a current spatial characteristic of the user from the image data and the authentication patterns, the mobile device grants the user access to the banking account if no spoofing is detected, or blocks access to the banking account if spoofing is detected. The mobile device may transmit information related to the time, location, device, account, or any combination thereof, associated with the spoofing attempt, to an appropriate notification channel and/or database for further processing.

Example 2 – Encoded Authentication Pattern

[0100] A user attempts to access a stock trading application on their mobile device. To grant access to the stock trading account of the user, the application prompts the user to position their mobile device such that the screen of the mobile device points towards their face. The application then captures image data of the user, via the front-facing camera, while simultaneously displaying a authentication pattern on the screen of the mobile device, wherein the authentication pattern comprises a plurality of images, wherein each image comprises a plurality of regions, wherein at least one of the regions varies in at least one of: brightness, position, size, shape, and color over time causing a variance of lighting effects which create highlights and shadows on the user over time, and wherein one image in the authentication pattern comprises an encoding image.

[0101] The encoding image comprises a region of bright red pixels on the left half of the screen of the mobile device, and a region of bright green pixels on the right half of the screen of the mobile device, which is unique to the user, the user's account, the time of the authentication attempt, the day of the authentication attempt, and the location of the user during the authentication attempt. The mobile device grants the user access to the stock trading account if red and green highlights and shadows on the user, captured by the 2D representation, correlate with the encoding image, or blocks access to the stock trading account if the 2D representation does not display red and green highlights and shadows on the user correlating with the encoding image. The mobile device then alerts an authority with information related to the time, location, device, account, or any combination thereof, associated with the attempted access.

CLAIMS

WHAT IS CLAIMED IS:

1. A mobile device comprising: a front-facing camera, a front-facing screen, at least one processor, a memory, an operating system configured to perform executable instructions, and a computer program including instructions executable by the at least one processor to run an application for detecting spoofing of a 3D object, using a 2D representation of the 3D object, in a mobile object authentication process, the application comprising:
 - a) a software module capturing, via the front-facing camera,
 - i) a first image data of the 3D object while displaying, via the front-facing screen, a first authentication pattern, the first authentication pattern comprising a plurality of first authentication pattern regions, wherein at least one of the first authentication pattern regions varies from another first authentication pattern region in at least one of: brightness, position, size, shape, and color over time causing a first variance of lighting effects, wherein the first image data comprises a first set of highlights and shadows on the 3D object over time, and
 - ii) a second image data of the 3D object while displaying, via the front-facing screen, the second authentication pattern after displaying the first authentication pattern, wherein the second authentication pattern is different from the first authentication pattern, the second authentication pattern comprising a plurality of second authentication pattern regions, wherein at least one of the second authentication pattern regions varies from another second authentication pattern regions in at least one of brightness, position, size, shape, and color causing a second variance of lighting effects, wherein the second image data comprises a second set of highlights and shadows on the 3D object over time;
 - b) a software module calculating a difference between the first set of highlights and shadows and the second set of highlights and shadows to determine a current spatial characteristic of the 3D object; and
 - c) a software module determining if spoofing of the 3D object, using the 2D representation, is attempted in the mobile authentication process by comparing

the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object.

2. The device of claim 1, wherein the 3D object comprises a face, a palm (palm print), a finger (fingerprint), or an ear.
3. The device of claim 1, wherein the 2D representation comprises a photograph of the 3D object.
4. The device of claim 1, wherein at least one of the first image data and the second image data comprises a plurality of photographs of the 3D object, a video of the 3D object, or both.
5. The device of claim 1, wherein at least one of the first authentication pattern and the second authentication pattern comprises a plurality of images, a video, or both.
6. The device of claim 1, wherein the at least one of the plurality of the first authentication pattern regions and the plurality of the second authentication pattern regions are arranged in two or more vertical or horizontal bands.

7. The device of claim 1, wherein the variation within at least one of the first authentication pattern regions and the second authentication pattern regions forms a regular pulse or a random pulse in the first or second authentication pattern.
8. The device of claim 1, wherein the variation within at least one of the first authentication pattern regions and the second authentication pattern regions forms a translation or rotation of the first authentication pattern region or the second authentication pattern region in the first authentication pattern or the second authentication pattern, forms a contraction or expansion of the first authentication pattern region or the second authentication pattern region in the first authentication pattern or the second authentication pattern, or both.
9. The device of claim 1, wherein the application further comprises a software module receiving a request to authenticate the 3D object, and a software module instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the first image data, the second image data, or both.
10. The device of claim 1, wherein the variation within at least one of the first authentication pattern regions and the second authentication pattern regions encodes information in the first or second authentication pattern.
11. A system for detecting spoofing of a 3D object, using a 2D representation of the 3D object, in a mobile object authentication process, the system comprising: a mobile device comprising a front-facing camera, a front-facing screen, at least one processor, a memory; and a server comprising at least one processor and a memory:
the mobile device configured to:
 - a) capture, via the front-facing camera,
 - i) a first image data of the 3D object while displaying, via the front-facing screen, first authentication pattern comprising a plurality of first authentication pattern regions, wherein at least one of the first authentication pattern regions varies from another first authentication pattern region in at least one of: brightness, position, size, shape, and color over time causing a first variance of lighting effects, wherein the first image data comprises a first set of highlights and shadows on the 3D object over time;
 - ii) a second image data of the 3D object while displaying, via the front-facing screen, the second authentication pattern after displaying the first

authentication pattern, wherein the second authentication pattern is different from the first authentication pattern, the second authentication pattern comprising a plurality of second authentication pattern regions, wherein at least one of the second authentication pattern regions varies from another second authentication pattern regions in at least one of brightness, position, size, shape, and color causing a second variance of lighting effects, wherein the second image data comprises a second set of highlights and shadows on the 3D object over time; and

b) transmit the first image data and the second image data to the server;

the server configured to:

- a) receive the first image data and the second image data from the mobile device;
 - b) calculate a difference between the first set of highlights and shadows and the second set of highlights and shadows to determine a current spatial characteristic of the 3D object;
 - c) determine if spoofing of the 3D object, using a 2D representation of the 3D object, is attempted in the mobile authentication process by comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object; and
 - d) transmit a spoofing result to the mobile device.
12. The system of claim 11, wherein the 3D object comprises a face, a palm (palm print), a finger (fingerprint), or an ear.
13. The system of claim 11, wherein the 2D representation comprises a photograph of the 3D object.
14. The system of claim 11, wherein at least one of the first image data and the second image data comprises a plurality of photographs of the 3D object, a video of the 3D object, or both.
15. The system of claim 11, wherein at least one of the first authentication pattern and the second authentication pattern comprises a plurality of images, a video, or both.
16. The system of claim 11, wherein at least one of the plurality of first authentication pattern regions and second authentication pattern regions are arranged in two or more vertical or horizontal bands.
17. The system of claim 11, wherein the variation within at least one of the first authentication pattern regions and the second authentication pattern regions forms a regular pulse or a random pulse in the first or second authentication pattern.
18. The system of claim 11, wherein the variation within at least one of the first authentication pattern regions and the second authentication pattern regions forms a translation or rotation of the first authentication pattern region or the second authentication pattern region in the first authentication pattern or the second authentication pattern, forms a contraction or expansion of the first authentication pattern region or the second authentication pattern region in the first authentication pattern or the second authentication pattern, or both.

19. The system of claim 11, wherein the application further comprises a software module receiving a request to authenticate the 3D object, and a software module instructing a user to orient the front-facing camera of the mobile device in a fixed position relative to the object during the capturing of the first image data, the second image data, or both.
20. The system of claim 11, wherein the variation within at least one of the first authentication pattern regions and the second authentication pattern regions encodes information in the first or second authentication pattern.
21. A method of detecting spoofing of a 3D object, using a 2D representation of the 3D object, in a mobile object authentication process, the method comprising:
 - a) capturing, via a front-facing camera of a mobile device,
 - i) a first image data of the 3D object while displaying, via a front-facing screen of the mobile device, a first authentication pattern, the first authentication pattern comprising a plurality of first authentication pattern regions, wherein at least one of the first authentication pattern regions varies from another first authentication pattern region in at least one of: brightness, position, size, shape, and color over time causing a first variance of lighting effects, wherein the first image data comprises a first set of highlights and shadows on the 3D object over time, and
 - ii) a second image data of the 3D object while displaying, via the front-facing screen, the second authentication pattern after displaying the first authentication pattern, wherein the second authentication pattern is different from the first authentication pattern, the second authentication pattern comprising a plurality of second authentication pattern regions, wherein at least one of the second authentication pattern regions varies from another second authentication pattern regions in at least one of brightness, position, size, shape, and color causing a second variance of lighting effects, wherein the second image data comprises a second set of highlights and shadows on the 3D object over time;

- b) calculating a difference between the first set of highlights and shadows and the second set of highlights and shadows to determine a current spatial characteristic of the 3D object; and
- c) determining if spoofing of the 3D object, using the 2D representation, is attempted in the mobile authentication process by comparing the current spatial characteristic of the 3D object with a stored reference spatial characteristic of the 3D object.