

Description

The present invention relates to a process for removing iodine or iodide impurities from the products of carbonylation processes. In particular the present invention relates to the removal of iodine or iodide impurities from carboxylic acid or carboxylic acid anhydrides prepared by the rhodium catalysed carbonylation of alcohols, olefins or esters.

The use of rhodium/iodide catalysts to effect the carbonylation of alcohols (eg methanol to acetic acid), olefins (eg ethylene to propionic acid) and esters (eg methyl acetate to acetic anhydride) is well known. It is also known that the carboxylic acid or carboxylic acid anhydride products tend to retain iodide, in the forms of iodine or soluble iodides, which must be subsequently removed.

A number of methods have been developed to effect iodide removal and some are operated commercially on plant using carbonylation technology. US 4029553 describes a distillation process for generating high purity acetic acid containing less than 20 parts per billion iodide. A different approach is described in US 3772156 which discloses a two column distillation process in which the crude acetic acid is contacted with an alkali or alkaline earth metal compound either alone or in combination with hypophosphorus acid. Finally US 3709795 discloses a process for removing halide impurities from acetic acid which involves the use of a strong inorganic oxidising agent such as potassium permanganate. Whilst effective, this latter process is not easy to carry out commercially.

Other approaches of interest include the use of a silver ion-exchange resin (EP 196173) and the use of a peracid (DE 3612504)

US 4664753 discloses a particularly effective method of removing iodine and soluble iodide impurities from the products of carbonylation processes. This patent describes contacting the product with a mixture of (a) an alkyl or aryl phosphine or a heterocyclic aromatic nitrogen compound and (b) a metal selected from copper, silver, zinc or cadmium.

A problem arises with the approach described in US 4664753 in that when such a two component system is employed there is a possibility of contaminating the carbonylation product with the first of the above mentioned components. Hence the problem to be solved is the prevention of such contamination whilst maintaining an efficient scavenging system.

Accordingly, the present invention provides a process for removing iodine or soluble iodide impurities from a carboxylic acid or carboxylic acid anhydride, the carboxylic acid or carboxylic acid anhydride having been produced by a carbonylation process, which process comprises step (a) treating impure carboxylic acid or carboxylic acid anhydride containing iodine or soluble iodide impurities with an unsupported scavenger at a temperature of between 20 and 250°C and step (b) thereafter separating the treated carboxylic acid or carboxylic acid anhydride from the scavenger characterised in that the scavenger consists of a silver salt in the absence of a trialkyl phosphine, a triaryl phosphine and a heterocyclic aromatic nitrogen compound.

The invention solves the problem by selecting from US 4664753 a metal (silver) which is more effective without a phosphine or heterocyclic aromatic nitrogen compound. This is unexpected because US 4664753 suggests (see Examples 1 and 3) that a phosphine is needed in order to obtain a product of high purity.

The silver salt can be any one which will react with iodide to generate insoluble silver iodide. Preferably, the salt should be soluble in the carboxylic acid or carboxylic acid anhydride. It is most preferred, if possible to use a silver salt having an anion corresponding to the carboxylic acid being treated. Thus for acetic acid, silver acetate is most preferred whilst for propionic acid silver propionate should be used.

It is also possible to use suspensions of silver salts if the silver salt is insoluble or sparingly soluble in the liquid medium being purified. In these cases, it is preferred that the suspension is finely divided.

The process of the present invention, is particularly suitable for treating carboxylic acids or carboxylic acid anhydrides having up to 300 ppm iodine or soluble iodide impurities. The silver is recovered from the process as silver iodide which can either be disposed of or treated to regenerate the appropriate silver salt.

The scavenger and the carboxylic acid or carboxylic acid anhydride are kept in contact until substantially all the iodine or iodide is scavenged. For a process operating under a preferred temperature in the range 80 to 150°C, a suitable contact time is one in the range 10 to 100 minutes. The mixture may be stirred or otherwise agitated if desired. Typically the process of the present invention is able to reduce the level of iodine or soluble iodide impurities to levels in the order of less than 100 parts per billion, preferably to less than 20 parts per billion.

The process of the present invention is particularly suitable for use in purifying (a) acetic acid produced by rhodium/iodide catalysed methanol carbonylation, (b) propionic acid produced by rhodium/iodide catalysed ethylene carbonylation and (c) acetic anhydride produced by rhodium/iodide catalysed car-

bonylation of methyl acetate. However, the process is equally applicable to kettles for processes using carboxylic acids and carboxylic acid anhydride feedstocks in conjunction with iodide sensitive catalysts (e.g. vinyl acetate monomer production).

The invention will now be illustrated by reference to the following Examples.

Batch Reactions - General Method

A 500 ml three necked round bottomed flask was equipped with a Eurotherm controlled heating mantle, a thermo-couple pocket, two wide bore taps - one connected to a Liebig condenser and the other to a stillhead condenser and receiver. The flask was charged with 450 ml of the impure acetic acid (iodide level as determined by neutron activation analysis), the prerequisite amount of scavenger and a few antibumping granules. Both the condenser and the distillation apparatus were purged with nitrogen.

With the tap open to the condenser only, the apparatus was brought to a gentle reflux (simmer). After 1 hour the second tap was opened and the first closed. The reflux was increased to rapid distillation of the treated acetic acid. The experiment was terminated when 90% of the acetic acid had been collected. The distilled acetic acid was analysed for total iodide content (by neutron activation analysis).

Examples 1 and A to C

Compare a silver acetate salt with copper (II) acetate and two scavenger systems according to US 4664753. Examples A to C do not constitute part of the invention. The results (Table 1) show the unexpected superiority of silver acetate in the absence of a phosphine.

TABLE 1

Example	Scavenger	% w/w Scavenger	Initial iodide (ppb)	Final iodide (ppb)	% Removal
1	Silver Acetate	0.03	991	50 ± 2	95
A	Silver Acetate + Triphenylphosphine	0.03 of each	662	653 ± 40	0
B	Copper (II) Acetate	0.03	991	850 ± 100	0
C	Copper (II) Acetate + Triphenylphosphine	0.03 of each	1380	800 ± 47	42

Claims

1. A process for removing iodine or soluble iodide impurities from a carboxylic acid or carboxylic acid anhydride, the carboxylic acid or carboxylic acid anhydride having been produced by a carbonylation process, which process comprises step (a) treating impure carboxylic acid or carboxylic acid anhydride containing iodine or soluble iodide impurities with an unsupported scavenger at a temperature of between 20 and 250° and (b) thereafter separating the treated carboxylic acid or carboxylic acid anhydride from the scavenger characterized in that the scavenger consists of a silver salt in the absence of a trialkyl phosphine, a triaryl phosphine and a heterocyclic aromatic nitrogen compound.
2. A process as claimed in claim 1 wherein the silver salt has an anion corresponding to the carboxylic acid or carboxylic acid anhydride.
3. A process as claimed in claim 1 wherein the silver salt is silver acetate.
4. A process as claimed in any one of claims 1 to 3 wherein the impure carboxylic acid or carboxylic acid anhydride contains up to 300 parts per million by weight in total of iodine and soluble iodide impurities.
5. A process as claimed in claim 4 wherein the treated carboxylic acid or carboxylic acid anhydride contains less than 100 parts per billion by weight in total of iodine and soluble iodide impurities.
6. A process as claimed in any one of claims 1 to 5 wherein the carboxylic acid or carboxylic acid anhydride is chosen from the group consisting of acetic acid, propionic acid and acetic anhydride.



bonylation of methyl acetate. However, the process is equally applicable to kettles for processes using carboxylic acids and carboxylic acid anhydride feedstocks in conjunction with iodide sensitive catalysts (e.g. vinyl acetate monomer production).

The invention will now be illustrated by reference to the following Examples.

Batch Reactions - General Method

A 500 ml three necked round bottomed flask was equipped with a Eurotherm controlled heating mantle, a thermo-couple pocket, two wide bore taps - one connected to a Liebig condenser and the other to a stillhead condenser and receiver. The flask was charged with 450 ml of the impure acetic acid (iodide level as determined by neutron activation analysis), the prerequisite amount of scavenger and a few antibumping granules. Both the condenser and the distillation apparatus were purged with nitrogen.

With the tap open to the condenser only, the apparatus was brought to a gentle reflux (simmer). After 1 hour the second tap was opened and the first closed. The reflux was increased to rapid distillation of the treated acetic acid. The experiment was terminated when 90% of the acetic acid had been collected. The distilled acetic acid was analysed for total iodide content (by neutron activation analysis).

Examples 1 and A to C

Compare a silver acetate salt with copper (II) acetate and two scavenger systems according to US 4664753. Examples A to C do not constitute part of the invention. The results (Table 1) show the unexpected superiority of silver acetate in the absence of a phosphine.

TABLE 1

Example	Scavenger	% w/w Scavenger	Initial Iodide (ppb)	Final Iodide (ppb)	% Removal
1	Silver Acetate	0.03	991	50 ± 2	95
A	Silver Acetate + Triphenylphosphine	0.03 of each	662	653 ± 40	0
B	Copper (II) Acetate	0.03	991	850 ± 100	0
C	Copper (II) Acetate + Triphenylphosphine	0.03 of each	1380	800 ± 47	42

Claims

1. A process for removing iodine or soluble iodide impurities from a carboxylic acid or carboxylic acid anhydride, the carboxylic acid or carboxylic acid anhydride having been produced by a carbonylation process, which process comprises step (a) treating impure carboxylic acid or carboxylic acid anhydride containing iodine or soluble iodide impurities with an unsupported scavenger at a temperature of between 20 and 250° and (b) thereafter separating the treated carboxylic acid or carboxylic acid anhydride from the scavenger characterized in that the scavenger consists of a silver salt in the absence of a trialkyl phosphine, a triaryl phosphine and a heterocyclic aromatic nitrogen compound.
2. A process as claimed in claim 1 wherein the silver salt has an anion corresponding to the carboxylic acid or carboxylic acid anhydride.
3. A process as claimed in claim 1 wherein the silver salt is silver acetate.
4. A process as claimed in any one of claims 1 to 3 wherein the impure carboxylic acid or carboxylic acid anhydride contains up to 300 parts per million by weight in total of iodine and soluble iodide impurities.
5. A process as claimed in claim 4 wherein the treated carboxylic acid or carboxylic acid anhydride contains less than 100 parts per billion by weight in total of iodine and soluble iodide impurities.
6. A process as claimed in any one of claims 1 to 5 wherein the carboxylic acid or carboxylic acid anhydride is chosen from the group consisting of acetic acid, propionic acid and acetic anhydride.



7. A process as claimed in claim 1 wherein the step (a) is carried out at a temperature in the range 80 - 150 °C.
8. A process as claimed in claim 1 wherein the impure carboxylic acid or carboxylic acid anhydride is treated with an unsupported scavenger for a period of time in the range from 10 to 100 minutes.

Patentansprüche

1. Verfahren zur Entfernung von Iod oder löslichen Iodidverunreinigungen aus einer Carbonsäure oder einem Carbonsäureanhydrid, wobei die Carbonsäure oder das Carbonsäureanhydrid durch ein Carbonylierungsverfahren hergestellt worden sind, welches Verfahren die Stufen (a) des Behandeln von Iod oder lösliche Iodidverunreinigungen enthaltender unreiner Carbonsäure oder Carbonsäureanhydrid mit einem trägerlosen Reiniger bei einer Temperatur von zwischen 20° und 250° C und (b) des anschließenden Abtrennens der behandelten Carbonsäure oder des Carbonsäureanhydrids von dem Reiniger umfaßt, **dadurch gekennzeichnet**, daß der Reiniger aus einem Silbersalz in Abwesenheit eines Trialkylphosphins, eines Triarylphosphins und einer heterocyclischen aromatischen Stickstoff-Verbindung, besteht.
2. Verfahren nach Anspruch 1, **dadurch gekennzeichnet**, daß das Silbersalz ein Anion, entsprechend der Carbonsäure oder des Carbonsäureanhydrids, enthält.
3. Verfahren nach Anspruch 1, **dadurch gekennzeichnet**, daß das Silbersalz Silberacetat ist.
4. Verfahren nach einem der Ansprüche 1 bis 3, **dadurch gekennzeichnet**, daß die unreine Carbonsäure oder das Carbonsäureanhydrid bis zu 300 Gewichtsteile pro Million insgesamt an Iod und löslichen Iodidverunreinigungen enthält.
5. Verfahren nach Anspruch 4, **dadurch gekennzeichnet**, daß die behandelte Carbonsäure oder das Carbonsäureanhydrid weniger als 100 Gewichtsteile pro Billion insgesamt an Iod oder löslichen Iodidverunreinigungen enthält.
6. Verfahren nach einem der Ansprüche 1 bis 5, **dadurch gekennzeichnet**, daß die Carbonsäure oder das Carbonsäureanhydrid aus der Gruppe bestehend aus Essigsäure, Propionsäure und Essigsäureanhydrid ausgewählt sind.
7. Verfahren nach Anspruch 1, **dadurch gekennzeichnet**, daß die Stufe (a) bei einer Temperatur im Bereich von 80° bis 150 °C durchgeführt wird.
8. Verfahren nach Anspruch 1, **dadurch gekennzeichnet**, daß die unreine Carbonsäure oder das Carbonsäureanhydrid mit einem trägerlosen Reiniger während eines Zeitraums im Bereich von 10 bis 100 Minuten behandelt wird.

Revendications

1. Procédé pour éliminer l'iode ou des impuretés formées d'iodures solubles, d'un acide carboxylique ou d'un anhydride d'acide carboxylique, l'acide carboxylique ou l'anhydride d'acide carboxylique ayant été produit par un procédé de carbonylation, le procédé de l'invention comprenant une étape (a) qui consiste à traiter l'acide carboxylique ou l'anhydride d'acide carboxylique contenant de l'iode ou des impuretés formées d'iodures solubles avec un épurateur non fixé sur un support à une température comprise entre 20 et 250 °C, puis une étape (b) qui consiste à séparer de l'épurateur l'acide carboxylique ou l'anhydride d'acide carboxylique traité, caractérisé en ce que l'épurateur est constitué d'un sel d'argent en l'absence d'une trialkyl-phosphine, d'une triaryl-phosphine et d'un composé azoté aromatique hétérocyclique.
2. Procédé suivant la revendication 1, dans lequel le sel d'argent porte un anion correspondant à l'acide carboxylique ou à l'anhydride d'acide carboxylique.
3. Procédé suivant la revendication 1, dans lequel le sel d'argent est l'acétate d'argent.



4. Procédé suivant lequel l'une quelconque des revendications 1 à 3, dans lequel l'acide carboxylique ou l'anhydride d'acide carboxylique pur contient jusqu'à 300 parties par million en poids, au total, d'iode et d'impuretés formées d'iodures solubles.
5. Procédé suivant la revendication 4, dans lequel l'acide carboxylique ou l'anhydride d'acide carboxylique contient moins de 100 parties par billion en poids, au total, d'iode et d'impuretés formées d'iodures solubles.
6. Procédé suivant l'une quelconque des revendications 1 à 5, dans lequel l'acide carboxylique ou l'anhydride d'acide carboxylique est choisi dans le groupe comprenant l'acide acétique, l'acide propionique et l'anhydride acétique.
7. Procédé suivant la revendication 1, dans lequel l'étape (a) est conduite à une température comprise dans la plage de 80 à 150 ° C.
8. Procédé suivant la revendication 1, dans lequel l'acide carboxylique ou l'anhydride d'acide carboxylique impur est traité avec un épurateur non fixé sur un support pendant une période comprise dans la plage de 10 à 100 minutes.