



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/32, 7/22		A1	(11) International Publication Number: WO 99/48314
			(43) International Publication Date: 23 September 1999 (23.09.99)
(21) International Application Number: PCT/FI99/00205		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 17 March 1999 (17.03.99)			
(30) Priority Data: 980588 17 March 1998 (17.03.98) FI			
(71) Applicant (for all designated States except US): NOKIA TELECOMMUNICATIONS OY [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).			
(72) Inventor; and			
(75) Inventor/Applicant (for US only): WALLENIUS, Jukka [FI/FI]; Keinutie 8 G 41, FIN-00940 Helsinki (FI).			
(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).		<p>Published</p> <p><i>With international search report.</i></p> <p><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p> <p><i>In English translation (filed in Finnish).</i></p>	

(54) Title: CONFIGURATION OF INTELLIGENT NETWORK SERVICE

(57) Abstract

A method of configuring an intelligent network service over a user interface of a mobile station. The mobile station (MS) comprises an extension layer (MEXE) to support routines to be installed. The mobile station is loaded (4-2) with a configuration routine of the intelligent network service in question. The extension layer (MEXE) receives an input (4-3a) through the configuration routine in order to configure the intelligent network service. On the basis of the input, the mobile station (MS) transmits configuration information to a mobile services switching centre (MSC) in a configuration message (4-3d). The mobile services switching centre (MSC) recognizes the configuration message (4-3d) and transmits at least the essential part thereof to a service control point (SCP). The service control point (SCP) interprets the configuration information included in the configuration message (4-3d) and configures the intelligent network service.

