

DESCRIPTION

PASSENGER INFORMATION CONTROL DEVICE AND METHOD FOR
PROVIDING VIDEO DATA FOR PASSANGER INFORMATION CONTROL
5 DEVICE

TECHNICAL FIELD

[0001] The present invention relates to an passenger
information control device that provides advertisement
10 information to passengers in a train.

BACKGROUND ART

[0002] Along with increasing diversities in lifestyles
and activity patterns of people today, advertisement videos
provided by mass media and the like have significant
15 influence on such people with diversities. The increased
availability of the Internet in recent years also makes
people demand for new information, and advertisement
pictures or videos posted or displayed in trains, for
example, are expected to have high advertising effects.
20 Particularly due to the fact that an in-train space is
confined and activities of passengers are limited,
advertisement videos are considered to be highly effective
as means for advertisement. Accordingly, the demand for
such advertisement is rapidly growing.

25 [0003] Further, with the emergence of high definition
videos and display devices with larger-sized screens, video
data for some advertisements is now as large as 50
megabytes. Accordingly, it is desired that a storage
medium for use in a train is capable of storing a large
30 amount of video data for a long period of time. However,
conditions specific to trains require a storage medium that
is very expensive per unit capacity, for example, a
semiconductor disk that is resistant to heat and vibration.

Thus, it poses large limitations on recording of video data. Therefore, there have been taken some measures such as deleting unnecessary video data to efficiently use the storage capacity of a storage medium.

5 [0004] Conventionally, information providing devices disclosed in, for example, Patent Documents 1 and 2, secure a free space in a storage medium by deleting video data in chronological order, i.e., from one recorded on the storage medium at an earlier time and whose validity period has
10 expired.

[0005] Patent Document 1: Japanese Patent Application Laid-open No. 2002-314910

Patent Document 2: Japanese Patent Application Laid-open No. 2003-110982

15 DISCLOSURE OF INVENTION

PROBLEM TO BE SOLVED BY THE INVENTION

[0006] Video data for advertisement videos to be presented in a train is transmitted from a ground transmission controller when the train stops at a station
20 and then stored in a storage medium carried in the train. Although such video data includes a large quantity of video data that is to be presented again, conventional devices adopt an approach of deleting video data upon expiration of validity period to secure a free space in the storage
25 medium. It may appear that once deleted video data can be retransmitted when the train stops at a station. However, because video data has a tendency to have a larger volume as mentioned above, the boarding and alighting time is sometimes not sufficient enough to transmit video data.
30 That is, there is a problem in that the storage capacity of a storage medium cannot be efficiently used with the approach of deleting video data whose validity period has

expired, because this approach is not able to delete only video data that is really unnecessary.

[0007] The present invention has been achieved in view of the above problem, and an object of the present
5 invention is to provide an passenger information control device that is capable of effectively using the storage capacity of a storage medium.

MEANS FOR SOLVING PROBLEM

[0008] To solve the above problem and achieve the object,
10 a passenger information control device according to the present invention has a video display controller that transmits, to a display device in a train, video data for an in-train advertisement, which is transmitted from a ground transmission controller to an onboard transmission
15 controller, the passenger information control device includes: a storage unit that stores a program table and the video data, the program table storing at least one of number of times an advertisement video has been presented, a validity period of the advertisement video, a time period
20 from a last presentation time to present time, and a volume of the video data, being associated with each advertisement; a deletion determining unit that receives the program table via the video display controller and determines whether to designate the video data as a
25 candidate for deletion based on the program table; and a deleting unit that deletes the video data stored in the storage unit based on determination by the deletion determining unit.

EFFECT OF THE INVENTION

30 [0009] Because the passenger information control device according to the present invention determines the number of times an advertisement video has been presented, the validity period, the time period from the last presentation

time to the present time, or the volume of the video data, the passenger information control device can effectively use the storage capacity of a recording medium.

BRIEF DESCRIPTION OF DRAWINGS

5 [0010] Fig. 1 depicts an exemplar configuration of a passenger information control device according to a first embodiment and devices connected to the passenger information control device.

Fig. 2 depicts an exemplar configuration of a ground
10 transmission controller and devices connected to the ground transmission controller.

Fig. 3 depicts a block diagram of an example of a configuration of the passenger information control device.

Fig. 4 depicts an example of a program table.

15 Fig. 5 depicts an example of a presentation count table.

Fig. 6 depicts an exemplar flowchart of a flow of determining video data that is a candidate for deletion.

Fig. 7 depicts an exemplar flowchart of a flow of
20 determining presentation on display devices.

Fig. 8 depicts an exemplar flowchart of a flow of determining how much space is available in a storage unit on the ground transmission controller.

Fig. 9 depicts an exemplar flowchart of a flow of
25 determining deletion of video data.

Fig. 10 depicts an exemplar flowchart of a flow of determining deletion of video data on a passenger information control device according to a second embodiment.

Fig. 11 depicts an exemplar flowchart of a flow of
30 determining deletion of video data on a passenger information control device according to a third embodiment.

Fig. 12 depicts an exemplar flowchart of a flow of determining deletion of video data on the ground

transmission controller side.

EXPLANATIONS OF LETTERS OR NUMERALS

	[0011]	1	Display device
		2	Passenger information control device
5		3	Onboard transmission controller
		4	Train control device
		5	Information processing device
		6	Ground transmission controller
		7	Terminal
10		8	Storage unit
		9	Number of presentation
		10	Timer
		11	Deletion determining unit
		12	Deleting unit
15		13	Video display controller
		14	Program-table storing unit
		15	Presentation count database
		16	Video-data storing unit
		17	Time
20		40a, 40b, 40c, 40d	Program table
		41	Validity period (start)
		42	Validity period (expire)
		43	Last presentation time
		44	Video data name
25		45	File volume
		46	Deletion-candidate-flag storage portion
		50	Presentation count table
		51	Video data name
		52	Presentation-count display portion
30		60a, 60b, 60c	Video data

BEST MODE(S) FOR CARRYING OUT THE INVENTION

[0012] Exemplary embodiments of a passenger information control device according to the present invention will be

explained below in detail with reference to the accompanying drawings. The present invention is not limited to the embodiments.

[0013] First embodiment

5 Fig. 1 is an example of a configuration of a passenger information control device according to a first embodiment and devices connected to the passenger information control device. A train car shown in Fig. 1 includes display devices 1, a passenger information control device 2, an
10 onboard transmission controller 3, and a train control device 4.

[0014] Fig. 2 is an example of a configuration of a ground transmission controller and devices connected to the ground transmission controller. A ground transmission
15 controller 6 is installed at a station platform, for example, and is connected to an information processing device 5 that processes program tables and the like. To the information processing device 5, a terminal 7 such as a
20 personal computer is connected and is used for updating a program table and other operations.

[0015] Fig. 3 is a block diagram of an example of a configuration of the passenger information control device. The passenger information control device 2 includes a
25 storage unit 8, a timer 10, a deletion determining unit 11, a deleting unit 12, and a video display controller 13. To the passenger information control device 2, the onboard transmission controller 3 and the display devices 1 are connected.

[0016] In Fig. 1, the onboard transmission controller 3
30 is installed in the front car of a train, for example, and is capable of receiving a program table 40a and video data 60a transmitted from the ground transmission controller 6 when the train stops at a station platform. The passenger

information control device 2 is capable of receiving and storing the program table 40a and the video data 60a transmitted from the ground transmission controller 6 via the onboard transmission controller 3.

5 [0017] The train control device 4 processes station information, estimated arrival times and the like, and provides the latest route information and the like to the display devices 1 via the passenger information control device 2.

10 [0018] The display devices 1 receive from the passenger information control device 2 the video data 60b relating to advertisements or data on routes supplied by the train control device 4, and provide advertisement videos or the like to the passengers in the train.

15 [0019] Fig. 1 depicts the display devices 1, the passenger information control device 2, the onboard transmission controller 3, and the train control device 4 which are installed in a train car. When there are plural train cars, the passenger information control device 2 is
20 installed in each train car to transmit video data 60c to plural display devices 1 in the train cars. In this case, such a configuration can be obtained by connecting a transmission path provided across train cars to the passenger information control device 2 on each car and
25 transmitting the program table 40a and the video data 60a, which are received by the passenger information control device 2 of the front car, to the passenger information control device 2 of each train car.

[0020] In Fig. 3, the storage unit 8 includes a program-
30 table storing unit 14, a presentation count database 15, a video-data storing unit 16 or the like.

[0021] The program-table storing unit 14 is capable of storing the program table 40a transmitted from the ground

transmission controller 6 and sending a program table 40b to the video display controller 13. The presentation count database 15 can store the number of presentations 9 of an advertisement video on the display devices 1. The video-
5 data storing unit 16 can store the video data 60a transmitted from the ground transmission controller 6.

[0022] The deletion determining unit 11 determines whether to designate the video data 60a recorded in the video-data storing unit 16 as a candidate for deletion
10 based on the validity period (dates and times of presentation start and end) of the video data 60a. When there is any video data 60a as a candidate for deletion, a code indicating that the video data 60a is a candidate for deletion (hereinafter, "deletion candidate flag") can be
15 set in a program table 40c. Determination of whether to designate video data as a candidate for deletion, can also utilize used the time period from the last presentation time of the corresponding advertisement video to the present time, the number of presentations 9, or the volume
20 of the video data 60a, in addition to the validity period of the video data 60a.

[0023] The deleting unit 12 receives a program table 40d sent from the deletion determining unit 11, and checks the video data 60a, on which the deletion candidate flag is set
25 against several further conditions for determination. According to the result of determination, the deleting unit 12 deletes the appropriate video data 60a recorded in the storage unit 8.

[0024] The timer 10 is used for calculating the time
30 period between the last presentation time and the present time. Specifically, the timer 10 transmits a time 17 to the deletion determining unit 11 or the deleting unit 12. The deletion determining unit 11 or the deleting unit 12

compares the time 17 with the last presentation time recorded in the program table 40c or 40d, and calculates the time period from the last presentation time to the present time. Although Fig. 3 depicts a configuration such that the timer 10 is connected with the deletion
5 determining unit 11, this embodiment is not limited thereto, and the timer 10 can be connected to the deleting unit 12, for example.

[0025] The video display controller 13 takes in the
10 program table 40b and video data 60b from the storage unit 8, and determines the validity period of the video data 60b and whether the deletion candidate flag is set on the video data 60b. Then, the video display controller 13 transmits the video data 60c of an advertisement video that is within
15 its validity period and that does not have a deletion candidate flag to the display devices 1. When the video data 60c is transmitted to the display devices 1, the video display controller 13 also increments the number of presentations and records the last presentation time.

20 [0026] As described above, the passenger information control device 2 is configured to be able to determine whether an advertisement video has been presented not frequently because the video is not popular, whether a considerable amount of time has elapsed from the last
25 presentation time to the present, or whether the volume of video data is relatively large in addition to determining the validity period of the video data 60a, through predetermined determination performed by the deletion determining unit 11 or the deleting unit 12. This means
30 the video data 60a which is likely to be presented again can be kept in the storage unit 8.

[0027] Fig. 4 is an example of a program table. A program table 40 shown in Fig. 4 includes a validity period

(start) 41, a validity period (expire) 42, a last presentation time 43, a video data name 44, a file volume 45, and a deletion-candidate-flag storage portion 46.

[0028] The validity period (start) 41 indicates the date and time at which presentation of the video data 60a starts. The validity period (expire) 42 indicates the date and time at which presentation of the video data 60a ends. The last presentation time 43 indicates the date and time the advertisement video was last presented. The video data name 44 indicates the title of the video data 60a.

[0029] The file volume 45 indicates the volume of a video data file having the title indicated in the video data name 44.

[0030] The deletion-candidate-flag storage portion 46 is an entry for recording a deletion candidate flag when a deletion candidate flag is set on the video data 60a chosen as a candidate for deletion by the deletion determining unit 11.

[0031] Because the entries in the program table 40 correspond to serial numbers in the leftmost column, the deletion determining unit 11 or the deleting unit 12 can check the video data 60a in order of the serial numbers and make determination on deletion for each video data. The number and the contents of entries in the program table 40 are not limited to those described here. Also, serial numbers can be arranged in descending order to make it possible to perform a deletion determination process. Furthermore, although a deletion candidate flag is given to the video data 60a as a candidate for deletion, this embodiment is not limited thereto and, for example, a checkbox format can be used and checkmarks are provided for checking.

[0032] Fig. 5 is an example of a presentation count table. A presentation count table 50 shown in Fig. 5 includes a video data name 51 and a presentation-count display portion 52.

5 [0033] The presentation-count display portion 52 can record the number of times an advertisement video has been presented. The presentation-count display portion 52 can also indicate the number of presentations which is arbitrarily set on the ground transmission controller 6
10 side for an advertisement video whose number of presentations is negotiated with a sponsor, for example, instead of the number of times an advertisement video has been presented on the display devices 1.

[0034] Because the entries in the presentation count
15 table 50 correspond to serial numbers shown in the leftmost column, the deletion determining unit 11 or the deleting unit 12 can check the video data 60a in order of the serial numbers and make determination on deletion for each video data. The number and the contents of entries in the
20 presentation count table 50 are not limited to those described here.

[0035] Fig. 6 is a flowchart of an example of a flow of determining video data as a candidate for deletion. For the video data 60a with $m=1$ (Step S61), the deletion
25 determining unit 11 reads the program table 40c (Step S62). The deletion determining unit 11 determines whether the video data 60a with $m=1$ is still within its validity period, and when the validity period of the video data 60a has expired (NO at Step S63), the deletion determining unit
30 11 sets a deletion candidate flag in the deletion-candidate-flag storage portion 46 (Step S64). The value m is incremented by 1 (Step S65). When the value m exceeds the maximum value of serial numbers indicated in the

program table 40c as a result of incrementing m by 1 (YES at Step S66), the processes of Step S61 and the subsequent steps are repeated with the video data 60a exceeding the maximum value as m=1 data.

5 [0036] The value m is a variable, indicating a number assigned for determining the video data 60a in the program table 40c.

[0037] When the video data 60a with m=1 is still within its validity period (YES at Step S63), m is incremented by
10 1 (Step S67), and the processes of Step S62 and the subsequent steps are repeated for the second and subsequent video data 60a.

[0038] If m does not exceed the maximum value (NO at Step S66), the processes of Step S62 and the subsequent
15 steps are repeated for the second and subsequent video data 60a.

[0039] Fig. 7 is a flowchart of an example of a flow of determining presentation on display devices. For the video data 60a with n=1 (Step S71), the video display controller
20 13 reads the program table 40b (Step S72). The video display controller 13 determines whether the video data 60a with n=1 is still within its validity period and has a deletion candidate flag. If the video data 60a is still within its validity period and does not have a deletion
25 candidate flag (YES at Step S73), the corresponding advertisement video is presented on the display devices 1, the number of presentation in the presentation count table 50 is incremented by 1, and the last presentation time is recorded in the program table 40b (Step S74). Thereafter,
30 n is incremented by 1 (Step S75), and if the value n exceeds the maximum value of serial numbers indicated in the program table 40b as a result of incrementing n by 1 (YES at Step S76), the processes of Step S71 and the

subsequent steps are repeated with the video data 60a exceeding the maximum value as $n=1$ data.

[0040] The value n is a variable, and it indicates a number assigned for determining the video data 60a in the
5 program table 40b.

[0041] When the validity period of the video data 60a exceeds a predetermined value or when the video data 60a has a deletion candidate flag (NO at Step S73), the flow proceeds to determination at Step S76 while skipping Steps
10 S74 and S75.

[0042] If n has not exceeded the maximum value (NO at Step S76), the processes of Step S72 and the subsequent steps are repeated for the second and subsequent video data 60a.

[0043] It is possible to add a step for determining that upon reading the program table 40b by the video display controller 13 (Step S72), whether the read program table 40b has been updated to a new program table 40 transmitted from the ground transmission controller 6. For example, if
20 the read program table 40b has not been updated, the processes of Step S73 and the subsequent steps can be repeated with the program table 40b not updated. When the read program table 40b has been updated, the processes of Step S71 and the subsequent steps can be repeated with the
25 new program table 40b.

[0044] Fig. 8 is a flowchart of an example of a flow for determining how much space is available in the storage unit on the ground transmission controller. When the train stops at a station and a connection is established between
30 the ground transmission controller 6 and the onboard transmission controller 3 (YES at Step S81), the onboard transmission controller 3 transmits the program table 40a stored in the storage unit 8 and information indicating how

much space is free in the storage unit 8 to the ground transmission controller 6 (Step S82). The ground transmission controller 6 compares the received program table 40a transmitted from the onboard transmission controller 3 to the latest program table 40 stored in the information processing device 5 (Step S83). With this comparison, the ground transmission controller 6 can determine whether new video data 60a to be transmitted to the onboard transmission controller 3 is of a size that can be saved in the storage unit 8. When the free space in the storage unit 8 is equal to or larger than the volume of the new video data 60a (YES at Step S84), the ground transmission controller 6 transmits the latest program table 40 and the new video data 60a to the onboard transmission controller 3. The onboard transmission controller 3 receives the latest program table 40 and the new video data 60a, and stores them in the storage unit 8 (Step S85).

[0045] When the free space in the storage unit 8 is smaller than the volume of the video data 60a (NO at Step S84), the process terminates without the ground transmission controller 6 transmitting the video data 60a to the onboard transmission controller 3.

[0046] As described above, the ground transmission controller 6 can receive the program table 40a and data relating to the free space in the storage unit 8 from the onboard transmission controller 3, determine whether new video data 60a for transmission is of a size that can fit into the free space, and then transmit the video data 60a to the onboard transmission controller 3. Accordingly, when a free space in the storage unit 8 is small, for example, large-sized video data 60a cannot be transmitted while the video data 60a of a small size can be transmitted.

This allows the free space in the storage unit 8 to be efficiently utilized. Also, because transmission of large-sized video data 60a can be avoided, the efficiency of transmission to the onboard transmission controller 3 can be improved as well.

[0047] Fig. 9 is a flowchart of an example of a flow for determining deletion of video data. For the video data 60a with $m=1$ (Step S91), the deletion determining unit 11 reads the program table 40c (Step S92). The deletion determining unit 11 determines whether the video data 60a with $m=1$ is still within its validity period. If the validity period of the video data 60a has expired, the deletion determining unit 11 sets a deletion candidate flag in the deletion-candidate-flag storage portion 46. When a deletion candidate flag is set in the deletion-candidate-flag storage portion 46 (YES at Step S93), and when the time period from the last presentation time of the corresponding advertisement video to the present time is equal to or greater than a predetermined value (YES at Step S94), for example, the flow proceeds to Step S95. When the number of presentations is equal to or less than a predetermined value (YES at Step S95), the deleting unit 12 proceeds to Step S96, where the deleting unit 12 deletes the video data 60a (YES at Step S96). Setting of the predetermined values mentioned above can be made by the terminal 7 connected to the ground transmission controller 6, for example.

[0048] If a deletion candidate flag is not set in the deletion-candidate-flag storage portion 46 (NO at Step S93), the deleting unit 12 increments m by 1 (Step S98), and the processes of Step S92 and the subsequent steps is repeated for the second and subsequent video data 60a.

[0049] When the time period between the last presentation time of the advertisement video and the

present time is less than the predetermined value (NO at Step S94), m is incremented by 1 (Step S98), and the processes of Step S92 and the subsequent steps are repeated for the second and subsequent video data 60a.

5 [0050] Further, when the number of presentations exceeds the predetermined value (NO at Step S95), m is incremented by 1 (Step S98), and the processes of Step S92 and the subsequent steps are repeated for the second and subsequent video data 60a.

10 [0051] When the value m exceeds the maximum value of serial numbers indicated in the program table 40d (YES at Step S97), the deleting unit 12 repeats the processes of Step S91 and the subsequent steps with the video data 60a exceeding the maximum value as m=1 data. When the value m
15 does not exceed the maximum value (NO at Step S97), the deleting unit 12 increments m by 1 (Step S98), and repeats the processes of Step S92 and the subsequent steps for the second and subsequent video data 60a.

[0052] The free space in the storage unit 8 can be
20 further increased by adding a step for determining the volume of the video data 60a after "NO" at Step S94 or S95 and deleting the video data 60a having a volume equal to or larger than a certain value.

[0053] The predetermined values can be varied from one
25 video data to another. For example, for different pieces of video data, a larger or smaller number of presentations can be set as well as a longer or shorter time period from the last presentation time to the present time can be set. The combinations of determination steps shown above are
30 merely examples and not limited thereto.

[0054] As described above, the passenger information control device 2 according to the first embodiment determines not only the validity period of the video data

60a, but the time period from the last presentation time of the corresponding advertisement video to the present time, the number of times the advertisement video has been presented and the like, and outputs a result of

5 determination on deletion candidates. Therefore, an advertisement video that is probably requested to be presented again by the sponsor or the like after being played for a certain time period can be kept in the storage unit 8. This can avoid a situation where, for example, the
10 video data 60a is once deleted and cannot be stored in the storage unit 8 again due to shortage of the free space in the storage unit 8 at a time when the video data 60a should be recorded again. In addition, because retransmission of deleted video data 60a to the passenger information control
15 device 2 becomes less frequently, the efficiency of transmission between the ground transmission controller 6 and the onboard transmission controller 3 can be also improved.

[0055] Second embodiment

20 The passenger information control device 2 according to a second embodiment is configured to secure a free space sufficient for the volume of newly received video data 60a.

[0056] Fig. 10 is a flowchart of an example of a flow of determining deletion of video data on the passenger
25 information control device according to the second embodiment. For the video data 60a with $m=1$ (Step S101), the deletion determining unit 11 reads the program table 40c (Step S102). The deletion determining unit 11 determines whether the video data 60a with $m=1$ is still
30 within its validity period, and if the validity period of the video data 60a has expired (NO at Step S103), the deletion determining unit 11 sets a deletion candidate flag in the deletion-candidate-flag storage portion 46 (Step

S104). The deleting unit 12 determines whether the volume of the video data 60a with $m=1$ is equal to or larger than the volume of the video data 60a to be newly received.

When the volume of the video data 60a with $m=1$ is equal to
5 or larger than the volume of the video data 60a to be newly received (YES at Step S105), the deleting unit 12 deletes the video data 60a with $m=1$ (Step S106), and increments m by 1 (Step S107). When the value m exceeds the maximum value of serial numbers indicated in the program table 40c
10 as a result of incrementing m by 1 (YES at Step S108), the processes of Step S101 and the subsequent steps are repeated with the video data 60a exceeding the maximum value as $m=1$ data.

[0057] The volume of the video data 60a can be
15 recognized because it is determined from the value of the file volume 45 in the program table 40a when the program table 40a is sent from the ground transmission controller 6.

[0058] If the video data 60a with $m=1$ is still within
20 its validity period (YES at Step S103), m is incremented by 1 (Step S109), and the processes of Step S102 and the subsequent steps are repeated for the second and subsequent video data 60a.

[0059] When the volume of the video data 60a with $m=1$ is
25 smaller than the volume of video data 60a to be newly received (NO at Step S105), m is incremented by 1 (Step S109), and the processes of Step S102 and the subsequent steps are repeated for the second and subsequent video data 60a.

30 [0060] If the value m has not exceeded the maximum value (NO at Step S108), the processes of Step S102 and the subsequent steps are repeated for the second and subsequent video data 60a.

[0061] As described above, the passenger information control device 2 according to the second embodiment deletes only the video data 60a whose volume is large enough for the volume of the video data 60a to be newly received from among advertisement videos designated as candidates for deletion due to expiration of validity period at a time when the onboard transmission controller 3 receives the program table 40a. Therefore, when a sponsor requests that a new advertisement video be preferentially presented, for example, the latest video data 60a can be stored without having to delete all of the video data 60a that will be represented.

[0062] Third embodiment

The passenger information control device 2 according to a third embodiment is configured to delete the video data 60a that has been presented for a predetermined number of times, without relying on the time period from the last presentation time to the present time or validity period.

[0063] Fig. 11 is a flowchart of an example of a flow for determining deletion of video data on the passenger information control device according to the third embodiment. For the video data 60a with $m=1$ (Step S111), the deletion determining unit 11 reads the program table 40c (Step S112). The deletion determining unit 11 determines whether the number of times the video data 60a with $m=1$ has been presented is equal to or greater than a predetermined value. When the number of presentation times the video data 60a with $m=1$ has been presented is equal to or greater than the predetermined value (YES at Step S113), the deleting unit 12 sets a deletion candidate flag in the program table 40d (Step S114), and deletes the video data 60a (Step S115). The value m is incremented by 1 (Step S116). When the value m exceeds the maximum value of

serial numbers indicated in the program table 40d as a result of incrementing m by 1 (YES at Step S117), the processes of Step S111 and the subsequent steps are repeated with the video data 60a exceeding the maximum value as m=1 data.

[0064] If the number of times the video data 60a with m=1 has been presented is less than the predetermined value (NO at Step S113), m is incremented by 1 (Step S118), and the processes of Step S112 and the subsequent steps are repeated for the second and subsequent video data 60a.

[0065] If m does not exceed the maximum value (NO at Step S117), the processes of Step S112 and the subsequent steps are repeated for the second and subsequent video data 60a.

[0066] As described above, the passenger information control device 2 according to the third embodiment deletes the video data 60a that has been presented for a predetermined number of times. Therefore, it is able to preferentially delete video data that can be deleted regardless of the time period since its last presentation time or validity period, such as an advertisement video whose number of presentations is fixed, to secure a free space in the storage unit 8. The passenger information control device 2 can also delete the video data 60a that is not a candidate for deletion because its validity period has not expired when the number of presentations of the video data 60a has reached a predetermined number of times. Thus, a free space can be secured in the storage unit 8 more efficiently than the conventional approach of deleting the video data 60a upon expiration of validity period.

[0067] Fourth embodiment

The passenger information control device 2 according to a fourth embodiment is configured to be able to delete

the video data 60a based on deletion candidate flags that are set on the ground transmission controller 6 side.

[0068] Fig. 12 is a flowchart of an example of a flow for determining deletion of video data on the ground

5 transmission controller. When the train stops at a station and a connection is established between the ground transmission controller 6 and the onboard transmission controller 3 (YES at Step S121), the onboard transmission controller 3 transmits the program table 40a stored in the
10 storage unit 8 and information indicating a free space available in the storage unit 8 to the ground transmission controller 6 (Step S122). When the program table 40a transmitted from the onboard transmission controller 3 contains any video data 60a that should be deleted (YES at
15 Step S123), a deletion candidate flag is set in the program table 40 on the terminal 7 (Step S124). The latest program table 40 with the deletion candidate flag is transmitted to the onboard transmission controller 3 (Step S125). Upon receiving the latest program table 40, the onboard
20 transmission controller 3 stores the program table 40 in the storage unit 8, and sends the program table 40 to the deletion determining unit 11 and the deleting unit 12, which delete the video data 60a with the deletion candidate flag set (Step S126).

25 [0069] If no video data 60a for deletion is found in the program table 40a transmitted from the onboard transmission controller 3 on the terminal 7 (NO at Step S123), the process terminates without setting a deletion candidate flag in the program table 40a.

30 [0070] As described above, according to the passenger information control device 2 of the fourth embodiment, a deletion candidate flag is set on the ground transmission controller 6 and the video data 60a can be deleted based on

the deletion candidate flag. It is therefore possible to arbitrarily delete the video data 60a and receive new video data 60a without relying on the time period between the last presentation time and the present time, the validity
5 period, or the number of times an advertisement video has been presented. In addition, with the ability to delete the video data 60a at an arbitrary time, sponsors' requests can be flexibly handled.

INDUSTRIAL APPLICABILITY

10 [0071] As described above, the passenger information control device according to the present invention is useful as a passenger information control device having a video display controller that transmits video data of in-train advertisements to display devices in a train.

CLAIMS

1. A passenger information control device having a video display controller that transmits, to a display device in a train, video data for an in-train advertisement, which is
5 transmitted from a ground transmission controller to an onboard transmission controller, the passenger information control device comprising:

a storage unit that stores a program table and the video data, the program table storing at least one of
10 number of times an advertisement video has been presented, a validity period of the advertisement video, a time period from a last presentation time to present time, and a volume of the video data, being associated with each advertisement;

15 a deletion determining unit that receives the program table via the video display controller and determines whether to designate the video data as a candidate for deletion based on the program table; and

a deleting unit that deletes the video data stored in
20 the storage unit based on determination by the deletion determining unit.

2. The passenger information control device according to claim 1, wherein the deletion determining unit sets a flag
25 indicating that the video data is a candidate for deletion in the program table.

3. The passenger information control device according to claim 2, wherein the deletion determining unit determines a
30 volume of the video data, and sets the flag on video data having a volume equal to or larger than a predetermined volume.

4. The passenger information control device according to claim 2, wherein the deletion determining unit determines the number of times the video data has been presented, and sets the flag on video data that has been presented for a
5 predetermined number of times or more.

5. The passenger information control device according to any one of claims 2 to 4, wherein the ground transmission controller sets the flag in the program table, which is
10 transmitted from an onboard transmission controller, and transmits the program table to the onboard transmission controller.

6. The passenger information control device according to
15 any one of claims 1 to 5, wherein the ground transmission controller compares a first program table transmitted from an onboard transmission controller to a second program table stored in the ground transmission controller, and transmits video data for a program that is not recorded in
20 the first program table to the onboard transmission controller.

7. A method for providing video data for a passenger information control device having a transmitting step of
25 transmitting, to a display device in a train, video data for an in-train advertisement, which is transmitted from a ground transmission controller to an onboard transmission controller, the method comprising:

a storing step of storing a program table and the
30 video data, the program table storing at least one of number of times an advertisement video has been presented, a validity period of the advertisement video, a time period from a last presentation time to present time, and a volume

of the video data, being associated with each advertisement;

5 a deletion determining step of receiving the program table via the sending step and determining whether to designate the video data as a candidate for deletion based on the program table; and

a deleting step of deleting the video data based on determination at the deletion determining step.