

Composite Gas Sampling System

This PCT international application claims priority of U.S. application
Serial Number 14/205,526 filed March 12, 2014 and U.S. provisional application
5 Serial Number 61/794,240 filed March 15, 2013.

Technical Field

This invention relates to collecting composite gas samples for
analysis, and particularly for composite sample collection after a cryogenic gas
10 has been conditioned by a system of the type described in US 7,484,404,
Thompson, which is owned by the Applicant herein and sold as a Mustang
Sampling system. More particularly, this composite sample system is
complementary to a gas sample conditioning vaporizer employed to collect
conditioned vaporized samples of liquid natural gas and/or natural gas liquid.

Background

Liquid natural gas sampling is governed by the standard ISO 8943
and GIIGNL LNG custody transfer handbook. Europe and other areas of the
world impose additional requirements such as mandating composite sampling of
transferred LNG contents, and particularly, that from tanker ship off-loading. The
20 standard calls for a composite sampling to be collected for the duration of time
that a ship is off-loading. The sampled gas stream is transferred to small
cylinder sample containers for storage and comparison to continuous online
analysis averages.

During transfer processing of a liquid natural gas shipping vehicle, it
25 is desirable to obtain accurate sampling for auditing the energy content of the
off-loaded LNG. This can be accomplished using known techniques such as

periodic direct sampling from a takeoff vaporizer stream and/or composite sampling. While direct sampling allows for immediate analysis by an appropriate analyzer such as a gas chromatograph, it provides an accurate portrayal of the content of the LNG off-loaded from the vehicle during the entire transfer process only by extrapolating selected accumulated data. Additionally, manual direct
5 sampling can be taken intermittently, for example, at $\frac{1}{4}$, $\frac{1}{2}$, and $\frac{3}{4}$ of vessel cargo transfer. Automatic composite sampling is used to obtain particular volumes of vaporized LNG at select periodic intervals during the transfer processing. However, analysis of the typical composite sample content is available only
10 after the transfer processing is complete.

Conventional composite sampling technology for LNG typically takes the form of dome or floating piston systems. Dome systems are bladder based and require a fluid (typically water) to isolate the collection dome from the ambient environment and maintain pressure on the collected samples. The resulting
15 extracted composite sample is subsequently transferred from the dome to sample cylinders for analysis and/or storage for later qualitative analysis. Because dome systems rely on fluid/water failure of associated water seals will contaminate the composite sample.

Floating piston samplers are of a more simple construction than
20 dome samplers and avoid the introduction of water/fluid as the seal method, but rely on mechanical seals. Correspondingly, floating piston systems are believed to minimize the introduction of other ambient gases (e.g., oxygen) into the composite natural gas sample. However, floating piston systems include a number movable parts and seals as well as requiring a motive source to

pressurize the piston. Not only do such movable parts introduce sources for sample contamination from leakage and the like, but also it is known that such systems employ relatively higher pressures to evacuate the sample chamber during cycling.

5 **Summary of Invention**

It is an object of the present invention to provide a novel sample system and methodology for conditioned vaporized, gas during transfer processing.

It is another object of the present invention to overcome the
10 aforementioned problems associated with conventional structures of the prior art.

Another object of the present invention is to provide an expedient to overcome recognized problems with existing sample collection techniques.

A further object of the present invention is to provide greater flexibility in customizing the sampling technique selection and execution for any particular
15 transfer operation.

Still another object of the present invention is selectively provide coincidental fresh gas and composite gas sample sequestration for analysis.

Yet another object of the invention is to provide a convenient,
integrated composite gas sample system with a minimum of moving parts.

20 These and other objects are satisfied by an apparatus for capturing a periodic gas sample following vaporizing and conditioning into a gas phase of a cryogenic liquid hydrocarbon source during transfer processing characterized by at least a first and a second vaporized sample input lines each incorporating at least a first direct feed line, a second speed loop line,

and a third accumulator feed line; each of the first direct feed lines of the first and second vaporized sample input lines being directly connected to a gas analyzer for on-line, real-time, periodic analysis of a non-composite gas sample; each of the speed loop lines being connected to a speed loop having
5 an a pressure regulator, a high pressure pump, a plurality of solenoid controlled valves for controlled filling of a plurality of non-composite sample cylinders for storage of fresh gas samples obtained at specified processing intervals, and a by-pass outlet to a boil-off-gas system; each of the accumulator lines including at least one solenoid controlled valve, said
10 accumulator line for passing a gas sample of a select volume at select time intervals to a pressure regulator, a solenoid controlled valve, and a gas accumulator for receiving multiple periodic select volume gas samples to create a composite gas sample, and a high pressure pump to maintain pressure sufficient in the gas accumulator to prevent dew point drop-out of
15 the gas sample in the accumulator, a valve controlled outlet from the gas accumulator, and a plurality of sample grab cylinders for receiving composite samples from the gas accumulator upon completion of source processing.

Other objects are satisfied by a system for selected sampling cryogenic liquid hydrocarbon source where the liquid hydrocarbon has been vaporized
20 and conditioned by a vaporizer during transfer processing characterized by a housing; a controller for controlling the gas sampling operation contained within the housing; a vaporized gas port providing a first, a second and a third gas stream feed lines adapted to receive a vaporized gas sample of a select volume at a select time; a gas analyzer connected to said first gas

stream feed line; a speed loop connected to said second feed line; a plurality of removable, sample cylinders connected to the speed loop for collection of non-composite fresh samples at select times directly from the vaporizer; an accumulator connected to said third gas stream for receiving a select volume
5 of gas to create a composite sample of vaporized gas; a pump associated with said accumulator to maintain accumulator pressure at a level to prevent dew point drop out of the vaporized gas; a plurality of removable sample grab cylinders for receiving composite vaporized gas samples from the accumulator; and a residual gas removal array for removing residual gas as
10 from the system following transfer processing of the cryogenic liquid hydrocarbon.

Still other objects are satisfied by a method for sampling of vaporized gas from a cryogenic liquid hydrocarbon liquid using a gas sample system, characterized by the steps of obtaining a first vaporized gas sample of
15 selected volume and at first select intervals from a vaporizer connected to a cryogenic liquid hydrocarbon repository; passing a select volume of said first vaporized gas sample to a first sample grab cylinder; pumping a second select volume of said vaporized first gas sample to a composite sample accumulator tank under pressure sufficient to prevent dew point dropout;
20 obtaining a second gas sample of selected volume at select interval different from the first select interval; passing a first select volume of said vaporized second gas sample to a second sample grab cylinder; pumping a second select volume of said vaporized second gas sample to the composite sample accumulator tank under pressure sufficient to prevent dew point dropout to

obtain a composite gas sample; passing the composite gas sample to a select one of a plurality of removable composite sample collection cylinders for receiving said composite vaporized sample from the accumulator tank; removing the select one of the composite sample cylinders; and removing at
5 least said first sample grab cylinder.

The sample system of the present invention is designed to take timed samples after an sample conditioning system has converted a liquid sample to a gas from one or more input gas streams and provide an associated gas chromatograph or other analyzer with a direct feed for instant analysis, a fresh
10 sample for subsequent analysis at select time intervals during processing and a composite sample for subsequent analysis representative of the entire gas content over the entire sample gathering process. That is, for example, after loading or unloading a ship or container has been completed, the composite sample is in the accumulator, the sampler is turned off. The associated
15 sample cylinders, generally having a 500cc volume are then filled from the accumulator. After the sample cylinders have been filled, the remaining gas in the accumulator is vented and the system cleaned by use of gas purge, vacuum etc.

For control of the various processes carried out by the invention, use of
20 a resident Programmable Logic Controller (PLC) is preferred. The PLC controls the sequential operations and timing of the composite sample pumps and gas line valves to perform the desired incremental sampling. Furthermore, when redundant or multiple gas streams and pumps are utilized, the invention contemplated that they all feed into a common

accumulator rated for the system.

The inventive system does not rely only on volume measurements but also facilitates controlled, periodic sampling based on sample accumulation discrete, known time intervals. That is, the continuous sampling process to fill
5 the sample cylinders provides more accurate results based on its more technical approach to sample collection by relying on select timing of sample accumulation rather than sample gas flow, alone. The invention contemplates a sample system that functions to obtain samples while maintaining relatively low pressures using a static structure (no moving parts)
10 thereby minimizing risks of leakage and contamination. Furthermore, use of the invention substantially reduces the risk of Joule-Thompson cooling and concomitant hydrocarbon dew pint dropout which adversely impacts the accuracy of the samples being analyzed.

For definitional purposes and as used herein "connected" includes
15 physical, whether direct or indirect, affixed or adjustably mounted, as for example, the composite sample system is connected to the a vaporizer, the speed loop line is connected to the sample grab cylinders and the bypass. Thus, unless specified, "connected" is intended to embrace any operationally functional connection.

20 As used herein "transfer processing" means any processes involving the movement of cryogenic liquid from one place to another in the conventional

sense as well as from or to any large cryogenic liquid natural gas container such as ships, railcars or trucks.

As used herein "substantially," "generally," and other words of degree are relative modifiers intended to indicate permissible variation from the characteristic so modified. It is not intended to be limited to the absolute value or characteristic which it modifies but rather possessing more of the physical or functional characteristic than its opposite, and preferably, approaching or approximating such a physical or functional characteristic.

In the following description, reference is made to the accompanying drawing, and which is shown by way of illustration to the specific embodiments in which the invention may be practiced. The following illustrated embodiments are described in sufficient detail to enable those skilled in the art to practice the invention. It is to be understood that other embodiments may be utilized and that structural changes based on presently known structural and/or functional equivalents may be made without departing from the scope of the invention.

Brief Description of the Drawings

Figure 1 is a photographic depiction of a composite sample system in accordance with an embodiment of the invention.

Figure 2 is a schematic diagram of the embodiment of Figure 1.

Figure 3 is a schematic diagram of a multi-stream, multi-sample collection embodiment of the invention.

Figure 4 is a schematic diagram of an embodiment of the invention that with a bladderless accumulator and a vacuum unit for removing residual gas from the system upon completion of a transfer process.

Detailed Description of the Drawings

The embodiment illustrated in Figure 1 includes the composite sample system 10 contained in housing 11. The system 10 provides a representative gas composition sample by taking small bite size samples over a period of time.

5 The system 10 includes a programmed logic controller (PLC) 12 with a connection to a remote communication facility for controlling the valves and solenoids and indicator lights for system operation as well as monitoring system status. In addition to the controller 12, the housing 11 of sampling system 10 contains sample pumps 14, a plurality of removable accumulator grab sample
10 cylinders 16 (four cylinders are used in the illustrated system), a plurality of fresh sample cylinders 18 each for receiving a respective gas sample at a specific interval (e.g., 1/3 load transfer, 1/2 load transfer, and 2/3 load transfer) during the transfer processing. The grab cylinders 16 are connected to accumulator 20 through appropriate tubing for communication the composite sample. The
15 accumulator 20 which receives a multiplicity of samples of a specified small volume, e.g., 0.5cc, at a preset time interval (i.e., 1 sec.) under conditions (pressure and temperature) maintained to prevent dew point dropout. Similarly when feeding the composite gas from the sample accumulator 20 to the respective grab sample cylinders, the associated pump(s) must maintain the
20 pressure of the gas to prevent dew point drop out. For maintenance of system stability, the interior of cabinet 11 includes the electrical housing heater 22 to maintained temperatures at an elevated level.

In operation, the composite sample system according to the invention grabs a fresh, 0.5 cc, sample every second, storing it in the accumulator 20 for

transfer to the associated grab cylinders 16 following the conclusion of the transfer operation. The composite sample can then be removed and transferred to a laboratory or analyzer site for subsequent analysis.

The invention contemplates residual sampled gas removal at the conclusion offloading or transfer processing to reset the system for the next processing operation. Figure 2 illustrates a gas purge subsystem based on nitrogen gas fed into the system from the tank 24. The purging operation can be completely automated or may be semi- manual (the nitrogen regulator is opened manually when the PLC has been instructed to open the system valves for purging.

Turning to the embodiment illustrated in Figure 3, it illustrates a multipath, multi-vaporizer takeoff system for multiple simultaneous inputs. This embodiment also provides speed loops 24 that provide alternative feed lines for the vaporized gas directly from the vaporizer to one or more select collection cylinders and/or overflow from the gas pumps 14 associated with the accumulator 20. The particular arrangement provides the system user with the greatest flexibility by allowing for either collection cylinder set to be used for non-composite sampling as well as providing venting to line feed 28 for a BOG (boil-off-gas) collector/header system.

Another option for resetting the system is illustrated in Figure 4 where a vacuum generating unit 26 is disposed in line with the system and activated by the PLC 12 has all valves opened, to create a negative system pressure and move the residual gas to an appropriate outlet such as a BOG header 28 or using the above-mentioned positive pressure purging gas, e.g., Helium, from the

tank 23 to push the residual gas to a vent or the like. Once removed, the system has been effectively reset and is ready for the next sampling operation.

Industrial Applicability

5 The sample system of the present invention is useful in the transfer of LNG from a transport vehicle and particularly transoceanic LNG tanker ships. The system is designed for taking vaporized samples from a sample conditioning system after conversion from a liquid to a gas from multiple input gas streams and to provide a sample feed to an analyzer, direct periodic samples, and an
10 accumulated composite sample from the transfer operation. The analysis of the respective collected gas samples from the different inputs are compared at the conclusion of the transfer operation and select samples are stored for later energy audits or disputes.

 The invention has been disclosed in the forgoing specification. It is
15 understood by those skilled in the art that many modifications and embodiments of the invention will come to mind to which the invention pertains, having benefit of the teaching presented in the foregoing description and associated drawings. It is therefore understood that the invention is not limited to the specific embodiments disclosed herein, and that many modifications and other
20 embodiments of the invention are intended to be included within the scope of the invention. Moreover, although specific terms are employed herein, they are used only in generic and descriptive sense, and not for the purposes of limiting the description invention.

We Claim:

1. An apparatus for capturing a periodic gas sample following vaporizing and
5 conditioning into a gas phase of a cryogenic liquid hydrocarbon source during transfer processing characterized by at least a first and a second vaporized sample input lines each incorporating at least a first direct feed line, a second speed loop line, and a third accumulator feed line;
each of the first direct feed lines of the first and second vaporized sample input
10 lines being directly connected to a gas analyzer for on-line, real-time, periodic analysis of a non-composite gas sample;
each of the speed loop lines being connected to a speed loop having an a pressure regulator, a high pressure pump, a plurality of solenoid controlled valves for controlled filling of a plurality of non-composite sample cylinders for storage of fresh gas
15 samples obtained at specified processing intervals, and a by-pass outlet to a boil-off-gas system;
each of the accumulator lines including at least one solenoid controlled valve, said accumulator line for passing a gas sample of a select volume at select time intervals to a pressure regulator, a solenoid controlled valve, and a gas accumulator for receiving
20 multiple periodic select volume gas samples to create a composite gas sample, and a high pressure pump to maintain pressure sufficient in the gas accumulator to prevent dew point drop-out of the gas sample, a valve controlled outlet from the gas accumulator, and

a plurality of sample grab cylinders for receiving composite samples from the gas accumulator upon completion of source processing.

2. The apparatus of claim 1 further characterized by a control unit for
5 controlling the solenoid valves, flow operations, speed loop fresh non-composite sample collection timing, and accumulator composite gas sample retention.

3. The apparatus of claims 1-2 characterized by a third vaporized gas sample
input line and a second, duplicate accumulator line connected to a said gas accumulator
10 for simultaneous sampling from multiple inputs from the source.

4. The apparatus of claims 1-3 characterized by a residual gas removal
system following completion of processing sampling operations.

15 5. The apparatus of claims 1-4 characterized in that the residual gas removal system is a gas purge system and where the Boil-off-gas system comprises a boil-off gas header.

20 6. The apparatus of claims 1-4 characterized in that the residual gas removal system includes an evacuation method.

7. The apparatus of claims 1-6 further characterized by a housing cabinet
including a heater and over pressure vent.

8. The apparatus of claims 1-7 further characterized by a separate analyzer cabinet connected to or within said housing cabinet defining a housing cabinet for housing at least one gas analyzer.

5

9. The apparatus of claims 1-8 characterized in that said analyzer is a gas chromatograph, and further includes a heater in the analyzer cabinet and a calibration gas station.

10

10. The apparatus of claims 1 further characterized by at least one flow controller disposed in said speed loop line and a second flow controller disposed in said accumulator line for diverting the gas sample to said speed loop line.

15

11. The apparatus of claims 1-10 further characterized by at least a first second and third check valves to prevent backflow respectively between said high pressure pump and gas accumulator, said accumulator line and said speed loop line, and said sample grab cylinders and said boil-off gas system.

20

12. The apparatus of claims 1-11 further characterized by a control unit for controlling the solenoid valves, flow operations, and sample introduction into said accumulator.

25

13. The apparatus of claims 1-12 characterized in that there are three non-composite sample cylinders for storage of fresh non-composite samples obtained at 1/3,

½ and 2/3 of the elapsed processing intervals.

14. The apparatus of claims 1-13 characterized in that there are four removable, receiving composite sample grab cylinders.

5

15. A system for selected sampling cryogenic liquid hydrocarbon source where the liquid hydrocarbon has been vaporized and conditioned by a vaporizer during transfer processing characterized by a housing;

10 a controller for controlling the gas sampling operation contained within the housing;

a vaporized gas port providing a first, a second and a third gas stream feed lines adapted to receive a vaporized gas sample of a select volume at a select time; a gas analyzer connected to said first gas stream feed line; a speed loop connected to said second feed line;

15 a plurality of removable, sample cylinders connected to the speed loop for collection of non-composite fresh samples at select times directly from the vaporizer;

an accumulator connected to said third gas stream for receiving a select volume of gas to create a composite sample of vaporized gas;

20 at least one pump associated with said accumulator to build accumulator pressure at a level to prevent dew point drop out of the vaporized gas;

a plurality of removable sample grab cylinders for receiving composite vaporized gas samples from the accumulator;

a residual gas removal array for removing residual gas as from the system following transfer processing of the cryogenic liquid hydrocarbon.

16. The system of claim 15 further characterized by a redundant vaporized gas port connected to the accumulator.

5

17. A method for sampling of vaporized gas from a cryogenic liquid hydrocarbon liquid using a gas sample system characterized by the steps of:

obtaining a first vaporized gas sample of selected volume and at first select intervals from a vaporizer connected to a cryogenic liquid hydrocarbon repository;

10 passing a select volume of said first vaporized gas sample to a first sample grab cylinder;

pumping a second select volume of said vaporized first gas sample to a composite sample accumulator tank under pressure sufficient to prevent dew point dropout;

15

obtaining a second gas sample of selected volume at select interval different from the first select interval;

passing a first select volume of said vaporized second gas sample to a second sample grab cylinder;

20 pumping a second select volume of said vaporized second gas sample to the composite sample accumulator tank under pressure sufficient to prevent dew point dropout to obtain a composite gas sample;

passing the composite gas sample to a select one of a plurality of removable composite sample collection cylinders for receiving said composite vaporized sample from the accumulator tank;

25

removing the select one of the composite sample cylinders; and

removing at least said first sample grab cylinder.

18. The method of claim 17 further characterized by the step of removing
5 residual gas from the gas sample system after removing the composite sample cylinder
and the sample grab cylinder.

19. The method of claims 17-18 further characterized by the step of
10 purging residual gas in the gas sample system after removing the composite sample
cylinder and the sample grab cylinder.

20. The method of claims 17-19 further characterized by the step of
15 analyzing the content of the removed composite sample cylinder and said sample
grab cylinder.