WHAT IS CLAIMED IS:

1. A wireless communication method, comprising:

Detecting a first signal or channel sent by a network device; and

determining whether to detect a second signal or channel according to a detection result of the first signal or channel and a configuration made by the network device regarding a relationship between the detection result of the first signal or channel and whether to detect the second signal or channel.

2. The method according to claim 1, wherein determining whether to detect a second signal or channel comprises:

determining whether to detect the second signal or channel at a specific detection time period or a specific detection time point according to the detection result of the first signal or channel and the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel.

3. The method according to claim 2, wherein the specific detection time period or the specific detection time point is at least one detection time period or time point in periodic detection time periods or time points.

4. The method according to claim 3, wherein the specific detection time period or the specific detection time point is an on duration in a discontinuous reception DRX cycle; or, the specific detection time point is at least one paging occasion in periodic paging occasions.

5. The method according to claim 4, wherein determining whether to detect a second signal or channel comprises:

determining whether to detect the second signal or channel in the on duration of a current DRX cycle, according to the detection result of the first signal or channel at a specific time or time period in an opportunity for DRX of a previous DRX cycle of the current DRX cycle, and the configuration made by the network device regarding the relationship between

the detection result of the first signal or channel and whether to detect the second signal or channel; or

determining whether to detect the second signal or channel at a current paging occasion, according to the detection result of the first signal or channel at a specific time or time period before the current paging occasion and the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel.

6. The method according to any one of claims 1 to 5, wherein the second signal or channel is a physical downlink control channel PDCCH or paging signaling.

7. The method according to any one of claims 1 to 6, wherein the method further comprises:

receiving configuration information sent by the network device, wherein the configuration information is used to configure the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel.

8. The method according to claim 7, wherein the configuration information is carried in a system message, radio resource control RRC dedicated signaling, PDCCH signaling, or a media access control MAC control element CE.

9. The method according to any one of claims 1 to 8, wherein the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel comprises a first configuration; wherein

the first configuration is used to indicate that detection of the second signal or channel is performed when the first signal or channel is not detected.

10. The method according to claim 9, wherein the first configuration is further used to indicate that detection of the second signal or channel is performed when the first signal or

channel is detected and a first field of the first signal or channel carries a first value; or that detection of the second signal or channel is not performed when the first signal or channel is detected and the first field of the first signal or channel carries a second value.

11. The method according to any one of claims 1 to 8, wherein the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel comprises a second configuration; wherein

the second configuration is used to indicate that detection of the second signal or channel is not performed when the first signal or channel is not detected.

12. The method according to claim 11, wherein the second configuration is further used to indicate that detection of the second signal or channel is performed when the first signal or channel is detected and a second field of the first signal or channel carries a third value; or that detection of the second signal or channel is not performed when the first signal or channel is detected and the second field of the first signal or channel carries a fourth value.

13. The method according to claim 1, wherein the method further comprises:

determining whether to detect the second signal or channel according to a preset rule when the first signal or channel is detected; wherein the preset rule is used to indicate that detection of the second signal or channel is performed when the second field of the first signal or channel carries a fifth value; or that detection of the second signal or channel is not performed when the second field of the first signal or channel carries a sixth value.

14. The method according to any one of claims 1 to 13, wherein the first signal or channel is a specific signal sequence, or is a physical channel.

15. A wireless communication method, comprising:

determining configuration information, wherein the configuration information is used to indicate a configuration of a relationship between a detection result of a first signal or

channel performed by a terminal device and whether to detect a second signal or channel; and

sending the configuration information to the terminal device.

16. A terminal device, comprising a communication unit and a processing unit, wherein:

the communication unit is configured to detect a first signal or channel sent by a network device; and

the processing unit is configured to determine whether to detect a second signal or channel according to a detection result of the first signal or channel and a configuration made by the network device regarding a relationship between the detection result of the first signal or channel and whether to detect the second signal or channel.

17. The terminal device according to claim 16, wherein the processing unit is further configured to:

determine whether to detect the second signal or channel at a specific detection time period or a specific detection time point according to the detection result of the first signal or channel and the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel.

18. The terminal device according to claim 17, wherein the specific detection time period or the specific detection time point is at least one detection time period or time point in periodic detection time periods or time points.

19. The terminal device according to claim 18, wherein the specific detection time period or the specific detection time point is an on duration in a discontinuous reception DRX cycle; or, the specific detection time point is at least one paging occasion in periodic paging occasions.

20. The terminal device according to claim 19, wherein the processing unit is further configured to:

determine whether to detect the second signal or channel in the on duration of a current DRX cycle, according to the detection result of the first signal or channel at a specific time or time period in an opportunity for DRX of a previous DRX cycle of the current DRX cycle and the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel; or

determine whether to detect the second signal or channel at a current paging occasion according to the detection result of the first signal or channel at a specific time or time period before the current paging occasion and the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel.

21. The terminal device according to any one of claims 16 to 20, wherein the second signal or channel is a physical downlink control channel PDCCH or paging signaling.

22. The terminal device according to any one of claims 16 to 21, wherein the communication unit is further configured to:

receive configuration information sent by the network device, wherein the configuration information is used to configure the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel.

23. The terminal device according to claim 22, wherein the configuration information is carried in a system message, radio resource control RRC dedicated signaling, PDCCH signaling, or a media access control MAC control element CE.

24. The terminal device according to any one of claims 16 to 23, wherein the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel comprises a first configuration; wherein

the first configuration is used to indicate that detection of the second signal or channel is

performed when the first signal or channel is not detected.

25. The terminal device according to claim 24, wherein the first configuration is further used to indicate that detection of the second signal or channel is performed when the first signal or channel is detected and a first field of the first signal or channel carries a first value; or that the detection of the second signal or channel is not performed when the first signal or channel is detected and a first field of the first signal or channel carries a second value.

26. The terminal device according to any one of claims 16 to 25, wherein the configuration made by the network device regarding the relationship between the detection result of the first signal or channel and whether to detect the second signal or channel comprises a second configuration; wherein

the second configuration is used to indicate detection of the second signal or channel is not performed when the first signal or channel is not detected.

27. The terminal device according to claim 26, wherein the second configuration is further used to indicate that detection of the second signal or channel is performed when the first signal or channel is detected and a second field of the first signal or channel carries a third value; or that detection of the second signal or channel is not performed when the first signal or channel is detected and the second field of the first signal or channel carries a fourth value.

28. The terminal device according to claim 16, wherein the processing unit is further configured to:

determine whether to detect the second signal or channel according to a preset rule when the communication unit detects the first signal or channel; wherein, the preset rule is used to indicate that detection of the second signal or channel is performed when the second field of the first signal or channel carries a fifth value; or that detection of the second signal or channel is not performed when the second field of the first signal or channel carries a sixth value.

29. The terminal device according to any one of claims 16 to 28, wherein the first signal or channel is a specific signal sequence or a physical channel.

30. A network device, comprising a processing unit and a communication unit, wherein:

the processing unit is configured to determine configuration information, wherein the configuration information is used to indicate a configuration of a relationship between a detection result of a first signal or channel performed by a terminal device and whether to detect a second signal or channel; and

the communication unit is configured to send the configuration information to the terminal device.