WELLHEAD ASSEMBLY HAVING SEAL ASSEMBLY WITH AXIAL RESTRAINT

BACKGROUND

[0001] The invention relates generally to seal assemblies for use in sealing components of oil and gas wells. In particular, the invention relates to a seal assembly for a casing hanger or a tubing hanger of a wellhead, the seal assembly having a system for axially restraining the seal assembly within the wellhead and a method for installing the seal assembly in the wellhead.

[0002] Casing is strong steel pipe that is used in an oil and gas well to ensure a pressure-tight connection from the surface to the oil and/or gas reservoir. Casing serves many purposes in the well. It can protect the wellbore from caving in or being washed out. It can also confine production to the wellbore, so that water does not intrude into the wellbore or drilling mud intrude into the surrounding formations. It can also provide an anchor for the components of the well. Production tubing, such as coiled tubing, typically is used to transport oil to the surface.

[0003] Several sections of casing joined together end-to-end are known as a "casing string." Because casing serves several different purposes, it is typical to install more than one casing string in a well. Casing strings typically are run in a concentric arrangement, similar to an upside-down wedding cake, which extends downward into the ground from a wellhead located at the surface. For example, the casing string with the greatest diameter is the shortest, followed by smaller diameter casing string which goes deeper than the first casing string, followed by an even smaller diameter casing string that is run even deeper than the second casing string.

[0004] A casing hanger is a device that is used to support a casing string from a wellhead or other structure within the well. In addition, the casing hanger serves to ensure that the casing is properly located in the well. When the casing string has been run into the wellbore, the casing string is hung, or suspended, in the well by the casing

hanger. Typically, the casing hanger rests on a landing shoulder inside the wellhead. Multiple casing hangers may be supported within a single wellhead.

[0005] Seals are used to seal the annulus between the casing hanger and the wellhead to isolate fluids in different casing strings from each other and to prevent production fluid from being diverted from its desired path. However, forces in the well may be produced that urge the seals upward, potentially causing the seals to leak. This also may lead to the seal unseating and moving relative to the casing hanger or tubing hanger. For example, fluid pressure in the annulus may urge the seal upward or downward. Similarly, thermal conditions in the annulus may exert forces that urge the seal upward.

[0006] One method that has been attempted to restrain axial movement of the casing hanger seal and casing hanger is by installing a latch ring on the casing hanger. The latch ring extends between the casing hanger and wellhead. The latch ring is activated by the installation of the seal. Unfortunately, a latch ring that is installed on a casing hanger will restrict the flow of fluid in the annulus surrounding the casing hanger during cementing operations. The casing string is cemented in position within the wellbore of the well. Cement is poured down the interior of the casing string and flows out the bottom of the casing string into the annulus between the casing string and its nearest concentric drill string. Fluid in the annulus is displaced upward through the annulus. The casing hanger latch ring interferes with the flow of this fluid.

[0007] Another method that has been used to restrain axial movement of the casing hanger and casng hanger seal is the use of wickers. Wickers are located on the outer surface of the casing hanger and inner surface of the casing hanger seal. Similar wickers are located on the outer surface of the casing hanger seal and the inner surface of the wellhead. The seal material is softer than the wellhead and casing hanger materials. When the seal is activated, the softer material of the seal is driven into the wickers of the casing hanger and wellhead. The engagement between the various wickers limits axial movement of the casing hanger and casing hanger seal relative to the wellhead. However, there are physical limits to the pressures and

thermal conditions that this wicker configuration can be used to provide axial restraint. These physical limits may be exceeded with the higher pressures and temperatures associated with deepwater subsea wells.

[0008] Sill another method that may be used is to provide a separate lockdown sub dedicated to providing axial restraint for the casing hanger seal and casing hanger. However, the installation of a lockdown sub requires an additional trip of the drill string into and out of the well, a considerable expense. In addition, the lockdown sub occupies space, which is limited in a wellhead. Finally, the lockdown sub does not provide the axial restriant immediately upon installation of the casing hanger and casing hanger seal.

[0009] Therefore, an improved technique for preventing axial movement of a casing hanger and casing hanger seal within a wellhead is needed. In particular, a technique is needed to prevent axial movement of a casing hanger or tubing hanger seal within a wellhead immediately upon installation of the casing hanger and casing hanger seal, without interfering with the flow of fluids in the annulus surrounding the casing hanger during cementing operations, without occupying additional space in the wellhead, or requiring additional trips into the well.

BRIEF DESCRIPTION

[0009a] According to one aspect, there is provided a wellhead assembly, comprising: a housing, comprising an inner bore and an inner profile disposed around a portion of the inner bore of the housing; and a seal assembly adapted to form a seal between a tubular member and the housing, the seal assembly, comprising: a seal member; an energizing ring adapted to be driven into the seal member to expand the seal member into sealing engagement with an inner surface of the housing and an outer surface of the tubular member; a latch ring secured to and carried by the seal member and axially movable relative to the seal member and the tubular member, wherein the latch ring is adapted to be driven outward into the inner profile of the housing, whereupon axial movement of the seal assembly is restricted by abutment between the latch ring and the inner profile of the housing; and wherein the tubular member comprises a tapered shoulder and the latch ring comprises a first tapered surface, the tapered shoulder of the tubular member and the first tapered surface of the latch ring being adapted to

cooperate to drive the latch ring outward when the seal assembly and the tubular member abut.

[0009b] According to another aspect, there is provided a wellhead assembly, comprising: a housing, comprising an inner bore and an inner profile disposed around a portion of the inner bore of the housing; a seal assembly adapted to form a seal between a tubular member and the housing, the seal assembly comprising: a seal member; an energizing ring adapted to be driven into the seal member to expand the seal member into sealing engagement with an inner surface of the housing and an outer surface of the tubular member; and a latch ring secured to the seal member and axially movable relative to the seal member, wherein the latch ring is adapted to be driven outward into the inner profile of the housing, whereupon axial movement of the seal assembly is restricted by abutment between the latch ring and the inner profile of the housing; wherein the tubular member comprises a tapered shoulder and the latch ring comprises a first tapered surface, the tapered shoulder of the tubular member and the first tapered surface of the latch ring being adapted to cooperate to drive the latch ring outward when the seal assembly and the tubular member abut; wherein the seal assembly comprises a nose ring having a tapered surface and the latch ring comprises a second tapered surface, the tapered surface of the nose ring and the second tapered surface of the latch ring being adapted to cooperate to drive the latch ring outward when the seal assembly is abutted against the tubular member; and wherein the latch ring comprises a first catch surface and the nose ring comprises a second catch surface, the first catch surface and second catch surface being adapted to cooperate to lift the latch ring when the nose ring is lifted from the housing during removal of the seal assembly.

[0010] Herein disclosed is a wellhead system comprising a seal with a movable restraining member adapted to cooperate with a housing to restrict axial movement of the seal. The seal is adapted to form a seal between the housing, such as a high pressure wellhead, and a tubular member, such as a casing hanger. The restraining member may be a ring that is expanded outward as the seal is installed within the wellhead. The ring may have a split to facilitate the expansion of the ring outward. In addition, the ring may be adapted with a tapered surface that slidingly engages a corresponding tapered surface on the hanger as the seal is installed within the wellhead. The sliding engagement of the tapered surfaces cooperates to urge the restraining member outward. In addition, the corresponding tapered surface may be a shoulder of the tubular member. The seal

may have an additional ring with a tapered surface that is adapted to cooperate with a second tapered surface of the restraining member to provide additional mechanical advantage to expand the restraining member outward when the seal is installed in the wellhead.

[0011] The restraining member and the housing may be adapted so that a portion of the seal is received by at least one recess in the inner profile of the housing when the restraining member is expanded outward. The portion of the seal that is received in the at least one recess may be one or more projections extending from the ring. The projections may engage the at least one recessed in the housing upon installation. Alternatively, the projections may engage the at least one recess in the housing after axially traveling a distance, enabling the seal to have some axial movement relative to the wellhead.

DRAWINGS

[0012] These and other features, aspects, and advantages of the present invention will become better understood when the following detailed description is read with reference to the accompanying drawings in which like characters represent like parts throughout the drawings, wherein:

[0013] FIG. 1 is a cross-sectional view of a wellhead assembly, in accordance with an exemplary embodiment of the present technique;

[0014] FIG. 2 is a detailed view of a first casing hanger seal of the wellhead assembly of FIG. 1, in accordance with an exemplary embodiment of the present technique;

[0015] FIG. 3 is a perspective view of the first casing hanger seal, in accordance with an exemplary embodiment of the present technique;

[0016] FIG. 4 is an elevation view of the first casing hanger seal of FIG. 3, in accordance with an exemplary embodiment of the present technique;

[0017] FIG. 5 is a cross-sectional view of the first casing hanger seal assembly of FIG. 4, in accordance with an exemplary embodiment of the present technique;

[0018] FIG. 6 is a bottom view of the latch ring of the first casing hanger seal assembly of FIG. 4, in accordance with an exemplary embodiment of the present technique;

[0019] FIG. 7 is a detailed view of an additional casing hanger seal of the wellhead assembly of FIG. 1, in accordance with an exemplary embodiment of the present technique;

[0020] FIG. 8 is a partial cross-sectional view of the high pressure wellhead, first casing hanger, first casing hanger seal, and a setting tool for installing the casing hanger and casing hanger seal during the running of the casing hanger and casing hanger seal into the well, in accordance with an exemplary embodiment of the present technique;

[0021] FIG. 9 is a detailed view of the wellhead, casing hanger, and casing hanger seal of FIG. 8, in accordance with an exemplary embodiment of the present technique;

[0022] FIG. 10 is a partial cross-sectional view of the high pressure wellhead, first casing hanger, first casing hanger seal, and the setting tool during the casing hanger seal installation with the latch ring of the casing hanger seal landed on a shoulder of the casing hanger, in accordance with an exemplary embodiment of the present technique;

[0023] FIG. 11 is a detailed view of the wellhead, casing hanger, and casing hanger seal of FIG. 10, in accordance with an exemplary embodiment of the present technique;

[0024] FIG. 12 is a partial cross-sectional view of the high pressure wellhead, first casing hanger, first casing hanger seal, and the setting tool during the casing hanger seal installation with the latch ring of the casing hanger seal driven outward into the wellhead, in accordance with an exemplary embodiment of the present technique;

[0025] FIG. 13 is a detailed view of the wellhead, casing hanger, and casing hanger seal of FIG. 12, in accordance with an exemplary embodiment of the present technique;

[0026] FIG. 14 is a partial cross-sectional view of the high pressure wellhead, first casing hanger, first casing hanger seal, and the setting tool during the casing hanger seal installation with the energizing ring of the casing hanger seal driven into the seal ring of the casing hanger seal to activate the casing hanger seal to seal the annulus between the casing hanger and high pressure wellhead, in accordance with an exemplary embodiment of the present technique; and

[0027] FIG. 15 is a detailed view of the wellhead, casing hanger, and casing hanger seal of FIG. 14, in accordance with an exemplary embodiment of the present technique.

DETAILED DESCRIPTION

[0028] Referring now to FIG. 1, the present invention will be described as it might be applied in conjunction with an exemplary technique, in this case a wellhead assembly for directing oil and/or gas from a well to transmission pipelines or a storage facility, as represented generally by reference numeral (20).

[0029] The wellhead assembly (20) comprises a low pressure wellhead 22 and a high pressure wellhead (24). In the illustrated embodiment, the high pressure wellhead (24) supports three casing hangers: a first casing hanger (26), a second casing hanger (28), and a third casing hanger (30) within an inner bore (32) of the wellhead (24). However, the high pressure wellhead (24) may be used to support a greater or lesser number of casing hangers. The first casing hanger (26), second casing hanger (28), and third casing hanger (30) support casing strings (34, 36, and 38), respectively.

[0030] The annulus between the first casing hanger (26) and the high pressure wellhead (24) is sealed by a first casing hanger seal (40). Similarly, the annulus between the wellhead (24) and the second casing hanger (28) is sealed by a second

casing hanger seal (42). Finally, the annulus between the third casing hanger (30) and the high pressure wellhead (24) is sealed by a third casing hanger seal (44). In the illustrated embodiment, the first casing hanger seal (40) and second casing hanger seal (42) are identical. However, the third casing hanger seal (44) differs from the first and second casing hanger seals (40), (42).

[0031] As will be discussed in more detail below, the high pressure wellhead (24) and each of the casing hanger seals are adapted to cooperate to restrict axial movement of the casing hanger seals and the casing hangers within the high pressure wellhead (24). In particular, each of the casing hanger seals is adapted with a latch ring that is expanded outward into a corresponding profile in the inner bore (32) of the high pressure wellhead (24). Forces that urge a casing hanger seal upward or downward are opposed by engagement between the latch ring of the casing hanger seal and the high pressure wellhead (24).

[0032] Referring generally to FIG. 2, the first casing hanger seal (40) comprises a seal ring (46), an energizing ring (48), a nose ring (50), and a latch ring (52). The energizing ring (48) is used to drive the seal ring (46) outward into sealing engagement with the high pressure wellhead (24) and the first casing hanger (26). The energizing ring (48) has a lower portion (54) that is driven into a slot 56 in the seal ring (46) to activate the seal. As the lower portion (54) of the energizing ring (48) is driven into the slot 56 in the seal ring, it elastically deforms an inner leg (58) of the seal ring (46) inward into engagement with the first casing hanger (26) and an outer leg 60 of the seal ring (46) outward into engagement with the wellhead (24).

[0033] In the illustrated embodiment, the casing hanger seal (40) has a series of wickers (62) that engage corresponding wickers (64) on the first casing hanger (26) to form a seal between the first casing hanger (26) and the first casing hanger seal (40). In the illustrated embodiment, the material of the first casing hanger seal (40) is softer than the material of the first casing hanger (26) so that the casing hanger seal wickers (62) deform into the wickers (64) of the first casing hanger (26), enhancing the seal between the first casing hanger (26) and the first casing hanger seal (40). In addition, the engagement of the wickers (62), (64) restricts axial movement of the first casing

hanger (26) relative to the first casing hanger seal (40). In the illustrated embodiment, the outer leg (60) of the seal ring (46) has inlays (66) that are driven against the wellhead (24) to form a seal between the first casing hanger seal (40) and the wellhead (24). The inlays (66) are adapted to maintain a seal between the first casing hanger seal (40) and the wellhead (24) even if there is some axial movement of the first casing hanger seal (40) relative to the wellhead (24).

[0034] As will be discussed in more detail below, the first casing hanger (26) and the first casing hanger seal (40) are installed in the wellhead (24) by a setting tool (not shown). In addition, the setting tool is used to drive the energizing ring 48 downward into the seal ring (46) to activate the first casing hanger seal (40) in the wellhead (24).

[0035] The illustrated embodiments of the first casing hanger seal (40) and the wellhead (24) restrict axial movement of the first casing hanger seal (40) to a small amount relative to the wellhead (24). The restriction of the axial movement of the first casing hanger seal (40) relative to the wellhead (24) is achieved by the engagement of the latch ring (52) of the first casing hanger seal (40) with the inner profile of the wellhead (24). As will be discussed in more detail below, the latch ring (52) is split, or may have a notch to allow the latch ring (52) to split during installation. The latch ring (52) of the first casing hanger seal (40) is biased inward to maintain the latch ring (52) as a closed ring during installation. However, as will be discussed in detail below, the latch ring (52) is driven outward into recesses in the wellhead (24) as the first casing hanger seal (40) is installed in the wellhead (24). The latch ring (52) thereby becomes a C-ring.

[0036] The axial movement of the first casing hanger seal (40) relative to the wellhead (24) is restricted by engagement between a first projection 68 and a second projection (70) of the seal (40) with a first recess (72) and a second recess (74), respectively, in the profile of the inner bore (32) of the wellhead (24). In the illustrated embodiment, there is a gap (76) between the first projection 68 of the seal (40) and an upper edge (78) of the first recess (72). Similarly, there is a gap (80) between the second projection (70) of the seal (40) and the upper edge (82) of the second recess (74) in the wellhead (24). The gaps (76), (80) between the latch ring

(52) and the upper edges (78), (82) of the recesses (72), (74) of the wellhead allow some upper axial movement of the seal (40) relative to the wellhead (24). However, upward axial movement of the first casing hanger seal (40) is limited by engagement between the first projection (68) of the seal (40) and the upper edge (78) of the first recess (72) of the wellhead (24). In addition, upward axial movement of the seal (40) is restricted by engagement between the second projection (70) of the seal (40) and the upper edge (82) of the second recess (74) of the wellhead (24). Similar gaps are present below the projections (68, 70). Downward axial movement of the seal (40) is limited by engagement between the projections (68, 70) of the seal (40) and the lower edges of the recesses (72), (74) of the wellhead (24).

[0037] The first projection (68) and second projection (70) of the latch ring (52) are driven into the first recess (72) and second recess (74) of the wellhead (24) during the installation of the first casing hanger seal (40) into the wellhead (24). As the latch ring (52) of the first casing hanger seal (40) is lowered into the wellhead (24), a downward-facing tapered surface (84) of the seal (40) engages an upward-facing tapered shoulder (86) of the first casing hanger (26). The engagement between the downward-facing tapered surface (84) of the latch ring (52) of the seal (40) and the upward-facing tapered shoulder (86) of the first casing hanger (26) as the seal (40) is lowered further into the wellhead (24) drives the latch ring (52) outward. In addition, the latch ring (52) has an inward-facing tapered surface (88) that engages an outward–facing tapered surface (90) of the nose ring (50). The engagement of the inward-facing tapered surface (88) of the latch ring (52) with the outward–facing tapered surface (90) of the nose ring (50) provides additional mechanical advantage to overcome the inward bias of the latch ring (52) and drive the latch ring (52) outward. The outward movement of the latch ring (52) is limited by engagement between a stop portion (92) of the latch ring (52) and a corresponding stop portion (94) of the wellhead (24). The engagement of the stop portion (92) of the latch ring (52) with the stop portion (94) of the wellhead (24) position the projections 68, 70 of the latch ring (52) at a desired position within the recessed profiles (72), (74) of the wellhead (24).

[0038] The latch ring (52) of the first casing hanger seal (40) is removed with the seal (40) when the seal is removed from the wellhead (24). The energizing ring 48 of the seal (40) is withdrawn from the seal ring 46 of the seal (40) to enable the inner leg 58 and the outer leg (6)0 of the seal ring (46) to relax and withdraw to their original shape, disengaging the seal ring (46) from the first casing hanger (26) and the wellhead (24), respectively. The latch ring (52) has a first catch surface (96) that extends over a corresponding second catch surface (98) of the nose ring (50). During removal of the first casing hanger seal (40), the second catch surface (98) of the nose ring (50) engages the first catch surface (96) of the latch ring (52), lifting the latch ring (52) upward. Thus, the axial restraint for the first casing hanger seal (40) is removed on the same trip as the first casing hanger seal (40) is removed. Therefore, removal of the axial restraining member of the casing hanger and/or seal does not require an additional trip into the well to remove. In addition, the cooperation of the first catch surface (96) and second catch surface (98) secures the latch ring (52) to the nose ring (50).

[0039] Referring generally to FIGS. 3-5, various views of the first casing hanger seal (40) are presented. As discussed above, the seal ring (46) is activated by driving the energizing ring 48 into the seal ring (46). An upper ring (99) is threaded to the seal ring (46). The upper ring (99) has a first pair of notches (100) and the energizing ring 48 has a second pair of notches (102) that are used by the setting tool to engage the energizing ring 48 and the seal ring (46). As best illustrated in FIG 5, the upper ring (99) and the seal ring (46) have threaded portions (104, 106,) respectively.

[0040] As best seen in FIGS. 4 and 5, the seal ring (46) has a port 108 and the energizing ring 48 has a channel 110 that enable pressure to equalize within the seal (40), preventing hydraulic lock when the energizing ring 48 is driven into the seal ring (46). Prior to installation, the slot 56 in the seal ring (46) may be filled with grease. The port 108 and channel 110 enable the grease, and any other fluids, within the slot 56 to equalize between the inside of the seal (40) and the outside of the seal (40) as the lower portion (54) of the energizing ring 48 is driven into the slot 56 of the seal

ring (46). As a result, there is no build-up of pressure in the slot 56 or the outside of the seal (40).

[0041] Referring generally to FIGS. 5 and 6, the illustrated embodiment of the latch ring (52) has a split (112) that enables the latch ring (52) to expand as it is driven outward during installation. Alternatively, the latch ring (52) may be notched so that there is a weakened region in the latch ring (52) that splits as the latch ring (52) is urged outward upon engagement with the shoulder of the casing hanger.

[0042] Referring generally to FIG. 7, the third casing hanger (30) and third casing hanger seal (44) are presented. In contrast to the first casing hanger seal (40), the third casing hanger seal (44) has inlays (114) on its inner leg (116) and wickers (118) on its outer leg (120). Corresponding wickers (122) on the wellhead (24) are provided to engage the wickers (118) on the third casing hanger seal (44). The inlays (114) enable relative movement between the third casing hanger (30) and the third casing hanger seal (44). The engagement of the wickers (118), (122) forms a seal between the third casing hanger seal (44) and the wellhead (24), as well as restricting axial movement of the third casing hanger seal (44) relative to the wellhead (24).

[0043] In the illustrated embodiment, the third casing hanger seal (44) has an alternative embodiment of a latch ring (1(24)). The latch ring (1(24)) has a series of teeth (126) that are driven into a corresponding toothed profile (128) in the inner bore (32) of the wellhead (24). Here, the teeth 1(26) are driven into engagement with the toothed profile (128) in the wellhead (24), preloading the latch ring (1(24)) with the wellhead (24). Any upward or downward force on the third casing hanger seal (44) is opposed by engagement between the latch ring (1(24)) and the wellhead (24). Installation and removal of the third casing hanger (30) and third casing hanger seal (44) is the same as for the first casing hanger (26) and first casing hanger seal (40).

[0044] Referring generally to FIGS. 8-15, the process of installing a casing hanger and casing hanger seal is presented. The casing hanger and casing hanger seal are installed within the wellhead (24) as a pair by a setting tool (130). The setting tool (130) has a connector (132) for connecting the setting tool (130) to a drill string. In

addition, the setting tool (130) has a casing hanger handling member (134) that is used to install the casing hanger and a casing hanger seal handling member (136) that is used to install the casing hanger seal. The casing hanger handling member (134) and casing hanger seal handling member (136) are configured to enable relative movement between them.

[0045] Referring generally to FIGS. 8 and 9, the setting tool (130) positions the first casing hanger seal (40) above the first casing hanger (26) as the two are lowered into the wellhead (24). The first casing hanger (26) may be landed on a shoulder of the wellhead (24) or another casing hanger. Once the first casing hanger (26) is in a desired position within the wellhead (24), the first casing string (34) is cemented into place. Cement is pumped down through the center of the first casing string (34) and flows upward in the annulus between the first casing string (34) and an adjacent outer casing string (not shown).

[0046] As best illustrated in FIG. 9, there is a free flow path 138 for cement and other well fluids to flow upward from below the first casing hanger (26) through the annulus between the first casing hanger seal (40) and the first casing hanger (26) during the cementing operations because the axial restraint for the first casing hanger (26) and first casing hanger seal (40) is provided on the first casing hanger seal (40), rather than on the first casing hanger (26). If the axial restraint was provided by a restraining member disposed between the first casing hanger (26) and the wellhead (24), the restraining member would interfere with the flow of fluids flowing up the wellbore from below the first casing hanger (26).

[0047] Referring generally to FIGS. 10 and 11, the drill string is used to lower the setting tool (130) still further into the wellhead (24), as represented generally by arrow (140), to install the first casing hanger seal (40) in the desired position within the wellhead (24). The casing hanger handling member (134), which is secured to the first casing hanger (26), remains stationary while the casing hanger seal handling member 136 of the setting tool (130) is lowered with the first casing hanger seal (40).

[0048] In the view presented in FIG. 11, the downward-facing tapered surface 84 of the latch ring (52) has just contacted the shoulder 86 of the first casing hanger (26) during the process of installing the first casing hanger seal (40). The latch ring (52) has not yet been driven outward at this point of the casing hanger seal installation process. In addition, this view enables the releasable dogs (142 of the setting tool (130) to be seen. The releasable dogs (142) are used to secure the casing hanger handling member (134) to the first casing hanger (26), as well as the second and third casing hangers (28, 30).

[0049] Referring generally to FIGS. 12 and 13, the continued downward movement of the drill string lowers the casing hanger seal handling member 136 of the setting tool (130) further into the wellhead (24), as represented generally by arrow 144. This downward movement drives the latch ring (52) of the first casing hanger seal (40) outward, as represented by arrow (146), into the recessed profiles (72), (74) of the wellhead (24). As noted above, the stop portion (92) of the latch ring (52) abuts the stop portion (94) of the wellhead (24) to end the outward movement of the latch ring (52). This positions the projecting members (68, 70) of the latch ring (52) at the desired depth within the recessed portions (72), (74) of the wellhead (24).

[0050] Referring generally to FIGS. 14 and 15, the setting tool (130) is then used to drive the energizing ring (48) downward relative to the seal ring (46) to activate the seal ring (46), as represented by arrow (148), forming a seal between the first casing hanger (26) and the wellhead (24). The lower portion (54) of the energizing ring (48) is driven into the slot (56) of the seal ring (46). The inner leg (58) of the seal ring (46) is driven against the first casing hanger (26) and the outer leg (60) is driven against the wellhead (24), sealing the annulus between the first casing hanger (26) and the wellhead (24).

[0051] The process is reversed to remove the first casing hanger (26) and the first casing hanger seal (40). The setting tool (10) or another tool is used to apply a force to withdraw the energizing ring (48)

[0052] from the seal ring (46). The first casing hanger seal (40) is then lifted. The latch ring (52) is lifted with the other portions of the first casing hanger seal (40) as the seal (40) is lifted from the wellhead (24). In addition, the latch ring (52) is withdrawn from the recessed profiles (72), (74) as the latch ring (52) is lifted.

[0053] While only certain features of the invention have been illustrated and described herein, many modifications and changes will occur to those skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

The invention claimed is:

1. A wellhead assembly, comprising:

a housing, comprising an inner bore and an inner profile disposed around a portion of the inner bore of the housing; and

a seal assembly adapted to form a seal between a tubular member and the housing, the seal assembly, comprising:

a seal member;

an energizing ring adapted to be driven into the seal member to expand the seal member into sealing engagement with an inner surface of the housing and an outer surface of the tubular member;

a latch ring secured to and carried by the seal member and axially movable relative to the seal member and the tubular member, wherein the latch ring is adapted to be driven outward into the inner profile of the housing, whereupon axial movement of the seal assembly is restricted by abutment between the latch ring and the inner profile of the housing; and

wherein the tubular member comprises a tapered shoulder and the latch ring comprises a first tapered surface, the tapered shoulder of the tubular member and the first tapered surface of the latch ring being adapted to cooperate to drive the latch ring outward when the seal assembly and the tubular member abut.

2. The wellhead assembly as recited in claim 1, wherein the latch ring is a split ring.

3. The wellhead assembly as recited in claim 1, wherein the seal assembly comprises a nose ring having a tapered surface and the latch ring comprises a second tapered surface, the tapered surface of the nose ring and the second tapered surface of the latch ring being adapted to cooperate to drive the latch ring outward when the seal assembly is abutted against the tubular member.

4. The wellhead assembly as recited in claim 3, wherein the latch ring comprises a first catch surface and the nose ring comprises a second catch surface, the first catch surface and second catch surface being adapted to cooperate to lift the latch ring when the nose ring is lifted from the housing during removal of the seal assembly.

5. The wellhead assembly as recited in claim 1, wherein the tapered shoulder comprises an upward-facing tapered surface.

6. The wellhead assembly as recited in claim 5, wherein the first tapered surface of the latch ring comprises a downward-facing tapered surface.

7. The wellhead assembly as recited in claim 1, wherein the seal assembly comprises a first series of wickers and the tubular member comprises a second series of wickers, the first series of wickers being urged against the second series of wickers when the seal member engages the tubular member.

8. A wellhead assembly, comprising:

a housing, comprising an inner bore and an inner profile disposed around a portion of the inner bore of the housing;

a seal assembly adapted to form a seal between a tubular member and the housing, the seal assembly comprising:

a seal member;

an energizing ring adapted to be driven into the seal member to expand the seal member into sealing engagement with an inner surface of the housing and an outer surface of the tubular member; and

a latch ring secured to the seal member and axially movable relative to the seal member, wherein the latch ring is adapted to be driven outward into the inner profile of the housing, whereupon axial movement of the seal assembly is restricted by abutment between the latch ring and the inner profile of the housing;

wherein the tubular member comprises a tapered shoulder and the latch ring comprises a first tapered surface, the tapered shoulder of the tubular member and the first tapered surface of the latch ring being adapted to cooperate to drive the latch ring outward when the seal assembly and the tubular member abut;

wherein the seal assembly comprises a nose ring having a tapered surface and the latch ring comprises a second tapered surface, the tapered surface of the nose ring and the second tapered surface of the latch ring being adapted to cooperate to drive the latch ring outward when the seal assembly is abutted against the tubular member; and

wherein the latch ring comprises a first catch surface and the nose ring comprises a second catch surface, the first catch surface and second catch surface being adapted to

cooperate to lift the latch ring when the nose ring is lifted from the housing during removal of the seal assembly.

WELLHEAD ASSEMBLY HAVING SEAL ASSEMBLY WITH AXIAL RESTRAINT

ABSTRACT

A wellhead system (20) comprising a seal (40) with a restraining member (52, 124) adapted to cooperate with a housing (24) to restrict axial movement of the seal (40). The seal (40) is adapted to form a seal between the housing (24), such as a wellhead, and a tubular member (26), such as a casing hanger. The seal (40) has a latch ring (52, 124) that is expanded outward as the seal (40) is installed within the wellhead. Axial movement of the seal (40) is restricted by engagement between the expanded latch ring (52, 124) and the inner profile (32) of the housing (24). The seal (40) and housing (26) may be adapted so that a portion of the seal is received by a recess (72, 74, 128) in the inner profile (32) of the housing (24).

Fig. 1