

Payload Dispensing System

Field of the Invention

[0001] The present invention relates to earth-orbiting communication satellites, and, more particularly, a system and method for assembling and deploying multiple satellites from a launch vehicle.

Background of the Invention

[0002] Satellites, such as communications satellites, are typically placed in orbit via a multistage launch vehicle. The launch vehicle carries one or perhaps a few satellites to an insertion orbit at which point the satellites separate from the launch vehicle and fly to their final operational orbit.

[0003] A great deal of time is spent at the launch site to prepare a satellite for launch. In particular, with current practice, it takes a substantial amount of time to mount and integrate a single satellite into a launch vehicle. And for launches in which the launch vehicle will carry multiple satellites, that already-substantial amount of time is multiplied by the number of satellites that are being launched.

[0004] It is expected that satellite constellations having a very large number of satellites (> 500 satellites) will be deployed in the future. For such systems to be financially feasible, it will be necessary to launch a relatively large number of satellites (10-100) in a single launch vehicle. Due to the time issue raised above, in addition to any other constraints, new approaches for satellite launch must be developed. **FR 2 938 825 and EP 1 038 772 disclose payload dispensing systems.**

Summary of the Invention

[0005] The present invention provides a way to launch satellites that avoids some of the drawbacks of the prior art. In accordance with the illustrative embodiment, satellites are coupled to a payload dispensing system that, once populated with satellites, is placed in a launch vehicle.

coupled to a payload dispensing system that, once populated with satellites, is placed in a launch vehicle.

[0006] The payload dispensing system includes a payload dispenser and a plurality of rail assemblies. In the illustrative embodiment, the payload dispenser is a shell in the form of a cylindrical tube. Each rail assembly comprises two rails and a plurality of couplings attached thereto and arranged as cross-members, the rail assembly thus presenting a ladder-like form. The couplings facilitate: (1) coupling satellites to the rail assembly and (2) coupling the satellite-laden rail assembly to the payload dispenser.

[0007] Each rail assembly is capable of receiving multiple satellites and the shell is capable of accommodating a plurality of satellite-laden rail assemblies. In this manner, the payload dispenser is capable of accommodating many satellites.

[0008] In operation, plural satellites are loaded onto a rail assembly. Each satellite is coupled to the rail assembly by attaching two of the couplings (cross-members) to a panel of the satellite. In typical embodiments, as few as 2 and as many as 10 satellites are attached to each rail assembly.

[0009] The foregoing operation is the most time-intensive part of the pre-launch process. This operation can be performed at the satellite manufacturing facility, an integration facility adjacent to the launch site, or at some other convenient facility. Multiple teams of technicians can work on multiple rail assemblies at the same time. Because of this parallel approach to satellite-preloading and assuming that the manpower is available, it will take no more time to populate nine rail assemblies with satellites than it would take to populate a single rail assembly. Furthermore, to the extent there is a problem on a particular rail assembly, it will not slow the preloading process that is proceeding on other rail assemblies.

[0010] Once completed, the preloaded rail assemblies are transported to the launch site and coupled to the shell. Connecting the rail assemblies to the shell is a relatively quick process, since it simply requires bolting the rail assemblies thereto and performing connector mating operations, both of which can be accomplished quite efficiently. The payload dispenser,

now fully populated with satellites, is then placed in the region of the launch vehicle designated for the payload (*i.e.*, the volume defined within the payload fairings).

[0011] The cost and schedule savings realizable using the inventive system is substantial. Consider a launch vehicle —a rocket— that will be used to launch 36 satellites into orbit. Assume that integrating a single satellite to a common payload dispenser, in accordance with the prior art, typically takes a minimum of 4 hours. As a consequence, the methods of the prior-art will require: 36 satellites x 4 hours/satellite= 144 hours (6 days of round-the-clock effort) to fully populate the prior-art dispenser for launch.

[0012] In accordance with the present teachings, a payload dispenser is populated with 36 satellites by attaching four satellites to each of nine rail assemblies, and then attaching the rail assemblies to the shell. As previously noted, this can be performed at the satellite manufacturing facility. It is expected that attaching a populated rail assembly to the shell will take about half of the time (c.a., 2 hours) that it takes to attach a single satellite (to a payload dispenser) because of the simplified nature of the connections. Thus, using embodiments of the present invention, it would take only about 18 hours (<1 day) to fully populate the payload dispenser, which is 12.5% of the time it would take using prior art methods.

Brief Description of the Drawings

[0013] **FIG. 1** depicts a perspective view of a payload dispenser in accordance with the illustrative embodiment of the present invention.

[0014] **FIG. 2** depicts an exploded view of the payload dispenser.

[0015] **FIG. 3** depicts an illustrative embodiment of the rail assembly for use with the payload dispenser of FIG. 1.

[0016] **FIG. 4** depicts a perspective view of a coupling of the rail assembly of FIG. 3.

[0017] **FIG. 5** depicts the payload dispenser of FIG. 1 with rail assemblies coupled thereto.

[0018] **FIG. 6** depicts four satellites coupled to the rail assembly of FIG. 3.

[0019] **FIGs. 7A and 7B** depict respective side and top views of the payload dispenser being populated with satellites by coupling satellite-bearing rail assemblies to the payload dispenser of FIG. 1.

[0020] **FIGs. 8A and 8B** depict respective side and top views of a fully populated payload dispenser in the launch fairing of a launch vehicle.

[0021] **FIG. 9** depicts a method for preparing satellites for launch in accordance with an illustrative embodiment of the invention.

Detailed Description

[0022] Embodiments of the present invention can be used in conjunction with many types of satellites (*e.g.*, LEO, GEO, *etc.*). The satellite depicted in conjunction with the illustrative embodiment is an LEO communications satellite for internet communications, such as described in U.S. Pat. Appl. 14/673,170 filed March 30, 2015 and incorporated by reference herein.

[0023] **FIGs. 1 and 2** depict a perspective view and an “exploded” view, respectively, of payload dispenser **100** in accordance with the illustrative embodiment of the present invention. The salient features of payload dispenser **100** include: shell **102**, shell support braces **104**, and payload attach fitting **106**, configured as shown.

[0024] In the illustrative embodiment, shell **102** is in the form of a cylindrical tube. In some other embodiments, shell **102** has a different configuration (*e.g.*, an open-form cage, *etc.*). Shell **102** must be relatively light weight, capable of supporting plural satellites, and able to withstand extreme launch loads and vibration. To that end, shell **102** is formed from an appropriate material and, in some embodiments, is appropriately reinforced.

[0025] With regard to materials of construction, in some embodiments, shell **102** comprises a carbon-composite solid laminate, such as is formed, for example, using RS-36 epoxy with T700 carbon fiber, available from TenCate Advanced Composites of Almelo, Netherlands. Other

light-weight and suitably strong materials known in the aerospace or related arts may suitably be used.

[0026] In the illustrative embodiment, shell **102** is further strengthened by shell support braces **104**. These braces, which are disposed inside of shell **102**, ensure that shell **102** maintains its cross-sectional shape (*i.e.*, circular in the illustrative embodiment) under extreme loads and/or vibration, such as experienced during launch. An unbraced shell having a circular cross section might otherwise tend to ovalize under such conditions.

[0027] In the illustrative embodiment, shell support braces **104** are shaped like “wagon wheels,” having felloes **208**, spokes **210**, and hub **212**. This configuration provides excellent radial stiffness as a function of its weight and is therefore well suited for use as internal bracing for shell **102**. To perform its intended function, braces **104** have an outer diameter that is just slightly smaller (about 1 millimeter or less) than the inner diameter of shell **102**. In some embodiments, each shell support brace **104** comprises a carbon/aluminum honeycomb core with carbon fiber (*e.g.*, TenCate T700, *etc.*) facing.

[0028] Payload attach fitting (“PAF”) **106** couples payload dispenser **100** to the launch vehicle’s upper stage. In some embodiments, PAF **106** comprises a carbon composite solid laminate, such as quasi-isotropic T700 carbon fiber and RS-36 epoxy.

[0029] FIG. 3 depicts rail assembly **320**. In the illustrative embodiment, the rail assembly comprises two rails **322** that are parallel to one another and a plurality of couplings **324**. The couplings are arranged like rungs on a ladder. Referring now to FIG. 4 as well as FIG. 3, in the illustrative embodiment, each coupling **324** is attached to both of rails **322**. In the illustrative embodiment, two fasteners **428** are used to fasten each coupling **324** to the rails; however, more than two fasteners can be used. Cutouts **426** provide weight savings while keep the coupling stiff. In the illustrative embodiment, rails **322** are extruded aluminum and couplings **324** are machined billets of aluminum.

[0030] Two couplings **324** are used to attach a satellite to rail assembly **320**. Spacing D_1 between paired couplings **324** is a function of the size and design of the satellite being

launched. Spacing **D₂** between adjacent sets of paired couplings must be sufficient to accommodate any external features of the satellite, such as appended antennas, *etc.*

[0031] Opening **424** in each coupling **324** receives a fastening element (bolt, *etc.*) to attach rail assembly **320** to payload dispenser **100** at openings **110** after all satellites are coupled to the rail assembly. It will be appreciated that rail assembly **320** and shell **102** must be designed in concert with one another and in light of the payload (*i.e.*, the satellites), since the satellite dimensions and configuration will affect placement of couplings **324** and openings **110** in shell **102** must be appropriately placed to align with the couplings. Additional flexibility could be provided by using slots, rather than openings **110**, but the lack of positive support (*i.e.*, holes) for rail assemblies **320** might result in slippage of the satellite-laden rail assemblies under the launch loads.

[0032] Brackets (not depicted) connect a satellite separation system (not depicted) to couplings **324**. Satellite separation systems, which are well known to those skilled in the art, typically comprises either pyros (explosive bolts) or non-explosive release actuators, such as ERM actuators available from TiNi Aerospace of San Rafael, CA. Timing between satellite deployments can be controlled in a variety of ways, including, without limitation, a built-in time delay, an automatic deployment once the launch vehicle has moved to a new orientation, or manually commanded release from a control station on the ground.

[0033] FIG. 5 depicts payload dispenser **100** with rail assemblies **320** attached. It is to be understood that the rail assemblies **320** are typically attached to the payload dispenser only after satellites have been coupled to the rail assemblies. Rail assemblies **320** are shown coupled to the dispenser without any satellites attached for pedagogical purposes.

[0034] As depicted in FIG. 5, rail assemblies **320** are attached to payload dispenser **100** at openings **110**. A fastening element (bolt, *etc.*) extends through hole **430** in coupling **324** and passes through one of the openings **110** in shell **102**. In the illustrative embodiment, nine rail assemblies **320**, each having eight couplings **324**, are attached to the payload dispenser.

[0035] FIG. 6 depicts four satellites **600** attached to rail assembly **320**. Panel **601** of each satellite **600** couples to paired couplings **324** of the rail assembly.

[0036] FIGs. 7A and 7B depict respective end and side views of payload dispenser **100** having eight satellite-laden rail assemblies **320** attached thereto. A ninth rail assembly **320** having four satellites **600** attached (see also FIG. 6) is being coupled to the payload dispenser to fully populate it.

[0037] In some embodiments, a satellite-laden rail assembly **320** is attached to payload dispenser **100** as follows. The payload dispenser is supported horizontally via typical ground support equipment (not depicted) that enables it to be spun (in the manner of a rotisserie). A rail assembly **320** is positioned below dispenser **100**. A "row" (in the horizontal orientation) of holes **110** (see, e.g., FIGs 1 and 2) in shell **102** is moved into alignment with opening **430** in each coupling **324** in the rail assembly by rotating the payload dispenser. The satellite-laden rail assembly **320** is then lifted, as necessary, so the fastening element that was positioned in opening **430** (prior to attaching the satellites) extends through opening **110**. The fastener is fastened (e.g., using a nut and washer, etc.) by a technician, thereby securing rail assembly **320** to shell **102**. Technicians involved in this process are situated inside of shell **102**.

[0038] After a satellite-laden rail assembly **320** is attached to shell **102**, the shell is rotated and another satellite-laden rail assembly is moved into position for attachment to the shell. The process is repeated until all satellite-laden rail assemblies **320** are attached to payload dispenser **102**.

[0039] Depending on the launch vehicle being used, fully populated payload dispenser **100** is then either (1) bolted to into the payload region of a horizontal rocket that is then upended vertically or (2) the payload dispenser is tilted-up vertically and craned into position and situated in the payload volume of the upright launch vehicle.

[0040] It will be appreciated that the dimensions of payload dispenser **100** and the design of the rail assembly must be compatible with the satellites being launched as well as the launch vehicle being used.

[0041] FIGs. 8A and 8B depict fully populated payload dispenser **100** in the payload volume defined by payload fairing **850** (one-half of the fairing is removed in FIGs. 8A and 8B for clarity), which is located atop of a launch vehicle. Fairing **850** protects the satellites against aerodynamic, thermal and acoustic environments that the launch vehicle experiences during atmospheric flight. In the illustrative embodiment, there are nine rail assemblies **320**, each carrying four satellites **600**, for a total of thirty-six satellites coupled to payload dispenser **100**.

[0042] As best seen in FIG. 8A, the satellites present as being arranged in four “rings” **840A**, **840B**, **840C**, and **840D**. Although the rings do not have any physical significance, when the satellites are actually deployed, they are deployed ring-by-ring.

[0043] More particularly, after the launch vehicle has left the atmosphere, fairing **850** is jettisoned by pyrotechnically or hydraulically actuated systems. The fairing is typically composed of 2 “clamshell” halves. In some embodiments, the fairing-separation system includes longitudinal and lateral mechanical locks linked together by pushing rods and connected to pyro pushers. Four vertical jacks powered by a pyrotechnic gas generator are used to open and rotate the two fairing halves. Final jettisoning of the fairing halves is provided by lateral springs. Separation of the fairing occurs during second stage flight, after the launcher has left the dense portion of the atmosphere such that aerodynamic and thermal loads are at acceptable levels for the payload (*i.e.*, satellites).

[0044] With the fairing gone, the satellites can separate freely once in final position. A few (1-3) satellites, but not all satellites, from the same “ring” are deployed at a time. In various embodiments, a time delay and/or a change in the launch vehicle’s orientation or velocity is required between each subsequent satellite deployment.

[0045] *EXAMPLE.* Assume that a Soyuz 2 rocket is used as the launch vehicle and the satellites being launch are those described in U.S. Pat. Appl. 14/673,170. For this example, each satellite is assumed to have the following dimensions:

Bottom panel (which attaches to rail assembly): 0.5 meters x 0.8 meters

Height of satellite (from base to top of horn support web): 0.95 meters

Top panel: 0.8 meters x 0.8 meters

The approximate dimensions of the payload region of the Soyuz rocket are:

Height (including step): 5.4 meters

Diameter: 3.8 meters

[0046] Since the diameter of the payload region is 3.8 meters, the maximum allowable diameter of the satellite-laden payload dispenser **100** is about 3.7 meters, allowing about 50 millimeters clearance between the satellites and the payload fairing of the rocket on all sides. The diameter of the satellite-laden payload dispenser is approximately:

$$D = \text{diameter of shell } \mathbf{102} + 2 \times \text{height of the satellite}$$

Thus, diameter of shell **102** can be a maximum of about $3.7 - 2 \times 0.95 = 1.8$ meters. Shell **102** comprises a carbon-composite solid laminate (e.g., RS-36 epoxy with T700 carbon fiber) and has a wall thickness that tapers from a thickness of 3 millimeters at the top of shell **102** tube to 7 millimeters at the bottom thereof.

[0047] The height of shell **102** is not strictly limited by the height of straight region of the fairing. A height for the shell of about 5.1 meters is selected. Rail assembly **320** has a length that is no more than (and typically somewhat less than) the height of shell **102**. In this example, the length of rail assemblies **320** is about 4.7 meters. Each rail assembly **320** includes 8 couplings **324** for attaching four satellites to the rail assembly. Paired couplings are spaced apart by about 0.64 meters (center-to-center) and the distance between adjacent pairs of couplings is about 0.61 meters (center-to-center).

[0048] In a further aspect of the invention, FIG. 9 depicts method **900** for launching a plurality of satellites. Per operation **901**, a plurality of rail assemblies, such as rail assemblies **320**, are provided. As previously discussed, the rail assemblies must be compatibly sized and arranged to (1) receive a satellite, (2) to receive the desired number of satellites, and (3) attach to payload dispenser **100**.

[0049] In operation **903**, the satellites are coupled to rail assemblies **320**. As noted previously, this process can be performed in parallel, with satellites being coupled to the plural rail assemblies at the same time. The satellites are attached to the rail assemblies at couplings **324**, two couplings per satellite. Brackets (not depicted) connect a satellite separation system (not depicted) to the couplings. Before attaching each satellite to a rail assembly, a fastening element is positioned in opening **430** of each coupling **324** in preparation for operation **905**.

[0050] Satellite-laden rail assemblies **320** are attached to payload dispenser **100** in operation **905**. As previously disclosed, in some embodiments, this operation is accomplished as follows. Payload dispenser **100** is supported, in a horizontal orientation, for rotational movement. A satellite-laden rail assembly **320** is positioned below payload dispenser **100**. The dispenser is rotated to bring a "row" (in the horizontal orientation) of holes **110** (see FIGs. 1 and 2) in shell **102** into alignment with opening **430** in each coupling **324** in the rail assembly. The satellite-laden rail assembly **320** is then lifted to so that the fastening element extending from opening **430** in each coupling extends through opening **110** in dispenser **100**. A technician working inside of payload dispenser **100** fastens the fastener, thereby securing rail assembly **320** to shell **102**.

[0051] After a given satellite-laden rail assembly **320** is attached, the payload dispenser is rotated and another satellite-laden rail assembly is moved into position for attachment. The process is repeated until all satellite-laden rail assemblies **320** are attached to payload dispenser **102**.

[0052] After payload dispenser **100** is populated with the requisite amount of satellites, it is then coupled to the launch vehicle.

[0053] It is to be understood that the disclosure describes a few embodiments and that many variations of the invention can easily be devised by those skilled in the art after reading this disclosure and that the scope of the present invention is to be determined by the following claims.

What is claimed is:

1. A system for dispensing a plurality of satellites, comprising:
a plurality of rail assemblies (320), wherein each rail assembly comprises two spaced-apart rails (322) and at least four couplings (324) that are attached to the rails and disposed orthogonally thereto, and wherein the couplings are arranged in pairs, and further wherein each pair of couplings is dimensioned and arranged to couple to a satellite (600) such that the four couplings of each rail assembly are capable of coupling to at least two satellites; and
a payload dispenser (100), the payload dispenser including a shell (102), wherein the shell is physically adapted to securely engage the plurality of rail assemblies.
2. The system of claim 1 wherein the shell (102) comprises a cylindrical tube, and further wherein the cylindrical tube comprises a plurality of openings (110) arranged in plural columns along a length of the cylindrical tube, wherein at least some of the plurality of openings in a respective column are positioned to receive a respective fastening member extending from each coupling (324) in a respective rail assembly (320).
3. The system of claim 2 wherein the cylindrical tube has an outer diameter in a range of about 1 meter to about 2 meters.
4. The system of claim 3 wherein the cylindrical tube has a length in a range of about 3 meters to about 5.5 meters.
5. The system of claim 1 wherein the rails and the couplings comprise aluminum.
6. The system of claim 1 wherein the shell comprises a carbon-composite solid laminate.

7. The system of claim 1 further comprising a plurality of shell support braces (104), wherein the shell support braces are disposed within the shell (102) and are physically adapted to prevent a cross-sectional shape of the shell from deforming under load or vibration.
8. The system of claim 1 wherein the payload dispenser (100) is dimensioned and arranged to couple to nine rail assemblies (320), and wherein each rail assembly is dimensioned and arranged to couple to four satellites (600).
9. The system of claim 1 wherein each coupling (324) in each rail assembly (320) comprises a centrally located opening (430), at least some of which openings receive a fastening element that fastens the rail assembly and the shell (102) to one another.
10. The system of claim 1 wherein the shell (102) is internally reinforced to prevent deformation of a cross-sectional shape of the tube under load or vibration.
11. The system of claim 1 wherein each rail assembly receives at least three satellites.
12. A method for populating a payload dispenser (100) with a first plurality of satellites (600), wherein the method comprises:
- providing a first plurality of rail assemblies (320), each rail assembly comprising two spaced-apart rails and at least two pairs of couplings (324), each of which pairs is dimensioned and arranged to couple to one satellite (600);
 - coupling the first plurality of satellites to the first plurality of rail assemblies; and
 - coupling the first plurality of rail assemblies, with the first plurality of satellites attached thereto, to the payload dispenser.
13. The method of claim 12 wherein coupling the first plurality of satellites to the first plurality of rail assemblies (320) further comprises performing the coupling of satellites to each rail assembly at the same time as one another.

14. The method of claim 12 wherein coupling the first plurality of satellites to the first plurality of rail assemblies is performed at a location other than a launch site.

15. The method of claim 12 wherein coupling the first plurality of rail assemblies (320) to the payload dispenser (100) further comprises orienting the payload dispenser in a horizontal position and supporting the payload dispenser for rotation about a longitudinal axis thereof.

16. The method of claim 15 and further comprising:
disposing a first one of the rail assemblies (320) with satellites coupled thereto below the payload dispenser (100);
fastening the couplings (324) of the first one of the rail assembly to the payload dispenser.

17. The method of claim 16 and further comprising:
rotating the payload dispenser (100) to a second position;
disposing a second one of the rail assemblies (320) with satellites coupled thereto below the payload dispenser; and
fastening the couplings (324) of the second one of the rail assemblies to the payload dispenser.

18. The method of claim 16 wherein the fastening is performed from within the payload dispenser.