



- (51) **International Patent Classification:** Not classified
- (21) **International Application Number:** PCT/NO2012/050169
- (22) **International Filing Date:** 5 September 2012 (05.09.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:** 61/532,770 9 September 2011 (09.09.2011) US
- (71) **Applicant (for all designated States except US):** **NATIONAL OILWELL VARCO NORWAY AS** [NO/NO]; Serviceboks 401, N-4604 Kristiansand S (NO).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** **WEBB, Jonathan, Garrick** [GB/NO]; Andøysløyfen 41, N-4623 Kristiansand S (NO). **MOEN, Trond, Werner** [NO/NO]; Kirsten Flagstadsvei 4, N-4621 Kristiansand (NO). **HILL, David, Allen** [US/NO]; Lerkeveien 18B, N-4622 Kristiansand (NO).
- (74) **Agent:** **HÅMSØ PATENTBYRÅ ANS**; Postboks 171, N-4302 Sandnes (NO).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) **Title:** A TORQUE DEVICE FOR OIL FIELD USE AND METHOD OF OPERATION FOR SAME




Fig. 4

(57) **Abstract:** A torque device (1) and operational method for oil field use that includes a first torque device member (10) that has an operational axis (34) of rotation, and where a first torque actuator (42) is pivotally connected to the first torque device member (10) at a first radial distance (46) from a centre line (48) of the first torque device member (10), wherein a rod (50) or a second torque actuator (66) is pivotally connected to the first torque device member (10) at a second radial distance (54) extending in the opposite direction relative to the first radial distance from the centre line (48), and where the first torque actuator (42) is pivotally connected to a first portion (56) of an actuator support (58), and where the rod (50), alternatively the second torque actuator (66), is pivotally connected to a second portion (60) of the actuator support (66), and where the actuator support (66) is radially movable relative to the operational axis (34), but is restricted from rotating in a plane (XY) that is perpendicular to the operational axis (34).

