

Description

BACKGROUND OF THE INVENTION

Intraocular lenses (IOL's) are a well-known type of surgical implant used to replace the natural lens of an eye which has been damaged as a result of trauma or disease. Such IOL'S typically comprise an optic and at least one fixation member attached to the optic. The fixation member functions to position the optic in the correct optical alignment within the eye. Many fixation members are of filamentary form, and are attached to the optic at or near the periphery of the optic.

It is conventional practice to construct the optic of a hard biocompatible polymer, such as polymethylmethacrylate (PMMA). A technique for attaching fixation members to such a hard optic using bosses is described in US-A-4468820.

More recently, it has been proposed to construct the optic from a relatively flexible or deformable material. When so constructed, the optic can be rolled or flexed into a relatively small cross-sectional configuration to permit it to be inserted through a relatively small incision into the eye to thereby reduce the trauma and likelihood of infection from the surgery. Such an arrangement is described in GB-A-2153688. This document does not, however, describe how the fixation members are attached to the optic, and does not disclose or suggest anchor means, like those defined by the invention.

In known IOL's, the fixation members are constructed of a resilient material, typically polypropylene. In some IOL'S, the fixation members are integrally formed with the optic. In other types of IOL's, various methods of attaching the fixation members to the optic have been devised.

A common method of attaching requires drilling two small intersecting holes in the edge portion of the optic. A proximal end portion of the fixation member is inserted into one hole and a heated rod is inserted through the other of the intersecting holes. The heated rod melts the proximal end portion of the fixation member where contacted causing the melted material to flow into the second intersecting hole to form a mechanical interlock when the material solidifies. Great precision is required in the drilling of the intersecting holes. Also characteristic of the IOL'S made according to this method is the potential of debris-trapping cavities remaining from a less-than-complete filling of the holes in the optic by the melted portion of the fixation member.

The attachment of the fixation members to the optic is particularly troublesome when the optic is constructed of soft or deformable materials, such as silicone. When the deformable optic is folded or

rolled prior to insertion through the incision into the eye, flexure of the optic creates a likelihood that the fixation member will become detached from the optic. If this occurs, it not only renders the IOL useless, but also is a potential hazard to the patient. The soft optic materials, such as silicone, do not have sufficient rigidity to be used as an integral fixation member or haptic.

It is known to attach the fixation members to a large resilient, circular ring and to mold the soft optic material over the ring so that the ring is concentric with the optic and extends along a peripheral region of the optic. However, for foldable optics, this construction precludes the use of rigid or non-foldable materials for the ring and requires the dedication of a large diameter annulus of the optic to capture the ring.

SUMMARY OF THE INVENTION

According to the present invention, the fixation members are attached to optic by means of anchors coupled to the proximal end portions of the fixation members.

In one aspect, the invention provides an anchor which includes an elongated member which forms a segment of an arc and which is coupled to the proximal end portion of the first fixation member, the elongated member extending generally along the periphery of the optic generally coaxial with the optic.

In another aspect, the invention provides an anchor which extends transversely on both sides of the associated fixation member at the location where the anchor is coupled to the fixation member.

In another aspect, the invention provides an anchor having a hole receiving a region of the proximal end portion of the fixation member, the anchor extending transversely on both sides of the fixation member at the location where the anchor is coupled to the second fixation member.

This invention improves the attachment of the fixation members to a soft or deformable optic and eliminates the ring of the prior art in favor of first and second elongated anchors or supports which are coupled to the proximal end portions of first and second fixation members, respectively. The anchors and proximal end portions are within peripheral regions of a deformable optic so that the anchors assist in attaching the fixation members to the optic. The anchors are spaced apart so that the deformable optic can be folded to facilitate insertion of the optic through a relatively small incision into the eye.

Because the anchors are spaced apart, they do not interfere with folding of the deformable optic. Accordingly, the anchors may be constructed of

resilient material, rigid material, material which is more rigid than the material of the optic, or virtually any material suitable for placement within the optic. Also, the anchors can be much smaller than the ring of the prior art and thereby require much less dedicated space within the optic to accommodate them.

The anchors can be of various different constructions. For example, each of the anchors may include a filament which is molded integrally with the associated fixation member or formed separately and attached thereto as by welding or staking. The anchors may be of the same or different materials than the optic and the fixation members. By elongating the anchors, they can form a strong mechanical interlock with the optic and can hold the fixation members against rotation relative to the optic.

So as to best serve as an anchor, each of the anchors preferably extends away from the axis of the associated fixation member at the location where the anchor is coupled to the fixation member. For example, each of the anchors may include a filament which forms a segment of an arc and/or which extends generally transverse to the proximal end portion of the associated fixation member. In one preferred construction, the filament is elongated, forms the segment of an arc and is more rigid than the deformable optic so that it can provide a frame or skeleton to support the soft optic so as to decrease the likelihood that the optical properties of the optic will be altered when the IOL is introduced into the eye.

The invention, together with additional features and advantages thereof may best be understood by reference to the following description taken in connection with the accompanying illustrative drawing.

BRIEF DESCRIPTION OF THE DRAWING

Fig. 1 is a elevational view partially in section of one form of IOL constructed in accordance with the teachings of this invention.

Fig. 2 is a side elevational view of the IOL.

Fig. 3 is a fragmentary sectional view taken generally along line 3-3 of Fig. 1.

Fig. 4 is an isometric view of one form of fixation member and anchor.

Figs. 5 and 6 are fragmentary sectional views illustrating portions of optics and fixation members being utilized with anchors of different configurations.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 shows an IOL 11 which comprises an

optic 13 of a transparent, biocompatible material, fixation members 15 and 17 and anchors 19 and 21. Although the optic 13 could be of various different configurations, in the embodiment illustrated, it has a convex, anterior face 23 (Fig. 2), a convex posterior face 25, and a cylindrical periphery or edge 27. The optic 13 is constructed of a suitable, soft, deformable material, such as silicone or polyurethane which permits the optic to be rolled or folded into a smaller configuration for insertion through a relatively small incision into the eye.

The fixation members 15 and 17 retain or fix the optic 13 in the correct position within the eye. Each of the fixation members 15 and 17 is in the form of an elongated, resilient strand or filament. Although the fixation members can be of various different configurations, in this embodiment, they are each constructed of a generally J-shaped configuration, and they are constructed of a resilient, biocompatible material, such as polypropylene.

Although the anchors 19 and 21 can be of various different configurations, in the embodiment of Figs. 1-4, each of them is in the form of an elongated filament which forms a segment of an arc and which extends away from the axis of the associated fixation member. In this embodiment, the anchors 19 and 21 are of identical construction, although this is not essential. Each of the anchors 19 and 21 is joined to the associated fixation member 15 and 17 at a location spaced from the center of the segment of the arc. The anchors 19 and 21 may be constructed of any suitable biocompatible material, such as polymethylmethacrylate (PMMA), which is quite rigid, or polypropylene, which is relatively resilient. In either case in this specific embodiment, the anchors 19 and 21 are more rigid than a silicone or polyurethane deformable optic 13. The anchors 19 and 21 may be molded integrally with the fixation members 15 and 17 or they may be formed separately and attached to the proximal end portions 29 as by welding or staking.

Although the length of the arcs formed by the anchors 19 and 21 can vary, in this embodiment, each of the anchors extends for about 90 degrees. The anchors 19 and 21 in this embodiment, are diametrically opposite and are spaced apart by approximately 90 degrees. The anchors 19 and 21 are coupled to proximal end portions 29 of the fixation members 15 and 17, respectively. The anchors 19 and 21 and the proximal end portions 29 are within peripheral regions of the optic 13, and the anchors are closely adjacent the periphery 27. In addition, the anchors 19 and 21 are preferably concentric with the optic 13. The optic 13 is cast or molded over the proximal end portions 29 and the anchors 19 and 21.

This construction provides important advantages. For example, the anchors 19 and 21 form a

strong mechanical interlock with the optic 13 which not only prevents withdrawal of the fixation members 15 and 17 from the optic, but also prevents rotation of the fixation members relative to the optic. In addition, because the opposite ends of the anchors 19 and 21 are widely spaced, the anchors do not interfere with folding or rolling of the optic 13 into a smaller configuration for insertion through a relatively small incision into the eye. Accordingly, even if the anchors 19 and 21 are constructed of rigid material, the optic 13 can still be folded for insertion through the small incision. Also, the anchors 19 and 21 serve as supports to support the deformable optic 13 so as to decrease the likelihood that the optical properties of the optic will be altered when the IOL is introduced into the eye.

Figs. 5 and 6 show IOL'S 11a and 11b, respectively, and each of these IOL'S is identical to the IOL 11 in all respects not shown or described herein. Portions of the IOL'S 11a and 11b corresponding to portions of the IOL 11 are designated by corresponding reference numerals followed by the letters "a" and "b", respectively.

The IOL'S 11a and 11b differ from the IOL 11 in the construction of the anchors 19a and 19b. Each of the anchors 19a and 19b is in the form of an elongated rod, plate filament or plug of a suitable plastic, such as PMMA or polypropylene. Both of the anchors 19a and 19b extend generally transverse to the associated proximal end portions 29a and 29b. The anchor 19a is welded to the proximal end portion 29a, and the anchor 19b is staked to the proximal end portion 29b. More specifically, the staking may be carried out, for example, by inserting a region of the proximal end portion 29b into or through a hole 41 of the anchor 19b and inserting a hot rod through a bore 43 to melt a portion of the proximal end portion 29b and form a projection 45 in the bore 43 which interlocks with the bore to attach the anchor 19b to the proximal end portion 29b. Following the attachment of the anchors 19a and 19b, the optics 13a and 13b are molded, respectively, about the proximal end portions 29a and 29b and the anchors.

The anchors 19a and 19b interlock with the material of the associated optics 13a and 13b to provide a strong mechanical interlock. In addition, the anchors 19a and 19b prevent rotation of the associated fixation members 15a and 15b relative to the optic. Of course, additional fixation members can be attached to the optics 13a and 13b in accordance with the principles of this invention.

Although exemplary embodiments of the invention have been shown and described, many changes, modifications and substitutions may be made by one having ordinary skill in the art without necessarily departing from the scope of this invention.

Claims

Claims for the following Contracting States :
DE, FR, GB

1. An intraocular lens (11) comprising:
 - an optic (13) which is deformable to facilitate insertion of the optic through an incision into the eye, said optic (13) having a generally circular periphery (27);
 - first and second fixation members (15,17) each of said fixation members (15,17) having a proximal end portion (29);
 - first and second elongated anchors (19,21) coupled to the proximal end portions (29) of the first and second fixation members (15,17), respectively;
 - said anchors (19,21) and proximal end portions (29) being within peripheral regions of the optic (13) whereby the anchors (19,21) assist in attaching the fixation members (15, 17) to the optic (13);
 - said anchors (19,21) being spaced apart whereby the deformable optic (13) can be folded to facilitate insertion of the optic through an incision into the eye; and
 - at least one of said anchors (19,21) including an elongated member which forms a segment of an arc and which is coupled to the proximal end portion (29) of the first fixation member (15), said elongated member extending generally along the periphery of the optic (13) generally coaxial with the optic (13);
 - the fixation members (15, 17) extending from the optic (13) and are inclined relative to the general plane of the optic (13).
2. An intraocular lens (11a, 11b) comprising:
 - an optic (13a, 13b) which is deformable to facilitate insertion of the optic through an incision into the eye;
 - first and second fixation members (15a, 15b), each of said fixation members (15a, 15b) having a proximal end portion (29a, 29b);
 - first and second anchors (19a, 19b) coupled to the proximal end portions (29a, 29b) of the first and second fixation members (15a, 15b), respectively;
 - said optic (13a, 13b) receiving said anchors (19a, 19b) and said proximal end portions (29a, 29b);
 - said anchors (19a, 19b) and proximal end portions (29a, 29b) being within peripheral regions of the optic (13a, 13b) whereby the anchors (19a, 19b) assist in attaching the fixation members (15a, 15b) to the optic (13a, 13b);
 - said anchors (19a, 19b) being spaced apart whereby the deformable optic (13a, 13b) can be folded to facilitate insertion of the optic



strong mechanical interlock with the optic 13 which not only prevents withdrawal of the fixation members 15 and 17 from the optic, but also prevents rotation of the fixation members relative to the optic. In addition, because the opposite ends of the anchors 19 and 21 are widely spaced, the anchors do not interfere with folding or rolling of the optic 13 into a smaller configuration for insertion through a relatively small incision into the eye. Accordingly, even if the anchors 19 and 21 are constructed of rigid material, the optic 13 can still be folded for insertion through the small incision. Also, the anchors 19 and 21 serve as supports to support the deformable optic 13 so as to decrease the likelihood that the optical properties of the optic will be altered when the IOL is introduced into the eye.

Figs. 5 and 6 show IOL'S 11a and 11b, respectively, and each of these IOL'S is identical to the IOL 11 in all respects not shown or described herein. Portions of the IOL'S 11a and 11b corresponding to portions of the IOL 11 are designated by corresponding reference numerals followed by the letters "a" and "b", respectively.

The IOL'S 11a and 11b differ from the IOL 11 in the construction of the anchors 19a and 19b. Each of the anchors 19a and 19b is in the form of an elongated rod, plate filament or plug of a suitable plastic, such as PMMA or polypropylene. Both of the anchors 19a and 19b extend generally transverse to the associated proximal end portions 29a and 29b. The anchor 19a is welded to the proximal end portion 29a, and the anchor 19b is staked to the proximal end portion 29b. More specifically, the staking may be carried out, for example, by inserting a rod 41 of the anchor 19b and inserting a hot rod through a bore 43 to melt a portion of the proximal end portion 29b and form a projection 45 in the bore 43 which interlocks with the bore to attach the anchor 19b to the proximal end portion 29b. Following the attachment of the anchors 19a and 19b, the optics 13a and 13b are molded, respectively, about the proximal end portions 29a and 29b and the anchors.

The anchors 19a and 19b interlock with the material of the associated optics 13a and 13b to provide a strong mechanical interlock. In addition, the anchors 19a and 19b prevent rotation of the associated fixation members 15a and 15b relative to the optic. Of course, additional fixation members can be attached to the optics 13a and 13b in accordance with the principles of this invention.

Although exemplary embodiments of the invention have been shown and described, many changes, modifications and substitutions may be made by one having ordinary skill in the art without necessarily departing from the scope of this invention.

Claims

Claims for the following Contracting States :
DE, FR, GB

1. An intraocular lens (11) comprising:
 - an optic (13) which is deformable to facilitate insertion of the optic through an incision into the eye, said optic (13) having a generally circular periphery (27);
 - first and second fixation members (15,17) each of said fixation members (15,17) having a proximal end portion (29);
 - first and second elongated anchors (19,21) coupled to the proximal end portions (29) of the first and second fixation members (15,17), respectively;
 - said anchors (19,21) and proximal end portions (29) being within peripheral regions of the optic (13) whereby the anchors (19,21) assist in attaching the fixation members (15, 17) to the optic (13);
 - said anchors (19,21) being spaced apart whereby the deformable optic (13) can be folded to facilitate insertion of the optic through an incision into the eye; and
 - at least one of said anchors (19,21) including an elongated member which forms a segment of an arc and which is coupled to the proximal end portion (29) of the first fixation member (15), said elongated member extending generally along the periphery of the optic (13) generally coaxial with the optic (13);
 - the fixation members (15, 17) extending from the optic (13) and are inclined relative to the general plane of the optic (13).
2. An intraocular lens (11a, 11b) comprising:
 - an optic (13a, 13b) which is deformable to facilitate insertion of the optic through an incision into the eye;
 - first and second fixation members (15a, 15b), each of said fixation members (15a, 15b) having a proximal end portion (29a, 29b);
 - first and second anchors (19a, 19b) coupled to the proximal end portions (29a, 29b) of the first and second fixation members (15a, 15b), respectively;
 - said optic (13a, 13b) receiving said anchors (19a, 19b) and said proximal end portions (29a, 29b);
 - said anchors (19a, 19b) and proximal end portions (29a, 29b) being within peripheral regions of the optic (13a, 13b) whereby the anchors (19a, 19b) assist in attaching the fixation members (15a, 15b) to the optic (13a, 13b);
 - said anchors (19a, 19b) being spaced apart whereby the deformable optic (13a, 13b) can be folded to facilitate insertion of the optic



through an incision into the eye, and
 at least one of said anchors (19a, 19b)
 extending substantially perpendicularly on both
 sides of the associated fixation member at the
 location where said one anchor is coupled to
 such fixation member.

3. An intraocular lens (11b) comprising:
 - an optic (13b) which is deformable to facilitate insertion of the optic through an incision into the eye;
 - first and second fixation members (15b), each of said fixation members having a proximal end portion (29b);
 - a first anchor (19b) coupled to the proximal end portion (29b) of the first fixation member (15b);
 - a second anchor (19b) coupled to the proximal end portion (29b) of the second fixation member (15b);
 - said optic (13b) receiving said anchors (19b) and said proximal end portions (29b);
 - said anchors (19b) and proximal end portions (29b) being within peripheral regions of the optic (13b) whereby the anchors (19b) assist in attaching the fixation members (15b) to the optic (13b);
 - said anchors (19b) being spaced apart whereby the deformable optic (13b) can be folded to facilitate insertion of the optic through an incision into the eye;
 - said second anchor (19b) having a hole (41) receiving a region of the proximal end portion (29b) of the second fixation member (15b), said second anchor (19b) extending transversely on both sides of the second fixation member (15b) at the location where said second anchor (19b) is coupled to the second fixation member (15b).
4. An intraocular lens (11) as defined in claim 1, wherein said elongated member includes a filament.
5. An intraocular lens (11) as defined in claim 1 or 4 wherein said one anchor (19) is joined to the first fixation member (15) at a location spaced from the center of the segment of the arc.
6. An intraocular lens as defined in claim 1, 4 or 5, wherein the other of said anchors (21) includes a filament which forms a segment of an arc.
7. An intraocular lens as defined in claim 1, 4, 5 or 6, wherein at least one of the anchors (19, 21) is integral with the associated fixation

member (15, 17).

8. An intraocular lens as defined in claim 1, 4, 5, 6 or 7, wherein said first fixation member (15) has a proximal end and said elongated member extends in both directions on opposite sides of the proximal end of the first fixation member (15).
9. An intraocular lens (11a, 11b) as defined in claim 3, wherein said second anchor (19b) includes a filament staked to the associated proximal end portion (29b).
10. An intraocular lens (11, 11a, 11b) as defined in any of claims 1, 2, 4 to 8 wherein at least one of said anchors (19, 21, 19a) includes a filament welded to the associated proximal end portion (29, 29a).
11. An intraocular lens (11, 11a, 11b) as defined in any of claims 1 to 10 wherein each of said anchors (19, 21, 19a, 19b) is more rigid than the optic (13, 13a, 13b) and supports regions of the optic.
12. An intraocular lens (11) according to any preceding claim, wherein said optic (13) is moulded over said anchors (19) and said proximal end portions (29).

Claims for the following Contracting State : IT

1. An intraocular lens (11) comprising:
 - an optic (13) which is deformable to facilitate insertion of the optic through an incision into the eye, said optic (13) having a generally circular periphery (27);
 - first and second fixation members (15,17) each of said fixation members (15,17) having a proximal end portion (29);
 - first and second elongated anchors (19,21) coupled to the proximal end portions (29) of the first and second fixation members (15,17), respectively;
 - said anchors (19,21) and proximal end portions (29) being within peripheral regions of the optic (13) whereby the anchors (19,21) assist in attaching the fixation members (15, 17) to the optic (13);
 - said anchors (19,21) being spaced apart whereby the deformable optic (13) can be folded to facilitate insertion of the optic through an incision into the eye; and
 - at least one of said anchors (19,21) including an elongated member which forms a segment of an arc and which is coupled to the proximal end portion (29) of the first fixation



member (15), said elongated member extending generally along the periphery of the optic (13) generally coaxial with the optic (13).

2. An intraocular lens (11a, 11b) comprising:

an optic (13a, 13b) which is deformable to facilitate insertion of the optic through an incision into the eye;

first and second fixation members (15a, 15b), each of said fixation members (15a, 15b) having a proximal end portion (29a, 29b);

first and second anchors (19a, 19b) coupled to the proximal end portions (29a, 29b) of the first and second fixation members (15a, 15b), respectively;

said optic (13a, 13b) receiving said anchors (19a, 19b) and said proximal end portions (29a, 29b);

said anchors (19a, 19b) and proximal end portions (29a, 29b) being within peripheral regions of the optic (13a, 13b) whereby the anchors (19a, 19b) assist in attaching the fixation members (15a, 15b) to the optic (13a, 13b);

said anchors (19a, 19b) being spaced apart whereby the deformable optic (13a, 13b) can be folded to facilitate insertion of the optic through an incision into the eye, and

at least one of said anchors (19a, 19b) extending transversely on both sides of the associated fixation member at the location where said one anchor is coupled to such fixation member.

3. An intraocular lens (11b) comprising:

an optic (13b) which is deformable to facilitate insertion of the optic through an incision into the eye;

first and second fixation members (15b), each of said fixation members having a proximal end portion (29b);

a first anchor (19b) coupled to the proximal end portion (29b) of the first fixation member (15b);

a second anchor (19b) coupled to the proximal end portion (29b) of the second fixation member (15b);

said optic (13b) receiving said anchors (19b) and said proximal end portions (29b);

said anchors (19b) and proximal end portions (29b) being within peripheral regions of the optic (13b) whereby the anchors (19b) assist in attaching the fixation members (15b) to the optic (13b);

said anchors (19b) being spaced apart whereby the deformable optic (13b) can be folded to facilitate insertion of the optic through an incision into the eye;

and said second anchor (19b) having a

hole (41) receiving a region of the proximal end portion (29b) of the second fixation member (15b), said second anchor (19b) extending transversely on both sides of the second fixation member (15b) at the location where said second anchor (19b) is coupled to the second fixation member (15b).

4. An intraocular lens (11) as defined in claim 1, wherein said elongated member includes a filament.

5. An intraocular lens (11) as defined in claim 1 or 4 wherein said one anchor (19) is joined to the first fixation member (15) at a location spaced from the center of the segment of the arc.

6. An intraocular lens as defined in claim 1, 4 or 5, wherein the other of said anchors (21) includes a filament which forms a segment of an arc.

7. An intraocular lens as defined in claim 1, 4, 5 or 6, wherein at least one of the anchors (19, 21) is integral with the associated fixation member (15, 17).

8. An intraocular lens as defined in claim 1, 4, 5, 6 or 7, wherein said first fixation member (15) has a proximal end and said elongated member extends in both directions on opposite sides of the proximal end of the first fixation member (15).

9. An intraocular lens (11a, 11b) as defined in claim 3, wherein said one anchor (19a, 19b) includes a filament staked to the associated proximal end portion (29a, 29b).

10. An intraocular lens (11, 11a, 11b) as defined in any of claims 1, 2, 4 to 8 wherein at least one of said anchors (19, 21, 19a, 19b) includes a filament welded to the associated proximal end portion (29, 29a, 29b).

11. An intraocular lens (11, 11a, 11b) as defined in any of claims 1 to 10 wherein each of said anchors (19, 21, 19a, 19b) is more rigid than the optic (13, 13a, 13b) and supports regions of the optic.

12. An intraocular lens (11) according to any preceding claim, wherein said optic (13) is moulded over said anchors (19) and said proximal end portions.

13. An intraocular lens (11) according to any



preceeding claim, wherein the fixation members (15, 17) extend from the optic (13) and are inclined relative to the general plane of the optic (13)

Revendications

Revendications pour les Etats contractants suivants : DE, FR, GB

1. Lentille intra-oculaire (11) comportant:

un dispositif d'optique (13) qui est susceptible d'être déformé de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil, ledit dispositif d'optique (13) ayant une périphérie globalement circulaire (27);

un premier et un second organes de fixation (15, 17), chacun desdits organes de fixation (15, 17) possédant une partie d'extrémité proximale (29);

un premier et un second dispositifs allongés d'ancrage (19, 21) couplés aux parties d'extrémité proximales (29) des premier et second organes de fixation (15, 17), respectivement;

lesdits dispositifs d'ancrage (19, 21) et parties d'extrémité proximales (29) étant situés à l'intérieur de zones périphériques du dispositif d'optique (13) si bien que les dispositifs d'ancrage (19, 21) aident à attacher les organes de fixation (15, 17) au dispositif d'optique (13);

lesdits dispositifs d'ancrage (19, 21) étant espacés l'un de l'autre si bien que le dispositif d'optique (13) susceptible d'être déformé peut être plié de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil; et

au moins l'un desdits dispositifs d'ancrage (19, 21) comprenant un organe allongé qui constitue un segment d'arc et qui est couplé à la partie d'extrémité proximale (29) du premier organe de fixation (15), ledit organe allongé qui s'étend globalement le long de la périphérie du dispositif d'optique (13) ayant globalement le même axe que le dispositif d'optique (13);

les organes de fixation (15, 17) s'étendant à partir du dispositif d'optique (13) et étant inclinés par rapport au plan d'ensemble de ce dispositif d'optique (13).

2. Lentille intra-oculaire (11a, 11b) comportant:

un dispositif d'optique (13a, 13b) qui est susceptible d'être déformé de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil;

un premier et un second organes de fixation (15a, 15b), chacun desdits organes de

fixation (15a, 15b) possédant une partie d'extrémité proximale (29a, 29b);

un premier et un second dispositifs d'ancrage (19a, 19b) couplés aux parties d'extrémité proximales (29a, 29b) des premier et second organes de fixation (15a, 15b), respectivement;

lesdits dispositifs d'ancrage (19a, 19b) et lesdites parties d'extrémité proximales (29a, 29b) trouvant leurs places dans ledit dispositif d'optique (13a, 13b);

lesdits dispositifs d'ancrage (19a, 19b) et parties d'extrémité proximales (29a, 29b) étant situés à l'intérieur de zones périphériques du dispositif d'optique (13a, 13b) si bien que les dispositifs d'ancrage (19a, 19b) aident à attacher les organes de fixation (15a, 15b) au dispositif d'optique (13a, 13b);

lesdits dispositifs d'ancrage (19a, 19b) étant espacés l'un de l'autre si bien que le dispositif d'optique (13a, 13b) susceptible d'être déformé peut être plié de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil, et

au moins l'un desdits dispositifs d'ancrage (19a, 19b) s'étendant dans une direction sensiblement perpendiculaire sur les deux côtés de l'organe de fixation associé à l'emplacement où ledit dispositif d'ancrage au moins unique est couplé à cet organe de fixation.

3. Lentille intra-oculaire (11b) comportant:

un dispositif d'optique (13b) qui est susceptible d'être déformé de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil;

un premier et un second organes de fixation (15b), chacun desdits organes de fixation possédant une partie d'extrémité proximale (29b);

un premier dispositif d'ancrage (19b) couplé à la partie d'extrémité proximale (29b) du premier organe de fixation (15b);

un second dispositif d'ancrage (19b) couplé à la partie d'extrémité proximale (29b) du second organe de fixation (15b);

lesdits dispositifs d'ancrage (19b) et lesdites parties d'extrémité proximales (29b) trouvant leurs places dans ledit dispositif d'optique (13b);

lesdits dispositifs d'ancrage (19b) et parties d'extrémité proximales (29b) étant situés à l'intérieur de zones périphériques du dispositif d'optique (13b) si bien que les dispositifs d'ancrage (19b) aident à attacher les organes de fixation (15b) à ce dispositif d'optique (13b);

lesdits dispositifs d'ancrage (19b) étant espacés l'un de l'autre si bien que le dispositif



d'optique (13b) susceptible d'être déformé peut être plié de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil; et

ledit second dispositif d'ancrage (19b) présentant un trou (41) où trouve sa place une portion de la partie d'extrémité proximale (29b) du second organe de fixation (15b), ledit second dispositif d'ancrage (19b) s'étendant transversalement sur les deux côtés du second organe de fixation (15b) à l'emplacement où ledit second dispositif d'ancrage (19b) est couplé à ce second organe de fixation (15b).

4. Lentille intra-oculaire (11) telle que définie par la revendication 1, dans laquelle ledit organe allongé comprend un filament.

5. Lentille intra-oculaire (11) telle que définie par la revendication 1 ou la revendication 4 dans laquelle ledit dispositif d'ancrage au moins unique (19) est relié au premier organe (15) de fixation à un emplacement espacé du centre du segment d'arc.

6. Lentille intra-oculaire telle que définie par la revendication 1, la revendication 4 ou la revendication 5, dans laquelle l'autre desdits dispositifs d'ancrage (21) comprend un filament qui constitue un segment d'arc.

7. Lentille intra-oculaire telle que définie par la revendication 1, la revendication 4, la revendication 5 ou la revendication 6, dans laquelle au moins l'un des dispositifs d'ancrage (19, 21) fait corps avec l'organe de fixation (15, 17) associé.

8. Lentille intra-oculaire telle que définie par la revendication 1, la revendication 4, la revendication 5, la revendication 6 ou la revendication 7, dans laquelle ledit premier organe (15) de fixation possède une extrémité proximale et ledit organe allongé s'étend dans les deux sens sur les côtés opposés de l'extrémité proximale de ce premier organe (15) de fixation.

9. Lentille intra-oculaire (11a, 11b) telle que définie par la revendication 3, dans laquelle ledit second dispositif d'ancrage (19b) comprend un filament empalé sur la partie d'extrémité proximale (29b) associée.

10. Lentille intra-oculaire (11, 11a, 11b) telle que définie par l'une quelconque des revendications 1, 2, 4 à 8 dans laquelle au moins l'un desdits dispositifs d'ancrage (19, 21, 19a)

comprend un filament soudé sur la partie d'extrémité proximale (29, 29a) associée.

11. Lentille intra-oculaire (11, 11a, 11b) telle que définie par l'une quelconque des revendications 1 à 10 dans laquelle chacun desdits dispositifs d'ancrage (19, 21, 19a, 19b) est plus rigide que le dispositif d'optique (13, 13a, 13b) et soutient des zones de ce dispositif d'optique.

12. Lentille intra-oculaire (11) conforme à l'une quelconque des revendications précédentes, dans laquelle ledit dispositif d'optique (13) est moulé sur lesdits dispositifs d'ancrage (19) et lesdites parties d'extrémité proximales (29).

Revendications pour l'Etat contractant suivant : IT

1. Lentille intra-oculaire (11) comportant:

un dispositif d'optique (13) qui est susceptible d'être déformé de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil, ledit dispositif d'optique (13) ayant une périphérie globalement circulaire (27);

un premier et un second organes de fixation (15, 17), chacun desdits organes de fixation (15, 17) possédant une partie d'extrémité proximale (29);

un premier et un second dispositifs allongés d'ancrage (19, 21) couplés aux parties d'extrémité proximales (29) des premier et second organes de fixation (15, 17), respectivement;

lesdits dispositifs d'ancrage (19, 21) et parties d'extrémité proximales (29) étant situés à l'intérieur de zones périphériques du dispositif d'optique (13) si bien que les dispositifs d'ancrage (19, 21) aident à attacher les organes de fixation (15, 17) au dispositif d'optique (13);

lesdits dispositifs d'ancrage (19, 21) étant espacés l'un de l'autre si bien que le dispositif d'optique (13) susceptible d'être déformé peut être plié de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil; et

au moins l'un desdits dispositifs d'ancrage (19, 21) comprenant un organe allongé qui constitue un segment d'arc et qui est couplé à la partie d'extrémité proximale (29) du premier organe de fixation (15), ledit organe allongé qui s'étend globalement le long de la périphérie du dispositif d'optique (13) ayant globalement le même axe que le dispositif d'optique (13).



2. Lentille intra-oculaire (11a, 11b) comportant:

un dispositif d'optique (13a, 13b) qui est susceptible d'être déformé de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil;

un premier et un second organes de fixation (15a, 15b), chacun desdits organes de fixation (15a, 15b) possédant une partie d'extrémité proximale (29a, 29b);

un premier et un second dispositifs d'ancrage (19a, 19b) couplés aux parties d'extrémité proximales (29a, 29b) des premier et second organes de fixation (15a, 15b), respectivement;

lesdits dispositifs d'ancrage (19a, 19b) et lesdites parties d'extrémité proximales (29a, 29b) trouvant leurs places dans ledit dispositif d'optique (13a, 13b);

lesdits dispositifs d'ancrage (19a, 19b) et parties d'extrémité proximales (29a, 29b) étant situés à l'intérieur de zones périphériques du dispositif d'optique (13a, 13b) si bien que les dispositifs d'ancrage (19a, 19b) aident à attacher les organes de fixation (15a, 15b) au dispositif d'optique (13a, 13b);

lesdits dispositifs d'ancrage (19a, 19b) étant espacés l'un de l'autre si bien que le dispositif d'optique (13a, 13b) susceptible d'être déformé peut être plié de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil, et

au moins l'un desdits dispositifs d'ancrage (19a, 19b) s'étendant transversalement sur les deux côtés de l'organe de fixation associé à l'emplacement où ledit dispositif d'ancrage au moins unique est couplé à cet organe de fixation.

3. Lentille intraculaire (11b) comportant:

un dispositif d'optique (13b) qui est susceptible d'être déformé de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil;

un premier et un second organes de fixation (15b), chacun desdits organes de fixation possédant une partie d'extrémité proximale (29b);

un premier dispositif d'ancrage (19b) couplé à la partie d'extrémité proximale (29b) du premier organe de fixation (15b);

un second dispositif d'ancrage (19b) couplé à la partie d'extrémité proximale (29b) du second organe de fixation (15b);

lesdits dispositifs d'ancrage (19b) et lesdites parties d'extrémité proximales (29b) trouvant leurs places dans ledit dispositif d'optique (13b);

lesdits dispositifs d'ancrage (19b) et par-

ties d'extrémité proximales (29b) étant situés à l'intérieur de zones périphériques du dispositif d'optique (13b) si bien que les dispositifs d'ancrage (19b) aident à attacher les organes de fixation (15b) à ce dispositif d'optique (13b);

lesdits dispositifs d'ancrage (19b) étant espacés l'un de l'autre si bien que le dispositif d'optique (13b) susceptible d'être déformé peut être plié de façon à faciliter l'insertion de ce dispositif d'optique à travers une incision effectuée dans l'oeil;

et ledit second dispositif d'ancrage (19b) présentant un trou (41) où trouve sa place une portion de la partie d'extrémité proximale (29b) du second organe de fixation (15b), ledit second dispositif d'ancrage (19b) s'étendant transversalement sur les deux côtés du second organe de fixation (15b) à l'emplacement où ledit second dispositif d'ancrage (19b) est couplé à ce second organe de fixation (15b).

4. Lentille intra-oculaire (11) telle que définie par la revendication 1, dans laquelle ledit organe allongé comprend un filament.

5. Lentille intra-oculaire (11) telle que définie par la revendication 1 ou la revendication 4 dans laquelle ledit dispositif d'ancrage au moins unique (19) est relié au premier organe (15) de fixation à un emplacement espacé du centre du segment d'arc.

6. Lentille intra-oculaire telle que définie par la revendication 1, la revendication 4 ou la revendication 5, dans laquelle l'autre desdits dispositifs d'ancrage (21) comprend un filament qui constitue un segment d'arc.

7. Lentille intra-oculaire telle que définie par la revendication 1, la revendication 4, la revendication 5 ou la revendication 6, dans laquelle au moins l'un des dispositifs d'ancrage (19, 21) fait corps avec l'organe de fixation (15, 17) associé.

8. Lentille intra-oculaire telle que définie par la revendication 1, la revendication 4, la revendication 5, la revendication 6 ou la revendication 1, dans laquelle ledit premier organe (15) de fixation possède une extrémité proximale et ledit organe allongé s'étend dans les deux sens sur les côtés opposés de l'extrémité proximale de ce premier organe (15) de fixation.

9. Lentille intra-oculaire (11a, 11b) telle que définie par la revendication 3, dans laquelle ledit premier dispositif d'ancrage (19a, 19b) com-



prend un filament empalé sur la partie d'extrémité proximale (29a, 29b) associée.

10. Lentille intra-oculaire (11, 11a, 11b) telle que définie par l'une quelconque des revendications 1, 2, 4 à 8 dans laquelle au moins l'un desdits dispositifs d'ancrage (19, 21, 19a, 19b) comprend un filament soudé sur la partie d'extrémité proximale (29, 29a, 29b) associée.

11. Lentille intra-oculaire (11, 11a, 11b) telle que définie par l'une quelconque des revendications 1 à 10 dans laquelle chacun desdits dispositifs d'ancrage (19, 21, 19a, 19b) est plus rigide que le dispositif d'optique (13, 13a, 13b) et soutient des zones de ce dispositif d'optique.

12. Lentille intra-oculaire (11) conforme à l'une quelconque des revendications précédentes, dans laquelle ledit dispositif d'optique (13) est moulé sur lesdits dispositifs d'ancrage (19) et lesdites parties d'extrémité proximales (29).

13. Lentille intraculaire (11) conforme à l'une quelconque des revendications précédentes, dans laquelle les organes de fixation (15, 17) s'étendent à partir du dispositif d'optique (13) et sont inclinés par rapport au plan d'ensemble de ce dispositif d'optique (13).

Patentansprüche

Patentansprüche für folgende Vertragsstaaten:
: DE, FR, GB

1. Intraokulare Linse (11) mit:
einer einen generell kreisförmigen Umfang (27) aufweisenden Optik (13), welche zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge deformierbar ist,
einem ersten und zweiten Fixierungselement (15, 17), die jeweils ein freies Endteil (29) aufweisen,
einem ersten und zweiten langgestreckten Anker (19, 21), die jeweils an ein freies Endteil (29) des ersten bzw. zweiten Fixierungselementes (15, 17) angekoppelt sind,
einer Anordnung der Anker (19, 21) und der freien Endteile (29) in Umfangsbereichen der Optik (13), wodurch die Anker (19, 21) die Befestigung der Fixierungselemente (15, 17) an der Optik (13) unterstützen,
einer beabstandeten Anordnung der Anker (19, 21), wodurch die deformierbare Optik (13) zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge faltbar ist, und
einem langgestreckten Element in wenigstens einem der Anker (19, 21), das ein Segment

eines Bogens bildet, mit dem freien Endteil (29) des ersten Befestigungselementes (15) gekoppelt ist und generell koaxial zur Optik (13) und generell längs des Umfangs der Optik (13) verläuft,
wobei die Fixierungselemente (15, 17) von der Optik (13) ausgehen und relativ zur generellen Ebene der Optik (13) geneigt sind.

2. Intraokulare Linse (11a, 11b) mit:
einer Optik (13a, 13b), welche zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge deformierbar ist,
einem ersten und zweiten Fixierungselement (15a, 15b), die jeweils ein freies Endteil (29a, 29b) besitzen,
einem ersten und zweiten Anker (19a, 19b), die jeweils an das freie Endteil (29a, 29b) des ersten bzw. zweiten Fixierungselementes (15a, 15b) angekoppelt sind,
einer Aufnahme der Anker (19a, 19b) und der freien Endteile (29a, 29b) durch die Optik (13a, 13b),
einer Anordnung der Anker (19a, 19b) und der freien Endteile (29a, 29b) in Umfangsbereichen der Optik (13a, 13b), wodurch die Anker (19a, 19b) die Befestigung der Fixierungselemente (15a, 15b) an der Optik (13a, 13b) unterstützen,
einer beabstandeten Anordnung der Anker (19a, 19b), wodurch die deformierbare Optik (13a, 13b) zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge faltbar ist, und
eines im wesentlichen senkrechten Verlaufs wenigstens einer der Anker (19a, 19b) auf beiden Seiten des zugeordneten Fixierungselementes an der Stelle, an welcher der eine Anker mit diesem Fixierungselement gekoppelt ist.

3. Intraokulare Linse (11b) mit:
einer Optik (13b), welche zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge deformierbar einem ersten und zweiten Fixierungselement (15b), die jeweils ein freies Endteil (29b) besitzen,
einem mit dem freien Endteil (29b) des ersten Fixierungselementes (15b) gekoppelten ersten Anker (19b),
einem mit dem freien Endteil (29b) des zweiten Fixierungselementes (15b) gekoppelten zweiten Anker (19b),
einer Aufnahme der Anker (19b) und der freien Endteile (29b) durch die Optik (13b),
einer Anordnung der Anker (19b) und der freien Endteile (29b) in Umfangsbereichen der Optik (13b), wodurch die Anker (19b) die Befestigung der Fixierungselemente (15b) an der



Optik (13b) unterstützen, einer beabstandeten Anordnung der Anker (19b), wodurch die deformierbare Optik (13b) zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge faltbar ist, und einem Loch (41) im zweiten Anker (19b), das einen Bereich des freien Endteils (29b) des zweiten Fixierungselementes (15b) aufnimmt, wobei der zweite Anker (19b) quer auf beiden Seiten des zweiten Fixierungselementes (15b) an der Stelle verläuft, an welcher der zweite Anker (19b) mit dem zweiten Fixierungselement (15b) gekoppelt ist.

4. Intraokulare Linse (11) nach Anspruch 1, bei welcher das langgestreckte Element einen Faden enthält.

5. Intraokulare Linse (11) nach Anspruch 1 oder 4, bei welcher der eine Anker (19) mit dem ersten Fixierungselement (15) an einer Stelle verbunden ist, welche vom Mittelpunkt des Segmentes des Bogens beabstandet ist.

6. Intraokulare Linse nach Anspruch 1, 4 oder 5, bei welcher der andere Anker (21) einen Faden enthält, welcher ein Segment eines Bogens bildet.

7. Intraokulare Linse nach Anspruch 1, 4, 5 oder 6, bei welcher wenigstens einer der Anker (19, 21) einstückig mit dem zugehörigen Fixierungselement (15, 17) ausgebildet ist.

8. Intraokulare Linse nach Anspruch 1, 4, 5, 6 oder 7, bei welcher das erste Fixierungselement (15) ein freies Ende besitzt und das langgestreckte Element in beiden Richtungen auf entgegengesetzten Seiten des freien Endes des ersten Fixierungselementes (15) verläuft.

9. Intraokulare Linse (11a, 11b) nach Anspruch 3, bei welcher der zweite Anker (19b) einen Faden enthält, der auf das zugehörige freie Endteil (29b) gesteckt ist.

10. Intraokulare Linse (11, 11a, 11b) nach den Ansprüchen 1, 2 und 4 bis 8, bei welcher wenigstens einer der Anker (19, 21, 19a) einen Faden enthält, der an das zugehörige freie Endteil (29, 29a) angeschweißt ist.

11. Intraokulare Linse (11, 11a, 11b) nach den Ansprüchen 1 bis 10, bei welcher die Anker (19, 21, 19a, 19b) starrer als die Optik (13, 13a, 13b) sind und Bereiche der Optik stützen.

12. Intraokulare Linse (11) nach den vorhergehenden Ansprüchen, bei welcher die Optik (13) auf die Anker (19) und die freien Endteile (29) gegossen ist.

Patentansprüche für folgenden Vertragsstaat : IT

1. Intraokulare Linse (11) mit:
einer einen generell kreisförmigen Umfang (27) aufweisenden Optik (13), welche zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge deformierbar ist,
einem ersten und zweiten Fixierungselement (15, 17), die jeweils ein freies Endteil (29) aufweisen,
einem ersten und zweiten langgestreckten Anker (19, 21), die jeweils an ein freies Endteil (29) des ersten bzw. zweiten Fixierungselementes (15, 17) angekoppelt sind,
einer Anordnung der Anker (19, 21) und der freien Endteile (29) in Umfangsbereichen der Optik (13), wodurch die Anker (19, 21) die Befestigung der Fixierungselemente (15, 17) an der Optik (13) unterstützen,
einer beabstandeten Anordnung der Anker (19, 21), wodurch die deformierbare Optik (13) zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge faltbar ist, und
einem langgestreckten Element in wenigstens einem der Anker (19, 21), das ein Segment eines Bogens bildet, mit dem freien Endteil (29) des ersten Befestigungselementes (15) gekoppelt ist und generell coaxial zur Optik (13) und generell längs des Umfangs der Optik (13) verläuft.

2. Intraokulare Linse (11a, 11b) mit:
einer Optik (13a, 13b), welche zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge deformierbar ist,
einem ersten und zweiten Fixierungselement (15a, 15b), die jeweils ein freies Endteil (29a, 29b) besitzen,
einem ersten und zweiten Anker (19a, 19b), die jeweils an das freie Endteil (29a, 29b) des ersten bzw. zweiten Fixierungselementes (15a, 15b) angekoppelt sind,
einer Aufnahme der Anker (19a, 19b) und der freien Endteile (29a, 29b) durch die Optik (13a, 13b),
einer Anordnung der Anker (19a, 19b) und der freien Endteile (29a, 29b) in Umfangsbereichen der Optik (13a, 13b), wodurch die Anker (19a, 19b) die Befestigung der Fixierungselemente (15a, 15b) an der Optik (13a, 13b) unterstützen,
einer beabstandeten Anordnung der Anker



(19a, 19b), wodurch die deformierbare Optik (13a, 13b) zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge faltbar ist, und einem Querverlauf wenigstens eines der Anker (19a, 19b) auf beiden Seiten des zugeordneten Fixierungselementes an der Stelle, an welcher der eine Anker mit diesem Fixierungselement gekoppelt ist.

3. Intraokulare Linse (11b) mit:
einer Optik (13b), welche zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge deformierbar ist,
einem ersten und zweiten Fixierungselement (15b), die jeweils ein freies Endteil (29b) besitzen,
einem mit dem freien Endteil (29b) des ersten Fixierungselementes (15b) gekoppelten ersten Anker (19b),
einem mit dem freien Endteil (29b) des zweiten Fixierungselementes (15b) gekoppelten zweiten Anker (19b),
einer Aufnahme der Anker (19b) und der freien Endteile (29b) durch die Optik (13b),
einer Anordnung der Anker (19b) und der freien Endteile (29b) in Umfangsbereichen der Optik (13b), wodurch die Anker (19b) die Befestigung der Fixierungselemente (15b) an der Optik (13b) unterstützen,
einer beabstandeten Anordnung der Anker (19b), wodurch die deformierbare Optik (13b) zur Erleichterung ihres Einsetzens durch einen Schnitt in das Auge faltbar ist, und
einem Loch (41) im zweiten Anker (19b), das einen Bereich des freien Endteils (29b) des zweiten Fixierungselementes (15b) aufnimmt, wobei der zweite Anker (19b) quer auf beiden Seiten des zweiten Fixierungselementes (15b) an der Stelle verläuft, an welcher der zweite Anker (19b) mit dem zweiten Fixierungselement (15b) gekoppelt ist.
4. Intraokulare Linse (11) nach Anspruch 1, bei welcher das langgestreckte Element einen Faden enthält.
5. Intraokulare Linse (11) nach Anspruch 1 oder 4, bei welcher der eine Anker (19) mit dem ersten Fixierungselement (15) an einer Stelle verbunden ist, welche vom Mittelpunkt des Segmentes des Bogens beabstandet ist.
6. Intraokulare Linse nach Anspruch 1, 4 oder 5, bei welcher der andere Anker (21) einen Faden enthält, welcher ein Segment eines Bogens bildet.
7. Intraokulare Linse nach Anspruch 1, 4, 5 oder

6, bei welcher wenigstens einer der Anker (19, 21) einstückig mit dem zugehörigen Fixierungselement (15, 17) ausgebildet ist.

8. Intraokulare Linse nach Anspruch 1, 4, 5, 6 oder 7, bei welcher das erste Fixierungselement (15) ein freies Ende besitzt und das langgestreckte Element in beiden Richtungen auf entgegengesetzten Seiten des freien Endes des ersten Fixierungselementes (15) verläuft.
9. Intraokulare Linse (11a, 11b) nach Anspruch 3, bei welcher der eine Anker (19a, 19b) einen Faden enthält, der auf das zugehörige freie Endteil (29a, 29b) gesteckt ist.
10. Intraokulare Linse (11, 11a, 11b) nach den Ansprüchen 1, 2 und 4 bis 8, bei welcher wenigstens einer der Anker (19, 21, 19a, 19b) einen Faden enthält, der an das zugehörige freie Endteil (29, 29a, 29b) angeschweißt ist.
11. Intraokulare Linse (11, 11a, 11b) nach den Ansprüchen 1 bis 10, bei welcher die Anker (19, 21, 19a, 19b) starrer als die Optik (13, 13a, 13b) sind und Bereiche der Optik stützen.
12. Intraokulare Linse (11) nach den vorhergehenden Ansprüchen, bei welcher die Optik (13) auf die Anker (19) und die freien Endteile gegossen ist.
13. Intraokulare Linse (11) nach den vorhergehenden Ansprüchen, bei welcher die Fixierungselemente (15, 17) von der Optik (13) ausgehen und in Bezug auf die generelle Ebene der Optik (13) geneigt sind.