



- (51) **International Patent Classification:**  
*A47J 31/32* (2006.01) *A47J 31/36* (2006.01)
- (21) **International Application Number:**  
PCT/US2013/024590
- (22) **International Filing Date:**  
4 February 2013 (04.02.2013)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**  
13/370,005 9 February 2012 (09.02.2012) US
- (71) **Applicant:** **KEURIG, INCORPORATED** [US/US]; 55 Walkers Brook Drive, Reading, MA 01867-3272 (US).
- (72) **Inventors:** **COMINELLI, Tom**; 5 Starknought Heights, Gloucester, MA 01930 (US). **SHEPARD, James, E.**; 3 Calumet Lane, Marblehead, MA 01945 (US). **VITELLA, Thomas**; 23 Odell Road, Sandown, NH 03873 (US).
- (74) **Agent:** **HUNT, Robert, E.**; Wolf, Greenfield & Sacks, P.C., 600 Atlantic Avenue, Boston, MA 02210-2206 (US).
- (81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report (Art. 21(3))

(54) **Title:** LIQUID DELIVERY TANK WITH EXPANSION CHAMBER




FIG. 2

(57) **Abstract:** A beverage forming method and system employing the introduction of air into the heater tank and/or an expansion chamber after liquid delivery is complete. An expansion chamber may be provided at the top of the heater tank and provide a tortuous flow path from an air inlet to the tank outlet.