

ABNORMALITY DETECTION METHOD, APPARATUS, AND DEVICE FOR UNMANNED CHECKOUT

TECHNICAL FIELD

[0001] The present specification relates to the data processing field, and in
5 particular, to abnormality detection methods, apparatuses, and devices for unmanned
checkout.

BACKGROUND

[0002] With the development of science and technology, self-checkout or
unmanned checkout scenarios are increasingly applied to daily life, for example,
10 unmanned shops and unmanned stores. After selecting a product, the customer can
enter a specified detection area for automatic detection and payment. In the detection
area, a central control system can automatically detect the product purchased by the
customer, send the product information to a payment platform, and complete an
automatic payment operation. However, in the detection area, abnormal events may
15 occur, causing losses to merchants or customers, etc. Therefore, an effective
abnormality detection solution needs to be provided for unmanned checkout.

SUMMARY

[0003] To alleviate the problem in the related technology, the present specification
provides abnormality detection methods, apparatuses, and devices for unmanned
20 checkout.

[0004] According to a first aspect of some embodiments of the present
specification, an abnormality detection method for unmanned checkout is provided,
where a photographing area for unmanned checkout includes at least a depth camera
of a detection area, the detection area is an area for detecting a to-be-paid product, and
25 the method includes: obtaining image data in the depth camera, where the image data
includes a depth image and an RGB image; detecting, by using the image data, one or
more people that enter the detection area, where the detection includes one or more of
headcount detection and gesture detection; and when it is determined, based on the

detection result, that a predetermined abnormal condition is satisfied, notifying a central control system to stop product detection and triggering an alarm, where the abnormal condition includes one or more of the following: the quantity of the one or more people that enter the detection area is greater than a predetermined quantity
5 threshold, and a gesture of the one or more people that enter the detection area is a predetermined abnormal gesture.

[0005] In some embodiments, the step of headcount detection includes: obtaining, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, where the background
10 model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area; and if the foreground image is used to determine that the moving object is one or more people, performing connected component analysis on the foreground image with reference to a depth value in the depth image, and obtaining the quantity of the one or more people in the detection
15 area based on the analysis result.

[0006] In some embodiments, the depth image and the RGB image are obtained by the depth camera by collecting the same scenario at the same moment, and the step of gesture detection includes: obtaining, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a
20 moving object, where the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area; if the foreground image is used to determine that the moving object is one or more people, performing connected component analysis on the foreground image with reference to a depth value in the depth image, and segmenting a people
25 area in the foreground image based on the analysis result to obtain a connected component that represents an independent people; and determining the gesture of the one or more people with reference to the connected component in the depth image and an area in the RGB image and corresponding to the connected component.

[0007] In some embodiments, determining the gesture of the one or more people with reference to the connected component in the depth image and an area in the RGB
30 image and corresponding to the connected component includes: locating hands of the people in the connected component, in the depth image, that represent an independent people; if a hand area is obtained, performing skeleton detection of the hands on an area in the RGB image and corresponding to the hand area, and determining the

gesture of the one or more people based on the detection result; and if a hand area is not obtained, obtaining an independent people area in the corresponding RGB image based on the connected component that represents an independent people in the depth image, performing skeleton detection of the hands on the independent people area in the RGB image, and determining the gesture of the one or more people based on the detection result.

[0008] In some embodiments, the method further includes one or more of the following: when it is detected, by using the depth image, that one or more people enter the detection area with no people, notifying the central control system to start product detection; and when it is detected, by using the depth image, that the current one or more people leave and no other people enters the detection area, notifying the central control system to stop product detection.

[0009] According to a second aspect of some embodiments of the present specification, an abnormality detection apparatus for unmanned checkout is provided, where a photographing area for unmanned checkout includes at least a depth camera of a detection area, the detection area is an area for detecting a to-be-paid product, and the apparatus includes: a data acquisition module, configured to obtain image data in the depth camera, where the image data includes a depth image and an RGB image; an abnormality detection module, configured to detect, by using the image data, one or more people that enter the detection area, where the detection includes one or more of headcount detection and gesture detection; and an abnormality processing module, configured to: when it is determined, based on the detection result, that a predetermined abnormal condition is satisfied, notify a central control system to stop product detection and trigger an alarm, where the abnormal condition includes one or more of the following: the quantity of one or more people that enter the detection area is greater than a predetermined quantity threshold, and a gesture of the one or more people that enter the detection area is a predetermined abnormal gesture.

[0010] In some embodiments, the abnormality detection module is configured to: obtain, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, where the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area; if the foreground image is used to determine that the moving object is one or more people, perform connected component analysis on the foreground image with reference to a depth

value in the depth image, and obtain the quantity of the one or more people in the detection area based on the analysis result.

[0011] In some embodiments, the depth image and the RGB image are obtained by the depth camera by collecting the same scenario at the same moment, and the
5 abnormality detection module is configured to: obtain, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, where the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area; if the foreground image is used to determine that the
10 moving object is one or more people, perform connected component analysis on the foreground image with reference to a depth value in the depth image, and segment a people area in the foreground image based on the analysis result to obtain a connected component that represents an independent people; and determine the gesture of the one or more people with reference to the connected component in the depth image and
15 an area in the RGB image and corresponding to the connected component.

[0012] In some embodiments, the abnormality detection module is specifically configured to: locate hands of the people, in the depth image, that represent an independent people; if a hand area is obtained, perform skeleton detection of the hands on an area in the RGB image and corresponding to the hand area, and
20 determine the gesture of the one or more people based on the detection result; and if a hand area is not obtained, obtain an independent people area in the corresponding RGB image based on the connected component that represents an independent people in the depth image, perform skeleton detection of the hands on the independent people area in the RGB image, and determine the gesture of the one or more people based on
25 the detection result.

[0013] According to a third aspect of some embodiments of the present specification, a computer device is provided, including a memory, a processor, and a computer program stored in the memory and running on the processor, where a photographing area for unmanned checkout includes at least a depth camera of a
30 detection area, the detection area is an area for detecting a to-be-paid product, and the processor implements the following method when executing the program: obtaining image data in the depth camera, where the image data includes a depth image and an RGB image; detecting, by using the image data, one or more people that enter the detection area, where the detection includes one or more of headcount detection and

gesture detection; and when it is determined, based on the detection result, that a predetermined abnormal condition is satisfied, notifying a central control system to stop product detection and triggering an alarm, where the abnormal condition includes one or more of the following: the quantity of one or more people that enter the detection area is greater than a predetermined quantity threshold, and a gesture of the one or more people that enter the detection area is a predetermined abnormal gesture.

[0014] The technical solutions provided in some embodiments of the present specification have the following beneficial effects:

[0015] In some embodiments of the present specification, a photographing area for unmanned checkout includes at least a depth camera of a detection area, and one or more people that enter the detection area can be detected by using image data obtained from the depth camera. Because the image data includes a depth image and an RGB image, and the detection area is an area for detecting a to-be-paid product, the depth image and the RGB image can be used to determine whether the quantity of the one or more people in the detection area is abnormal or the gesture of the people is abnormal, and further determine whether to notify a central control system to stop product detection and trigger an alarm, so as to avoid a loss caused by an abnormality to a customer or a merchant.

[0016] It should be understood that the previous general description and the following detailed description are merely examples, and impose no limitation on the present specification.

BRIEF DESCRIPTION OF DRAWINGS

[0017] The accompanying drawings, which are incorporated in and constitute a part of the present specification, illustrate embodiments consistent with the present specification and, together with the present specification, serve to explain the principles of the present specification.

[0018] FIG. 1 is a flowchart illustrating an abnormality detection method for unmanned checkout, according to example embodiments of the present specification;

[0019] FIG. 2 is a flowchart illustrating another abnormality detection method for unmanned checkout, according to example embodiments of the present specification;

[0020] FIG. 3 is a schematic diagram illustrating an application scenario of an abnormality detection method, according to example embodiments of the present specification;

[0021] FIG. 4 is a hardware structural diagram illustrating a computer device that an abnormality detection apparatus for unmanned checkout is located, according to example embodiments of the present specification; and

[0022] FIG. 5 is a block diagram illustrating an abnormality detection apparatus for unmanned checkout, according to example embodiments of the present specification.

DESCRIPTION OF EMBODIMENTS

[0023] Example embodiments are described in detail here, and examples of the example embodiments are presented in the accompanying drawings. When the following description relates to the accompanying drawings, unless specified otherwise, same numbers in different accompanying drawings represent same or similar elements. Embodiments described in the following do not represent all embodiments consistent with the present specification. On the contrary, some embodiments are only examples of devices and methods that are described in the appended claims in details and consistent with some aspects of the present specification.

[0024] The terms used in the present specification are merely for illustrating specific embodiments, and are not intended to limit the present specification. The terms "a" and "the" of singular forms used in the present specification and the appended claims are also intended to include plural forms, unless otherwise specified in the context clearly. It should be further understood that the term "and/or" used in the present specification indicates and includes any or all possible combinations of one or more associated listed items.

[0025] It should be understood that although terms "first", "second", "third", etc. may be used in the present specification to describe various types of information, the information is not limited to the terms. These terms are only used to distinguish between information of the same type. For example, without departing from the scope of the present specification, first information can also be referred to as second information, and similarly, the second information can be referred to as the first

information. Depending on the context, for example, the word "if" used here can be explained as "while", "when", or "in response to determining".

[0026] With the development of mobile payment technologies, unmanned supermarkets appear, and they subvert the conventional retail mode because they are
5 unmanned and customers independently make payment. After selecting a product, a customer can enter a detection area for product detection, so as to implement automatic payment, for example, enter a "payment gate" for payment. However, because of "being unmanned" feature, in the detection area, there may be a case that a customer lifts a product to avoid being detected, or an abnormality such as identifying
10 a product purchased by another customer as a product purchased by the current customer.

[0027] In view of this, embodiments of the present specification provide an abnormality detection solution for unmanned checkout. In some embodiments of the present specification, a photographing area for unmanned checkout includes at least a
15 depth camera of a detection area, and one or more people that enter the detection area can be detected by using image data obtained from the depth camera. Because the image data includes a depth image and an RGB image, and the detection area is an area for detecting a to-be-paid product, the depth image and the RGB image can be used to determine whether the quantity of the one or more people in the detection area
20 is abnormal or the gesture of the one or more people is abnormal, and further determine whether to notify a central control system to stop product detection and trigger an alarm, so as to avoid a loss caused by an abnormality to a customer or a merchant.

[0028] The following exemplarily describes some embodiments of the present
25 specification with reference to the accompanying drawings.

[0029] FIG. 1 is a flowchart illustrating an abnormality detection method for unmanned checkout, according to example embodiments of the present specification. A photographing area for unmanned checkout includes at least a depth camera of a detection area, the detection area is an area for detecting a to-be-paid product, and the
30 method can include the following steps:

[0030] In step 102, obtain image data in the depth camera, where the image data includes a depth image and an RGB image.

[0031] In step 104, detect, by using the image data, one or more people that enter the detection area, where the detection includes one or more of headcount detection and gesture detection.

[0032] In step 106, when it is determined, based on the detection result, that a predetermined abnormal condition is satisfied, notify a central control system to stop product detection and trigger an alarm, where the abnormal condition includes one or more of the following: the quantity of one or more people that enter the detection area is greater than a predetermined quantity threshold, and a gesture of the one or more people that enter the detection area is a predetermined abnormal gesture.

[0033] In some embodiments, the unmanned checkout scenario can be a scenario that no manual product payment is performed, for example, a scenario such as an unmanned supermarket, an unmanned store, or an unmanned shopping mall. In some embodiments, a customer can complete a product detection operation in the detection area, and the central control system can send the detection result to a payment platform, so the payment platform completes a payment operation. For example, product detection is completed in a detection area instructed by a payment gate, and then a product payment operation is completed. In some embodiments, the payment gate can be a payment channel having at least one gate, and product detection can be completed in the channel, and a product payment operation can be completed in the channel, or does not have to be completed in the channel. For example, in some embodiments, the gate is controlled to be closed until the payment is completed. In some embodiments, because a payment account of the customer is associated in advance, the door can be controlled to be opened when product detection is completed, and a payment operation is subsequently performed, so the customer does not need to wait for the payment process to end. Therefore, the payment channel can also be referred to as a detection channel. In one example, the payment channel can be enclosed region. In another example, to improve user experience, the payment channel does not need to be enclosed region.

[0034] The method in some embodiments of the present specification can be applied to an unmanned checkout scenario. In some embodiments, the method can be applied to an embedded development board disposed in the payment channel, and the embedded development board can have a GPU operation function, so as to implement integration of abnormality detection and product detection.

Further, a model compression method can be further used to reduce the calculation amount of the embedded development board.

[0035] In unmanned checkout of some embodiments, the photographing area includes at least the depth camera of the detection area. The depth camera can be an imaging device that can collect a depth image and an RGB image. Each pixel value of the depth image can be used to represent the distance between a certain point in the scenario and the imaging device, and the pixel value can also be referred to as a depth value or depth information of the pixel. Different depth cameras can use different depth image acquisition methods. For example, a depth camera including dual RGB cameras can be used to obtain a depth image by using a stereo matching method that matches both eyes. For another example, a depth camera including an RGB camera + a structured light projector (infrared) + a structured light depth sensor can be used to obtain a depth image by using a structured light detection method. It should be understood that another depth camera and another method for obtaining a depth image can also be used, and details are omitted here for simplicity.

[0036] The photographing area of the depth camera includes at least a detection area, and the depth camera can be disposed at a location associated with the payment channel for this purpose. In some embodiments, the depth camera can be disposed at the end of the payment channel, and the depth camera can be disposed provided that the detection area can be photographed, so when a customer walks from the head end of the payment channel to the tail end, a depth value used to indicate the customer in the depth image becomes smaller and smaller.

[0037] To detect, by using the image data, one or more people that enter the detection area, the detection area can be pre-marked, so as to determine a relationship between the detection area and the image in an actual scenario. In some embodiments, an area in the image and corresponding to the detection area can be marked by detecting a specified object disposed at the edge of the detection area. For example, the specified object is disposed at the edge of the detection area in the actual scenario to determine the edge of the detection area. The depth image and the RGB image are obtained from the depth camera, image recognition is performed by using the RGB image to detect the area of the specified object in the image, and a depth value of the specified object is obtained by using the depth image, so as to complete automatic marking of the detection area. In some embodiments, the specified object can be a square plate to reduce the detection difficulty.

[0038] In some embodiments of the present specification, the one or more people that enter the detection area can be detected by using the image data, so as to determine whether an abnormal event occurs, give an alarm when an abnormal event occurs, and stop product detection. The abnormal event can be determined based on a specific application scenario, and different predetermined abnormal conditions are configured based on different abnormal events.

[0039] In some embodiments, to avoid misidentifying a product of another customer as a product of the current customer, the quantity of the one or more people that enter the detection area can be limited. The abnormal condition can include that the quantity of one or more people that enter the detection area is greater than a predetermined quantity threshold. Correspondingly, when the quantity of one or more people that enter the detection area is greater than the predetermined quantity threshold, it is determined that an abnormal event occurs. The predetermined quantity threshold is determined based on a device configured in an application scenario. In an example, the predetermined quantity threshold can be 1, so the quantity of the one or more people to enter the detection area is limited to 1. When the quantity of the one or more people is greater than 1, product detection is stopped and an alarm is triggered.

[0040] The quantity of the one or more people can be obtained based on detecting of the depth image obtained from the depth camera. For example, moving pedestrian detection and pedestrian segmentation are performed based on the depth image to obtain the quantity of the one or more people in the detection area. The following uses a specific embodiment as an example for description. The step of headcount detection can include: obtaining, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, where the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area; if the foreground image is used to determine that the moving object is one or more people, performing connected component analysis on the foreground image with reference to a depth value in the depth image, and obtaining the quantity of the one or more people in the detection area based on the analysis result.

[0041] Background modeling can be continuously updated dynamically, and data can be continuously read and background modeling can be re-performed. For example, the background model obtained in the previous update is used to determine whether there is anyone in the detection area, periodically obtain an image without anyone

included, and update the background model in the previous update by using a Gaussian background modeling method. The initial background model is obtained by initializing the collected image without anyone included.

5 **[0042]** By comparing the currently obtained depth image (the depth image of the current frame) with the background model, a foreground image used to represent a moving object can be obtained from the depth image of the current frame. For example, the depth image of the current frame is compared with the background image, the difference between the two in each corresponding pixel is calculated, and position coordinates of each pixel at which the difference satisfies a specific condition
10 are found, so as to obtain the foreground image.

15 **[0043]** In some embodiments, the background modeling process can be completed by using a depth video. When an object enters the detection area, a moving object with a change can be considered as a motion foreground, and then it is determined, by using an image recognition technology, whether the moving object is one or more people.

20 **[0044]** Because depth values of one people are often relatively close to each other, and the same individual has connectivity, connected component analysis can be performed on the foreground image with reference to the depth value in the depth image, and the quantity of the one or more people in the detection area is obtained based on the analysis result. A connected component can be an image region (Region, Blob) that is formed by foreground pixels having similar pixel values and adjacent positions in the image. The connected component analysis can refer to finding and marking each connected component in the image.

25 **[0045]** In one example, connected component analysis can be performed on the foreground image based on domain determination. Whether properties of pixels at a domain location of a pixel are similar to the property of the pixel is determined, and pixels having the similar properties are classified as the same whole. In some embodiments, being similar in the property can mean being similar in the depth value.

30 **[0046]** It can be understood from the previous embodiments that, in some embodiments, the foreground image is extracted in the background modeling method, and when it is determined that a moving object in the foreground image is one or more people, connected component analysis is performed on the foreground image with reference to the depth value in the depth image, to implement people segmentation. Compared with people segmentation by using the RGB image, the

quantity of the one or more people in the detection area can be quickly obtained, and the calculation amount is reduced.

[0047] In some embodiments, a customer may perform some abnormal behaviors, especially an abnormal gesture, so as to avoid payment. Therefore, a gesture of one or more people that enter the detection area can be detected, and when the gesture of the one or more people that enter the detection area is a predetermined abnormal gesture, it is determined that an abnormal event occurs. The predetermined abnormal gesture can be determined based on a detectable range of a product detection apparatus. For example, a gesture that can exceed the detectable range of the detection apparatus can be determined as a predetermined abnormal gesture. For example, the predetermined abnormal gesture can be a hand lifting gesture or a hand raising gesture, and a product can be prevented from being monitored when a customer makes the abnormal gesture. In some scenarios, the abnormal gesture can be further distinguished by the left and right hands, so as to avoid different determining results when different hands make the same gesture. The abnormal gesture of the left and right hands can be determined based on specific scenarios.

[0048] The gesture can be obtained based on detecting of the depth image and the RGB image obtained from the depth camera. The depth image and the RGB image are obtained by the depth camera by collecting the same scenario at the same moment. The depth image and the RGB image reflect images of the same scenario by using different data. The depth image reflects the distance between a certain point in the scenario and the imaging device by using a depth value. In one example, moving pedestrian detection, pedestrian segmentation, hands of the person locating and capturing, and gesture recognition are performed based on depth images and RGB images to obtain gestures of pedestrians in the detection area. The following uses a specific embodiment as an example for description. The step of gesture detection can include: obtaining, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, where the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area; if the foreground image is used to determine that the moving object is one or more people, performing connected component analysis on the foreground image with reference to a depth value in the depth image, and segmenting a people area in the foreground image based on the analysis result to obtain a connected component that represents an

independent people; and determining the gesture of the one or more people with reference to the connected component in the depth image and an area in the RGB image and corresponding to the connected component.

[0049] Foreground image acquisition, people determining, and connected component analysis are the same as those in the related technologies of headcount detection, and details are omitted here for simplicity. In some embodiments, the depth image is used to obtain a connected component that represents an independent people. Compared with the RGB image being used to obtain a connected component that represents an independent people, the calculation amount can be reduced.

[0050] In some embodiments, after the connected component that represents an independent people is obtained by using the depth image, the gesture of the one or more people can be determined with reference to the connected component in the depth image and an area in the RGB image and corresponding to the connected component. After the connected component is obtained, gesture recognition can be performed with reference to the RGB image and the depth image. For example, the confidence degree of a hand area is determined by using the depth image. If the confidence degree is greater than a predetermined threshold, the hand area in the depth image is mapped to the RGB image, and gesture determining is performed on an area in the RGB image and corresponding to the hand area. If the hand area cannot be determined by using the depth image, the connected component in the depth image is mapped to the RGB image, and the hand area and the gesture are determined by using the RGB image. Specifically, determining the gesture of the one or more people with reference to the connected component in the depth image and an area in the RGB image and corresponding to the connected component can include: locating hands of the people, in the depth image, that represent an independent people; if a hand area is obtained, performing skeleton detection of the hands on an area in the RGB image and corresponding to the hand area, and determining the gesture of the one or more people based on the detection result; and if a hand area is not obtained, obtaining an independent people area in the corresponding RGB image based on the connected component that represents an independent people in the depth image, performing skeleton detection of the hands on the independent people area in the RGB image, and determining the gesture of the one or more people based on the detection result.

[0051] In some embodiments, a separate depth connected component of each people can be obtained by using people segmentation information, a hand area relative

to the front of the people is obtained by using the depth information of a separate people, and finally, a left hand and a right hand are determined and captured by using a relative position between the front area and the people area, so as to obtain the hand area. The hand area in the corresponding area of the RGB image is captured by using
5 the location of the hand area obtained in the depth image, so as to obtain the hand image. Hand skeleton shape recognition is performed on the hand image to obtain the shape of the hand skeleton, and then gesture recognition is performed accordingly. For example, the hand skeleton can be obtained by using a skeleton detection of the hands method, and then the shapes of the five finger skeletons in the hand skeleton are
10 determined to implement recognition of a hand action.

[0052] It can be understood from the previous embodiments that the hand area is first obtained by using the depth image, then skeleton detection of the hands is performed on the area in the RGB image and corresponding to the hand area, and the gesture of the one or more people is determined based on the detection result, thereby
15 reducing the calculation amount.

[0053] It should be understood that the abnormal condition can further include another condition. For example, the posture of the one or more people that enter the detection area is a predetermined abnormal posture. Therefore, the detection can further include people posture detection. For another case, details are omitted here for
20 simplicity.

[0054] When the predetermined abnormal condition is satisfied, the central control system can be notified to stop product detection and an alarm is triggered. Product detection is before the payment operation. Therefore, when the product detection is interrupted, the payment operation is also interrupted. The central control system can
25 be a system for detecting a product before payment. Detecting a product can include identifying a product and obtaining product information required for payment, such as the product quantity and price. For example, a radio frequency identification (RFID) technology can be used to read an electronic tag on a product to obtain product information required for payment. Certainly, another method can be used to detect the
30 product to obtain the product information required for payment, which is not limited here. The alarm can be triggered by the current administrator by using the central control system, or the current administrator directly notifies an alarm module to perform the alarm.

[0055] It can be understood from the previous embodiments that, in some embodiments, a photographing area for unmanned checkout includes at least a depth camera of a detection area, and one or more people that enter the detection area can be detected by using image data obtained from the depth camera. Because the image data
5 includes a depth image and an RGB image, and the detection area is an area for detecting a to-be-paid product, the depth image can be used to determine whether the quantity of the one or more people in the detection area is abnormal or the depth image and the RGB image can be used to determine whether the gesture of the one or more people in the detection area is abnormal, and further determine whether to notify
10 a central control system to stop product detection and trigger an alarm, so as to avoid a loss caused by an abnormality to a customer or a merchant.

[0056] To avoid a waste of resources caused by real-time detection performed by the central control system, in some embodiments, the central control system is notified to start product detection only when it is detected, by using the depth image,
15 that one or more people enter a detection area that no people exists.

[0057] In some embodiments, the product detection function can be enabled when a people newly appears in the detection area. It can be understood that the product detection operation is triggered only when a people enters a detection area with no other people's presence in it, and the product detection function can be automatically
20 enabled.

[0058] In some embodiments, when it is detected, by using the depth image, that the current one or more people leave and no other people enters the detection area, the central control system is notified to stop product detection.

[0059] In some embodiments, when the one or more people leave the detection area
25 and no other people enters the detection area, the product detection function can be disabled. Further, within a predetermined time period after the current one or more people leave the detection area, if no other people enters the detection area, the central control system can be notified to stop product detection.

[0060] It can be understood that the product detection function can be
30 automatically disabled by using the depth image, so as to avoid a waste of resources caused by real-time detection performed by the central control system.

[0061] Various technical features in the previous embodiments can be combined randomly, provided that the combinations of the features do not conflict or contradict, and the combinations are not described one by one here due to length limitation.

Therefore, any combination of the various technical features in the previous embodiments also falls within the scope disclosed in the present specification.

[0062] The following uses one of the combinations as an example for description.

[0063] FIG. 2 is a flowchart illustrating another abnormality detection method for unmanned checkout, according to example embodiments of the present specification.
5 A photographing area for unmanned checkout includes at least a depth camera of a detection area, the detection area is an area for detecting a to-be-paid product, and the method can include the following steps:

[0064] In step 202, obtain a depth image and an RGB image of the same scene that
10 are collected by the depth camera at the same moment.

[0065] The depth camera can be in a steady-on state, or can be in a steady-on state in a specified working time period. For example, the specified working time can be the business hours of an unmanned store.

[0066] In step 204, perform a moving pedestrian detection by using the depth
15 image, if it is detected that one or more people enter a detection area that no people exists, notify a central control system to start product detection, and if it is detected that the current one or more people leave the detection area and no other people enters the detection area, notify the central control system to stop product detection.

[0067] In an example, a foreground image used to represent a moving object can be
20 obtained from the currently obtained depth image based on a background model and the depth image, and whether the moving object is one or more people is determined by using the foreground image.

[0068] In step 206, perform pedestrian segmentation on the moving pedestrian
25 detection result, to obtain a connected component that represents an independent people and the quantity of one or more people that enter the detection area, and determine the gesture of the one or more people with reference to a connected component in the depth image and an area in the RGB image and corresponding to the connected component.

[0069] Connected component analysis can be performed on the foreground image
30 with reference to a depth value of the depth image, so as to perform pedestrian segmentation.

[0070] In step 208, if the quantity of one or more people that enter the detection area is greater than a predetermined quantity threshold, notify the central control system to stop product detection and trigger an alarm.

[0071] In step 210, if the gesture of the one or more people that enter the detection area is a predetermined abnormal gesture, notify the central control system to stop product detection and trigger an alarm.

[0072] For the related technologies in FIG. 2 that are the same as those in FIG. 1,
5 details are omitted here for simplicity.

[0073] In some embodiments, moving pedestrian detection and pedestrian segmentation are implemented by using the depth image, and the gesture of the one or more people is determined with reference to the connected component in the depth image and the region in the RGB image and corresponding to the connected
10 component, thereby reducing the calculation amount. In addition, the product detection function can be automatically controlled to be enabled or disabled, so as to avoid a waste of resources caused by the product detection function being in a steady-on state. In addition, when the quantity of the one or more people in the detection area is abnormal and the gesture of the one or more people is abnormal, the
15 central control system can be notified to stop product detection and an alarm can be triggered, so as to avoid a loss caused by an abnormality to a customer or a merchant.

[0074] Some embodiments of the present specification further use a specific application scenario as an example to describe an abnormality detection solution for unmanned checkout. FIG. 3 is a schematic diagram illustrating an application scenario
20 of an abnormality detection method, according to example embodiments of the present specification. In some embodiments, a payment channel can be non-enclosed, and a depth camera can be an RGBD camera disposed at the tail end of the payment channel. The area of the payment channel is a detection area. Because a depth image and an RGB image can be obtained in real time from the RGBD camera, whether a
25 customer enters the detection area can be determined by using the depth image. If yes, a central control system can be notified to enable a product detection function. The depth image and the RGB image are used to determine whether an abnormal event occurs. When an abnormal event occurs, the central control system is prevented from detecting the product held by the customer, and an alarm is triggered to avoid a
30 conflict of interests caused by the abnormal event. If no abnormal event occurs, the central control system can continue to perform product detection, send obtained product information to a payment platform, and complete a payment operation by using the payment platform. For example, when multiple customers exist in the detection area, the central control system can be controlled to stop detecting products

held by the customers, and trigger an alarm. When a customer makes an abnormal gesture in the detection area, the central control system can be controlled to stop detecting the product held by the customer, and trigger an alarm. A gate can also be disposed at the tail end of the payment channel. When the detection or payment is
5 completed, the gate is opened to release the customer.

[0075] Corresponding to the previous embodiments of the abnormality detection method for unmanned checkout, the present specification further provides some embodiments of an abnormality detection apparatus for unmanned checkout and an electronic device that the apparatus is applied.

10 **[0076]** Some embodiments of an abnormality detection apparatus for unmanned checkout in the present specification can be applied to a computer device, and the computer device can have a GPU operation function. The apparatus embodiment can be implemented by software, hardware, or a combination of hardware and software. Software embodiment is used as an example. As a logical apparatus, the apparatus is
15 formed by reading a corresponding computer program instruction in a non-volatile memory to a memory by a processor of a computer device where the apparatus is located. In terms of the hardware level, FIG. 4 is a schematic diagram illustrating a hardware structure of a computer device that an abnormality detection apparatus for unmanned checkout is located. In addition to a processor 410, a network interface 420,
20 a memory 430, and a non-volatile memory 440 shown in FIG. 4, the computer device that an abnormality detection apparatus 431 for unmanned checkout is located in some embodiments can further include other hardware based on actual functions of the device. Details are omitted here for simplicity.

[0077] FIG. 5 is a block diagram illustrating an abnormality detection apparatus for
25 unmanned checkout, according to example embodiments of the present specification. A photographing area for unmanned checkout includes at least a depth camera of a detection area, the detection area is an area for detecting a to-be-paid product, and the apparatus includes: a data acquisition module 52, configured to obtain image data in the depth camera, where the image data can include a depth image and an RGB image;
30 an abnormality detection module 54, configured to detect, by using the image data, one or more people that enter the detection area, where the detection includes one or more of headcount detection and gesture detection; and an abnormality processing module 56, configured to: when it is determined, based on the detection result, that a predetermined abnormal condition is satisfied, notify a central control system to stop

product detection and trigger an alarm, where the abnormal condition includes one or more of the following: the quantity of one or more people that enter the detection area is greater than a predetermined quantity threshold, and a gesture of the one or more people that enter the detection area is a predetermined abnormal gesture.

5 **[0078]** In some embodiments, the abnormality detection module 54 is configured to: obtain, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, where the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area; and if the
10 foreground image is used to determine that the moving object is one or more people, perform connected component analysis on the foreground image with reference to a depth value in the depth image, and obtain the quantity of the one or more people in the detection area based on the analysis result.

[0079] In some embodiments, the depth image and the RGB image are obtained by
15 the depth camera by collecting the same scenario at the same moment, and the abnormality detection module 54 is configured to: obtain, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, where the background model is obtained based on background modeling using a depth image obtained when no moving object passes
20 through the detection area; if the foreground image is used to determine that the moving object is one or more people, perform connected component analysis on the foreground image with reference to a depth value in the depth image, and segment a people area in the foreground image based on the analysis result to obtain a connected component that represents an independent people; and determine the gesture of the
25 one or more people with reference to the connected component in the depth image and an area in the RGB image and corresponding to the connected component.

[0080] In some embodiments, the abnormality detection module 54 is specifically configured to: locate hands of the people, in the depth image, that represent an independent people; if a hand area is obtained, perform skeleton detection of the
30 hands on an area in the RGB image and corresponding to the hand area, and determine the gesture of the one or more people based on the detection result; and if a hand area is not obtained, obtain an independent people area in the corresponding RGB image based on the connected component that represents an independent people in the depth image, perform skeleton detection of the hands on the independent people

area in the RGB image, and determine the gesture of the one or more people based on the detection result.

[0081] In some embodiments, the abnormality processing module 56 is further configured to perform one or more of the following: when it is detected, by using the depth image, that one or more people enter the detection area with no people, notifying the central control system to start product detection; and when it is detected, by using the depth image, that the current one or more people leave and no other people enters the detection area, notifying the central control system to stop product detection.

[0082] Because the apparatus embodiments basically correspond to the method embodiments, for related parts, references can be made to related descriptions in the method embodiment. The previously described apparatus embodiment is merely an example. The modules described as separate parts may or may not be physically separate, and parts displayed as modules may or may not be physical modules, may be located in one position, or may be distributed on a plurality of network modules. Some or all of the modules can be selected based on actual needs to achieve the objectives of the solutions of the present specification. A person of ordinary skill in the art can understand and implement some embodiments of the present application without creative efforts.

[0083] Correspondingly, some embodiments of the present specification further provide a computer device, including a memory, a processor, and a computer program stored in the memory and running on the processor, where a photographing area for unmanned checkout includes at least a depth camera of a detection area, the detection area is an area for detecting a to-be-paid product, and the processor implements the following method when executing the program: obtaining image data in the depth camera, where the image data includes a depth image and an RGB image; detecting, by using the image data, one or more people that enter the detection area, where the detection includes one or more of headcount detection and gesture detection; and when it is determined, based on the detection result, that a predetermined abnormal condition is satisfied, notifying a central control system to stop product detection and triggering an alarm, where the abnormal condition includes one or more of the following: the quantity of one or more people that enter the detection area is greater than a predetermined quantity threshold, and a gesture of the one or more people that enter the detection area is a predetermined abnormal gesture.

[0084] Some embodiments in the present specification are described in a progressive way. For same or similar parts of some embodiments, references can be made to some embodiments. Each embodiment focuses on a difference from other embodiments. Particularly, a device embodiment is similar to a method embodiment,
5 and therefore is described briefly. For related parts, references can be made to related descriptions in the method embodiment.

[0085] A computer storage medium, where the storage medium stores program instructions, and the program instructions include: obtaining image data in the depth camera, where the image data includes a depth image and an RGB image; detecting,
10 by using the image data, one or more people that enter the detection area, where the detection includes one or more of headcount detection and gesture detection; and when it is determined, based on the detection result, that a predetermined abnormal condition is satisfied, notifying a central control system to stop product detection and triggering an alarm, where the abnormal condition includes one or more of the
15 following: the quantity of one or more people that enter the detection area is greater than a predetermined quantity threshold, and a gesture of the one or more people that enter the detection area is a predetermined abnormal gesture.

[0086] Embodiments of the present specification can be used in a form of a computer program product implemented on one or more storage media (including but
20 not limited to a disk memory, a CD-ROM, an optical memory, etc.) including program code. A computer readable storage medium includes persistent, non-persistent, removable, and unmovable media that can store information by using any method or technology. The information can be a computer readable instruction, a data structure, a program module, or other data. A computer storage medium includes
25 but is not limited to a phase change memory (PRAM), a static random access memory (SRAM), a dynamic random access memory (DRAM), a random access memory (RAM) of another type, a read-only memory, an electrically erasable programmable read-only memory (EEPROM), a flash memory or another memory technology, a compact disc read-only memory (CD-ROM), a digital versatile disc (DVD), or
30 another optical storage, a cassette, a cassette magnetic disk storage, or another magnetic storage device or any other non-transmission medium. The computer storage medium can be configured to store information that can be accessed by a computing device.

- [0087] Persons skilled in the art can easily figure out another embodiment of the present specification after considering the present specification and practicing the present application here. The present specification is intended to cover any variations, uses, or adaptations of the present specification, and these variations, uses, or adaptations follow the general principles of the present specification and include common knowledge or conventional techniques that are not disclosed in the technical field of the present specification. The present specification and some embodiments are merely considered as examples, and the actual scope and the spirit of the present specification are pointed out by the following claims.
- 10 [0088] It should be understood that the present specification is not limited to the precise structures that have been described above and shown in the drawings, and various modifications and changes can be made without departing from the scope of the present specification. The scope of the present specification is limited by the appended claims only.
- 15 [0089] The previous descriptions are merely preferred embodiments of the present specification, but are not intended to limit the present specification. Any modification, equivalent replacement, or improvement made without departing from the spirit and principle of the present specification shall fall within the protection scope of the present specification.

20

CLAIMS

What is claimed is:

1. An abnormality detection method for unmanned checkout, wherein a
5 photographing area for unmanned checkout comprises at least a depth camera of a
detection area, the detection area is an area for detecting a to-be-paid product, and the
method comprises:

obtaining image data in the depth camera, wherein the image data comprises a
depth image and an RGB image;

10 detecting, by using the image data, one or more people that enter the detection
area, wherein the detection comprises one or more of headcount detection and gesture
detection; and

when it is determined, based on the detection result, that a predetermined
abnormal condition is satisfied, notifying a central control system to stop product
15 detection and triggering an alarm, wherein the abnormal condition comprises one or
more of the following: the quantity of one or more people that enter the detection area
is greater than a predetermined quantity threshold, and a gesture of the one or more
people that enter the detection area is a predetermined abnormal gesture.

2. The method according to claim 1, wherein the step of headcount detection
20 comprises:

obtaining, from the currently obtained depth image based on a background model
and the depth image, a foreground image for representing a moving object, wherein
the background model is obtained based on background modeling using a depth image
obtained when no moving object passes through the detection area; and

25 if the foreground image is used to determine that the moving object is one or
more people, performing connected component analysis on the foreground image with
reference to a depth value in the depth image, and obtaining the quantity of the one or
more people in the detection area based on the analysis result.

3. The method according to claim 1, wherein the depth image and the RGB
30 image are obtained by the depth camera by collecting the same scenario at the same
moment, and the step of gesture detection comprises:

obtaining, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, wherein the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area;

- 5 if the foreground image is used to determine that the moving object is one or more people, performing connected component analysis on the foreground image with reference to a depth value in the depth image, and segmenting a people area in the foreground image based on the analysis result to obtain a connected component that represents an independent people; and
- 10 determining the gesture of the one or more people with reference to the connected component in the depth image and an area in the RGB image and corresponding to the connected component.

4. The method according to claim 3, wherein determining the gesture of the one or more people with reference to the connected component in the depth image and an area in the RGB image and corresponding to the connected component comprises:
- 15

locating hands of the people, in the depth image, that represent an independent people;

- if a hand area is obtained, performing skeleton detection of the hands on an area in the RGB image and corresponding to the hand area, and determining the gesture of the one or more people based on the detection result; and
- 20

- if a hand area is not obtained, obtaining an independent people area in the corresponding RGB image based on the connected component that represents an independent people in the depth image, performing skeleton detection of the hands on the independent people area in the RGB image, and determining the gesture of the one or more people based on the detection result.
- 25

5. The method according to any one of claims 1 to 4, wherein the method further comprises one or more of the following:

- when it is detected, by using the depth image, that one or more people enter the detection area with no people, notifying the central control system to start product detection; and
- 30

when it is detected, by using the depth image, that the current one or more people leave and no other people enters the detection area, notifying the central control system to stop product detection.

6. An abnormality detection apparatus for unmanned checkout, wherein a photographing area for unmanned checkout comprises at least a depth camera of a detection area, the detection area is an area for detecting a to-be-paid product, and the apparatus comprises:

5 a data acquisition module, configured to obtain image data in the depth camera, wherein the image data comprises a depth image and an RGB image;

 an abnormality detection module, configured to detect, by using the image data, one or more people that enter the detection area, wherein the detection comprises one or more of headcount detection and gesture detection; and

10 an abnormality processing module, configured to: when it is determined, based on the detection result, that a predetermined abnormal condition is satisfied, notify a central control system to stop product detection and trigger an alarm, wherein the abnormal condition comprises one or more of the following: the quantity of one or more people that enter the detection area is greater than a predetermined quantity
15 threshold, and a gesture of the one or more people that enter the detection area is a predetermined abnormal gesture.

7. The apparatus according to claim 6, wherein the abnormality detection module is configured to:

 obtain, from the currently obtained depth image based on a background model
20 and the depth image, a foreground image for representing a moving object, wherein the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area;

 if the foreground image is used to determine that the moving object is one or more people, perform connected component analysis on the foreground image with
25 reference to a depth value in the depth image, and obtain the quantity of the one or more people in the detection area based on the analysis result.

8. The apparatus according to claim 6, wherein the depth image and the RGB image are obtained by the depth camera by collecting the same scenario at the same moment, and the abnormality detection module is configured to:

30 obtain, from the currently obtained depth image based on a background model and the depth image, a foreground image for representing a moving object, wherein the background model is obtained based on background modeling using a depth image obtained when no moving object passes through the detection area;

if the foreground image is used to determine that the moving object is one or more people, perform connected component analysis on the foreground image with reference to a depth value in the depth image, and segment a people area in the foreground image based on the analysis result to obtain a connected component that
5 represents an independent people; and

determine the gesture of the one or more people with reference to the connected component in the depth image and an area in the RGB image and corresponding to the connected component.

9. The apparatus according to claim 8, wherein the abnormality detection module
10 is specifically configured to:

locate hands of the people, in the depth image, that represent an independent people;

if a hand area is obtained, perform skeleton detection of the hands on an area in the RGB image and corresponding to the hand area, and determine the gesture of the
15 one or more people based on the detection result; and

if a hand area is not obtained, obtain an independent people area in the corresponding RGB image based on the connected component that represents an independent people in the depth image, perform skeleton detection of the hands on the independent people area in the RGB image, and determine the gesture of the one or
20 more people based on the detection result.

10. The apparatus according to any one of claims 6 to 9, wherein the abnormality processing module is further configured to perform one or more of the following:

when it is detected, by using the depth image, that one or more people enter the detection area with no people, notifying the central control system to start product
25 detection; and

when it is detected, by using the depth image, that the current one or more people leave and no other people enters the detection area, notifying the central control system to stop product detection.

11. A computer device, comprising a memory, a processor, and a computer
30 program stored in the memory and running on the processor, wherein a photographing area for unmanned checkout comprises at least a depth camera of a detection area, the detection area is an area for detecting a to-be-paid product, and the processor implements the following method when executing the program:

obtaining image data in the depth camera, wherein the image data comprises a depth image and an RGB image;

detecting, by using the image data, one or more people that enter the detection area, wherein the detection comprises one or more of headcount detection and gesture

5 detection; and

when it is determined, based on the detection result, that a predetermined abnormal condition is satisfied, notifying a central control system to stop product detection and

triggering an alarm, wherein the abnormal condition comprises one or more of the

following: the quantity of one or more people that enter the detection area is greater

10 than a predetermined quantity threshold, and a gesture of the one or more people that

enter the detection area is a predetermined abnormal gesture.