

METAL SEAT SEAL WITH FLEXIBLE SEALING EDGE

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] This invention relates in general to gate valve seat seals, and in particular to a metal seat seal that has a flexible sealing edge to form a dual seal.

2. Description of the Prior Art

[0002] Gate valves have been used on subsea wellhead assemblies for a number of purposes. In such service usage, gate valves have been required to provide reliable sealing under harsh service conditions, which include high pressure, wide temperature ranges, the presence of corrosive fluids, sand particles, debris and the like. A number of gate valves have used various forms of seals which have been formed of elastomeric or other non-metallic materials and fitted at the locations required for sealing against fluid leakage. However, so far as is known, such non-metallic seals have been regarded as often failing to meet the requirement of sealing under harsh service conditions.

SUMMARY OF THE INVENTION

[0003] Briefly, the present invention provides a new and improved valve seat, having a tubular body member for mounting in a valve body. The tubular body of the valve seat has a rearward end and a forward end for engagement by a valve element. The tubular body member further has a passage having a longitudinal axis and extending from the forward end through the tubular body member to the rearward end. A flexible lip is formed on the tubular body member at the rearward end. The flexible lip extends rearwardly outwardly from the rearward end of the tubular body member and has a curved rearward sealing surface formed thereon for sealing

engagement with the valve body. The flexible lip further extends radially outwardly beyond an outer diameter of the tubular body member and has a radial outward sealing surface formed thereon for sealing engagement with the valve body.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 is an isometric view, partially broken away, of a gate valve having seat seal according to the present invention.

[0005] FIG. 2 is an enlarged sectional view of one of the seat rings of the gate valve of FIG. 1

[0006] FIG. 3 is a further enlarged sectional view of a portion of the seat ring of FIG. 2.

[0007] FIG. 4 is an enlarged sectional view of the structure of FIG. 3 illustrating a first of the dual seals formed with the present invention.

[0008] FIG. 5 is an enlarged sectional view of the structure of FIG. 3 illustrating a second of the dual seals formed with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0009] Referring to FIG. 1, gate valve 10 has a body 12 which has a longitudinally extending passage 14 which is connected at each end to a flowline or other mating equipment (not shown). The passage 14 extends transversely through the valve body 10 from opposite sides and through a vertically extending central cavity 16. A pair of seat rings 20 are mounted on each side of the central cavity 16 at the juncture of the passage 14 and cavity 16 in circumferentially extending counterbores 22. The counterbores 22 extend along central axes which are coaxial with the longitudinal axis of the passage 14.

[0010] A gate member 24 of the gate valve 10 moves within cavity 16 between an open position, which is shown in FIG. 1, and a closed position. Gate 24 may be a split slab or may be a single slab as shown. Gate 24 has a central opening 26 through it that registers with passage 14 when in the open position. An actuator stem 28 causes gate 24 to move between the open and closed positions. Stem 28 may be either a non-rising type or a type that moves along its axis when rotated. Actuator stem 28 is operated by a valve actuator 30, which may be of the hydraulic, electrical, or manual type, to move the gate 24 between the closed and open positions.

[0011] Referring to FIG. 2, a seat ring 20 according to the present invention is located within each of the counterbores 22 with a slight clearance in the valve body 12. The seat ring 20 may be formed, for example, from 17-4 ph stainless steel or 718 nickel steel alloy. It should be understood that other steels may also be used, if desired. Seat ring 20 is a tubular member having an outer diameter surface 32 that fits closely in counterbore 22 and an inner passage 34 which has a diameter corresponding to the inner diameter of the passage 14. Inner passage 34 thus has effectively the inner diameter as passage 14. Seat ring 20 has a forward end or face 36 formed on a forward end for engagement by gate 24 (FIG. 1). The front end or face 36 of the seat ring 20 may take any of several conventional forms. By way of example the front face 36 of seat ring 20 may be of the type set forth in commonly owned U. S. Patent No. 7,325,783, which is incorporated herein by reference.

[0012] Seat ring 20 according to the present invention is provided with a cylindrical metal sealing lip or collar member 40 (Figure 3) formed extending outwardly and radially away from an annular rear shoulder or collar surface 42 on a rear face 44. The sealing lip 40 has an inclined rear face 46 extending outwardly from a rounded or arcuate transition surface 48 adjacent the

rear surface 42. The inclined rear face 46 is a rear wall of the circumferentially extending sealing lip or collar member 40.

[0013] The rear face 46 of the sealing lip 40 extends radially outwardly and away to a first rounded, circumferentially extending contact and sealing surface 52. When the lip 40 is unflexed (FIG. 3), the sealing surface 52 extends rearwardly and outwardly beyond the vertical plane of the rear face 44. The lip 40 is flexible, however, and the sealing surface 52 provides, in a manner to be set forth, a first of the dual seals according to the present invention. The sealing occurs due to sealing contact of surface 52 with an inner transverse wall 22a of the counterbore 22.

[0014] The sealing ring 46 has a circumferentially extending inclined outer rim surface 54 formed between the first sealing surface 52 on an outer portion 56 of the sealing collar 40. A second rounded, circumferentially extending contact and sealing surface 58 is formed on an inner portion of the sealing collar member 40 opposite the first sealing surface 52. When the lip 40 is unflexed (FIG. 2), the sealing surface 58 extends radially outwardly beyond the outer diameter 32 of the sealing ring 20. The surface 58 on flexible lip 40 provides, in a manner to be set forth, a second of the dual seals according to the present invention by sealing with a cylindrical inner wall 22b of the counterbore 22. The sealing occurs due to sealing contact of surface 58 with an inner cylindrical wall 22b of the counterbore 22. The sealing ring 46 has an inwardly extending inclined surface 60 extending from the surface 56 to a rounded or arcuate juncture 62 with an inner face 64 of the seat ring 20 to define a chamber 66.

[0015] In one example, seat ring 20 begins at the arcuate transition surface 48 beginning at an upper end of the rear shoulder 42. The rear face 46 of the sealing lip 40 extends radially

outwardly (FIG. 3) from the vertical upwardly to the first sealing contact surface 52. The first sealing contact surface 52 extends rearwardly beyond the vertical plane of the rear surface 42 in an unflexed position or condition. The outer rim surface 54 extends from contact surface 52 at an angle from the vertical to the second sealing surface 58. The second sealing surface 58 is also rounded to an arcuate surface. The second sealing contact surface 58 extends radially outwardly beyond the outer diameter of the seat ring 20 in the unflexed position, due to the clearance between the outer diameter of seat ring 20 and the side wall of counterbore 22.

[0016] The inwardly extending inclined surface 60 is formed at an angle (FIG. 3) from the vertical downwardly to the arcuate juncture 62, which is rounded with an arcuate surface. The transition surface between the inner passage 14 and the rear shoulder 42 has an inclined bevel or chamfer surface at an angle from vertical, and the rear end of an outer wall of the seat ring 20 has a similar chamfer or bevel surface (FIG. 3).

[0017] During operation of the present invention, as a load is applied the seat ring 20 moves rearwardly in the counterbore 22 and the first sealing surface 52 contacts the rear wall 22a of the counterbore. As the seat ring 20 continues rearward movement, the sealing lip 40 flexes forwardly towards the remaining structure of the seat ring 20. The flexure or deflection is essentially elastic and non-permanent. The first metal to metal seal according to the present invention is thus formed between surface 52 and the rear wall 22a of the counterbore 22.

[0018] As applied forces on the seat ring 20 increase, contact is made between the rear surface 44 of the seat ring 20 (FIG. 5) and the rear wall 22a. At this time, lip 40 flexes and surface 52 continues in sealing engagement with rear wall 22a. As flexure of the lip occurs, contact is made

by the second sealing surface 58 against inner cylindrical wall 22b of the counterbore 22, forming the second metal to metal seal according to the present invention.

[0019] As can be seen, the gate valve seat the seat ring 20 according to the present invention flexes when loaded from pressure on the closed gate. The gate valve 10 is provided with a floating seat with static metal sealing by lip 40 on the seat to the body or rearward side at surface 52, as well as on the seat to gate or outward side at surface 58. The structure of the lip 40 causes a metal to metal seal to be formed in these two places when the seat is loaded due to pressure when the gate valve 10 is closed.

[0020] The seals formed according to the present invention are reliable in harsh service conditions because of the metal to metal seals formed. The seat ring 20 according to the present invention thus provides increased reliability and permits gate valve usage under a wider range of applications.

[0021] While the invention has been shown in its preferred form, it should be apparent to those skilled in the art that it is not so limited but is susceptible to various changes without departing from the scope of the invention.

CLAIMS

What is claimed is:

1. A valve seat, comprising: a tubular body member for mounting in a valve body, a rearward end, the tubular body member having: a forward end for engagement by a valve element; a rearward end; a passage having a longitudinal axis and extending from forward end through the tubular body member to the rearward end; and a flexible lip formed on the tubular body member at the rearward end, the flexible lip extending rearwardly outwardly from the rearward end of the tubular body member and having a curved rearward sealing surface formed thereon for sealing engagement with the valve body; the flexible lip further extending radially outwardly beyond an outer diameter of the tubular body member and having a radial outward sealing surface formed thereon for sealing engagement with the valve body.
2. The valve seat according to claim 1, wherein the flexible lip extends radially outwardly in a plane inclined relative to the longitudinal axis of the passage in the tubular body member.
3. The valve seat according to claim 1, wherein the flexible lip has a thickness which decreases between an inner end adjacent the tubular body member and the sealing surfaces.
4. The valve seat according to claim 1, wherein the tubular body member is mountable in a cylindrical counterbore having a rear wall and a cylindrical side wall in the valve body and the rearward sealing surface of the flexible lip is engageable with the rear wall of the counterbore.
5. The valve seat according to claim 1, wherein the tubular body member is mountable in a cylindrical counterbore having a rear wall and a cylindrical side wall in the valve body and the

outward sealing surface of the flexible lip is engageable with the cylindrical side wall of the counterbore.

6. The valve seat according to claim 1, wherein the flexible lip has an outer rim surface extending between the rearward and outward sealing surfaces, and the outer rim surface is inclined with respect to the longitudinal axis of the passage in the tubular body member.

7. The valve seat according to claim 1, wherein the tubular body member has a rear cylindrical sleeve portion formed on its rear end and the flexible lip is formed on the rear cylindrical sleeve portion.

8. The valve seat according to claim 7, wherein an arcuate transition surface is formed on a lower base portion of the flexible lip adjacent a rear surface on which the rearward sealing surface is formed.

9. A valve seat mounted in a valve, the valve seat comprising: a tubular body member for mounting in a valve body, a rearward end, the tubular body member having: a forward end for engagement by a valve element; a rearward end; a passage having a longitudinal axis and extending from forward end through the tubular body member to the rearward end; and a flexible lip formed on the tubular body member at the rearward end, the flexible lip extending rearwardly outwardly from the rearward end of the tubular body member and having a curved first sealing surface formed thereon for sealing engagement with the valve body; the flexible lip further extending radially outwardly beyond an outer diameter of the tubular body member and having a radial second sealing surface formed thereon for sealing engagement with the valve body.

10. The valve seat according to claim 9, wherein the flexible lip extends radially outwardly in a plane inclined relative to the longitudinal axis of the passage in the tubular body member.
11. The valve seat according to claim 9, wherein the flexible lip extends radially outwardly in a plane inclined relative to the longitudinal axis of the passage in the tubular body member.
12. The valve seat according to claim 9, wherein the tubular body member is mountable in a cylindrical counterbore having a rear wall and a cylindrical side wall in the valve body and the first sealing surface of the flexible lip is engageable with the rear wall of the counterbore.
13. The valve seat according to claim 9, wherein the tubular body member is mountable in a cylindrical counterbore having a rear wall and a cylindrical side wall in the valve body and the second sealing surface of the flexible lip is engageable with the cylindrical side wall of the counterbore.
14. The valve seat according to claim 9, wherein the flexible lip has an outer rim surface extending between the first and second sealing surfaces, and the outer rim surface is inclined with respect to the longitudinal axis of the passage in the tubular body member.
15. The valve seat according to claim 9, wherein the tubular body member has a rear cylindrical sleeve portion formed on its rear end and the flexible lip is formed on the rear cylindrical sleeve portion.
16. The valve seat according to claim 9, wherein an arcuate transition surface is formed on a lower base portion of the flexible lip adjacent a rear surface on which the first sealing surface is formed.