

ELECTRIC TOOTHBRUSH WITH AT LEAST ONE BRUSH HEAD

This invention relates to electric toothbrushes including
5 those powered by a rechargeable battery from a mains
domestic electricity supply.

BACKGROUND TO THE INVENTION

10 In US patent No. 5,226,206, there is described an electric
toothbrush having twin brush heads which are drivingly
connected together by a rack and pinion assembly in which
the rack is reciprocated via a drive shaft connected to a
crank shaft mounted at one end for rotation on a gear
15 driven by a motor. The twin brush heads are therefore able
to oscillate about their respective axes either in the same
direction or in opposite directions, depending upon the
configuration of the rack, this being generally 'U' shaped
so as to facilitate the use of gear teeth on the inside
20 thereof for driving the respective heads via respective
pinions in mesh therewith.

A potential problem with this arrangement is that it is
relatively complex and is not easily cleanable with running
25 water such that the moving parts may become clogged with
toothpaste or debris. In addition, the complexity and
number of the parts used to provide the oscillating motion

for the twin heads adds to the cost and complexity of manufacture.

In US 5,353,460 the use of a rack and pinion assembly is
5 dispensed with in favour of a crank mechanism connecting
the first brush head to the second brush head. The first
brush head is directly driven by a mitre gear or crown
wheel which then, in turn, drives the second brush head to
oscillate in the opposite direction to that of the first
10 brush head. This arrangement involves fewer moving parts
but still depends on the presence of gears and the crank
mechanism for its operation, leading to the possibility of
these moving parts being difficult to clean and becoming
clogged etc. In addition, because the crank arm
15 necessarily has to connect the respective brush heads on
the sides thereof remote from the bristles, it will be
understood that additional space is required to provide for
free movement of the crank arm when the brush is in use.
This also has the disadvantage in that the working ends of
20 the crank linkage can never be directly exposed to running
water for rinsing and cleaning purposes.

In a first aspect the present invention is derived from the
realisation that it would be preferable to have an electric
25 toothbrush having multiple, such as two, rotatable brush
heads but which dispenses with the need for gears or crank
mechanisms for transferring oscillating rotary motion from

one brush to another, typically a first brush driven by a connection to an electric motor and the second brush driven by movement of the first brush.

5 SUMMARY OF THE INVENTION

According to a first aspect of the invention there is provided an electric toothbrush having a housing containing an electric motor, the motor being drivingly connected to a
10 first brush head rotatably mounted on an end of the toothbrush remote from the motor adjacent to at least one other rotatable brush head, wherein the first brush head includes a drive pin extending therefrom substantially at right angles from the axis of rotation, the free end of the
15 drive pin being received within a guide slot in a brush head to be driven thereby, the arrangement being such that the drive pin bears against respectively opposite sides of the guide slot to thereby drive a driven brush head clockwise and anti-clockwise about its axis of rotation as
20 the first brush head is also being oscillated.

This arrangement has the advantage in that the connection between two or more brush heads is extremely simple and since there are no moving parts other than the free end of
25 the or each drive pin as it rocks back and forth within the or a respective guide slot, such can be easily cleaned under running water. A further advantage is that the

mechanical motion of the brush head driven by the first brush head is necessarily magnified slightly due to its displacement from the first brush head and this overcomes any backlash that may be inherent in the system.

5

Although a preferred embodiment of the invention uses only two brush heads, one driven directly via the drive link between the electric motor and the brush itself and the other being driven by a drive pin extending from the periphery of the first brush head, nevertheless it will be apparent that the same principle can be used to drive more than a second brush head and, in turn, the second brush head may itself drive a third brush head, and so on. Additionally, one or more of the brush heads may be of different diameter to the first brush head, although it will be appreciated that where there are differences in diameter a consideration of equivalent gear ratios then becomes necessary to determine whether the difference is too great to allow for the required movement.

20

The means by which the first brush head is driven back and forth about its axis may comprise a bell crank arrangement in which an elbowed end of a crankshaft, drivingly connected at its other end to the motor, is received within an elongated slot extending into the periphery of the first brush head diametrically opposite the drive pin (for a twin brush head toothbrush), the length of the slot being at

25

least as great as the range of movement available to the elbow when the crankshaft is rotated through 360°.

The use of a drive pin for driving a second brush head has a still further advantage to the linkages referred to in the preamble hereto in that the second head may have a plane of rotation which is angled relative to the plane of rotation of the first brush head, such as being angled inwardly slightly, although it will be understood that there are practical limits to the amount that a second or even more such brush heads can be angled with respect to the plane of rotation of the first brush head.

Preferably, the end of the elbowed end of the crankshaft and the or each drive pin is partly spherical and takes the form of a ball joint, each being receivable within a respective slot of substantially the same diameter so as to minimise rattle and wear. A convenient arrangement has been found to be a ball joint made of nylon where the bristle holding part of the brush heads are made of e.g. PVC or some other suitable plastics material. Preferably, the slot for receiving each ball joint is partly arcuate so as to maximise the surface area in contact between the ball joint to thereby decrease the load forces on the slot and therefore reduce wear.

According to a second embodiment of the invention, the toothbrush is packaged in e.g. a blister pack and includes a "try me" facility for remotely testing the operation of the toothbrush, such as by a prospective purchaser of the toothbrush, whilst the toothbrush is still in its protective sales packaging, which "try me" feature comprises a two-sided metal foil or strip (such as aluminium foil), separated by a di-electric material such as paper or plastics, respective sides of the foil or strip being connected at one end to respective conductors of an electric circuit used to operate the electric toothbrush and, in particular, to energise the electric motor thereof, the other end of the foil or strip being folded over and including a centrally disposed aperture onto or over which is disposed a bendable metal connector such that upon bending or pressing of the connector the two sides of the strip or foil are electrically connected together to temporarily operate the toothbrush whilst still in its packaging.

Preferably, the "try me" feature may be permanently disconnected from the toothbrush after being purchased by simply being pulled away from the electrical connectors to which it is attached.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described, by way of example
5 only, with reference to the accompanying drawings in which:

Figure 1 is a side elevation of a toothbrush according to a
first embodiment of the invention having a pair of brush
heads, one of which is angled inwardly slightly with
10 respect to the other;

Figure 2 is an enlarged and partly cut away view of the end
of the toothbrush of Figure 1 which includes the brush
heads;

15 Figure 3 is a schematic plan view showing the mode of
operation of the toothbrush heads of Figure 1 and 2,

Figure 4 is an enlarged schematic view of the brush head
20 end of a toothbrush according to a preferred embodiment of
the invention, and,

Figure 5 is a section of elevation along the line "A" - "A"
of part of Figure 5.

25 Figure 6 is a perspective and partly cut away view of a
second embodiment of the invention, which includes a "try

me" feature.

DETAILED DESCRIPTION OF THE DRAWINGS

5 Referring firstly to Figure 1, an electric toothbrush shown generally at 1 comprises a plastics body portion 2 for housing a motor, battery and associated electrical circuitry (not shown) and a detachable generally hollow
10 brush head holder 3 including at the free end thereof a first brush head 4 and a second brush head 5, each being partly rotatable by being drivingly connected to the motor in the housing 2 in a manner to be described. A push button 6 in the housing 2 is used to operate the toothbrush 1 and a "try me" feature shown generally at 7 can be used
15 to temporarily operate the toothbrush 1 in accordance with a second embodiment of the invention in a manner to be described with reference to Figure 6.

In Figures 2 and 3 there is shown the operable end of the
20 brush head holder 3 in which it will be seen that the first brush head 4 includes a generally disc-shaped bristle holder 8 from which extend respective sets of bristles shown generally at 9 in Figure 2. similarly, the second brush head 5 comprises a generally disc-shaped bristle
25 holder 10 from which extend sets of bristles shown generally at 11. Brush head 4 is mounted for rotation on a pivot pin 12 and brush head 5 is mounted for rotation on a

pivot pin 13, although the plane of rotation of brush head 5 is slightly offset to the plane of rotation of brush head 4 by about 5° such that the bristles 11 are inclined slightly inwardly towards the bristles 9. This has been found to be advantageous in that the brush heads 4,5 can collectively clean a greater surface area of teeth than would be the case if both were rotatable in the same plane, by virtue of the generally curved placement of teeth within a mouth.

10

Reciprocating clockwise and anti-clockwise rotation of the first brush head 4 is facilitated by means of a bell crank mechanism which includes a stainless steel crankshaft 14 secured for rotation about its major axis in a journal 15 extending from a spigot 16 on the inside of the brush head holder 3 as shown more clearly in Figure 2. The end of the crankshaft adjacent thereto includes an elbow joint 17, the free end of which extends into a slotted region 18 within the bristle holder 8 of the brush head 4, which slotted region 18 is sufficiently long (or tall) to accommodate 360° rotation of the crankshaft 14 and in particular movement of the elbow 17 about the major axis of the crankshaft 14 so that upon rotation thereof continuously clockwise or anti-clockwise it will be apparent that the brush head 4 will be forced to oscillate back and forth about the pivot 12.

25

Brush head 5 is driven in a different manner by means of a drive pin 19 which extends diametrically outwardly from the bristle holder 8 of the brush 4, to which it is fixed for rotation therewith, and is received in a slotted region 20 of the bristle holder 10 of the brush head 5. In this case, the slotted region 20 is wide enough to permit the drive pin 19 to move in an arc dictated by the movement of the elbow 17 within the slotted region 18 about the major axis of the crankshaft 14 but in an opposite sense so that clockwise movement of the brush head 4 causes anticlockwise movement of the brush head 5, and vice versa.

As will be understood by those skilled in the art, the absence of any gears in this part of the electric toothbrush 1 enables it to be easily cleaned in running water and because there are few moving parts as compared to toothbrushes which include gears or crank arms for driving the or each brush head it will be appreciated that manufacture of the toothbrush according to the first embodiment of the invention can be easily facilitated.

In Figures 4 and 5 there is shown a preferred embodiment of the engagement between the elbowed end 17 of the crankshaft 14 with the slot 18 in the first brush head 8 and between the drive pin 19 within the slot 20 in the second brush head 10. In each case a respective part-spherical ball joint 21, 22 made of nylon are received within the

respective slots 18, 20, which in this instance are partly arcuate so as to maximise the surface area available for contact by the ball joints 21, 22. This has the advantage of minimising wear and in practice it has been found that the use of nylon in the ball joints 21, 22 gives excellent results in terms of self-lubrication properties when the brush heads 8,10 are made of a suitable plastics material, such as PVC. As well, it will be apparent that during use of the toothbrush, saliva and indeed debris from foodstuffs being cleaned will also assist in lubricating the moving parts, whereafter they may be cleaned in running water with little risk of particles of debris adhering to the generally smoothly profiled surfaces in this region of the toothbrush.

In Figures 4 and 5 the locus of movement of the ball joint 21 is shown in which it will be seen that as the crankshaft 14 rotates in one direction only the ball joint 21 essentially assumes maximum upper and lower positions about the central axis of the crankshaft 14 within the slot 18 as shown in Figure 5 and left to right positions as shown in Figure 4 to thereby drive the bristle holder 8 back and forth about its central axis in the manner shown arrowed to, in turn, drive the second bristle holder 10 via the drive shaft 14 back and forth about its own axis, but in the opposite sense so that as one brush head moves clockwise, the other always moves anti-clockwise, and so on.

In Figure 6 there is shown a second embodiment of the invention which again includes a "try me" feature shown generally at 7. This includes a twin sided metal foil strip 23, such as a double sided aluminium strip separated by a dielectric material (not shown) such as paper or plastics, respective sides of the strip 23 being electrically connected to respective parts of a printed circuit board 24 by connectors 25 and 26 forming part of a closeable circuit for operating a motor 27 to, in turn, rotate the crankshaft 14 and hence oscillate the brush heads 4, 5 in the manner as described with reference to Figures 2 and 3.

The free end of the strip 23 has a folded over region in the form of a ring 28 onto which can be fitted a metal disc 29 which includes a domed central region 30 which may be pressed to temporarily connect both sides of the strip 23 to complete the circuit between the connectors 25 and 26 and thereby temporarily activate the toothbrush 1. As will be appreciated, because the "try me" feature 7 includes a strip 23 by which it allows a prospective purchaser of the toothbrush to determine if and how it works prior to purchase following pressing of the metal disc 29, after purchase the "try me" feature 7 can be effectively deactivated by simply pulling the strip 23 away from the printed circuit board 24 and hence out of engagement with

the connectors 25, 26 thereon, whereafter an end cap 31 can be refitted onto the housing 2 of the toothbrush 1 in order to commence normal operation via pressing of the button 6.

CLAIMS

1. An electric toothbrush (1) having a housing (2) containing an electric motor (27), the motor being
5 drivingly connected to a first brush head (4) rotatably mounted on an end of the toothbrush remote from the motor adjacent to at least one other rotatable brush head (5), wherein the first brush head includes a drive pin (19) extending therefrom substantially at right angles from the
10 axis of rotation, the free end of the drive pin being received within a guide slot (20) in a brush head (5) to be driven thereby, the arrangement being such that the drive pin bears against respectively opposite sides of the guide slot to thereby drive a driven brush head clockwise and
15 anti-clockwise about its axis of rotation as the first brush head is also being oscillated.

2. An electric toothbrush according to Claim 1 having first and second brush heads (4,5), the second brush head
20 having a plane of rotation which is angled relative to the plane of rotation of the first brush head.

3. An electric toothbrush according to Claim 2 wherein the second brush head (5) is angled inwardly towards the
25 first brush head (4).

4. An electric toothbrush according to any preceding

claim wherein the means by which the motor (27) is
drivingly connected to the first brush head (4) and the
means by which the drive pin (19) is received within a
guide slot (20) in a brush head (5) to be driven thereby
5 includes a part-spherical ball joint (22).

5. An electric toothbrush according to claim 4 wherein
the ball joint is made of nylon.

10 6. A detachable brush head holder (3) for an electric
toothbrush body (2) housing a motor (27), a battery and
associated electrical circuitry, the detachable brush head
holder including at the free end thereof when connected at
the other end to the toothbrush body, a first partly
15 rotatable brush head (4) and a second partly rotatable
brush head (5), the first brush head in said position being
drivingly connected to the motor and including a drive pin
(19) extending therefrom substantially at right angles from
the axis of rotation of the first brush head, the free end
20 of the drive pin being received within a guide slot (20) in
the second brush head, the arrangement being such that the
drive pin bears against respectively opposite sides of the
guide slot to thereby drive the second brush head clockwise
and anti-clockwise about its axis of rotation as the first
25 brush head is also being oscillated.

7. A packaged electric toothbrush (1) including a body

portion (2) for containing a battery operated motor (27) drivingly connected or connectable to a brush head holder including at least one brush head (4), wherein the toothbrush includes a "try me" facility (7) for remotely
5 testing the operation of the toothbrush, such as by a prospective purchaser of the toothbrush whilst the toothbrush is still in its protective sales packaging, which "try me" feature comprises a two-sided metal strip (23), such as aluminium foil, separated by a dielectric
10 material, such as paper or plastics, respective sides of the strip being connected at one end to respective parts of an electric circuit (24) used to operate the electric toothbrush and, in particular, to energise the electric motor thereof, the other end (28) of the strip being folded
15 over and including a centrally disposed aperture onto or over which is disposed a bendable metal connector (29,30) such that upon bending or pressing of the connector the two sides of the strip or foil are electrically connected together to temporarily operate the toothbrush whilst still
20 in its packaging.

8. A toothbrush according to Claim 7 in which the "try me" feature may be permanently disconnected from the toothbrush by being pulled away from the electrical circuit
25 (24) to which it is attached.