

are very different than gas and diesel engines. Fourth, the high energy content of nitroparaffins requires modification of the engine, and additional care in transport, storage, and handling of both the nitroparaffin and the fuel containing the additive. Further, in some fuel applications, nitroparaffins have had a tendency to gel. The high cost, and extremely high energy content of nitroparaffins, has precluded their use as an automotive and/or truck fuel. Moreover, the extreme volatility and danger of explosion from nitromethane taught away from its use as a motor fuel for automobiles and/or trucks.

Summary

[0019a] In one example of the present disclosure, there is provided an additive formulation for a fuel comprising:

about 40 to about 65 weight percent nitropropane;

about 10 to about 30 weight percent nitromethane;

about 0.5 to about 5 weight percent C₅-C₁₀ fatty acid ester comprising at least one of pentaerythritol and dipentaerythritol;

about 10 to about 40 weight percent aromatic hydrocarbon;

wherein the additive is substantially free of nitroethane.

[0019b] In one aspect of the present disclosure, there is provided an additive formulation for a fuel comprising: 40 to 65 weight percent nitropropane;

10 to 30 weight percent nitromethane;

0.5 to 5 weight percent lubricant, wherein the lubricant comprises C₅-C₁₀ fatty acid ester comprising at least one of pentaerythritol and dipentaerythritol;

10 to 40 weight percent aromatic hydrocarbon;

wherein the additive is substantially free of nitroethane.

Advantages of the Disclosure

[0020] It is an advantage of the present disclosure to provide a motor fuel additive that provides improved performance at additive concentrations typical of known additives, and reduced emissions at lower concentrations, while avoiding many of the problems associated with prior known additives and motor fuels.

[0021] Another advantage of the present disclosure is to provide a motor fuel that exhibits improved performance relative to prior known motor fuels, while avoiding many of the problems associated with prior known motor fuels.

[0022] A further advantage of the present disclosure is to provide a motor fuel that reduces emissions relative to prior known motor fuels, while avoiding many of the problems associated with prior known motor fuels.

CLAIMS

We claim:

1. An additive formulation for a fuel comprising:
40 to 65 weight percent nitropropane;
10 to 30 weight percent nitromethane;
0.5 to 5 weight percent lubricant, wherein the lubricant comprises C₅-C₁₀ fatty acid ester comprising at least one of pentaerythritol and dipentaerythritol;
10 to 40 weight percent aromatic hydrocarbon;
wherein the additive is substantially free of nitroethane.
2. The formulation of claim 1, wherein the lubricant is a C₅-C₁₀ fatty acid ester with pentaerythritol.
3. The formulation of claim 1, wherein the lubricant is a C₅-C₁₀ fatty acid ester with dipentaerythritol.
4. The formulation of claim 1, wherein the lubricant is a C₅-C₁₀ fatty acid ester with pentaerythritol and dipentaerythritol.
5. The formulation of claim 2, wherein the lubricant comprises 75 wt.% to 80 wt.% C₅-C₁₀ fatty acid ester with pentaerythritol.
6. The formulation of claim 3, wherein the lubricant comprises 19 wt.% to 24 wt.% C₅-C₁₀ fatty acid ester with dipentaerythritol.
7. The formulation of claim 1, wherein the aromatic hydrocarbon is selected from the group consisting of: ethyl benzene, xylene, and toluene.
8. The formulation of claim 4, wherein the aromatic hydrocarbon is toluene.