

SPECIFICATION

INTEGRATED CIRCUIT CHIP, INTEGRATED CIRCUIT ELEMENT,
PRINTED CIRCUIT BOARD AND ELECTRONIC DEVICE

TECHNICAL FIELD

This invention relates to an integrated circuit chip in which a plurality of circuit modules are integrated, an integrated circuit element with the integrated circuit chip packaged therein, and an electronic device with the
5 integrated circuit element mounted therein.

BACKGROUND ARTS

Recently, in a field of an integrated circuit, a design rule for fabrication of a semiconductor has become finer and a circuit scale which can be integrated per unit
10 area is enlarged as the techniques of semiconductor fabrication process progresses. Therefore, the size of an integrated circuit chip can be reduced as compared with before, if the circuit scale is the same. On the other hand, a width of a data bus of a digital signal processing
15 circuit in the integrated circuit is enlarged as compared with before. Due to the synergy of the increase of the integration density and enlargement of the data bus width, the number of the input/output (I/O) terminals necessary for inputting/outputting a signal between the integrated

circuit in the chip and external equipment is increased more and more. Conventionally, the I/O terminals are arranged in a row along edges of the chip. For example, when the chip is square, the terminals are arranged on four
5 sides of the square without leaving a gap between each of the terminals. The I/O terminals each usually have a bonding pad and a buffer circuit. The buffer circuit functions to protect circuit modules in the chip from external noises and it ordinarily comprises a transistor
10 having a relatively large capacity.

The integrated circuit chip is mounted on the printed circuit board of an electronic device by either of the following two methods.

The first one is such that the integrated circuit
15 chip is encapsulated in a package of a resin to form an integrated circuit element and the thus formed integrated circuit element is mounted on a printed circuit board. In this case, bonding pads of the I/O terminals in the chip are connected to terminals in the package for external
20 connection by wire bonding and the connected portions are sealed in the package. When the terminals for external connection are connected to the printed circuit board, the integrated circuit chip and the printed circuit board are connected each other. According to this method, the
25 circuit modules on the chip are protected by the package, which contributes to enhancement of reliability.

Another one is so-called a direct bonding method according to which a chip is directly bonded on a printed circuit board. Since the chip is directly wire-bonded on the printed circuit board in the form of so-called a bare
5 chip, without being encapsulated in a package, a space needed for arranging the integrated circuit chip on the printed circuit board is reduced by a space corresponding to a package. In addition, advantageously, the cost of the package can also be saved.

10

DISCLOSURE OF THE INVENTION

As mentioned above, although the circuit modules in the chip is reduced in size as the semiconductor fabrication process becomes finer, a pitch of the I/O
15 terminals is not reduced so much. It is because there is a limit to reduce an interval between wires or between a wire and an adjacent lead during wire bonding to avoid an electrical short circuiting between wires adjacent to each other or an electrical short circuiting between a wire and
20 an adjacent lead.

It therefore occurs that even if the chip size is determined from a view point of the scale of the circuit modules in the chip, the peripheral length of the chip is not sufficient for arranging the I/O terminals along the
25 length. For this reason, the chip size should be determined based on the number of the I/O terminals and a

phenomenon of "pad neck" occurs in which it is not possible to reduce a chip size than the size determined from the number of the terminals. In the "pad necked" chip, the chip size is larger than necessary for the scale of the circuit modules in the chip and therefore a vacant area where no circuit modules are disposed is present in an inner area of the chip while the I/O terminals are disposed around the periphery of the chip without a gap between each of the terminals.

10 If the chip size is larger than necessary for the circuit modules, the chip costs high.

 The present invention is made in view of the facts as mentioned above, and it is an object of the present invention to provide an integrated circuit chip which is capable of avoiding the "pad neck" and having an optimum size for its circuit scale.

 According to the invention, there is provided an integrated circuit chip comprising a substrate, circuit modules formed on the substrate, and input/output terminals for inputting/outputting a signal to/from the circuit modules;

 the input/output terminals including input/output terminals for operation time which input/output a signal during operation of the circuit modules and input/output terminals for inspection which inspect the circuit modules; and

the input/output terminals for operation time being arranged on the substrate along edges of the substrate and the input/output terminals for inspection and the circuit modules being arranged on the substrate in an inner area
5 than said input/output terminals for operation time.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a top plan view showing a structure of an integrated circuit chip 10 according to a first embodiment of the present invention.

Fig. 2 is a sectional view showing a structure of an
10 integrated circuit element 20 with the integrated circuit chip 10 of Fig. 1 packaged therein.

Fig. 3(a) is a sectional view of the integrated circuit chip 10, taken along a line A-A of Fig. 1.

Fig. 3(b) is a sectional view of the integrated
15 circuit element 20, taken along a line B-B of Fig. 2.

Fig. 4 is a top plan view showing a structure of a probe card 40 to be used during the fabrication of the integrated circuit chip 10 according to the first embodiment of the present invention.

20 Fig. 5 is a top plan view showing a structure of a printed circuit board 50 with the integrated circuit element 20 mounted thereon.

Fig. 6 is a front elevational view of an electronic device 100 with the printed circuit board 50 mounted

thereon and a top plan view of an operating unit 200 according to a second embodiment of the present invention.

Fig. 7 is a perspective view of the electronic device 100 according to the second embodiment of the present invention.

Fig. 8 is a sectional view of the electronic device 100, taken along a line C-C of Fig. 7.

Fig. 9(a) is an explanatory view showing a structure of an integrated circuit chip 90 of a comparative example.

Fig. 9(b) is an explanatory view showing a structure of an integrated circuit chip 91.

Fig. 10(a) is an explanatory view showing arrangement of I/O terminals 2 of the integrated circuit chip 91 of the comparative example.

Fig. 10(b) is an explanatory view showing arrangement of I/O terminals of the integrated circuit chip 92 of the comparative example.

BEST MODE FOR CARRYING OUT THE INVENTION

Hereinafter, one of embodiments of the present invention will be described.

An integrated circuit chip 10 and an integrated circuit element 20 with the integrated circuit chip packaged therein in accordance with a first embodiment of the present invention will be described referring to Figs. 1, 2, 3(a) and 3(b).

As shown in Figs. 1 and 3(a), the integrated circuit chip 10 comprises a semiconductor substrate 1 of a square shape having a lateral length $\underline{a}$ $\times$ a longitudinal length $\underline{b}$ and thirty four (34) I/O terminals which are arranged at a pitch $\underline{c}$ on four sides of the substrate without leaving a gap between each of the I/O terminals. In an inner area of the substrate which is surrounded by the I/O terminals, are disposed circuit modules 6, 7 and 8 and six (6) I/O terminals 4.

The I/O terminals 2 are electrically connected to wirings on a printed circuit board through bonding wires and leads when the chip 10 is mounted on the printed circuit board, for functioning as users' I/O terminals (or I/O terminals for operation time) for carrying out inputting or outputting signals when the circuit modules 6, 7 and/or 8 are operated. On the other hand, the I/O terminals 4 are I/O terminals other than the I/O terminals 2 for users which are irrelevant to functions or specifications of the integrated circuit chip 10 from a view point of the users. These terminals 4 are not used when the circuit modules 6, 7 and/or 8 of the mounted circuit chip 10 are in a normal operation. The I/O terminals 4 are used, for example, as terminals for inspection, when signals are inputted or outputted for inspecting whether the circuit modules 6, 7 and 8 are in normal conditions for operation or not during the

fabrication of the chip 10 or prior to the shipping thereof, when producing conditions of film forming or etching during the fabrication of the integrated circuit chips 10 are checked or when they are used as terminals for repair or

5 BIST (Built-In Self Test)/BISR (Built-In Self repair). Hereinafter, the I/O terminals 4 may also be referred to as I/O terminals for testing.

The I/O terminals 2 each comprise a bonding pad 3 for wire bonding and a buffer circuit (not shown) for

10 connecting the bonding pad 3 to the circuit modules 6, 7 and 8. The I/O terminals 4 each comprise a probe pad 5 for contact with a probe for testing and a buffer circuit (not shown) for connecting the probe pad 5 to the circuit modules 6, 7 and 8. The buffer circuits of both the I/O

15 terminals 2 and 4 are formed of transistors and function to protect the circuit modules 6, 7 and 8 from external noise signals.

An upper face of the chip 10 is covered with a protective film 8 of a resin (Fig. 3(a)) which is not shown

20 in Fig. 1 for simplicity of illustration. The protective film 3 has through holes at positions corresponding to the bonding pads 3 and the probe pads 5, letting the upper surfaces of the bonding pads 3 and the probe pads 5 be exposed.

25 Next, the integrated circuit element 20 with the chip 10 packaged therein will be described in reference

with Figs. 2 and 3(b).

The integrated circuit element 20 comprises the chip 10, an island 11 for mounting the chip thereon, leads 12 and a package 13 of a resin for encapsulating these elements therein. The leads 12 are each connected to the bonding pads 3 of the I/O terminals 2 by wires 14, respectively.

The pads 5 of the I/O terminals 4 are not connected to the leads 12. It is because the I/O terminals 4 are only for testing the operations as mentioned above and there is no need to connect to the wirings of the printed circuit board.

Now, the fabrication method of the chip 10 and the integrated circuit element 20 is described.

First, the circuit formation of the circuit modules 6, 7 and 8 and the I/O terminals 2 and 4, and the layout on the substrate 1 are designed. At this time, the I/O terminals necessary for the chip 10 are divided into the I/O terminals 2 for users which are to be connected to the printed circuit board after mounting and the I/O terminals 4 for testing which are used for testing and not needed to be connected to the printed circuit board. Then, the I/O terminals 2 for users are laid out so that the terminals 2 are arranged in a row around the substrate 1 without gaps between each of the terminals 2 as illustrated in Fig. 1. The circuit modules 6, 7 and 8 and the I/O terminals 4 for

testing are designed so that they are disposed in an inner area surrounded with the I/O terminals 2 for users. The size of the substrate 1 is determined to be minimum, $a \times b$, which is needed for this arrangement.

5 A semiconductor wafer is used as the substrate 1 and a semiconductor fabricating techniques such as film formation, diffusion and/or photolithography are employed to form the circuit modules 6, 7 and 8 and the I/O terminals 2 and 4 on the substrate 1. Then, the
10 semiconductor wafer is diced to obtain the substrate 1 having a size of $a \times b$. Thus, the chip 10 is provided.

Before or after the dicing, a test is conducted using a probe card 40 as illustrated in Fig. 4 for checking the operations of the circuit modules 6, 7 and 8.

15 The probe card 40 has an opening 43 at a central portion thereof and probes 41 and 42 which are set around the opening 43. In this connection, it is to be noted that the probes 41 and 42 are not shown in full for simplicity for illustration, but the number of the probes 41 is as
20 many as the I/O terminals 2 for users and the number of the probes 42 is as many as the I/O terminals 4 for testing. The tip ends of the probes 41 and 42 are converged towards the area at the central position of the opening 43 where the chip 10 is to be placed. The tip ends of the probes 41
25 are so disposed at predetermined intervals that they may contact the bonding pads 3 of the I/O terminals 2,

respectively. Similarly the tip ends of the probes 42 are disposed so as to contact the probe pads 5 of the I/O terminals 4, respectively.

With this construction, the semiconductor wafer
5 before dicing or the chip 10 after the dicing may be placed at a central portion of the opening 43 of the probe card 40 to contact the probes 41 and 42 with the bonding pad 3 and the pad for probing, respectively, for allowing signals to be inputted or outputted from or to an external circuit
10 through the probes 41 and 42. By this, the operation test of the circuit modules 6, 7 and 8 and the checking of the fabrication conditions, i.e. whether the film forming or etching is being carried out as designed can be effected.

Thereafter, the chip 10 is subjected to packaging.
15 First, the chip 10 is die-bonded onto the island 11 of the lead frame. The bonding pads 3 of the user's I/O terminals 2 are bonded to the leads 12 of the lead frame through wires 14 (Fig. 2). The pads 5 of the I/O terminals 4 for testing are not bonded. Then, the chip 10 and the
20 connection portions of the leads 12 are encapsulated with the resin package 13. The leads 12 and the island 11 are cut off from the lead frame, and the leads 12 are bent to produce the integrated circuit element 20.

As mentioned above, the chip 10 is so constructed
25 that the I/O terminals are divided into the I/O terminals 2 for users and the I/O terminals 4 for testing, and only the

I/O terminals 2 are arranged around the periphery of the chip 10. This construction allows the chip size to be reduced as compared with conventional chips in which all the I/O terminals are arranged around the periphery of the chip. Besides, in the chip 10, the number of the I/O terminals which should be bonded is reduced, and therefore the time necessary for bonding can also be reduced. Thus, the fabrication efficiency can be improved. On the other hand, in the case where the size of the chip 10 is kept the same as the conventional one, the I/O terminals 2 for users can be arranged leaving margins as much as the number of the I/O terminals which are not arranged around the periphery of the chip 10. As a result of this, the spaces between the bonding wires 14 and the spaces between the bonding wires 14 and the respective adjacent leads 12 can be assured easily. Thus, it makes it possible to reduce the incidence of defects.

As the integrated circuit element 20 which packages the chip 10 of the present invention can be small-sized as much as the chip 10 can be reduced in size, the area which it occupies on the printed circuit board is reduced. Thus, the mounting efficiency can be improved. On the other hand, if the size of the chip 10 is kept the same as compared with the conventional one, the space between the leads 12 can be broader because the number of the I/O terminals 2 to be arranged around the periphery of the chip 10 is smaller

than the conventional one. In this case, such an advantage that the incidence of rejects due to possible short-circuiting caused between the adjacent leads 12 in soldering can be reduced.

5 In this connection, comparative examples will now be described referring to Figs. 9(a) and 9(b) and Fig. 10(a) and 10(b) in which chips 90 and 91 have I/O terminals 2 and 4 all arranged around the periphery of the substrate 1.

 In the chip 90 of the comparative example, both
10 thirty four (34) I/O terminals 2 for users and six (6) I/O terminals 4 for testing, forty (40) in total are all arranged in row around the periphery of the substrate 1. The I/O terminals 2 each have a bonding pad 3 as illustrated in Figs. 10(a) and 10(b) and the I/O terminals
15 4 each have a pad (5)(not shown). The pitch c of the I/O terminals 2 and 4 as shown in Figs. 9(a) and 9(b) is the same as the pitch c of the I/O terminals 2 of the above-mentioned embodiment as illustrated in Fig. 1. However, the number of the I/O terminals arranged around the
20 periphery of the substrate is larger by the number of the I/O terminals 4 for testing, and accordingly the lengths d and e of the sides of the substrate 1 are longer than a and b of the substrate 1 in Fig. 1, respectively.

 Circuit modules 96, 97 and 98 each have circuit
25 constitution substantially the same as those of the circuit modules 6, 7 and 8, but they are designed according to the

design rule rougher than that for the circuit modules 6, 7 and 8. As a result of this, the circuit modules 96, 97 and 98 occupy larger spaces on the substrate. Therefore, the area surrounded by the I/O terminals 2 and 4 is

5 substantially occupied by the circuit modules 96, 97 and 98.

In this connection, it is to be noted that in the case where the I/O terminals 2 for users and the I/O terminals 4 for testing are mixedly arranged as in the chip 90 of the comparative example, not only the bonding pads 3

10 of the I/O terminals 2 for users but also the pads 5 of the I/O terminals 4 for inspection are bonded because a bonding machine cannot discriminatively select the I/O terminals 4 for testing. By this reason, leads 12 as many as 40 in total of the numbers of the I/O terminals 2 and 4 are

15 necessary for packaging.

Next, the design rule for the circuit modules 96, 97 and 98 of the chip 90 of the comparative example is changed to a fine design rule used for the embodiment of the present invention to obtain a chip 91 of another

20 comparative example (Fig. 9(b)). The circuit modules 6, 7 and 8 of the chip 91 are reduced by 0.7 in the longitudinal direction than the chip 90, and the area occupied on the substrate 1 by the circuit modules 6, 7 and 8 is reduced to 1/2 of that of the circuit modules 96, 97 and 98. As a

25 result of this, there remains an unoccupied space in the interior region of the substrate 1 as can be seen from Fig.

9(b).

However, in the chip 91, the pitches of the I/O terminals 2 and 4 cannot be smaller than c in order to keep the predetermined intervals between the bonding wires. For this reason, the lengths of the sides of the substrate 1 of the chip 91 cannot be smaller than d and e for all the unoccupied space in the inner region. Thus, the chip 91 cannot be smaller than the chip 90 of the comparative example irrespective of the application of the fine design rule. A so-called "pad neck" problem is thus caused in which the number of the I/O terminals 2 and 4 determines the size of the substrate 1.

To avoid the "pad neck" problem, a chip 92 may be contemplated as a comparative example in which I/O terminals 2 are arranged zigzagged in two rows around the periphery of the substrate 1 as illustrated in Fig. 10(b). By arranging the I/O terminals in two rows, the inner area of the substrate 1 can be made good use of and therefore if the size of the substrate is not changed, the number of the I/O terminals can be increased up to 1.5 times.

However, in such a structure that the I/O terminals 2 are arranged zigzaggedy, bonding wires connected to the outer row of the I/O terminals 2 should be spaced by at least a predetermined distance from bonding wires connected to the inner row of the I/O terminals 2. For this reason, it is required that the space between the outer row of the

I/O terminals 2 be broadened and the inner row of the I/O terminals 2 be positioned between each of the outer row I/O terminals as shown in Fig. 10(b). In addition, there is further a strict restriction that the positions of the pads 3 of the inner row I/O terminals 2 be close to the outer row I/O terminals 2 because the existing bonding machine cannot carry out bonding if the positions of the pads 3 of the inner I/O terminals 2 are distant from the edges of the substrate 1. This makes the design for optimum arrangement of the I/O terminals 2 very complicated.

In comparison with the chips 90,91 and 92 of the comparative examples, the chip 10 of the present invention as described above can be provided by dividing the I/O terminals into the I/O terminals 2 for users and the I/O terminals 4 for testing and arranging the I/O terminals 4 for testing in the inner unoccupied space of the substrate 1. Further, the I/O terminals 4 for testing may be placed at any unoccupied area distant from the edge of the substrate 1 as long as the measurement by using the probe card 40 can be made, because the I/O terminals 4 for testing are not necessary to be bonded. Thus, freedom in design becomes very large. Actually, the design of the chip 10 is very easy and the size of the chip 10 can be reduced overcoming the "pad neck" problem. Further, as the number of the bonding places can be reduced, the bonding itself can be effected easily, which realizes a direct cost

down.

The chip 10 according to the present embodiment not only requires no reduction in the number of the I/O terminals 4 for testing, but also it is possible to increase the number of the I/O terminals 4 for testing if there remains vacant space in the inner area of the substrate 1. By this, there can be provided a chip 10 which has a sufficient number of I/O terminals 4 for testing for inspecting the operation condition and fabrication condition with respect to the circuit modules 6, 7 and 8. Thus, the finding of rejects can be effected at a high efficiency and the fabrication conditions can be seen easily. Chips 10 of the quality can therefore be manufactured at a high yield.

It should be appreciated that some of the I/O terminals 4 for testing may be arranged around the periphery of the substrate 1 if the size of the substrate is allows it, although all the I/O terminals 4 for testing are arranged in the inner area of the substrate 1 in the illustrated embodiment. It is further to be noted that the I/O terminals 4 for testing which also function as the I/O terminal 2 for users, or the I/O terminals 4 which input or output a test signal through a printed circuit board after the chip have been mounted on the printed circuit board should be mounted around the periphery of the substrate and bonded.

The number and/or the shape of the I/O terminal 2 for users and the I/O terminal 4 for testing are not limited to those as illustrated in Fig. 1 and may be changed according to necessity. The shape of the substrate is not limited to a square as illustrated in Fig. 1, either.

Next, a printed circuit board 50 on which the integrated circuit element 20 of the first embodiment is mounted and an electronic device 100 on which the printed circuit board is mounted will be described as a second embodiment referring to Figs. 5 to 8.

On the printed circuit board 50 are mounted the integrated circuit element 20 of the first embodiment and integrated circuit elements 51, 52 and 53 by soldering. In the chip 10 of the integrated circuit element 20 is provided with a circuit which functions as a main processor of the electronic device 100 in the forms of the circuit modules 6, 7 and 8. In the integrated circuit element 51, the integrated circuit element 52 and the integrated circuit element 53, are provided, in the forms of circuit modules, a circuit dedicated for image processing, an input/output controlling circuit and a memory circuit, respectively. On the printed circuit board 50, there are further mounted a circuit element 54, connectors 55, 56, 57 and 58 and wirings (not shown).

The printed circuit board 50 is mounted in a housing 110 of the electronic device 100 as illustrated in

Fig. 8. The electronic device 100 is, for example, an entertainment equipment and it comprises a disk device 103 for reproducing a CD (Compact Disk) or DVD (Digital Video Disk) and slot units 105 and 106 as illustrated in Fig. 6.

5 The electronic device 100 is connected to an image display unit (not shown). The slot unit 106 is connected to a connector 232 of an operating unit 200. The slot unit 105 is connectable to a small-sized memory device. The housing 110 has a resetting switch 104, an ejecting switch 102 for

10 the disk device 103 and legs 107 and 108 for supporting the housing in a standing position and in the laying down position, respectively.

A main processor of the integrated circuit element 20 functions to make an image stored in the DVD set on a

15 tray 101 of the disk device 103 be displayed on the image display unit or read programs recorded preliminarily on the DVD or CD and instruct the circuit dedicated only for image processing of the integrated circuit element 51 for production of an image according to the programs and

20 display of the produced image on the display unit.

The main processor of the integrated circuit element 20 functions to respond to a user's operation through a switch 210 of the operating unit 200 to instruct the circuit dedicated for image processing of the integrated

25 circuit element 51 to change the image according to the program as mentioned above. By this, the image of the

image display unit changes and the user can enjoy an
entertainment such as a game. The main processor of the
integrated circuit element 20 stores, in a memory device,
the progress of the game which is loaded in the slot unit
5 106.

Inside the housing are arranged parts other than the
integrated circuit board 50 such as a power unit, a switch-
inlet unit 115, etc. A pipe type heat sink 114 is provided
above the printed circuit board 50 for releasing heat
10 generated by the integrated circuit element 20 etc. The
pipe type heat sink 114 is connected to a heat radiation
fin 112. An exhaust fan 115 is provided on the housing 110
for dissipating heat of the radiation fin 112 etc. A
shield 113 for protecting the integrated circuit element
15 etc. from external electromagnetic wave is provided for the
printed circuit board 50.

The integrated circuit element 20 mounted on the
printed circuit board 50 is small device as described
referring to the first embodiment of the present invention
20 as mentioned above and contributes high mounting efficiency.
Therefore, it realizes printed circuit board 50 of a small
size. This in turn enables the entire size of the
electronic device 100 to be small. In addition, as the
integrated circuit element 20 can be produced at a low cost,
25 the costs of the printed circuit board 50 and the
electronic device 100 can be lowered accordingly.

Although the chip 10 is mounted on the printed circuit board 50 in the form of the packaged integrated circuit element 20 in the foregoing embodiments, the chip 10 may be directly bonded on the printed circuit board 50.

5 In this case, the mounting efficiency is further enhanced because the package is not needed. This realizes a more small-sized printed circuit board 50 or electronic device 100. Further, the cost can be more lowered due to the fact that the package is not needed and there can be provided

10 the printed circuit board 50 and the electronic device 100 of a lower price.

The pads 3 of the I/O terminals 2 for users are connected to the printed circuit board 50 through the bonding wires and the leads 12 in the foregoing embodiments,

15 but they may be connected to the printed circuit board 50 through other means such as TAB (Tape-Automated Bonding).

The integrated circuit element 20 of the electronic device 100 is used for controlling complicated operations of a plurality of devices such as the disk device 103,

20 operating unit 200, memory unit, image display unit, etc. Therefore, use of the chip according to the first embodiment, as the chip 10 of the integrated circuit element 20 for the electronic device 100 will contribute very much for small-sization and cost down.

25 As described above, according to the present invention, a pad neck problem is solved and an integrated

circuit chip having a size suited for its circuit scale can be provided.

INDUSTRIAL APPLICABILITY

- 5 The present invention is applicable to an integrated circuit chip having a plurality of circuit modules integrated therein, an integrated circuit element with the integrated circuit chip packaged therein, and an electronic device with the integrated circuit element mounted thereon.



CLAIMS

1 1. An integrated circuit chip comprising a substrate,
2 circuit modules formed on the substrate, and input/output
3 terminals for inputting/outputting a signal to/from said
4 circuit modules;

5 said input/output terminals including input/output
6 terminals for operation time which input/output a signal
7 during operation of the circuit modules and input/output
8 terminals for inspection which inspect the circuit modules;
9 and

10 said input/output terminals for operation time being
11 arranged on said substrate along edges of the substrate and
12 said input/output terminals for inspection and said circuit
13 modules being arranged on the substrate in an inner area
14 than said input/output terminals for operation time.

1 2. An integrated circuit chip as set forth in claim
2 1, wherein said input/output terminals for operation time
3 are arranged in a row along the edges of the substrate
4 without leaving a gap between each of the input/output
5 terminals.

1 3. An integrated circuit chip as set forth in claim
2 1, wherein said input/output terminals for operation time
3 each have a bonding pad and said input/output terminals for



4 inspection each have a pad for contacting a probe.

1 4. An integrated circuit chip comprising a substrate,
2 circuit modules formed on the substrate, and input/output
3 terminals for inputting/outputting a signal to/from said
4 circuit modules;

5 said input/output terminals including input/output
6 terminals for bonding which are connected to an external
7 conductive member through bonding wires and input/output
8 terminals for non-bonding which are not connected to the
9 external conductive member through the bonding wires;

10 said input/output terminals for bonding being
11 arranged on said substrate along edges of the substrate and
12 said input/output terminals for non-bonding being arranged
13 on the substrate in an inner area than said input/output
14 terminals for bonding.

1 5. An integrated circuit element comprising an
2 integrated circuit chip, leads and a package encapsulating
3 said integrated circuit chip and part of said leads;

4 said integrated circuit chip including a substrate,
5 circuit modules formed on the substrate, and input/output
6 terminals for inputting/outputting a signal to/from said
7 circuit modules;

8 said input/output terminals including input/output
9 terminals for operation time which input/output a signal



10 during operation of the circuit modules and input/output
11 terminals for inspection which inspect the circuit modules;
12 and

13 said input/output terminals for operation time being
14 arranged on said substrate along edges of the substrate and
15 said input/output terminals for inspection and said circuit
16 modules being arranged on the substrate in an inner area
17 than said input/output terminals for operation time.

1 6. An integrated circuit element as set forth in
2 claim 5, wherein said input/output terminals for operation
3 time are connected to the leads, respectively and said
4 input/output terminals for inspection are not connected to
5 the leads.

1 7. An integrated circuit element as set forth in
2 claim 6, wherein said input/output terminals for inspection
3 each have a pad for contact with a probe.

1 8. An integrated circuit element as set forth in
2 claim 6, wherein said input/output terminals each have a
3 bonding pad which is connected to respective lead with a
4 bonding wire.

1 9. An integrated circuit element as set forth in
2 claim 5, wherein said input/output terminals for operation



3 time are arranged in a row along edges of the substrate
4 without a gap between each of said terminals.

1 10. A printed circuit board comprising the
2 integrated circuit element as set forth in claim 5 and a
3 circuit board with said integrated circuit element mounted
4 thereon; and

5 said circuit board including printed wirings, which
6 are electrically connected to said leads.

1 11. An electronic device comprising a printed
2 circuit board; said printed circuit board including an
3 integrated circuit element as set forth in claim 5 and a
4 circuit board with said integrated circuit element mounted
5 thereon; and said circuit board including printed wirings,
6 which are electrically connected to said leads.