



- (51) International Patent Classification:
H03M 7/40 (2006.01) *H04N 7/30* (2006.01)
- (21) International Application Number:
PCT/US2012/063070
- (22) International Filing Date:
1 November 2012 (01.11.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/555,469 3 November 2011 (03.11.2011) US
61/556,808 7 November 2011 (07.11.2011) US
61/557,785 9 November 2011 (09.11.2011) US
61/560,107 15 November 2011 (15.11.2011) US
13/665,467 31 October 2012 (31.10.2012) US
- (71) Applicant: **QUALCOMM INCORPORATED** [US/US];
ATTN: International IP Administration, 5775 Morehouse
Drive, San Diego, California 92121-1714 (US).
- (72) Inventors: **GUO, Liwei**; 5775 Morehouse Drive, San
Diego, California 92121-1714 (US). **WANG, Xianglin**;
5775 Morehouse Drive, San Diego, California 92121-1714
(US). **KARCZEWICZ, Marta**; 5775 Morehouse Drive,
San Diego, California 92121-1714 (US). **SOLE ROJALS,**
Joel; 5775 Morehouse Drive, San Diego, California
92121-1714 (US).
- (74) Agent: **FITZGERALD, Kelly Patrick**; Shumaker & Sief-
fert, P.A., 1625 Radio Drive, Suite 300, Woodbury, Min-
nesota 55125 (US).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,

[Continued on next page]

(54) Title: CONTEXT STATE AND PROBABILITY INITIALIZATION FOR CONTEXT ADAPTIVE ENTROPY CODING




FIG. 5

(57) Abstract: In one example, an apparatus for context adaptive entropy coding may include a coder configured to determine one or more initialization parameters for a context adaptive entropy coding process based on one or more initialization parameter index values. The coder may be further configured to determine one or more initial context states for initializing one or more contexts of the context adaptive entropy coding process based on the initialization parameters. The coder may be still further configured to initialize the contexts based on the initial context states. In some examples, the initialization parameters may be included in one or more tables, wherein, to determine the initialization parameters, the coder may be configured to map the initialization parameter index values to the initialization parameters in the tables. Alternatively, the coder may be configured to calculate the initialization parameters using the initialization parameter index values and one or more formulas.



TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,

EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))