

METHOD, NETWORK APPARATUS, AND TERMINAL APPARATUS FOR INDICATING POSITION OF SYNCHRONIZATION SIGNAL BLOCK

TECHNICAL FIELD

[0001] The present disclosure relates to the field of information processing technology, and more particularly, to a method for indicating a position of a synchronous signal block, a network apparatus, a terminal apparatus, and a computer storage medium.

BACKGROUND

[0002] The synchronous channels in the LTE system are PSS and SSS signals, and the reference signal for a terminal to measure RRM is a CRS or CSI-RS signal. In a 5G NR system design, 3GPP has reached a conclusion that a network apparatus sends an SS burst set containing a plurality of SS blocks to the terminal, and each SS block includes PSS, SSS, and PBCH. Based on the implementation of the base station, each SS block may correspond to one downlink beam. The terminal searches for the SS block in the system bandwidth to acquire time-frequency synchronization and PBCH information, and performs RRM measurement based on the SSS and the DMRS of the PBCH.

[0003] At present, 3GPP has also reached a conclusion that a SS block position for actual transmission in one SS burst set may be notified to the terminal via a broadcast signaling RMSI by a serving cell of the terminal in a manner of bitmap.

[0004] However, the processing method of the existing technology mentioned above is only for the current cell to obtain the synchronous signal, and it cannot further guarantee to reduce the terminal measurement time and power consumption of the terminal apparatus.

SUMMARY

[0005] In order to solve the above technical problem, the embodiments of the present disclosure provides a method for indicating a position of a synchronous signal block, a network apparatus, a terminal apparatus, and a computer storage medium.

[0006] The embodiments of the present disclosure provide a method for indicating a position of a synchronous signal block, applied to a network apparatus, including:

[0007] determining a transmission position of a synchronous signal block of at least one first type of cell; and

[0008] sending, by a signaling, the transmission position of the synchronous signal block of the at least one first type of cell to a terminal apparatus; wherein the terminal apparatus is located within a range of a second type of cell managed by the network apparatus.

[0009] The embodiments of the present disclosure provide a method for indicating a position of a synchronous signal block, applied to a terminal apparatus, including:

[0010] receiving a transmission position of a synchronous signal block of at least one first type of cell sent by a network apparatus via a signaling; and

[0011] measuring, the synchronous signal block of at least one first type of cell based on the transmission position of the synchronous signal block of at least one first type of cell.

[0012] The embodiments of the present disclosure provide a network apparatus, including:

[0013] a processing unit, configured to determine a transmission position of a synchronous signal block of at least one first type of cell; and control to send the transmission position of the synchronous signal block of at least one first type of cell to a terminal apparatus by a signaling; wherein, the terminal apparatus is located within a range of a second type of cell managed by the network apparatus; and

[0014] a communication unit, configured to send the signaling to the terminal apparatus.

[0015] The embodiments of the present disclosure provide a terminal apparatus, including:

[0016] an information receiving unit, configured to receive a transmission position of the synchronous signal block of at least one first type of cell sent by a network apparatus via a signaling; and

[0017] a measuring unit, configured to measure, the synchronous signal block of at least one first type of cell based on the transmission position of the synchronous signal block of at least one first type of cell.

[0018] The embodiments of the present disclosure provide a network apparatus,

including: a processor and a memory for storing a computer program executable on the processor,

[0019] wherein, when executing the computer programs, the processor performs the steps of the foregoing method.

[0020] The embodiments of the present disclosure provide a terminal apparatus, including: a processor and a memory for storing a computer program executable on the processor,

[0021] wherein, when executing the computer program, the processor performs the steps of the foregoing method.

[0022] The embodiments of the present disclosure provide a computer storage medium for storing computer executable instructions, wherein when the computer executable instructions are executed, the steps of the foregoing method is performed.

[0023] In the technical solutions of the embodiments of the present disclosure, the transmission position of the synchronous signal block of the first type of cell is sent to the terminal apparatus, so as to guarantee that the terminal apparatus can directly measure the neighboring cell at a time corresponding to the notified transmission position of the synchronous signal block of the first type of cell, without performing measurement at other positions, thereby saving terminal measurement time and power consumption overhead.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] Fig. 1 is a first schematic flowchart showing a method for indicating a position of a synchronous signal block according to an embodiment of the present disclosure;

[0025] Fig. 2 is a first schematic diagram showing a scenario of an embodiment of the present disclosure;

[0026] Fig. 3 is a second schematic diagram showing a scenario of an embodiment of the present disclosure;

[0027] Fig. 4 is a second schematic flowchart showing a method for indicating a position of a synchronous signal block according to an embodiment of the present disclosure;

[0028] Fig. 5 is a schematic block diagram showing a structure of a network apparatus according to an embodiment of the present disclosure;

[0029] Fig. 6 is a schematic block diagram showing a structure of a terminal apparatus according to an embodiment of the present disclosure; and

[0030] Fig. 7 is a schematic diagram showing a hardware architecture according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0031] In order to have a more detailed understanding of the characteristic and technical contents of the embodiments of the present disclosure, the implementation of the embodiments of the present disclosure will be described below with reference to the drawings. The accompanying drawings are for reference only, rather than limiting the embodiments of the present disclosure.

[0032] First Embodiment

[0033] This embodiment provides a method for indicating a position of a synchronous signal block. As shown in Fig. 1, the method includes the following steps.

[0034] In step 101, a transmission position of a synchronous signal block of at least one first type of cell is determined.

[0035] In step 102, the transmission position of the synchronous signal block of the at least one first type of cell is sent to a terminal apparatus by a signaling, the terminal apparatus being located within a range of a second type of cell managed by the network apparatus.

[0036] Here, the network apparatus may be a base station, for example, may be an eNB, a gNB, or other apparatus. Alternatively, the network apparatus may be other network apparatus, as long as the apparatus can provide a function of accessing the mobile communication network for the terminal apparatus.

[0037] It should be further noted that the first type of cell refers to a cell adjacent to the cell where the terminal apparatus is located, which may be a neighboring cell.

[0038] In addition, it should be understood that, the terminal apparatus being within the cell managed by the network apparatus may be that the terminal apparatus is located in one of a plurality of cells managed by the network apparatus.

[0039] For a non-carrier aggregation (CA) scenario, the cell in which the terminal apparatus is located may be referred to as a second type of cell, and the second type of cell

may also be referred to as a serving cell of the terminal apparatus. In this embodiment, the second type of cell in which the terminal is located and the first type of cell (that is, the neighboring cell) may be cells managed by the same network apparatus, and may also be cells managed by different network apparatuses.

[0040] For a CA scenario, a Primary cell (i.e., P cell) in the cell in which the terminal apparatus is located may be referred to as a second type of cell; other cells except the P cell (including an S cell having the terminal apparatus, that is, the secondary cell) are all classified into the first type of cell. In the scenario, the second type of cell in which the terminal is located and the first type of cell (that is, the neighboring cell) may be cells managed by the same network apparatus, and may also be cells managed by different network apparatuses.

[0041] In the above step 101, the manners for the network apparatus to determine the transmission position of the actual synchronous signal block (SS block) of other cells adjacent to the network apparatus may include the followings.

[0042] In a first manner, the transmission position of the synchronous signal block of at least one first type of cell is acquired by an X2 interface or an S1 interface. (In the present embodiment, the first type of cell being a neighboring cell is taken as an example for subsequent description)

[0043] Specifically, the network apparatus may query the base station apparatus of other cells adjacent to itself by the S1 interface and the X2 interface, and the base station apparatus of other cells notifies the actual transmission position of the SS block of other cells to the network apparatus by the X2 interface and the S1 interface.

[0044] The querying and notifying process may be performed periodically. The period needs to be smaller than a period in which the base station apparatus updates the actual transmission position of the SS block.

[0045] It should be noted that, this manner is more suitable for the scenario where the first type of cell and the cell in which the terminal apparatus is located are managed by different network apparatuses.

[0046] In a second manner, a broadcast message sent by a network apparatus corresponding to at least one first type of cell is acquired; and

[0047] a transmission position of a synchronous signal block of at least one first type of cell is acquired from the broadcast message.

[0048] The network apparatus acquires the transmission position of an actual SS block of other cells adjacent to the network apparatus by receiving and reading the broadcast message of other cells adjacent to the network apparatus.

[0049] Specifically, since the network apparatus may notify the actual SS block transmission position of the local cell by the broadcast message RMSI, the network apparatus may periodically read the broadcast message of other cells adjacent to the network apparatus and obtain the actual transmission position of the SS block of the neighboring cell.

[0050] It should be noted that, this manner is more suitable for the scenario where the first type of cell and the cell where the terminal apparatus is located are managed by different network apparatuses.

[0051] In addition to the above two manners, for the scenario in which the cell in which the terminal device is located and the first type of cell (that is, the neighboring cell) are both managed by the same network apparatus, the method for acquiring the transmission position of the synchronous signal block of the neighboring cell may be directly acquired from the cell management information of the network apparatus, which will not be elaborated here.

[0052] In step 102, the transmitting, by the signaling, the transmission position of the synchronous signal block of the at least one first type of cell to the terminal apparatus, includes:

[0053] generating a bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and transmitting the bitmap to the terminal apparatus by the signaling.

[0054] The method for sending the bitmap to the terminal apparatus may be: the network apparatus notifies the terminal, by a broadcast signaling, the actual transmission position of the SS block of other cells;

[0055] or, the network apparatus notifies the terminal, by a RRC dedicated signaling, the actual transmission position of the SS block of other cells.

[0056] The generating the bitmap based on the transmission position of the

synchronous signal block of the at least one first type of cell, and transmitting the bitmap to the terminal apparatus by signaling, includes:

[0057] when the first type of cell is in a synchronous state with the cell managed by the network apparatus, generating the bitmap of the transmission position(s) of the synchronous signal block(s) including all the first type of cell(s) based on transmission position(s) of the synchronous signal block(s) of all the first type of cell(s); and

[0058] transmitting, by the signaling, the bitmap including the transmission position(s) of the synchronous signal block(s) of all the first type of cell(s) to the terminal apparatus.

[0059] That is, the network apparatus aggregates the transmission positions of the synchronous signal blocks of all neighboring cells into one bitmap, and notifies the actual transmission position of the SS block of other cells in the form of a bitmap. That is, the bitmap contains the complete set of actual SS block positions of all other cells needing to notify.

[0060] For example, referring to Fig. 2, a network apparatus and a terminal operate in a frequency band of 3-6 GHz, and one SS burst set may transmit up to eight SS blocks. Based on the actual deployment requirement and specific implementation of the network, the numbers of the SS blocks transmitted by different base station apparatuses are shown in Fig. 2.

[0061] For example, cell 1, cell 2, cell 3, and 4 are mutually neighboring cells, the SS block position actually transmitted by cell 1 is the first position of 8 candidate SS block positions, and cell 2 corresponds to the first and second positions; cell 2 corresponds to the second and third positions; and cell 2 corresponds to the first and third positions.

[0062] For cell 1, cell 2, cell 3 and cell 4 are neighboring cells, and cell 2, cell 3 and cell 4 use the first, second, third, and fourth SS block positions, when cell 1 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 1 to the UE served by cell 1, the bitmap is: "11110000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[0063] For cell 3, cell 1, cell 2 and cell 4 are neighboring cells, and cells 1, 2 and 4 use the first, second, and third SS block positions, when cell 3 uses a bitmap to notify the

actual transmission position of the SS block of the neighboring cell of cell 3 to the UE served by cell 3, the bitmap is: "11100000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[0064] For cell 4, cell 1, cell 2 and cell 3 are neighboring cells, and cell 1, cell 2 and cell 3 use the first, second, and fourth SS block positions, when cell 4 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 4 to the UE served by cell 4, the bitmap is: "11010000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[0065] The network apparatus notifies the actual transmission position of the SS block of each of other cells to be measured in the form of one bitmap.

[0066] Based on the foregoing scheme, the method may further include: transmitting, to the terminal apparatus, a synchronous relationship between the at least one first type of cell and the cell managed by the network apparatus;

[0067] wherein, the synchronous relationship includes: the first type of cell is in a synchronous state with the cell managed by the network apparatus; or, there is a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

[0068] That is, while the network apparatus notifies the terminal of the actual transmission position of the SS block of other cells by a signaling, the network apparatus notifies the terminal of the synchronous relationship between other cells and the local cell corresponding to the network apparatus, that is, the synchronous state or the synchronous deviation.

[0069] The synchronous state includes: notifying, by the network apparatus, that the local cell corresponding to the network apparatus is in a synchronous state with other neighboring cells, to the terminal.

[0070] Correspondingly, when the terminal performs measurement, if the local cell and the neighboring cell are synchronous, the terminal may determine the actual position of the SS block transmitted by the neighboring cell. The terminal directly acquires the actual position of the SS block of the neighboring cell based on the timing of the local cell.

[0071] Different from the foregoing synchronous situation, when there is a synchronous deviation between the local cell and the neighboring cell, the following manner may be adopted:

[0072] when there is a synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus, sending, to the terminal apparatus, the synchronous deviation between at least one first type of cell and the cell managed by the network apparatus;

[0073] generating a bitmap corresponding to each of the neighboring cell(s) based on the transmission position of the synchronous signal block of the at least one first type of cell; and

[0074] transmitting, by the signaling, the bitmap corresponding to each of the first type of cell to the terminal apparatus.

[0075] The network apparatus notifies the terminal of the synchronous deviation between other cells and the local cell corresponding to the network apparatus. Correspondingly, when the terminal performs measurement, if the local cell and the neighboring cell are not synchronous, the terminal may determine the actual position of the SS block transmitted by the neighboring cell based on the notification information and the deviation of the timings between the cells. The terminal directly acquires the actual position of the SS block of the neighboring cell to be measured based on the timing of the local cell and the timing deviation of the neighboring cell to be measured.

[0076] For example, as shown in Fig. 3, cell 1 and cell 3 are synchronous, cell 2 is 0.5ms backward offset from cell 1 and cell 3, then the first candidate SS block position of cell 2 corresponds to the second candidate SS block position of cell 2; and cell 4 is 1 ms backward offset from cell 1 and cell 3, then the first candidate SS block position of cell 4 corresponds to the third candidate SS block position of cell 1.

[0077] For example, cell 1 notifies the terminal of the time deviations between cell 2, cell 3, cell 4 and cell 1 respectively, and the terminal combines the actual SS block transmission position of each of the cell 2, cell 3 and cell 4 in 2.4, and then may determine the reception time of actual transmission SS block of each cell.

[0078] In addition, the present embodiment may also provide a processing manner for

a scenario in which a part of the neighboring cells is synchronous with the local cell and the other part of the neighboring cells is not synchronous with the local cell:

[0079] if there is a synchronous deviation between a first part of the first type of cell in the at least one first type of cell and the cell managed by the network apparatus, and a second part of the first type of cell in the first type of cell is in the synchronous state with the cell managed by the network apparatus; wherein, the first part of the first type of cell is different from the second part of the first type of cell, and the first part of the first type of cell and the second part of the first type of cell form all the neighboring cells;

[0080] then transmitting, to the terminal apparatus, the synchronous deviation between the first part of the first type of cell and the cell managed by the network apparatus; generating a bitmap corresponding to each of the first type of cell in the first part of first type of cell based on the transmission position of the synchronous signal block of the first part of the first type of cell; transmitting, by the signaling, the bitmap corresponding to each of the first type of cell in the first type of cell to the terminal apparatus;

[0081] and, generating, the bitmap including the transmission position of the synchronous signal block of the second part of the first type of cell according to the transmission position of the synchronous signal block of the second part of the first type of cell; and transmitting, to the terminal apparatus, the bitmap including the transmission position of the synchronous signal block of the second part of the first type of cell.

[0082] For example, in four neighboring cells, the synchronous relationship between the neighboring cells 1, 2 and the local cell is synchronous, and there is a deviation between the neighboring cells 3, 4 and the local cell; then, the transmission positions of the synchronous signal blocks of the neighboring cells 1 and 2 are all set in the bitmap and transmitted to the terminal apparatus; and the synchronous deviation of the neighboring cells 3 and 4, the bitmap of the transmission position of the synchronous signal block of the neighboring cell 3, and the bitmap of the transmission position of the synchronous signal block of the neighboring cell 4 are all transmitted to the terminal apparatus.

[0083] There is also a processing manner in this embodiment, that is, no matter whether there is a synchronous deviation between the neighboring cell and the local cell, the synchronous deviation of the neighboring cell and the bitmap of the transmission position of

the synchronous signal block of the neighboring cell are transmitted to the terminal apparatus.

[0084] That is, the synchronous deviation between each of the at least one first type of cell and the cell managed by the network apparatus is transmitted to the terminal apparatus;

[0085] a bitmap corresponding to each of the first type of cell is generated based on the transmission position of the synchronous signal block of the at least one first type of cell; and

[0086] the bitmap corresponding to each of the first type of cell is transmitted to the terminal apparatus by the signaling.

[0087] In this scenario, the synchronous deviation of the neighboring cell synchronized with the local cell is equal to 0.

[0088] Finally, it should be noted that, in this embodiment, the synchronous deviation of a certain neighboring cell and the bitmap corresponding to a certain neighboring cell may be sent simultaneously or sequentially, which is not limited herein.

[0089] It can be seen that by adopting the above scheme, the transmission position of the synchronous signal block of the neighboring cell can be transmitted to the terminal apparatus, thereby ensuring that the terminal apparatus can directly measure the neighboring cell at a moment corresponding to the notified transmission position of the synchronous signal block of the first type of cell, without performing measurement at other positions, thereby saving terminal measurement time and power consumption.

[0090] Second Embodiment

[0091] This embodiment provides a method for indicating a position of a synchronous signal block, applied to a terminal apparatus. As shown in Fig. 4, the method includes the following steps.

[0092] In step 401, a transmission position of a synchronous signal block of at least one first type of cell sent by a network apparatus via a signaling is received.

[0093] In step 402, the synchronous signal block of the at least one first type of cell is measured based on the transmission position of the synchronous signal block of the at least one first type of cell.

[0094] Here, the network apparatus may be a base station, for example, may be an

eNB, a gNB, or other apparatus. Alternatively, the network apparatus may be other network apparatus, as long as the apparatus can provide a function of accessing the mobile communication network for the terminal apparatus.

[0095] For a non-carrier aggregation (CA) scenario, the cell in which the terminal apparatus is located may be referred to as a second type of cell, and the second type of cell may also be referred to as a serving cell of the terminal apparatus. In this embodiment, the second type of cell in which the terminal is located and the first type of cell (that is, the neighboring cell) may be cells managed by the same network apparatus, and may also be cells managed by different network apparatuses.

[0096] For a CA scenario, a Primary cell (i.e., P cell) in the cell in which the terminal apparatus is located may be referred to as a second type of cell; other cells except the P cell (including an S cell having the terminal apparatus, that is, the secondary cell) are all classified into the first type of cell. In the scenario, the second type of cell in which the terminal is located and the first type of cell (that is, the neighboring cell) may be cells managed by the same network apparatus, and may also be cells managed by different network apparatuses.

[0097] The receiving the transmission position of the synchronous signal block of the at least one first type of cell sent by the network apparatus via the signaling, includes:

[0098] receiving the signaling from the network apparatus; and

[0099] acquiring a bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of at least one first type of cell.

[00100] The method for transmitting the bitmap to the terminal apparatus may be: the network apparatus notifies the terminal, by a broadcast signaling, the actual transmission position of the SS block of other cells;

[00101] or, the network apparatus notifies the terminal, by a RRC dedicated signaling, the actual transmission position of the SS block of other cells.

[00102] The method further includes:

[00103] receiving a synchronous relationship between the at least one first type of cell sent by the network apparatus and the cell managed by the network apparatus;

[00104] wherein, the synchronous relationship includes: the first type of cell is in a

synchronous state with the cell managed by the network apparatus; or, there is a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

[00105] The acquiring the bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell, includes:

[00106] when there is a synchronous deviation between the first type of cell and the cell managed by the network apparatus, acquiring, from the bitmap, the transmission position(s) of the synchronous signal block(s) of all the first type of cell(s).

[00107] That is, the network apparatus aggregates the transmission position(s) of the synchronous signal block(s) of all neighboring cell(s) into one bitmap, and notifies the actual transmission position(s) of the SS block(s) of other cell(s) in the form of one bitmap. That is, the bitmap contains the complete set of actual SS block positions of all other cells that need to notify.

[00108] For example, referring to Fig. 2, a network apparatus and a terminal operate in a frequency band of 3-6 GHz, and one SS burst set may transmit up to eight SS blocks. Based on the actual deployment requirement and specific implementation of the network, the numbers of SS blocks transmitted by different base station apparatuses are shown in Fig. 2.

[00109] For example, cell 1, cell 2, cell 3, and cell 4 are mutually neighboring cells, the SS block position actually transmitted by cell 1 is the first position of 8 candidate SS block positions, and cell 2 corresponds to the first and second positions; cell 2 corresponds to the second and third positions; and cell 2 corresponds to the first and third positions.

[00110] For cell 1, cell 2, cell 3 and cell 4 are neighboring cells, and cell 2, cell 3 and cell 4 use the first, second, third, and fourth SS block positions, when cell 1 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 1 to the UE served by cell 1, the bitmap is: "11110000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00111] For cell 3, cell 1, cell 2 and cell 4 are neighboring cells, and cells 1, 2 and 4 use the first, second, and third SS block positions, when cell 3 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 3 to the UE served

by cell 3, the bitmap is: "11100000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00112] For cell 4, cell 1, cell 2 and cell 3 are neighboring cells, and cell 1, cell 2 and cell 3 use the first, second, and fourth SS block positions, when cell 4 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 4 to the UE served by cell 4, the bitmap is: "11010000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00113] The network apparatus notifies the actual transmission position of the SS block of each of other cells to be measured in the form of one bitmap.

[00114] When the terminal performs measurement, if the local cell and the neighboring cell are synchronous, the terminal may determine the actual position of the SS block transmitted by the neighboring cell. The terminal directly acquires the actual position of the SS block of the neighboring cell based on the timing of the local cell.

[00115] Different from the foregoing synchronous situation, when there is a synchronous deviation between the local cell and the neighboring cell, the following manner may be adopted:

[00116] when there is a synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus,

[00117] acquiring, the synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus; and

[00118] acquiring, a bitmap corresponding to each of the first type of cell, and acquiring the transmission position of the synchronous signal block of each of the first type of cell based on the bitmap.

[00119] First of all, the network apparatus notifies the terminal of the synchronous deviation between other cell(s) and the local cell corresponding to the network apparatus. Correspondingly, when the terminal performs measurement, if the local cell and the neighboring cell are not synchronous, the terminal may determine the actual position of the SS block transmitted by the neighboring cell based on the notification information and the

deviation of the timings between the cells. The terminal directly acquires the actual position of the SS block of the neighboring cell to be measured based on the timing of the local cell and the timing deviation of the neighboring cell to be measured.

[00120] For example, as shown in Fig. 3, cell 1 and cell 3 are synchronous, cell 2 is 0.5ms backward offset from cell 1 and cell 3, then the first candidate SS block position of cell 2 corresponds to the second candidate SS block position of cell 2; and cell 4 is 1 ms backward offset from cell 1 and cell 3, then the first candidate SS block position of cell 4 corresponds to the third candidate SS block position of cell 1.

[00121] For example, cell 1 notifies the terminal of the time deviation of cell 2, cell 3, cell 4 and cell 1 respectively, the terminal combines the actual SS block transmission position of each of the cell 2, 3 and 4 in 2.4, and then the terminal may determine the reception time of actual transmission SS block of each cell.

[00122] In addition, the present embodiment may also provide a processing manner for a scenario in which a part of the neighboring cells is synchronous with the local cell and the other part of the neighboring cells is not synchronous with the local cell:

[00123] if there is a synchronous deviation between a first part of the first type of cell in at least one first type of cell and the cell managed by the network apparatus, and a second part of the first type of cell in the first type of cell is in the synchronous state with the cell managed by the network apparatus; wherein, the first part of the first type of cell is different from the second part of the first type of cell, and the first part of the first type of cell and the second part of the first type of cell form all the first type of cell;

[00124] then acquiring the transmission position of the synchronous signal block of the first part of the first type of cell based on the bitmap of each first type of cell in the first part of the first type of cell;

[00125] and, acquiring, according to the bitmap of the second part of the first type of cell, the transmission position of the synchronous signal block of the second part of the first type of cell.

[00126] For example, in four neighboring cells, the synchronous relationship between the neighboring cells 1, 2 and the local cell is synchronous, and the neighboring cells 3 and 4 have a deviation; then, the transmission positions of the synchronous signal blocks of the

neighboring cells 1 and 2 are all set in the bitmap and transmitted to the terminal apparatus; the synchronous deviation of the neighboring cells 3 and 4, and the bitmap of the transmission position of the synchronous signal block of the neighboring cell 3, and the bitmap of the transmission position of the synchronous signal block of the neighboring cell 4 are all transmitted to the terminal apparatus. Correspondingly, the terminal apparatus performs measurement on the neighboring cells 1 and 2 based on the bitmap of the transmission position of the synchronous signal block including the neighboring cells 1 and 2; and then, based on the synchronous deviation of the neighboring cells 3 and 4 and the respective bitmaps, perform the measurement at the transmission positions of the synchronous signal blocks of the neighboring cells 3 and 4 respectively.

[00127] There is also a processing manner in the present embodiment, that is, no matter whether there is a synchronous deviation between the neighboring cell and the local cell, the synchronous deviation of the neighboring cell and the bitmap of the transmission position of the synchronous signal block of the neighboring cell are transmitted to the terminal apparatus.

[00128] That is, the synchronous deviation between each of the at least one first type of cell and the cell managed by the network apparatus is transmitted to the terminal apparatus;

[00129] the bitmap corresponding to each of the first type of cell is acquired, and the transmission position of the synchronous signal block of each of the first type of cell is acquired from the bitmap.

[00130] In this scenario, the synchronous deviation of the neighboring cell synchronized with the local cell is equal to 0.

[00131] Finally, it should be noted that, in this embodiment, the synchronous deviation of a certain neighboring cell and the bitmap corresponding to a certain neighboring cell may be sent simultaneously or sequentially, which is not limited herein.

[00132] It can be seen that by adopting the above scheme, the transmission position of the synchronous signal block of the neighboring cell can be transmitted to the terminal apparatus, thereby ensuring that the terminal apparatus can directly measure the neighboring cell at a moment corresponding to the notified transmission position of the synchronous

signal block of the first type of cell, without performing measurement at other positions, thereby saving terminal measurement time and power consumption.

[00133] Third Embodiment

[00134] This embodiment provides a network apparatus. As shown in Fig. 5, the network apparatus includes: a processing unit 51 and a communication unit 52.

[00135] The processing unit 51 is configured to determine a transmission position of a synchronous signal block of at least one first type of cell; and control to send the transmission position of the synchronous signal block of the at least one first type of cell to a terminal apparatus by a signaling; wherein, the terminal apparatus is located within a range of second type of cell managed by the network apparatus.

[00136] The communication unit 52 is configured to send the signaling to the terminal apparatus.

[00137] Here, the network apparatus may be a base station, for example, may be an eNB, a gNB, or other apparatus. Alternatively, the network apparatus may be other network apparatus, as long as the apparatus can provide a function of accessing the mobile communication network for the terminal apparatus.

[00138] It should be further noted that the first type of cell refers to a cell adjacent to the cell where the terminal apparatus is located, which may be a neighboring cell.

[00139] In addition, it should be understood that, the terminal apparatus being within the cell managed by the network apparatus, may be that the terminal apparatus is located in one of a plurality of cells managed by the network apparatus.

[00140] For a non-carrier aggregation (CA) scenario, the cell in which the terminal apparatus is located may be referred to as a second type of cell, and the second type of cell may also be referred to as a serving cell of the terminal apparatus. In the embodiment, the second type of cell in which the terminal is located and the first type of cell (that is, the neighboring cell) may be cells managed by the same network apparatus, and may also be cells managed by different network apparatuses.

[00141] For a CA scenario, a Primary Cell (i.e., P cell) in the cell in which the terminal apparatus is located may be referred to as a second type of cell; and other cells except the P cell (including an S cell having the terminal apparatus, that is, the secondary cell) are all

classified into the first type of cell. In the scenario, the second type of cell in which the terminal is located and the first type of cell (that is, the neighboring cell) may be cells managed by the same network apparatus, and may also be cells managed by different network apparatuses.

[00142] The manners for the network apparatus to determine the transmission position of the actual synchronous signal block (SS block) of other cells adjacent to the network apparatus may include the followings.

[00143] In a first manner, the processing unit 51 is configured to acquire the transmission position of the synchronous signal block of at least one first type of cell by an X2 interface or an S1 interface. (In the present embodiment, the first type of cell being a neighboring cell is taken as an example for subsequent description)

[00144] Specifically, the network apparatus may query the base station apparatus of other cells adjacent to itself by the S1 interface and the X2 interface, and the base station apparatus of other cells notifies the actual transmission position of the SS block of other cells to the network apparatus by the X2 interface and the S1 interface.

[00145] The above querying and notifying process may be performed periodically. The period needs to be smaller than a period in which the base station apparatus updates the actual transmission position of the SS block.

[00146] It should be noted that, this manner is more suitable for the scenario where the first type of cell and the cell in which the terminal apparatus is located are managed by different network apparatuses.

[00147] In a second manner, the processing unit 51 is configured to acquire a broadcast message sent by a network apparatus corresponding to at least one first type of cell; and

[00148] acquire a transmission position of a synchronous signal block of at least one first type of cell is from the broadcast message.

[00149] The network apparatus acquires the actual transmission position of the SS block of other cells adjacent to the network apparatus by receiving and reading the broadcast message of other cells adjacent to the network apparatus.

[00150] Specifically, since the network apparatus may notify the actual SS block transmission position of the local cell by the broadcast message RMSI, the network apparatus

may periodically read the broadcast message of other cells adjacent to the network apparatus and obtain the actual transmission position of the SS block of the neighboring cell.

[00151] It should be noted that, this manner is more suitable for the scenario where the first type of cell and the cell where the terminal apparatus is located are managed by different network apparatuses.

[00152] In addition to the above two manners, for the scenario in which the cell in which the terminal device is located and the first type of cell (that is, the neighboring cell) are both managed by the same network apparatus, the method for acquiring the transmission position of the synchronous signal block of the neighboring cell may be directly acquired from the cell management information of the network apparatus, which will not be elaborated here.

[00153] The processing unit 51 is configured to generate a bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and transmit the bitmap to the terminal apparatus by the signaling.

[00154] The method for sending the bitmap to the terminal apparatus may be: the network apparatus notifies the terminal, by a broadcast signaling, the actual transmission position of the SS block of other cells;

[00155] or, the network apparatus notifies the terminal, by a RRC dedicated signaling, the actual transmission position of the SS block of other cells.

[00156] The processing unit 51 is configured to, when the first type of cell is in a synchronous state with the cell managed by the network apparatus, generate the bitmap of the transmission position(s) of the synchronous signal block(s) including all the first type of cell(s) based on transmission position(s) of the synchronous signal block(s) of all the first type of cell(s); and

[00157] transmit, by the signaling, the bitmap including the transmission position(s) of the synchronous signal block(s) of all the first type of cell(s) to the terminal apparatus.

[00158] That is, the network apparatus aggregates the transmission positions of the synchronous signal blocks of all neighboring cells into one bitmap, and notifies the actual transmission position of the SS block of other cells in the form of a bitmap. That is, the bitmap contains the complete set of actual SS block positions of all other cells needing to

notify.

[00159] For example, referring to Fig. 2, a network apparatus and a terminal operate in a frequency band of 3-6 GHz, and one SS burst set may transmit up to eight SS blocks. Based on the actual deployment requirement and specific implementation of the network, the numbers of the SS blocks transmitted by different base station apparatuses are shown in Fig. 2.

[00160] For example, cell 1, cell 2, cell 3, and cell 4 are mutually neighboring cells, the SS block position actually transmitted by cell 1 is the first position of 8 candidate SS block positions, and cell 2 corresponds to the first and second positions; cell 2 corresponds to the second and third positions; and cell 2 corresponds to the first and third positions.

[00161] For cell 1, cell 2, cell 3 and cell 4 are neighboring cells, and cell 2, cell 3 and cell 4 use the first, second, third, and fourth SS block positions, when cell 1 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 1 to the UE served by cell 1, the bitmap is: "11110000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00162] For cell 3, cell 1, cell 2 and cell 4 are neighboring cells, and cells 1, 2 and 4 use the first, second, and third SS block positions, when cell 3 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 3 to the UE served by cell 3, the bitmap is: "11100000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00163] For cell 4, cell 1, cell 2 and cell 3 are neighboring cells, and cells 1, 2 and 3 use the first, second, and fourth SS block positions, when cell 4 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 4 to UE served by cell 4, the bitmap is: "11010000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00164] The network apparatus notifies the actual transmission position of the SS block of each of other cells to be measured in the form of one bitmap.

[00165] Based on the foregoing scheme, the method may further include: transmitting, to the terminal apparatus, a synchronous relationship between the at least one first type of cell and the cell managed by the network apparatus;

[00166] wherein, the synchronous relationship includes: the first type of cell is in a synchronous state with the cell managed by the network apparatus; or, there is a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

[00167] That is, while the network apparatus notifies the terminal of the actual transmission position of the SS block of other cells by a signaling, the network apparatus notifies the terminal of the synchronous relationship between other cells and the local cell corresponding to the network apparatus, that is, the synchronous state or the synchronous deviation.

[00168] The synchronous state includes: notifying, by the network apparatus, that the local cell corresponding to the network apparatus is in a synchronous state with other neighboring cell(s), to the terminal.

[00169] Correspondingly, when the terminal performs measurement, if the local cell and the neighboring cell are synchronous, the terminal may determine the actual position of the SS block transmitted by the neighboring cell. The terminal directly acquires the actual position of the SS block of the neighboring cell based on the timing of the local cell.

[00170] Different from the foregoing synchronous situation, when there is a synchronous deviation between the local cell and the neighboring cell, the following manner may be adopted.

[00171] The processing unit 51 is configured to send, when there is a synchronous deviation between the first type of cell and the cell managed by the network apparatus, to the terminal apparatus, the synchronous deviation between at least one first type of cell and the cell managed by the network apparatus;

[00172] generate a bitmap corresponding to each of the neighboring first type of cell(s) based on the transmission position of the synchronous signal block of the at least one first type of cell; and

[00173] transmit, by the signaling, the bitmap corresponding to each of the first type of cell to the terminal apparatus.

[00174] First of all, the network apparatus notifies the terminal of the synchronous deviation between other cells and the local cell corresponding to the network apparatus. Correspondingly, when the terminal performs measurement, if the local cell and the neighboring cell are not synchronous, the terminal may determine the actual position of the SS block transmitted by the neighboring cell based on the notification information and the deviation of the timings between the cells. The terminal directly acquires the actual position of the SS block of the neighboring cell to be measured based on the timing of the local cell and the timing deviation of the neighboring cell to be measured.

[00175] For example, as shown in Fig. 3, cell 1 and cell 3 are synchronous, cell 2 is 0.5ms backward offset from cell 1 and cell 3, then the first candidate SS block position of cell 2 corresponds to the second candidate SS block position of cell 1; and cell 4 is 1 ms backward offset from cell 1 and cell 3, then the first candidate SS block position of cell 4 corresponds to the third candidate SS block position of cell 1.

[00176] For example, cell 1 notifies the terminal of the time deviations between cell 2, cell 3, cell 4 and cell 1 respectively, and the terminal combines the actual SS block transmission position of each of the cell 2, cell 3 and cell 4 in 2.4, and then may determine the reception time of actual transmission SS block of each cell.

[00177] In addition, the present embodiment may also provide a processing manner for a scenario in which part of neighboring cells is synchronous with the local cell and the other part of the neighboring cells is not synchronous with the local cell:

[00178] if there is a synchronous deviation between a first part of the first type of cell in the at least one first type of cell and the cell managed by the network apparatus, and a second part of the first type of cell in the first type of cell is in the synchronous state with the cell managed by the network apparatus; wherein, the first part of the first type of cell is different from the second part of the first type of cell, and the first part of the first type of cell and the second part of the first type of cell form all the first type of cells; and

[00179] then transmitting, to the terminal apparatus, the synchronous deviation between the first part of the first type of cell and the cell managed by the network apparatus; generating a bitmap corresponding to each of the first type of cell in the first part of first type of cell based on the transmission position of the synchronous signal block of the first part of

the first type of cell; transmitting, by the signaling, a bitmap corresponding to each of the first type of cell in the first type of cell to the terminal apparatus;

[00180] and, generating, the bitmap including the transmission position of the synchronous signal block of the second part of the first type of cell according to the transmission position of the synchronous signal block of the second part of the first type of cell; and transmitting, to the terminal apparatus, the bitmap including the transmission position of the synchronous signal block of the second part of the first type of cell.

[00181] For example, in four neighboring cells, the synchronous relationship between the neighboring cells 1, 2 and the local cell is synchronous, and there is a deviation between the neighboring cells 3, 4 and the local cell; then, the transmission positions of the synchronous signal blocks of the neighboring cells 1 and 2 are all set in the bitmap and transmitted to the terminal apparatus; and the synchronous deviation of the neighboring cells 3 and 4, the bitmap of the transmission position of the synchronous signal block of the neighboring cell 3, and the bitmap of the transmission position of the synchronous signal block of the neighboring cell 4 are all transmitted to the terminal apparatus.

[00182] There is also a processing manner in the embodiment, that is, no matter whether there is a synchronous deviation between the neighboring cell and the local cell, the synchronous deviation of the neighboring cell and the bitmap of the transmission position of the synchronous signal block of the neighboring cell are transmitted to the terminal apparatus.

[00183] That is, the processing unit 51 is configured to transmit the synchronous deviation between each of the at least one first type of cell and the cell managed by the network apparatus to the terminal apparatus;

[00184] generate a bitmap corresponding to each of the first type of cell based on the transmission position of the synchronous signal block of the at least one first type of cell; and

[00185] transmit the bitmap corresponding to each of the first type of cell to the terminal apparatus by the signaling.

[00186] In this scenario, the synchronous deviation of the neighboring cell synchronized with the local cell is equal to 0.

[00187] Finally, it should be noted that, in this embodiment, the synchronous deviation of a certain neighboring cell and the bitmap corresponding to a certain neighboring cell may

be transmitted simultaneously or sequentially, which is not limited herein.

[00188] It can be seen that by adopting the above scheme, the transmission position of the synchronous signal block of the neighboring cell can be transmitted to the terminal apparatus, thereby ensuring that the terminal apparatus can directly measure the neighboring cell at a moment corresponding to the notified transmission position of the synchronous signal block of the notified first type of cell, without performing measurement at other positions, thereby saving terminal measurement time and power consumption.

[00189] Fourth Embodiment

[00190] This embodiment provides a terminal apparatus. As shown in Fig. 6, the apparatus includes: an information receiving unit 61 and a measuring unit 62.

[00191] The information receiving unit 61 is configured to receive a transmission position of the synchronous signal block of at least one first type of cell sent by a network apparatus via a signaling.

[00192] The measuring unit 62 is configured to measure the synchronous signal block of the at least one first type of cell based on the transmission position of the synchronous signal block of the at least one first type of cell.

[00193] Here, the network apparatus may be a base station, for example, may be an eNB, a gNB, or other apparatus. Alternatively, the network apparatus may be other network apparatus, as long as the apparatus can provide a function of accessing the mobile communication network for the terminal apparatus.

[00194] For a non-carrier aggregation (CA) scenario, the cell in which the terminal apparatus is located may be referred to as a second type of cell, and the second type of cell may also be referred to as a serving cell of the terminal apparatus. In this embodiment, the second type of cell in which the terminal is located and the first type of cell (that is, the neighboring cell) may be cells managed by the same network apparatus, and may also be cells managed by different network apparatuses.

[00195] For a CA scenario, a Primary cell (i.e., P cell) in the cell in which the terminal apparatus is located may be referred to as a second type of cell; other cells except the P cell (including an S cell having the terminal apparatus, that is, the secondary cell) are all classified into the first type of cell. In the scenario, the second type of cell in which the

terminal is located and the first type of cell (that is, the neighboring cell) may be cells managed by the same network apparatus, and may also be cells managed by different network apparatuses.

[00196] The information receiving unit is configured to receive the signaling from the network apparatus.

[00197] Accordingly, the measuring unit is configured to acquire a bitmap from the signaling, and acquire, by the bitmap, the transmission position of the synchronous signal block of at least one first type of cell.

[00198] The method for transmitting the bitmap to the terminal apparatus may be: the network apparatus notifies the terminal, by a broadcast signaling, the actual transmission position of the SS block of other cells;

[00199] or, the network apparatus notifies the terminal, by a RRC dedicated signaling, the actual transmission position of the SS block of other cells.

[00200] The information receiving unit 61 is configured to receive a synchronous relationship between the at least one first type of cell sent by the network apparatus and the cell managed by the network apparatus;

[00201] wherein, the synchronous relationship includes: the first type of cell is in a synchronous state with the cell managed by the network apparatus; or, there is a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

[00202] The measuring unit 62 is configured to, when there is a synchronous deviation between the first type of cell and the cell managed by the network apparatus, acquire from the bitmap, the transmission position(s) of the synchronous signal block(s) of all the first type of cell(s).

[00203] That is, the network apparatus aggregates the transmission position(s) of the synchronous signal block(s) of all neighboring cell(s) into one bitmap, and notifies the actual transmission position(s) of the SS block(s) of other cell(s) in the form of one bitmap. That is, the bitmap contains the complete set of actual SS block positions of all other cells that need to notify.

[00204] For example, referring to Fig. 2, a network apparatus and a terminal operate in a frequency band of 3-6 GHz, and one SS burst set may transmit up to eight SS blocks. Based

on the actual deployment requirement and specific implementation of the network, the numbers of SS blocks transmitted by different base station apparatuses are shown in Fig. 2.

[00205] For example, cell 1, cell 2, cell 3, and cell 4 are mutually neighboring cells, the SS block position actually transmitted by cell 1 is the first position of 8 candidate SS block positions, and cell 2 corresponds to the first and second positions; cell 2 corresponds to the second and third positions; and cell 2 corresponds to the first and third positions.

[00206] For cell 1, cell 2, cell 3 and cell 4 are neighboring cells, and cell 2, cell 3 and cell 4 use the first, second, third, and fourth SS block positions, when cell 1 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 1 to the UE served by cell 1, the bitmap is: "11110000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00207] For cell 3, cell 1, cell 2 and cell 4 are neighboring cells, and cells 1, 2 and 4 use the first, second, and third SS block positions, when cell 3 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 3 to the UE served by cell 3, the bitmap is: "11100000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00208] For cell 4, cell 1, cell 2 and cell 3 are neighboring cells, and cell 1, cell 2 and cell 3 use the first, second, and fourth SS block positions, when cell 4 uses a bitmap to notify the actual transmission position of the SS block of the neighboring cell of cell 4 to the UE served by cell 4, the bitmap is: "11010000", where "1" indicates that the SS block is transmitted at this candidate position, and "0" indicates that the SS block is not transmitted at this candidate position.

[00209] The network apparatus notifies the actual transmission position of the SS block of each of other cells to be measured in the form of one bitmap.

[00210] When the terminal performs measurement, if the local cell and the neighboring cell are synchronous, the terminal may determine the actual position of the SS block transmitted by the neighboring cell. The terminal directly acquires the actual position of the SS block of the neighboring cell based on the timing of the local cell.

[00211] Different from the foregoing synchronous situation, when there is a synchronous deviation between the local cell and the neighboring cell, the following manner may be adopted.

[00212] The measuring unit 62 is configured to, when there is a synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus,

[00213] acquire, the synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus; and

[00214] acquire, the bitmap corresponding to each of the first type of cell, and acquiring the transmission position of the synchronous signal block of each of the first type of cell based on the bitmap.

[00215] First of all, the network apparatus notifies the terminal of the synchronous deviation between other cell(s) and the local cell corresponding to the network apparatus. Correspondingly, when the terminal performs measurement, if the local cell and the neighboring cell are not synchronous, the terminal may determine the actual position of the SS block transmitted by the neighboring cell based on the notification information and the deviation of the timings between the cells. The terminal directly acquires the actual position of the SS block of the neighboring cell to be measured based on the timing of the local cell and the timing deviation of the neighboring cell to be measured.

[00216] For example, as shown in Fig. 3, cell 1 and cell 3 are synchronous, cell 2 is 0.5ms backward offset from cell 1 and cell 3, then the first candidate SS block position of cell 2 corresponds to the second candidate SS block position of cell 1; and cell 4 is 1 ms backward offset from cell 1 and cell 3, so the first candidate SS block location of cell 4 corresponds to the third candidate SS block location of cell 1.

[00217] For example, cell 1 notifies the terminal of the time deviation between cell 2, cell 3, cell 4 and cell 1 respectively, the terminal combines the actual SS block transmission position of each of the cell 2, 3 and 4 in 2.4, and then the terminal may determine the reception time of actual transmission SS block of each cell.

[00218] In addition, the present embodiment may also provide a processing manner for a scenario in which a part of the neighboring cells is synchronous with the local cell and another part of the neighboring cells is not synchronous with the local cell:

[00219] if there is a synchronous deviation between a first part of the first type of cell in at least one first type of cell and the cell managed by the network apparatus, and a second part of the first type of cell in the first type of cell is in the synchronous state with the cell managed by the network apparatus; wherein, the first part of the first type of cell is different from the second part of the first type of cell, and the first part of the first type of cell and the second part of the first type of cell form all the first type of cell;

[00220] then acquiring the transmission position of the synchronous signal block of the first part of the first type of cell based on the bitmap of each first type of cell in the first part of the first type of cell;

[00221] and, acquiring, according to the bitmap of the second part of the first type of cell, the transmission position of the synchronous signal block of the second part of the first type of cell.

[00222] For example, in four neighboring cells, the synchronous relationship between the neighboring cells 1, 2 and the local cell is synchronous, and the neighboring cells 3 and 4 have a deviation; then, the transmission positions of the synchronous signal blocks of the neighboring cells 1 and 2 are all set in the bitmap and transmitted to the terminal apparatus; the synchronous deviation of the neighboring cells 3 and 4, and the bitmap of the transmission position of the synchronous signal block of the neighboring cell 3, and the bitmap of the transmission position of the synchronous signal block of the neighboring cell 4 are all transmitted to the terminal apparatus. Correspondingly, the terminal apparatus performs measurement on the neighboring cells 1 and 2 based on the bitmap of the transmission position of the synchronous signal block including the neighboring cell 1 and cell 2; and then, based on the synchronous deviation of the neighboring cells 3 and 4 and the respective bitmaps, perform the measurement at the transmission positions of the synchronous signal blocks of the neighboring cells 3 and 4 respectively.

[00223] There is also a processing manner in the present embodiment, that is, no matter whether there is a synchronous deviation between the neighboring cell and the local cell, the synchronous deviation of the neighboring cell and the bitmap of the transmission position of the synchronous signal block of the neighboring cell are transmitted to the terminal apparatus.

[00224] That is, the measuring unit 62 is configured to acquire the synchronous deviation between each of the at least one first type of cell and the cell managed by the network apparatus;

[00225] acquire the bitmap corresponding to each of the first type of cell, and acquire the transmission position of the synchronous signal block of each of the first type of cell from the bitmap.

[00226] In this scenario, the synchronous deviation of the neighboring cell synchronized with the local cell is equal to 0.

[00227] Finally, it should be noted that, in this embodiment, the synchronous deviation of a certain neighboring cell and the bitmap corresponding to a certain neighboring cell may be sent simultaneously or sequentially, which is not limited herein.

[00228] It can be seen that by adopting the above scheme, the transmission position of the synchronous signal block of the neighboring cell can be transmitted to the terminal apparatus, thereby ensuring that the terminal apparatus can directly measure the neighboring cell at a moment corresponding to the notified transmission position of the synchronous signal block of the first type of cell, without performing measurement at other locations, thereby saving terminal measurement time and power consumption.

[00229] The embodiments of the present disclosure further provide a hardware composition of the network apparatus, as shown in Fig. 7, including: at least one processor 71, a memory 72, and at least one network interface 73. The components are coupled together through a bus system 74. It should be understood that the bus system 74 is used to implement connection communication between these components. The bus system 84 includes a power bus, a control bus, and a status signal bus expect for the data bus. However, for clarity of description, various buses are labeled as the bus system 74 in Fig. 7.

[00230] It should be understood that, the memory 72 in the embodiments of the present disclosure may be a volatile memory or a non-volatile memory, or may include both volatile memory and non-volatile memory.

[00231] In some embodiments, the memory 72 stores following elements, executable modules or data structures, or a subset thereof, or their extension set:

[00232] an operating system 721 and an application 722.

[00233] The processor 71 is configured to determine a transmission position of a synchronous signal block of at least one first type of cell; and transmit the transmission position of the synchronous signal block of at least one first type of cell to a terminal apparatus by a signaling; wherein, the terminal apparatus is located within a range of a second type of cell managed by the network apparatus. Further, the processor 71 may perform the method steps of the First Embodiment, and details are not elaborated herein.

[00234] A terminal apparatus in the embodiments of the present disclosure includes: a processor and a memory storing a computer program executable on the processor,

[00235] wherein, when the computer programs are executed by the processor, the method steps of the second embodiment are implemented, and details are not elaborated herein.

[00236] The embodiments of the present disclosure provide a computer storage medium, storing computer executable instructions, when the computer executable instructions are executed, the method steps of the first embodiment or second embodiment are implemented.

[00237] The above apparatus of the embodiments of the present disclosure may also be stored in a computer-readable storage medium if being implemented in the form of a software functional unit and sold or used as an independent product. Based on such understanding, the essence of the technical solutions of the present application, or the part contributing to the related art or all or a part of the technical solutions, may be embodied in the form of a software product. The computer software product is stored in the storage medium including a number of instructions such that a computer device (which may be a personal computer, a server, or a network device, etc.) performs all or a part of steps of the method described in each of the embodiments of the present disclosure. The foregoing storage medium includes: any medium that is capable of storing program codes such as a USB disk, a mobile hard disk, a Read-Only Memory (ROM), a Random Access Memory (RAM), a magnetic disk or an optical disk, and the like. Thus, the embodiments of the present disclosure are not limited to any specific combination of hardware and software.

[00238] Accordingly, the embodiments of the present disclosure further provide a computer storage medium, storing a computer program, and the computer program is

configured to perform data scheduling method of embodiments of the present disclosure.

[00239] Although the preferred embodiments of the present disclosure have been disclosed for purpose of illustration, those skilled in the art will recognize that various modifications, additions and substitutions are possible, and the scope of the disclosure should not be limited to the embodiments described above.

WHAT IS CLAIMED IS:

1. A method for indicating a position of a synchronous signal block, applied to a network apparatus, comprising:

determining a transmission position of a synchronous signal block of at least one first type of cell; and

sending, by a signaling, the transmission position of the synchronous signal block of the at least one first type of cell to a terminal apparatus; wherein the terminal apparatus is located within a range of a second type of cell managed by the network apparatus.

2. The method according to claim 1, wherein, the sending, by the signaling, the transmission position of the synchronous signal block of the at least one first type of cell to the terminal apparatus, comprises:

generating a bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and sending the bitmap to the terminal apparatus by the signaling.

3. The method according to claim 2, further comprising:

sending, to the terminal apparatus, a synchronous relationship between the at least one first type of cell and a cell managed by the network apparatus;

wherein, the synchronous relationship comprises: a synchronous state between the first type of cell and the cell managed by the network apparatus; or, a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

4. The method according to claim 2, wherein, the generating the bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and sending the bitmap to the terminal apparatus by the signaling, comprises:

when at least one first type of cell is in a synchronous state with the cell managed by the network apparatus, generating the bitmap of the transmission position of the synchronous signal block comprising all the first type of cell based on the transmission position of the synchronous signal block of all the first type of cell; and

sending, by the signaling, the bitmap comprising the transmission position of the synchronous signal block of all the first type of cell to the terminal apparatus.

5. The method according to claim 2, wherein, the generating the bitmap based on the

transmission position of the synchronous signal block of the at least one first type of cell, and sending the bitmap to the terminal apparatus by the signaling, comprises:

when there is a synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus, sending, to the terminal apparatus, the synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus;

generating the bitmap corresponding to each of the at least one first type of cell based on the transmission position of the synchronous signal block of the at least one first type of cell; and

sending, by the signaling, the bitmap corresponding to each of the first type of cell to the terminal apparatus.

6. The method according to claim 2, wherein, the generating the bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and sending the bitmap to the terminal apparatus by the signaling, comprises:

if there is a synchronous deviation between a first part of first type of cell in the at least one first type of cell and the cell managed by the network apparatus, and a second part of first type of cell in the first type of cell is in a synchronous state with the cell managed by the network apparatus; wherein, the first part of first type of cell is different from the second part of first type of cell, and the first part of first type of cell and the second part of first type of cell form all of the at least one first type of cell;

then sending, to the terminal apparatus, the synchronous deviation between the first part of first type of cell and the cell managed by the network apparatus; generating the bitmap corresponding to each of the first type of cell in the first part of first type of cell based on the transmission position of the synchronous signal block of the first part of first type of cell; sending, by the signaling, the bitmap corresponding to each of the first type of cell in the first part of first type of cell to the terminal apparatus;

and, generating the bitmap comprising the transmission position of the synchronous signal block of the second part of first type of cell based on the transmission position of the synchronous signal block of the second part of first type of cell; and sending, by the signaling, the bitmap comprising the transmission position of the synchronous signal block of the

second part of first type of cell to the terminal apparatus.

7. The method according to claim 2, wherein, the generating the bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and sending the bitmap to the terminal apparatus by the signaling, comprises:

sending, to the terminal apparatus, a synchronous deviation between each first type of cell in the at least one first type of cell and the cell managed by the network apparatus;

generating the bitmap corresponding to said each first type of cell based on the transmission position of the synchronous signal block of the first type of cell; and

sending, by the signaling, the bitmap corresponding to said each first type of cell to the terminal apparatus.

8. The method according to claim 1, wherein, the determining the transmission position of the synchronous signal block of the at least one first type of cell, comprises:

acquiring, by an X2 interface or an S1 interface, the transmission position of the synchronous signal block of the at least one first type of cell.

9. The method according to claim 8, wherein, the acquiring, by the X2 interface or the S1 interface, the transmission position of the synchronous signal block of the at least one first type of cell, comprises:

sending, by the X2 interface or the S2 interface, inquiry information of the synchronous signal block to the network apparatus corresponding to at least one first type of cell; and

receiving, by the X2 interface or the S2 interface, the transmission position of the synchronous signal block of the first type of cell fed back by the network apparatus corresponding to the at least one first type of cell.

10. The method according to claim 1, wherein, the determining the transmission position of the synchronous signal block of the at least one first type of cell, comprises:

acquiring a broadcast message sent by the network apparatus corresponding to at least one first type of cell; and

acquiring, from the broadcast message, the transmission position of the synchronous signal block of the at least one first type of cell.

11. A method for indicating a position of a synchronous signal block, applied to a terminal apparatus, comprising:

receiving a transmission position of a synchronous signal block of at least one first type of cell sent by a network apparatus via a signaling; and

measuring the synchronous signal block of the at least one first type of cell based on the transmission position of the synchronous signal block of the at least one first type of cell.

12. The method according to claim 11, wherein, the receiving the transmission position of the synchronous signal block of the at least one first type of cell sent by the network apparatus via the signaling, comprises:

receiving a signaling sent by the network apparatus; and

acquiring a bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell.

13. The method according to claim 12, further comprising:

receiving a synchronous relationship between the at least one first type of cell sent by the network apparatus and a cell managed by the network apparatus;

wherein, the synchronous relationship comprises: a synchronous state between the first type of cell and the cell managed by the network apparatus; or, a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

14. The method according to claim 13, wherein, the acquiring the bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell, comprises:

when the at least one first type of cell is in the synchronous state with the cell managed by the network apparatus, acquiring, from the bitmap, the transmission position of the synchronous signal block of all the at least one first type of cell.

15. The method according to claim 13, wherein, the acquiring the bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell, comprises:

when there is a synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus,

acquiring the synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus; and

acquiring the bitmap corresponding to each of the first type of cell, and acquiring the

transmission position of the synchronous signal block of each of the first type of cell based on the bitmap.

16. The method according to claim 13, wherein, the acquiring the bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell, comprises:

if there is a synchronous deviation between a first part of first type of cell in the at least one first type of cell and the cell managed by the network apparatus, and a second part of first type of cell in the first type of cell is in a synchronous state with the cell managed by the network apparatus; wherein, the first part of first type of cell is different from the second part of first type of cell, and the first part of first type of cell and the second part of first type of cell form all of the first type of cell;

then acquiring the transmission position of the synchronous signal block of the first part of first type of cell based on the bitmap of each first type of cell in the first part of first type of cell;

and, acquiring the transmission position of the synchronous signal block of the second part of first type of cell according to the bitmap of the second part of first type of cell.

17. The method according to claim 12, wherein, the acquiring the bitmap from the signaling, and acquiring, by the bitmap, the transmission position of the synchronous signal block of the at least one first type of cell, comprises:

acquiring a synchronous deviation between each of the first type of cell in the at least one first type of cell and the cell managed by the network apparatus; and

acquiring the bitmap corresponding to each of the first type of cell, and acquiring the transmission position of the synchronous signal block of each of the first type of cell from the bitmap.

18. A network apparatus, comprising:

a processing unit, configured to determine a transmission position of a synchronous signal block of at least one first type of cell; and control to send the transmission position of the synchronous signal block of the at least one first type of cell to a terminal apparatus by a signaling; wherein, the terminal apparatus is located within a range of a second type of cell managed by the network apparatus; and

a communication unit, configured to send the signaling to the terminal apparatus.

19. The network apparatus according to claim 18, wherein, the processing unit is configured to generate a bitmap based on the transmission position of the synchronous signal block of the at least one first type of cell, and send the bitmap to the terminal apparatus by the signaling.

20. The network apparatus according to claim 19, wherein, the communication unit is configured to send, to the terminal apparatus, a synchronous relationship between the at least one first type of cell and the cell managed by the network apparatus;

wherein, the synchronous relationship comprises: a synchronous state between the first type of cell and the cell managed by the network apparatus; or, a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

21. The network apparatus according to claim 19, wherein, the processing unit is configured to, when the at least one first type of cell is in a synchronous state with the cell managed by the network apparatus, generate the bitmap of the transmission position of the synchronous signal block comprising all the first type of cell based on the transmission position of the synchronous signal block of all the first type of cell; and control the communication unit to send, by the signaling, the bitmap comprising the transmission position of the synchronous signal block of all the first type of cell to the terminal apparatus.

22. The network apparatus according to claim 19, wherein, the processing unit is configured to, when there is a synchronous deviation between the first type of cell and the cell managed by the network apparatus, send, to the terminal apparatus, the synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus; generate the bitmap corresponding to each of the first type of cell based on the transmission position of the synchronous signal block of the at least one first type of cell; and control the communication unit to send, by the signaling, the bitmap corresponding to each of the first type of cell to the terminal apparatus.

23. The network apparatus according to claim 19, wherein, the processing unit is configured to, if there is a synchronous deviation between a first part of first type of cell in the at least one first type of cell and the cell managed by the network apparatus, and a second part of first type of cell in the first type of cell is in a synchronous state with the cell managed

by the network apparatus; wherein, the first part of first type of cell is different from the second part of first type of cell, and the first part of first type of cell and the second part of first type of cell form all of the first type of cell;

then send, to the terminal apparatus, the synchronous deviation between the first part of first type of cell and the cell managed by the network apparatus; generate the bitmap corresponding to each of the first type of cell in the first part of first type of cell based on the transmission position of the synchronous signal block of the first part of first type of cell; and control the communication unit to send, by the signaling, the bitmap corresponding to each of the first type of cell in the first type of cell to the terminal apparatus;

and, generate, the bitmap comprising the transmission position of the synchronous signal block of the second part of first type of cell according to the transmission position of the synchronous signal block of the second part of first type of cell; and control the communication unit to send, to the terminal apparatus, the bitmap comprising the transmission position of the synchronous signal block of the second part of the first type of cell by the signaling.

24. The network apparatus according to claim 19, wherein, the processing unit is configured to send, to the terminal apparatus, a synchronous deviation between each of the first type of cell in the at least one first type of cell and the cell managed by the network apparatus; and generate the bitmap corresponding to each of the first type of cell based on the transmission position of the synchronous signal block of the first type of cell; and control the communication to send, by the signaling, the bitmap corresponding to each of the first type of cell to the terminal apparatus.

25. The network apparatus according to claim 18, wherein, the processing unit is configured to acquire, by an X2 interface or an S1 interface, the transmission position of the synchronous signal block of at least one first type of cell.

26. The network apparatus according to claim 25, wherein, the processing unit is configured to send, by the X2 interface or the S2 interface, inquiry information of the synchronous signal block to the network apparatus corresponding to at least one first type of cell; and receive, by the X2 interface or the S2 interface, the transmission position of the synchronous signal block of the first type of cell fed back by the network apparatus

corresponding to the at least one first type of cell.

27. The network apparatus according to claim 18, wherein, the processing unit is configured to acquire, a broadcast message sent by the network apparatus corresponding to at least one first type of cell by the communication unit; and acquire, from the broadcast message, the transmission position of the synchronous signal block of at least one first type of cell.

28. A terminal apparatus, comprising:

an information receiving unit, configured to receive a transmission position of a synchronous signal block of at least one first type of cell sent by a network apparatus via a signaling; and

a measuring unit, configured to measure the synchronous signal block of the at least one first type of cell based on the transmission position of the synchronous signal block of the at least one first type of cell.

29. The terminal apparatus according to claim 28, wherein, the information receiving unit is configured to receive a signaling from the network apparatus; and

accordingly, the measuring unit is configured to acquire a bitmap from the signaling, and acquire, by the bitmap, the transmission position of the synchronous signal block of at least one first type of cell.

30. The terminal apparatus according to claim 29, wherein, the information receiving unit is configured to receive a synchronous relationship between the at least one first type of cell sent by the network apparatus and a cell managed by the network apparatus;

wherein, the synchronous relationship comprises: a synchronous state between the first type of cell and the cell managed by the network apparatus; or, a synchronous deviation between the first type of cell and the cell managed by the network apparatus.

31. The terminal apparatus according to claim 30, wherein, the measuring unit is configured to, when there is the synchronous deviation between the first type of cell and the cell managed by the network apparatus, acquire, from the bitmap, the transmission position of the synchronous signal block of all the first type of cell.

32. The terminal apparatus according to claim 30, wherein, the measuring unit is configured to, when there is the synchronous deviation between the first type of cell and the

cell managed by the network apparatus, acquire, the synchronous deviation between the at least one first type of cell and the cell managed by the network apparatus; and acquire, the bitmap corresponding to each of the first type of cell, and acquire the transmission position of the synchronous signal block of each of the first type of cell based on the bitmap.

33. The terminal apparatus according to claim 30, wherein, the measuring unit is configured to, if there is the synchronous deviation between a first part of first type of cell in the at least one first type of cell and the cell managed by the network apparatus, and a second part of first type of cell in the first type of cell is in the synchronous state with the cell managed by the network apparatus; wherein, the first part of first type of cell is different from the second part of first type of cell, and the first part of first type of cell and the second part of first type of cell form all of the first type of cell;

then acquire the transmission position of the synchronous signal block of the first part of first type of cell based on the bitmap of each first type of cell in the first part of first type of cell;

and, acquire, according to the bitmap of the second part the first type of cell, the transmission position of the synchronous signal block of the second part of first type of cell.

34. The terminal apparatus according to claim 30, wherein, the measuring unit is configured to acquire the synchronous deviation between each first type of cell in the at least one first type of cell and the cell managed by the network apparatus; and

acquire the bitmap corresponding to each of the first type of cell, and acquire the transmission position of the synchronous signal block of each of the first type of cell from the bitmap.

35. A network apparatus, comprising: a processor and a memory for storing a computer program executable on the processor,

wherein, when executing the computer program, the processor performs the method according to any one of claims 1 to 10.

36. A terminal apparatus, comprising: a processor and a memory for storing a computer program executable on the processor,

wherein, when executing the computer program, the processor performs the method according to any one of claims 11 to 17.

37. A computer storage medium for storing computer executable instructions, wherein when the computer executable instructions are executed, the method according to any one of claims 1 to 10 is implemented.

38. A computer storage medium for storing computer executable instructions, wherein when the computer executable instructions are executed, the method according to any one of claims 11 to 17 is implemented.