

METHOD, APPARATUS, AND SYSTEM FOR SERVICE DATA PROCESSING AND VERIFICATION

TECHNICAL FIELD

[0001] The present application relates to the field of computer data processing technologies, and in particular, to a method, an apparatus, and a system for service data processing and verification.

BACKGROUND

[0002] Security and reliability of service data play a very important role in ensuring normal processing of the service system data and output of a reliable result. Especially, with continuous development of Internet finance, current payment institutions usually construct their own core accounting systems to process fund transfer requests of users. However, how to ensure that service data in these similar core accounting systems is not tampered with and to improve credibility of data disclosed by the payment institutions is a problem that currently draws increasing attention of many financial enterprise users.

[0003] Sensitive accounting data in the service data is usually recorded in an accounting system database of the payment institution. Because the payment institution has the highest management authority for the database, the payment institution theoretically can randomly tamper with data in the database. The accounting data is directly associated with funds, and therefore the accounting data is usually a type of data with the highest importance in the payment institution. Therefore, the payment institution usually uses some technical methods to show the public that the accounting data of the payment institution is authentic and reliable, and cannot be tampered with once the accounting data is generated, to improve credibility of the payment institution. For example, it is confirmed that transfer of a donation is authentic and reliable in a charity donation scenario. For another example, it is confirmed that fund record data of a payment institution is not modified in a regulatory review scenario. An existing common method for determining reliability of

the accounting data is usually to perform account checking. For example, in a method, verification can be performed using data of another institution or similar entity. For the same fund transfer, related participants can store accounting data from the perspectives of the related participants, and the accounting data is used to perform verification on the data of the payment institution. That is, whether the accounting data of the payment institution is tampered with is verified by presenting different data of the same fund transfer document. The accounting data and related data of another institution support each other, so that the accounting data and the related data can be supported by each other, to increase costs for forgery of the accounting data.

[0004] In the previous described and other existing methods, relatively high costs are needed for maintaining credibility of accounting data of an institution. For example, when verification is performed using data of another institution, usually at least three parties need to save different copies of the same service data, so that a party whose data is forged can be determined. Furthermore, there is a relatively high requirement on security of software or hardware for data transmission and storage. In addition, it is inappropriate to disclose some sensitive data for some payment institutions. Therefore, in a process of monitoring and processing accounting data, the original accounting data or a processing procedure is largely changed and modified, affecting the original processing procedure and performance of a system for the accounting data. Furthermore, a trust problem cannot be fundamentally resolved in the method. For example, an external institution can be an institution associated with the payment institution, and the external institution and the payment institution can make forgery together.

[0005] Therefore, currently a problem that the accounting data is modified cannot be fundamentally resolved in terms of the accounting data in some existing monitoring methods used by the payment institution to ensure authenticity and reliability of the accounting data of the payment institution, thereby reducing reliability of data disclosed by the payment institution.

SUMMARY

[0006] The present application is intended to provide a method, an apparatus, and a system for service data processing and verification, so that on the premise that impact on an original processing procedure and performance is relatively small, a

copy of original service data is stored by embedding the original service data in fingerprint data and writing the fingerprint data to a blockchain. As such, whether the service data is tampered with can be verified, and it can be ensured that the service data cannot be modified, thereby improving reliability and credibility of the service data.

[0007] The method, apparatus, and system for service data processing and verification provided in the present application are implemented as follows:

[0008] A method for service data processing is provided, and the method includes: obtaining service data that is to be processed, and generating, by using a predetermined method, fingerprint data of the service data that is to be processed; and writing the fingerprint data to a blockchain corresponding to the service data that is to be processed, and generating blockchain copy data of the service data that is to be processed in the blockchain, where the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node.

[0009] An apparatus for service data processing is provided, and the apparatus includes: a fingerprint data generation module, configured to obtain service data that is to be processed, and generate, by using a predetermined method, fingerprint data of the service data that is to be processed; and a blockchain data generation module, configured to write the fingerprint data to a blockchain corresponding to the service data that is to be processed, and generate blockchain copy data of the service data that is to be processed in the blockchain, where the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node.

[0010] A method for service data verification is provided, and the method includes: determining service data that is to be verified, and obtaining, from stored blockchain data, blockchain copy data associated with the service data that is to be verified, where the blockchain copy data includes data information that is generated based on fingerprint data of service data to be processed and that is stored in a blockchain, and the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node; calculating, by using a predetermined method, first fingerprint data of the service data that is to be verified, and obtaining second fingerprint data in the blockchain copy data that is corresponding to the service data that is to be verified; and determining, through comparison, whether the first fingerprint data is the same as the second fingerprint data, and determining that the service data that is to be verified is not modified if the first fingerprint data is the

same as the second fingerprint data.

[0011] A service system is provided, and includes an I/O interface and a processing unit, where the I/O interface is configured to receive service data that is to be processed; and the processing unit is configured to generate, by using a
 5 predetermined method, fingerprint data of the service data that is to be processed; and is further configured to write the service data to an original database, write the fingerprint data to a blockchain database corresponding to the service data that is to be processed, and generate blockchain copy data of the service data that is to be processed in the blockchain, where the blockchain copy data stores fingerprint data in
 10 blockchain copy data of a previous adjacent node.

[0012] According to the method, apparatus, and system for service data processing and verification provided in the present application, a blockchain is used to store a copy of data in a conventional service database. In a processing procedure of an original service system, only fingerprint data corresponding to service data needs
 15 to be generated, and the fingerprint data is then stored in a corresponding blockchain to generate blockchain copy data. As such, the processing procedure of the original service system is slightly invaded, and while it is ensured that the conventional database has a high-performance capability, a monitoring effect of the service data is ensured, and the service data cannot be modified, thereby improving reliability and
 20 credibility of the service data, especially, sensitive accounting data.

BRIEF DESCRIPTION OF DRAWINGS

[0013] To describe the technical solutions in the implementations of the present application or in the existing technology more clearly, the following briefly describes the accompanying drawings needed for describing the implementations or the existing
 25 technology. Apparently, the accompanying drawings in the following description merely show some implementations of the present application, and a person of ordinary skill in the art can still derive other drawings from these accompanying drawings without creative efforts.

[0014] FIG. 1 is a schematic diagram illustrating a data structure for storing
 30 blockchain data, according to the present application;

[0015] FIG. 2 is a method flowchart illustrating an implementation of a method for data processing, according to the present application;

[0016] FIG. 3 is a schematic diagram illustrating an implementation scenario of generating fingerprint data of service data that is to be processed, according to the present application;

[0017] FIG. 4 is a schematic diagram illustrating implementation of another implementation scenario of a method for service data processing, according to the present application;

[0018] FIG. 5 is a schematic method flowchart illustrating another implementation of a method for service data processing, according to the present application;

[0019] FIG. 6 is a schematic diagram illustrating another implementation scenario of generating fingerprint data of service data that is to be processed, according to the present application;

[0020] FIG. 7 is a schematic diagram illustrating another implementation scenario of generating fingerprint data of service data that is to be processed, according to the present application;

[0021] FIG. 8 is a method flowchart illustrating an implementation of a method for service data verification, according to the present application;

[0022] FIG. 9 is a schematic diagram illustrating a module structure in an implementation of an apparatus for service data processing, according to the present application;

[0023] FIG. 10 is a schematic diagram illustrating a module structure in another implementation of an apparatus for service data processing, according to the present application;

[0024] FIG. 11 is a schematic diagram illustrating a module structure in another implementation of an apparatus for service data processing, according to the present application; and

[0025] FIG. 12 is a schematic structural diagram illustrating an implementation of a service system, according to the present application.

DESCRIPTION OF IMPLEMENTATIONS

[0026] To make a person skilled in the art understand the technical solutions in the present application better, the following clearly and comprehensively describes the technical solutions in the implementations of the present application with reference to

the accompanying drawings in the implementations of the present application. Apparently, the described implementations are merely some but not all of the implementations of the present application. All other implementations obtained by a person of ordinary skill in the art based on the implementations of the present application without creative efforts shall fall within the protection scope of the present application.

[0027] FIG. 2 is a method flowchart illustrating an implementation of a method for service data processing, according to the present application. Although operation steps of a method or structures of an apparatus shown in the following implementations or the accompanying drawings are provided in the present application, the method or the apparatus can include more or fewer operation steps or module units based on conventional or noncreative efforts. An execution sequence of steps or module structures of the apparatus without a logical causal relationship are not limited to an execution sequence or module structures shown in the implementations of the present application or the accompanying drawings. When being applied to an actual apparatus or end-user device product, the method or the module structures can be performed sequentially or in parallel based on the method or the module structures shown in the implementations or the accompanying drawings (for example, in an environment of parallel processing or multithreaded processing, or even an implementation environment including distributed processing).

[0028] A blockchain is a decentralized, trustless, and tamper-resistant distributed data storage technology. FIG. 1 is a schematic diagram illustrating a data structure for storing blockchain data, according to the present application. As shown in FIG. 1, a linked data structure of a blockchain ensures that data can be changed only by using an incremental method. Recorded data remains in a state it is when being created. In addition, the blockchain determines, by using a specific consensus algorithm, a node responsible for recording data of each block, and the node is agreed upon by one or more nodes. In a case of changing existing data, the data usually can be replaced only by forging the entire blockchain. This is almost impossible in a consensus algorithm for proof of work or a consensus algorithm for proof of stake. As such, in the solutions of the present application, a blockchain is used to store a copy of data in a conventional service database. In a processing procedure of an original service system, only fingerprint data corresponding to service data needs to be generated, and the fingerprint data is then stored in a corresponding blockchain to generate blockchain

copy data. As such, the processing procedure is merely slightly changed, and while it is ensured that the conventional database has a high-performance capability, a monitoring effect of the service data is ensured, and the service data cannot be modified, thereby improving reliability and credibility of the service data.

5 **[0029]** For clarity, an application scenario in which an accounting system of a specific payment institution generates blockchain copy data of accounting data is used for description. Certainly, service data processed in the present implementation is accounting data. However, a person skilled in the art can understand that an essence spirit of the solutions can be applied to another scenario in which service data in a service system is prevented from being tampered with. That is, a fingerprint data generation logic is embedded in an original system processing procedure, and the fingerprint data is written to a blockchain, so that it can be determined, by comparing a fingerprint data value of current service data with an original fingerprint data value stored in the blockchain, whether the current service data is modified, and the possibility of tampering with the data is eliminated, thereby improving reliability and credibility of the service data. The service data in the implementation solutions of the present application is not limited to the accounting data, but there is a more obvious application effect on the sensitive accounting data. The solutions can significantly improve credibility of data disclosed by related financial service users such as a payment institution and enhance service use experience of a user who has an interest relationship with the accounting data.

[0030] A specific implementation is shown in FIG. 2. In an implementation of the method for service data processing provided in the present application, the method can include the following steps.

25 **[0031]** S1. Obtain service data that is to be processed, and generate, by using a predetermined method, fingerprint data of the service data that is to be processed.

[0032] A service system of a payment institution can obtain and store corresponding service data based on an accounting request of an accounting initiator. In an application scenario of the implementation of the present application, when an accounting system normally stores accounting data in a database, the accounting data can be obtained. The accounting data can be collectively referred to as service data that is to be processed here. The service data that is to be processed then can be processed by using the predetermined method, to generate the fingerprint data of the service data that is to be processed.

[0033] In the implementation, the payment institution can be understood as an institution that provides some or all currency fund transfer services and that serves as an intermediary institution between a payer and a payee. The service data can include fund change credential data generated in a system database when the payment institution provides a fund transfer and record service, or can include fund change credential data or associated data that is directly obtained from the accounting initiator and that is generated in fund transfer and record. For example, the service data that is to be processed can be billing data received from the service system.

[0034] In an application scenario of the implementation, fingerprint data can be defined for the accounting data based on an implementation scenario, a service type, etc. of the accounting data, and one piece of accounting data can be uniquely determined by using the fingerprint data. If the accounting data is tampered with, the generated fingerprint data of the accounting data is also changed. As such, authenticity of certain accounting data can be determined by comparing fingerprint data of the accounting data.

[0035] To protect sensitive data in the original service data, in another implementation of the method in the present application, a predetermined algorithm can be selected, which may include an algorithm in which generated fingerprint data cannot be reversely obtained. In an implementation provided in the present application, a process of generating the fingerprint data is set to be unidirectional and irreversible.

[0036] In the solution provided in the implementation, the process of generating the fingerprint data is unidirectional and irreversible. As such, in the implementation, the fingerprint data of the data can be easily obtained by using the data, but the data cannot be deduced by using the fingerprint data. Therefore, the method provided in the implementation can effectively and reliably ensure data security and privacy protection.

[0037] An algorithm used for generating the fingerprint data of the service data that is to be processed can be selected or customized based on a service scenario or a service data processing demand, and the service data that is to be processed is converted into identification information that can uniquely determine the service data that is to be processed. The predetermined algorithm for generating the fingerprint data usually can include a plurality of methods. The predetermined method in an implementation in the present application can be performing data hash processing,

namely, hash (Hash) processing, on the service data that is to be processed, and a generated hash value can be used as the fingerprint data of the service data that is to be processed in the present implementation. Therefore, in an implementation of the method for service data processing provided in the present application, the generating, by using a predetermined method, fingerprint data of the service data that is to be processed can include the following step:

[0038] S101. Perform hash processing on the service data that is to be processed, and use a hash value generated through the hash processing as the fingerprint data of the service data that is to be processed.

[0039] In information security technologies, a hash (Hash) function can provide a message integrity verification service, and can generate output of a fixed length for input messages of different lengths. The output of the fixed length is referred to as a "hash" or a "message digest" (Message digest) of the original input message. FIG. 3 is a schematic diagram illustrating an implementation scenario of generating fingerprint data of service data that is to be processed, according to the present application. A specific hash method can be customized, or can be MD5, SHA-1, or another algorithm. In the implementation of the present application, the hash value of the service data that is to be processed can be used as the fingerprint data of the service data that is to be processed, to improve security of the original service data and privacy.

[0040] S2. Write the fingerprint data to a blockchain corresponding to the service data that is to be processed, and generate blockchain copy data of the service data that is to be processed in the blockchain, where the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node.

[0041] In the existing service system of the payment institution, when the accounting data is stored, the fingerprint data of the accounting data can be calculated by using the previous method, and then the fingerprint data can be written to the blockchain. The fingerprint data can be stored in a corresponding data storage unit, for example, a database or another storage medium that is dedicated for storing data in a public blockchain. As such, it is equivalent to that there are different versions of the same accounting data in both the existing database and the blockchain, and the two versions are anchored to and associated with each other to determine whether the original accounting data in the database is tampered with.

[0042] A linked data structure of the blockchain ensures that data can be changed

only by using an incremental method. The blockchain copy data of the service data that is recorded in the blockchain remains in a state it is when being created. In addition, the blockchain determines, by using a specific consensus algorithm (for example, the blockchain copy data includes the fingerprint data in the blockchain copy data of the previous adjacent node), a node responsible for recording data of each block, and the node is agreed upon by one or more nodes. In a case of changing existing data, the data usually can be replaced only by forging the entire blockchain. Currently, in a case of full disclosure to the outside (or full disclosure to a specified monitored object), it is almost impossible to replace data in the entire blockchain. Therefore, in the present application, a feature that the fingerprint data in the blockchain cannot be tampered with can be used to determine, in an associated way, whether the original accounting data in the database is tampered with, improving credibility of the accounting data.

[0043] In some implementations of the present application, the fingerprint data can be stored when the service data is stored in the database, and the fingerprint data is written to the blockchain. In another implementation, to further reduce impact on the original service system and improve processing performance of the original service system, after the service data that is to be processed is stored in the database, the service data that is to be processed can be written into the blockchain by using an asynchronous method (in other words, the service data is written to both the database and the blockchain). An overall service system processing procedure is shown in FIG. 4. FIG. 4 is a schematic diagram illustrating implementation of another implementation scenario of a method for service data processing, according to the present application. In other words, accounting data in FIG. 4 is a specific application scenario of the service data in the implementation of the present application. Therefore, in another implementation of the method for service data processing provided in the present application, the writing the fingerprint data to a blockchain corresponding to the service data that is to be processed includes the following step:

[0044] S102. Write, by using an asynchronous method, the fingerprint data to the blockchain corresponding to the service data that is to be processed.

[0045] As such, the impact on the original service system can be further reduced, and the processing performance of the original service system can be improved.

[0046] According to the method for service data processing provided in the present application, a blockchain is used to store a copy of data in a conventional

service database. In a processing procedure of an original service system, only fingerprint data corresponding to service data needs to be generated, and the fingerprint data is then stored in a corresponding blockchain to generate blockchain copy data. As such, the processing procedure of the original service system is slightly
 5 invaded, and while it is ensured that the conventional database has a high-performance capability, a monitoring effect of the service data is ensured, and the service data cannot be modified, thereby improving reliability and credibility of the service data.

[0047] FIG. 5 is a schematic method flowchart illustrating another
 10 implementation of a method for service data processing, according to the present application. As shown in FIG. 5, when the service data that is to be processed is generated, determined key elements such as IDs of two transfer parties, time, and an amount in the service data that is to be processed can be first extracted, and then the fingerprint data is generated for the key element data. As such, common key element
 15 data can be extracted from a plurality of different types of service data. Therefore, source data of fingerprint data is simplified, and the fingerprint data is quickly generated, improving a data processing effect. In another implementation of the method for service data processing provided in the present application, the method can further include the following step:

[0048] S10. Extract key element data of a predetermined type from the service
 20 data that is to be processed. Correspondingly, the generating, by using a predetermined method, fingerprint data of the service data that is to be processed includes the following: processing the extracted key element data by using the predetermined method, to generate the fingerprint data of the service data that is to be
 25 processed.

[0049] FIG. 6 is a schematic diagram illustrating another implementation scenario
 of generating fingerprint data of service data that is to be processed, according to the present application. As shown in FIG. 6, key element data Data_Key, such as two transfer parties, time, an amount, a service document number, and a service type in an
 30 accounting data model Data_Count can be extracted, and then fingerprint data Data_MD5 is generated for these key elements.

[0050] In some other implementations, when at least one piece of the key element
 data is absent from the service data that is to be processed, the method can include the following step:

[0051] S11. Determine a default value of the key element data that is absent based on a service type of the service data, and use the default value as a value of the key element data for generating the fingerprint data.

[0052] In a specific application scenario, for example, when a quantity of pieces
 5 of the key element data that is absent is less than a predetermined quantity (for example, two), the fingerprint data of the service data that is to be processed can be generated by using the key element data extracted from the service data that is to be processed and the default value of the key element data that is absent. For example, FIG. 7 is a schematic diagram illustrating another implementation scenario of
 10 generating fingerprint data of service data that is to be processed, according to the present application. When the key element data of the service type is absent, the default service type, namely, "the value is a default value", can be used as a default value of the service type, and then the fingerprint data Data_MD5 of the service data that is to be processed is generated with reference to the obtained key element data
 15 such as a sequence number, a payee, a payer, the amount, and the time.

[0053] According to the method for service data processing provided in the implementation of the present application, there can be different versions of the same document in both an existing database and a blockchain, and the two versions are anchored to each other. Data in the blockchain can be disclosed, or disclosed to a
 20 specified object such as a regulatory authority or a specified user, to verify whether service data stored in the database is tampered with, and improve credibility of the service data. Therefore, based on the previous description, the present application further provides a method for service data verification. FIG. 8 is a method flowchart illustrating an implementation of a method for service data verification, according to
 25 the present application. As shown in FIG. 8, the method can include the following steps.

[0054] S100. Determine service data that is to be verified, and obtain, from stored blockchain data, blockchain copy data associated with the service data that is to be verified, where the blockchain copy data includes data information that is generated
 30 based on fingerprint data of service data to be processed and that is stored in a blockchain, and the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node.

[0055] S200. Calculate, by using a predetermined method, first fingerprint data of the service data that is to be verified, and obtain second fingerprint data in the

blockchain copy data that is corresponding to the service that is to be verified.

[0056] S300. Determine, through comparison, whether the first fingerprint data is the same as the second fingerprint data, and determine that the service data that is to be verified is not modified if the first fingerprint data is the same as the second fingerprint data.

[0057] As such, in the solution provided in the implementation of the present application, a feature that fingerprint data in a blockchain cannot be tampered with can be used to determine, in an associated way, whether data in a database is tampered with, and service data in a service system of a payment institution is tampered with can be effectively and reliably verified, and the possibility that the service data (especially accounting data) is forged is fundamentally eliminated in terms of technology, thereby improving credibility of the accounting data disclosed by the payment institution.

[0058] Based on the method for service data processing described in the previous implementation of the present application, the present application further provides an apparatus for service data processing. FIG. 9 is a schematic diagram illustrating a module structure in an implementation of an apparatus for service data processing, according to the present application. As shown in FIG. 9, the apparatus can include: a fingerprint data generation module 101, configured to obtain service data that is to be processed, and generate, by using a predetermined method, fingerprint data of the service data that is to be processed; and a blockchain data generation module 102, configured to write the fingerprint data to a blockchain corresponding to the service data that is to be processed, and generate blockchain copy data of the service data that is to be processed in the blockchain, where the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node.

[0059] According to the apparatus for service data processing provided in the present application, when service data is stored, fingerprint data of the service data is calculated, and the fingerprint data is written to a blockchain. As such, it is equivalent to that there are different versions of the same document in both an existing database and the blockchain, and the two versions are anchored to each other. Therefore, a feature that the fingerprint data in the blockchain cannot be tampered with can be used to determine, in an associated way, whether data in the database is tampered with.

[0060] FIG. 10 is a schematic diagram illustrating a module structure in another implementation of an apparatus for service data processing, according to the present

application. As shown in FIG. 10, the apparatus can further include: a key element extraction module 103, configured to extract key element data of a predetermined type from the service data that is to be processed.

[0061] Correspondingly, the fingerprint data generation module 101 generates, by using a predetermined method, fingerprint data of the service data that is to be processed, including the following: processing the extracted key element data by using the predetermined method, to generate the fingerprint data of the service data that is to be processed.

[0062] Certainly, as described in the previous method implementation, in some implementations of the apparatus, a process of generating the fingerprint data by the fingerprint data generation module 101 can be set to be unidirectional and irreversible. In addition, the fingerprint data generation module 101 generates, by using a predetermined method, fingerprint data of the service data that is to be processed, including the following: performing hash processing on the service data that is to be processed, and using a hash value generated through the hash processing as the fingerprint data of the service data that is to be processed. Furthermore, in another implementation of the apparatus, the blockchain data generation module 102 can write, by using an asynchronous method, the fingerprint data to the blockchain corresponding to the service data that is to be processed.

[0063] FIG. 11 is a schematic diagram illustrating a module structure in another implementation of an apparatus for service data processing, according to the present application. As shown in FIG. 11, the apparatus can further include: a default processing module 104, configured to determine a default value of the key element data that is absent based on a service type of the service data when at least one piece of the key element data is absent from the service data that is to be processed, and use the default value as a value of the key element data for generating the fingerprint data.

[0064] According to the apparatus for service data processing provided in the present application, a blockchain is used to store a copy of data in a conventional service database. In a processing procedure of an original service system, only fingerprint data corresponding to service data needs to be generated, and the fingerprint data is then stored in a corresponding blockchain to generate blockchain copy data. As such, the processing procedure of the original service system is slightly invaded, and while it is ensured that the conventional database has a high-performance capability, a monitoring effect of the service data is ensured, and

the service data cannot be modified, thereby improving reliability and credibility of the service data.

[0065] The method/apparatus for service data processing and verification, etc. described in the previous implementations can be applied to another service system that includes a payment institution, to use a blockchain to store a copy of service data to improve credibility of the service data and reduce change/invasion to an original service system. FIG. 12 is a schematic structural diagram illustrating an implementation of a service system, according to the present application. The present application provides a service system, and the service system can include an I/O interface and a processing unit.

[0066] The I/O interface is configured to receive service data that is to be processed.

[0067] The processing unit is configured to generate, by using a predetermined method, fingerprint data of the service data that is to be processed; and is further configured to write the service data to an original database, write the fingerprint data to a blockchain database corresponding to the service data that is to be processed, and generate blockchain copy data of the service data that is to be processed in the blockchain, where the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node.

[0068] In an implementation, the original database that stores a service data set of the service system and the blockchain database that stores blockchain can be separated from the service system, and separately store data. In another implementation, any one of the original database and the blockchain database can be included in the service system. For example, in an implementation, the service system can include the original database of the service system, and the blockchain database can be separately disposed in a service server, a server of a third party, or a storage apparatus.

[0069] The processing unit can be further configured to extract key element data of a predetermined type from the service data that is to be processed; and correspondingly, the generating, by using a predetermined method, fingerprint data of the service data that is to be processed includes the following: processing the extracted key element data by using the predetermined method, to generate the fingerprint data of the service data that is to be processed.

[0070] The processing unit can be further configured to obtain, from stored

blockchain data, blockchain copy data associated with service data that is to be verified, calculate, by using a predetermined method, first fingerprint data of the service data that is to be verified, and obtain second fingerprint data in the blockchain copy data that is corresponding to the service data that is to be verified; and can be
5 further configured to determine, through comparison, whether the first fingerprint data is the same as the second fingerprint data, and determine that the service data that is to be verified is not modified if the first fingerprint data is the same as the second fingerprint data.

[0071] According to the method, apparatus, and system for service data
10 processing and verification provided in the present application, a blockchain is used to store a copy of data in a conventional service database. In a processing procedure of an original service system, only fingerprint data corresponding to service data needs to be generated, and the fingerprint data is then stored in a corresponding blockchain to generate blockchain copy data. As such, the processing procedure of the original
15 service system is slightly invaded, and while it is ensured that the conventional database has a high-performance capability, a monitoring effect of the service data is ensured, and the service data cannot be modified, thereby improving reliability and credibility of the service data.

[0072] Although the schematic diagram format of the blockchain, the definition
20 and the extraction method of the key element data, generating the fingerprint data by using MD5, comparing the fingerprint data of the service data in the database and the blockchain to determine whether the service data is tampered with, data definition, acquisition, interaction, calculation, determining, etc. are mentioned in the content of the present application, the present application is not limited to complying with an
25 industry communication standard, a standard data structure, a standard database data processing method or situations described in the implementations of the present application. An implementation solution obtained by using some industry standards, or in a self-defined way, or by slightly modifying the implementation described in the implementations can also achieve an implementation effect the same as, equivalent to,
30 or similar to that achieved in the previous implementations, or an expected implementation effect obtained after transformation. An implementation that is obtained by applying a modified or transformed data acquisition, storage, determining, and processing method can still fall within an optional implementation solution range of the present application.

[0073] In the 1990s, whether a technical improvement is a hardware improvement (for example, an improvement to a circuit structure such as a diode, a transistor, or a switch) or a software improvement (an improvement to a method procedure) can be clearly distinguished. However, as technologies develop, current improvements to many method procedures can be considered as direct improvements to hardware circuit structures. A designer usually programs an improved method procedure into a hardware circuit, to obtain a corresponding hardware circuit structure. Therefore, a method procedure can be improved by using a hardware entity module. For example, a programmable logic device (PLD) (for example, a field programmable gate array (FPGA)) is such an integrated circuit, and a logical function of the PLD is determined by a user through device programming. The designer independently performs programming to "integrate" a digital system to a PLD without requesting a chip manufacturer to design and produce an application-specific integrated circuit chip. In addition, at present, instead of manually manufacturing an integrated circuit chip, this type of programming is mostly implemented by using "logic compiler" software. The logic compiler software is similar to a software compiler used to develop and write a program, and the original code needs to be written in a particular programming language for compilation referred to as a hardware description language (HDL). There are many HDLs, such as the Advanced Boolean Expression Language (ABEL), the Altera Hardware Description Language (AHDL), Confluence, the Cornell University Programming Language (CUPL), HDcAl, the Java Hardware Description Language (JHDL), Lava, Lola, MyHDL, PALASM, and the Ruby Hardware Description Language (RHDL). The very-high-speed integrated circuit hardware description language (VHDL) and Verilog are most commonly used. A person skilled in the art should also understand that a hardware circuit that implements a logical method procedure can be readily obtained once the method procedure is logically programmed by using the several described hardware description languages and is programmed into an integrated circuit.

[0074] A controller can be implemented by using any appropriate method. For example, the controller can be, for example, a microprocessor or a processor, or a computer readable medium that stores computer readable program code (such as software or firmware) that can be executed by the microprocessor or the processor, a logic gate, a switch, an application-specific integrated circuit (ASIC), a programmable logic controller, or an embedded microprocessor. Examples of the controller include

but are not limited to the following microprocessors: ARC 625D, Atmel AT91SAM, Microchip PIC18F26K20, and Silicon Labs C8051F320. The memory controller can also be implemented as a part of control logic of a memory. A person skilled in the art should also know that in addition to implementing the controller by using the computer readable program code, logic programming can be performed on the method steps to allow the controller to implement the same function in forms of the logic gate, the switch, the application-specific integrated circuit, the programmable logic controller, and the embedded microcontroller. Therefore, the controller can be considered as a hardware component, and an apparatus configured to implement various functions in the controller can also be considered as a structure in the hardware component. Or the apparatus configured to implement various functions can even be considered as both a software module implementing the method and a structure in the hardware component.

[0075] The system, apparatus, module, or unit illustrated in the previous implementations can be implemented by using a computer chip or an entity, or can be implemented by using a product having a certain function. A typical implementation device is a computer. The computer can be, for example, a personal computer, a laptop computer, an in-vehicle human-machine interaction device, a cellular phone, a camera phone, a smartphone, a personal digital assistant, a media player, a navigation device, an email device, a game console, a tablet computer, a wearable device, or any combination of these devices.

[0076] Although the method operation steps in the implementations or the flowcharts are provided in the present application, more or fewer operation steps can be included based on conventional or noncreative means. The sequence of the steps listed in the implementations is merely one of numerous step execution sequences, and does not represent the unique execution sequence. For an actual apparatus or end-user device product, the steps can be performed based on the method sequence in the implementations or the accompanying drawings or performed in parallel (for example, an environment of parallel processing or multithreaded processing, or even a distributed data processing environment). Terms "include", "contain", or their any other variant is intended to cover non-exclusive inclusion, so that a process, a method, a product, or a device that includes a series of elements not only includes these elements, but also includes other elements that are not expressly listed, or further includes elements inherent to such a process, method, product, or device. An element

described by "includes a ..." further includes, without more constraints, another same or identical element in the process, method, product, or device that includes the element.

[0077] For ease of description, the previous apparatus is described by dividing the
5 functions into various modules. Certainly, when the present application is implemented, functions of various modules can be implemented in one or more pieces of software and/or hardware, modules that implement the same function can be implemented by using a combination of a plurality of submodules or subunits, etc. The described apparatus implementation is merely an example. For example, the unit
10 division is merely logical function division and can be other division in actual implementation. For example, a plurality of units or components can be combined or integrated into another system, or some features can be ignored or not performed. In addition, the displayed or discussed mutual couplings or direct couplings or communication connections can be implemented by using some interfaces. The
15 indirect couplings or communication connections between the apparatuses or units can be implemented in electronic, mechanical, or other forms.

[0078] A person skilled in the art should also know that in addition to implementing the controller by using the computer readable program code, logic programming can be performed on the method steps to allow the controller to
20 implement the same function in forms of the logic gate, the switch, the application-specific integrated circuit, the programmable logic controller, and the embedded microcontroller. Therefore, the controller can be considered as a hardware component, and an apparatus configured to implement various functions in the controller can also be considered as a structure in the hardware component. Or the
25 apparatus configured to implement various functions can even be considered as both a software module implementing the method and a structure in the hardware component.

[0079] The present disclosure is described with reference to the flowcharts and/or block diagrams of the method, the device (system), and the computer program product
30 in the implementations of the present disclosure. It should be understood that computer program instructions can be used to implement each process and/or each block in the flowcharts and/or the block diagrams and a combination of a process and/or a block in the flowcharts and/or the block diagrams. These computer program instructions can be provided for a general-purpose computer, a dedicated computer, an

embedded processor, or a processor of another programmable data processing device to generate a machine, so that an apparatus for implementing a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams can be generated by using the instructions executed by the computer or the processor of the another programmable data processing device.

[0080] These computer program instructions can be stored in a computer readable memory that can instruct a computer or another programmable data processing device to work in a specific way, so that the instructions stored in the computer readable memory generate an artifact that includes an instruction apparatus. The instruction apparatus implements a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0081] These computer program instructions can be loaded onto a computer or another programmable data processing device, so that a series of operation steps are performed on the computer or the another programmable device, thereby generating computer-implemented processing. Therefore, the instructions executed on the computer or the another programmable device provide steps for implementing a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0082] In a typical configuration, a computing device includes one or more processors (CPU), one or more input/output interfaces, one or more network interfaces, and one or more memories.

[0083] The memory can include a non-persistent memory, a random access memory (RAM), and/or a nonvolatile memory in a computer readable medium, for example, a read-only memory (ROM) or a flash memory (flash RAM). The memory is an example of the computer readable medium.

[0084] The computer readable medium includes persistent, non-persistent, movable, and unmovable media that can store information by using any method or technology. The information can be a computer readable instruction, a data structure, a program module, or other data. Examples of the computer storage medium include but are not limited to a phase-change random access memory (PRAM), a static random access memory (SRAM), a dynamic random access memory (DRAM), another type of random access memory (RAM), a read-only memory (ROM), an electrically erasable programmable read-only memory (EEPROM), a flash memory or another memory technology, a compact disc read-only memory (CD-ROM), a digital

versatile disc (DVD) or another optical storage, a cassette magnetic tape, a magnetic tape/magnetic disk storage, another magnetic storage device, or any other non-transmission medium. The computer storage medium can be used to store information accessible by the computing device. Based on the definition in the present specification, the computer readable medium does not include transitory computer readable media (transitory media) such as a modulated data signal and carrier.

[0085] A person skilled in the art should understand that an implementation of the present application can be provided as a method, a system, or a computer program product. Therefore, the present application can use a form of hardware only implementations, software only implementations, or implementations with a combination of software and hardware. Moreover, the present application can use a form of a computer program product that is implemented on one or more computer-usable storage media (including but not limited to a disk memory, a CD-ROM, an optical memory, etc.) that include computer-usable program code.

[0086] The present application can be described in the general context of computer-executable instructions, for example, a program module. Generally, the program module includes a routine, a program, an object, a component, a data structure, etc. executing a specific task or implementing a specific abstract data type. The present application can alternatively be practiced in distributed computing environments where tasks are performed by remote processing devices that are connected through a communications network. In the distributed computing environment, the program module can be located in both local and remote computer storage media including storage devices.

[0087] The implementations of the present specification are described in a progressive way. For same or similar parts of the implementations, references can be made to the implementations. Each implementation focuses on a difference from the other implementations. Especially, a system implementation is basically similar to the method implementations, and therefore is described briefly. For related parts, references can be made to partial descriptions in the method implementations.

[0088] The previous descriptions are merely implementations of the present application, and are not intended to limit the present application. For a person skilled in the art, the present application can have various changes and variations. Any modifications, equivalent substitutions, and improvements made within the spirit and the principle of the present application shall fall within the scope of the claims of the

present application.

CLAIMS

What is claimed is:

1. A method for service data processing, wherein the method comprises:
 obtaining service data that is to be processed, and generating, by using a
 5 predetermined method, fingerprint data of the service data that is to be processed; and
 writing the fingerprint data to a blockchain corresponding to the service data that
 is to be processed, and generating blockchain copy data of the service data that is to
 be processed in the blockchain, wherein the blockchain copy data stores fingerprint
 data in blockchain copy data of a previous adjacent node.
- 10 2. The method for service data processing according to claim 1, wherein after the
 obtaining service data that is to be processed, the method further comprises:
 extracting key element data of a predetermined type from the service data that is
 to be processed; and
 correspondingly, the generating, by using a predetermined method, fingerprint
 15 data of the service data that is to be processed comprises: processing the extracted key
 element data by using the predetermined method, to generate the fingerprint data of
 the service data that is to be processed.
3. The method for service data processing according to claim 1 or 2, wherein a
 process of generating the fingerprint data is set to be unidirectional and irreversible.
- 20 4. The method for service data processing according to claim 1, wherein the
 generating, by using a predetermined method, fingerprint data of the service data that
 is to be processed comprises:
 performing hash processing on the service data that is to be processed, and using
 a hash value generated through the hash processing as the fingerprint data of the
 25 service data that is to be processed.
5. The method for service data processing according to claim 2, wherein when at
 least one piece of the key element data is absent from the service data that is to be
 processed, the method comprises:
 determining a default value of the key element data that is absent based on a
 30 service type of the service data, and using the default value as a value of the key
 element data for generating the fingerprint data.
6. The method for service data processing according to claim 1, wherein the

writing the fingerprint data to a blockchain corresponding to the service data that is to be processed comprises:

writing, by using an asynchronous method, the fingerprint data to the blockchain corresponding to the service data that is to be processed.

5 7. A method for service data verification, wherein the method comprises:

determining service data that is to be verified, and obtaining, from stored blockchain data, blockchain copy data associated with the service data that is to be verified, wherein the blockchain copy data comprises data information that is generated based on fingerprint data of service data to be processed and that is stored
10 in a blockchain, and the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node;

calculating, by using a predetermined method, first fingerprint data of the service data that is to be verified, and obtaining second fingerprint data in the blockchain copy data that is corresponding to the service data that is to be verified; and

15 determining, through comparison, whether the first fingerprint data is the same as the second fingerprint data, and determining that the service data that is to be verified is not modified if the first fingerprint data is the same as the second fingerprint data.

8. An apparatus for service data processing, wherein the apparatus comprises:

20 a fingerprint data generation module, configured to obtain service data that is to be processed, and generate, by using a predetermined method, fingerprint data of the service data that is to be processed; and

a blockchain data generation module, configured to write the fingerprint data to a blockchain corresponding to the service data that is to be processed, and generate
25 blockchain copy data of the service data that is to be processed in the blockchain, wherein the blockchain copy data stores fingerprint data in blockchain copy data of a previous adjacent node.

9. The apparatus for service data processing according to claim 8, wherein the apparatus further comprises:

30 a key element extraction module, configured to extract key element data of a predetermined type from the service data that is to be processed; and

correspondingly, the fingerprint data generation module generates, by using a predetermined method, fingerprint data of the service data that is to be processed, comprising: processing the extracted key element data by using the predetermined

method, to generate the fingerprint data of the service data that is to be processed.

10. The apparatus for service data processing according to claim 8 or 9, wherein a process of generating the fingerprint data by the fingerprint data generation module is set to be unidirectional and irreversible.

5 11. The apparatus for service data processing according to claim 8, wherein the fingerprint data generation module generates, by using a predetermined method, fingerprint data of the service data that is to be processed, comprising:

performing hash processing on the service data that is to be processed, and using a hash value generated through the hash processing as the fingerprint data of the
10 service data that is to be processed.

12. The apparatus for service data processing according to claim 8, wherein the blockchain data generation module writes, by using an asynchronous method, the fingerprint data to the blockchain corresponding to the service data that is to be processed.

15 13. The apparatus for service data processing according to claim 9, wherein the apparatus further comprises:

a default processing module, configured to determine a default value of the key element data that is absent based on a service type of the service data when at least one piece of the key element data is absent from the service data that is to be
20 processed, and use the default value as a value of the key element data for generating the fingerprint data.

14. A service system, comprising an I/O interface and a processing unit, wherein the I/O interface is configured to receive service data that is to be processed; and the processing unit is configured to generate, by using a predetermined method,
25 fingerprint data of the service data that is to be processed; and is further configured to write the service data to an original database, write the fingerprint data to a blockchain database corresponding to the service data that is to be processed, and generate blockchain copy data of the service data that is to be processed in the blockchain, wherein the blockchain copy data stores fingerprint data in blockchain
30 copy data of a previous adjacent node.

15. The service system according to claim 14, wherein the processing unit is further configured to:

extract key element data of a predetermined type from the service data that is to be processed; and correspondingly, the generating, by using a predetermined method,

fingerprint data of the service data that is to be processed comprises: processing the extracted key element data by using the predetermined method, to generate the fingerprint data of the service data that is to be processed.

16. The service system according to claim 14 or 15, wherein the processing unit
5 is further configured to:

obtain, from stored blockchain data, blockchain copy data associated with service data that is to be verified, calculate, by using a predetermined method, first fingerprint data of the service data that is to be verified, and obtain second fingerprint data in the blockchain copy data that is corresponding to the service data that is to be
10 verified; and the processing unit is further configured to determine, through comparison, whether the first fingerprint data is the same as the second fingerprint data, and determine that the service data that is to be verified is not modified if the first fingerprint data is the same as the second fingerprint data.