

Description

The invention relates to a lamp/reflector assembly comprising

- a reflector having a concave, reflecting surface, an optical axis with an optical centre, a luminous window and a lamp opening,
- an electric lamp having a lamp vessel which is sealed in a vacuumtight manner, in which an electric element is positioned and which is connected to a lamp cap provided with contacts, current conductors connecting the electric element to respective contacts of the lamp cap, while the optical centre of the reflector coincides with the electric element,
- a convex, spherically curved mounting surface outside the reflector, aligned relative to the lamp opening in the reflector, which mounting surface has a centre of curvature which substantially coincides with the optical centre of the reflector,

the lamp being connected to the mounting surface and projecting through the lamp opening.

The invention also relates to an electric lamp suitable for use in this assembly.

Such an assembly is known from FR-2 649 185 A1.

The known assembly is designed for use as a headlamp in motor vehicles. The assembly in addition comprises an annular lamp carrier which has a concave, spherical surface and facing away therefrom a flat surface. The lamp carrier is immovably fastened against the mounting surface with its spherical surface.

The electric lamp comprises a lamp cap having a flat circumferential collar. The lamp is held in the annular lamp carrier with its flat collar against the flat surface.

The known assembly has for its object to render it possible for the electric element to be arranged coaxially with the reflector inside the latter while its centre coincides with the optical centre of the reflector. For realizing such an arrangement, the electric element must be aligned when a lamp is inserted and whenever a lamp is replaced by a new one. If the electric element in the lamp has a tilted position, the lamp carrier can be loosed from the mounting surface, after which the lamp carrier can be shifted over the mounting surface so as to be tilted relative to the optical axis. The electric element can thereby be brought into a position parallel to the optical axis. Subsequently, the collar of the lamp cap can be shifted in two directions over the flat surface in order to let the electric element cover the optical centre.

It is often not possible for the user to carry out these alignment steps since they require a high degree of expertness and/or special equipment.

For practical applications, the known assembly

has the drawback that a non-expert user is capable of making a greater positioning error by the lateral displacement possibility of the lamp alone, with the flat collar moving over the flat surface of the lamp carrier, than if the lamp carrier were to be just large enough to accommodate the lamp cap. For practical purposes the construction of the known assembly is equivalent to that of a reflector having a fixed lamp opening in which a lamp is laterally displaceable. The construction of the known assembly is accordingly of a totally insufficient accuracy for use in an optical system.

A lamp opening which is just large enough to accommodate the lamp cap does not offer a sufficiently accurate positioning of the electric element in the reflector either. This is caused by the spread in the dimensions of the lamp opening and of the lamp cap which occurs in mass manufacture.

DE-1 472 529-A discloses an assembly in which the reflector has a lamp opening bounded by a conical wall and the lamp cap has a conical surface, so that the position of the electric element inside the reflector can be three-dimensionally determined.

This latter construction, however, is not sufficiently accurate for various applications because the lamp opening and the lamp cap cannot be manufactured to sufficiently narrow tolerances. Moreover, the accuracy of the position of the electric element along the optical axis is greatest in this case when the cones have the greatest possible apex angle, but the position transverse to the axis is most accurately determined when the cones have a small apex angle. So it is only possible to choose an apex angle which is a compromise. Aspects which then come into play are how securely the lamp cap is pressed into the lamp opening and to what extent a skew position of the lamp cap is prevented.

US-4 061 912 discloses an assembly which is similar to the assembly described in the opening paragraph. In this case, however, the centre of curvature of the mounting surface does not lie in the optical centre of the reflector but in its lamp opening, and the optical centre does not coincide with the electric element. This known assembly is designed for use in a luminaire for theatre illumination. It envisages to provide a possibility of changing the position of the electric element, an incandescent body, in the reflector during lamp operation so as to change the shape of the generated light beam. To this end, a lampholder in which the lamp cap of the lamp is accommodated is fastened to the mounting surface with lateral shifting possibility. This renders the same displacement of the incandescent body within the reflector possible as would be possible if the lamp were suspended in a ball joint in the lamp opening. Moreover, the lampholder may be brought to a varying distance from the mounting surface, so that the lamp can project more or less deeply into the reflector. The adjustment possibility of the lampholder is necessary not only for pro-

ducing light beams of various shapes, but also because the incandescent body assumes a random position relative to the lamp cap, and thus relative to the lampholder. The advantage of this construction with the centre of curvature in the lamp opening is that major lateral displacements of the lampholder, and thus of the lamp cap and of the incandescent body, are possible without the lamp opening having to be substantially greater than the diameter of the lamp vessel.

An adjustment possibility for the location of the electric element is only possible in those applications in which an exact position of the electric element is of no importance for obtaining a light beam of a certain kind.

For many applications in optical systems, however, it is necessary for the electric element of a lamp to take up a predetermined position inside the reflector with a high accuracy. It is often not possible then to allow the user to find this location because of the high skill and/or special aids necessary for this. The electric element in these cases must take up a predetermined position relative to a lamp cap, and the lamp cap must automatically assume a predetermined position relative to the reflector, so that the electric element will be in the correct position inside the reflector when the lamp is inserted.

The invention has for its object to provide a lamp/reflector assembly of the kind described in the opening paragraph which renders possible a high accuracy of the position of the electric element inside the reflector and which nevertheless is of a simple construction. The invention also has for its object to provide an electric lamp suitable for use in this assembly.

According to the invention, this object is achieved in that

- the lamp cap has a first, a second and a third projection which are tangent to an imaginary sphere whose centre of curvature coincides with the electric element, and
- the said projections rest against the mounting surface.

In the lamp of the assembly according to the invention, the position of the electric element is accurately determined relative to the projections at the lamp cap in that the centre of curvature of a sphere which these projections touch coincides with the electric element. The lamp cap and the lamp vessel may be placed in an alignment unit during lamp manufacture with the projections of the lamp cap resting against and touching a portion of a sphere. The lamp vessel is then moved until the electric element assumes the predetermined position in the centre of curvature of the sphere, after which the lamp vessel and lamp cap are joined together, for example, with lamp cement.

The spherical surface in the alignment unit es-

entially has the same radius of curvature as the mounting surface which is present in the assembly, aligned relative to the lamp opening.

During mounting of the lamp in the reflector, the projections need only be applied against the mounting surface in order to ensure that the electric element will be in the correct position inside the reflector.

This correct position, therefore, is realised in each of a large number of positions of the lamp cap against the mounting surface. The force with which the lamp cap is pressed against this surface is of no importance in this case.

In a favourable embodiment, the lamp cap has a ceramic body. Especially in this embodiment, it is very favourable for the lamp cap to have projections which touch an imaginary sphere. Inaccuracies in the shape of the lamp cap, which was obtained through baking, are eliminated by this. The lamp is highly insensitive to spread in the shape and dimensions of these projections. In fact, the location of the centre of the sphere which these projections touch relative to the lamp cap is determined separately for each individual lamp cap during the assembly of lamp cap and lamp vessel.

The mounting surface may be an external surface of the reflector. Alternatively, however, for example if the distance of the lamp cap to the electric element in the case of a comparatively long lamp is much greater than the distance from the optical centre of the reflector to its lamp opening, the mounting surface may be present at a reflector holder in which the reflector is securely fixed.

The surface area of the mounting surface depends on the spread in the possible positions of the lamp cap relative to the reflector which is deemed desirable or admissible in a given application. The mounting surface may be the surface of a spherical zone or portions thereof whose relative positions correspond to the relative positions of the projections of the lamp cap. Such portions of a segment of a spherical surface may be used if the rotation possibility of the lamp cap about an own axis is limited. The surface of a segment of a sphere is present, for example, in a bending-edge where a conical or cylindrical portion of a reflector holder is bent to form a transition to an adjoining conical or flat portion.

The electric element may be, for example, an incandescent body or a pair of electrodes with a discharge path in an ionizable gas between them. The gas may contain metal vapour and/or metal halides. The lamp vessel may have an exhaust tube tip where the lamp vessel, after being provided with its filling, has been sealed off. The lamp vessel is possibly surrounded by an outer envelope.

If the lamp vessel has a exhaust tube tip and contains metal vapour and/or metal halides in its gas filling, it is important for the exhaust tube tip to be above the discharge path during lamp operation in order to

avoid the exhaust tube tip assuming a comparatively low temperature so that metal vapour and/or metal halides condense there and are thus removed from the discharge.

This may be easily realised in a lamp whose lamp cap has an unround circumference portion which co-operates with a lateral stop connected to the reflector.

In a favourable embodiment, the reflector holder has connected to it a lampholder which has bent tongues as lateral stops for the lamp cap. The lampholder may also comprise means for holding the lamp fixed, for example, a spring having a free end, which spring grips across the lamp cap and is enclosed with its free end in a recess in the lampholder.

In a favourable embodiment, the reflector holder has a first portion and a second portion fastened thereto which keep enclosed between them an edge of the reflector.

The lamp/reflector assembly may be used, for example, in LCD projection TV sets and as a motor vehicle headlamp. The optical centre need not necessarily lie on the optical axis of the reflector or be a focus of the reflector. The optical centre may also be the centre from where light beams must leave the light source in a certain application.

Embodiments of the lamp/reflector assembly and of the lamp according to the invention are shown in the drawings, in which

Fig. 1 shows an embodiment of the assembly in side elevation,

Fig. 2 is a longitudinal section of the reflector holder of Fig. 1,

Fig. 3a shows the lampholder of Fig. 1 taken on the line IIIa,

Fig. 3b shows the lampholder taken on the line IIIb in Fig. 3a,

Fig. 4 shows the lamp of Fig. 1 taken on the line IV,

Fig. 5 is an elevation of the lamp cap of Fig. 4 taken on the line V, and

Fig. 6 shows an alternative embodiment of the lamp.

In Fig. 1, the lamp/reflector assembly comprises a reflector 1 with a concave reflecting surface 2, an optical axis 3 with an optical centre 4, a luminous window 5, and a lamp opening 6. The reflecting surface 2 is paraboloidally curved, but it may alternatively be, for example, spherically or ellipsoidally curved.

An electric lamp 10 (see also Fig. 4) has a lamp vessel 11 which is sealed in a vacuumtight manner, in which an electric element 12 is arranged, and which is connected to a lamp cap 13 provided with contacts 14. Current conductors 15, 16 connect the electric element 12 to respective contacts 14 of the lamp cap 13. The electric element 12 in the Figure is a pair of electrodes with a discharge path in an ionizable gas between them, for example, in mercury, rare gas, and metal halide.

The assembly furthermore has a convex, spherically curved mounting surface 30 outside the reflector 1 aligned relative to the lamp opening 6 in the reflector 1. The lamp 10 is connected to the mounting surface 30, projects through the lamp opening 6, and has the electric element 12 inside the reflector 1.

The mounting surface 30 has a centre of curvature 31 which essentially coincides with the optical centre on the axis of the reflector 1.

The lamp cap 13 has a first, a second, and a third projection 17, 18, 19, respectively, which are tangent to an imaginary sphere whose centre of curvature 20 coincides with the electric element 12. The first, the second, and the third projection 17, 18, 19, respectively, rest with substantially flat surfaces directly against the mounting surface 30, and the optical centre 4 of the reflecting surface 2 coincides with the electric element 12.

In Fig. 1, the mounting surface 30 (see also Fig. 2) is present at a reflector holder 32 in which the reflector 1 is securely fixed. The drawn reflector holder has a first and a second portion 38, 39, respectively, which keep an edge 7 at the reflector 1 enclosed between them. In the embodiment drawn, the first portion 38 for this purpose has stamped-out tongues 40 which are distributed over its circumference, are pressed inwards, and which press against the edge 7, and it is tightened against the second portion 39 with screws 41, thus clamping in the edge 7.

A lampholder 34 for the lamp 10 is fastened to the first portion 38 of the holder 32.

It is apparent from Fig. 2 that the mounting surface 30 is a bent rim at the first portion 38 of the reflector holder 32. In this embodiment, the said mounting surface has the shape of a surface of a segment of a sphere. The first portion 38 of the holder 32 comprises a transition from a cylindrical portion 42 to a flat end portion 43 in the bending rim 30. The first portion 38 has dimples 44 which press laterally against the edge 7 of the reflector 1 in order to centre this reflector. The lampholder 34 is mounted against a flat portion 45 in Fig. 1.

In Fig. 3, the lampholder 34 has a lateral stop 33 which is connected to the reflector via the reflector holder 32. The stop 33 comprises two bent tongues 33a at substantially equal distances from the optical axis 3 and a bent tongue 33b at a smaller distance from this optical axis. The stop 33 restricts the rotation possibility of the lamp in the holder in order to keep an exhaust tube tip at the lamp vessel in a desired position relative to the electric element.

The lampholder 34 has fixation means 35, 36, 37 for holding the lamp fixed. In the embodiment drawn, the lampholder 34 has a spring 35 which is U-shaped, grips across the lamp cap 13 (Fig. 1) and has a free end 36 which is enclosed in a recess 37 in the lampholder 34.

The mounting surface 30 projects through the

lampholder 34 when the latter is mounted to the reflector holder 32 (Fig. 1).

In Fig. 4, the lamp has a lamp cap 13, for example of ceramic material, with projections 17, 18, 19 which in Fig. 1 touch the mounting surface 30. The lamp vessel 11 is enveloped in a closed outer bulb 22. The lamp cap 13 has an unround circumference portion 31, i.e. an edge with a flat side 23 (Fig. 5). The lamp vessel 11 has an exhaust tube tip 24.

When the assembly has the position shown in Fig. 1, the exhaust tube tip 24 is above the electric element 12 since, as is apparent from Fig. 1, the bent tongue 33b which cooperates with the flat side 23 at the lamp cap 13 is below the optical axis 3, diametrically opposite the exhaust tube tip 24.

The lamp of Fig. 6 has a similar lamp vessel 11 to those in Figs. 1 and 4, but it has no outer bulb. The reference numerals referring to the lamp cap 53 are 40 higher than those in Figs. 1 and 4.

In Figs. 4 and 6, the electric element 12 is positioned relative to the centre of curvature 20 of the imaginary sphere touching the ends of the projections 17-19 or 57-59 during assembly of the lamp vessel 11 with the lamp cap 13 or 53. This centre of curvature coincides with the electric element 12.

During this assembly, the projections come to rest against the mounting surface 30 (Fig. 1) which is part of the outer surface of a sphere whose centre of curvature 31 essentially coincides with the optical centre 4 of the reflector 1. Since the electric element is aligned relative to the projections, and the mounting surface relative to the optical centre, it is achieved that the electric element will be in a predetermined position, in the optical centre, when the projections rest against the mounting surface. Thanks to the imaginary sphere and the outer surface of the sphere forming the mounting surface, the lamp can assume positions which are tilted relative to the optical axis of the reflector, while nevertheless the optical centre of the reflector still coincides with the electric element.

As a result, the lamp may be mounted by a non-expert, without aids, in the correct position. The stop necessitates, if applicable, a correct rotational position, if an exhaust tube tip is present. The fixation means keep the lamp in its position, also when the optical axis is not vertically directed, with the luminous window facing downwards.

Claims

1. A lamp/reflector assembly comprising

- a reflector (1) having a concave, reflecting surface (2) with an optical axis (3), an optical centre (4), a luminous window (5) and a lamp opening (6),
- an electric lamp (10) having a lamp vessel (11) which is closed in a vacuumtight man-

ner, in which an electric element (12) is positioned and which is connected to a lamp cap (13) provided with contacts (14), current conductors (15, 16) connecting the electric element (12) to respective contacts (14) of the lamp cap (13), while the optical centre (4) of the reflecting surface (2) coincides with the electric element (12),

- a convex, spherically curved mounting surface (30) outside the reflector (1), aligned relative to the lamp opening (6) in the reflector (1), which mounting surface (30) has a centre of curvature (31) which substantially coincides with the optical centre (4) of the reflector (1), the lamp (10) being connected to the mounting surface (30) and projecting through the lamp opening (6), characterized in that
- the lamp cap (13) has a first, a second and a third projection (17, 18, 19, respectively) which are tangent to an imaginary sphere whose centre of curvature (20) coincides with the electric element (12), and
- the said projections (17, 18, 19) rest against the mounting surface (30).

2. A lamp/reflector assembly as claimed in Claim 1, characterized in that the mounting surface (30) is present at a reflector holder (32) in which the reflector (1) is securely fixed.

3. A lamp/reflector assembly as claimed in Claim 2, characterized in that the reflector holder (32) has a first and a second portion (33, 34, respectively) which keep an edge (7) at the reflector (1) enclosed between them.

4. A lamp/reflector assembly as claimed in Claim 2, characterized in that the mounting surface (30) is the surface of a segment of a sphere.

5. A lamp/reflector assembly as claimed in Claim 4, characterized in that the mounting surface (30) is a bending-edge in the reflector holder (32).

6. A lamp/reflector assembly as claimed in Claim 1 or 2, characterized in that the lamp cap (13) has an unround circumference portion (21) which cooperates with a lateral stop (33) connected to the reflector (1).

7. A lamp/reflector assembly as claimed in Claim 2, characterized in that a lampholder (34) is connected to the reflector holder (32).

8. A lamp/reflector assembly as claimed in Claim 7, characterized in that the lampholder (34) has

lampholder 34 when the latter is mounted to the reflector holder 32 (Fig. 1).

In Fig. 4, the lamp has a lamp cap 13, for example of ceramic material, with projections 17, 18, 19 which in Fig. 1 touch the mounting surface 30. The lamp vessel 11 is enveloped in a closed outer bulb 22. The lamp cap 13 has an unround circumference portion 31, i.e. an edge with a flat side 23 (Fig. 5). The lamp vessel 11 has an exhaust tube tip 24.

When the assembly has the position shown in Fig. 1, the exhaust tube tip 24 is above the electric element 12 since, as is apparent from Fig. 1, the bent tongue 33b which cooperates with the flat side 23 at the lamp cap 13 is below the optical axis 3, diametrically opposite the exhaust tube tip 24.

The lamp of Fig. 6 has a similar lamp vessel 11 to those in Figs. 1 and 4, but it has no outer bulb. The reference numerals referring to the lamp cap 53 are 40 higher than those in Figs. 1 and 4.

In Figs. 4 and 6, the electric element 12 is positioned relative to the centre of curvature 20 of the imaginary sphere touching the ends of the projections 17-19 or 57-59 during assembly of the lamp vessel 11 with the lamp cap 13 or 53. This centre of curvature coincides with the electric element 12.

During this assembly, the projections come to rest against the mounting surface 30 (Fig. 1) which is part of the outer surface of a sphere whose centre of curvature 31 essentially coincides with the optical centre 4 of the reflector 1. Since the electric element is aligned relative to the projections, and the mounting surface relative to the optical centre, it is achieved that the electric element will be in a predetermined position, in the optical centre, when the projections rest against the mounting surface. Thanks to the imaginary sphere and the outer surface of the sphere forming the mounting surface, the lamp can assume positions which are tilted relative to the optical axis of the reflector, while nevertheless the optical centre of the reflector still coincides with the electric element.

As a result, the lamp may be mounted by a non-expert, without aids, in the correct position. The stop necessitates, if applicable, a correct rotational position, if an exhaust tube tip is present. The fixation means keep the lamp in its position, also when the optical axis is not vertically directed, with the luminous window facing downwards.

Claims

1. A lamp/reflector assembly comprising

- a reflector (1) having a concave, reflecting surface (2) with an optical axis (3), an optical centre (4), a luminous window (5) and a lamp opening (6),
- an electric lamp (10) having a lamp vessel (11) which is closed in a vacuumtight man-

ner, in which an electric element (12) is positioned and which is connected to a lamp cap (13) provided with contacts (14), current conductors (15, 16) connecting the electric element (12) to respective contacts (14) of the lamp cap (13), while the optical centre (4) of the reflecting surface (2) coincides with the electric element (12),

- a convex, spherically curved mounting surface (30) outside the reflector (1), aligned relative to the lamp opening (6) in the reflector (1), which mounting surface (30) has a centre of curvature (31) which substantially coincides with the optical centre (4) of the reflector (1), the lamp (10) being connected to the mounting surface (30) and projecting through the lamp opening (6), characterized in that
- the lamp cap (13) has a first, a second and a third projection (17, 18, 19, respectively) which are tangent to an imaginary sphere whose centre of curvature (20) coincides with the electric element (12), and
- the said projections (17, 18, 19) rest against the mounting surface (30).

2. A lamp/reflector assembly as claimed in Claim 1, characterized in that the mounting surface (30) is present at a reflector holder (32) in which the reflector (1) is securely fixed.

3. A lamp/reflector assembly as claimed in Claim 2, characterized in that the reflector holder (32) has a first and a second portion (33, 34, respectively) which keep an edge (7) at the reflector (1) enclosed between them.

4. A lamp/reflector assembly as claimed in Claim 2, characterized in that the mounting surface (30) is the surface of a segment of a sphere.

5. A lamp/reflector assembly as claimed in Claim 4, characterized in that the mounting surface (30) is a bending-edge in the reflector holder (32).

6. A lamp/reflector assembly as claimed in Claim 1 or 2, characterized in that the lamp cap (13) has an unround circumference portion (21) which cooperates with a lateral stop (33) connected to the reflector (1).

7. A lamp/reflector assembly as claimed in Claim 2, characterized in that a lampholder (34) is connected to the reflector holder (32).

8. A lamp/reflector assembly as claimed in Claim 7, characterized in that the lampholder (34) has



bent tongues to form a lateral stop for the lamp cap (13).

9. A lamp/reflector assembly as claimed in Claim 7, characterized in that the lampholder (34) comprises means (35, 36, 37) for keeping the lamp (10) fixed.

10. A lamp/reflector assembly as claimed in Claim 9, characterized in that a spring (35) is present which grips around the lamp cap (13) and which is enclosed with a free end (36) thereof in a recess (37) in the lampholder (34).

11. An electric lamp for use in the assembly as claimed in Claim 1, characterized in that the lamp has a lamp vessel (11) which is closed in a vacuumtight manner, in which an electric element (12) is positioned, and which is connected to a lamp cap (13) provided with contacts (14), current conductors (15, 16) connecting the electric element (12) to respective contacts (14), and

the lamp cap (13) is a ceramic body provided with a first, a second, and a third projection (17, 18, 19) which touch an imaginary sphere whose centre of curvature (20) coincides with the electric element (12).

12. An electric lamp as claimed in Claim 11, characterized in that the lamp cap (13) has an unround circumference portion (21).

13. An electric lamp as claimed in Claim 12, characterized in that the unround circumference portion (21) has a flat edge (23), and in that the lamp vessel has an exhaust tube tip (24) which is aligned relative to the flat edge (23).

Patentansprüche

1. Lampen/Reflektoreinheit mit

- einem Reflektor (1) mit einer konkaven Reflexionsfläche (2) mit einer optischen Achse (3) einer optischen Mitte (4), einem Lichtfenster (5) und einer Lampenöffnung (6),
- einer elektrischen Lampe (10) mit einem vakuumdicht geschlossenen Lampenkolben (11), in dem ein elektrisches Element (12) positioniert ist, und der mit einem Lampensockel (13) mit Kontakten (14) verbunden ist, wobei Stromzuführungsleiter (15, 16) zum Verbinden des elektrischen Elements (12) jeweils mit Kontakten (14) des Lampensockels (13) verbunden sind, während die optische Mitte (4) der Reflexions-

fläche (2) mit dem elektrischen Element (12) zusammenfällt,

- einer konvexen, sphärisch gekrümmten Montagefläche (30) außerhalb des Reflektors (1), die in bezug auf die Lampenöffnung (6) im Reflektor (1) ausgerichtet ist, wobei die Montagefläche (30) eine Krümmungsmitte (31) aufweist, die im wesentlichen mit der optischen Mitte (4) des Reflektors (1) zusammenfällt, wobei die Lampe (10) mit der Montagefläche (30) verbunden ist und durch die Lampenöffnung (6) herausragt,

dadurch gekennzeichnet, daß

- der Lampensockel (13) einen ersten, einen zweiten und einen dritten Vorsprung (17, 18 bzw. 19) enthält, die eine imaginäre Kugel tangieren, deren Krümmungsmitte (20) mit dem elektrischen Element (12) zusammenfällt, und
- die Vorsprünge (17, 18, 19) an der Montagefläche (30) liegen.

2. Lampen/Reflektoreinheit nach Anspruch 1, dadurch gekennzeichnet, daß die Montagefläche (30) sich auf einer Reflektorfassung (32) befindet, in der der Reflektor (1) gut befestigt ist.

3. Lampen/Reflektoreinheit nach Anspruch 2, dadurch gekennzeichnet, daß die Reflektorfassung (32) einen ersten und einen zweiten Anteil (33, bzw. 34) enthält, die zwischen ihnen einen Rand (7) am Reflektor (1) eingeschlossen halten.

4. Lampen/Reflektoreinheit nach Anspruch 2, dadurch gekennzeichnet, daß die Montagefläche (30) die Oberfläche eines Segments einer Kugel ist.

5. Lampen/Reflektoreinheit nach Anspruch 4, dadurch gekennzeichnet, daß die Montagefläche (30) ein Biegungsrand in der Reflektorfassung (32) ist.

6. Lampen/Reflektoreinheit nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß der Lampensockel (13) einen unround Umfangsanteil (21) enthält, der mit einem Seitenanschlag (33) zusammenarbeitet, der mit dem Reflektor (1) verbunden ist.

7. Lampen/Reflektoreinheit nach Anspruch 2, dadurch gekennzeichnet, daß das eine Lampenfassung (34) mit der Reflektorfassung (32) verbunden ist.

8. Lampen/Reflektoreinheit nach Anspruch 7, dadurch gekennzeichnet, daß die Lampenfassung (34) gebogene Zungen zur Bildung eines Seiten-



anschlags für den Lampensockel (13) enthält.

9. Lampen/Reflektoreinheit nach Anspruch 7, dadurch gekennzeichnet, daß die Lampenfassung (34) Mittel (35, 36, 37) zum Festhalten der Lampe (10) enthält. 5
10. Lampen/Reflektoreinheit nach Anspruch 9, dadurch gekennzeichnet, daß eine Feder (35) vorgesehen ist, die um den Lampensockel (13) greift und die mit einem freien Ende (36) in eine Ausnehmung (37) in der Lampenfassung (34) eingeschlossen ist. 10
11. Elektrische Lampe zur Verwendung in der Einheit nach Anspruch 1, dadurch gekennzeichnet, daß die Lampe einen vakuum geschlossenen Lampenkolben (11) enthält, in dem ein elektrisches Element (12) positioniert ist und mit einem Lampensockel (13) mit den Kontakten (14) verbunden ist, wobei Stromzuführungsleiter (15, 16) das elektrische Element jeweils mit den Kontakten (14) verbinden, und 15
der Lampensockel (13) ein Keramikkörper mit einem ersten, einem zweiten und einem dritten Vorsprung (17, 18, 19) ist, die eine imaginäre Kugel tangieren, deren Krümmungsmitte (20) mit dem elektrischen Element 12 zusammenfällt. 20 25
12. Elektrische Lampe nach Anspruch 11, dadurch gekennzeichnet, daß der Lampensockel (13) einen unrunder Umfangaanteil (21) enthält. 30
13. Elektrische Lampe nach Anspruch 12, dadurch gekennzeichnet, daß der unrunde Umfangaanteil (21) einen flachen Rand (23) enthält, und daß der Lampenkolben eine Pumprohrspitze (24) aufweist, die in bezug auf den flachen Rand (23) ausgerichtet ist. 35 40

Revendications

1. Ensemble de lampe et de réflecteur comportant 45
 - un réflecteur (1) présentant une surface de réfléchissement concave (2) avec un axe optique (3), un centre optique (4), une fenêtre de sortie de lumière (5) et une ouverture de lampe (6),
 - une lampe électrique (10) présentant un récipient de lampe (11) scellé de manière étanche au vide dans lequel est disposé un élément électrique (12) et qui est relié à un culot de lampe (13) muni de contacts (14), des conducteurs de courant (15, 16) reliant l'élément électrique (12) à de propres contacts (14) du culot de lampe (13), alors que le centre optique (4) de la surface de 50

réfléchissement (2) coïncide avec l'élément électrique (12).

- une surface de montage convexe et courbée sphériquement (30) située à l'extérieur du réflecteur (1) et alignée par rapport à l'ouverture de lampe (6) percée dans le réflecteur (1), surface de montage (30) qui présente un centre de courbure (31) coïncidant sensiblement avec le centre optique (4) du réflecteur (1), la lampe (10) étant reliée à la surface de montage (30) et traversant l'ouverture de lampe (6), caractérisé en ce que
 - le culot de lampe (13) présente une première (17), une deuxième (18) respectivement une troisième saillie (19) tangentes à une sphère imaginaire dont le centre de courbure (20) coïncide avec l'élément électrique (12), et en ce que
 - lesdites saillies (17, 18, 19) s'appuient contre la surface de montage (30).
2. Ensemble de lampe et de réflecteur selon la revendication 1, caractérisé en ce que la surface de montage (30) se situe à un support de réflecteur (32) dans lequel est fixé sûrement le réflecteur (1).
 3. Ensemble de lampe et de réflecteur selon la revendication 2, caractérisé en ce que le support de réflecteur (32) présente une première et une deuxième partie (33 respectivement 34) qui maintiennent renfermé entre elles un bord (7) prévu au réflecteur (1).
 4. Ensemble de lampe et de réflecteur selon la revendication 2, caractérisé en ce que la surface de montage (30) est la surface d'un segment de sphère.
 5. Ensemble de lampe et de réflecteur selon la revendication 4, caractérisé en ce que la surface de montage (30) est un bord de courbure prévu dans le support de réflecteur (32).
 6. Ensemble de lampe et de réflecteur selon la revendication 1 ou 2, caractérisé en ce que le culot de lampe (13) présente une partie circonferentielle non circulaire (21) coopérant avec une butée latérale (33) reliée au réflecteur (1).
 7. Ensemble de lampe et de réflecteur selon la revendication 2, caractérisé en ce qu'une douille de lampe (34) est reliée au support de réflecteur (32).
 8. Ensemble de lampe et de réflecteur selon la revendication 7, caractérisé en ce que la douille de 7



lampe (34) présente des languettes courbées conçues pour former une butée latérale pour le culot de lampe (13).

9. Ensemble de lampe et de réflecteur selon la revendication 7, caractérisé en ce que la douille de lampe (34) comporte des moyens (35, 36, 37) pour maintenir fixée la lampe (10). 5

10. Ensemble de lampe et de réflecteur selon la revendication 9, caractérisé en ce qu'un ressort (35) est présent qui s'agrippe autour du culot de lampe (13) et qui est renfermé avec l'une de ses extrémités libres (36) dans un évidement (37) pratiqué dans la douille de lampe (34). 10
15

11. Lampe électrique conçue pour être utilisée dans l'ensemble selon la revendication 1, caractérisée en ce que
 la lampe présente un récipient de lampe 20
 (11) scellé de manière étanche au vide, dans lequel est positionné un élément électrique (12) et qui est relié à un culot de lampe (13) muni de contacts (14), des conducteurs de courant (15, 16) reliant l'élément électrique (12) à de propres 25
 contacts (14), et en ce que
 le culot de lampe (13) est un corps céramique muni d'une première, d'une deuxième et d'une troisième saillie (17, 18, 19) touchant une sphère imaginaire dont le centre de courbure (20) 30
 coïncide avec l'élément électrique (12). 30

12. Lampe électrique selon la revendication 11, caractérisée en ce que le culot de lampe (13) présente une partie circonférentielle non circulaire 35
 (21). 35

13. Lampe électrique selon la revendication 12, caractérisée en ce que la partie circonférentielle non circulaire (21) présente un bord plat (23) et en 40
 ce que le récipient de lampe présente une extrémité de tube de pompage (24) alignée par rapport au bord plat (23). 40
45
50
55

