

BOX COVER FOR BUTTON TYPE SEALING BOX, AND BUTTON TYPE SEALING BOX

Technical Field

The present invention relates to an airtight container, particularly to a button-type airtight container and the lid thereof.

Background Art

A crisper is a very convenient product that people often use in life, storing food in categories making people's health further guaranteed. The crisper is divided into three kinds: (1) a plastic crisper: being made of resin materials, having a general temperature-resistant range from -20°C to 120°C ; (2) a tempered glass crisper: being made of common glass that is tempered; and (3) a heat-resistant glass crisper: being made of the borosilicate glass material.

Both a lunchbox and a crisper require high airtightness. A Korean lock&lock plastic crisper is a more common crisper with higher airtightness; however, the Korean lock&lock plastic crisper needs four buckles to buckle up, which makes the closing operation not convenient enough.

In order to solve this problem, a Chinese utility model patent (CN200920130787.8) discloses an airtight container, which comprises a container body and an outer lid disposed at the upper section of the container body; with a lever spring mechanism arranged inside the outer lid for airtightness, a lever, by being pushed with the key, drives an inner lid to move upward; and a seal ring undergoes compressive deformation under the action of the inner lid and outer lid, which brings the seal ring mounted on the inner lid into close contact with the edge of the container body, thus making the entire airtight container achieve high airtightness. The lever spring mechanism of this airtight container is driven by a key through a hinge rod, with the hinge rod difficult to be assembled to the lever. In the process of assembling and buckling up the button, i.e. in an installation environment with poor visibility, the hinge rod is prone to deviate from the connection post; if the hinge rod cannot enter the restoring buckling groove in the connection post smoothly, the button is prone to suffer such defects as installation failure and poor pop-up effect. Besides, the inner lid and the seal ring of this airtight container have a sectional structure, with the seal ring embedded in the groove of the inner lid, leaving a corner or spot that is hard to clean. The seal ring and the groove of the inner lid are prone to keep dirt to breed bacteria.

Disclosure of the Invention

The technical problem to be solved by the present invention is to provide a button-type airtight container lid that has easy assembly, high reliability, and stable operational performance.

The technical problem to be further solved by the present invention is to provide a button-type airtight container lid that is easy to clean and not prone to keep dirt at its seal ring section.

Another technical problem to be solved by the present invention is to provide a button-type airtight container that has an easily assembled lid, high airtight reliability, and stable performance.

In order to solve the above technical problems, the present invention adopts the following technical solution: A button-type airtight container lid is provided, comprising an upper lid, a lower lid, a dish seal ring, a button, a rotary toothed member, a vertical shaft and a lever spring mechanism, the button being mounted in a button hole of the upper lid, the dish seal ring being fixed at the periphery of the lower lid; the rotary toothed member includes a sleeve and N spline teeth, the spline teeth being provided at the top and bottom with a helicoid, respectively, with the upper helicoid and the lower helicoid rotating in the opposite direction; the rotary toothed member is rotatably mounted at the lower section of the vertical shaft, with the upper end of the vertical shaft fixed on the button; the button hole of the upper lid is provided at the lower section with a bottom plate, which includes an N-groove spline hole, whose tooth groove has a width adapted to the spline tooth; the bottom plate is provided at the bottom with an end gear, which includes 2N end teeth, whose tooth groove is adapted to the top of the spline tooth, with the tooth groove of the N-groove spline hole located at the tooth groove section of the end tooth; the lower lid includes a 2N-tooth end ratchet, whose ratchet tooth is adapted to the lower helicoid of the spline tooth, with N greater than or equal to 3.

In the button-type airtight container lid as described above, the lower lid includes a 2N-groove spline hole, the axial top surface of the spline tooth of which includes a helicoid adapted to the lower helicoid of the spline tooth, thus forming the end ratchet, with the tooth groove of the 2N-groove spline hole having a width adapted to the spline tooth; and the tooth groove of the N-groove spline hole offsets the tooth groove of the 2N-groove spline hole in the circumferential direction.

In the button-type airtight container lid as described above, with N equal to 3, the tooth groove of the end gear is V-shaped, and the top of the spline tooth is A-shaped; the tooth groove of the 3-groove spline hole, located at the groove bottom section of the V-shaped tooth groove of the end tooth, is ahead of the tooth groove of the 6-groove spline hole in the rotary direction of the rotary toothed member by 10° - 20° .

In the button-type airtight container lid as described above, the lever spring mechanism includes a central spring and two levers, the levers including a lever arm and a cam, the cam being provided at both ends in the axial direction with a rotary shaft, respectively; the lever arm is connected at the lower end with an end of the cam in the axial direction, and stretches out at the upper end along the radial direction of the cam; the lower lid includes two sets of brackets, each of the sets including two vertical plates; the upper lid is provided at the bottom plate with 4 vertical plate holes, with the vertical plate going through the vertical plate holes from the bottom up; the vertical plate is provided at the upper end with a hinge hole, with the two rotary shafts of the cam inserted into the two hinge holes of the bracket, respectively; the central spring is arranged between the bottom plate of the upper lid and the lower lid, the upper end of the lever arm abuts against the button, and the profile of the cam abuts against the bottom plate of the upper lid.

In the button-type airtight container lid as described above, the lower lid comprises a bottom lid and a lever seat, the lever seat including a base and the two sets of brackets, the base being provided at the central section with the 2N-groove spline hole; and the bottom lid includes a bearing hole of the base, with the base buckled into the bearing hole.

In the button-type airtight container lid as described above, the lever arm is provided at the upper end with a cross arm; the two sets of brackets have their centers deviate from the central axis of container lid, respectively, centrosymmetric with respect to the axis of the vertical shaft.

In the button-type airtight container lid as described above, the dish seal ring is fixed at the edge of the lower lid by double-shot injection molding.

A button-type airtight container is provided, comprising a container body and a container lid, with the container lid being the button-type airtight container lid as described above.

In the above button-type airtight container, with the container lid provided at the top near the periphery with a groove, when two of the button-type airtight containers are stacked, the bottom of the container body of the button-type airtight container disposed above will enter the groove of the button-type airtight container lid disposed below.

The button-type airtight container lid of the present invention provides easy assembly, high reliability, and stable operational performance.

Brief Description of Drawings

The present invention will further be described below in detail with reference to drawings and embodiments.

Fig. 1 is an exploded view of the button-type airtight container lid of the example of the present invention.

Fig. 2 is an exploded view of the button-type airtight container lid of the example of the present invention from another perspective.

Fig. 3 is a cross-sectional view of the button-type airtight container lid of the example of the present invention where the button is not pressed.

Fig. 4 is a cross-sectional view of the button-type airtight container lid of the example of the present invention where the button is pressed.

Fig. 5 is the first schematic view of the working status of the rotary toothed member of the example of the present invention.

Fig. 6 is the second schematic view of the working status of the rotary toothed member of the example of the present invention.

Fig. 7 is the third schematic view of the working status of the rotary toothed member of the example of the present invention.

Fig. 8 is the fourth schematic view of the working status of the rotary toothed member of the example of the present invention.

Fig. 9 is the fifth schematic view of the working status of the rotary toothed member of the example of the present invention.

Fig. 10 is a front view of the upper lid of the example of the present invention.

Fig. 11 is a top view of the upper lid of the example of the present invention.

Fig. 12 is a rotated cross-sectional view of Fig.11 in the A direction.

Fig. 13 is a bottom view of the upper lid of the example of the present invention.

Fig. 14 is a cross-sectional view of the bottom lid assembly of the example of the present invention.

Fig. 15 is a top view of the bottom lid assembly of the example of the present invention.

Fig. 16 is a front view of the lever seat of the example of the present invention.

Fig. 17 is a top view of the lever seat of the example of the present invention.

Fig. 18 is a cross-sectional view of Fig. 17 in the B direction.

Fig. 19 is a front view of the lever of the example of the present invention.

Fig. 20 is a top view of the lever of the example of the present invention.

Fig. 21 is a stereoscopic view of the lever of the example of the present invention.

Fig. 22 is a front view of the rotary toothed member of the example of the present invention.

Fig. 23 is a top view of the rotary toothed member of the example of the present invention.

Fig. 24 is a bottom view of the rotary toothed member of the example of the present invention.

Fig. 25 is a right view of the rotary toothed member of the example of the present invention.

Fig. 26 is a stereoscopic view of the rotary toothed member of the example of the present invention.

Fig. 27 is a stereoscopic view of the rotary toothed member of the example of the present invention from another perspective.

Fig. 28 is a stereoscopic view of the button of the example of the present invention.

Fig. 29 is a front view of the button-type airtight container of the example of the present invention.

Best Mode for Carrying out the Invention

The structure of the button-type airtight container of the present invention is as shown in Fig. 29, comprising a container body 200 and a container lid 100.

The structure of the container lid 100 is as shown in Figs. 1-28, comprising an upper lid 1, a lower lid, a dish seal ring 2, a button 3, a rotary toothed member 4, a mounting screw 5 as the vertical shaft of the rotary toothed member, and a lever spring mechanism.

The lower lid comprises a bottom lid 6 and a lever seat 7, with a dish seal ring 2 embedded non-detachably at the edge of the bottom lid 6 by double-shot injection molding.

The lever seat 7 includes a base 701 and two sets of brackets. Each set of the brackets includes two vertical plates 702, which have a hinge hole 703 at the upper end. The bottom lid 6 is provided at the central section with a bearing hole 601 of the base, in which is a slot 602. The base 701 is provided at the edge with a boss 704, which is screwed into the slot 602, thus buckling the base 701 into the bearing hole 601 of the bottom lid 6.

The two sets of brackets have their centers deviate from the central axis of container lid, respectively, centrosymmetric with respect to the axis of the mounting screw 5.

The lever spring mechanism includes a central spring 8 and two levers 9.

The levers 9 include a lever arm 902 and a cam 901, the cam 901 being provided at both ends in the axial direction with a rotary shaft 903, respectively; the lever arm 902 is connected at the lower end with an end of the cam 901 near the rotary shaft, and stretches out at the upper end along the radial direction of the cam 901; and the lever arm 902 is provided at the upper end with a cross arm 904.

The button 3, mounted in a button hole 101 of the upper lid 1, is provided at the lower section with a plurality of elastic hooks 301, and can move up and down after it is inserted into the button hole 101 without being released.

The upper lid 1 is provided below the button hole 101 with a bottom plate 102, which has 4 vertical plate holes 103, through which the vertical plate 702 goes from the bottom up, with the two rotary shafts 903 of the cam 901 inserted into the two hinge holes 703 of the bracket, respectively. The cross arm 904 at the upper end of the lever arm 902 abuts against the button 3, and the profile of the cam 901 abuts against the bottom plate 102 of the upper lid 1.

The central spring 8 has its upper end abutted against the bottom plate 102 and its lower end supported on the base 701 of the lower lid, with the lower lid and upper lid separated from each other under the action of the elastic force of the central spring 8.

The button 3 is provided at the central section with a downwardly extending cylindrical platform 302, which is provided inside with a threaded hole 303, into which is screwed the upper end of the mounting screw 5. The rotary toothed member 4 is loosely fitted over the mounting screw 5, facilitating rotation. The head of the mounting screw 5 and the cylinder platform 302 limit the axial movement of the rotary toothed member 4 with respect to the button 3.

The rotary toothed member 4 includes a sleeve 401 and 3 spline teeth 402, with the spline teeth 402 having a helicoid 403 at the bottom. The spline tooth 402, A-shaped at the top, is provided at the top right with a helicoid 404, with the lower helicoid 403 clockwise and the upper helicoid 404 counterclockwise.

The bottom plate 102 is provided at the central section with a 3-groove spline hole 107, whose tooth groove 106 has a width adapted to the width of the spline tooth 402 of the rotary toothed member 4, thus achieving sliding fit between the 3-groove spline hole 107 and the spline tooth 402 of the rotary toothed member 4.

The bottom plate 102 is provided at the bottom with an end gear 104, which has 6 end teeth; the tooth groove of the end gear 104 is V-shaped, which is adapted to the shape of the top of the spline tooth 402.

The tooth groove of the 3-groove spline hole 107 is located at the groove bottom section of the V-shaped tooth groove of the end tooth.

The base 701 of the lever seat of the lower lid is provided at the central section with a 6-groove spline hole 705, the axial top 706 of the spline tooth of which is a clockwise helicoid, with the helicoid 706 having the same helical angle with the lower helicoid of the spline tooth 402; the tooth groove 707 of the 6-groove spline hole 705 has a width adapted to the width of the spline tooth 402, thus achieving sliding fit between the 6-groove spline hole 705 and the spline tooth 402; the tooth groove of the 3-groove spline hole 107 offsets the tooth groove of the 6-groove spline hole 705 in the circumferential direction, with the tooth groove of the 3-groove spline hole 107 ahead of the tooth groove of the 6-groove spline hole 705 in the rotary direction of the rotary toothed member 4 by 15° .

With the tooth groove of the 6-groove spline hole 705 providing downward space for the spline tooth 402, if the helical angle at the bottom of the spline tooth 402 is big enough, the tooth groove of the spline hole 705 can be omitted, i.e. the 6-groove spline hole 705 can be replaced by the 6-tooth end ratchet.

There can also be 4-5 spline teeth 402 of the rotary toothed member 4, and here the spline hole and the tooth of the end gear should be increased correspondingly in number.

When the button 3 is pressed, as shown in Figs. 3 and 4, the button 3 pushes the lever arm 902 downward, the cam 901 rotates around the hinge hole 703 of the vertical plate 702, pulling the upper lid upward while pushing the upper lid 1 downward, thus shortening the distance between them and making the central spring 8 compressed. Meanwhile, the edge 108 of the upper lid 1 pushes the ring edge 201 of the dish seal ring 2 downward, which makes the ring edge 201 of the dish seal ring 2 open, forming a seal with the inner hole at the upper edge of the container body 200.

As shown in Fig. 5, when the button 3 is pressed, the rotary toothed member 4 slides downward along the tooth groove 106 of the 3-groove spline hole 107; after the spline tooth 402 of the rotary toothed member 4 leaves the tooth groove 106, the helicoid 403 at the bottom of the spline tooth 402 comes into contact with the axial top 706 of the spline tooth of the 6-groove spline hole 705; when the rotary toothed member 4 continues to move downward with the button 3, it rotates along the helicoid 706, entering the spline groove 707 of the spline hole 705, as shown in Fig. 6.

Here the button 3 is released, and the rotary toothed member 4 moves upward under the action of the resilience force of the central spring. With the rotary toothed member 4 having been

rotated, when moving backward, the top end of the spline tooth 402 enters the V-shaped tooth groove 105 of the end gear 104, and the helicoid 404 at the top right of the spline tooth 402 comes into contact with the counterclockwise helicoid of the end gear 104, with the spline tooth 402 continuing to rotate while rising until the top end of the spline tooth 402 completely enters the V-shaped tooth groove 105 of the end gear 104, as shown in Fig. 7. The end gear 104 has 5 V-shaped tooth grooves 105 in total, 3 of which are not in communication with the tooth groove 106 of the 3-groove spline hole 107. After the top end of the spline tooth 402 completely enters the V-shaped tooth groove 105 of the end gear 104, the spline tooth 402 gets stuck, as shown in Fig. 4, and the ring edge 201 of the dish seal ring 2 is kept in an open position, forming a good seal with the inner hole at the upper edge of the container body 200.

When the container lid 200 needs to be opened, the button 3 is pressed again, as shown in Fig. 8, and the rotary toothed member 4 continues to rotate forward while moving downward, with the spline tooth 402 entering a front spline groove 707 of the spline hole 705. Here the button 3 is released, and the rotary toothed member 4 moves upward under the action of the resilience force of the central spring. With the rotary toothed member 4 having been rotated, when moving backward, the top end of the spline tooth 402 enters a front V-shaped tooth groove 105 of the end gear 104, with the V-shaped tooth groove 105 in communication with the tooth groove 106 of the 3-groove spline hole 107 and not seizing the spline tooth 402; with the spline tooth 402 moving upward along the tooth groove 106, the upper lid 1 gets separated from the lower lid under the action of the resilience force of the central spring 8, and the ring edge 201 of the dish seal ring 2 retracts to get away from the inner hole of the upper edge of the container body 200.

With the container lid 100 provided at the top near the periphery with a groove 109, when two of the button-type airtight containers are stacked, the bottom 201 of the container body 200 of the button-type airtight container disposed above will enter the groove 109 of the button-type airtight container lid 100 disposed below, facilitating stacked storage of a plurality of button-type airtight containers.

The above examples of the present invention have the following beneficial effects:

1. The button-type airtight container lid of the present invention provides easy assembly, high reliability, and stable operational performance; the container lid, having a detachable structure, facilitates cleaning and maintenance; the driving structure of the button is simple and easy to handle, eliminating the need for tedious operation of opening and closing the lid, facilitating storage of the articles to be sealed.

2. With a dish seal ring 2 embedded non-detachably at the edge of the bottom lid 6 by double-shot injection molding, there is neither a gap between them nor a corner or spot hard to be cleaned, not prone to keep dirt, easy to be cleaned, healthy and safe.

CLAIMS

1. A button-type airtight container lid, comprising an upper lid, a lower lid, a dish seal ring, a button and a lever spring mechanism, the button being mounted in a button hole of the upper lid, the dish seal ring being fixed at the periphery of the lower lid, characterized in that: the container lid includes a rotary toothed member and a vertical shaft; the rotary toothed member includes a sleeve and N spline teeth, the spline teeth being provided at the top and bottom with a helicoid, respectively, with the upper helicoid and the lower helicoid rotating in the opposite direction; the rotary toothed member is rotatably mounted at the lower section of the vertical shaft, with the upper end of the vertical shaft fixed on the button; the button hole of the upper lid is provided at the lower section with a bottom plate, which includes an N-groove spline hole, whose tooth groove has a width adapted to the spline tooth; the bottom plate is provided at the bottom with an end gear, which includes 2N end teeth, whose tooth groove is adapted to the top of the spline tooth, with the tooth groove of the N-groove spline hole located at the tooth groove section of the end tooth; and the lower lid includes a 2N-tooth end ratchet, whose ratchet tooth is adapted to the lower helicoid of the spline tooth, with N greater than or equal to 3.
2. The button-type airtight container lid according to claim 1, characterized in that: the lower lid includes a 2N-groove spline hole, the axial top surface of the spline tooth of which includes a helicoid adapted to the lower helicoid of the spline tooth, thus forming the end ratchet, with the tooth groove of the 2N-groove spline hole having a width adapted to the spline tooth; and the tooth groove of the N-groove spline hole offsets the tooth groove of the 2N-groove spline hole in the circumferential direction.
3. The button-type airtight container lid according to claim 2, characterized in that: with N equal to 3, the tooth groove of the end gear is V-shaped, and the top of the spline tooth is A-shaped; the tooth groove of the 3-groove spline hole, located at the groove bottom section of the V-shaped tooth groove of the end tooth, is ahead of the tooth groove of the 6-groove spline hole in the rotary direction of the rotary toothed member by 10°-20°.
4. The button-type airtight container lid according to claim 2, characterized in that: the lever spring mechanism includes a central spring and two levers, the levers including a lever arm and a cam, the cam being provided at both ends in the axial direction with a rotary shaft, respectively; the lever arm is connected at the lower end with an end of the cam in the axial direction, and stretches out at the upper end along the radial direction of the cam; the lower lid includes two sets of brackets, each of the sets including two vertical plates; the upper lid is provided at the bottom plate with 4 vertical plate holes, with the vertical plate going through the vertical plate holes from the bottom up; the vertical plate is provided at the upper end with a hinge hole, with the two rotary shafts of the cam inserted into the two hinge holes of the bracket, respectively; the central spring is arranged between the bottom plate of the upper lid and the lower lid, the upper end of the lever arm abuts against the button, and the profile of the cam abuts against the bottom plate of the upper lid.
5. The button-type airtight container lid according to claim 4, characterized in that: the lower lid comprises a bottom lid and a lever seat, the lever seat including a base and the two sets of brackets,

the base being provided at the central section with the 2N-groove spline hole; and the bottom lid includes a bearing hole of the base, with the base buckled into the bearing hole.

6. The button-type airtight container lid according to claim 4, characterized in that: the lever arm is provided at the upper end with a cross arm; and the two sets of brackets have their centers deviate from the central axis of container lid, respectively, centrosymmetric with respect to the axis of the vertical shaft.

7. The button-type airtight container lid according to claim 1, characterized in that: the dish seal ring is fixed at the edge of the lower lid by double-shot injection molding.

8. A button-type airtight container, comprising a container body and a container lid, characterized in that: the container lid is the button-type airtight container lid according to claims 1-7.

9. The button-type airtight container according to claim 8, characterized in that: with the container lid provided at the top near the periphery with a groove, when two of the button-type airtight containers are stacked, the bottom of the container body of the button-type airtight container disposed above will enter the groove of the button-type airtight container lid disposed below.