

- 1 -

## WING SYSTEM FOR AIR VEHICLE

### TECHNOLOGICAL FIELD

5           This invention relates to wing systems for an air vehicle, in particular to high-lift aerofoils, and wings therefor.

### BACKGROUND

10           Some types of air vehicles, for example some types of unmanned air vehicles (UAVs), are configured as subsonic air vehicles. In some cases, the air vehicle is launched with the lift-generating wings folded in close proximity to the fuselage, and the wings are subsequently deployed to enable aerodynamic flight.

          By way of non-limiting example, US 2017/369150 describes, in one embodiment,  
15   a wing for an unmanned aerial vehicle. The unmanned aerial vehicle includes a first body of the wing with a first end proximate a body of the vehicle. A second end is opposite the first end. A first joint is on the first end of the first main body of the wing. The joint rotatably couples the wing to the vehicle. A second joint is on the second end of the vehicle. A second body of the wing is rotatably coupled to the first body via the second  
20   joint.

          Also by way of non-limiting example, CN107380402 discloses an unmanned aerial vehicle with folding wings. The unmanned aerial vehicle with the folding wings comprises a fuselage, the wings, horizontal tails, vertical tails, a folding wing releasing mechanism and a fixing base, and positioning holes are formed in the wings, the  
25   horizontal tails and the vertical tails; and positioning clamp columns are arranged on the fixing base, and the positioning clamp columns are matched with the positioning holes.

- 2 -

## GENERAL DESCRIPTION

According to a first aspect of the presently disclosed subject matter there is provided a wing system for an air vehicle, the wing system having a stowed configuration, a pre-deployed configuration and a deployed configuration, the wing system comprising:

5 two wings, each said wing having an aerofoil profile and being pivotably deployable about a respective pivot axis between the pre-deployed configuration and the deployed configuration, wherein:

in the stowed configuration the two wings are in first general superposed spatial relationship with respect to one another and are capable of or configured for being accommodated within an envelope having an envelope cross-sectional profile and a corresponding envelope cross-sectional area;

10 in the pre-deployed configuration the two wings are in second general superposed spatial relationship with respect to one another and capable of deploying to the deployed configuration; and

15 in the deployed configuration the wings are each capable of generating aerodynamic lift in an airstream;

each said aerofoil profile being a slotted aerofoil having a primary element, a secondary element and a chord, the secondary element being pivotable with respect to the primary element and spaced therefrom by a gap, each said aerofoil profile having a respective maximum thickness, and a respective maximum absolute thickness;

20 wherein in said stowed configuration, the respective second element of each said aerofoil profile of one said wing is set at a different flap angle as compared with the respective second element of each said aerofoil profile of the other said wing.

25 For example, each said wing having a span and an aerofoil profile at least at one respective transverse cross-section orthogonal to the respective span.

Additionally or alternatively, for example, in said stowed configuration, the respective second element of each said aerofoil profile of one said wing is set at a different flap angle as compared with the respective second element of each said aerofoil profile of the other said wing.

30 Additionally or alternatively, for example, said two wings comprise a first said wing having a first said aerofoil profile, the first aerofoil profile comprising a first leading

- 3 -

edge and a first trailing edge, and a said second wing having a first said aerofoil profile, the second aerofoil profile comprising a second leading edge and a second trailing edge. For example, in said pre-deployed configuration, said first leading edge is generally superposed over said second trailing edge.

5        Additionally or alternatively, for example, a respective maximum absolute thickness to chord ratio of each said wing is such as to enable the wings to deploy from the pre-deployed configuration to the deployed configuration without interference therebetween.

          Additionally or alternatively, for example, the respective second element of each  
10    said aerofoil profile of each said wing has a hinge axis for enabling pivoting of the respective second element with respect to the respective primary element. For example, said hinge axis is facing a pressure surface of the respective secondary element. Additionally or alternatively, for example, wherein for each said aerofoil profile, the respective hinge axis is spaced from the pressure surface of the respective secondary  
15    element by a spacing. For example, said spacing is less than 50% of a maximum thickness of the secondary element. For example, example, said spacing can be any one of: 40%, 30%, 20%, 10%, 5%, 1%, 0%, of a maximum thickness of the secondary element.

          Additionally or alternatively, for example, in said pre-deployed configuration, the respective second element of each said aerofoil profile of each said wing is set at a  
20    respective first negative flap angle.

          Additionally or alternatively, for example, in said pre-deployed configuration, the respective second element of each said aerofoil profile of each said wing is set at an identical flap angle.

          Additionally or alternatively, for example, in said pre-deployed configuration, the  
25    respective second element of each said aerofoil profile of each said wing is set at a respective first flap angle such that no part of the respective second flap intersects an imaginary line that is tangential to the respective aerofoil profile leading edge and that intersects the respective hinge axis.

          Additionally or alternatively, for example, wherein each said aerofoil profile is  
30    configured with a minimum respective said absolute thickness and a maximum said chord

- 4 -

such that in said stowed configuration the respective said aerofoil profiles of said two wings in said first general superposed spatial relationship are capable of being accommodated within said envelope cross-sectional profile while concurrently maximizing occupancy of said envelope cross-sectional area.

5        Additionally or alternatively, for example, the wing system is configured for being mounted to an underside of a fuselage of the air vehicle. For example, in said stowed configuration, the respective second element of each said aerofoil profile of each said wing is set at a respective negative flap angle. Additionally or alternatively, for example, in said stowed configuration, the respective second element of each said aerofoil profile  
10 of an uppermost said wing is set at a respective negative flap angle in a range  $-25^{\circ}$  to  $-35^{\circ}$ , and wherein the respective second element of each said aerofoil profile of an lowermost said wing is set at a respective negative flap angle in a range  $-55^{\circ}$  to  $-65^{\circ}$ . Additionally or alternatively, for example, wherein in said stowed configuration, the respective second element of each said aerofoil profile of each said wing is set at a  
15 respective second flap angle such that the respective said trailing edge and the respective hinge axis of the respective second element are on opposite sides of the respective chord line of the aerofoil profile.

            Additionally or alternatively, for example, the wing system is configured for being mounted to an upper side of a fuselage of the air vehicle. For example, in said stowed  
20 configuration, the respective second element of each said aerofoil profile of each said wing is set at a respective positive flap angle. Additionally or alternatively, for example, in said stowed configuration, the respective second element of each said aerofoil profile of an uppermost said wing is set at a respective positive flap angle in a range  $+15^{\circ}$  to  $+25^{\circ}$ , and wherein the respective second element of each said aerofoil profile of an  
25 lowermost said wing is set at a respective positive flap angle in a range  $+1^{\circ}$  to  $+10^{\circ}$ .

            Additionally or alternatively, for example, each said aerofoil profile has a first maximum spacing of the respective pressure surface from the chord line, and a second maximum spacing of the respective hinge axis from the chord line, wherein said first maximum spacing and said second maximum spacing are similar for example within 10%  
30 of one another.

- 5 -

Additionally or alternatively, for example, for each said aerofoil profile, the respective said maximum thickness to chord ratio, and the respective said maximum absolute thickness to chord ratio have magnitudes that are within 10% of one another, for example 1% of the chord.

- 5        Additionally or alternatively, for example, for each said aerofoil profile, the respective said maximum thickness to chord ratio is in the range 0.10 to 0.14.

Additionally or alternatively, for example, for each said aerofoil profile, the respective said maximum absolute thickness to chord ratio is in the range 0.10 to 0.15.

- 10       Additionally or alternatively, for example, each said aerofoil profile has a respective said maximum thickness at a position less than 25% of the chord from the leading edge of the aerofoil profile.

Additionally or alternatively, for example, each said aerofoil profile has a respective said maximum thickness at a position about 20% of the chord from the leading edge of the aerofoil profile.

- 15       Additionally or alternatively, for example, each said aerofoil profile has a camber profile with a maximum camber of about 6% or less of the chord.

Additionally or alternatively, for example, wherein each said aerofoil profile, includes at least one of the following:

- 20
  - the respective said gap varies between about 2.3% to about 1.2% of the chord, as the respective said flap angle increases from 0° to 30°;
  - the respective said gap varies between about 2.3% to about 2.5% of the chord, as the respective said flap angle decreases from 0° to -20°.

Additionally or alternatively, for example, for each said aerofoil profile, the respective leading edge radius is about 2% of the chord.

- 25       Additionally or alternatively, for example, for each said aerofoil profile, the respective said primary element has a primary element trailing edge, and wherein the respective said secondary element has a secondary element leading edge includes one of the following:

- 6 -

- wherein the primary element trailing edge overlaps the secondary element leading edge by a longitudinal overlap in a direction parallel to the chord;
- wherein the primary element trailing edge overlaps the secondary element leading edge by a longitudinal overlap in a direction parallel to the chord, and, the  
5       respective said longitudinal overlap varies between about 5% to about 3% of the chord, as the respective said flap angle increases from 0° to 30°;
- wherein the primary element trailing edge overlaps the secondary element leading edge by a longitudinal overlap in a direction parallel to the chord, and, wherein  
10       for each said aerofoil profile, the respective said longitudinal overlap varies between about 5% to about 5.5% of the chord, as the respective said flap angle decreases from 0° to -20°.

Additionally or alternatively, for example, each said aerofoil profile is configured as a high lift aerofoil profile. For example, said aerofoil profile is configured as having a maximum lift coefficient of at least 2.5 at zero flap angle, or, said aerofoil profile is  
15       configured as having a maximum lift coefficient of greater than 2.3 at zero flap angle. Additionally or alternatively, for example, said maximum lift coefficient corresponds to an angle of attack of between about 15° and about 16°.

Additionally or alternatively, for example, said aerofoil profile is configured as having a lift coefficient of 1.0 corresponds to an angle of attack of about 0°.

20       Additionally or alternatively, for example, said aerofoil profiles of said two wings have an aggregate cross-sectional area corresponding to a said occupancy of between 40% and 30% of said envelope cross-sectional area.

Additionally or alternatively, for example, said envelope cross-sectional profile is in the form of a segment of a circle of predetermined diameter, the segment being defined  
25       by a corresponding arc portion and a corresponding chord portion. For example, for each said aerofoil profile, a respective first ratio of said chord to said diameter is in the range 70% to 87%. For example, for each said aerofoil profile, the respective first ratio is in the range 75% to 85%. Additionally or alternatively, for example, for each said aerofoil profile, a respective second ratio of said maximum thickness to said diameter is in the  
30       range 7% to 12%. Additionally or alternatively, for example, for each said aerofoil profile,

- 7 -

a respective second ratio of said maximum absolute thickness to said diameter is in the range 8% to 14%.

Additionally or alternatively, for example, each said wing is configured with zero taper, and wherein each wing has a uniform said aerofoil profile along the respective span thereof. Alternatively, for example, each said wing is configured with non-zero taper, and wherein each wing has a uniform said aerofoil profile along the respective span thereof.

Additionally or alternatively, for example, the wing system is configured for selectively enabling the wings to transition from the stowed configuration to the pre-deployed configuration under predetermined conditions.

10 Additionally or alternatively, for example, the wing system is configured for maintain a negative said deflection angle for each aerofoil profile of each wing during deployment from the pre-deployed configuration through to the deployed configuration.

According to the first aspect of the presently disclosed subject matter there is also provided a wing system for an air vehicle, the wing system having at least a stowed 15 configuration, a pre-deployed configuration and a deployed configuration, the wing system comprising:

two wings, each said wing being pivotably deployable about a respective pivot axis between the pre-deployed configuration and the deployed configuration, wherein:

20 in the stowed configuration the two wings are in first general superposed spatial relationship with respect to one another and are capable of being accommodated within an envelope having an envelope cross-sectional profile and a corresponding envelope cross-sectional area;

in the pre-deployed configuration the two wings are in second general 25 superposed spatial relationship with respect to one another and capable of deploying to the deployed configuration; and

in the deployed configuration the wings are each capable of generating aerodynamic lift in an airstream;

30 each said wing having a span and an aerofoil profile at least at one respective transverse cross-section orthogonal to the respective span;

- 8 -

each said aerofoil profile being a slotted aerofoil having a primary element, a secondary element and a chord, the secondary element being pivotable with respect to the primary element and spaced therefrom by a gap, each said aerofoil profile having a respective maximum thickness, and a respective maximum absolute  
5 thickness;

wherein each said aerofoil profile is configured with a minimum respective said absolute thickness and a maximum said chord such that in said stowed configuration the respective said aerofoil profiles of said two wings in said first general superposed spatial relationship are capable of being accommodated within  
10 said envelope cross-sectional profile while concurrently maximizing occupancy of said envelope cross-sectional area.

For example, in said stowed configuration, the respective second element of each said aerofoil profile of one said wing is set at a different flap angle as compared with the respective second element of each said aerofoil profile of the other said wing.

15 Additionally or alternatively, for example, said two wings comprise a first said wing having a first said aerofoil profile, the first aerofoil profile comprising a first leading edge and a first trailing edge, and a said second wing having a first said aerofoil profile, the second aerofoil profile comprising a second leading edge and a second trailing edge. For example, in said pre-deployed configuration, said first leading edge is generally  
20 superposed over said second trailing edge.

Additionally or alternatively, for example, a respective maximum absolute thickness to chord ratio of each said wing is such as to enable the wings to deploy from the pre-deployed configuration to the deployed configuration without interference therebetween.

25 Additionally or alternatively, for example, the respective second element of each said aerofoil profile of each said wing has a hinge axis for enabling pivoting of the respective second element with respect to the respective primary element. For example, said hinge axis is facing a pressure surface of the respective secondary element. Additionally or alternatively, for example, wherein for each said aerofoil profile, the  
30 respective hinge axis is spaced from the pressure surface of the respective secondary element by a spacing. For example, said spacing is less than 50% of a maximum thickness

- 9 -

of the secondary element. For example, example, said spacing can be any one of: 40%, 30%, 20%, 10%, 5%, 1%, 0%, of a maximum thickness of the secondary element.

Additionally or alternatively, for example, in said pre-deployed configuration, the respective second element of each said aerofoil profile of each said wing is set at a  
5    respective first negative flap angle.

Additionally or alternatively, for example, in said pre-deployed configuration, the respective second element of each said aerofoil profile of each said wing is set at an identical flap angle.

Additionally or alternatively, for example, in said pre-deployed configuration, the  
10    respective second element of each said aerofoil profile of each said wing is set at a respective first flap angle such that no part of the respective second flap intersects an imaginary line that is tangential to the respective aerofoil profile leading edge and that intersects the respective hinge axis.

Additionally or alternatively, for example, the wing system is configured for being  
15    mounted to an underside of a fuselage of the air vehicle. For example, in said stowed configuration, the respective second element of each said aerofoil profile of each said wing is set at a respective negative flap angle. Additionally or alternatively, for example, in said stowed configuration, the respective second element of each said aerofoil profile of an uppermost said wing is set at a respective negative flap angle in a range  $-25^{\circ}$  to -  
20     $35^{\circ}$ , and wherein the respective second element of each said aerofoil profile of an lowermost said wing is set at a respective negative flap angle in a range  $-55^{\circ}$  to  $-65^{\circ}$ . Additionally or alternatively, for example, wherein in said stowed configuration, the respective second element of each said aerofoil profile of each said wing is set at a respective second flap angle such that the respective said trailing edge and the respective  
25    hinge axis of the respective second element are on opposite sides of the respective chord line of the aerofoil profile.

Additionally or alternatively, for example, the wing system is configured for being mounted to an upper side of a fuselage of the air vehicle. For example, in said stowed configuration, the respective second element of each said aerofoil profile of each said  
30    wing is set at a respective positive flap angle. Additionally or alternatively, for example,

- 10 -

in said stowed configuration, the respective second element of each said aerofoil profile of an uppermost said wing is set at a respective positive flap angle in a range  $+15^{\circ}$  to  $+25^{\circ}$ , and wherein the respective second element of each said aerofoil profile of an lowermost said wing is set at a respective positive flap angle in a range  $+1^{\circ}$  to  $+10^{\circ}$ .

5            Additionally or alternatively, for example, each said aerofoil profile has a first maximum spacing of the respective pressure surface from the chord line, and a second maximum spacing of the respective hinge axis from the chord line, wherein said first maximum spacing and said second maximum spacing are similar, for example within 10% of one another.

10           Additionally or alternatively, for example, for each said aerofoil profile, the respective said maximum thickness to chord ratio, and the respective said maximum absolute thickness to chord ratio have magnitudes that are within 10% of one another, for example 1% of the chord.

                 Additionally or alternatively, for example, for each said aerofoil profile, the  
15        respective said maximum thickness to chord ratio is in the range 0.10 to 0.14.

                 Additionally or alternatively, for example, for each said aerofoil profile, the respective said maximum absolute thickness to chord ratio is in the range 0.10 to 0.15.

                 Additionally or alternatively, for example, each said aerofoil profile has a  
20        respective said maximum thickness at a position less than 25% of the chord from the leading edge of the aerofoil profile.

                 Additionally or alternatively, for example, each said aerofoil profile has a  
                 respective said maximum thickness at a position about 20% of the chord from the leading  
                 edge of the aerofoil profile.

                 Additionally or alternatively, for example, each said aerofoil profile has a camber  
25        profile with a maximum camber of about 6% or less of the chord.

                 Additionally or alternatively, for example, wherein each said aerofoil profile, includes at least one of the following:

- the respective said gap varies between about 2.3% to about 1.2% of the chord, as the respective said flap angle increases from  $0^{\circ}$  to  $30^{\circ}$ ;

- 11 -

- the respective said gap varies between about 2.3% to about 2.5% of the chord, as the respective said flap angle decreases from 0° to -20°.

Additionally or alternatively, for example, for each said aerofoil profile, the respective leading edge radius is about 2% of the chord.

5        Additionally or alternatively, for example, for each said aerofoil profile, the respective said primary element has a primary element trailing edge, and wherein the respective said secondary element has a secondary element leading edge includes one of the following:

- wherein the primary element trailing edge overlaps the secondary element leading edge by a longitudinal overlap in a direction parallel to the chord;
- 10        • wherein the primary element trailing edge overlaps the secondary element leading edge by a longitudinal overlap in a direction parallel to the chord, and, the respective said longitudinal overlap varies between about 5% to about 3% of the chord, as the respective said flap angle increases from 0° to 30°;
- 15        • wherein the primary element trailing edge overlaps the secondary element leading edge by a longitudinal overlap in a direction parallel to the chord, and, wherein for each said aerofoil profile, the respective said longitudinal overlap varies between about 5% to about 5.5% of the chord, as the respective said flap angle decreases from 0° to -20°.

20        Additionally or alternatively, for example, each said aerofoil profile is configured as a high lift aerofoil profile. For example, said aerofoil profile is configured as having a maximum lift coefficient of at least 2.5 at zero flap angle, or, said aerofoil profile is configured as having a maximum lift coefficient of greater than 2.3 at zero flap angle. Additionally or alternatively, for example, said maximum lift coefficient corresponds to  
25        an angle of attack of between about 15° and about 16°.

Additionally or alternatively, for example, said aerofoil profile is configured as having a lift coefficient of 1.0 corresponds to an angle of attack of about 0°.

Additionally or alternatively, for example, said aerofoil profiles of said two wings have an aggregate cross-sectional area corresponding to a said occupancy of between 40%  
30        and 30% of said envelope cross-sectional area.

- 12 -

Additionally or alternatively, for example, said envelope cross-sectional profile is in the form of a segment of a circle of predetermined diameter, the segment being defined by a corresponding arc portion and a corresponding chord portion. For example, for each said aerofoil profile, a respective first ratio of said chord to said diameter is in the range  
5 70% to 87%. For example, for each said aerofoil profile, the respective first ratio is in the range 75% to 85%. Additionally or alternatively, for example, for each said aerofoil profile, a respective second ratio of said maximum thickness to said diameter is in the range 7% to 12%. Additionally or alternatively, for example, for each said aerofoil profile, a respective second ratio of said maximum absolute thickness to said diameter is in the  
10 range 8% to 14%.

Additionally or alternatively, for example, each said wing is configured with zero taper, and wherein each wing has a uniform said aerofoil profile along the respective span thereof. Alternatively, for example, each said wing is configured with non-zero taper, and wherein each wing has a uniform said aerofoil profile along the respective span thereof.

15 Additionally or alternatively, for example, the wing system is configured for selectively enabling the wings to transition from the stowed configuration to the pre-deployed configuration under predetermined conditions.

Additionally or alternatively, for example, the wing system is configured for maintain a negative said deflection angle for each aerofoil profile of each wing during  
20 deployment from the pre-deployed configuration through to the deployed configuration.

According to a second aspect of the presently disclosed subject matter, there is provided an air vehicle, comprising the wing system as defined above regarding the first aspect of the presently disclosed subject matter. For example, the air vehicle is a UAV.

According to a third aspect of the presently disclosed subject matter, there is  
25 provided a launch system comprising an air vehicle as defined above regarding the second aspect of the presently disclosed subject matter, accommodated in a fairing having an internal chamber defining said envelope, said envelope cross-sectional profile and said envelope cross-sectional area.

For example, the launch system is configured for selectively releasing said air  
30 vehicle from said fairing. For example, the launch system is configured for selectively

- 13 -

transitioning the wing system from the stowed configuration to the pre-deployed configuration following release of said air vehicle from said fairing. For example, the launch system is configured for selectively transitioning the wing system from the pre-deployed configuration to the deployed configuration and for subsequently enabling  
5 aerodynamic flight of the air vehicle.

A feature of at least one example of the presently disclosed subject matter is that two element aerofoil profiles are provided for deployable wings for an air vehicle, in which in said stowed configuration, the respective second element of each said aerofoil profile of one said wing is set at a different flap angle as compared with the respective  
10 second element of each said aerofoil profile of the other said wing, thereby enabling maximizing occupancy of an envelope cross-sectional area in which it is desired to accommodate the wing system in stowed configuration. Such a feature can be of particular use in applications of the presently disclosed subject matter in which such an envelope cross-sectional area is semi-circular, or in the form of a segment or trapezium  
15 in which the two superposed aerofoil profiles in the stowed configuration can have different-sized widths of the envelope for being accommodated therein.

Another feature of at least one example of the presently disclosed subject matter is that two element aerofoil profiles are provided for deployable wings for an air vehicle, in which the respective second element of each said aerofoil profile of one said wing and  
20 the respective second element of each said aerofoil profile of the other said wing have to be pivoted to a different flap angle to that corresponding to the stowed configuration, to enable the wings to deploy from the pre-deployed configuration to the deployed configuration.

Another feature of at least one example of the presently disclosed subject matter  
25 is that two element aerofoil profiles are provided for deployable wings for an air vehicle, in which a high degree of flexibility can be applied to the design of the two element aerofoil profiles, including maximum absolute thickness, maximum aerofoil thickness, leading edge radius, camber, location of flap hinge point, and flap angle, wherein to enable for efficient packaging within an envelope provided by a fairing, while providing  
30 high lift and endurance characteristics, as well as mission adaptive features via flap deflection settings for take-off and landing, cruise, loiter, and so on.

- 14 -

Another feature of at least one example of the presently disclosed subject matter is that two element aerofoil profiles are provided for deployable wings for an air vehicle, in which it can be possible to extend the flight envelope, particularly in the low speed range, by providing high lift characteristics, for example including a reduced thickness to  
5 chord ratio.

Another feature of at least one example of the presently disclosed subject matter is that two element aerofoil profiles are provided for deployable wings for an air vehicle, in which the aerofoil profiles have high lift and long endurance characteristics.

## 10 BRIEF DESCRIPTION OF THE DRAWINGS

In order to better understand the subject matter that is disclosed herein and to exemplify how it may be carried out in practice, examples will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

**Fig. 1** is a transverse cross-sectional view of an air vehicle according to a first example  
15 of the presently disclosed subject matter, in the stowed configuration accommodated in a fairing; **Fig. 1(a)** is a transverse cross-sectional view of the air vehicle according to the example of Fig. 1, in the pre-deployed configuration.

**Fig. 2** is a transverse cross-sectional view of the air vehicle according to the example of Fig. 1, in the deployed configuration.

20 **Fig. 3** illustrates a slotted aerofoil section on which the wings of the air vehicle according to the example of Fig. 1 is based; **Fig. 3(a)** schematically illustrated flap deflections of the flap of the aerofoil of Fig. 3; **Fig. 3(b)** shows relative sizes of the primary element and the secondary element of the aerofoil of Fig. 3.

**Fig. 4** schematically illustrates a geometric relationship between maximum absolute  
25 thickness and aerofoil thickness of the slotted aerofoil section of Fig. 3.

**Fig. 5(a)** illustrates a reference datum slotted aerofoil section, and **Fig. 5(b)** illustrates the slotted aerofoil section of Fig. 3.

- 15 -

**Fig. 6** schematically compares the thickness distributions of airfoils of Fig. 5(a) and Fig. 5(b) along the respective chords.

**Fig. 7** schematically compares the camber distributions of airfoils of Fig. 5(a) and Fig. 5(b) along the respective chords.

5 **Fig. 8** schematically compares the lift coefficient distributions of airfoils of Fig. 5(a) and Fig. 5(b) with angle of attack, at zero flap angle and Reynold numbers of 1,000,000; **Fig. 8(a)** schematically compares the lift coefficient distributions of airfoils of Fig. 5(a) and Fig. 5(b) with drag coefficient, at zero flap angle and Reynold numbers of 1,000,000; **Fig. 8(b)** schematically compares the hinge  
10 moment coefficient distributions for the secondary elements of airfoils of Fig. 5(a) and Fig. 5(b) with lift coefficient, at zero flap angle and Reynold numbers of 1,000,000; **Fig. 8(c)** schematically compares the hinge moment coefficient distributions for the secondary elements of airfoils of Fig. 5(a) and Fig. 5(b) with lift coefficient, at flap angle  $+10^\circ$  and Reynold numbers of 1,000,000.

15 **Fig. 9** schematically illustrates the gap size and longitudinal overlap between the primary element and the secondary element of the slotted aerofoil section of Fig. 3.

**Fig. 10(a)** schematically compares the gap size distributions of airfoils of Fig. 5(a) and Fig. 5(b) with flap deflection angle; **Fig. 10(b)** schematically compares the longitudinal overlap distributions of airfoils of Fig. 5(a) and Fig. 5(b) with flap  
20 deflection angle.

**Fig. 11(a)** illustrates the slotted aerofoil section of Fig. 3 in stowed configuration; **Fig. 11(b)** illustrates the slotted aerofoil section of Fig. 3 in pre-deployed configuration; **Fig. 11(c)** illustrates the slotted aerofoil section of Fig. 3 in deployed configuration.

25 **Fig. 12(a)** is a transverse cross-sectional view of an air vehicle of Fig. 1, showing the envelope therein; **Fig. 12(b)** shows a cross-sectional envelope of Fig. 12(a).

**Fig. 13** is a transverse cross-sectional view of an air vehicle according to a variation of the example of Fig. 1, in the stowed configuration accommodated in a fairing.

- 16 -

**Fig. 14** schematically compares the lift coefficient distributions of the airfoil of the example of Fig. 3 with angle of attack, at zero flap angle, at +10° flap angle, and at -10° flap angle.

## 5 DETAILED DESCRIPTION

Referring to Figs. 1, 1(a) and 2, an air vehicle according to a first example of the presently disclosed subject matter, generally designated **100**, comprises a wing system **200**, which is *per se* novel.

In at least this example, the air vehicle **100** is a powered, fixed-wing type air vehicle, comprising a subsonic configuration, having a fuselage section **110** (also referred to herein as the fuselage **110**), said wing system **200**, a suitable propulsion system (not shown), and an empennage (not shown) – for example (but not limited to) including a tailplane and vertical stabilizers. Furthermore, while the presently disclosed subject matter finds particular application in UAV aircraft, the presently disclosed subject matter can also be applied to manned aircraft, *mutatis mutandis*, in particular to general aviation, subsonic transport, naval aviation, and so on, for example. In alternative variations of this example, and in other examples, the air vehicle **100** can instead be configured as an un-powered, fixed-wing type subsonic air vehicle, manned or unmanned.

The air vehicle **100** further comprises a control system comprising a controller (not shown) configured for operating the air vehicle **100** at least within the flight envelope thereof.

As will become clearer herein, the wing system **200** has a stowed configuration **SC**, a pre-deployed configuration **PC** and a deployed configuration **DC**.

The wing system **200** comprises two wings **220**, in particular a port wing **220P** and a starboard wing **220S**. Thus, unless otherwise specified herein, the reference numeral **220** shall also refer to each one of the port wing **220P** and the starboard wing **220S**.

Each said wing **220** is pivotably mounted to the fuselage **110** about a respective pivot axis **PA**, thereby enabling the wings **220** to each pivot about its respective axis **PA**

- 17 -

between the respective pre-deployed configuration **PC** and the respective deployed configuration **DC**. While in at least this example, the respective pivot axes **PA** of the two wings **220** are coaxial, in alternative variations of this example, and in other examples, respective pivot axes **PA** of the two wings **220** are not coaxial – for example parallel and spaced, or non-parallel and spaced. Examples of suitable mechanisms for providing such pivoting, including actuation systems therefor, are known in the art.

In at least this example, the pivot axis **PA** of each wing **220** is parallel to the yaw axis of the air vehicle **100**.

The port wing **220P** and the starboard wing **220S** are essentially mirror images of one another, and are otherwise substantially identical with the exception that at least in this example, a portion of each wing **220** in the vicinity of the respective pivot axis **PA** are in superposed configuration with respect to one another.

In at least this example, the air vehicle **100** is configured for being accommodated in a fairing **800**, while the wing system **200** is in the stowed configuration **SC**. For example, such a fairing **800** enables the air vehicle **100** to be isolated from aerodynamic forces as the air vehicle **100** is accelerated to required speed and altitude, and/or such a fairing can protect the air vehicle while in storage or while being transported. For example the air vehicle **100** can be accelerated to required speed and altitude via an external launch system, for example a launch barrel, or for example via a booster rocket (as a payload thereof for example), or for example can be delivered to required altitude and required speed via a carrier air vehicle.

The fairing **800** has an internal profile and fairing cross-sectional areas at transverse planes orthogonal to the longitudinal axis **LAF** of the fairing such as to enable the respective transverse cross-sections of the air vehicle **100** (i.e., the respective external profiles and transverse cross-sectional areas of the air vehicle **100**) to be accommodated therein. In at least this example, fairing **800** has a substantially uniform internal profile and a substantially uniform cross-sectional area at transverse planes orthogonal to the longitudinal axis **LAF** for at least cross-sections of the air vehicle which include the wings **220** in the stowed configuration **SC**. The longitudinal axis **LAF** of the fairing is generally defined at the centerline of the fairing.

- 18 -

It is to be noted that at least for some implementations of this example in which the acceleration of the air vehicle **100** (while accommodated in the fairing **800** in a respective assembly) is achieved by applying a force to the assembly (for example a thrust force via a booster rocket, or as a result of being fired from a launch barrel), there can be advantages in having such a force aligned with the fairing longitudinal axis **LAF**, in particular the centerline of the fairing. In at least such cases there can also be corresponding advantages in having the center of gravity **CG** of the air vehicle **100** also lying on the fairing longitudinal axis **LAF** (Fig. 1), in particular on the centerline of the fairing. For example, such an arrangement can minimize or eliminate risk of nutation. In at least some such cases, the air vehicle **100** can be configured such that the center of gravity **CG** thereof is accommodated within the fuselage **110**. Thus at transverse cross-sections along the fairing longitudinal axis **LAF**, the respective cross-section of the fuselage **110** occupies more than half of the respective internal cross-section of the fairing **800**, while the two wings **220** (in the stowed configuration **SC**) occupy less than half of the internal cross-section of the fairing **800**. In at least some such cases, the fuselage **110** has greater mass than the wings **220**. As will become clearer herein, according to an aspect of the presently disclosed subject matter, the maximum absolute thickness **ABS** of the wings can be minimized to enable fitting of the two wings **220** in the smallest possible part of the internal volume provided by the fairing **800** to thereby enable maximization of the fuselage cross-section, and thereby maximize payload capacity of the air vehicle **100**, for example.

In at least the example of Fig. 1, the wings **220** are below the fuselage, that is, the suction surface of the uppermost wing **220** (for example the starboard wing **220S**) of the wing system **200** is facing a bottom portion **115** of the fuselage **110**. However, in at least one alternative variation of the example of Fig. 1, and referring now to Fig. 13, the wings **220** can be above the fuselage, that is, the pressure surface of the lowermost wing **220** (for example the port wing **220P**) of the wing system **200** is facing an upper portion **116** of the fuselage **110**.

Referring also to Fig. 3, each wing **220** is based on (i.e., the wing **220** comprises a plurality of aerofoil sections each corresponding to) a two-element slotted aerofoil **300**, also interchangeably referred to herein as SA aerofoil or SA aerofoil **300**, in particular

- 19 -

exhibiting high lift characteristics. In other words, each wing **220** comprises a plurality of aerofoil sections each corresponding to the two-element slotted aerofoil **300**.

Herein, the term "slotted aerofoil" (SA-aerofoils) – generally refers to two-element aerofoils (also referred to herein as dual element aerofoils) composed of a first or primary element - the main aerofoil body - and a second or secondary element, for example in the form of a flap or aileron. The second element of SA-aerofoils is separated from the main body by a slot which is substantially open for the airflow at any deflection of the flap. A feature of slotted aerofoil type structures is that this type of structure facilitates actuation of the second element through positive or negative deflection angles. Another feature of this type of structure is that a box-like relatively rigid construction may be achieved. In general, when the second aerofoil element is coupled to actuators, the SA-aerofoils can provide features of adjustable geometry and have built-in options for operating as take-off/landing flaps, ailerons, airbrakes and for providing decambering at maximum speed flight. SA-aerofoils can include mission-adaptive, two-element, high-lift arrangements, and are inherently high-lift aerofoils that are particularly suitable for development of long endurance UAV and other aircraft, loitering at high lift coefficients. Such SA-aerofoils can be designed for cruising/loitering flight at high lift coefficients, and optionally rely on a second element rotation around external hinge point for adjustment of the aerofoil to different flight regimes.

In implementations of this example in which the wings **220** are in plan form generally rectangular, the SA aerofoil **300** is uniform in size and profile along the respective span of the wing **220**.

In implementations of this example in which the wings **220** are in plan form generally trapezoidal (i.e., having a taper) or any other shape, the SA aerofoil **300** is uniform in profile along the respective span of the wing **220**, but the size of the SA aerofoil **300** at each span-wise position along the span of the respective wing changes in proportion to the size of the chord **C** at the respective span-wise position.

In at least one of the above implementations the respective thickness to chord ratio along the respective span of the wing **220** can be uniform.

- 20 -

In at least one variation of the above implementations the respective thickness to chord ratio along the respective span of the wing **220** can be non-uniform. For example, respective thickness to chord ratio along the respective span can be reduced in a direction from the respective wing root to wing tip. In such cases, and according to an aspect of the  
5 presently disclosed subject matter, the respective maximum thickness to chord ratio between the wing root and wing tip is still maintained within a range that provides the respective AS aerofoil **300** with high lift characteristics. For example such a range can be 10% to 14%. In at least some such cases, there can be advantages in having a relatively thin wing tip (as compared with the wing root).

10 Aerofoil **300** comprises a first or primary element **332** (also referred to interchangeably herein as the "main body of the aerofoil", or as the "main body"), and a pivotable second or secondary element **334** (also referred to interchangeably herein as the "aerofoil flap", or as the "flap"). Thus, correspondingly, each wing **220** has a primary wing portion (also referred to herein as the main wing portion) **222**, corresponding to the  
15 primary elements **332** of the aerofoils **300**, and a secondary wing portion (also referred to herein as the flap portion) **224**, corresponding to the secondary elements **334** of the aerofoils **300**. In at least this example, the two element structure of each wing **220**, i.e., the respective primary wing portion **222** and the respective secondary wing portion **224**, generally extend from the wing tip **221** to the wing root **226** (Fig. 2), while portions **227**  
20 of the wings **220**, in-board of the wing roots **226** and that remain in overlapping relationship with the fuselage **110** in the deployed configuration **DC**, do not require any aerodynamic profile, nor the two-element wing structure.

The primary element **332** comprises the leading edge **338** of the SA aerofoil **300**, which coincides with the leading edge **252** of the respective wing **220**. The primary  
25 element **332** also comprises major portions **331a**, **333a**, of the suction surface **331** and pressure surface **333**, respectively, of the SA aerofoil **300**. The primary element **332** also comprises a trailing end **338a**, also referred to interchangeably herein as the trailing edge of the primary element **332**.

The secondary element **334** is configured as single continuous flap segment, and  
30 comprises the trailing edge **339** of the SA aerofoil **300**, which coincides with the trailing edge **254** of the wing **220**. The secondary element **334** also comprises minor portion

- 21 -

**331b, 333b**, of the suction surface **331** and pressure surface **333** of the SA aerofoil **300**, respectively.

The SA aerofoil **300** comprises chord **C**, defined along chord line **CL**, which corresponds to the angle of attack  $\alpha$  of zero for the SA aerofoil **300**. In other words, the chord line **CL** is generally parallel to the longitudinal axis of the air vehicle **100** or is at a desired inclination angle to the longitudinal axis of the air vehicle **100**, and/or, the chord line **CL** is generally parallel to the roll axis of the air vehicle **100** or is at a desired inclination angle about the pitch axis of the air vehicle **100**.

It is to be noted that in at least some implementations of the above example, the chord line **CL** can be set at a desired inclination angle to the longitudinal axis of the air vehicle **100**, such that when the wings **220** are deployed from the pre-deployed configuration **PC** to the deployed configuration **DC**, the wings **220** automatically have the desired inclination to the longitudinal axis of the air vehicle **100**, without the need to manipulate the wings **220** other than pivoting of the wings about the pivot axes **PA**. In other words, in the pre-deployed configuration **PC**, and correspondingly in the stowed configuration **SC**, the wings **220** can be oriented relative to one another and relative to the pivot axes **PA** such that the wings **220** automatically provide the desired inclination to the longitudinal axis of the air vehicle **100** in the deployed configuration **DC**.

The secondary element **334** is pivotable about hinge point **359** (also referred to interchangeably herein as the hinge axis) to provide a range of positive and negative deflection angles  $\delta$  for the secondary element **334** with respect to the primary element **332**.

The deflection angle  $\delta$  is also referred to interchangeably herein as flap deflection angle  $\delta$  or as flap angle  $\delta$ .

The deflection angle  $\delta$  of the secondary element **334**, is defined with respect to a flap datum line **FL**, which is at angle  $\theta$  to the chord line **CL**, i.e., in which the leading end **335** is vertically higher than the trailing edge **339**, in the view of Fig. 3. In other words, a deflection angle  $\delta$  of zero for the secondary element **334** corresponds to the secondary element **334** being aligned with flap datum line **FL**.

- 22 -

Referring also to Fig. 3(a), positive deflection angle  $\delta$  corresponds to the flap datum line **FL** being at an angle greater than angle  $\theta$  to the chord line **CL** (i.e., the secondary element **334** pivots about hinge point **359** in a clockwise direction in the view of Fig. 3), while negative deflection angle  $\delta$  corresponds to the flap datum line **FL** being  
 5 at an angle smaller than angle  $\theta$  to the chord line **CL** (i.e., the secondary element **334** pivots about hinge point **359** in a counter clockwise direction in the view of Fig. 3).

It is to be noted that in at least some implementations of the above examples, the position of the chord line **CL** with respect to the aerofoil **300** such as to corresponds to the angle of attack  $\alpha$  of zero for the SA aerofoil **300** can also be chosen such that at zero  
 10 deflection angle  $\delta$  the coefficient of lift  $C_l$  for the aerofoil is 1.0, while at the same time allowing for the second element **334** to be pivoted to deflection angles  $\delta$  in an "aerodynamic" range of up to  $\pm 20^\circ$  or up to  $\pm 25^\circ$ , for example, for enabling aerodynamic operation second element **334**. By "aerodynamic operation second element **334**" is meant that at the respective deflection angles  $\delta$  in the aforesaid aerodynamic range, attached  
 15 flow is maintained over the aerofoil **300**, and furthermore that efficient control is provided by the aerofoil **300** – i.e., within the aforesaid aerodynamic range, changes in deflection angle  $\delta$  provide corresponding controlled changes in the coefficient of lift  $C_l$  for the aerofoil **300**. It is also to be noted that in such implementations of the above examples, the position of the chord line **CL** with respect to the aerofoil **300** such as to provide  
 20 reduced drag at cruise, and a maximum coefficient of lift  $C_l$  at zero deflection angle  $\delta$  that is consistent with high lift performance, i.e., a maximum coefficient of lift  $C_l$  of more than 2.2, for example 2.3 or more, at such conditions. In yet other alternative variations of this example, the "aerodynamic" range can be up to  $\pm 30^\circ$ , for example.

In at least some implementations of the above examples, the angle  $\theta$  can be about  
 25  $12^\circ$ .

In yet other implementations of the above examples, the angle  $\theta$  can be in the range of about  $8^\circ$  to about  $16^\circ$ . In such examples where the angle  $\theta$  is less than  $12^\circ$ , for example between  $8^\circ$  to less than  $12^\circ$ , the range of positive/negative deflection angles  $\delta$  for enabling aerodynamic operation of the second element **334** can change to an  
 30 aerodynamic range of between more than  $+20^\circ$  to less than  $-20^\circ$  (for example up to  $+24^\circ/-16^\circ$ ), as compared with  $\pm 20^\circ$  for the example of Fig. 3, or to an aerodynamic range of

- 23 -

between more than  $+25^\circ$  to less than  $-25^\circ$  (for example up to  $+29^\circ/-21^\circ$ ), as compared with  $\pm 25^\circ$  for the example of Fig. 3. In such examples where the angle  $\theta$  is more than  $12^\circ$ , for example between more than  $12^\circ$  to  $16^\circ$ , the range of positive/negative deflection angles  $\delta$  for enabling aerodynamic operation of the second element **334** can change to to  
 5 an aerodynamic range of between less than  $+20^\circ$  to more than  $-20^\circ$  (for example up to  $+16^\circ/-24^\circ$ ), as compared with  $\pm 20^\circ$  for the example of Fig. 3, or to an aerodynamic range of between less than  $+25^\circ$  to more than  $-25^\circ$  (for example up to  $+21^\circ/-29^\circ$ ), as compared with  $\pm 25^\circ$  for the example of Fig. 3.

Referring to Fig. 14, at flap deflection angle  $\delta$  of  $0^\circ$ , at least in this example the  
 10 SA aerofoil **300** exhibits a maximum coefficient of lift of about 2.5 at an angle of attack  $\alpha$  of about  $15^\circ$  to  $16^\circ$ , while the coefficient of lift is about 1.0 at angle of attack  $\alpha$  of about  $0^\circ$ , trailing off to  $C_l$  of about 2.1 at angle of attack  $\alpha$  of about  $20^\circ$ . For the same aerofoil **300**, at a positive flap deflection angle  $\delta$  of  $+10^\circ$ , the SA aerofoil **300** exhibits a maximum coefficient of lift of over 2.6 at an angle of attack  $\alpha$  of about  $14^\circ$  to  $15^\circ$ , while the  
 15 coefficient of lift is about 1.6 at angle of attack  $\alpha$  of about  $0^\circ$ , trailing off to  $C_l$  of about 2.1 at angle of attack  $\alpha$  of about  $20^\circ$ . For the same aerofoil **300**, at a negative flap deflection angle  $\delta$  of  $-10^\circ$ , the SA aerofoil **300** exhibits a maximum coefficient of lift of about 2.15 at an angle of attack  $\alpha$  of about  $17^\circ$ , while the coefficient of lift is about 0.4 at angle of attack  $\alpha$  of about  $0^\circ$ , trailing off to  $C_l$  of about 2.0 at angle of attack  $\alpha$  of about  
 20  $20^\circ$ .

It is to be noted that at least in this example, the second element **334** can be pivoted to deflection angles  $\delta$  in an aerodynamic range of at least up to  $\pm 20^\circ$  or up to  $\pm 25^\circ$ , for example, for enabling aerodynamic operation of the second element **334**. Nevertheless in at least this example it is also possible to pivot the second element **334** to deflection angles  
 25  $\delta$  over a "mechanical range" that is higher than the aerodynamic range of up to  $\pm 20^\circ$  or up to  $\pm 25^\circ$ . Such a mechanical range can be limited by mechanical constraints. For example the mechanical negative deflection angle  $\delta$  limit for the example of Fig. 3 is about  $-72^\circ$ , at which negative deflection the suction surface of the second element **334** abuts the trailing end of the first element **332**. In this example the mechanical positive  
 30 deflection angle  $\delta$  limit is over  $90^\circ$ , at which positive deflection the trailing edge of the

- 24 -

second element **334** abuts the pressure surface of the first element **332**. In alternative variations of this example, the mechanical range for deflection angles  $\delta$  can be any one of:  $+90^\circ$  to  $-90^\circ$ ;  $+90^\circ$  to  $-80^\circ$ ;  $+90^\circ$  to  $-70^\circ$ ;  $+90^\circ$  to  $-60^\circ$ ;  $+80^\circ$  to  $-90^\circ$ ;  $+90^\circ$  to  $-80^\circ$ ;  $+80^\circ$  to  $-70^\circ$ ;  $+80^\circ$  to  $-60^\circ$ ;  $+70^\circ$  to  $-90^\circ$ ;  $+70^\circ$  to  $-80^\circ$ ;  $+70^\circ$  to  $-70^\circ$ ;  $+70^\circ$  to  $-60^\circ$ ;  $+60^\circ$  to  $-90^\circ$ ;  $+60^\circ$  to  $-80^\circ$ ;  $+60^\circ$  to  $-70^\circ$ ;  $+60^\circ$  to  $-60^\circ$ ;  $+50^\circ$  to  $-90^\circ$ ;  $+50^\circ$  to  $-80^\circ$ ;  $+50^\circ$  to  $-70^\circ$ ;  $+50^\circ$  to  $-60^\circ$ .

It is to be noted that the actuator for each secondary element **334** can be matched to the required range (including the required aerodynamic range and the required mechanical range for the specific wing **220**) of positive and negative deflection angles.

Referring to Fig. 3(b), in at least this example, the primary element **332** has a primary chord **C1** of about 77% of the chord **C**, wherein primary chord **C1** is defined as the spacing between the leading edge **338** and the trailing end **338a**, taken along a direction parallel to the chord line **CL**. Also in at least this example, the secondary element **334** has a secondary chord **C2** of about 27.5% of the chord **C**, wherein the secondary chord **C2** is defined as the spacing between the leading end **335** and the trailing edge **339**, taken along a direction parallel to the chord line **CL**, when the secondary element **334** is at deflection angle  $\delta$  of  $0^\circ$ . In alternative variations of this example, and in other examples, the primary element **332** can have a primary chord **C1** with respect to the chord **C**, within any one of the following ranges: 70% to 80%; 65% to 85%; 75% to 80%. In this or other alternative variations of this example, and in other examples, the secondary element **334** can have a secondary chord **C2** with respect to the chord **C**, within any one of the following ranges: 20% to 30%; 25% to 35%; 25% to 30%.

A slot **355** separates the leading end **335** of the secondary element **334** (also referred to interchangeably herein as the leading edge of the secondary element **334**) from the trailing end **338a** of the primary element **332**.

For example, the slot **355** can have an exit width of about 2.3% of the aerofoil chord **C** in a non-deflected position of the flap element, i.e., at deflection angle  $\delta$  of zero.

Without being bound to theory, the inventors believe that the airflow through slot **255** provides enhanced efficiency and linearity of the aerodynamic characteristics of the aerofoil as compared to a similar non-slotted aerofoil, and provides or enhances high lift

- 25 -

characteristics to the aerofoil, and/or, provides or enhances flap efficiency characteristics to the aerofoil.

Referring in particular to Fig. 3(a), the deflection angle  $\delta$  of the secondary element **334** generally depends on the particular mode of operation of the wing **220**. For example,  
 5 in cruise/loiter mode  $\sim$  deflection angle  $\delta = 0^\circ$ ; take-off/landing mode **TLM**  $\sim$  deflection angle  $\delta = +20$  to  $+25^\circ$ ; aileron mode **AM**  $\sim$  deflection angle  $\delta = \pm 20^\circ$  to  $\pm 25^\circ$ ; maximum speed decambering mode **DM**  $\sim$  negative flap deflection, deflection angle  $\delta = -10^\circ$  to  $-15^\circ$ .

The precise form and size of the slot **355** can generally vary with deflection angle  
 10  $\delta$  of the secondary element **334**, and thus generally depends on the particular mode of operation of the wing **220**.

Furthermore, in at least this example, in the stowed configuration **SC**, the deflection angle  $\delta$  can be between  $+20^\circ$  and  $-60^\circ$ .

For example, in at least one implementation of the above example, and referring  
 15 again to Fig. 1, one wing **220** (for example the starboard wing **220S**) can have a deflection angle  $\delta$  (annotated as angle  $\delta_1$  in Fig. 1) of about  $-30^\circ$ , for example  $-32^\circ$ , while the other wing **220** (for example the port wing **220P**) can have a deflection angle  $\delta$  (annotated as angle  $\delta_2$  in Fig. 1) of about  $-60^\circ$ . For example, in at least one other implementation of the above example, and referring again to Fig. 13, one wing **220** (for example the starboard  
 20 wing **220S**) can have a deflection angle  $\delta$  (annotated as angle  $\delta_1'$  in Fig. 13) of about  $+20^\circ$ , while the other wing **220** (for example the port wing **220P**) can have a deflection angle  $\delta$  (annotated as angle  $\delta_2'$  in Fig. 13) of about  $+5^\circ$ .

Furthermore, in at least this example, and referring to Fig. 1(a), in the pre-deployed configuration **PC**, the deflection angle  $\delta$  can be identical to one another, for  
 25 example between  $-10^\circ$  and  $-15^\circ$ .

Referring again to Fig. 3, the hinge point **359** of the secondary element **334** is spatially fixed with respect to the SA aerofoil **300**. In particular, the hinge point **359** of the secondary element **334** is spatially fixed at an outwardly displaced position with respect to the lower (pressure) surface of the secondary element **334**. In at least this  
 30 example, the spacing **FS** is minimized, in order to enable minimizing the value of the

- 26 -

maximum absolute thickness **ABT** of the acrofoil **300**, and thus the hinge point **359** is as close as possible to the secondary element **334**. In alternative variations of this example, and in other examples, the hinge point **359** can be enclosed within the secondary element **334**. In yet other alternative variations of this example, and in other examples, the hinge point **359** can be facing the suction surface of the secondary element **334**, i.e. the respective minor portion **331b** of the suction surface **331**.

Preferably, the hinge point **359** is further located with respect to the second element **334** such that: the second element **334** is aerodynamically stable relative to the hinge point **359** (that is that the hinge point is preferably forward of the aerodynamic center of the second element **334**); actuator loads are minimized if possible.

For example, spacing **FS** is less than 50% of the maximum thickness of the secondary element **334**. For example, spacing **FS** can be any one of: 40%, 30%, 20%, 10%, 5%, 1%, 0%, of the maximum thickness of the secondary element **334**.

A suitable actuation mechanism (not shown) is provided for actuating the secondary element **334** to adopt the range of positive and negative deflection angles desired, including the aforesaid aerodynamic range as well as the aforesaid mechanical range.

In alternative variations of this example, the secondary element **334** can instead be formed as a slotted flap segment, rather than as a continuous flap segment. In such an example, the slotted flap segment can have a slotted flap construction, comprising two or more sub-elements, rigidly connected to one another and separated by minor slot, such that the secondary element still rotates about hinge point **359** as a rigid body.

It is to be noted that the leading edge **338** is also rounded, having a leading edge radius **315**, for providing enhanced high lift characteristics. For example, the leading edge radius **315** can be greater than 1.7% of the chord **C**. In this example, the leading edge radius **315** is about 2% of the chord **C**.

It is also to be noted that the leading end **335** is also rounded, to enable a wide deflection range of deflection angles  $\delta$  while maintaining attached flow over the second element **334**.

- 27 -

Referring in particular to Fig. 4, which illustrates the aerofoil **300** in the pre-deployed configuration **PC**, it is to be noted that the SA aerofoil **300** also has a minimum value for maximum absolute thickness **ABT** that is similar in magnitude to the maximum thickness **t** of the SA aerofoil **300**.

5 By "maximum absolute thickness" is meant the maximum spacing, taken along a direction parallel with the respective pivot axis **PA**, between any point on the upper part of the SA aerofoil **300** with respect to any point on the lower part of the SA aerofoil **300**, including the hinge point **359**.

Such a maximum absolute thickness can be minimized for a given profile of the  
10 SA aerofoil **300** to provide the minimum value for maximum absolute thickness **ABT**, by pivoting the secondary element **334** about the hinge point **359** to a suitable negative deflection angle  $\delta$  such as to minimize the spacing of any part of the secondary element **334** from the chord line **CL** in a direction parallel with the respective pivot axis **PA** (and extending in a downward direction in the view of Fig. 3). For example, such a suitable  
15 negative deflection angle  $\delta$  can be similar to the value of the angle  $\theta$ . For example, such a suitable negative deflection angle  $\delta$  can be for example in the range  $-10^\circ$  to  $-15^\circ$ .

In at least this example, when the deflection angle  $\delta$  is zero for the secondary element **334**, the trailing edge **339** is below the hinge point **359**, while when the deflection angle  $\delta$  is negative such as to provide the minimum value for maximum absolute thickness  
20 **ABT**, the trailing edge **339** is above the hinge point **359**.

In at least this example, in which the hinge point **359** is spaced away from the pressure surface of the secondary element **334** by spacing **FS**, the aforesaid suitable negative deflection angle  $\delta$  is such that all parts of the secondary element **334** are closer to the chord line **CL** than the hinge point **359**. In at least this position, this position of the  
25 secondary element **334** is referred to as the pre-deployed position of the secondary element **334**, corresponding to the pre-deployed configuration **PC**.

Such a minimum value for maximum absolute thickness **ABT** can be further minimized for a given chord **C** of the SA aerofoil **300**, by controlling one or more of the camber, the spacing of the lowest point **301** of the pressure "belly" **310** of the aerofoil  
30 **300** from the chord line **CL**, and maximum aerofoil thickness **t**.

- 28 -

For example, by lowering the camber of the aerofoil **300**, the minimum value for maximum absolute thickness **ABT** can be reduced.

For example, by lowering the spacing of the lowest point **301** of the pressure "belly" **310** of the aerofoil **300** from the chord line **CL**, the minimum value for maximum absolute thickness **ABT** can be reduced.

For example, by lowering the maximum thickness of the aerofoil **300**, the minimum value for maximum absolute thickness **ABT** can be reduced.

On the other hand, lowering the camber of the aerofoil **300**, and/or, lowering the spacing of the lowest point **301** of the pressure "belly" **310** of the aerofoil **300** from the chord line **CL**, and/or, lowering the maximum thickness of the aerofoil **300**, can lead to lowering of the leading edge radius, that conventionally runs counter to general principles when designing a high-lift two element aerofoil.

Referring to Fig. 3, in at least this example, the spacing **BS** of the pressure belly lowermost point **301** from the chord line **CL** of the aerofoil **300**, and the spacing of the flap hinge point **359** from the chord line **CL** of the aerofoil **300**, are similar in magnitude.

In at least this example, for each aerofoil profile **300**, the respective maximum thickness to chord ratio, and the minimum value for the respective maximum absolute thickness to chord ratio have magnitudes that are within 10% of one another. For example at least in this example, the respective maximum thickness to chord ratio, and the minimum value for the respective maximum absolute thickness to chord ratio have magnitudes that are within 1% of the chord **C**.

In at least this example, for each aerofoil profile **300**, the respective maximum thickness to chord ratio is in the range 0.10 to 0.14, for example.

In at least this example, for each aerofoil profile **300**, the respective maximum absolute thickness to chord ratio is in the range 0.10 to 0.15, for example.

In at least this example, each aerofoil profile **300**, in particular the primary element **332** thereof, has a maximum camber of about 6% of the chord **C**. The camber for the aerofoil profile **300**, in particular the primary element **332** thereof, can be determined as  $\Delta y/\text{chord } C$ , with respect to a cartesian coordinate system, wherein for each spacing  $x$

- 29 -

from the leading edge 338 (i.e., each x-coordinate), the value of  $\Delta y$  is determined from the following expression:

$$\Delta y = (y_{upper}(x) + y_{lower}(x))/2$$

wherein  $y_{upper}(x)$  is the y-coordinate of the upper (suction) surface of primary element 332, and wherein  $y_{lower}(x)$  is the y-coordinate of the lower (pressure) surface of primary element 332. Other ways of defining the camber are of course possible. For example, the camber measured this way can change when applying an inclination angle to the chord line CL.

Essentially, and referring in particular to Fig. 3 and Fig. 4, in at least this example, the minimum value of the maximum absolute thickness ABT of the SA aerofoil 300 is actually the minimum height that the aerofoil 300 can adopt, i.e., along a direction parallel to the pivot axis PA. The minimum value of maximum absolute thickness ABT is thus the spacing between a first imaginary line IM1 that tangentially touches the uppermost part of the aerofoil 300, and a second imaginary line IM2 that tangentially touches the lowermost part of the aerofoil 300 including the hinge point 359. In at least this example, the lowermost part of the aerofoil 300 is the hinge point 359 (when the secondary element 334 is at the respective pre-deployed position), but in alternative variations of this example, the hinge point 359 can be closer to the chord line CL, and thus the lowermost part of the aerofoil 300 can be instead the lowest point 301 of the pressure "belly" 310 of the aerofoil 300. The pressure belly 310 can be defined as a portion or point of the primary element 332 that is the most spaced below the chord line CL as seen in the view of Fig. 3.

Thus, the minimum value of maximum absolute thickness ABT of the SA aerofoil 300 is the minimum spacing (in a direction parallel to the pivot axis PA) that is required to be free of obstacles so that the respective wing 220 and aerofoil 300 can pivot about the respective pivot axis PA without colliding with any such obstacles, for example the other wing 220 during deployment from the pre-deployed configuration PC to the deployed configuration DC.

Referring also to Figs. 5(a) to 10(b) the SA profile 300 can be compared with a reference aerofoil profile DA, for example as follows.

- 30 -

The datum aerofoil **DA** is a well known high lift, long endurance two-element aerofoil, for example the Heron tip aerofoil as disclosed in the following publications:

- "Aerodynamic Concept of IAI Long Endurance UAV, by Misha Shepshelovich, dated 25-26 February 2004. The Heron 1 tip slotted aerofoil is shown in Fig. 4 of this publication, having a maximum thickness to chord ratio of 17.5%, and having high lift characteristics (Fig. 3).
- "Aerodynamics of Contaminated UAV Wings, by B. Marcus, M. Sarid and Misha Shepshelovich, dated 25-26 February 2005. The Heron 1 tip slotted aerofoil is shown in Fig. 1 of this publication, having a maximum thickness to chord ratio of 17.5%, and having high lift characteristics (Fig. 9).
- "Ice Accretion of Two-Element High-Lift UAV Wings", by Danny Abramov and Misha Shepshelovich, dated 6-7 March 2013. The Heron 1 tip slotted aerofoil is shown in Fig. 4 of this publication, referred to as the SAT-41 aerofoil, and discussed in page 5 thereof, and having high lift characteristics (Fig. 7).

According to the three publications, the Heron 1 tip slotted aerofoil, provides endurance performance as well as lift characteristics, with a maximum coefficient of lift of between about 2.3 to 2.5, with zero flap deflection.

The SA aerofoil **300**, has significant geometrical/aerodynamic differences with respect to the reference aerofoil profile **DA**, for example as follows.

Referring in particular to Fig. 3 and Fig. 7, the SA aerofoil **300** comprises a camber line **CAM**, that at least in this example peaks at about 6% of the chord **C**, and that at least in this example remains within 5% to 6% of the chord **C** between about 21% to about 60% of the chord **C** from the leading edge **338**. This compares with a camber line for the reference aerofoil profile **DA** that peaks at about 8% of the respective chord, and that remains within 6% to 8% of the chord between about 21% to about 60% of the chord from the respective leading edge. In Fig. 7, the camber of the aerofoil **300** and of the datum aerofoil **DA** are defined in a similar manner.

Referring in particular to Fig. 3 and Fig. 6, the SA aerofoil **300** comprises a thickness distribution, that at least in this example has a maximum thickness **t** of about

- 31 -

13% of the chord **C**, and that at least in this example remains within 10% to 13% of the chord **C** between about 5% to about 50% of the chord **C** from the leading edge **338**. This compares with a thickness distribution for the reference aerofoil profile **DA** that has a maximum thickness **t'** of about 17.5% of the respective chord, and that remains within  
 5 10% to 17.5% of the chord between about 5% to about 50% of the chord from the leading edge.

Referring to Fig. 5(a) and Fig. 5(b), the maximum thickness **t** of the aerofoil **300** is reached at a chord position **ct** less than 25%, or example about 20%, of the chord **C** from the leading edge **338** of the aerofoil **300**. In contrast, the maximum thickness **t'** of  
 10 the datum aerofoil **DA** is reached at a chord position **ct'** of about 30% of the chord from the leading edge **338'** thereof. Furthermore, the leading edge radius **305** of the aerofoil **300** is about 2% of the chord **C** from the leading edge **338** of the aerofoil **300**. In contrast, the leading edge radius **305'** of the datum aerofoil **DA** is about 2.3% of the chord from the leading edge **338'** thereof.

15 Thus, since the maximum thickness **t** of the of the aerofoil **300** is more sharply reduced with respect to the maximum thickness **t'** of the of the datum aerofoil **DA** (17.5% to 13%), as compared to the relatively smaller decrease in respective leading edge radius (2.3% to 2%), the effective leading edge radius to maximum thickness of the aerofoil **300** is significantly larger than that of the datum aerofoil **DA**.

20 Furthermore, and referring again to Fig. 5(a) and Fig. 5(b), the spacing **FS** of the flap hinge point **359** from the secondary element **334** of the aerofoil **300** is significantly smaller than the spacing **FS'** of the flap hinge point **359'** from the secondary element of the datum aerofoil **DA**.

Furthermore, and referring again to Fig. 5(a) and Fig. 5(b), the spacing **BS** of the  
 25 pressure belly lowermost point **301** from the chord line **CL** of the aerofoil **300** is significantly smaller than the spacing **BS'** of the pressure belly **301'** from the chord line **CL'** of the datum aerofoil **DA**. Furthermore, the spacing of the pressure belly lowermost point **301** from leading edge **338** of the aerofoil **300** is significantly smaller than the spacing of the pressure belly lowermost point **301'** from the leading edge **338'** of the  
 30 datum aerofoil **DA**.

- 32 -

Referring also to Fig. 8, the SA aerofoil **300** exhibits a maximum coefficient of lift of about 2.5 at an angle of attack  $\alpha$  of about  $15^\circ$  or  $16^\circ$ , and at least in this example the coefficient of lift is about 1.0 at angle of attack  $\alpha$  of about  $0^\circ$ , and trails off to about 2.1 at angle of attack  $\alpha$  of about  $20^\circ$ . This compares with a maximum coefficient of lift of about 2.5 for the reference aerofoil profile **DA** at an angle of attack  $\alpha$  of about  $13^\circ$  or  $14^\circ$ , and the coefficient of lift is about 1.1 at angle of attack  $\alpha$  of about  $0^\circ$ , and trails off to about 1.95 at angle of attack  $\alpha$  of about  $20^\circ$ . On the other hand, and as can be seen in Fig. 8(a), 8(b), and 8(c), the SA aerofoil **300** exhibits greater drag and greater actuator loads, as compared with the reference aerofoil profile **DA**.

Referring to Fig. 9 and Fig. 10(a), the secondary element **334** is spatially positioned with respect to the primary element **332** to provide a characteristic relationship between the gap size **M1** of gap **355** (between primary element **332** and the secondary element **334**), and the deflection angle  $\delta$  of the secondary element **334** with respect to the primary element **332**. This relationship is illustrated in Fig. 10(a), and shows that the gap size **M1** of gap **355** is at a maximum of about 2.5% of the chord **C** at a deflection angle  $\delta$  of  $-20^\circ$ , and this gap size **M1** reduces to about 2.3% at of the chord **C** at a deflection angle  $\delta$  of  $0^\circ$ , and continues to reduce to about 1.2% of the chord **C** at a deflection angle  $\delta$  of  $30^\circ$ . This compares with a maximum gap size of about 2.9% of the chord for the reference aerofoil profile **DA** at a deflection angle  $\delta$  of  $-20^\circ$ , and this gap size reduces to about 2.4% at of the chord at a deflection angle  $\delta$  of  $0^\circ$ , and continues to reduce to about 1.4% of the chord at a deflection angle  $\delta$  of  $30^\circ$ .

Referring to Figs. 9 and 10(b), the secondary element **334** is spatially positioned with respect to the primary element **332** to provide a characteristic relationship between the longitudinal overlap **M2** (between primary element **332** and the secondary element **334**), and the deflection angle  $\delta$  of the secondary element **334** with respect to the primary element **332**. This relationship is illustrated in Fig. 10(b), and shows that the longitudinal overlap **M2** is at a maximum of about 5.7% of the chord **C** at a deflection angle  $\delta$  of  $-20^\circ$ , and this longitudinal overlap **M2** reduces to about 5% at of the chord **C** at a deflection angle  $\delta$  of  $0^\circ$ , and continues to reduce to about 3% of the chord **C** at a deflection angle  $\delta$  of  $30^\circ$ . This compares with a maximum longitudinal overlap of about 8% of the chord for the reference aerofoil profile **DA** at a deflection angle  $\delta$  of  $-20^\circ$ , and this longitudinal

- 33 -

overlap reduces to about 6% at of the chord at a deflection angle  $\delta$  of  $0^\circ$ , and continues to reduce to about 2% of the chord at a deflection angle  $\delta$  of  $30^\circ$ .

It is considered that the aerofoil **300** can have certain characteristics relative to the aforesaid reference aerofoil profile **DA**, including for example the following:

- 5     ▪ Reduced maximum thickness, and at relative forward position, which together can reduce the maximum absolute thickness, and/or increase maximum lift.
- Reduced maximum camber, which can reduce maximum absolute thickness and can decrease the maximum lift.
- Relatively (to the max. thickness) large leading edge radius to maximum thickness  
10     ratio, which can increase the maximum lift.
- Hinge location nearer the lower flap surface, which can reduce the minimum value for maximum absolute thickness.
- More forward and less pronounced pressure “belly” on the pressure surface of the  
15     aerofoil, which can reduce the minimum value for maximum absolute thickness, and can slightly increase maximum lift.

As mentioned above, the wing system **200** has a stowed configuration **SC**, a pre-deployed configuration **PC** and a deployed configuration **DC**.

Referring to Fig. 1, Fig. 11(a), Fig. 12(a) and Fig. 12(b), in the stowed configuration **SC** the two wings **220P**, **200S** are in a first general superposed spatial relationship with  
20     respect to one another and are capable of being accommodated within an envelope **EV** having an envelope cross-sectional profile **EP** and a corresponding envelope cross-sectional area **EA**. In this configuration, the leading edge of one wing **220** is generally superposed over the trailing edge of the other wing **220**.

Such an envelope **EV** is defined, in at least this example, by the space available in  
25     the fairing **800** for the wing system **200**, once the cross-section of the fuselage **110** has been accounted for. In at least this example, in which the fairing **800** has a circular cross-sectional area, the envelope **EV** is defined as a sector of a circle having a diameter **D** equal to the internal diameter of the fairing **800**.

- 34 -

Thus, the envelope cross-sectional profile **EP** includes an arc portion **EP1** and a chord portion **EP2**, and the envelope cross-sectional area **EA** is given by the area enclosed in the cross-sectional profile **EP**, between the arc portion **EP1** and the chord portion **EP2**.

According to an aspect of the presently disclosed subject matter, each aerofoil profile **300** of the two wings **220P**, **220S** is configured with a minimum respective said absolute thickness **ABT** and a maximum chord **C** such that in said stowed configuration **SC** the respective aerofoil profiles **300** of the two wings **220** in the respective general superposed spatial relationship are capable of being accommodated within the envelope cross-sectional profile **EP** while concurrently maximizing occupancy of the envelope cross-sectional area **EA**. In other words, according to an aspect of the presently disclosed subject matter, each aerofoil profile **300** of the two wings **220P**, **220S** is configured for maximizing occupancy of the envelope cross-sectional area **EA**, while taking account of the shape of the envelope cross-sectional profile **EP** in which the two superposed aerofoils **300** are required to fit into, and while providing high lift characteristics. In general, the lower the maximum thickness **t**, the larger the chord **C** that can be provided, within limits.

In at least this example, this is achieved by designing the two superposed aerofoil sections **300** with a profile having a minimum value for maximum absolute thickness **ABT**, and concurrently with a maximum value for the chord **C**, such that allows the two aerofoils **300** of the two wings **220P**, **220S** in the aforesaid first general superposed spatial relationship to be accommodated within the envelope cross-sectional profile **EP**. This is enhanced by providing reduced maximum thickness, reduced camber, and increased leading edge radius to thickness ratio, as compared with designing an aerofoil of the same chord and general high lift characteristics, but that is not required to fit within the envelope **EV**.

In at least this example, the aerofoil profiles **300** of the two wings **220** have an aggregate cross-sectional area corresponding to an occupancy of between 40% and 30% of said envelope cross-sectional area. In other words, the aerofoil profiles **300** of the two wings **220** have an aggregate cross-sectional area of between 40% and 30% of said envelope cross-sectional area **EA**.

Referring in particular to Fig. 11(a) it is to be noted that a feature of the slotted two-element airfoil nature of aerofoil **300** is that the pivotability of the secondary element **334** allows the secondary element **334** to be pivoted to a large negative deflection angle  $\delta$ , and

- 35 -

thereby effectively reduces the magnitude of the chord **C** to a smaller effective chord **C'** in the stowed configuration **SC**. For example, in the example of aerofoil **300** of Fig. 3, chord **C** is reduced by 13% to provide reduced chord **C'** at a negative deflection angle  $\delta$  for the secondary element **334** of about  $-72^\circ$ . Furthermore, pivoting the secondary element **334** to such a large negative deflection angle  $\delta$  also allows more usage of the space available in the curved part of the arch portion **EP1**, as best seen in Fig. 12(a) in particular for the aerofoil **300** of the lower port wing **220P**.

It is also to be noted that another feature of the slotted two-element airfoil nature of aerofoil **300** is that the pivotability of the secondary element **334** also allows the secondary element **334** of each of the two superposed wings **220S**, **220P** to be pivoted to two negative deflection angles  $\delta$ , different from one another, or for the secondary element **334** of each of the two superposed wings **220S**, **220P** to be pivoted to two positive deflection angles  $\delta$ , different from one another.

For example, in the example illustrated in Fig. 1, in which the wing system **200** is mounted to an underside of the fuselage **110**, the upper wing **220** (for example the starboard wing **220S**) can have a deflection angle  $\delta_1$  in a range  $-25^\circ$  to  $-35^\circ$ , for example about  $-30^\circ$ , for example  $-32^\circ$ , while the lower wing **220** (for example the port wing **220P**) can have a deflection angle  $\delta_2$  in a range  $-55^\circ$  to  $-65^\circ$ , for example about  $-60^\circ$ . This versatility in deflection angles for the wings **220**, and in particular for enabling providing different negative deflection angles  $\delta$  for the two wings **220** in the stowed configuration **SC** allows designing the aerofoil **300** with a larger chord **C** than would otherwise be the case (for example also larger than would be possible with a single element aerofoil). Furthermore, the aforesaid versatility, together with the reduced camber, reduced thickness, and reduced absolute maximum thickness, also allows for maximizing usage of the envelope **EV**, and minimizing the size of such an envelope **EV** as compared for example with the datum aerofoil **300**. In this example, in which the wings **220** are below the fuselage **110**, the room available for the lower wing **220** (in a direction parallel to the chord line **CL**) is less than the room available for the upper wing **220**, in view of the curvature of the arc portion **EP1**. However, rather than having the chord limited by the room available to the lower wing, which would be the case for a single element wing, the presently disclosed subject matter allows for a pair of a two-element aerofoil **300** of relatively larger chord to be fitted, in "nose

- 36 -

to tail" arrangement, in which there can be significant overlap between parts of the two wings in a direction parallel to the pivot axes **PA**. Such overlap is removed when the wing system **200** is transitioned to the pre-deployed configuration **PC**. By "nose to tail" arrangement is meant that the leading edge of each wing **220** (or corresponding aerofoils **300**) is in close  
5 proximity to the trailing edge of the other wing **220** (or corresponding aerofoils **300**).

Also for example, in the example illustrated in Fig. 13, in which the wing system **200** is mounted to an upper side of the fuselage **110**, the upper wing **220** (for example the starboard wing **220S**) can have a positive deflection angle  $\delta 1'$  in a range  $+15^\circ$  to  $+25^\circ$ , for example of about  $+20^\circ$ , while the lower wing **220** (for example the port wing **220P**) can  
10 have a deflection angle  $\delta 2'$  in a range  $+1^\circ$  to  $+10^\circ$ , for example about  $+5^\circ$ . This versatility in deflection angles for the wings **220**, and in particular for enabling providing different positive deflection angles  $\delta$  for the two wings **220** in the stowed configuration **SC** allows designing the aerofoil **300** with a larger chord **C** than would otherwise be the case (for example also larger than would be possible with a single element aerofoil). Furthermore, the  
15 aforesaid versatility, together with the reduced camber, reduced thickness, and reduced absolute maximum thickness, also allows for maximizing usage of the envelope **EV**, and minimizing the size of such an envelope **EV** as compared for example with the datum aerofoil **300**. In this example, in which the wings **220** are above the fuselage **110**, the room available for the lower wing **220** (in a direction parallel to the chord line **CL**) is greater than  
20 the room available for the upper wing **220**, in view of the curvature of the arc portion of the respective envelope. However, rather than having the chord limited by the room available to the upper wing, which would be the case for a single element wing, the presently disclosed subject matter allows for a pair of a two-element aerofoil **300** of relatively larger chord to be fitted, in "nose to tail" arrangement, in which there can be significant overlap between parts  
25 of the two wings in a direction parallel to the pivot axes **PA**. Such overlap is removed when the wing system **200** is transitioned to the pre-deployed configuration **PC**.

It is also to be noted that in the stowed configuration **SC**, it is possible to deflect the respective secondary elements **334** of the two wings to the maximum possible of the respective mechanical ranges, if necessary, to maximize the usage of the envelope. For  
30 example, a respective ratio of the chord **C** to internal diameter **D** of the fairing **800** is in any one of the following ranges: 70% to 90%; 70% to 87%; 75% to 85%.

- 37 -

For example, a respective ratio of the maximum thickness **t** to internal diameter **D** of the fairing **800** is in any one of the following ranges: 7% to 12%; 8% to 11%; 9% to 10%.

For example, a respective ratio of the minimum value of maximum absolute thickness **ABT** to internal diameter **D** of the fairing **800** is in any one of the following ranges:  
5 7% to 12%; 8% to 14%; 7% to 14%.

Referring in particular to Fig 1(a), Fig. 4 and Fig. 11(b), in the pre-deployed configuration **PC** the two wings **220P**, **200S** are in second general superposed spatial relationship with respect to one another and capable of deploying to the deployed configuration **DC**. In this configuration, the leading edge of one wing **220** is generally  
10 superposed over the trailing edge of the other wing **220**.

In this configuration, the two superposed aerofoils **300** have their respective secondary elements **334** pivoted, from the respective deflection angle  $\delta$  corresponding to the stowed configuration **SC**, to a particular negative deflection angle  $\delta$  such that each aerofoil **300** presents a transverse height equal to the minimum value of the maximum absolute  
15 thickness **ABT**. In this and other examples, deflection angle  $\delta$  for the two wings is identical, for example  $-10^\circ$  to  $-15^\circ$ .

It is to be noted that at least in this example, and in other examples, in the stowed configuration **SC** the value of the maximum absolute thickness is greater than the minimum value of the maximum absolute thickness **ABT**. Thus, concurrent with transitioning the  
20 aerofoils **300** from the stowed configuration **SC** to the pre-deployed configuration **PC**, the two superposed aerofoils **300** have their respective secondary elements **334** pivoted such as to reduce the maximum absolute thickness at the stowed configuration **SC** to the minimum value of the maximum absolute thickness **ABT** required for the pre-deployed configuration **PC**.

25 To maximize usage of the envelope **EV** the two aerofoils **300** are stacked at the pivot axis **PA** as close to one another as possible, in which the corresponding first imaginary line **IM1** of the lower aerofoil **300** (i.e., of the port wing **220P**) is at, or spaced close to, the second imaginary line **IM2** of the upper aerofoil **300** (i.e., of the starboard wing **220S**). For example, in the pre-deployed configuration **PC**, the deflection angle  $\delta$  can be set at an angle  
30 in the range between  $-10^\circ$  to  $-15^\circ$ .

- 38 -

Transitioning of the wing system **200** from the stowed configuration **SC** to the pre-deployed configuration **PC** can occur responsive to separating the air vehicle **100** from the fairing **800**. Such separation can occur while the air vehicle **100** is already airborne and travelling at a significant forward speed, for example. Once the fairing **800** is removed, in  
5 the example of Fig. 1, the secondary elements **334** can be pivoted from the large negative deflection angle  $\delta$  corresponding to the stowed configuration **SC**, to a smaller negative deflection angle  $\delta$  corresponding to the pre-deployed configuration **PC**, to thereby enable the respective aerofoils **300** to minimize their respective transverse heights to each equal the maximum absolute thickness **ABT**. Similarly, once the fairing **800** is removed in the  
10 example of Fig. 13, the secondary elements **334** can be pivoted from the respective positive deflection angles  $\delta$  corresponding to the stowed configuration **SC**, to the required negative deflection angle  $\delta$  corresponding to the pre-deployed configuration **PC**, to thereby enable the respective aerofoils **300** to minimize their respective transverse heights to each equal the maximum absolute thickness **ABT**.

15 In each of the two examples, this results in the two stacked wings **220P**, **220S**, being capable of pivoting about their pivot axes **PA** from the pre-deployed configuration **PC** to the deployed configuration **DP** without colliding or otherwise interfering with one another.

It is to be noted that the maximum absolute thickness to chord ratio of each wing **220** is such as to enable the wings **220** to deploy from the pre-deployed configuration **PC** to  
20 the deployed configuration **DC** without interference therebetween.

Fig. 11(b) schematically illustrates an intermediate position as the wings **220** are transitioning from the pre-deployed configuration **PC** to the deployed configuration **DC**.

Referring in particular to Fig. 2 and Fig. 11(b), in the deployed configuration **DC** the wings **220** are now fully deployed, such that the leading edge of the wings are now facing  
25 an airstream **AS**. Such an airstream relative to the wings **220** can be a result of the air vehicle **100** travelling at a significant forward speed in air. For example, the wings **220** are pivoted about their respective axes by about  $90^\circ$  from the pre-deployed configuration **PC**, in which the spans of the wings **220** are substantially parallel to the longitudinal axis of the air vehicle **100**. In the deployed configuration **DC**, each wing **220** is capable of generating aerodynamic  
30 lift **L** in the airstream **AS**, and this enables the air vehicle **100** to be flown in aerodynamic flight mode. In particular, the high lift characteristics of the aerofoils **300** provide high lift

- 39 -

performance to the air vehicle **100**. For example, in the deployed configuration **DC**, the spans of the wings **220** are substantially non-parallel to the longitudinal axis of the air vehicle **100**, for example at  $90^\circ$  to the longitudinal axis of the air vehicle **100** for examples in which the wings **220** are zero-swept wings, or less than  $90^\circ$  for examples in which the wings **220** are swept wings.

It is to be noted that at the commencement of the deployed configuration **DC**, and thus at the end of transitioning from the pre-deployed configuration **PC** to the deployed configuration **DC**, the respective secondary elements **334** of the two wings **220** deployed configuration **DC**, are at a relative large negative deflection angles  $\delta$ , for example  $-10^\circ$  to  $-15^\circ$ . Referring to Fig. 14, this corresponds to a lower coefficient of lift than at deflection angles  $\delta$  of zero, for example, that correspond to cruise conditions. This feature results in relatively low wing loading, as a result of less lift being generated by the wings **220**, as the wings are being suddenly exposed to the air stream, as compared with providing the wings **220** immediately at the beginning of the deployed configuration **DC** with the required deflection angle  $\delta$  of, say, zero. This feature, which is inherent according to an aspect of the presently disclosed subject matter, can enable the wings to be designed lighter than otherwise, since less impact loads can be expected on deployment. Furthermore, this feature can also be taken into account in the design process to design the aerofoil **300** already with a larger negative deflection angles  $\delta$  at the pre-deployed configuration to further reduce initial impact loads at the deployed configuration **DC**. Thus, in at least this example, the secondary elements **334** can be maintained with large negative deflection angles  $\delta$ , for example  $-10^\circ$  to  $-15^\circ$ , until full deployment at the deployed configuration **DC**, and after initial impact loads from the airstream, the secondary elements **334** can be pivoted to zero or positive deflection angles  $\delta$ , according to the lift or performance requirements of the mission, for example cruise or loiter.

It is to be noted that in alternative variations of this example, and in other examples, the fairing can have an internal geometry different from that of a segment of a circle. For example, the corresponding cross-sectional profile **EP** can be for example polygonal (for example rectangular, square, hexagonal and so on), or part of an ellipse, or part of a super-ellipse. In a similar manner to the illustrated example, *mutatis mutandis*, each aerofoil profile **300** of the two wings **220P**, **220S** is similarly configured for maximizing occupancy of the respective envelope cross-sectional area of the envelope, while taking account of the shape

- 40 -

of the envelope cross-sectional profile of the envelope in which the two superposed acrofoils **300** are required to fit into.

It is also to be noted that in yet other alternative variations of this example, and in other examples, the fairing can be omitted, and instead the respective envelope refers instead to a corresponding cross-sectional profile **EP** relating to a container in which the air vehicle **100** can be stored for transport or for safety, until required to be used. In such a container, the air vehicle **100** is accommodated in the respective stowed configuration, and once removed from the container, can be transitioned to the respective pre-deployed configuration, for example by ground crews.

It is further to be noted that in at least one example of the presently disclosed subject matter, in the stowed configuration the corresponding cross-sectional profile **EP** can be limited due to a variety of factors, for example required fuselage cross-section, and the presently disclosed subject matter enables providing two-element acrofoil wings that enable maximizing usage of this limited space.

In the method claims that follow, alphanumeric characters and Roman numerals used to designate claim steps are provided for convenience only and do not imply any particular order of performing the steps.

Finally, it should be noted that the word “comprising” as used throughout the appended claims is to be interpreted to mean “including but not limited to”.

While there has been shown and disclosed examples in accordance with the presently disclosed subject matter, it will be appreciated that many changes may be made therein without departing from the scope of the presently disclosed subject matter as set out in the claims.

**CLAIMS:**

1. A wing system for an air vehicle, the wing system having a stowed configuration, a pre-deployed configuration and a deployed configuration, the wing system comprising:

two wings, each said wing having aerofoil profiles and being pivotably  
5 deployable about a respective pivot axis between the pre-deployed configuration and the deployed configuration, wherein:

in the stowed configuration the two wings are in first general superposed spatial relationship with respect to one another and are capable of being accommodated within an envelope having an envelope cross-sectional profile  
10 and a corresponding envelope cross-sectional area;

in the pre-deployed configuration the two wings are in second general superposed spatial relationship with respect to one another and capable of deploying to the deployed configuration without interfering with one another; and

15 in the deployed configuration the wings are each capable of generating aerodynamic lift in an airstream;

each said aerofoil profile of each wing being a slotted aerofoil having a primary element, a secondary element and a chord, the secondary element being pivotable with respect to the primary element and spaced therefrom by a gap, each  
20 said aerofoil profile having a respective maximum thickness, and a respective maximum absolute thickness;

wherein in said stowed configuration, the respective second element of each said aerofoil of one said wing is set at a different flap angle as compared with the respective second element of each said aerofoil of the other said wing.

25

2. The wing system according to claim 1, wherein said two wings comprise a first said wing having a first said aerofoil profile, the first aerofoil profile comprising a first leading edge and a first trailing edge, and a said second wing having a second said aerofoil profile, the second aerofoil profile comprising a second leading edge and a second trailing

30 edge.

3. The wing system according to claim 2, wherein in said pre-deployed configuration, said first leading edge is generally superposed over said second trailing edge.
- 5 4. The wing system according to any one of claims 1 to 3, wherein a respective maximum absolute thickness to chord ratio of each said wing is such as to enable the wings to deploy from the pre-deployed configuration to the deployed configuration without interference therebetween.
- 10 5. The wing system according to any one of claims 1 to 4, wherein the respective second element of each said aerofoil profile of each said wing has a hinge axis for enabling pivoting of the respective second element with respect to the respective primary element.
- 15 6. The wing system according to claim 5, wherein said hinge axis is facing a pressure surface of the respective secondary element.
7. The wing system according to claim 5 to claim 6, wherein for each said aerofoil profile, the respective hinge axis is spaced from the pressure surface of the respective  
20 secondary element by a spacing.
8. The wing system according to claim 7, wherein said spacing is less than 50% of a maximum thickness of the secondary element.
- 25 9. The wing system according to any one of claims 1 to 8, wherein in said pre-deployed configuration, the respective second element of each said aerofoil profile of each said wing is set at a respective negative flap angle.
- 30 10. The wing system according to any one of claims 1 to 9, wherein in said pre-deployed configuration, the respective second element of each said aerofoil profile of each said wing is set at an identical flap angle.

11. The wing system according to any one of claims 1 to 10, wherein in said pre-deployed configuration, the respective second element of each said aerofoil profile of each said wing is set at a respective first flap angle such that no part of the respective second flap intersects an imaginary line that is tangential to the respective aerofoil leading  
5 edge and that intersects the respective hinge axis.

12. The wing system according to any one of claims 1 to 11, wherein each said aerofoil profile is configured with a minimum respective said absolute thickness and a maximum said chord such that in said stowed configuration the respective said aerofoil  
10 profiles of said two wings in said first general superposed spatial relationship are capable of being accommodated within said envelope cross-sectional profile while concurrently maximizing occupancy of said envelope cross-sectional area.

13. The wing system according to any one of claims 1 to 12, wherein the wing system  
15 is configured for being mounted to an underside of a fuselage of the air vehicle.

14. The wing system according to claim 13, wherein in said stowed configuration, the respective second element of each said aerofoil profile of each said wing is set at a respective negative flap angle.  
20

15. The wing system according to claim 13 to claim 14, wherein in said stowed configuration, the respective second element of each said aerofoil profile of an uppermost said wing is set at a respective negative flap angle in a range  $-25^{\circ}$  to  $-35^{\circ}$ , and wherein the respective second element of each said aerofoil profile of an lowermost said wing is  
25 set at a respective negative flap angle in a range  $-55^{\circ}$  to  $-65^{\circ}$

16. The wing system according to any one of claims 13 to 15, wherein in said stowed configuration, the respective second element of each said aerofoil profile of each said wing is set at a respective second flap angle such that the respective said trailing edge and  
30 the respective hinge axis of the respective second element are on opposite sides of the respective chord line of the aerofoil profile.

17. The wing system according to any one of claims 1 to 12, wherein the wing system is configured for being mounted to an upper side of a fuselage of the air vehicle.
18. The wing system according to claim 17, wherein in said stowed configuration, the  
5 respective second element of each said aerofoil profile of each said wing is set at a respective positive flap angle.
19. The wing system according to claim 13 to claim 14, wherein in said stowed configuration, the respective second element of each said aerofoil profile of an uppermost  
10 said wing is set at a respective positive flap angle in a range  $+15^{\circ}$  to  $+25^{\circ}$ , and wherein the respective second element of each said aerofoil profile of a lowermost said wing is set at a respective positive flap angle in a range  $+1^{\circ}$  to  $+10^{\circ}$ .
20. The wing system according to any one of claims 1 to 19, wherein each said  
15 aerofoil profile has a first maximum spacing of the respective pressure surface from the chord line, and a second maximum spacing of the respective hinge axis from the chord line, wherein said first maximum spacing and said second maximum spacing are within 10% of one another.
- 20 21. The wing system according to any one of claims 1 to 11, wherein for each said aerofoil profile, the respective said maximum thickness to chord ratio, and the respective said maximum absolute thickness to chord ratio have magnitudes that are within 1% of the chord.
- 25 22. The wing system according to any one of claims 1 to 21, wherein for each said aerofoil profile, the respective said maximum thickness to chord ratio is in the range 0.10 to 0.14.
23. The wing system according to any one of claims 1 to 22, wherein for each said  
30 aerofoil profile, the respective said maximum absolute thickness to chord ratio is in the range 0.10 to 0.15.

24. The wing system according to any one of claims 1 to 23, wherein each said aerofoil profile has a respective said maximum thickness at a position less than 25% of the chord from the leading edge of the aerofoil profile.
- 5 25. The wing system according to any one of claims 1 to 24, wherein each said aerofoil profile has a respective said maximum thickness at a position about 20% of the chord from the leading edge of the aerofoil profile.
26. The wing system according to any one of claims 1 to 25, wherein each said  
10 aerofoil profile has a camber profile with a maximum camber of about 6% or less of the chord.
27. The wing system according to any one of claims 1 to 26, wherein for each said aerofoil profile, including at least one of the following:
- 15
- the respective said gap varies between about 2.3% to about 1.2% of the chord, as the respective said flap angle increases from 0° to 30°;
  - the respective said gap varies between about 2.3% to about 2.5% of the chord, as the respective said flap angle decreases from 0° to -20°.
- 20 28. The wing system according to any one of claims 1 to 27, wherein for each said aerofoil profile, the respective leading edge radius is about 2% of the chord.
29. The wing system according to any one of claims 1 to 28, wherein for each said aerofoil profile, the respective said primary element has a primary element trailing edge,  
25 and wherein the respective said secondary element has a secondary element leading edge including one of the following:
- wherein the primary element trailing edge overlaps the secondary element leading edge by a longitudinal overlap in a direction parallel to the chord;
  - wherein the primary element trailing edge overlaps the secondary element leading  
30 edge by a longitudinal overlap in a direction parallel to the chord, and, the respective said longitudinal overlap varies between about 5% to about 3% of the chord, as the respective said flap angle increases from 0° to 30°;

- wherein the primary element trailing edge overlaps the secondary element leading edge by a longitudinal overlap in a direction parallel to the chord, and, wherein for each said aerofoil profile, the respective said longitudinal overlap varies between about 5% to about 5.5% of the chord, as the respective said flap angle decreases from 0° to -20°.

30. The wing system according to any one of claims 1 to 29, wherein each said aerofoil profile is configured as a high lift aerofoil profile.

31. The wing system according to claim 30, wherein said aerofoil profile is configured as having a maximum lift coefficient of at least 2.5 at zero flap angle.

32. The wing system according to claim 30, wherein said aerofoil profile is configured as having a maximum lift coefficient of greater than 2.3 at zero flap angle.

33. The wing system according to any one of claims 31 to 32, wherein said maximum lift coefficient corresponds to an angle of attack of between about 15° and about 16°.

34. The wing system according to any one of claims 1 to 33, wherein said aerofoil profile is configured as having a lift coefficient of 1.0 corresponds to an angle of attack of about 0°.

35. The wing system according to any one of claims 1 to 34, wherein said aerofoil profiles of said two wings have an aggregate cross-sectional area corresponding to a said occupancy of between 40% to 30% of said envelope cross-sectional area.

36. The wing system according to any one of claims 1 to 35, wherein said envelope cross-sectional profile is in the form of a segment of a circle of predetermined diameter, the segment being defined by a corresponding arc portion and a corresponding chord portion.

37. The wing system according to claim 36, wherein for each said aerofoil profile, a respective first ratio of said chord to said diameter is in the range 70% to 87%.

**38.** The wing system according to claim 37, wherein for each said aerofoil profile, the respective first ratio is in the range 75% to 85%.

5 **39.** The wing system according to any one of claims 36 to 38, including at least one of the following:

- wherein for each said aerofoil profile, a respective second ratio of said maximum thickness to said diameter is in the range 7% to 12%;
- wherein for each said aerofoil profile, a respective second ratio of said  
10 maximum absolute thickness to said diameter is in the range 8% to 14%.

**40.** The wing system according to any one of claims 1 to 39, wherein each said wing is configured with zero taper, and wherein each wing has a uniform said aerofoil profile along a respective span thereof.

15

**41.** The wing system according to any one of claims 1 to 39, wherein each said wing is configured with non-zero taper, and wherein each wing has a uniform said aerofoil profile along a respective span thereof.

**42.** The wing system according to any one of claims 1 to 41, configured for selectively  
20 enabling the wings to transition from the stowed configuration to the pre-deployed configuration under predetermined conditions.

**43.** The wing system according to any one of claims 1 to 42, configured for maintain a negative said deflection angle for each aerofoil of each wing during deployment from the pre-deployed configuration through to the deployed configuration.

25

**44.** A wing system for an air vehicle, the wing system having at least a stowed configuration, a pre-deployed configuration and a deployed configuration, the wing system comprising:

30 two wings, each said wing being pivotably deployable about a respective pivot axis between the pre-deployed configuration and the deployed configuration, wherein:

in the stowed configuration the two wings are in first general superposed spatial relationship with respect to one another and are capable

of being accommodated within an envelope having an envelope cross-sectional profile and a corresponding envelope cross-sectional area; and

in the pre-deployed configuration the two wings are in second general superposed spatial relationship with respect to one another and capable of deploying to the deployed configuration; and

in the deployed configuration the wings are each capable of generating aerodynamic lift in an airstream;

each said wing having a span and an aerofoil profile at least at one respective transverse cross-section orthogonal to the respective span;

each said aerofoil profile being a slotted aerofoil having a primary element, a secondary element and a chord, the secondary element being pivotable with respect to the primary element and spaced therefrom by a gap, each said aerofoil profile having a respective maximum thickness, and a respective maximum absolute thickness;

wherein each said aerofoil profile is configured with a minimum respective said absolute thickness and a maximum said chord such that in said stowed configuration the respective said aerofoil profiles of said two wings in said first general superposed spatial relationship are capable of being accommodated within said envelope cross-sectional profile while concurrently maximizing occupancy of said envelope cross-sectional area.

**45.** An air vehicle, comprising the wing system as defined in any one of claims 1 to 44.

**46.** The air vehicle according to claim 45, wherein the air vehicle is a UAV.

**47.** A launch system comprising an air vehicle as defined in claim 45 or claim 46, accommodated in a fairing having an internal chamber defining said envelope, said envelope cross-sectional profile and said envelope cross-sectional area.

**48.** The launch system according to claim 47, configured for selectively releasing said air vehicle from said fairing.

- 49.** The launch system according to claim 48, configured for selectively transitioning the wing system from the stowed configuration to the pre-deployed configuration following release of said air vehicle from said fairing.
- 5 **50.** The launch system according to claim 49, configured for selectively transitioning the wing system from the pre-deployed configuration to the deployed configuration and for subsequently enabling aerodynamic flight of the air vehicle.