

Coaxial connector for connection to a printed circuit board

This invention relates to a coaxial connector comprising at least one outermost and one innermost contact socket or pin, mutually electrically insulated and surrounded by a housing, and having connecting portions of electrically conducting material for connecting the coaxial connector to a printed circuit board, the outermost contact socket being electrically connected to an outer connecting portion for connecting it to said printed circuit board and the innermost contact socket or pin having an inner connecting portion for connecting it to said printed circuit board.

Such a coaxial connector is known from the German patent application 3.620.111, which comprises an additional contact case inserted into the outermost contact socket in order to establish good electrical and mechanical contact. The additional contact case is provided with two contact strips extending from the case and suitable to be soldered to contact pads on a predetermined side of a printed circuit board. The innermost contact socket is provided with an inner contact strip extending beyond the case and suitable to be soldered to the same predetermined side of the printed circuit board.

United States patent 3.958.852 describes a connector having one side that can be connected to several coaxial plugs of coaxial cables and one side that can be connected to a printed circuit board or the like. This connector therefore serves as an intermediate between coaxial cables and a printed circuit board or the like. The side of the connector to be connected to the circuit board or the like is provided with an inner conductor and an outer conductor between which the printed circuit board can be inserted, both the inner and the outer conductor being arranged to establish good electrical and mechanical contact with predetermined contact pads on the printed circuit board.

United States patent 3.689.865 discloses a connector having a first side connected to several coaxial cables and a second side into which a printed circuit board or the like can be inserted. The connector comprises a plurality of inner contact members being soldered to respective inner conductors of the coaxial cables and to respective metallic pads on a small internal printed circuit

board. The inner contact members are arranged to establish electrical contact to contact pads on a predetermined side of the printed circuit board or the like. One outer contact member is provided to establish good electrical contact to a ground plane on the opposite side of the printed circuit board or the like. The one outer contact member is soldered to the small internal printed circuit board through a foil layer at its rear side. Moreover, the outer conductors of all coaxial cables are electrically connected to the second contact member.

A connector module generally comprises a housing of electrically insulative material which accommodates a plurality of contact elements or terminals arranged in rows and columns. The contact elements have a base section and a contact end and connecting end extending from opposite ends of the base section. The connecting ends project outside one side of the housing and are connected to a printed circuit board.

There have long been attempts to accommodate electronic circuits in as modular a design as possible on printed circuit boards of standard dimensions. The interconnections between the individual modules and components, such as recorders, playback devices, etc., are preferably made via electronic connectors. As a consequence of miniaturization and due to the high density of present day integrated circuits, a large number of electronic components can be mounted on a printed circuit board so that a large number of functions can be carried out by a module of this type. The number of terminals needed for connection to other modules has, likewise, increased.

As a result, there is a great need for connectors with a high contact element density, i.e., with a large number of electrical contacts or terminals per unit of volume. The need for connectors with high contact element density has become even greater as a result of the advent of surface mounting technology whereby electronic components are surface mounted to the printed circuit board. Surface mounted devices (SMD) are not mounted on a printed circuit board via the usual pinhole connection but are connected directly to the surface of the printed circuit itself. By surface mounting techniques, it is possible to mount electronic components readily on either surface of a board without interfering with connecting

pins which project through the board. This results in a component density which is even higher than that achieved with conventional pinhole connections and a further increase in the number of terminals.

5 The object of the present invention is to provide a coaxial connector of a type defined in the preamble of claim 1 which is able to contact at least one contact pad on a predetermined side of a printed circuit board by its at least one innermost contact socket or pin and to contact the opposite side of the printed circuit board by the at least one outermost contact socket by a surface mounting technique.

10 Therefore, the coaxial connector according to the present invention is characterized in that said outer connecting portion and said inner connecting portion are arranged to contact opposite sides of said printed circuit board by a surface mounting technique, said outer connecting portion being integrally made with said outermost contact socket and said inner connecting portion being integrally made with said innermost contact socket or pin. Connectors designed in this manner possess sufficient mechanical stability and a sufficiently large contact surface so that reliable and mechanically stable connections with a printed circuit board can be made by surface mounting technique.

15 In a preferred embodiment the coaxial connector according to the invention is characterized in that the outer connecting portion of the outermost contact socket is a substantially half-cylindrical portion of said outermost contact socket extending outside the housing and the inner connecting portion of the innermost contact socket or pin is a connecting tongue. Such a connector can be easily manufactured from existing coaxial connectors by removing a part of the connecting end of the outermost contact socket from the circumference, and by removing part of the jacket of the innermost contact socket or pin.

20 Several coaxial connectors according to the invention can be accommodated in a single module housing.

25 In a further embodiment of the invention such a connector module housing may comprise at least one power connector, the latter comprising at least one contact socket or contact pin, surrounded by a housing, with an elongated connecting portion of elec-

trically conducting material for connecting the power connector to a printed circuit board, said connecting portion being provided with a slot-shaped opening in which the printed circuit board can be received for connecting the power connector to one or both flat sides of said board by a surface mounting technique.

In this application, the term "printed circuit board", which is also commonly referred to as "printing wiring board", is understood as meaning, in general, substrates with conducting tracks and thus, for example, also substrates of liquid crystal displays.

In the text which follows, the invention will be illustrated by reference to a single drawing of a preferred embodiment of a coaxial connector for surface mounting technique.

The single figure shows diagrammatically in perspective power and coaxial connectors connected surface mounted to a printed wiring board.

The figure shows diagrammatically in perspective and in partially cut-away view, power connectors 40, 41 and coaxial connectors 46, 47 for connecting by surface mounting feed cables and coaxial cables to a printed circuit board. Connectors described in the parent European patent application 0,393,251 are less suitable for connecting feed cables carrying a relatively large current.

The unipolar power connector 40 is essentially constructed from a contact socket 42 of electrically conducting material having a spring-loaded contact end for receiving a contact pin and an elongated socket-shaped connecting end 43 for connection to a printed wiring board. The power connector 41 has a pin-shaped contact end 52 and a similar socket-shaped connecting end 43. In order to make it possible to connect the connecting end to a printed circuit board by surface mounting, the elongate connecting end 43 is provided, according to the invention, with a slot-shaped recess 45 in which the printed circuit board 2 may be received so that the connecting end 43 can be connected to the printed circuit board 2 at the two opposite flat sides thereof.

For connecting coaxial plugs, coaxial connectors 46, 47 are used in practice. These connectors have an elongated outermost contact socket 48 and innermost contact socket 49 which are electrically insulated from each other and respectively an outermost contact socket and an innermost contact pin (not shown) of electri-

cally conducting material.

To permit surface mounting of the coaxial connectors to a printed circuit board, a part of the connecting end of the outermost contact socket 48 is removed from the circumference so that the remaining, virtually semicylindrical connecting end 50 can be connected to one side of the printed circuit board 2. Part of the jacket of the innermost contact socket 49, or the innermost contact pin, is removed so that the remaining connecting tongue 51 can be connected to the other side of the printed circuit board 2.

The connectors designed in this manner possess sufficient mechanical stability and a sufficiently large contact surface so that reliable and mechanically stable connections with a printed circuit board can be made by surface mounting technique. In practice, of course, it is possible, as a departure from the embodiments shown in the figure, for several coaxial connectors and/or several power connectors to be accommodated in a single module housing.

It will be clear that the invention is not limited to the preferred embodiment thereof described and shown in the drawing, but that other variations and modifications are possible. For example, the connector modules may include optoelectronic connectors connected to optical fiber cables, shielded connectors, to locking means or so called polarity indicators to prevent incorrect connection of the connector modules, etc., all without deviating from the scope of the invention which is defined by the claims.

Claims

1. A coaxial connector comprising at least one outermost (48) and one innermost contact socket or pin (49), mutually electrically insulated and surrounded by a housing, and having connecting portions of electrically conducting material for connecting the coaxial connector to a printed circuit board (2), the outermost contact socket (48) being electrically connected to an outer connecting portion (50) for connecting it to said printed circuit board and the innermost contact socket or pin (49) having an inner connecting portion (51) for connecting it to said printed circuit board characterized in that said outer connecting portion (48) and said inner connecting portion (49) are arranged to contact opposite sides of said printed circuit board by a surface mounting technique, said outer connecting portion (50) being integrally made with said outermost contact socket (48) and said inner connecting portion (51) being integrally made with said innermost contact socket or pin (49).

2. A coaxial connector according to claim 1 characterized in that the outer connecting portion (50) of the outermost contact socket is a substantially half-cylindrical portion of said outermost contact socket extending outside the housing and the inner connecting portion (51) of the innermost contact socket or pin (49) is a connecting tongue.


3. A connector module housing comprising several coaxial connectors according to claim 1 or 2.

4. A connector module housing according to claim 3 furthermore comprising at least one power connector (40; 41), the latter comprising at least one contact socket or contact pin (42; 52), surrounded by a housing, with an elongated connecting portion (43) of electrically conducting material for connecting the power connector to a printed circuit board (2), said connecting portion being provided with a slot-shaped opening (45) in which the printed circuit board can be received for connecting the power connector to



one or both flat sides of said board by a surface mounting technique.





Abstract

5 A coaxial connector comprising at least one outermost (48)
and one innermost contact socket or pin (49), mutually electrically
insulated and surrounded by a housing, and having connecting por-
tions of electrically conducting material for connecting the
coaxial connector to a printed circuit board (2), the outermost
contact socket (48) being electrically connected to an outer con-
necting portion (50) for connecting it to said printed circuit
10 board and the innermost contact socket or pin (49) having an inner
connecting portion (51) for connecting it to said printed circuit
board, said outer connecting portion (48) and said inner connecting
portion (49) being arranged to contact opposite sides of said
printed circuit board by a surface mounting technique, said outer
15 connecting portion (50) being integrally made with said outermost
contact socket (48) and said inner connecting portion (51) being
integrally made with said innermost contact socket or pin (49).

20 [fig.]

This Sheet Has Been Replaced



9608634-3
JPO's copy

THIS SHEET HAS BEEN
REPLACED

REPLACEMENT SHEET

17 JAN 1997

8

COAXIAL CONNECTOR FOR CONNECTION TO A PRINTED CIRCUIT BOARD

Abstract

A coaxial connector comprising at least one outermost (48) and one innermost contact socket or pin (49), mutually electrically insulated and surrounded by a housing, and having connecting portions of electrically conducting material for connecting the coaxial connector to a printed circuit board (2), the outermost contact socket (48) being electrically connected to an outer connecting portion (50) for connecting it to said printed circuit board and the innermost contact socket or pin (49) having an inner connecting portion (51) for connecting it to said printed circuit board, said outer connecting portion (48) and said inner connecting portion (49) being arranged to contact opposite sides of said printed circuit board by a surface mounting technique, said outer connecting portion (50) being integrally made with said outermost contact socket (48) and said inner connecting portion (51) being integrally made with said innermost contact socket or pin (49).

FIGURE 1

This Sheet Has Been Replaced





TEXT OF THE ABSTRACT

COAXIAL SYSTEMS TECHNOLOGY N.V.

A coaxial connector includes an outermost contact socket (48) electrically connected to an outer connecting portion (50) to connect it to the printed circuit board and the innermost contact socket or pin (49). It has an inner connecting portion (51) which connects it to the printed circuit board.

The outer and the inner connecting portion (48 and 49) contact opposite sides of the printed circuit board using a surface mounting technique. The outer connecting portion is made integrally with the inner connecting portion and is made integrally with the innermost socket or pin (49).

This is the replacement sheet

Date: 27 OCT 1998