

CLAIMS

1. A method for controlling a sliding control, the method comprising:
receiving an instruction associated with a first sliding control, the first sliding control located on a first side of a second sliding control, wherein the instruction instructs the first sliding control to be slid to a second side of the second sliding control; and
sliding the first sliding control to the second side of the second sliding control in response to receiving the instruction, wherein sliding the first sliding control to the second side of the second sliding control comprises sliding the first sliding control to the second side of the second sliding control by moving the first sliding control through a location at which the second sliding control is located while preventing the first sliding control from overlapping with the second sliding control.
2. The method according to claim 1, wherein the instruction is received in response to a drag operation performed on the first sliding control.
3. The method according to claim 1, wherein the first sliding control and the second sliding control are located on a same sliding track.
4. The method according to any one of claims 1-3, wherein moving the first sliding control follows along a sliding track that is configured to specify a value interval; and
the first sliding control and the second sliding control are configured to select a value subinterval from the value interval.
5. The method according to claim 4, wherein, further comprising after sliding the first sliding control to the second side of the second sliding control,
determining, based on a location of the first sliding control on the sliding track and the location of the second sliding control on the sliding track, the value subinterval selected from the value interval.
6. The method according to claim 4, wherein each value in the value interval corresponds to

at least one location on the sliding track.

7. The method according to any one of claims 1 to 6, wherein the first sliding control and the second sliding control are slider controls.

8. The method according to any one of claims 1 to 3, wherein the first sliding control and the second sliding control are sliding handle controls configured to select a page element displayed on a page on which the first sliding control and the second sliding control are located; and

after the sliding the first sliding control to the second side of the second sliding control, the method further comprises:

determining, based on a location of the first sliding control obtained after sliding and the location of the second sliding control, the page element selected by using the first sliding control and the second sliding control.

9. The method according to any one of claims 4 to 6, wherein the sliding track is a horizontal track, a vertical track or a curve track.

10. The method according to any one of claims 4 to 6, wherein
the sliding track is a loop sliding track, and
the sliding the first sliding control is sliding the first sliding control to the second side of the second sliding control in an opposite direction of the second sliding control on the loop sliding track.

11. A device for controlling a sliding control, the device comprising a plurality of modules configured to perform the method of any one of claims 1 to 10.