

Description

This invention relates to ovenware, and particularly to cooking pans which are to be used in the circumstances where foodstuffs are likely to adhere to one or more surfaces thereon. The invention has an immediately apparent application in pans which are to be heated on a stove, but is also suitable for ovenware.

A continuing problem with cooking utensils of all kinds is that foodstuff will tend to adhere to heated surfaces. This is a particular problem in frying pans and other vessels which are used on a stove, but one which also develops on pans used in oven cooking. In recent years, various attempts have been made to produce surfaces for such pans to which foodstuff will not adhere or will not readily adhere in the cooking process, and the most effective of these has been the provision of "non-stick" surfaces. The most commonly used material for such "non-stick" surface is polytetrafluoroethylene (PTFE).

Cooking utensils, particularly for toasting and grilling, have also been designed with ribbed or uneven surfaces to maintain a piece of food spaced from the body of the utensil. Examples of such utensils are disclosed in U.S. Patent No. 2,875,683 (Burns); and British Patent Nos. 372,025 (Bells), 422,378 (Moneta), 742,484 (Knight), Swiss CH-A-274,184 (Kroyer) and DE-U-1,934,269 (Alcan). However, support for food in these utensils is often unsatisfactory, and they render the use of cooking implements on the surface rather difficult.

Kroyer in particular discloses a cooking pan with isolated dimples and depressions of relatively large diameter 3-10mm ($1/8'' - 3/8''$) and depth 1mm ($1/25''$). Kroyer is aimed at providing a more uniform cooking surface with a more even heat transfer using less oil but it neither minimizes food sticking nor lengthens the life of the cooking surface.

Alcan discloses a pan-type cooking vessel in which the surface of the utensil that comes into contact with the food being cooked is so profiled that the area of contact is only relatively small, however there is no suggestion of the small pitch spacing of the present invention.

While the provision of "non-stick" surfaces alone is effective, such surfaces have a limited life. In normal use, it is almost inevitable that they will become scratched, and over a period of time, the surface will be broken, and partially or totally removed.

Accordingly the present invention provides a cooking or a frying pan comprising a base having an outer heat receiving surface and an inner or upper contact surface for engaging the food to be cooked, wherein the contact surface is formed with

corrugations defining closely spaced peaks in a substantially common plane, the corrugations forming a definable pattern, a non-stick material being applied to the corrugated surface, characterized in that the corrugated contact surface defines concentric circular grooves and wherein the pitch spacing of the corrugations does not exceed 2 mm. When using a pan of the present invention, the degree of adherence of foodstuffs is reduced as a consequence of the reduced area of contact, and during cleaning and/or removal of any foodstuff that has so adhered, contact between any cleaning tool or device is concentrated at the peaks. The troughs or valleys are thus left relatively unscathed, and any surface thereon is substantially preserved.

The presence of a "non-stick" surface reduces any tendency of foodstuffs to adhere in the troughs of the corrugations, and the "non-stick" characteristics of the surface in the troughs is better preserved as cleaning tools and devices are unlikely to make contact therewith. Also, during cleaning, any scratching that is caused will be substantially restricted to the peaks of the corrugations, reducing the area of surface to which foodstuff is likely to adhere, even as the "non-stick" surface is eroded. As the peaks are worn away by cleaning, the base material is only progressively revealed as initially, only the "non-stick" material on the walls of the corrugations is exposed. If the primary material of the cooking pan base is of a particularly hard resilient material, then this erosion of the corrugations is very slow, and the useful life of cooking pan according to this embodiment of the invention can therefore be considerable.

A preferred primary material for cooking pans according to the invention, particularly frying pans, is anodized aluminium. Other materials such as steel, stainless steel or cast iron can though, be used quite satisfactory, as can the use of materials which are surface hardened only, and laminates. Such a laminate might be a steel clad aluminium sandwich base for a pan particularly for use on electric stoves.

The lower surface of pans according to the invention can be selected for the intended use of a pan. A pan for use on an electric stove should normally have a substantially flat base for good conductive contact with an heating element, but for other uses irregular surfaces can be satisfactory.

Normally, the pitch spacing of the corrugations is no more than 1mm, preferably less.

The invention will now be described, by way of example, and with reference to the accompanying drawings, wherein:

Figure 1 shows a perspective view of a frying pan embodying the invention;

Figure 2 shows a plan view of the frying pan of Figure 1;

Figure 3 shows an enlarged cross section of a portion of the frying pan base; and

Figure 4 shows a perspective view of a saucepan or baking pan embodying the invention

The frying pan shown in Figure 1 is of conventional overall design and comprises a body 2 and a handle 4. The body has a lower heat receiving surface (not visible), and an upper cooking surface 6. The upper cooking surface 6 is formed with a plurality of closely spaced corrugations 8, shown more clearly in figures 2 and 3.

The pan body itself is normally made from a single piece of material, either cast or machined, and can be adapted for use either with open flame stoves (gas) or electric (unit or "smooth-top") cookers where the underside of the pan will be machined flat to ensure good contact with the electric heat source.

The corrugations shown in Figure 2 are in the form of concentric circles. Circular corrugations have the attraction of being easily machined into the surface of the pan and having no sharp bends therein.

A pan made of a suitable material and being formed with corrugations according to the invention offers substantial advantages over known flat surfaced pans. These benefits are enhanced by the application of a "non-stick" material to the corrugated surface. The construction of a pan base according to the invention, and with such a surface, is shown in more detail in Figure 3.

As shown in Figure 3, the body of the pan is formed with surface corrugations 8. These can be ground or machined into the surface by conventional means, and the sharp corners at the peaks and troughs have been removed. A continuous layer 10 of polytetrafluorethylene is then applied to the corrugated surface, also in a manner known per se. Again, these sharp corners at the peaks and troughs of the corrugations are removed such that the exposed cooking surface is relatively smooth. Towards the right of the figure, the results of long use and abrasive cleaning is illustrated. As can be seen, the peaks of the two corrugations 8a and 8b have been worn away, but only the peak corrugation 8b is worn away to such an extent that the base metal of the body 2 is exposed. Initial wear increases the exposed area of "non-stick" surface, and even after prolonged wear only a small area of the base material is exposed. Once the base material is exposed, then as this material (e.g. anodized aluminium) is considerably harder and more resilient than the "non-stick" material, the rate of further erosion of the corrugation peaks is reduced. It will be noted that in the valleys of the corrugations, the "non-stick" material will suffer little if any erosion.

It will be appreciated that the corrugated surface can extend into and up the side wall or side walls of a cooking pan, and this will be a particular benefit in ovenware. While the invention has been particularly described in connection with a frying pan, it is readily adapted for use in other pans or indeed, any cooking utensil in which adherence of foodstuffs to a surface is a problem. For example, it may also be embodied in griddle pans which are a permanent component of a piece of cooking apparatus.

Another example is shown in Figure 4, where a saucepan or baking pan is provided with a cooking surface 6 having a pattern of corrugations in the form of a plurality of concentric circular grooves 12 superimposed on an overall pattern of grooves 14. The side wall 16 of the pan is formed with straight corrugations 18. Between the corrugations 16 and the grooves 12 and 14 at the junction between the side wall and the cooking surface, a smooth annular area 20 is formed. This region is least subject to contact by cooking implements, and a smooth surface here is sufficient to minimize adherence of foodstuffs thereto. All the inner surfaces may be coated with a non-stick surface to achieve the additional benefits of the invention as described above. The inclusion of a smooth annular region 20 can be incorporated in all embodiments of the invention between the contact surface 6 and a side wall of the pan.

Claims

1. A cooking or a frying pan (2,4) comprising a base having an outer heat receiving surface and an inner or upper contact surface (6) for engaging the food to be cooked, wherein the contact surface is formed with corrugations (8) defining closely spaced peaks in a substantially common plane, the corrugations (8) forming a definable pattern, a non-stick material (10) being applied to the corrugated surface, characterized in that the corrugated contact surface defines concentric circular grooves (12,14) and wherein the pitch spacing of the corrugations does not exceed 2 mm.
2. A pan according to Claim 1 characterized in that the pitch spacing of the corrugations (8) does not exceed 1 mm.
3. A pan according to Claims 1 or 2 characterized in that the corrugated surface defines concentric circular grooves (14) around the centre of the base.
4. A pan according to Claim 1 to 3 characterized in that that definable pattern comprises a plu-

Figure 3 shows an enlarged cross section of a portion of the frying pan base; and

Figure 4 shows a perspective view of a saucepan or baking pan embodying the invention

The frying pan shown in Figure 1 is of conventional overall design and comprises a body 2 and a handle 4. The body has a lower heat receiving surface (not visible), and an upper cooking surface 6. The upper cooking surface 6 is formed with a plurality of closely spaced corrugations 8, shown more clearly in figures 2 and 3.

The pan body itself is normally made from a single piece of material, either cast or machined, and can be adapted for use either with open flame stoves (gas) or electric (unit or "smooth-top") cookers where the underside of the pan will be machined flat to ensure good contact with the electric heat source.

The corrugations shown in Figure 2 are in the form of concentric circles. Circular corrugations have the attraction of being easily machined into the surface of the pan and having no sharp bends therein.

A pan made of a suitable material and being formed with corrugations according to the invention offers substantial advantages over known flat surfaced pans. These benefits are enhanced by the application of a "non-stick" material to the corrugated surface. The construction of a pan base according to the invention, and with such a surface, is shown in more detail in Figure 3.

As shown in Figure 3, the body of the pan is formed with surface corrugations 8. These can be ground or machined into the surface by conventional means, and the sharp corners at the peaks and troughs have been removed. A continuous layer 10 of polytetrafluorethylene is then applied to the corrugated surface, also in a manner known per se. Again, these sharp corners at the peaks and troughs of the corrugations are removed such that the exposed cooking surface is relatively smooth. Towards the right of the figure, the results of long use and abrasive cleaning is illustrated. As can be seen, the peaks of the two corrugations 8a and 8b have been worn away, but only the peak corrugation 8b is worn away to such an extent that the base metal of the body 2 is exposed. Initial wear increases the exposed area of "non-stick" surface, and even after prolonged wear only a small area of the base material is exposed. Once the base material is exposed, then as this material (e.g. anodized aluminium) is considerably harder and more resilient than the "non-stick" material, the rate of further erosion of the corrugation peaks is reduced. It will be noted that in the valleys of the corrugations, the "non-stick" material will suffer little if any erosion.

It will be appreciated that the corrugated surface can extend into and up the side wall or side walls of a cooking pan, and this will be a particular benefit in ovenware. While the invention has been particularly described in connection with a frying pan, it is readily adapted for use in other pans or indeed, any cooking utensil in which adherence of foodstuffs to a surface is a problem. For example, it may also be embodied in griddle pans which are a permanent component of a piece of cooking apparatus.

Another example is shown in Figure 4, where a saucepan or baking pan is provided with a cooking surface 6 having a pattern of corrugations in the form of a plurality of concentric circular grooves 12 superimposed on an overall pattern of grooves 14. The side wall 16 of the pan is formed with straight corrugations 18. Between the corrugations 16 and the grooves 12 and 14 at the junction between the side wall and the cooking surface, a smooth annular area 20 is formed. This region is least subject to contact by cooking implements, and a smooth surface here is sufficient to minimize adherence of foodstuffs thereto. All the inner surfaces may be coated with a non-stick surface to achieve the additional benefits of the invention as described above. The inclusion of a smooth annular region 20 can be incorporated in all embodiments of the invention between the contact surface 6 and a side wall of the pan.

Claims

1. A cooking or a frying pan (2,4) comprising a base having an outer heat receiving surface and an inner or upper contact surface (6) for engaging the food to be cooked, wherein the contact surface is formed with corrugations (8) defining closely spaced peaks in a substantially common plane, the corrugations (8) forming a definable pattern, a non-stick material (10) being applied to the corrugated surface, characterized in that the corrugated contact surface defines concentric circular grooves (12,14) and wherein the pitch spacing of the corrugations does not exceed 2 mm.
2. A pan according to Claim 1 characterized in that the pitch spacing of the corrugations (8) does not exceed 1 mm.
3. A pan according to Claims 1 or 2 characterized in that the corrugated surface defines concentric circular grooves (14) around the centre of the base.
4. A pan according to Claim 1 to 3 characterized in that that definable pattern comprises a plu-



ality of groups of concentric grooves (12) superimposed on an overall pattern of grooves (14).

5. A pan according to any preceding Claim characterized in that the base material between the outer and contact surfaces is anodized aluminum.
6. A pan according to any preceding Claim characterized in that the base is substantially circular and has an upstanding side wall integral therewith, the corrugated contact surface terminating at the junction between the base and side wall.
7. A pan according to any of Claims 1 to 5 characterized in that the base is substantially circular and has an upstanding side wall integral therewith, the corrugated surface extending onto the side wall.
8. A pan according to any of claims 1 to 5 characterized in that the base is substantially circular and has an upstanding side wall integral therewith, the side wall and base both being provided with the corrugated surface and there being provided an annular region between the side wall and base, which region is substantially smooth.
9. A pan according to any preceding Claim characterized in that "non-stick" surface comprises polytetrafluoroethylene (PTFE).

Revendications

1. Ustensile de cuisine (2, 4) pour cuire ou frire, comprenant une base ayant une surface externe de réception de chaleur et une surface interne ou supérieure (6) de contact destinée à être au contact de l'aliment à cuire, dans lequel la surface de contact est réalisée avec des ondulations (8) qui délimitent des crêtes très rapprochées, dans un plan sensiblement commun, les ondulations (8) formant un dessin définissable, un matériau anti-adhérent (10) étant appliqué à la surface ondulée, caractérisé en ce que la surface ondulée de contact délimite des gorges circulaires concentriques (12, 14), et le pas des ondulations ne dépasse pas 2 mm.
2. Ustensile selon la revendication 1, caractérisé en ce que le pas des ondulations (8) ne dépasse pas 1 mm.
3. Ustensile selon la revendication 1 ou 2, caracté-

térisé en ce que la surface ondulée délimite des gorges circulaires concentriques (14) autour du centre de la base.

4. Ustensile selon les revendications 1 à 3, caractérisé en ce que le dessin définissable comprend plusieurs groupes de gorges concentriques (12) superposées à un dessin global de gorges (14).
5. Ustensile selon l'une quelconque des revendications précédentes, caractérisé en ce que le matériau de la base, entre les surfaces externe et de contact, est l'aluminium anodisé.
6. Ustensile selon l'une quelconque des revendications précédentes, caractérisé en ce que la base est sensiblement circulaire et a une paroi latérale qui en dépasse et en est solidaire, la surface ondulée de contact aboutissant au raccord entre la base et la paroi latérale.
7. Ustensile selon l'une quelconque des revendications 1 à 5, caractérisé en ce que la base est sensiblement circulaire et a une paroi latérale qui en dépasse et qui en est solidaire, la surface ondulée s'étendant sur la paroi latérale.
8. Ustensile selon l'une quelconque des revendications 1 à 5, caractérisé en ce que la base est sensiblement circulaire et a une paroi latérale qui en dépasse et qui est circulaire, la paroi latérale et la base étant toutes deux munies de la surface ondulée, et une région annulaire est placée entre la paroi latérale et la base et cette région est sensiblement lisse.
9. Ustensile selon l'une quelconque des revendications précédentes, caractérisé en ce que la surface antiadhérente est du polytétrafluoréthylène (PTFE).

Patentansprüche

1. Koch- oder Bratpfanne (2,4) bestehend aus einer Grundfläche mit einer äußeren hitzeaufnehmenden Oberfläche und einer inneren oder oberen Kontaktfläche (6) für die aufliegende Aufnahme der zu kochenden Speise, wobei die Kontaktfläche gebildet ist mit Riefelungen oder Riffeln (8), die räumlich eng beieinander liegende Spitzen oder Scheitel in einer allgemein gemeinsamen Ebene bestimmen, die Riefelungen oder Riffeln (8) ein bestimmbares Muster bilden und ein nichthaftendes Material (10) auf die geriffelte Oberfläche (10) aufgetragen wird, dadurch gekennzeichnet, daß die geriffelte



- Kontaktoberfläche konzentrisch kreisförmige Rillen (12, 14) bestimmt und daß der Spitzenhöhenabstand der Riefelungen oder Riffeln nicht größer als 2mm ist.
2. Pfanne nach Anspruch 1, dadurch gekennzeichnet, daß der Spitzenhöhenabstand der Riefelungen oder Riffeln (8) nicht größer als 1mm ist.
3. Pfanne nach einem der vorhergehenden Ansprüche 1 oder 2, dadurch gekennzeichnet, daß die geriffelte Oberfläche konzentrisch kreisförmige Rillen (14) um die Mitte der Grundfläche bestimmt.
4. Pfanne nach einem der vorhergehenden Ansprüche 1 bis 3, dadurch gekennzeichnet, daß das bestimmbare Muster mehrere Gruppen konzentrischer Rillen (12) aufweist, die einem Gesamtmuster der Rillen (14) überlagert sind.
5. Pfanne nach einem der vorhergehenden Ansprüche 1 bis 4, dadurch gekennzeichnet, daß als Grundflächenmaterial zwischen der äußeren und der Kontaktfläche eloxiertes Aluminium verwendet wird.
6. Pfanne nach einem der vorhergehenden Ansprüche 1 bis 5, dadurch gekennzeichnet, daß die Grundfläche im wesentlichen kreisförmig ist und eine mit dieser als ein Stück ausgebildeten nach oben stehende Seitenwand aufweist, wobei die geriffelte Kontaktfläche an der Verbindungsstelle zwischen Grundfläche und Seitenwand ausläuft.
7. Pfanne nach einem der vorhergehenden Ansprüche 1 bis 5, dadurch gekennzeichnet, daß die Grundfläche im wesentlichen kreisförmig ist und eine mit dieser als ein Stück ausgebildeten nach oben stehenden Seitenwand aufweist, wobei die geriffelte Oberfläche zur Seitenwand hin verläuft.
8. Pfanne nach einem der vorhergehenden Ansprüche 1 bis 5, dadurch gekennzeichnet, daß die Grundfläche im wesentlichen kreisförmig ist und eine mit dieser als ein Stück ausgebildeten nach oben stehenden Seitenwand aufweist, wobei sowohl die Seitenwand als auch die Grundfläche mit einer geriffelten Oberfläche versehen sind und ein ringförmiger, im wesentlichen glatter Bereich zwischen der Seitenwand und der Grundfläche vorgesehen ist.
9. Pfanne nach einem der vorhergehenden Ansprüche 1 bis 8, dadurch gekennzeichnet, daß die "nichthaftende" Oberfläche Polytetrafluoroäthylen (PTFE) aufweist.

