

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 May 2003 (01.05.2003)

PCT

(10) International Publication Number
WO 03/037030 A2

(51) International Patent Classification⁷: **H04Q 7/38**

(21) International Application Number: PCT/US02/34017

(22) International Filing Date: 23 October 2002 (23.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/038,184 24 October 2001 (24.10.2001) US

(71) Applicant: **QUALCOMM INCORPORATED** [US/US];
5775 Morehouse Drive, San Diego, CA 92121 (US).

(72) Inventor: **LEUNG, Nikolai, K., N.**; 7710 Takoma Avenue, Takoma Park, MD 20912 (US).

(74) Agents: **WADSWORTH, Philip, P.** et al.; Qualcomm Incorporated, 5775 Morehouse Drive, San Diego, CA 92121 (US).


(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *without international search report and to be republished upon receipt of that report*

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR HARD HANDOFF IN A BROADCAST COMMUNICATION SYSTEM



(57) Abstract: A method and system for a handoff in a broadcast communication system is disclosed. A subscriber-assisted handoff is impractical in a broadcast communication system due to e.g., a high signaling load, a difficulty to synchronize the broadcast transmission. On the other hand, the small number of broadcast channels enables the subscriber station to perform the handoff autonomously. While performing a handoff between broadcast transmissions, a disruption of service occurs due to lack of synchronization among the broadcast transmissions. To reduce the service disruption, upon detecting a need for handoff, the lower layers inform the application layer about the forthcoming handoff. The application layer thus may take measures to reduce or prevent the disruption.



WO 03/037030 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.