

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 February 2003 (06.02.2003)

PCT

(10) International Publication Number
WO 03/009901 A2

(51) International Patent Classification⁷: **A63B**

(21) International Application Number: PCT/US02/23350

(22) International Filing Date: 24 July 2002 (24.07.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/307,392 25 July 2001 (25.07.2001) US
10/200,496 23 July 2002 (23.07.2002) US

(71) Applicant: **SIMULA, INC.** [US/US]; 2625 South Plaza Drive, Suite 100, Tempe, AZ 85282 (US).

(72) Inventor: **BRADLEY, Gary**; 111 Glenwood Lane, Hendersonville, NC 28792 (US).

(74) Agents: **GOTTS, Lawrence, J.** et al.; Shaw Pittman LLP, 1650 Tysons Boulevard, McLean, VA 22102-4859 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MULTI-CHAMBERED FLOTATION DEVICE

(57) Abstract: A system for maintaining a afloat in a fluid environment is disclosed. The system includes multiple chambers such that if one chamber fails to operate, redundant chambers will function to maintain the user afloat in a face-up position. In a preferred embodiment, there are multiple activation mechanisms to ensure inflation of the chambers if a single activation mechanism fails to function.



WO 03/009901 A2