

What is claimed is:

1. A computing system including:

a data storage system storing entity data representing a plurality of entities, with each entity having one or more attributes, at least some of the entities each having multiple instances, and at least some of the instances each having respective values for one or more of the attributes, where the plurality of entities include a plurality of input entities and a plurality of output entities;

an input device or port for receiving input data that includes one or more mappings that each define a correspondence between one or more input attributes of one of the input entities and one or more output attributes of one of the output entities, where the input entity includes one or more key attributes identified as part of a unique key for the input entity, and the output entity includes one or more key attributes identified as part of a unique key for the output entity;

an output device or port for displaying a user interface configured to receive the input data; and

at least one processor configured to compute result information displayed in the user interface, the result information characterizing a result of processing instances of the input entities to generate instances of the output entities according to the one or more mappings included in the input data, the computing including:

processing instances of a first input entity to generate instances of a first output entity;

determining one or more mapped input attributes of the first input entity that correspond to each of the one or more key attributes of the first output entity, based on the one or more mappings;

generating the instances of the first output entity based on the determined one or more mapped input attributes, where the generating includes reorganizing entity data within the instances of the first input entity to provide reorganized entity data within the instances of the first output entity, and where the reorganizing is based at least in part on a difference between key attributes identified as part of a unique key for the input entity and key attributes identified as part of a unique key for the output entity;

computing a total number of instances of the first input entity that were processed;
and

computing a total number of instances of the first output entity that were generated according to the reorganizing.

2. The computing system of claim 1, wherein displaying the result information in the user interface includes displaying the total number of instances of the first output entity in association with a representation of the first output entity.

3. The computing system of claim 2, wherein displaying the result information in the user interface includes displaying the total number of instances of the first input entity in association with a representation of the first input entity.

4. The computing system of claim 1, wherein displaying the result information in the user interface includes displaying multiple elements representing one or more mappings between attributes of a displayed input entity and attributes of a displayed output entity, displaying an icon for each element that indicates whether or not the input data for any mappings between the displayed input entity and displayed output entity assign an output attribute to: (1) an input attribute of the same name, or (2) a constant value.

5. The computing system of claim 1, wherein determining one or more mapped input attributes of the input entity that correspond to each of the one or more key attributes of the output entity includes determining whether the one or more mapped input attributes have a one-to-one correspondence with respective key attributes of the output entity.

6. The computing system of claim 1, wherein the computing further includes comparing the mapped input attributes with the one or more key attributes of the input entity to determine whether the mapped input attributes include: (1) all of the key attributes of the input entity, or (2) fewer than all of the key attributes of the input entity.

7. The computing system of claim 6, wherein the processing further includes generating the instances of the output entity based on: (1) a one-to-one correspondence between the instances of the output entity and instances of the input entity that have matching key attributes, in response to determining that the mapped input attributes include all of the key attributes of the input entity, or (2) an aggregation of multiple instances of the input entity that share the same values for the mapped input attributes, in response to determining that the mapped input attributes include fewer than all of the key attributes of the input entity.

8. The computing system of claim 1, wherein the entity data represent a plurality of output entities that are related according to a hierarchy, where at least one root output entity is at a highest level of the hierarchy and one or more output entities are at one or more levels below the highest level of the hierarchy, and each output entity at a level lower than the root entity is a sub-entity of a single output entity.

9. The computing system of claim 8, wherein the entity data represent a plurality of input entities that are related according to a hierarchy, where at least one root input entity is at a highest level of the hierarchy and one or more input entities are at one or more levels below the highest level of the hierarchy, and each input entity at a level lower than the root entity is a sub-entity of a single input entity.

10. The computing system of claim 8, wherein at least a first entity that is not related to the plurality of output entities that are related according to a hierarchy includes at least one attribute that is referenced as an output attribute by at least one of the mappings included in the input data.

11. The computing system of claim 10, wherein the first entity includes at least one attribute that is referenced as an input attribute by at least one of the mappings included in the input data.

12. The computing system of claim 1, wherein a plurality of instances of a first entity that is a sub-entity of a second entity each include a common value of a key attribute of the first entity that identifies a particular instance of the second entity.

13. The computing system of claim 12, wherein the first entity corresponds to a first set of records, the second entity corresponds to a second set of records, and the key attribute of the first entity corresponds to a foreign key field of the first set of records that identifies a value included in a primary key field of a particular record in the second set of records.

14. The computing system of claim 1, wherein a plurality of instances of a first entity that is a sub-entity of a second entity correspond to a plurality of elements of a vector that is included within a data structure of a particular instance of the second entity.

15. The computing system of claim 14, wherein the processing further includes generating the instances of the output entity using a dataflow graph to process the instances of the input entity to generate the instances of the output entity, the dataflow graph including nodes representing components configured to perform operations on instances of an entity, and links between nodes representing flows of instances between components.

16. The computing system of claim 15, wherein the dataflow graph includes at least one split component that is configured to extract one or more vectors of instances of a sub-entity from a data structure of an instance of another entity based on the input attributes of the one or more mappings, and at least one combine component that is configured to insert one or more vectors of instances of a sub-entity into a data structure of an instance of another entity based on the output attributes of the one or more mappings.

17. A computing system including:

means for storing entity data representing a plurality of entities, with each entity having one or more attributes, at least some of the entities each having multiple instances, and at least some of the instances each having respective values for one or more of the attributes, where the plurality of entities include a plurality of input entities and a plurality of output entities;

means for receiving input data that includes one or more mappings that each define a correspondence between one or more input attributes of one of the input entities and one or more output attributes of one of the output entities, where the input entity includes one or more key attributes identified as part of a unique key for the input entity, and the output entity includes one or more key attributes identified as part of a unique key for the output entity;

means for displaying a user interface configured to receive the input data; and

means for computing result information displayed in the user interface, the result information characterizing a result of processing instances of the input entities to generate instances of the output entities according to the one or more mappings included in the input data, the computing including:

processing instances of a first input entity to generate instances of a first output entity;

determining one or more mapped input attributes of the first input entity that correspond to each of the one or more key attributes of the first output entity, based on the one or more mappings;

generating the instances of the first output entity based on the determined one or more mapped input attributes, where the generating includes reorganizing entity data within the instances of the first input entity to provide reorganized entity data within the instances of the first output entity, and where the reorganizing is based at least in part on a difference between key attributes identified as part of a unique key for the input entity and key attributes identified as part of a unique key for the output entity;

computing a total number of instances of the first input entity that were processed;
and

computing a total number of instances of the first output entity that were generated according to the reorganizing.

18. A method for processing data in a computing system, the method including:

storing, in a data storage system, entity data representing a plurality of entities, with each entity having one or more attributes, at least some of the entities each having multiple instances, and at least some of the instances each having respective values for one or more of the attributes, where the plurality of entities include a plurality of input entities and a plurality of output entities;

receiving, over an input device or port, input data that includes one or more mappings that each define a correspondence between one or more input attributes of one of the input entities and one or more output attributes of one of the output entities, where the input entity includes one or more key attributes identified as part of a unique key for the input entity, and the output entity includes one or more key attributes identified as part of a unique key for the output entity;

displaying, over an output device or port, a user interface configured to receive the input data; and

computing, with at least one processor, result information displayed in the user interface, the result information characterizing a result of processing instances of the input entities to generate instances of the output entities according to the one or more mappings included in the input data, the computing including:

processing instances of a first input entity to generate instances of a first output entity;

determining one or more mapped input attributes of the first input entity that correspond to each of the one or more key attributes of the first output entity, based on the one or more mappings;

generating the instances of the first output entity based on the determined one or more mapped input attributes, where the generating includes reorganizing entity data within the instances of the first input entity to provide reorganized entity data within the instances of the first output entity, and where the reorganizing is based at least in part on a difference between key attributes identified as part of a unique key for the input entity and key attributes identified as part of a unique key for the output entity;

computing a total number of instances of the first input entity that were processed; and

computing a total number of instances of the first output entity that were generated according to the reorganizing.

19. Software stored in non-transitory form on a computer-readable medium, the software including instructions for causing a computing system to:

store, in a data storage system, entity data representing a plurality of entities, with each entity having one or more attributes, at least some of the entities each having multiple instances, and at least some of the instances each having respective values for one or more of the attributes, where the plurality of entities include a plurality of input entities and a plurality of output entities;

receive, over an input device or port, input data that includes one or more mappings that each define a correspondence between one or more input attributes of one of the input entities and one or more output attributes of one of the output entities, where the input entity includes one or more key attributes identified as part of a unique key for the input entity, and the output entity includes one or more key attributes identified as part of a unique key for the output entity;

display, over an output device or port, a user interface configured to receive the input data; and

compute, with at least one processor, result information displayed in the user interface, the result information characterizing a result of processing instances of the input entities to generate instances of the output entities according to the one or more mappings included in the input data, the computing including:

processing instances of a first input entity to generate instances of a first output entity;

determining one or more mapped input attributes of the first input entity that correspond to each of the one or more key attributes of the first output entity, based on the one or more mappings;

generating the instances of the first output entity based on the determined one or more mapped input attributes, where the generating includes reorganizing entity data within the instances of the first input entity to provide reorganized entity data within the instances of the first output entity, and where the reorganizing is based at least in part on a difference between key attributes identified as part of a unique key for the input entity and key attributes identified as part of a unique key for the output entity;

computing a total number of instances of the first input entity that were processed; and

computing a total number of instances of the first output entity that were generated according to the reorganizing.