

CLAIMS

What is claimed is:

1. A method of decoding implemented by a video decoder, comprising:
receiving, by the video decoder, a video bitstream including a picture unit (PU), wherein any decoding capability information (DCI) network abstraction layer (NAL) unit, video parameter set (VPS) NAL unit, sequence parameter set (SPS) NAL unit, or picture parameter set (PPS) NAL unit referred to by the PU precedes a picture header (PH) NAL unit of the PU and a first video coding layer (VCL) NAL unit of the PU; and
decoding, by the video decoder, a coded picture from the PU to obtain a decoded picture.
2. The method of claim 1, wherein the PU contains only one picture header (PH), and wherein the coded picture is the only picture in the PU.
3. The method of any of claims 1 to 2, wherein a DCI is carried in the DCI NAL unit, wherein a VPS is carried in the VPS NAL unit, wherein a PPS is carried in the PPS NAL unit, and wherein a SPS is carried in the SPS NAL unit.
4. The method of any of claims 1 to 3, wherein the first VCL NAL unit contains a slice of the coded picture.
5. The method of any of claims 1 to 4, wherein the PH NAL unit is a non-VCL NAL unit.
6. The method of claim 2, wherein the PH NAL unit contains the only one PH.
7. The method of claim 6, wherein the only one PH in the PH NAL unit contains syntax elements that apply to all slices of the coded picture.
8. The method of any of claims 1 to 7, wherein the PH NAL unit immediately precedes the first VCL NAL unit in the PU.

9. The method of any of claims 1 to 8, further comprising displaying the decoded picture on a display of an electronic device.
10. A method of encoding implemented by a video encoder, the method comprising:
generating, by the video encoder, a picture unit (PU) containing one or more of a decoding capability information (DCI) network abstraction layer (NAL) unit, a video parameter set (VPS) NAL unit, a sequence parameter set (SPS) NAL unit, and a picture parameter set (PPS) NAL unit preceding a picture header (PH) NAL unit and a first video coding layer (VCL) NAL unit;
encoding, by the video encoder, the PU into a video bitstream; and
storing, by the video encoder, the video bitstream for communication toward a video decoder.
11. The method of claim 10, wherein the PU contains only one picture header (PH) and a coded picture, and wherein the coded picture is the only picture in the PU.
12. The method of claim 11, wherein a DCI is carried in the DCI NAL unit, wherein a VPS is carried in the VPS NAL unit, wherein a PPS is carried in the PPS NAL unit, and wherein a SPS is carried in the SPS NAL unit.
13. The method of any of claims 11 to 12, wherein the first VCL NAL unit contains a slice of the coded picture.
14. A decoding device, comprising:
a receiver configured to receive a video bitstream including a picture unit (PU), wherein any decoding capability information (DCI) network abstraction layer (NAL) unit, video parameter set (VPS) NAL unit, sequence parameter set (SPS) NAL unit, or picture parameter set (PPS) NAL unit referred to by the PU precedes a picture header (PH) NAL unit of the PU and a first video coding layer (VCL) NAL unit of the PU;
a memory coupled to the receiver, the memory storing instructions; and

a processor coupled to the memory, the processor configured to execute the instructions to cause the decoding device to:

decode a coded picture from the PU to obtain a decoded picture.

15. The decoding device of claim 14, wherein the PU contains only one picture header (PH), and wherein the coded picture is the only picture in the PU.

16. The decoding device of claim 15, wherein a DCI is carried in the DCI NAL unit, wherein a VPS is carried in the VPS NAL unit, wherein a PPS is carried in the PPS NAL unit, and wherein a SPS is carried in the SPS NAL unit.

17. The decoding device of any of claims 15 to 16, wherein the first VCL NAL unit contains a slice of the coded picture.

18. An encoding device, comprising:
a memory containing instructions;
a processor coupled to the memory, the processor configured to implement the instructions to cause the encoding device to:

generate a picture unit (PU) containing one or more of a decoding capability information (DCI) network abstraction layer (NAL) unit, a video parameter set (VPS) NAL unit, a sequence parameter set (SPS) NAL unit, and a picture parameter set (PPS) NAL unit preceding a picture header (PH) NAL unit and a first video coding layer (VCL) NAL unit;

encode the PU into a video bitstream; and

a transmitter coupled to the processor, the transmitter configured to transmit the video bitstream toward a video decoder.

19. The encoding device of claim 18, wherein the PU contains only one picture header (PH) and a coded picture, and wherein the coded picture is the only picture in the PU.

20. The encoding device of claim 19, wherein the PH NAL unit in the PU precedes each VCL NAL unit in the PU inclusive of the first VCL NAL unit, and wherein the first VCL NAL unit contains a slice of the coded picture.
21. A coding apparatus, comprising:
a receiver configured to receive a picture to encode or to receive a bitstream to decode;
a transmitter coupled to the receiver, the transmitter configured to transmit the bitstream to a decoder or to transmit a decoded image to a display;
a memory coupled to at least one of the receiver or the transmitter, the memory configured to store instructions; and
a processor coupled to the memory, the processor configured to execute the instructions stored in the memory to perform the method in any of claims 1 to 9 and any of claims 10 to 13.
22. The coding apparatus of claim 20, further comprising a display configured to display a decoded picture.
23. A system, comprising:
an encoder; and
a decoder in communication with the encoder, wherein the encoder or the decoder includes the decoding device, the encoding device, or the coding apparatus of any of claims 15 to 22.
24. A means for coding, comprising:
receiving means configured to receive a picture to encode or to receive a bitstream to decode;
transmission means coupled to the receiving means, the transmission means configured to transmit the bitstream to a decoding means or to transmit a decoded image to a display means;
storage means coupled to at least one of the receiving means or the transmission means, the storage means configured to store instructions; and
processing means coupled to the storage means, the processing means configured to execute the instructions stored in the storage means to perform the method in any of claims 1 to 9 and any of claims 10 to 13.