



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶:

F16B 7/06 // E04B 1/58, E04C 3/02

A1

(11) International Publication Number:

WO 96/18826

(43) International Publication Date:

20 June 1996 (20.06.96)

(21) International Application Number: PCT/AU95/00855

(22) International Filing Date: 18 December 1995 (18.12.95)

(30) Priority Data:

PN 0114

16 December 1994 (16.12.94) AU

(71)(72) Applicant and Inventor: PICCININ, Neil, Anthony
[AU/AU]; 4/47 Collingwood Street, Osborne Park, W.A.
6017 (AU).(74) Agent: GIRAUDO, Clinton; P.O. Box 265, Cottesloe, W.A.
6011 (AU).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM; TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: TURNBUCKLE SPIGOT ASSEMBLY

(57) Abstract

A turnbuckle spigot assembly (10) having a first spigot (24) for fixing into a main member (100) of a first truss (102) and a second spigot (26) for fixing into a main member (106) of a second truss (104). A drive bolt (22) rotatably seated in the first spigot (24) and threaded into the second spigot (26), and a turning element (20) for turning the drive bolt (22) for drawing the spigots (24 and 26) together for joining the trusses (102 and 104) for forming a single truss span. The first and second spigots (24 and 26) can be rotated to align with fixing holes in the main members (100 and 106) independent of the length of the assembly (10).

