

DEVICE PERMITTING A PLUG OR A COVER TO LOCK IN A DETACHABLE MANNER ONTO A FRAME

This invention involves a device permitting a plug or a cover to lock in a detachable manner onto a frame.

Similar devices are known to include fastening screws inserted through the plug's corresponding perforations and to have their threaded ends anchored in threaded holes of the frame. Each fastening screw has its head sunk into a housing emerging from the plug while resting against a flat surface at the bottom of this housing, so as to jam the plug onto the frame by tightening the screws. A waterproof washer made of elastomer, such as rubber, and a metal washer are successively interposed between the flat surface at the bottom of the housing and the screw head.

However, this known locking device has the following disadvantages.

First of all, during tightening of each plug's fastening screw to the frame, the metal washer tends to be rotated by contact with the screw head because of the tightening torque exerted on the screw head, causing a strain hardening of the waterproof washer made of elastomer. Furthermore, using the frame's threaded holes to affix the fastening screws is costly since it is necessary to thread these holes into the frame and, with time, threads can be stripped during repeated actions of unlocking the frame's plug and locking this plug to the frame, which gives rise to maintenance problems leading to increasing costs of such a device.

The purpose of this invention is to eliminate the disadvantages described above by proposing a device permitting a plug or a cover to lock in a detachable manner onto a frame, including at least one fastening screw inserted through a perforation in the plug and having its threaded end anchored to the frame and its head sunk into a housing emerging from the plug while resting against a flat surface at the bottom of this housing so as to jam the plug onto the frame by tightening the screw, a waterproof washer and a metal washer successively

interposed between the flat surface and the screw head, and whose distinction is that the metal washer is provided with at least one way of working together with the housing's internal parts to prevent the rotation of the metal washer during tightening of the fastening screw.

The metal washer's anti-rotational direction includes one radial wing.

Preferably, the metal washer would include two radial wings diametrically opposite.

The fastening screw's threaded end is inserted through a perforation of the frame's inside wall and is screwed in a nut confined inside the frame's housing and delimited on the upper end by the frame's inside wall so that the nut is jammed against this wall after the fastening screw is tightened.

Strategically, the internal parts abutting each metal washer's wing consist of the housing's inside surfaces, which are matched up to the wing.

The plug is fastened in a peripheral seating groove in the frame while resting against a metal-on-metal contact without hardly any play in the frame's groove walls by machining the walls' and plug's touching surfaces.

The device includes four fastening screws locking respectively four corners of the plug to the frame.

Strategically, the frame and plug are fastened to one another by fastening screws prior to sealing the frame with concrete in a groove alongside a floor opening to be closed off.

The invention will be better understood, and other purposes, characteristics, details and advantages of this invention will appear more clearly in the descriptive explanation that will follow made in reference to the visual drawings attached, given only as an example to illustrate how to construct the invention and in which:

- Figure 1 is a top view of a plug or cover locked to a supporting frame;

- Figure 2 is a cross-section following line II-II of figure 1 and representing the invention device ensuring the locking of the plug to the frame;

- Figure 3 is a view following arrow III of figure 3 without the plug;

- Figure 4 is a cross-section following line IV-IV of figure 1; and

- Figure 5 is a top view following arrow V of figure 1.

While referring to the figures, reference 1 designates a frame generally rectangular in shape which can be sunk into the pavement to line up evenly with it and onto which a plug or cover 2 is assembled. In a nonrestrictive way, the frame 1 and cover 2 can be a part of a pavement manhole. Furthermore, the frame 1 can have a circular instead of a rectangular shape.

The cover 2 is fastened in a detachable manner to the frame 1 by fastening screws 3; for example, numbering four while being positioned respectively to four corners of the cover 2.

Each fastening screw 3 has its head 4 sunk in a housing 5 emerging from the outer flat surface 6a of the upper wall 6 of the cover 2 so that, preferably, it lines up with the frame in a locked position from cover 2 to frame 1.

In a locking position from cover 2 to frame 1, each screw head 4 is resting against a flat surface 7 from the bottom of the housing 5 of the cover 2 through a waterproof washer made of elastomer 8, such as rubber, resting against a flat surface 7 and a metal washer 9 positioned between washer 8 and screw head 4.

The stem 10 of each fastening screw 3 is inserted through the cover's 2 perforation 11 and extends perpendicularly to the upper wall 6 of the cover 2. The threaded end 10a of the stem 10 of each fastening screw 3 is anchored to the frame 1 so as to permit each screw 3 to be tightened to jam the cover 2 to the frame 1. As is

better illustrated in figure 2, the cover 2 is fastened in a peripheral seating groove 12 of the frame 1 while resting against metal-on-metal without hardly any play in the inside surfaces $12a_1$, $12b_1$ of the walls 12a, 12b of the groove 12 by machining the touching surfaces. More precisely, figure 2 shows that the side wall 12a of the groove 12 of the frame 1 is tilted towards the outside in relation to the perpendicular wall, if the frame 1 is considered sunk in the pavement while its inside wall 12b is horizontal in order to receive respectively the tilted outer surface $6b_1$ of the side wall 6b of the cover 2 and the surface at the end $6b_2$ of the wall 6b of the cover 2 in locked position from cover 2 to frame 1, the slanting $12a_1$, $6b_1$ and horizontal $12b_1$ and $6b_2$ surfaces of the frame 1 and cover 2 machined so that the metal-on-metal contact between them is obtained with an extremely low tolerance, for example, of approximately 0.2 mm.

In accordance with the invention, the metal washer 9 includes two radial wings diametrically opposite 9a working together with internal parts abutting the housing 5 to prevent rotation of the metal washer 9 during tightening of the fastening screw 3.

According to a plan for construction of the invention, the internal parts abutting each wing 9a of the metal washer 9 consist of at least parallel inside surfaces 13 of the housing 5, positioned on each side of the wing 9a near this wing and, preferably, the housing 5 in cross-section is matched up to the washer 9 provided with its two wings 9a.

As an alternative, the metal washer's 9 anti-rotation can be ensured by only one wing 9a extending in a radial manner to the stem's longitudinal axis from the screw 10 inserted through this washer and working together with two opposite inside surfaces 13 of the housing 5.

The stem 10 of each fastening screw 3 is inserted through a perforation 14 of an inside wall 15 of the frame 1 extending horizontally. Perforation 14 is positioned in

a coaxial manner to perforation 11 of the cover 2 when this cover is locked onto the frame 1. The inside wall 15 of the frame 1 has a determined length in a parallel direction to the lateral wall 12a of the frame 1 and constitutes an extension of the horizontal peripheral wall 12b and on which the cover 2 rests.

The threaded end 10a of each fastening screw 3 leads into a cavity or specific housing 16 under the inside wall 15 and is screwed into a nut 17 confined in the housing 16. In the screw's 3 tightened position, the nut 17 rests under the wall 15. The dimensions of the housing 16 defined within the frame 1 are such so that the nut 17 is confined with weak play in this housing in order to allow the blind introduction into this nut of the threaded end 10a of the fastening screw 3. The housing 16 emerges inside the frame 1 through a rectangular window 18 made through the frontal wall 19 of the frame 1 delimiting the housing 16, in order to allow, prior to assembly, the introduction of the nut 17 into the housing 16.

During tightening of each fastening screw 3, the metal washer 9, with its wings resting against the corresponding surfaces 13 of the housing 5, is jammed in rotation, preventing as a result the strain hardening of the waterproof washer 8. Furthermore, jamming each fastening screw 3 with the aforementioned nut 17 confined in the chamber 16 reduces manufacturing costs in comparison to using the frame's 1 threaded hole and if threading of the nut 17 should be damaged during repeated actions of disassembling the cover 2 of the frame 1 and assembling of the cover 2 to the frame 1, then simply replacing the nut 17 with another will be sufficient.

Before sealing with concrete the frame in a groove bordering a floor opening to be closed off by the cover 2, this cover is affixed with fastening screws 3 to the frame 1, which makes it possible to ensure a perfect line-up between surfaces in a metal-to-metal contact of the frame 1 and cover 2, and simplifies its installation in the

pavement. Plastic caps, not shown here, can at any rate be inserted respectively into emerging housings 5 to plug them up and ensure a seal against contaminants to these housings. To ensure an effective grip of each cap in the corresponding housing, each screw head 4 can include flat sections 4a introduced into a matching part of the cap.

CLAIMS

1. Device permitting a plug or a cover (2) to lock in a detachable manner onto a frame (1), in particular a pavement manhole, including at least one fastening screw (3) inserted through the plug's (2) perforation (11) and which has its threaded part (10a) anchored to the frame (1) and head (4) sunk into a housing (5) emerging from the plug (2) while resting against a flat surface (7) at the bottom of the housing (5) in order to jam the plug (2) onto the frame (1) by tightening the screw (3), a waterproof washer (8) and a metal washer (9) interposed successively between the flat surface (7) and the screw head (4), characterized in that a metal washer (9) which is provided with at least one means of abutting (9a) the housing's (5) internal parts (13) to prevent a rotation of the metal washer (9) during tightening of the fastening screw (3).

2. Device in accordance with claim 1, specifically characterized in that an anti-rotational washer (9) is using a radial wing (9a).

3. Device in accordance with claim 2, specifically characterized in that a metal washer (9) is using two radial wings (9a) diametrically opposite.

4. Device in accordance with one of the previous claims, specifically characterized in that the fastening screw's (3) threaded end (10a) is inserted through a perforation (14) of the frame's (1) inside wall (15) and is screwed into a nut (17) confined inside the frame's (1) housing (16) delimited on the upper end by the wall (15) so that the nut (17) is jammed resting under this wall after tightening of the fastening screw (3).

5. Device in accordance with one of the previous claims, specifically characterized in that the internal parts abutting each metal washer's (9) wing (9a) consist of the housing's (5) two inside surfaces matched up to the wing.

6. Device in accordance with one of the previous claims, specifically characterized in that a plug (2) fastened in a peripheral seating groove (12) of the frame (1) while resting against a metal-on-metal contact without hardly any play in the groove walls (12a, 12b) of the frame (1) by machining the touching surfaces of the frame's and the plug's walls.

7. Device in accordance with one of the previous claims, specifically characterized in that there is four fastening screws (3) locking respectively four corners of the plug (2) to the frame (1).

8. Device in accordance with one of the previous claims, specifically characterized in that the frame (1) and plug (2) are fastened to one another by fastening screws (3) prior to sealing the frame (1) with concrete in a groove bordering a floor opening to be closed off.