

APPARATUS AND METHODS FOR SUPPORT OF A MEMBRANE FILTER IN A MEDICAL INFUSION SYSTEM

RELATED APPLICATION

5 The present application claims priority to U.S. patent application serial No. 12/273,899, filed November 19, 2008.

TECHNICAL FIELD

10 The present invention pertains to medical infusion systems and more particularly to the support of membrane filters incorporated therein.

BACKGROUND

15 Fluid circuits of medical infusion systems typically include at least one filter to assure that air, and/or other gases, are not introduced, for example, into a venous system of a patient, along with the infused fluid. The membrane-type filter includes a hydrophilic membrane, which extends between an inlet and an outlet of the filter, and a hydrophobic membrane which extends between the inlet and vent holes of the filter. The hydrophilic membrane is fluid permeable, yet gas impermeable, and the hydrophobic membrane is fluid impermeable, yet gas permeable. The design and operation of these membrane-type filters are known to those skilled in the art. One such filter is the Speedflow Adult 0.2 μ m Positive, which is available from GVS Group (headquartered in Bologna, Italy).

20 Membrane filters are typically constructed for relatively low pressure applications (i.e. less than approximately 3.5 bar or approximately 50 psi), and to be relatively inexpensive, flexible and disposable. Thus, the housings of these filters may be susceptible to failure, if the filters are employed by infusion systems that inject fluids at higher pressures. Support for the housings of these filters has been proposed, yet, there is still a need for new apparatus and methods for supporting membrane filters.

30

- 2 -

BRIEF DESCRIPTION OF THE DRAWINGS

The following drawings include those illustrative of particular embodiments of the present invention, and therefore do not limit the scope of the invention. The drawings are not to scale (unless so stated) and are intended for use in conjunction
5 with the explanations in the following detailed description. Embodiments of the present invention will hereinafter be described in conjunction with the appended drawings, wherein like numerals denote like elements.

Figure 1A is a perspective view of an exemplary membrane filter.

10 Figure 1B is a perspective view of an exemplary prior art auxiliary housing for the filter shown in Figure 1A.

Figure 2 is a perspective view of a removable clamp, according to some embodiments of the present invention.

Figure 3A is a perspective view of the filter of Figure 1A secured within the clamp of Figure 2, according to some embodiments.

15 Figure 3B is a cross-section view through section line A-A of Figure 3A, according to some embodiments.

Figure 4A is a perspective view of an exemplary infusion system.

Figure 4B is a perspective view of a portion of the infusion system, shown in Figure 4A, which may incorporate embodiments of the present invention.

20

DETAILED DESCRIPTION

The following detailed description is exemplary in nature and is not intended to limit the scope, applicability, or configuration of the invention in any way. Rather, the following description provides practical illustrations for implementing exemplary
25 embodiments. Utilizing the teaching provided herein, those skilled in the art will recognize that many of the examples have suitable alternatives that can be utilized.

Figure 1A is a perspective view of an exemplary membrane filter 10, which is very similar to the aforementioned filter supplied by GVS Group. Figure 1A illustrates filter 10 including a housing 12, an inlet 125 and an outlet 127; a first fitting 152, for example, a female Luer lock, is shown joined to inlet 125, and a second fitting 172, for example, a rotating male Luer lock, is shown joined to outlet 127. Figure 1A further illustrates housing 12 including a first sidewall 12A, a second

30

- 3 -

sidewall 12B and a perimeter seam 123 at which first and second sidewalls 12A, 12B are joined together, for example, via adhesive bonding or ultrasonic welding; vent holes 126 are shown formed through a protruding portion of first sidewall 12A, in proximity to inlet 125. Those skilled in the art will appreciate that a hydrophilic
5 membrane 190, which may be captured between sidewalls 12A, 12B, at seam 123 (Figure 3B), extends within housing to divide housing into an inlet compartment, in proximity to inlet 125, and an outlet compartment, in proximity to outlet 127; and, further, that a hydrophobic membrane, for example, being attached to first sidewall 12A, extends between the inlet compartment and vent holes 126. When filter 10 is
10 connected, via fittings 152, 172, into a fluid circuit of a medical infusion system, the joint at seam 123 should be able to withstand the pressures of injection fluid flow through filter 10, otherwise first and second sidewalls 12A, 12B of housing 12 will separate from one another, thereby causing a failure of the system.

Figure 1B is a perspective view of an exemplary prior art auxiliary housing
15 100, which is very similar to an auxiliary housing provided by GVS group for support of a filter that is similar to filter 10. Figure 1B illustrates housing 100 including a first part 100A and a second part 100B; each of first and second parts 100A, 100B include a cavity 105A and 105B, respectively, to surround and support housing 12 of filter 10 when auxiliary housing 100 is assembled around filter 10. In order to
20 assemble housing 100 around filter 10, first and second parts 100A, 100B must be fastened together around filter 10. Figure 1B further illustrates each part 100A, 100B including securing features 110 formed therein, and fasteners 115, for example, thumb screws, inserted into two of securing features 110 in first part 100A. In order to fasten parts 100A, 100B together around filter 10, cavities 105A, 105B of parts
25 100A, 100B must be aligned with filter housing 12, and securing features 110 of first part 100A also aligned with corresponding securing features 110 of second part 100B; then, fasteners 115 must be mated with the aligned features 110.

With reference back to Figure 1A, in conjunction with Figure 1B, it may be appreciated that a length L1 and a width W1 of housing 12 are either less than or
30 equal to a length L2 and a width W2, respectively, of cavities 105A, 105B, so that when auxiliary housing 100 is assembled around filter 10, filter housing 12 will be completely enclosed within cavities 105A, 105B. Furthermore, a depth D of each

- 4 -

cavity 105A, 105B, in conjunction with adjustment of fasteners 115, is such that first and second parts 100A, 100B, when fastened together around filter housing 12, may restrain sidewalls 12A, 12B from separating at seam 123, under higher operating pressures. Each part 100A, 100B is shown including a feature 145, which protrudes
5 into the respective cavity 105A, 105B, in order to directly interface with each of sidewalls 12A, 12B, when first and second parts 100A, 100B are fastened together around filter 10; at least one of features 145 may be movable to adjust a pressure at the interface with the corresponding sidewall 12A, 12B.

With further reference to Figure 1B, it may be appreciated that the design of
10 auxiliary housing 100 has several drawbacks, for example, related to the bulk and the handling thereof. In particular, a size of auxiliary housing 100 is such that vent holes 126 may be blocked by one of first and second parts 100A, 100B, when assembled around housing 12, thereby potentially compromising the function of filter 10; and, with respect to handling, the aforementioned steps, which are necessary to
15 assemble auxiliary housing 100 around filter 10, are relatively numerous and tedious.

Figure 2 is a perspective view of a removable clamp 200, according to some embodiments of the present invention. Figure 2 illustrates clamp 200 including a first support wall 210, which extends from a first end 211 thereof to a second end 212 thereof, a locking feature 250, which is connected to second end 212, and a second
20 support wall 220, opposite first support wall 210, which extends from a first, terminal end 221 thereof to a second end 222 thereof. Figure 2 further illustrates locking feature 250 being formed by a first sidewall 201, which extends from second end 212 of first support wall 210; first sidewall 201 is shown extending toward second support wall 220 and including a terminal portion 21 that bends toward first support wall 210.

According to the illustrated embodiment, first, terminal end 221 of second
25 support wall 220 bends away from first support wall 210, such that first, terminal end 221 can interlock with terminal portion 21 of first sidewall 201, when second support wall 220 is deflected toward first support wall 210. Figure 2 further illustrates second end 222 of second support wall 220 being flexibly connected to first end 211 of first
30 support wall 210 by a second sidewall 202, which extends opposite first sidewall 201, and allows for the deflection of second support wall 220. According to preferred embodiments, clamp 200 is an injection molded plastic part, such that each of walls

- 5 -

210, 201, 220, 202 are integrally formed. Clamp 200 is preferably formed from a polycarbonate resin, for a suitable combination of flexibility and strength; yet, those skilled in the art will appreciate that other plastic materials, which demonstrate similar flexibility and strength, may alternatively be employed. With reference to
5 Figures 1A and 2, according to an exemplary embodiment, when width W1 of filter 10 is approximately 1.14 inches, and a thickness t of filter 10 is approximately 0.356 inch, a width W3 of first support wall 210 is approximately 1.25 inches, and a height h of second sidewall 202 is approximately 0.375 inch.

According to the illustrated embodiment, after filter 10 is inserted between
10 support walls 210 and 220 of clamp 200, first, terminal end 221 of second support wall 220 may be engaged by locking feature 250, by simply pressing second support wall 220 toward first support wall 210. Figure 3A is a perspective view of filter 10 supported by clamp 200; and Figure 3B is a cross-section view through section line A-A of Figure 3A, according to some embodiments. Figures 3A-B illustrate first,
15 terminal end 221 of support wall 220 interlocking with terminal portion 21 of sidewall 201, in order to secure an inner surface of second support wall 220 against a first major surface 121 of filter sidewall 12A, and an inner surface of first support wall 210 against a second major surface 122 of filter sidewall 12B. Thus, clamp 200 supports housing 12 of inserted filter 10 against pressures that result from fluid flow through
20 filter 10, which may otherwise cause the joint, which connects first sidewall 12A to second sidewall 12B, at seam 123, to fail.

Figures 2 and 3B illustrate each of first and second support walls 210, 220 including an optional inward projecting plateau 245, which forms the corresponding inner surfaces of walls 210, 220; a width WP of each plateau 245 (Figure 2) may be
25 approximately 0.625 inch, when width W1 of filter 10 is approximately 1.14 inches. According to some preferred embodiments, the inner surfaces formed by plateaus 245 are spaced apart from one another at a distance that is less than a thickness t (Figure 1A) of filter 10, when locking feature 250 engages first, terminal end 221 of second support wall 220 to support housing 12; this spacing may be between
30 approximately 0.02 inch and approximately 0.05 inch less than thickness t. Figure 2 further illustrates second support wall 220 including an optional, outwardly projecting, strengthening feature 265, in the form of a rib.

- 6 -

With further reference to Figure 3A, it can be seen that no portion of clamp 200 extends over vent holes 126 of filter 10, when clamp 200 supports housing 12 of filter 10. According to an exemplary embodiment, when length L1 of filter 10 (Figure 1A) is approximately 1.575 inches, a length L3 of clamp 200 (Figure 2) is
5 approximately 0.625 inch.

Turning now to Figures 4A-B an exemplary medical infusion system, in which embodiments of the present invention may be employed, will now be briefly described. Figure 4A is a perspective view of a radiopharmaceutical infusion system 400; and Figure 4B is a perspective view of a portion of infusion system 400 that
10 includes a fluid circuit 300. Figure 4A illustrates infusion system 400 including a cabinet 410, in which a portion of fluid circuit 300 is enclosed, and which includes an access panel 432 by which enclosed fluid circuit 300 may be accessed for maintenance thereof. A shielding assembly 420 is also shown enclosed within cabinet 410 in order to shield radioactive segments of fluid circuit 300. Infusion
15 system 400 may be used for medical diagnostic imaging, for example, Positron Emission Tomography (PET), wherein doses of radiopharmaceutical, which are generated by elution within a radioisotope generator 321 (Figure 4B), are injected, or infused into a patient. The infused dose of radiopharmaceutical is absorbed by cells of a target organ, of the patient, and emits radiation, which is detected by a PET
20 scanner, in order to generate an image of the organ. An example of a radioactive isotope, which may be used for PET, is Rubidium-82 (produced by the decay of Strontium-82); and an example of a radioisotope generator, which yields a saline solution of Rubidium-82, via elution, is the CardioGen-82® available from Bracco Diagnostics Inc. (Princeton, NJ). Embodiments of such an infusion system 400 are
25 described in co-pending an commonly assigned U.S. patent application serial number 12/137,363 (Practitioner Docket number 56782.1.6), which is hereby incorporated by reference.

Figure 4A illustrates a reservoir 315 of fluid circuit 300, which is mounted outside cabinet 410, and Figure 4B illustrates a pump 333 of fluid circuit 300, which
30 is located within cabinet 410 and is supplied by reservoir 315, via a tubing line 310 that extends through a sidewall of cabinet 410. According to Figures 4A-B, pump 333 provides a pressure pulse to drive infusion injections, first through a filter, via an

- 7 -

input tubing line 325, and then through the remainder of tubing circuit 300, via an output tubing line 327. In order to assure quality diagnostic imaging, pressure pulses of between approximately 75 psi and approximately 125 psi are typically applied to inject doses, or boluses, of the radiopharmaceuticals, that are generated by system 400. Thus, those elements of fluid circuit 300, which are downstream of pump 333, must be able to withstand pressure pulses of up to, and possibly exceeding, approximately 125 psi. Furthermore, these elements of fluid circuit 300 are typically required to function for as many as 310 to 325 injection pulses, at these pressures.

According to some embodiments of the present invention, fluid circuit 300 of infusion system 400 incorporates filter 10, which is supported by clamp 200, for example, as is illustrated in Figures 3A-B. When inner surfaces of opposing support walls 210, 220 of clamp 200 are secured against surfaces 121, 122 of filter housing 12, as previously described, clamp 200 may prevent separation of housing sidewalls 12A, 12B at seam 123 when loaded under the aforementioned pressure pulses.

With reference to Figure 4B, input tubing line 325 may be connected to first fitting 152, at inlet 125 of filter 10, and output tubing line 327 to second fitting 172, at outlet 127 of filter 10. According to exemplary embodiments of system 400, filter 10 is the aforementioned Speedflow Adult 0.2 μ m Positive (GVS Group), and filter 10 and clamp 200 are each of a size defined by the corresponding and exemplary length, width, thickness and height dimensions set forth herein, above.

Filter 10, being supported by clamp 200, may be directly mounted within cabinet 410 of infusion system 400, for example, along an inside wall 407 thereof (Figure 4A). Alternatively, Figure 4B illustrates infusion system 400 including a holder 317 for filter 10 and clamp 200. Holder 317 may be formed from a thermoformed plastic sheet into a clam-shell structure, which encloses filter 10 and clamp 200 in an interior space, and allows inlet and outlet tubing lines 325, 327 to extend out from the interior space, in between opposing sides thereof. Holder 317 may be hung from a structure (not shown) along inside wall 407.

According to some methods of the present invention, in order to assemble filter 10 into fluid circuit 300, such that the filter can withstand the aforementioned pressure pulses without failure, filter 10 is first inserted between opposing support walls 210, 220 of clamp 200, either before or after connecting one or both of inlet

- 8 -

and outlet fittings 152, 172 to inlet and outlet tubing lines 325, 327, respectively. After filter 10 is inserted, the one assembling circuit 300, need only press second support wall 220 toward first support wall 210, or visa versa, in order to engage first, terminal end 221 of second support wall 220 with locking feature 250 of clamp 200, thereby securing inner surfaces of support walls 210, 220 against corresponding surfaces 121, 122 of filter 10. This securing step may be performed either before or after connecting inlet and outlet fittings 152, 172 of filter 10 to corresponding tubing lines 325, 327. When circuit 300 is disassembled, after a predetermined life, clamp 200 may be removed from filter 10, for example, by deflecting first and second sidewalls 201, 202 away from one another to release first, terminal end 221 of support wall 220 from the interlock with terminal portion 21 of first sidewall 201, so that clamp 200 may be re-used to support another filter.

In the foregoing detailed description, the invention has been described with reference to specific embodiments. However, it may be appreciated that various modifications and changes can be made without departing from the scope of the invention as set forth in the appended claims.

I claim:

1. A removable clamp (200) comprising:
 - a first support wall (210) that includes a first end (211), a second end (212) opposite the first end, and an inner surface formed by a first inward projecting plateau;
 - a second support wall (220) that is opposite the first support wall, the second support wall including a first, terminal end (221), a second end (222) opposite the first, terminal end, and an inner surface formed by a second inward projecting plateau, the second end of the second support wall being fixedly and flexibly connected to the first end of the first support wall to allow the first, terminal end of the second support wall to move toward and away from the first support wall; and
 - a locking feature (250) connected to the second end of the first support wall and being configured to engage and disengage the first, terminal end of the second support wall; and the clamp being characterized in that:
 - wherein the removable clamp is configured to support a housing (12) of a membrane filter (10) by receiving and locking the housing between the first support wall and the second support wall, and
 - wherein the first inward projecting plateau and the second inward projecting plateau are configured such that, when the removable clamp is assembled over the housing with the locking feature engaged with the first, terminal end of the second support wall, the first inward projecting plateau is positioned opposite and parallel to the second inward projecting plateau.
2. The clamp of claim 1, wherein the second support wall includes an outwardly projecting strengthening feature.
3. The clamp of claim 1, wherein the first and second support walls and the locking feature are integrally formed.

4. The clamp of claim 1, wherein the first and second support walls and the locking feature are integrally formed by injection molding.
5. The clamp of claim 1, wherein the first and second support walls and the locking feature are integrally formed from a polycarbonate resin.
6. The clamp of claim 1, wherein:
the locking feature is formed by a sidewall (201) extending from the second end of the first support wall to a terminal portion (21) thereof, the terminal portion bending toward the first support wall; and
the first, terminal end of the second support wall bends away from the first support wall, such that the first, terminal end interlocks with the terminal portion of the sidewall, when the locking feature engages the first, terminal end.
7. The clamp of claim 1, wherein the locking feature is formed by a first sidewall (201) extending from the second end of the first support wall; and further comprising a second sidewall (202) extending opposite the first sidewall to fixedly and flexibly connect the first end of the first support wall to the second end of the second support wall.
8. The removable clamp of claim 1, further comprising a membrane filter having a housing, the housing having a length (L1), a width (W1) which extends approximately orthogonal to the length, and a thickness (t), wherein the removable clamp is assembled over the housing, the first inward projecting plateau is spaced from the second inward projecting plateau such that the first inward projecting plateau and the second inward projecting plateau contact opposite surfaces of the housing.
9. The removable clamp of claim 8, wherein the housing includes vent holes protruding through a sidewall of the housing, and wherein at least one of the first and second support walls defines a length (L3) that is less than the length (L1) of the

housing of the membrane filter such that, when the removable clamp is assembled over the housing with the locking feature engaged with the first, terminal end of the second support wall, the clamp supports the housing without extending over the vent holes.

10. The removable clamp of claim 8, wherein the housing includes a first major surface, a second major surface opposite the first major surface, and wherein the first inward projecting plateau is spaced from the second inward projecting plateau by a distance less than the thickness of the housing, the thickness being defined as a distance from the first major surface to the second major surface.

11. A medical infusion system (400) for injecting radiopharmaceuticals into a patient, the infusion system comprising:

- a fluid circuit (300) through which pressure pulses of between approximately 75 psi and approximately 125 psi are applied;

- a membrane filter (10) connected between a fluid inlet line (325) of the fluid circuit and a fluid outlet line (327) of the fluid circuit, the membrane filter including a housing (12) that defines a length (L1), a width (W1), and a thickness (t); and

- a removable clamp (200), the removable clamp comprising:

- a first support wall (210) that includes a first end (211), a second end (212) opposite the first end, and an inner surface formed by a first inward projecting plateau;

- a second support wall (220) that is opposite the first support wall, the second support wall including a first, terminal end (221), and a second end (222) opposite the first, terminal end, and an inner surface formed by a second inward projecting plateau, the second end of the second support wall being fixedly and flexibly connected to the first end of the first support wall to allow the first, terminal end of the second support wall to move toward and away from the first support wall; and

- a locking feature (250) connected to the second end of the first support wall and being configured to engage and disengage the first, terminal end of the second support wall, the locking feature engaging the first terminal end of the second support wall of the assembled clamp to support the housing of the filter;

wherein the removable clamp is assembled about the membrane filter with the membrane filter locked between the first support wall and the second support wall, and

wherein the first inward projecting plateau is positioned opposite and parallel to the second inward projecting plateau.

12. The infusion system of claim 11, further comprising a cabinet enclosing the membrane filter, the removable clamp, and at least a portion of the fluid circuit.

13. The infusion system of claim 12, further comprising a holder (317) for the membrane filter and the removable clamp, assembled thereabout, wherein the cabinet includes an internal feature on which to hang the holder.

14. The infusion system of claim 11, wherein:

the locking feature of the removable clamp is formed by a sidewall (201) thereof extending from the second end of the first support wall of the clamp to a terminal portion (21) thereof, the terminal portion bending toward the first support wall of the clamp; and

the first, terminal end of the second support wall of the removable clamp bends away from the first support wall of the clamp, such that the first, terminal end interlocks with the terminal portion of the sidewall of the clamp, when the locking feature of the clamp engages the first, terminal end.

15. The infusion system of claim 11, wherein the first inward projecting plateau is spaced from the second inward projecting plateau such that the first inward projecting plateau and the second inward projecting plateau contact opposite surfaces of the housing.

16. The infusion system of claim 11, wherein the housing includes vent holes protruding through a sidewall of the housing, and wherein at least one of the first and second support walls defines a length (L3) that is less than the length (L1) of the

housing of the membrane filter such that the clamp is assembled over the housing without extending over the vent holes.

17. The infusion system of claim 11, wherein the housing includes a first major surface, a second major surface opposite the first major surface, and wherein the first inward projecting plateau is spaced from the second inward projecting plateau by a distance less than the thickness of the housing, the thickness being defined as a distance from the first major surface to the second major surface.