

FLOW RATE DEPENDENT FLOW CONTROL DEVICE

BACKGROUND OF THE DISCLOSURE

1. Field of the Disclosure

[0001] The present invention relates to fluid flow control for downhole tools.

2. Description of the Related Art

[0002] Control of fluid circulation can be of operational significance for numerous devices used in oil and gas wells. One illustrative example is a gravel packing tool used for gravel packing operations. In general, gravel packing includes the installation of a screen adjacent a subsurface formation followed by the packing of gravel in the perforations and around the screen to prevent sand from migrating from the formation to the production tubing. Usually, a slurry of gravel suspended in a viscous carrier fluid is pumped downhole through the work string and a cross-over assembly into the annulus. Pump pressure is applied to the slurry forcing the suspended gravel through the perforations or up against the formation sand. The gravel then accumulates in the annulus between the screen and the casing or the formation sand. The gravel forms a barrier which allows the in-flow of hydrocarbons but inhibits the flow of sand particles into the production tubing. Afterwards, a clean-up operation may be performed wherein a cleaning fluid is reverse circulated through the well to clean the tools of slurry and leaving only the gravel pack surrounding the screens behind.

[0003] The present disclosure provides methods and devices for controlling fluid circulation during gravel packing operations. The present disclosure also provides for controlling fluid circulation in other wellbore-related operations.

SUMMARY OF THE DISCLOSURE

[0004] In aspects, the present disclosure provides an apparatus for completing a well. The apparatus may include a tool configured have a first flow path in a first position and a second flow path in a second position. Each flow path allows fluid flow. The first flow path may include at least a port coupling the upper bore to a lower annulus surrounding the tool, a lower bore of the tool in communication with the lower annulus, and a mechanically static and bi-directional flow passage connecting the lower bore with an upper annulus surrounding the tool. The second flow path may include at least a first branch having the port coupling the upper annulus to the upper bore; and a second branch having a mechanically static and bi-directional flow passage coupling the upper annulus to the lower bore.

[0005] In aspects, the present disclosure also provides a method for completing a well using a tool disposed in the well. The method may include flowing a gravel slurry through an upper bore of the tool, a port coupling the upper bore to a lower annulus surrounding the tool, a lower bore of the tool in communication with the lower annulus, and a mechanically static and bi-directional flow passage connecting the lower bore with an upper annulus surrounding the tool; and flowing a cleaning fluid through a port coupling the upper annulus to the upper bore, and through a mechanically static and bi-directional flow passage coupling the upper annulus to the lower bore.

[0006] In still further aspects, the present disclosure provides a system for completing a well. The system may include a tool having an upper bore, a lower bore, and a port providing fluid communication between the upper bore and an exterior of the tool; a valve member selectively isolating the upper bore from the lower bore; a flow path formed in the tool, the flow path providing fluid communication between an exterior of the tool and the lower bore. The flow path

may include a mechanically static and bi-directional flow passage.

[0007] It should be understood that examples of the more illustrative features of the disclosure have been summarized rather broadly in order that detailed description thereof that follows may be better understood, and in order that the contributions to the art may be appreciated. There are, of course, additional features of the disclosure that will be described hereinafter and which will form the subject of the claims appended hereto.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The advantages and further aspects of the disclosure will be readily appreciated by those of ordinary skill in the art as the same becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings in which like reference characters designate like or similar elements throughout the several figures of the drawing and wherein:

Fig. 1 is a schematic elevation view of an exemplary production assembly;

Fig. 2 is a schematic cross-sectional view of a gravel pack tool that uses an exemplary flow control element made in accordance with one embodiment of the present disclosure;

Fig. 3 schematically illustrates a flow control device made in accordance with one embodiment of the present disclosure; and

Fig. 4 schematically illustrates a flow control device made in accordance with one embodiment of the present disclosure that is positioned for reverse circulation.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0009] The present disclosure relates to devices and methods for controlling fluid flow in downhole tools. The present disclosure is susceptible to embodiments of different forms. There are shown in the drawings, and herein will be described in detail, specific embodiments of the present disclosure with the understanding that the present disclosure is to be considered an exemplification of the principles of the disclosure, and is not intended to limit the disclosure to that illustrated and described herein.

[0010] Referring initially to **Fig. 1**, there is shown an exemplary well **10** that has been drilled into formations **14**, **16** from which it is desired to produce hydrocarbons. The wellbore **10** is cased by metal casing **17**, as is known in the art, and a number of perforations (not shown) penetrate and extend into the formations **14,16** so allow for in-flow of production fluids. The wellbore **10** may include a production assembly, generally indicated at **20**. Also, in certain situations, a tubing string (not shown) may extend downwardly from a wellhead **18** to the production assembly **20**. The production assembly **20** may be configured to control flow between the well **10** (**Fig. 1**) and the formations **14**, **16** (**Fig. 1**). The production assembly **20** may include a production tubular **22**, isolation elements **24**, and one or more filtration elements **26**. In one embodiment, the sealing members **24** may be packer elements that provide zonal isolation. The filtration element **26** may be a screen element that permits fluid flow into the tubular **22** while removing particles of a predetermined size from the in-flowing fluid.

[0011] For ease of explanation, embodiments of the present disclosure will be described in connection with a flow control device associated with a gravel pack tool. It should be understood, however, that the teachings of the present disclosure may be utilized in connection with any downhole tool that utilizes flow

control devices.

[0012] Referring now to **Fig. 2**, there is shown a production assembly **20** and a gravel pack tool **50**. The gravel pack tool **50** may be configured to deliver a granular material (or “gravel”) into the annular space **30** separating the filtration element **26** and the wall of the well **10**. In some embodiments, the wall may be the casing **17**. In other embodiments, the wall may be a rock face, *i.e.*, an open hole. In one embodiment, the tool **50** may include a bore **52**, a valve **54** that selectively occludes the bore **52**, and a cross over tool **55** that has a cross over port **56** that allows fluid flow between the bore **52** and the exterior of the tool **50**. One or more seal bores **57** may be used to channel fluid flow from the cross over tool **55** to the lower annulus **30**. As shown, the sealing member **24** isolates a lower annular zone **30** from an upper annular zone **32**. The tool **50** may also include a flow control device **58** that control flow between a lower bore **48** and the exterior of the tool **50**. The flow control device **58** may communicate with one or more axially aligned channels **64** that terminate at one or more ports **66**. The lower bore **48** may be a bore of the production tubular **22** or the gravel pack tool **50**.

[0013] Referring now to **Fig. 3**, there is shown in greater detail the flow control device **58** and related elements. In one embodiment, the flow control device includes a mechanically static and bi-directional flow control element **60** and a valve element **62**. The flow control element **60** and the valve element **62** may split the fluid into two separate flow paths such that fluid may flow through either or both of elements **60**, **62**. The term split does not require any particular ratio. The splitting may result in even or uneven flow rates across the flow control element **60** and the valve element **62**. In the electrical sense, the separate flow paths may be considered parallel because the two flow paths receive fluid from the same source and flow the fluid into a common point. Of course, some

embodiments may utilize more than two separate flow paths. Additionally, it should be understood that the flow does not necessarily remain separated until the fluid reaches the upper annular zone **32**. That is, the fluids flowing separately through the flow control element **60** and the valve element **62** may rejoin in an annular space or cavity and then enter the axially aligned channel(s) **64**. Thus, the fluid path between the lower bore **48** and the upper annular zone **32** may have a first section with split flow and then a second section with combined flow.

[0014] By mechanically static, it is generally meant that the flow control element **60** does not substantially change in size or shape or otherwise change in configuration during operation. In contrast, a mechanically dynamic device may include a flapper valve, a multi-position valve, a ball valve and other devices that can, for example, change a size of a cross sectional flow area during operation. Thus, in aspects, the term mechanically static includes structures that have a fixed dimension, orientation, or position during operation. In some arrangements, the flow control element **60** may include helical channels, orifices, grooves and other flow restricting conduits. In embodiments, the length and configuration of the helical channels may be selected to apply an amount of frictional losses in order to generate a predetermined amount of back pressure along the flow control device **58**. In embodiment, the shape and diameter of an orifice or orifices may be selected to reduce a cross-sectional flow area such that a desired predetermined amount of back pressure is generated in the flow control device **58**. These flow paths may be formed on an inner surface **70** of the tool **50**. A sleeve **72** may be used to enclose and seal the flow paths such that fluid is forced to flow along these flow paths. These features may be configured to generate a specified pressure drop such that a back pressure is applied to the channels **64**. The applied back pressure forces the fluid to flow into the upper bore **52** as described in greater detail below. The valve element **62** may be a one-way valve configured to allow flow from the lower bore **48** and block flow

-7-

from channels **64**, i.e., uni-directional flow. The valve element **62** may also utilize a biased piston that opens when a preset pressure differential is present between the bore **48** and the channels **64**; e.g., a pressure in the bore **48** that exceeds the pressure in the channels **64** by a preset value.

[0015] In the circulation mode, the tool **50** is positioned inside the production assembly **20**. After the seal bore **57** has been activated, surface pumps may pump slurry down the bore **52** of the gravel pack tool **50**. The slurry flows through the cross over port **56** and into the lower annulus **30**. The slurry may include a fluid carrier such as water, oil, brine, epoxies or other fluids formulated to convey entrained solids or semi-solids. The fluid component of the slurry flows through the filtration elements **26** and into the lower bore **48**. The solid or particulated components of the slurry pack into the lower annulus **30**. The fluid component flows up the lower bore **48** and through the flow control device **58**. Due to the relatively low fluid velocity, the fluid component may flow across both the valve element **62** and the flow control element **60**. Thereafter, the fluid components flow to the surface via the channels **64**, the ports **66**, and the upper annulus **32**. This circulation is maintained until a sufficient amount of particles, e.g., gravel, have been deposited into the lower annulus **30**. Thus, during a circulation mode, the tool **50** is positioned and configured to have a specified flow path for the gravel slurry material. As used herein, the term "flow path" refers to a structure that allows fluid to flow through rather than collect.

[0016] Referring now to **Fig. 4**, after the packing operation is completed, the gravel pack tool **50** is shifted uphole such that the cross over port **56** is positioned to communicate with the upper annulus **32** while the valve **54** is positioned to block fluid communication into the production assembly **20**. In this configuration, a reverse circulation may be performed to clean the bore **52** of slurry. For example, a cleaning fluid **74** (e.g., a liquid such as water or brine) is pumped

down via the upper annulus **32**. This fluid enters the bore **52** via the cross over port **56**. Thereafter, the cleaning fluid flows up the bore **52** to the surface. During this reverse circulation, the cleaning fluid also flows into the ports **66** and downwardly through the channels **64** to the flow control device **58**. That is, the cross over port **56** and the ports **66** may split the fluid into two separate flow paths, with one path leading to the upper bore **52** and another path leading to the lower bore **48**. The term split does not require any particular ratio and may result in even or uneven flow rates across the cross over port **56** and the ports **66**. Thus, during a cleaning mode, the tool **50** is re-positioned to have a different flow path from the circulation flow path.

[0017] The valve element **62** may be configured to prevent fluid flow during reverse circulation, which then forces the fluid to flow across the flow control element **60**. Because a relatively high fluid flow rate is used during reverse circulation, the flow control element **60** generates a back pressure across the channels **64** which acts to restrict fluid flow. Thus, most of the fluid passes through the cross over port **56**. In other situations, the valve element **62** may intentionally or inadvertently fail to close. In such situations, the flow control element **60** still provides a mechanism to generate a back pressure in the passages **64**. Reverse circulation is maintained until the bore **52** and other downhole components are cleaned of slurry. It should be understood that in certain embodiments, the valve element **62** may be omitted.

[0018] In embodiments, the slurry is circulated at a slower flow rate than the cleaning fluid. Because of the higher flow rate of the cleaning fluid, a greater back pressure is generated by the flow control element **62**.

[0019] After reverse circulation has been completed, the gravel pack tool **50** may be repositioned at another location in the wellbore to perform a subsequent gravel pack operation. For example, the tool **50** may be moved from the

formation **14** to the formation **16**. Each subsequent operation may be performed as generally described previously. It should be appreciated that as the gravel pack tool **50** is pushed into the well **10**, the fluid residing in the well **10** can bypass the valve **54** via the flow control element **60**. Thus, “surge” effect can be minimized. Surge effect is a pressure increase downhole of a moving tool caused by an obstruction in a bore. Also, as the tool **50** is pulled out of the well, the fluid uphole of the tool **50** can by bypass the valve **54** via the flow control element **60**. Thus, “swab” effect can be minimized. Swab effect is a pressure decrease downhole of a moving tool caused by an obstruction in a bore.

[0020] As stated previously, the teachings of the present disclosure may be utilized in connection with any downhole tool that utilizes flow control devices. Such flow control devices may be used in connection with tools that set packers, slips, perform pressure tests, etc. Also, such flow control devices may be used in drilling systems.

[0021] The foregoing description is directed to particular embodiments of the present invention for the purpose of illustration and explanation. It will be apparent, however, to one skilled in the art that many modifications and changes to the embodiment set forth above are possible without departing from the scope and the spirit of the invention. It is intended that the following claims be interpreted to embrace all such modifications and changes.

CLAIMS

WE CLAIM:

1. An apparatus for completing a well, comprising:

a tool having an upper bore and a lower bore, the tool being configured have a first flow path in a first position and a second flow path in a second position, each flow path allowing fluid flow, and wherein:

(i) the first flow path includes at least a port coupling an upper bore to a lower annulus surrounding the tool, a lower bore in communication with the lower annulus, and a mechanically static and bi-directional flow passage connecting the lower bore with an upper annulus surrounding the tool; and

(ii) the second flow path includes at least a first branch having the port coupling the upper annulus to the upper bore; and a second branch having a mechanically static and bi-directional flow passage coupling the upper annulus to the lower bore.

2. The apparatus of claim 1 wherein the mechanically static and bi-directional flow passage is configured to generate a back pressure along at least a portion of the second flow path.

3. The apparatus of claim 2, wherein the mechanically static and bi-directional flow passage includes a flow space selected from a group consisting of (i) at least one helical channel generating the back pressure using frictional losses, and (ii) an orifice generating the back pressure using a reduction in flow area.

4. The apparatus of claim 1 wherein the second branch includes at least one

passage connecting the upper annulus with mechanically static and bi-directional flow passage, and wherein the mechanically static and bi-directional flow passage is configured to generate a predetermined back pressure along the at least one channel.

5. The apparatus of claim 1 further comprising: (i) a supply of gravel slurry coupled to the upper bore when the tool is in the first position, and (ii) a supply of a cleaning fluid coupled to the upper annulus when the tool is in the second position.

6. The apparatus of claim 1, wherein the first flow path includes a valve element, the valve element configured to allow uni-directional flow from the lower bore to the upper annulus.

7. The apparatus of claim 6 wherein the mechanically static and bi-directional flow passage and the valve element split fluid flowing from the lower bore such that the fluid has two separate flow paths to the upper annulus.

8. A method for completing a well using a tool disposed in the well, the method comprising:

flowing a gravel slurry through an upper bore of the tool, a port coupling the upper bore to a lower annulus surrounding the tool, a lower bore of the tool in communication with the lower annulus, and a mechanically static and bi-directional flow passage connecting the lower bore with an upper annulus surrounding the tool; and

flowing a cleaning fluid through a port coupling the upper annulus to the upper bore, and through a mechanically static and bi-directional flow passage coupling the upper annulus to the lower bore.

-12-

9. The method of claim 8 generating a back pressure in the cleaning fluid using the mechanically static and bi-directional flow passage.

10. The method of claim 9, wherein the mechanically static and bi-directional flow passage includes a flow space selected from a group consisting of (i) at least one helical channel generating the back pressure using frictional losses, and (ii) an orifice generating the back pressure using a reduction in flow area.

11. The method of claim 8 further comprising generating a predetermined back pressure in the cleaning fluid in at least one passage coupling the mechanically static and bi-directional flow passage to the upper bore.

12. The method of claim 8 further comprising moving the tool after flowing the gravel slurry but before flowing the cleaning fluid.

13. The method of claim 8 further comprising splitting the cleaning fluid flowing in the upper annulus into a first flow path to the upper bore and a second flow path the lower bore of the tool.

14. A system for completing a well, comprising:

- a tool having an upper bore, a lower bore, and a port providing fluid communication between the upper bore and an exterior of the tool;

- a valve member selectively isolating the upper bore from the lower bore;
- and

- a flow path formed in the tool, the flow providing fluid communication between an exterior of the tool and the lower bore, the flow path including a mechanically static and bi-directional flow passage.

15. The system of claim 14, wherein the flow path includes a valve member configured to provide uni-directional flow from the lower bore to the exterior of the tool, wherein the valve member and the mechanically static and bi-directional flow passage provide split flow from the lower bore.

16. The system of claim 14, wherein the mechanically static and bi-directional flow passage is configured to generate a back pressure along at least a portion of the flow path.

17. The system of claim 14, wherein the mechanically static and bi-directional flow passage includes a flow space selected from a group consisting of (i) at least one helical channel generating the back pressure using frictional losses, and (ii) an orifice generating the back pressure using a reduction in flow area.

18. The system of claim 14, further comprising a production assembly configured to receive the tool, the production assembly including at least one filtration element filtering fluid flowing into the production assembly.