

TRAINING DEVICE FOR GRENADE LAUNCHERS

FIELD OF THE INVENTION

[0001] This invention is directed to a system for military training. More particularly, this invention is directed to a system allowing for realistic force-on-force simulated training with low velocity grenade launchers, high velocity grenade launchers, and certain shoulder-launched weapons.

BACKGROUND OF THE INVENTION

[0002] The U.S. military, as well as military forces in other countries, has trained soldiers for many years with a multiple integrated laser engagement system (MILES). One aspect of MILES involves a small arms laser transmitter (SAT), such as a gallium arsenide laser transmitter, which is affixed to the barrel of a small arms weapon or a machine gun. The soldier pulls the trigger of his or her weapon to fire a blank or blanks to simulate the firing of an actual round or multiple rounds. Each soldier is fitted with laser sensitive optical detectors on his or her helmet and on a body harness adapted to detect an infrared laser "bullet" hit. A semiconductor laser diode in the SAT is energized to emit an infrared laser beam toward the target in the conventional sights of the weapon. The infrared laser beam is encoded with the soldier's player identification code. Optionally each soldier wears a digital player control unit that tells the player whether he or she has suffered a particular type of casualty or had a near miss, the time of the event and the identity of the shooter.

[0003] The MILES devices allow for realistic force-on-force training (simulation) of military forces. MILES systems work very effectively with direct fire weapons. However, the training of weapons with indirect fire ballistics, such as modern grenade weapons, including but not limited to, MK19, MK47, M203, M79, M320, and MK13 grenade launchers, is not compatible with MILES systems.

[0004] The launching of grenades or other projectiles in a combat situation is an important part of military operations. There has been a definite need to provide more effective training for automatic or hand-held grenade launchers.

SUMMARY OF THE INVENTION

[0005] It is an objective of this invention to provide a novel system for military training.

[0006] It is also an objective of this invention to provide an effective training for weapons that launch grenades or other projectiles.

[0007] These objectives, as well as further objectives which will become apparent from the discussion that follows, are achieved, according to the present invention, by providing a novel system useful for training soldiers in the operation and/or use of a grenade launcher. The system includes a training assembly with a laser having a focal array to direct the laser beam. A control unit or controller records and measures the angle between the longitudinal axis of the training assembly housing and the barrel bore elevation (or longitudinal axis), the

initiation of a blank (or simulated) trigger pull, and the direction of earth gravity.

[0008] The training assembly is rotatably attached or connected via a shaft or connection member to the body of a grenade launcher comprising a body and a barrel. The training assembly initially is positioned so that the longitudinal axis of the training assembly and/or the direction of the laser is substantially parallel to the longitudinal axis of the barrel.

[0009] Once a soldier aims the grenade launcher in an intended direction, so that both the barrel and training assembly are pointed in an elevated manner, the soldier then pulls the trigger to simulate a firing. After sensing the firing, the training assembly rotates in a clockwise or counterclockwise manner (dependent upon position) at a rate corresponding to the post firing trajectory of a projectile or cartridge. The rotation is configured so that the longitudinal axis of the training assembly reaches horizontal, or an elevation depressed or elevated from horizontal, at the time that a projectile or cartridge would land. The output of the laser increases as the training assembly rotates. Beam divergence can be optimized to replicate a lethal impact area.

[00010] In another aspect of the invention, the training assembly is positioned or moves in the x-direction to simulate expected drift due to either the inertia of the ballistics or wind, or both.

[00011] The laser comprises a lower power laser suitable for emitting useful radiation. For example, semiconductor laser

diodes emit useful radiation having wavelengths in the range of from about 850 to about 910 nanometers.

[00012] A connector member or connector connects the training assembly to the body of a grenade launcher. The connection member comprises a shaft, and a motor in the training assembly engages the shaft to enable the training assembly to rotate as intended. Also, in one embodiment of the invention, the motor and shaft or shaft and connection member are configured so that the training assembly can rotate away from a vertical plane of the grenade launcher, in the x-direction.

[00013] The axis of device rotation and bore alignment are configured to simulate drift as the training assembly deflects. Burst fire is simulated as trigger pull/blank fire initiates delayed laser shots.

[00014] The training assembly comprises sensors to measure, for example, the direction of earth gravity, the position or elevation of the training assembly as compared to horizontal or the elevation of a target site or area (an inclinometer), the angle of the assembly to the bore elevation, movement or the rate of movement (an accelerometer), or the initiation of a blank or simulated trigger pull, or two or more of the foregoing.

[00015] A control unit, or controller, is operatively connected to the laser, the motor, and the sensors.

[00016] In another aspect of the invention one or more MILES sensors are positioned at the intended target area. As the training device rotates to horizontal or, if not horizontal, the

elevation of a target area, a laser beam hits one or more sensors to register a successful fire.

[00017] The strength of the laser beams can vary. As the training device rotates to horizontal or, if not horizontal, the elevation of a target area, the laser beam should be at full strength, to reach the sensors at the target areas.

[00018] In another aspect of the invention, a system useful for training soldiers in the operation and use of a grenade launcher having a body and a barrel, comprises:

a training assembly capable of being rotatably attached to the body of the launcher, comprising:

a housing;

a variable output laser within the housing to produce a laser beam along a longitudinal axis;

a shaft extending through the housing to the body of the grenade launcher;

a motor within the housing that engages the shaft and is capable of causing the housing to rotate about the shaft;

at least one sensor within the housing or attached to the housing to detect rotation of the housing, trigger pull, and/or gravitational direction; and

a control unit within the housing or attached to the housing and operationally connected to the laser, the at least one sensor, and the motor; and

at least one sensor to detect laser energy at a target site.

[00019] In another aspect of the invention, the laser has a focal array to direct the laser beam.

[00020] In another aspect of the invention, the control unit records and measures an angle between the longitudinal axis of the housing and the barrel elevation, the initiation of a blank or simulated trigger pull, and the direction of earth gravity.

[00021] In another aspect of the invention, the training assembly is rotatably attached or connected to the body of the grenade launcher.

[00022] In another aspect of the invention, the training assembly is attached or connected through a shaft or connector.

[00023] In another aspect of the invention, the training assembly initially is positioned so that a longitudinal axis of the training assembly and the laser beam is substantially parallel to a longitudinal axis of the barrel.

[00024] In another aspect of the invention, sensors to sense radiation are positioned at an intended target area.

[00025] In another aspect of the invention, as the training device rotates to the elevation corresponding to the target area,

a laser beam hits one or more sensors to register a successful fire.

[00026] In another aspect of the invention, the training assembly is positioned or moves in the x-direction to simulate expected drift due to at least one of the inertia of the ballistics and wind.

[00027] In another aspect of the invention, the laser comprises a lower power laser suitable for emitting useful radiation.

[00028] In another aspect of the invention, a shaft extends through or comprises a connector member to connect the training assembly to the body of a grenade launcher.

[00029] In another aspect of the invention, a motor in the training assembly engages the shaft to enable the training assembly to rotate as intended.

[00030] In another aspect of the invention, the motor and shaft are configured so that the training assembly can rotate away from a vertical plane of the grenade launcher, in the x-direction.

[00031] In another aspect of the invention, the axis of device rotation and bore alignment are configured to simulate drift as the training assembly deflects.

[00032] In another aspect of the invention, the sensors in the training assembly measure at least one of the direction of earth gravity, the position or elevation of the training assembly as compared to horizontal, the angle of the assembly to the bore

elevation, movement or the rate of movement, and the initiation of a blank or simulated trigger pull.

[00033] In another aspect of the invention, a method of training an individual to fire a grenade launcher comprises the steps of:

providing a grenade launcher having a barrel and a body and a training assembly rotatably attached to the body of the grenade launcher;

aiming the grenade launcher in an intended direction, and aiming the training assembly in the same direction, so that both the barrel and training assembly are pointed in an elevated manner;

pulling a trigger of the grenade launcher to simulate a firing; and

after firing, rotating the training assembly rotates at a rate corresponding to the post firing trajectory of a projectile or cartridge and for a time corresponding to the time it would take a projectile to land at a target area,

thereby causing the laser a beam to actuate at least one sensor at the target area.

[00034] For a full understanding of the present invention, reference should now be made to the following detailed description of the preferred embodiments of the invention as illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[00035] Figs. 1A and 2B are schematic representations of a top view and a lateral view, respectively, of a training assembly according to the invention attached to a grenade launcher;

[00036] Figs. 2A and 2B are schematic representations of a substantially cross-sectional top view and lateral view, respectively, of a training assembly according to the invention;

[00037] Figs. 3A and 3B are schematic representations of a training system according to the invention;

[00038] Fig. 4 is a graph of the intensity of laser light output versus range or time;

[00039] Fig. 5 is a schematic representation of a laser beam dispersion pattern at a target;

[00040] Figs. 6A to 6D are schematic representations of lateral views of use of a training assembly mounted on a grenade launcher;

[00041] Figs. 7A to 7D are schematic representations of top views of the training assembly and grenade launcher shown in Figs. 6A to 6D, respectively;

[00042] Fig. 8 is a graph representing depression angle verses time;

[00043] Figs. 9A and 9B are schematic representations of lateral views of use of a training assembly mounted on a grenade launcher;

[00044] Figs. 10A and 10B are schematic representations of top views of the training assembly and grenade launcher shown in Figs. 9A and 9B, respectively;

[00045] Fig. 11 is a graph of deflection and angular draft versus distance;

[00046] Fig. 12 is a schematic representation of burst fire simulation; and

[00047] Figs. 13 to 15 are schematic representations of lateral, top, and rear views, respectively, of a training assembly positioned on a grenade launcher according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

[00048] The preferred embodiments of the present invention will now be described with reference to Figs. 1-15 of the drawings. Identical elements in the various figures are designated with the same reference numerals

[00049] In the schematic representations of a top view and a lateral view, respectively, shown in Figs. 1A and 1B, a grenade launcher 2 has a body 4 and a barrel 6. A training assembly 10 is rotatably attached through a connector 12 to body 4. The longitudinal axis 14 of training assembly 10 is parallel to the longitudinal axis 16 of barrel 6.

[00050] Figs. 2A and 2B comprise schematic representations of substantially cross-sectional top and lateral views, respectively, of a training assembly 10. Training assembly 10

comprises a laser 22 that generates a beam that passes through focal array 24. A motor 26 is operationally connected to a connector/shaft 28 to rotate training assembly 10 about connector/shaft 28. Connector/shaft 28 connects to the body of a grenade launcher, such as body 4.

[00051] Training assembly 10 has a rotational sensor 30 to measure rotation about connector/shaft 28 and an inclinometer 32 to measure horizontal position. There is a power source 34 such as a battery and a control circuit or controller 36.

[00052] For a hand held device, such as an M203 or M320 grenade launcher, training assembly 10 may optimally comprise a stabilizer (not shown). The stabilizer would allow training assembly 10 to counter hand movement after firing.

[00053] The schematic representations in Figs. 3A and 3B represent firing sequences. Fig. 3A represents a lateral view of a training assembly 50 attached to a grenade launcher 52. Upon sensing a blank firing (or simulated trigger pull), training assembly 50 rotates (depresses) in clockwise or y- direction at a rate that simulates a post firing trajectory (y- position/drop) of a projectile in flight. A sensor (not shown) in training assembly 50 measures the relative position or effect of gravity, which will affect the ballistics of an automated grenade launcher (AGL), and a controller (not shown) in training assembly 50 adjusts the rate of rotation, also factoring in the relative elevation of firing position as compared to the target position.

[00054] The rate of rotation of the training assembly 50 allows for alignment of the laser (with targets) at time intervals. The time intervals and alignment resulting from rotation/depression

of the training assembly coincide with the simulated ballistic position/drop of a projectile in flight.

[00055] As training assembly 50 rotates or depresses, the intensity of the laser increases. At shorter distances, the laser output is lower. In Figs. 3A and 3B, the terminal laser light is optimized to reasonably match the range and dispersion of a 40mm projectile.

[00056] The graph shown in Fig. 4 is an estimate of the intensity of the laser output over distance and/or time.

[00057] Fig. 5 is a schematic representation of the width of a laser beam 60 at a simulated target point 62. The laser beam width is intended to approximate the width of a projectile burst at that distance. The focal array on training assembly 50 can change the laser beam dispersion at an intended range.

[00058] Another aspect of the invention is shown in lateral views in Figs. 6A to 6D and in top views in Figs. 7A to 7D. In Fig. 6A a training assembly 66 is rotatably mounted on a grenade launcher 68 having a body 70 and a barrel 72. A focal array 74 of training assembly 66 will focus a laser beam along longitudinal axis 76, which will be parallel in the y-direction to longitudinal axis 78 of barrel 72. A gunner's line of sight 80 extends from the rear of grenade launcher 68 to a target (not shown). In Figure 7A, as shown in a top view, longitudinal axis 76 is parallel to longitudinal axis 78 in the x-direction.

[00059] A gunner aligns a weapon sight with a target, as shown in Fig. 6A, and training assembly 66 is aligned with the bore of barrel 72 when grenade launcher 68 is "fired". After training

assembly 66 senses firing, the rate of rotation or depression of training assembly 66, as shown in Figs. 6B and 6C, coincides with the simulated post firing "y" ballistic position of a projectile, as represented in the graph in Fig. 8. The laser fires light pulses as training assembly 66 rotates.

[00060] The lateral view of Fig. 6D is intended to represent a composite of the initial gunner's line of sight to the target as compared to the laser beam aligned to the target as training assembly 66 rotated to its final position, which is horizontal, or, if not horizontal, depressed or elevated from horizontal.

[00061] The power of the laser increases as training assembly 66 rotates. Thus, as training assembly 66 rotates to a position corresponding to the elevation of the target, the power increases to a point that the light output triggers MILES sensors.

[00062] The top views of Figs. 7A to 7D correlate to the lateral views of Figs. 6A to 6D, respectively. As training assembly 66 rotates, the "x" (lateral) alignment between grenade launcher 68 and training assembly 66 simulates the actual "x" drift of a projectile in flight.

[00063] The movement of the training assembly is intended to replicate the actual "x" drift of a projectile in flight. The shift in "x" mis-alignment occurs as the training assembly rotates in the "y" direction.

[00064] The graph in Fig. 8 represents the projected depression angle in mils over a period of time for a simulated trajectory of a grenade or other projectile.

[00065] The relationship between rotation of a training assembly and drift is shown with more particularity in Figs. 9A to 10B. Figs. 9A and 9B are lateral views of a training assembly 84 positioned on a grenade launcher 86 having a body 88 and a barrel 90. Fig. 9A represents training assembly 84 and grenade launcher 88 at firing, while Fig. 9B represents a post firing configuration where training assembly 84 has rotated in a clockwise manner.

[00066] In the corresponding top views of Figs. 10A and 10B, a longitudinal axis or centerline 94 of barrel 90 is parallel to a longitudinal axis 96 of the laser beam from training assembly 84. As seen in Fig. 10B, however, the angular rotation of longitudinal axis 96 away from longitudinal axis 94 matches or approximates actual ballistic projectile drift.

[00067] The relationship between deflection and angular draft (mils deflection) versus distance is shown in Fig. 11. The ordinate is the distance in meters of projectile travel whereas the abscissa is the mils of deflection in the angle between the two longitudinal axes.

[00068] In one aspect of the invention burst fire can be simulated, as shown in Fig. 12. In this sequence a training assembly 102 or grenade launcher 104 senses multiple blank fires, or bursts. Once the training to assembly 102 rotates to the proper deflection, e.g., to horizontal, multiple laser bursts 106 simulate the blank fires. After the shots or bursts are final, the training assembly rotates back to its starting position.

[00069] It is possible to select an axis of rotation (relative to the gun barrel) according to the invention that allows for a

good approximation and simulation of ballistic drift. The formulas below, which are based upon variables set forth in the schematic representations of Figs. 13 to 15, express the position of the device rotational axis to properly simulate ballistic (flight) drift.

(a) At a given time (range) the change in X (deflection) is expressed as a resultant change in Θ .

(b) At a given time (range) the change in Y (drift) is expressed as a resultant change in Φ .

(c) Change in X (deflection) creates change in Y (drift) as determined by the mounting angle Δ .

$$\Delta = \cot (X_{Tx} / Y_{Tx})$$

Hence

$$\Delta = \cot (\Theta / \Phi)$$

In cases where the relationship between X and Y is (or near) constant, a single angle provides a satisfactory solution.

[00070] The angle is selected for the design use of the (above) geometric relationships along with an analysis of the standard ammunition ballistics. The resulting angle is a device simulates (proper alignment) of a laser impulse corresponding to the drift of a grenade (projectile) in flight.

[00071] There has thus been shown and described an improved training system for grenade launchers which fulfills all the objects and advantages sought therefore. Many changes, modifications, variations and other uses and applications of the

subject invention will, however, become apparent to those skilled in the art after considering this specification and the accompanying drawings which disclose the preferred embodiments thereof. All such changes, modifications, variations and other uses and applications which do not depart from the spirit and scope of the invention are deemed to be covered by the invention, which is to be limited only by the claims which follow.

C L A I M S

What is claimed is:

1. A system useful for training soldiers in the operation and use of a grenade launcher having a body and a barrel, which comprises:

a training assembly capable of being rotatably attached to the body of the launcher, comprising:

a housing;

a variable output laser within the housing to produce a laser beam along a longitudinal axis;

a shaft extending through the housing to the body of the grenade launcher;

a motor within the housing that engages the shaft and is capable of causing the housing to rotate about the shaft;

at least one sensor within the housing or attached to the housing to detect rotation of the housing, trigger pull, and/or gravitational direction; and

a control unit within the housing or attached to the housing and operationally connected to the laser, the at least one sensor, and the motor; and

at least one sensor to detect laser energy at a target site.

2. The system of claim 1, wherein a power source is in communication with each of the control unit, the laser, and the motor.

3. The system of claim 1, wherein the laser has a focal array to direct the laser beam.

4. The system of claim 1, wherein the control unit records and measures an angle between the longitudinal axis of the housing and the barrel elevation, the initiation of a blank or simulated trigger pull, and the direction of earth gravity.

5. The system of claim 1, wherein the training assembly is rotatably attached or connected to the body of the grenade launcher.

6. The system of claim 5, wherein the training assembly is attached or connected through a connector.

7. The system of claim 1, wherein the training assembly initially is positioned so that a longitudinal axis of the training assembly and/or the laser beam is substantially parallel to a longitudinal axis of the barrel.

8. The system of claim 1, wherein the control unit is operatively connected to the laser, the motor, and the sensors.

9. The system of claim 1, wherein two or more sensors to detect laser energy are positioned at an intended target area.

10. The system of claim 1, wherein as the training device rotates to the elevation of the target site, a laser beam hits one or more sensors to register a successful fire.

11. The system of claim 1, wherein the training assembly is positioned or moves in the x-direction to simulate expected drift due to at least one of the inertia of the ballistics and wind.

12. The system of claim 1, wherein the laser comprises a lower power laser suitable for emitting useful radiation.

13. The system of claim 1, wherein a shaft extends or comprises through a connector member to connect the training assembly to the body of a grenade launcher.

14. The system of claim 1, wherein a motor in the training assembly engages the shaft to enable the training assembly to rotate as intended.

15. The system of claim 1, wherein the motor and shaft are configured so that the training assembly can rotate away from a vertical plane of the grenade launcher, in the x-direction.

16. The system of claim 1, wherein the axis of device rotation and bore alignment are configured to simulate drift as the training assembly deflects.

17. The system of claim 1, wherein the sensors in the training assembly measure the direction of earth gravity, the position or elevation of the training assembly as compared to horizontal or the elevation of the target site, the angle of the

assembly to the bore elevation, movement or the rate of movement, and/or the initiation of a blank or simulated trigger pull.

18. A method of training an individual to fire a grenade launcher, which comprises the steps of:

providing a grenade launcher having a barrel and a body and comprising a laser-equipped training assembly rotatably attached to the body of the grenade launcher;

aiming the grenade launcher in an intended direction, and aiming the training assembly in the same direction, so that both the barrel and the training assembly are pointed in an elevated manner;

pulling a trigger of the grenade launcher to simulate a firing; and

after firing, rotating the training assembly at a rate corresponding to the post firing trajectory of a projectile or cartridge and for a time corresponding to the time it would take a projectile to land at a target area,

thereby causing the laser beam to actuate at least one sensor at the target area.