

Description**Technical Field**

This invention relates to staple cartridges used in devices for driving staples and the combination of a stapler and a staple cartridge.

Background Information

EP-A-0 130 784 describes generally the same bone stapling device described in this application which has numerous novel design features which facilitate driving staples into bone portions during surgery. Generally, the bone stapler described in EP-A-0 130 784 and in this application are staplers of the type adapted for use with generally U-shaped staples. The staplers comprise a housing having a passageway extending from an inlet opening to an outlet opening, which passageway is adapted to guide a single staple moved from the inlet to the outlet opening. Means are provided for biasing a stack of staples into the inlet opening, together with a driver having an end portion adapted to engage the central portion of a staple. The driver is mounted on the housing for sliding movement between a load position spaced from the inlet opening to afford movement of one of the staples of the stack into the passageway, along the passageway with the end portion of the driver pushing the staple, and to an eject position at which the driver pushes the staple out the outlet opening. Also manually activatable drive means are provided for rapidly and forcefully propelling the driver along the passageway from its load position to its eject position to move a staple from the inlet opening to the outlet opening and drive the staple into portions of bone adjacent the outlet opening.

The novel features described in the above mentioned prior application include a removable cartridge which precludes leaving a staple in the stapler that could be inadvertently driven after the cartridge is removed. The case in that cartridge comprises guide wall means defining an inner surface at the end of a stack of staples opposite a follower and side walls projecting normal to the inner surface, which side walls have opposed transverse openings at the inner surface and aligned with the passageway when the cartridge is in the stapler. The inner surface defined by the guide wall means defines a portion of the passageway for the driver at the inlet opening, with the driver being movable through the transverse openings and along the inner surface between its load and the eject positions. Thus because all of the staples remain within the cartridge until they are driven, the user can be assured that all the staples are removed from the stapler when the cartridge is re-

moved.

Disclosure of the Invention

The present invention provides a cartridge and a stapler generally of the types described above, but which include novel attachment means for releasably attaching the cartridge to the stapler that are less expensive to manufacture and significantly easier to use than the attachment means described in the applications described above.

According to one aspect of this invention there is provided a combination of a stapler and a staple cartridge with generally U-shaped staples each comprising a central portion and two generally parallel leg portions projecting generally in the same direction from opposite ends of its central portion and having distal ends; the stapler comprising: a housing having a passageway extending from an inlet opening to an outlet opening, the passageway being adapted to guide a single staple moved from the inlet opening to the outlet opening with the distal ends of its legs leading; a driver having an end portion adapted to engage the central portion of one of the staples and being mounted on the housing for sliding movement between a load position spaced from the inlet opening to afford movement of one of the staples into the passageway, along the passageway with the end portion pushing the staple, to an eject position at which the end portion of the driver pushes the staple out the outlet opening; and drive means adapted to be manually activated for propelling the driver along the passageway from the load to the eject position to move the staple from the inlet opening to the outlet opening; and the staple cartridge comprising: a case, a stack of said staples within the case, and a follower on one side of the stack of staples and movable within the case with the stack of staples, and a spring for biasing the follower and the stack of staples, the combination being characterised in that the housing of the stapler includes a support wall having an inner surface defining a socket at the inlet opening, the support wall also having an outer surface, and a through opening between the inner surface and the outer surface; and the case of the staple cartridge comprises a guide wall defining an inner surface and side walls projecting generally normal to the inner surface, the side walls having opposed transverse openings at the inner surface and aligned with the passageway of the stapler, the guide wall being received in the socket with the inner surface of the guide wall defining a portion of the passageway at the inlet opening so that the driver can be moved through the openings and along the inner surface between the load and eject positions, the follower being on the side of the stack of staples opposite

the passageway such that the spring biases the follower and the staples toward the inner surface of the case; and a locking member for releasably retaining the case of the cartridge in engagement with the housing of the stapler, the locking member comprising a spacing portion having an axis and an end mounted on the case, the spacing portion projecting axially and generally centrally away from the case on the side of the guide wall opposite the inner surface of the guide wall at generally a right angle to the inner surface of the guide wall for a first predetermined distance about equal to the distance between the inner surface and outer surfaces of the support wall, and being positioned within the through opening of the support wall when the cartridge is attached to the stapler; a locking portion projecting axially beyond the spacing portion, the locking portion including at least one lug extending laterally relative to the axis of the spacing portion, the lug having an engagement surface adjacent the guide wall engaging the outer surface of the support wall of the stapler; and means for releasing engagement of the engagement surface of the locking portion with the outer surface of the support wall to afford removal of the cartridge from the housing.

According to a further aspect of this invention there is provided a staple cartridge for use in a stapler, the staple cartridge comprising a case, a stack of staples within the case, and a follower on one side of the stack of staples and movable within the case with the stack of staples, and a spring for biasing the follower and the stack of staples, the staples being generally U-shaped and each staple comprising a central portion and two generally parallel leg portions projecting generally in the same direction from opposite ends of its central portion and having distal ends; the staple cartridge being characterised in that the case of the staple cartridge comprises a guide wall defining an inner surface and side walls projecting generally normal to the inner surface, the side walls having opposed transverse openings adjacent the inner surface adapted to be positioned in alignment with the passageway of the stapler, the guide wall being adapted to be received in the socket of the stapler with the transverse openings in alignment with the passageway of the stapler such that the driver can be moved through the transverse openings of the cartridge and along the inner surface between the load and eject positions, the follower being on the side of the stack of staples opposite the guide wall such that the spring biases the follower and the staples toward the inner surface of the case; and a locking member for releasably retaining the case of the cartridge in engagement with the housing of the stapler, the locking member comprising a spacing portion having an axis and an end mounted on the

case, the spacing portion projecting axially and generally centrally away from the case on the side of the guide wall opposite the inner surface of the guide wall at generally a right angle to the inner surface of the guide wall for a first predetermined distance about equal to the distance between the inner surface and outer surfaces of the support wall of the stapler, and being adapted to be positioned within the through opening of the support wall when the cartridge is attached to the stapler; a locking portion projecting axially beyond the spacing portion, the locking portion including at least one lug extending laterally relative to the axis of the spacing portion, the lug having an engagement surface adjacent the guide wall adapted for engaging the outer surface of the support wall of the stapler; and means for releasing engagement of the engagement surface of the lug with the outer surface of the support wall to afford removal of the cartridge from the housing.

Preferably the locking portion of the locking member has two opposite lugs projecting beyond the maximum radius of the spacing portion, the opening through the support wall has two opposite second portions adapted to pass the lugs in the release portion of the locking member, and the housing includes cam surfaces around the second portions of the opening and intersecting the outer surface of the support wall to facilitate rotation of the locking member from its release to its locking position when a major portion of the spacing portion of the locking member is in the opening.

Brief Description of the Drawing

The above and additional novel features will be described with reference to the accompanying drawing wherein like numbers refer to like parts in the several views and wherein:

Figure 1 is a top view of a bone stapler including the improved cartridge according to the present invention;

Figure 2 is a side view of the bone stapler of Figure 1;

Figure 3 is an enlarged sectional view taken along line 3-3 of Figure 1;

Figure 4 is an enlarged sectional view taken along line 3-3 of Figure 1 and similar to Figure 3, but in which drive means has been activated to drive a staple;

Figure 5 is an enlarged sectional view taken approximately along lines 5-5 of Figure 4;

Figure 6 is an enlarged fragmentary view of a barrel assembly on the bone stapler of Figure 1 from which the cartridge has been removed;

Figure 7 is a sectional view taken approximately along lines 7-7 of Figure 6;

Figure 8 is an enlarged perspective view of the

cartridge according to the present invention shown in combination with the stapler in Figures 1 through 4;

Figure 9 is a vertical sectional view of the cartridge shown in Figure 8;

Figure 10 is a sectional view taken approximately along line 10-10 of Figure 9; and

Figure 11 is a sectional view taken approximately along line 11-11 of Figure 9.

Detailed Description

Referring now to Figures 1 through 4 there is illustrated a bone stapler to which is attached a cartridge 21 according to the present invention, which stapler is generally designated by the reference numeral 10.

The stapler 10 is adapted for use with generally U-shaped staples 11 (Figure 11). Each of the staples 11 comprises a central portion 12 and two generally parallel leg portions 13 having pointed distal ends and projecting generally in the same direction from opposite ends of its central portion 12, which leg portion 13 preferably diverge by about 1 or 2 degrees so that the driven staple will provide a compressive effect on portions of bone joined by it. Generally the stapler 10 comprises a pistol-shaped housing 14 having a passageway 16 (Figure 3 and 4) extending from an inlet opening 18 to an outlet opening 20, which passageway 16 is adapted to guide one of the staples 11 from the inlet opening 18 to the outlet opening 20 with the distal ends of the staple 11 leading. Means are provided for biasing a stack of the staples 11 contained in the replaceable cartridge 21 into the inlet opening 18. A driver 22 having an end portion 24 adapted to engage the central portion 12 of one of the staples 11 is mounted on the housing 14 for sliding movement between a load position (Figure 3) with the driver 22 spaced from the inlet opening 18 to afford movement of one of the staples 11 into the passageway 16, along the passageway 16 with its end portion 24 pushing the staple, to an eject position (Figure 4) at which the end portion 24 of the driver 22 pushes the staple 11 out of the outlet opening 20 and at which eject position the driver 22 is stopped. Drive means including an air cylinder assembly 26 powered by air under greater than atmospheric pressure and adapted to be manually activated by pulling an actuating trigger 27 into a handle portion 25 of the housing 14 are provided for rapidly and forcefully propelling the driver 22 along the passageway 16 from the load position to the eject position to move the staple 11 from the inlet opening 18 to the outlet opening 20.

The driver 22 comprises a blade-like portion on which its end portion 24 is formed, and a cylindrical portion 17 that moves within a cylindrical

guide bore 19 in the housing 14, to which the cylindrical portion 17 the blade-like portion is attached by a pin 23 through an enlarged cylindrical part 17a of the cylindrical portion 17 that slides in close fitting engagement in the guide bore 19 and has through ports (not shown) to allow air to escape from in front of it.

The drive means for propelling the driver 22 comprises the air cylinder assembly 26 which includes a cylinder 28 partially defined by a cylindrical inner surface 29 of the housing 14 concentric with the guide bore 19, which inner surface 29 has first and second ends 30 and 31, and a piston 32 of the driver 22 opposite its end portion 24. This piston 32 is in slidable sealing engagement with the cylindrical inner surface 29, and is movable along the inner surface 29 between a first position adjacent the first end 30 of the cylinder 28 at which the piston 32 is located when the driver 22 is in its load position and to which the piston 32 is biased by a main spring 33 within the cylinder 28 and the housing 14; and a second position adjacent the second end 31 of the cylinder 28 at which the piston 32 is positioned when the driver 22 is in its eject position.

The end of the main spring 33 opposite the piston 32 is supported against an annular inwardly projecting ledge on a guide collar 35 which guide collar 35 has an outwardly projecting rim fixed against an inwardly projecting lip in the housing 14 by an anchor ring 35b threadably engaged with the housing 14. The inner surface of the inwardly projecting ledge is in close engagement around the driver 22 and carries a pin 35c positioned in a longitudinal groove 35d in the driver 22 to allow longitudinal movement of the driver 22 between its load and eject positions while the pin 35c prevents rotation of the driver 22 relative to the housing 14.

The actuating trigger 27 by which the air cylinder assembly 26 is actuated is included in a valve assembly 34 comprising the housing 14 having a bore opening through the front of its handle portion 25 in which a guide spool 39 is fixed and having an inlet port 36 and first and second outlet ports 37 and 38 communicating with the bore. An actuator 40 coupled to the actuating trigger 27 by a set screw (not shown) is manually movable within the guide spool 39 from an outer blocking position (Figure 3) at which an O-ring 41 around a groove in the actuator 40 engages a seat around and closes the inlet port 36, and clearance between a small diameter portion 42 of the actuator 40 and the inner surface of the guide spool 39 connects the outlet ports 37 and 38 through transverse passageways in the guide spool 39; and an inner activate position (Figure 4) with the O-ring 41 separated from the seat to connect the inlet port 36 and the

first outlet port 37 past the small diameter portion 42 of the actuator 40, and at which a larger diameter 43 portion of the actuator 40 essentially closes the transverse passageways in the guide spool 39 leading to the second outlet port 38. A spring 44 provides means for biasing the actuator 40 to its outer blocking position, against which spring 44 the actuator 40 may be manually moved or pulled to its activate position by the actuating trigger 27. The housing 14 has an outlet passageway 46 which communicates with the cylinder 28 adjacent its second end 31, communicates with the second outlet port 38, and is adapted to be coupled to a portion of a hose (not shown) leading to air at atmospheric pressure through a conventional surgical air inlet connector, a female half 45 of which is formed in the housing 14. The housing 14 also has an inlet passageway 47 including an enlarged reservoir portion 48 (which provides sufficient air volume to quickly move the piston 32) coupled to the inlet port 36 and a smaller portion 49 adapted to be coupled to a source of air under greater than atmospheric pressure through the female coupling half 45. Also included is a transfer passageway 51 coupled between the first outlet port 37 and communicating with the cylinder 28 adjacent its first end 30. Thus, when the stapler 10 is activated by the actuating trigger 27 being pulled into the housing 14 to move the actuator 40 to its activate position (Figure 4), air under greater than atmospheric pressure in the reservoir 48 and from the supply will flow through the inlet port 36, past the small diameter actuator portion 42 and out the transfer passageway 51 to the first end 30 of the cylinder 28, while the larger diameter portion 43 of the actuator 40 precludes any significant amount of the high pressure air from escaping into the outlet passageway 46. As the piston 32 starts to move from its first to its second position under the influence of the high pressure air, air between the piston 32 and the second end 31 of the cylinder 28 will flow out the outlet passageway 46 and to the atmosphere through a hose (not shown) coupled at the female coupling half 45. When the actuating trigger 27 is subsequently released (Figure 3), the actuator 40 will return to its deactivated position under the influence of the spring 44 so that the inlet port 36 is closed, and the first and second outlet ports 37 and 38 are connected past the small diameter portion 42 of the actuator 40 so that the high pressure air can escape from behind the piston 32 via the transfer passageway 51, bore 35 and outlet passageway 46, and air at atmospheric pressure as needed can flow to the front of the piston 32 via the outlet passageway 46.

The cartridge 21, best seen in Figures 8 through 11, includes a case 54 comprising a guide wall 55 defining an inner surface 56 at one end of

the stack of staples 11, side walls 57 projecting normal to the inner surface 56, and an end wall 53 opposite the guide wall 55. The side walls 57 have opposed transverse openings 58 adjacent the inner surface 56 and an end portion of the cartridge 21 including the guide wall 55 is received in a socket 59 (see figure 7) defined by an inner surface of a support wall 61 included in the housing 14 with the transverse openings 58 aligned with the passageway 16 and the inner surface 56 defining a portion of the passageway 16 at its inlet opening 18 so that the driver 22 is movable through the transverse openings 58 and along the inner surface 56 between its load and eject positions. The cartridge 21 further includes a follower 60 on the side of the stack of staples 11 opposite the inner surface 56 and passageway 16, which follower 60 is movable within the case 54 with the stack of staples 11, and the coil spring 15 between the end wall 53 of the case 54 and the follower 60 for biasing the follower 60 and the stack of staples 11 toward the inner surface 56. Thus as the driver 22 moves through the transverse openings 58 and along the inner surface 56 during movement from its load to its eject position, the driver 22 will carry with it the staple 11 pressed against the inner surface 56 by the follower 60 and spring 15. When removed, the cartridge 21 will carry with it all of the staples 11 remaining in the stapler 10 so that, with the cartridge 21 removed, it will be impossible to inadvertently fire a staple 11 from the stapler 10.

Means for releasably retaining the cartridge 21 in the socket 59 in the housing 14 is provided by the support wall 61 (best seen in Figures 6 and 7) having a through opening 62 between its inner surface defining the socket 59 and an outer surface 63 generally parallel to its inner surface at the bottom of the socket 59, which through opening 62 has a circular central first opening portion 64 and two generally U-shaped opposed second opening portions 65 on opposite sides of the central opening portion 64; and the cartridge 21 (best seen in Figures 8-11) having a locking member 66 mounted on the guide wall 55 for rotation about an axis generally normal to the inner surface 56, projecting from the side of the guide wall 55 opposite the inner surface 56, having a spacing portion 68 of a first maximum radius extending from the guide wall 55 for a first predetermined distance about equal to the distance between the inner and outer surfaces of the support wall 61 with the first maximum radius affording rotation of the spacing portion 68 within the central first opening portion 64, and having a locking portion with at least one, and as illustrated, two lugs 70 projecting beyond the maximum radius at the distal end of the spacing portion 68. The lugs 70 are adapted to pass through the second portions 65 of the opening 62 in a release

position of the locking member 66 relative to the case 54, and have a surface adjacent the support wall 61 in engagement with the outer surface 63 of the support wall 61 at positions of the locking member 66 spaced from its release position to hold the cartridge 21 in the socket 59 on the housing 14.

As is best seen in Figures 6 and 7, preferably the housing 14 includes a cam surface 72 around each of the second portions 65 of the opening 62. The cam surfaces 72 intersect the outer surface 63 of the support wall 61 and facilitate rotation of the locking member 66 from its release position to a position with the lugs 70 along the outer surface 63 of the support wall 61 when the spacing portion 68 of the locking member 66 is in the opening 62. Upon such rotation, engagement between the lugs 70 and the cam surfaces 72 will pull the cartridge 21 firmly into the socket 59, eliminating the necessity for the user to press the cartridge 21 fully to that position prior to rotating the locking member 66.

As is best illustrated in Figures 8-11, the cartridge 21 includes a stack of staples 11, the coil spring 15 and four polymeric moldings that provide the follower 60, the guide wall 55 and a cup-shaped member that includes the side walls 57 and the end wall 53 and is fused to the guide wall 55 to form the case 54, and the locking member 66. The locking member 66 has an annular rim 73 on its end opposite the lugs 70, which rim 73 is rotatably received in a recess from the inner surface 56 of the guide wall 55. The guide wall 55 has an orifice shaped to pass the lugs 70 and spacing portion 68 of the locking member 66 by slightly deflecting a central portion of the guide wall 55 defining a central portion of the orifice, which central portion of the guide wall 55 will move into a shallow groove 74 around the locking member 66 adjacent the annular rim 73 where the guide wall 55 is retained while the locking member 66 is freely rotatable relative to the guide wall 55.

The side of the follower 60 opposite the staples 11 has a circular recess that receives a large end of the spring 15, whereas the smaller end of the spring 15 is located around a post 75 projecting from the end wall 53. The spring 15 is tapered between the follower 60 and the end wall 53 to reduce the range of pressures that it will apply to the staples 11 as the height of the stack of staples 11 decreases, and to minimize its compressed height and thereby the height of the cartridge 21.

Means for guiding the follower 60 are provided by grooves 76 in the side walls 57 disposed at right angles to the guide wall 55, shoes 77 formed on the edges of the follower 60 adapted to slide within the grooves 76, and two parallel pins 78 projecting from the end wall 53 received in open-

ings in the follower 60. The shoes 77 on the sides of the follower 60 have upwardly projecting parts that prevent the follower 60 from being pushed into the path of the driver 22 after the last staple 11 is ejected from the cartridge 21.

The bone stapler 10 includes blocking means for automatically preventing movement of the driver 22 to its load position from an intermediate position between its load and eject positions with a portion of the driver 22 projecting partially through the cartridge 21 and across the inlet opening 18 to the passageway 16 after the driver 22 has moved from its load to its eject position. Thus, with the driver 22 initially in its load position, the drive means may be manually activated a first time by pulling the actuating trigger 27 to drive a staple 11 through the outlet opening 20 and may subsequently be manually activated an additional number of times by pulling the actuating trigger 27 so that the driver 22 will be again propelled to its eject position to further impact that driven staple 11 as may be needed to fully seat the driven staple 11, without driving an additional staple 11 from the cartridge 21. Also included are reset means manually activated by a reset member or trigger 79 for resetting the blocking means to allow return movement of the driver 22 from its intermediate to its load position so that another staple 11 may be driven.

The blocking means in the bone stapler 10 comprises a plunger 80 axially slidably mounted in a bore in the housing 14 communicating with the cylinder 28 at its first end 30 for movement in a direction normal to the axis of the cylinder 28 between a nonblocking position (Figure 3) spaced from within the cylinder 28, to a blocking position (Figure 4) partially within the cylinder 28 to which the plunger 80 is biased by a spring 81, so that engagement between the plunger 80 and the side of the piston 32 adjacent the first end 30 of the cylinder 28 will define the intermediate position for the piston 32. When the piston 32 is in its first position corresponding to the load position of the driver 22, the periphery of the piston 32 will retain the plunger 80 in its nonblocking position in opposition to the biasing of the spring 81 (Figure 3). Upon movement of the piston 32 from its first position toward its second position corresponding to the eject position of the driver 22, however, the plunger 80 will automatically move to its blocking position under the influence of the spring 81 (Figure 4) to thus preclude the piston 32 from returning to its first position and thus preclude the driver 22 from returning to its load position until the reset means is operated by the reset trigger 79.

The reset means comprises the reset trigger 79 fastened by a set screw (not shown) to an outer end portion of a spindle 83, which spindle 83 is slidably mounted in a sleeve 82 fixed in a bore

opening through the front of the handle portion 25 of the housing 14 for longitudinal sliding movement between an outer position (Figures 3 and 4) and an inner position (not shown). Also included in the reset means are means in the form of a spring 85 for biasing the reset trigger 79 to its outer position, and cam means on the spindle 83 and reset trigger 79 for moving the plunger 80 from its blocking to its nonblocking position against the bias of spring 81 upon manual movement of the spindle 83 from its outer to its inner position via the reset trigger 79. The cam means comprise a semispherical tip 88 on the inner end of the spindle 83, and a surface 89 inclined with respect to the axis of the spindle 83 partially defining a slot in the plunger 80 in which the tip 88 is received to prevent rotation of the plunger 80. The slot in the plunger 80 is sufficiently long to afford movement of the plunger 80 from its nonblocking to its blocking position under the influence of the spring 81 after the driver moves toward its eject position. With the plunger 80 in its blocking position the reset trigger 79 may be manually pulled toward the handle portion 25 of the housing 14 which will cause the tip 88 to engage the inclined surface 89 so that the plunger 80 will be pulled back to its nonblocking position. This will allow the piston 32 to return to its first position, and cause the driver 22 to return to its load position under the influence of the main spring 33.

The bone stapler 10 is designed to afford driving staples of different sizes in that it is made in two separable assemblies including a handle assembly 91 which includes the drive means mounted on one part of the housing 14, and a barrel assembly 92 which defines the passageway 16 and receives the cartridge 21 for staples 11 of one size on another part of the housing 14. Means are provided for releasably engaging the parts of the housing 14, and the driver 22 is separable into a second part 93 included in the handle assembly 91 and connected to the piston 32, and a first part 94 including its end portion 24 which is included in the barrel assembly 92. Different barrel assemblies that each have a housing part defining a passageway, a driver part and accept cartridges of a different size of staple may be substituted for the barrel assembly 92 to afford driving staples of different sizes.

Means are provided for releasably engaging the first and second parts 94 and 93 of the driver 22 and for releasably engaging the handle and barrel assemblies 91 and 92. These means comprise walls on the first part 94 of the driver 22 opposite its end portion 24 defining a socket with an outer portion 96 having a square cross section and an inner portion 97 with a circular cross section; and a tip on the first part 94 of the driver 22 including a distal square portion 99 adapted to

slide within the socket through its outer portion 96 and to rotate in its inner portion 97 out of alignment with the outer portion 96 (see Figure 5) with the walls defining the outer portion 96 around a reduced diameter cylindrical portion 100 of the driver's first part 94. The part of the housing 14 included in the barrel assembly 92 includes a collar 101 at its end opposite the outlet opening 20 received in a socket in the part of the housing 14 included in the handle assembly 91 with the square portion 99 of the tip out of alignment with the outer portion 96 of the wall defining the socket, with four evenly spaced radially outwardly projecting pins 102 fixed on the collar 101 received in four longitudinally extending slots opening through the end of the housing part included in the handle assembly 91, and with hooks 105 on a ring 103 mounted for rotation about its axis on the housing part included in the handle assembly 91 in engagement with the pins 102 to releasably latch the handle and barrel assemblies 91 and 92 together. The barrel assembly 92 can thus be located at different orientations displaced 90 degrees from each other with respect to the handle assembly 91 to provide various orientations of a driven staple 11 relative to the handle portion 25 of the housing 14. To release the handle and barrel assemblies 91 and 92 from each other, the ring 103 is rotated against the bias of a coil spring 104 to move the hooks 105 from around the pins 102. The handle and barrel assemblies 91 and 92 are pulled apart axially of the driver 22 which pulls the pins 102 from the slots in which they are received and pulls the part of the housing 14 on the barrel assembly 92 along the driver 22 until an inwardly projecting lip (not shown) on that part of the housing 14 engages the end of the enlarged part 17 of the driver 22 adjacent the piston 32, at which position a pin 107a carried by the driver portion 17 is moved by a spring 107b so that a ball 107c will be moved into housing a groove in the housing 14, which engagement will keep the end plug 23 from moving into the guide bore 19 after the handle and barrel assemblies 91 and 92 are separated. The handle and barrel assemblies 91 and 92 are then rotated about 45 degrees relative to each other about the axis of the driver 22 to align the square position 99 of the tip with the outer portion 96 of the socket, whereupon the tip may be pulled from the socket and the assemblies 91 and 92 may be separated. Reengagement of the handle and barrel assemblies 91 and 92 is accomplished by reversing the steps listed above which will cause a cam surface on the end of the first part 92 of the driver 22 around the end of the socket to move the pin 107a against the spring 107b to release the driver 22. Upon pressing the pins 102 into the slots, camming surfaces 105b on the hooks 105 will cause the collar 101 to

automatically rotate to engage the hooks 105 around the pins 102.

The bone stapler 10 also includes means for indicating to a user ready to fire the stapler 10 whether the driver 22 is in its load position from which a staple 11 can be driven or in its intermediate position. An indicating spool 106 is centrally slidably mounted in a removable plug 108 providing a portion of the housing 14 at the first end 30 of the cylinder 28. The indicating spool 106 is slidable between an inner position with a flange 109 at its outer end against the outer surface of the plug 108 to which the indicating spool 106 is biased by a spring 110, and an outer position with a portion of the spool 106 adjacent the flange 109, which is painted red, projecting from the plug 108. The piston 32 carries a central headed pin 112 at its end adjacent the first end 30 of the cylinder 28 around which pin 112 is a slidable washer 114 biased against the head of the pin 112 by a spring 113 with a greater spring constant than the spring 110. When the driver 22 is in its load position, the head of the pin 112 will enter an opening in the spool 106 while the washer 114 will be pressed against the adjacent end of the indicating spool 106 under the influence of the spring 113 causing the spool 106 to move to its outer position at which its red periphery indicates that the driver 22 is in its load position. When the driver 22 moves away from its load position, the indicating spool 106 will move to its inner position under the influence of the spring 110, thereby indicating to a user that the driver 22 is in its intermediate position.

Operation

The operation of the bone stapler 10 by a user will now be described assuming that a cartridge 21 containing a stock of staples 11 is held in the housing 14 by the locking member 66 and the stapler 10 is connected at the coupling half 45 to a hose assembly (not shown) including a central supply of air under greater than atmospheric pressure coupled to the inlet passageway 47 and on outer hose leading to air at atmospheric pressure coupled to the outlet passageway 46. The user can utilize a pair of pointed locating members 130 fixed to the housing 14 in positions flanking the outlet opening 20 and projecting generally parallel to the axis of the driver 22 to help position and stabilize bone portions to be stapled in the same plane. When the bone portions are thus positioned, the stapler 10 can be activated by manually pulling the actuating trigger 27 so that air under greater than atmospheric pressure is coupled through the reservoir 48, valve assembly 34 and transfer passageway 51 to the first end 30 of the cylinder 28 which will cause rapid movement of the piston 32 and

thereby the driver 22 from its load position (Figure 3) spaced from the staple inlet opening 18, and through the cartridge 21 along its inner surface 56 to push the adjacent staple 11 in the stack along the passageway 16 to the outlet opening 20 and drive that staple 11 into adjacent portions of bone (Figure 4), the driver 22 being stopped at its eject position at the outlet opening 20 by engagement of the piston 32 with a rubber collar 131 at the second end 31 of the cylinder 28. As the piston 32 thus is moved away from the first end 30 of the cylinder 28, the plunger 80 will move into the cylinder 28 under the influence of the spring 81 so that, after the actuating trigger 27 is released and the high pressure air at the first end 30 of the cylinder 28 escapes through the transfer passageway 51, valve assembly 34 and outlet passageway 46 to the hose coupled to atmospheric pressure and the piston 32 moves back toward its first position under the influence of the main spring 33, the piston will be stopped against the periphery of the plunger 80 with the end portion 24 of the driver 22 at an intermediate position extending through the cartridge 21 so that the next staple 11 in the stack of staples 11 can not move into the inlet opening 18 to the passageway 16. The user, if desired, can then again rapidly move the driver 22 to its eject position by again pulling the actuating trigger 27 as may be desired to further drive or seat the staple 11 previously driven into the bone portions.

When the user desires to drive a second staple 11, he can pull the reset trigger 79 which will move the tip 88 of the spindle 83 against the inclined surface 89 to cam the plunger 80 out of the cylinder 28 to its nonblocking position so that the main spring 33 can return the piston 32 to its first position and thereby the driver 22 to its load position allowing the uppermost staple 11 in the cartridge 21 to move against the inner surface 56 of the cartridge 21 at the inlet opening 18 so that subsequent activating of the drive means by the actuating trigger 27 will drive that staple 11.

If the user wishes to remove the cartridge 21 because it is empty, or to insure that the stapler 10 can not fire another staple 11, or to insert staples with different length leg portions 13, he may do so by manually rotating the locking member 66 to its release position with its lugs 70 aligned with the outer portions 65 of the opening 62 by pushing on one or both of the lugs 70, and then pulling the cartridge 21 from the socket 59 in the housing 14. He can then be sure that no staples 11 remain in the stapler 10, since the entire remaining stack of staples 11 (if any) remains in the cartridge 21. The same or a new cartridge 21 of staples 11 may again be loaded into the stapler 10 by inserting the cartridge 21 into the socket 59 in the housing 14 and then rotating the locking member 66 from its

release position, which will cause the lugs 70 to move along the cam surfaces 72 and onto the outer surface 63 of the support wall 61 to pull the cartridge 21 fully into the socket 59 and hold it in place.

If the user wishes to drive staples of a different width along its central portion 12, he may also do that by substituting an appropriate different barrel assembly for the barrel assembly 92 being used, which different barrel assembly is adapted to accommodate staples 11 of that width. Such substitution is easily accomplished by rotating the locking collar 103 to release the two parts of the housing 14, pulling and relatively rotating the housing parts with respect to the longitudinal axis of the driver 22 (as is described in greater detail above) which will cause the square portion 99 on the first part 94 of the driver 22 to align with the square cross section portion 96 of walls defining the socket in the second part 93 of the driver 22 in which the square portion 99 is received, and pulling the first and second parts of the housing 14 and driver 22 away from each other to pull the square portion 99 from the socket and separate them. The different barrel assembly can then be assembled on the handle assembly 91 by reversing the separating steps.

The present invention has now been described with reference to one embodiment thereof. It will be appreciated that many modifications and changes can be made in the structure of the cartridge 21 and the means by which it is attached to the bone stapler 10; for example, the locking member could have more or less locking lugs than were described.

Claims

1. A combination of a stapler (10) and a staple cartridge (21) with generally U-shaped staples (11) each comprising a central portion (12) and two generally parallel leg portions (13) projecting generally in the same direction from opposite ends of its central portion (12) and having distal ends;

the stapler (10) comprising:

a housing (14) having a passageway (16) extending from an inlet opening (18) to an outlet opening (20), the passageway (16) being adapted to guide a single staple (11) moved from the inlet opening (18) to the outlet opening (20) with the distal ends of its legs (13) leading;

a driver (22) having an end portion (24) adapted to engage the central portion (12) of one of the staples (11) and being mounted on the housing (14) for sliding movement between a load position (figure 3) with the driver (22) spaced from the inlet opening (18) to afford

movement of one of the staples (11) into the passageway (16), along the passageway (16) with the end portion (24) pushing the staple (11), to an eject position (figure 4) at which the end portion (24) of the driver (22) pushes the staple (11) out the outlet opening (20); and

drive means (26) adapted to be manually activated for propelling the driver (22) along the passageway (16) from the load to the eject position to move the staple (11) from the inlet opening (18) to the outlet opening (20); and

the staple cartridge (21) comprising:

a case (54), a stack of said staples (11) within the case (54), and a follower (60) on one side of the stack of staples (11) and movable within the case (54) with the stack of staples (11), and a spring (15) for biasing the follower (60) and the stack of staples (11),

the combination being characterized in that the housing (14) of the stapler (10) includes a support wall (61) having an inner surface defining a socket (59) at the inlet opening, the support wall (61) also having an outer surface (63), and a through opening (62) between the inner surface and the outer surface (63); and the case (54) of the staple cartridge (21) comprises a guide wall (55) defining an inner surface (56) and side walls (57) projecting generally normal to the inner surface (56), the side walls (57) having opposed transverse openings (58) at the inner surface (56) and aligned with the passageway (16) of the stapler (10), the guide wall (55) being received in the socket (59), with the inner surface (56) of the guide wall (55) defining a portion of the passageway (16) at the inlet opening (18) so that the driver (22) can be moved through the openings and along the inner surface between the load and eject positions, the follower (60) being on the side of the stack of staples (11) opposite the passageway (16) such that the spring (15) biases the follower (60) and the staples (11) toward the inner surface (56) of the case (54); and a locking member (66) for releasably retaining the case (54) of the cartridge (21) in engagement with the housing (14) of the stapler (10), the locking member (66) comprising a spacing portion (68) having an axis and an end (73) mounted on the case (54), the spacing portion (68) projecting axially and generally centrally away from the case (54) on the side of the guide wall (55) opposite the inner surface (56) of the guide wall (55) at generally a right angle to the inner surface (56) of the guide wall (55) for a first predetermined distance about equal to the distance between the inner surface and outer surfaces (63) of the support wall (61), and being positioned within



release position, which will cause the lugs 70 to move along the cam surfaces 72 and onto the outer surface 63 of the support wall 61 to pull the cartridge 21 fully into the socket 59 and hold it in place.

If the user wishes to drive staples of a different width along its central portion 12, he may also do that by substituting an appropriate different barrel assembly for the barrel assembly 92 being used, which different barrel assembly is adapted to accommodate staples 11 of that width. Such substitution is easily accomplished by rotating the locking collar 103 to release the two parts of the housing 14, pulling and relatively rotating the housing parts with respect to the longitudinal axis of the driver 22 (as is described in greater detail above) which will cause the square portion 99 on the first part 94 of the driver 22 to align with the square cross section portion 96 of walls defining the socket in the second part 93 of the driver 22 in which the square portion 99 is received, and pulling the first and second parts of the housing 14 and driver 22 away from each other to pull the square portion 99 from the socket and separate them. The different barrel assembly can then be assembled on the handle assembly 91 by reversing the separating steps.

The present invention has now been described with reference to one embodiment thereof. It will be appreciated that many modifications and changes can be made in the structure of the cartridge 21 and the means by which it is attached to the bone stapler 10; for example, the locking member could have more or less locking lugs than were described.

Claims

1. A combination of a stapler (10) and a staple cartridge (21) with generally U-shaped staples (11) each comprising a central portion (12) and two generally parallel leg portions (13) projecting generally in the same direction from opposite ends of its central portion (12) and having distal ends;

the stapler (10) comprising:

a housing (14) having a passageway (16) extending from an inlet opening (18) to an outlet opening (20), the passageway (16) being adapted to guide a single staple (11) moved from the inlet opening (18) to the outlet opening (20) with the distal ends of its legs (13) leading;

a driver (22) having an end portion (24) adapted to engage the central portion (12) of one of the staples (11) and being mounted on the housing (14) for sliding movement between a load position (figure 3) with the driver (22) spaced from the inlet opening (18) to afford

movement of one of the staples (11) into the passageway (16), along the passageway (16) with the end portion (24) pushing the staple (11), to an eject position (figure 4) at which the end portion (24) of the driver (22) pushes the staple (11) out the outlet opening (20); and

drive means (26) adapted to be manually activated for propelling the driver (22) along the passageway (16) from the load to the eject position to move the staple (11) from the inlet opening (18) to the outlet opening (20); and

the staple cartridge (21) comprising:

a case (54), a stack of said staples (11) within the case (54), and a follower (60) on one side of the stack of staples (11) and movable within the case (54) with the stack of staples (11), and a spring (15) for biasing the follower (60) and the stack of staples (11),

the combination being characterized in that the housing (14) of the stapler (10) includes a support wall (61) having an inner surface defining a socket (59) at the inlet opening, the support wall (61) also having an outer surface (63), and a through opening (62) between the inner surface and the outer surface (63); and the case (54) of the staple cartridge (21) comprises a guide wall (55) defining an inner surface (56) and side walls (57) projecting generally normal to the inner surface (56), the side walls (57) having opposed transverse openings (58) at the inner surface (56) and aligned with the passageway (16) of the stapler (10), the guide wall (55) being received in the socket (59) with the inner surface (56) of the guide wall (55) defining a portion of the passageway (16) at the inlet opening (18) so that the driver (22) can be moved through the openings and along the inner surface between the load and eject positions, the follower (60) being on the side of the stack of staples (11) opposite the passageway (16) such that the spring (15) biases the follower (60) and the staples (11) toward the inner surface (56) of the case (54); and a locking member (66) for releasably retaining the case (54) of the cartridge (21) in engagement with the housing (14) of the stapler (10), the locking member (66) comprising a spacing portion (68) having an axis and an end (73) mounted on the case (54), the spacing portion (68) projecting axially and generally centrally away from the case (54) on the side of the guide wall (55) opposite the inner surface (56) of the guide wall (55) at generally a right angle to the inner surface (56) of the guide wall (55) for a first predetermined distance about equal to the distance between the inner surface and outer surfaces (63) of the support wall (61), and being positioned within



the through opening (62) of the support wall (61) when the cartridge (21) is attached to the stapler (10); a locking portion (70) projecting axially beyond the spacing portion (68), the locking portion (70) including at least one lug (70) extending laterally relative to the axis of the spacing portion (68), the lug (70) having an engagement surface adjacent the guide wall (55) engaging the outer surface (63) of the support wall (61) of the stapler (10); and means for releasing engagement of the engagement surface of the locking portion (70) with the outer surface (63) of the support wall (61) to afford removal of the cartridge (21) from the housing (14).

2. A stapler-staple cartridge combination according to claim 1 wherein the staple cartridge (21) includes an annular rim (73) at the end of the spacing portion (68) opposite the locking portion (70) for mounting the locking member (66) for rotational movement relative to the case (54) to provide a portion of the means for releasing engagement of the engagement surface on said lug (70) with the outer surface of the support wall (61), and the locking portion (70) comprises two lugs (70) extending laterally outwardly from opposite sides of the locking portion (70), the lugs (70) being adapted to be manipulated to provide another portion of the means for releasing engagement of the engagement surface of the lugs (70).

3. A staple cartridge (21) for use in a stapler (10) as defined in claim 1, the staple cartridge (21) comprising a case (54), a stack of staples (11) within the case (54), and a follower (60) on one side of the stack of staples (11) and movable within the case (54) with the stack of staples (11), and a spring (15) for biasing the follower (60) and the stack of staples (11), the staples (11) being generally U-shaped and each staple (11) comprising a central portion (12) and two generally parallel leg portions (13) projecting generally in the same direction from opposite ends of its central portion (12) and having distal ends; the staple cartridge (21) being characterized in that the case (54) of the staple cartridge (21) comprises a guide wall (55) defining an inner surface (56) and side walls (57) projecting generally normal to the inner surface (56), the side walls (57) having opposed transverse openings (58) adjacent the inner surface (56) adapted to be positioned in alignment with the passageway (16) of the stapler (10), the guide wall (55) being adapted to be received in the socket (59) of the stapler (10) with the transverse openings (58) in alignment with the

passageway (16) of the stapler (10) such that the driver (22) can be moved through the transverse openings (58) of the cartridge (21) and along the inner surface (56) between the load and eject positions, the follower (60) being on the side of the stack of staples (11) opposite the guidewall (55) such that the spring (15) biases the follower (60) and the staples (11) toward the inner surface (56) of the case (54); and a locking member (66) for releasably retaining the case (54) of the cartridge (21) in engagement with the housing (14) of the stapler (10), the locking member (66) comprising a spacing portion (68) having an axis and an end (73) mounted on the case (54), the spacing portion (68) projecting axially and generally centrally away from the case (54) on the side of the guide wall (55) opposite the inner surface (56) of the guide wall (55) at generally a right angle to the inner surface (56) of the guide wall (55) for a first predetermined distance about equal to the distance between the inner surface and outer surfaces (63) of the support wall (61) of the stapler (10), and being adapted to be positioned within the through opening (62) of the support wall (61) when the cartridge (21) is attached to the stapler (10); a locking portion (70) projecting axially beyond the spacing portion (68), the locking portion (70) including at least one lug (70) extending laterally relative to the axis of the spacing portion (68), the lug (70) having an engagement surface adjacent the guide wall (55) adapted for engaging the outer surface (63) of the support wall (61) of the stapler (10); and means for releasing engagement of the engagement surface of the lug (70) with the outer surface (63) of the support wall (61) to afford removal of the cartridge (21) from the housing (14).

4. A staple cartridge (21) according to claim 3 which includes an annular rim (73) at the end of the spacing portion (68) opposite the locking portion (70) for mounting the locking member (66) for rotational movement relative to the case (54) to provide a portion of the means for releasing engagement of the engagement surface on said lug (70) with the outer surface of the support wall (61), and the locking portion (70) comprises two lugs (70) extending laterally outwardly from opposite sides of the locking portion (70), the lugs (70) being adapted to be manipulated to provide another portion of the means for releasing engagement of the engagement surface of the lugs (70).

Patentansprüche



1. Kombination einer Klammermaschine (10) und eines Klammermagazins (21) mit im allgemeinen U-förmigen Klammern (11), die jeweils aus einem Mittelabschnitt (12) und zwei im allgemeinen parallelen Schenkelabschnitten (13) bestehen, die sich von gegenüberliegenden Enden des Mittelabschnittes (12) im allgemeinen in die gleiche Richtung erstrecken und distale Enden besitzen;

wobei die Klammermaschine (10) umfaßt:

eine Gehäuse (14) mit einem Kanal (16), der sich von einer Einlaßöffnung (18) zu einer Auslaßöffnung (20) erstreckt, wobei der Kanal (16) eine einzelne Klammer (11) führen kann, die mit den distalen Enden ihrer Schenkel (13) voraus von der Einlaßöffnung (18) zu der Auslaßöffnung (20) bewegt wird;

einen Treiber (22) mit einem Endabschnitt (24), der an dem Mittelabschnitt (12) einer der Klammern (11) angreifen kann und auf dem Gehäuse (14) verschiebbar angeordnet ist, so daß er von einer Ladestellung (Fig. 3), in der der Treiber (22) im Abstand von der Einlaßöffnung (18) angeordnet ist, damit eine der Klammern (11) in den Kanal (16) bewegt werden kann, durch den Kanal (16), wobei der Endabschnitt (24) die Klammer (11) schiebt, zu einer Auswurfstellung (Fig. 4) bewegt werden kann, in der der Endabschnitt (24) des Treibers (22) die Klammer (11) aus der Auslaßöffnung (20) herausdrückt; und

eine Antriebseinrichtung (26), die von Hand betätigt werden kann, um den Treiber (22) durch den Kanal (16) von der Ladestellung in die Auswurfstellung zu schieben, so daß die Klammer (11) von der Einlaßöffnung (18) zu der Auslaßöffnung (20) bewegt wird; und

wobei das Klammermagazin (21) umfaßt:

ein Gehäuse (54), einen Stapel der Klammern (11) in dem Gehäuse (54), und einen Schieber (60) auf einer Seite des Stapels von Klammern (11), der in dem Gehäuse (54) mit dem Stapel von Klammern (11) bewegbar ist, und eine Feder (15), die den Schieber (60) und den Stapel von Klammern (11) vorspannt,

wobei die Kombination dadurch gekennzeichnet ist, daß das Gehäuse (14) der Klammermaschine (10) eine Stützwand (61) umfaßt mit einer Innenfläche, die eine Aufnahme (59) an der Einlaßöffnung aufweist, wobei die Stützwand (61) auch eine Außenfläche (63) aufweist, und eine durchgehende Öffnung (62) zwischen der Innenfläche und der Außenfläche (63); und daß das Gehäuse (54) des Klammermagazins (21) eine Führungswand (55) umfaßt, die eine Innenfläche (56) aufweist, und Seitenwände (57), die sich im allgemeinen senkrecht zu der

Innenfläche (56) erstrecken, wobei die Seitenwände (57) einander gegenüberliegende Querlöcher (58) an der Innenfläche (56) aufweisen, die mit dem Kanal (16) der Klammermaschine (10) fluchten, wobei die Führungswand (55) in die Aufnahme (59) eingesetzt ist und die Innenfläche (56) der Führungswand (55) einen Abschnitt des Kanals (16) an der Einlaßöffnung (18) bildet, so daß der Treiber (22) durch die Öffnungen und entlang der Innenfläche zwischen der Lade- und der Auswurfstellung bewegt werden kann, wobei sich der Schieber (60) auf der Seite des Stapels von Klammern (11) gegenüber dem Kanal (16) befindet, so daß die Feder (15) den Schieber (60) und die Klammern (11) in Richtung zur Innenfläche (56) des Gehäuses (54) vorspannt; und ein Verriegelungselement (66), welches das Gehäuse (54) des Magazins (21) lösbar verbunden hält mit dem Gehäuse (14) der Klammermaschine (10), wobei das Verriegelungselement (66) einen Abstandshalter (68) umfaßt, der mit einer Achse und einem Ende (73) auf dem Gehäuse (54) angeordnet ist, wobei sich der Abstandshalter (68) axial und im allgemeinen mittig von dem Gehäuse (54) weg erstreckt auf der Seite der Führungswand (55) gegenüber der Innenfläche (56) der Führungswand (55) in einem im allgemeinen rechten Winkel zu der Innenfläche (56) der Führungswand (55) über einen ersten vorbestimmten Abstand, der in etwa dem Abstand zwischen der Innenfläche und den Außenflächen (63) der Stützwand (61) entspricht, und wobei der Abstandshalter in der durchgehenden Öffnung (62) in der Stützwand (61) angeordnet ist, wenn das Magazin (21) an der Klammermaschine (10) befestigt ist; einen Verriegelungsabschnitt (70), der sich axial über den Abstandshalter (68) hinaus erstreckt, wobei der Verriegelungsabschnitt (70) mindestens einen Vorsprung (70) umfaßt, der sich seitlich in bezug auf die Achse des Abstandshalters (68) erstreckt, wobei der Vorsprung (70) eine Eingriffsfläche im Bereich der Führungswand (55) aufweist, die mit der Außenfläche (63) der Stützwand (61) der Klammermaschine in Eingriff kommt; und eine Einrichtung zum Lösen der Verbindung der Eingriffsfläche des Verriegelungsabschnittes (70) mit der Außenfläche (63) der Stützwand (61), so daß das Magazin (21) aus dem Gehäuse (14) entfernt werden kann.

2. Kombination von Klammermaschine und Klammermagazin nach Anspruch 1, dadurch gekennzeichnet, daß das Klammermagazin (21) einen ringförmigen Rand (73) am Ende des



Abstandshalters (68) gegenüber dem Verriegelungsabschnitt (70) aufweist, damit das Verriegelungselement (66) drehbar in bezug auf das Gehäuse (54) angeordnet werden kann, um einen Abschnitt der Einrichtung zum Lösen der Verbindung der Eingriffsfläche auf dem Vorsprung (70) mit der Außenfläche der Stützwand (61) zu bilden, und daß der Verriegelungsabschnitt (70) zwei Vorsprünge (70) umfaßt, die sich von gegenüberliegenden Seiten des Verriegelungsabschnittes (70) seitlich nach außen erstrecken, wobei die Vorsprünge (70) so bewegt werden können, daß ein weiterer Abschnitt der Einrichtung zum Lösen der Verbindung mit der Eingriffsfläche der Vorsprünge (70) entsteht.

3. Klammermagazin (21) zur Verwendung in einer Klammermaschine (10) nach Anspruch 1, wobei das Klammermagazin (21) ein Gehäuse (54), einen Stapel von Klammern (11) in dem Gehäuse (54), und einen Schieber (60) auf einer Seite des Stapels von Klammern (11), der in dem Gehäuse (54) mit dem Stapel von Klammern (11) bewegbar ist, sowie eine Feder (15) zum Vorspannen des Schiebers (60) und des Stapels von Klammern (11) umfaßt, wobei die Klammern (11) im allgemeinen U-förmig sind und jede Klammer (11) einen Mittelabschnitt (12) und zwei im allgemeinen parallele Schenkelabschnitte (13) umfaßt, die sich von gegenüberliegenden Enden des Mittelabschnittes (12) im allgemeinen in die gleiche Richtung erstrecken und distale Enden besitzen; wobei das Klammermagazin (21) dadurch gekennzeichnet ist, daß das Gehäuse (54) des Klammermagazins (21) eine Führungswand (55) aufweist, die eine Innenfläche (56) besitzt, und Seitenwände (57), die sich im allgemeinen senkrecht zu der Innenfläche (56) erstrecken, wobei die Seitenwände (57) einander gegenüberliegende Querlöcher (58) im Bereich der Innenfläche (56) aufweisen, die fluchtend mit dem Kanal (16) der Klammermaschine (10) angeordnet sein können, wobei die Führungswand (55) in die Aufnahme (59) in der Klammermaschine (10) eingesetzt sein kann, wobei die Querlöcher (58) mit dem Kanal (16) der Klammermaschine (10) fluchten, so daß der Treiber (22) durch die Querlöcher (58) des Magazins (21) und entlang der Innenfläche (56) zwischen der Lade- und der Auswurfstellung bewegt werden kann, wobei der Schieber (60) sich auf der Seite des Stapels von Klammern (11) gegenüber der Führungswand (55) befindet, so daß die Feder (15) den Schieber (60) und die Klammern (11) in Richtung zur Innenfläche (56) des Gehäuses (54) vorspannt; und

ein Verriegelungselement (66), welches das Gehäuse (54) des Magazins (21) lösbar verbunden hält mit dem Gehäuse (14) der Klammermaschine (21), wobei das Verriegelungselement (66) einen Abstandshalter (68) aufweist, der mit einer Achse und einem Ende (73) auf dem Gehäuse (54) angeordnet ist, wobei sich der Abstandshalter (68) axial und im allgemeinen mittig von dem Gehäuse (54) weg erstreckt auf der Seite der Führungswand (55) gegenüber der Innenfläche (56) der Führungswand (55) in einem im allgemeinen rechten Winkel zu der Innenfläche (56) der Führungswand (55) über einen ersten vorbestimmten Abstand, der in etwa dem Abstand zwischen der Innenfläche und den Außenflächen (63) der Stützwand (61) der Klammermaschine (10) entspricht, und wobei der Abstandshalter in der durchgehenden Öffnung (62) in der Stützwand (61) angeordnet sein kann, wenn das Magazin (21) an der Klammermaschine befestigt ist; einen Verriegelungsabschnitt (70), der sich axial über den Abstandshalter (68) hinaus erstreckt, wobei der Verriegelungsabschnitt (70) mindestens einen Vorsprung (70) aufweist, der sich seitlich in bezug auf die Achse des Abstandshalters (68) erstreckt, wobei der Vorsprung (70) eine Eingriffsfläche im Bereich der Führungswand (55) aufweist, die mit der Außenfläche (63) der Stützwand (61) der Klammermaschine (10) in Eingriff kommen kann; und eine Einrichtung zum Lösung der Verbindung der Eingriffsfläche des Vorsprungs (70) mit der Außenfläche (63) der Stützwand (61), so daß das Magazin (21) aus dem Gehäuse (14) entfernt werden kann.

4. Klammermagazin (21) nach Anspruch 3, welches einen ringförmigen Rand (73) am Ende des Abstandshalters (68) gegenüber dem Verriegelungsabschnitt (70) aufweist, um das Verriegelungselement (66) drehbar an dem Gehäuse (54) zu befestigen, so daß ein Abschnitt der Einrichtung zum Lösen der Verbindung der Eingriffsfläche auf dem Vorsprung (70) mit der Außenfläche der Stützwand (61) entsteht, und der Verriegelungsabschnitt (70) umfaßt zwei Vorsprünge (70), die sich von gegenüberliegenden Seiten des Verriegelungsabschnittes (70) seitlich nach außen erstrecken, wobei die Vorsprünge (70) so bewegt werden können, daß ein weiterer Abschnitt der Einrichtung zum Lösen der Verbindung mit der Eingriffsfläche der Vorsprünge (70) entsteht.

Revendications

1. Combinaison d'une agrafeuse (10) et d'une



cartouche d'agrafes (21) comportant des agrafes (11) généralement en forme de U, chacune comprenant une partie centrale (12) et deux parties de branche (13) généralement parallèles et faisant saillie généralement dans la même direction à partir d'extrémités opposées à sa partie centrale (12) et présentant des extrémités distales,

l'agrafeuse (10) comprenant :

- un logement (14) qui a un passage (16) s'étendant depuis un orifice d'entrée (18) jusqu'à un orifice de sortie (20), le passage (16) étant agencé pour guider une agrafe unique (11) déplacée depuis l'orifice d'entrée (18) jusqu'à l'orifice de sortie (20) avec les extrémités distales de ses branches (13) en avant,
- un entraîneur (22) qui a une partie d'extrémité (24) agencée pour être en prise avec la partie centrale (12) d'une des agrafes (11) et qui est monté dans le logement (14) pour un mouvement coulissant entre une position de chargement (figure 3), l'entraîneur (22) étant écarté de l'orifice d'entrée (18) pour permettre un mouvement d'une des agrafes (11) dans le passage (16), le long du passage (16), la partie d'extrémité (24) poussant l'agrafe (11), et une position d'éjection (figure 4) dans laquelle la partie d'extrémité (24) de l'entraîneur (22) pousse l'agrafe (11) hors de l'orifice de sortie (20), et
- des moyens de commande (26) agencés pour être actionnés à la main afin de propulser l'entraîneur (22) le long du passage (16) depuis la position de chargement jusqu'à la position d'éjection pour déplacer l'agrafe (11) depuis l'orifice d'entrée (18) jusqu'à l'orifice de sortie (20), et

la cartouche d'agrafes (21) comprenant un boîtier (54), une pile d'agrafes (11) dans le boîtier (54) et un plateau (60) d'un côté de la pile d'agrafes (11) et mobile dans le boîtier (54) avec la pile d'agrafes (11), et un ressort (15) pour solliciter le plateau (60) et la pile d'agrafes (11),

la combinaison étant caractérisée en ce que le logement (14) de l'agrafeuse (10) comporte une paroi portante (61) qui a une surface interne déterminant une emboîture (59) à l'orifice d'entrée, la paroi portante (61) comportant aussi une surface externe (63) et un orifice traversant (62) entre la surface interne et la surface externe (63) et en ce que le boîtier (54) de la cartouche d'agrafes (21) comporte une paroi de guidage (55) qui détermine une

surface interne (56) et des parois latérales (57) qui font saillie généralement perpendiculairement à la surface interne (56), les parois latérales (57) comportant des orifices transversaux opposés (58) sur la surface interne (56) et alignés avec le passage (16) de l'agrafeuse (10), la paroi de guidage (55) étant logée dans l'emboîture (59) et la surface interne (56) de la paroi de guidage (55) déterminant une partie du passage (16) dans l'orifice d'entrée (18) de sorte que l'entraîneur (22) puisse être déplacé, au travers des orifices et le long de la surface interne, entre les positions de chargement et d'éjection, le plateau (60) étant situé du côté de la pile d'agrafes (11) qui est opposé au passage (16) de sorte que le ressort (15) sollicite le plateau (60) et les agrafes (11) vers la surface interne (56) du boîtier (54), et un élément de blocage (66) pour maintenir de façon détachable le boîtier (54) de la cartouche (21) en prise avec le logement (14) de l'agrafeuse (10), l'élément de blocage (66) comportant une partie d'espacement (68) qui présente un axe et une extrémité (73) montée dans le boîtier (54), la partie d'espacement (68) faisant saillie axialement et généralement de façon centrée à l'écart du boîtier (54) du côté de la paroi de guidage (55) opposé à la surface interne (56) de la paroi de guidage (55), à un angle généralement droit par rapport à la surface interne (56) de la paroi de guidage (55), sur une première distance prédéterminée approximativement égale à la distance entre la surface interne et des surfaces externes (63) de la paroi portante (61), et étant positionnée dans l'orifice traversant (62) de la paroi portante (61) lorsque la cartouche (21) est fixée à l'agrafeuse (10), une partie de blocage (70) qui fait saillie axialement au-delà de la partie d'espacement (68), la partie de blocage (70) comportant au moins une oreille (70) qui s'étend latéralement par rapport à l'axe de la partie d'espacement (68), l'oreille (70) ayant une surface de prise voisine de la paroi de guidage (55) et en prise avec la surface externe (63) de la paroi portante (61) de l'agrafeuse (10), et des moyens de libération de la prise entre la surface de prise de la partie de blocage (70) et la surface externe (63) de la paroi portante (61) pour permettre de démonter la cartouche (21) du logement (14).

2. Combinaison d'une agrafeuse et d'une cartouche d'agrafes suivant la revendication 1, caractérisée en ce que la cartouche d'agrafes (21) comporte un bord annulaire (73), à l'extrémité de la partie d'espacement (68) opposée à la partie de blocage (70), pour monter l'élément



de blocage (66) en vue d'un mouvement de rotation par rapport au boîtier (54) afin de procurer une partie des moyens de libération de la prise entre la surface de prise de l'oreille (70) et la surface externe de la paroi portante (61) et en ce que la partie de blocage (70) comporte deux oreilles (70) qui s'étendent latéralement vers l'extérieur à partir de côtés opposés de la partie de blocage (70), les oreilles (70) étant agencées pour être manipulées afin de fournir une autre partie des moyens de libération de la prise de la surface de prise des oreilles (70).

3. Cartouche d'agrafes (21) à utiliser dans une agrafeuse (10) déterminée dans la revendication 1, la cartouche d'agrafes (21) comprenant un boîtier (54), une pile d'agrafes (11) dans le boîtier (54) et un plateau (60) d'un côté de la pile d'agrafes (11) et mobile dans le boîtier (54) avec la pile d'agrafes (11), et un ressort (15) pour solliciter le plateau (60) et la pile d'agrafes (11), les agrafes (11) ayant généralement une forme en U et chaque agrafe (11) comprenant une partie centrale (12) et deux parties de branche (13) généralement parallèles et faisant saillie généralement dans la même direction à partir d'extrémités opposées à sa partie centrale (12) et présentant des extrémités distales, la cartouche d'agrafes (21) étant caractérisée en ce que le boîtier (54) de la cartouche d'agrafes (21) comporte une paroi de guidage (55) qui détermine une surface interne (56) et des parois latérales (57) qui font saillie généralement perpendiculairement à la surface interne (56), les parois latérales (57) comportant des orifices transversaux opposés (58) adjacents à la surface interne (56) et agencés pour être positionnés en alignement avec le passage (16) de l'agrafeuse (10), la paroi de guidage (55) étant agencée pour être logée dans l'emboîture (59) de l'agrafeuse (10), les orifices transversaux (58) étant en alignement avec le passage (16) de l'agrafeuse (10) de sorte que l'entraîneur (22) puisse être déplacé, au travers des orifices transversaux (58) de la cartouche (21) et le long de la surface interne (56), entre les positions de chargement et d'éjection, le plateau (60) étant situé du côté de la pile d'agrafes (11) opposé à la paroi de guidage (55) de sorte que le ressort (15) sollicite le plateau (60) et les agrafes (11) vers la surface interne (56) du boîtier (54), et un élément de blocage (66) pour maintenir de façon détachable le boîtier (54) de la cartouche (21) en prise avec le logement (14) de l'agrafeuse (10), l'élément de blocage (66) comportant une partie d'espacement (68) qui

présente un axe et une extrémité (73) montée dans le boîtier (54), la partie d'espacement (68) faisant saillie axialement et généralement de façon centrée à l'écart du boîtier (54) du côté de la paroi de guidage (55) opposé à la surface interne (56) de la paroi de guidage (55), à un angle généralement droit par rapport à la surface interne (56) de la paroi de guidage (55), sur une première distance prédéterminée approximativement égale à la distance entre la surface interne et des surfaces externes (63) de la paroi portante (61) de l'agrafeuse (10), et étant agencée pour être positionnée dans l'orifice traversant (62) de la paroi portante (61) lorsque la cartouche (21) est fixée à l'agrafeuse (10), une partie de blocage (70) qui fait saillie axialement au-delà de la partie d'espacement (68), la partie de blocage (70) comportant au moins une oreille (70) qui s'étend latéralement par rapport à l'axe de la partie d'espacement (68), l'oreille (70) ayant une surface de prise voisine de la paroi de guidage (55) et agencée pour entrer en prise avec la surface externe (63) de la paroi portante (61) de l'agrafeuse (10), et des moyens de libération de la prise entre la surface de prise de l'oreille (70) et la surface externe (63) de la paroi portante (61) pour permettre de démonter la cartouche (21) du logement (10).

4. Cartouche d'agrafes (21) suivant la revendication 3, qui comporte un bord annulaire (73), à l'extrémité de la partie d'espacement (68) opposée à la partie de blocage (70), pour monter l'élément de blocage (66) en vue d'un mouvement de rotation par rapport au boîtier (54) afin de procurer une partie des moyens de libération de la prise entre la surface de prise de l'oreille (70) et la surface externe de la paroi portante (61), et en ce que la partie de blocage (70) comporte deux oreilles (70) qui s'étendent latéralement vers l'extérieur à partir de côtés opposés de la partie de blocage (70), les oreilles (70) étant agencées pour être manipulées afin de fournir une autre partie des moyens de libération de la prise de la surface de prise des oreilles (70).