

Description

Technical Field

The invention relates to timing circuits and, in particular, to a circuit which times an event, namely a signal zero crossing, and produces a digital representation of the timed event.

Background Art

The signal digitizing method used in the Hewlett-Packard 5371A Frequency and Time Analyzer is an example of a very useful type of signal representation based on continuous counting and sampling only at signal zero crossings. By means of this method it is possible to directly digitize the phase progression of the signal, thereby eliminating any need for the previously-required steps of voltage digitizing and voltage-to-phase conversion. The procedure may therefore be appropriately called "phase progression digitizing," or "phase digitizing". Amplitude information is discarded.

Phase digitizing is illustrated in Fig. 3, which shows signal sample locations, represented by dark dots, on a sinusoidal signal of changing frequency. Samples occur at occasional upcrossings at a relatively constant rate. Each sample produces two increasing numbers, the total cycle count and the time stamp at that point. The cycle count comes from reading a counter counting the signal. Every cycle is counted, not just those on which a sample occurs. When a sample occurs, a synchronizer gates the upcrossing of the cycle during which the sample occurs so as to time-stamp that cycle. This is accomplished by reading another counter which continuously counts a 500 MHz time base clock. With interpolation, the resolution is improved from 2 ns to 0.2 ns. In phase digitizing, down-crossings of the event signal, as well as upcrossings or as an alternative to upcrossings, can be time stamped.

The interpolation technique of the prior art is based on delay propagating through distributed high-speed flip-flops. As shown in Fig. 4, two latched signals, representing the event occurrence and the clock, go to a bank of nine high-speed D flip-flops which determine the relative phase between the two signals at nine equally spaced delay stages. The total delay spans the 2-ns period of the time base clock.

The event latch signal is progressively delayed by 200 ps per stage (one time quantum per stage). Flip-flop outputs will quantize the delay time interval with logical one and zero outputs indicating event latch delay. The flip-flops output a thermometer code, which is converted into a binary code and stored with the event count and time count in a memory system. The thermometer code counts as follows 000...000, 100...000, 110...000, 111...000, ..., 111...110, 111...111. At the end of the count, the code does not reset itself to zeros. The interpolator output, converted from thermometer code to bi-

nary, plus the digital representation of the event count, yields the digitized time of event signal.

There are a number of problems associated with this prior art method. Since the latching elements are discrete components, they do not match well. Good linearity is achieved only by individual adjustments of each element. Besides linearity, the total delay must match 1 period of the non-subdivided clock interval, for accuracy. The timing resolution is determined by the physical separation between discrete latching elements. In many delay lines, delays are set a priori and subject to variations. Both linearity and accuracy will be degraded with circuit parameter variations. Also delay lines sit idle until activated by a measurement. Thus, both accuracy and linearity change to some degree with various measurement rates.

This method also requires N-1 latching elements to interpolate N subparts. It would be desirable to reduce the number of latches relative to the number of subparts.

Another problem in the prior art is the necessity to actually isolate a particular clock pulse with a synchronizer, and to do so with low time jitter. The metastability of the synchronizing process makes this difficult, particularly at high frequencies. A circuit is "metastable" if a small jitter in one signal does not result in a sudden, large change in another. A lack of metastability is manifest during a transition of a pulse. More particularly, slight variations between the phase of a transition in an input signal and the phase of a transition in a reference signal can result in large and erroneous variations in an output signal. For example, in Fig. 11 the transition of a conventional counter or synchronizer is shown to be misaligned, i.e. skewed, with an event measuring pulse stream in plot A due to the statistical fluctuations mentioned above. If a measurement is made at the time indicated by vertical line α , the count is read as 63 or $((3 \times 16) + 15)$. If a measurement is made slightly later at time β , the count is 48 or $((3 \times 16) + 0)$. If a measurement is made at time γ , the count is 64 or $((4 \times 16) + 0)$. These counting uncertainties occur with high probability and produce serious systematic error.

Summary of Invention

The above problems have been overcome in an event timer which, like the prior art, uses an interpolator for fine time stamping between timed events, but has good linearity, improved accuracy and reduces the number of latches in forming the delay subparts. The new timer produces nearly uniform delay between elements, and reduces statistical error arising from metastability and pulse jitter, yielding a more reliable time stamp.

The event timer of the present invention uses a ring oscillator as a synchronizer substitute in the interpolator. The ring oscillator employs active circuit elements phase locked to a reference frequency standard to subdivide each clock pulse, together with linear combining ele-

Description

This invention relates to a method of weighing and dispensing a powdered dye and is typically used during the course of dyeing textile products and synthetic resin products, etc. It also relates to an apparatus suitable for carrying out the method, and more particularly, to a method and an apparatus for weighing and dispensing a powdered dye efficiently to thereby enable any error or deviation from a required quantity of a powdered dye to be minimized.

Description of the Prior Art:

To conduct dyeing treatments satisfactorily, it is required basically for a dye liquor to contain a proper required quantity of a dye. If the dye is powdery, it is not always easy to weigh and dispense a required quantity of the powdered dye accurately.

A conventional method, as disclosed in EP-A-0 299 522, of weighing and dispensing a powdered dye stored in a container has been to dispense the dye in an approximately required quantity by means of a measuring means such as a measuring cup, or by pouring it out from the lower part of the container and compensating for the surplus or the deficiency of the dye by means of an weighing instrument such as an electronic weigher; or alternatively to dilute the powdered dye, taken out by the same procedure as mentioned above in a quantity slightly more than the required amount, with a liquid such as, for example, water so as to prepare a dye liquor having a known dye concentration, and then dispensing the dye liquor in a quantity which contains the proper required quantity of the powdered dye out of the prepared dye liquor.

Out of the above-mentioned two conventional methods of weighing and dispensing powdered dye, the former method wherein a dye is dispensed in powdery state has been conducted commonly in laboratories. However, since this method is troublesome in weighing and compensating for the surplus or the deficiency and is therefore inefficient for industrial application. It has been general for industrial purposes to control the quantity of a powdered dye flowing out from a container by means of a fixed quantity delivery means in an error range of $\pm 0.5 \sim 0.25$ gr.. In case of dyeing, if the quantity of a powdered dye contained in a dye liquor has an error or deviation of 1 % or more from a required quantity, then there occurs a visually different result of dyeing. Therefore, the above-mentioned former method of dispensing a powdered dye has been used in bulk dyeing using a dye liquor containing a required quantity of more than 50 gr. of the dye in which the dye can be weighed and dispensed at a relatively high accuracy. However, small quantity dyeing using a dye liquor containing a required quantity of less than 50 gr. of the dye has required troublesome reweighing and compensation.

The latter method, wherein a powdered dye is weighed and dispensed in the form of a diluted solution which contains a required quantity of the dye, provides a highly accurate weighing depending on the degree of dilution. According to this method, however, the quantity of the diluted solution increases with an increase in the required quantity of the dye, thus posing problems on installation and operations; also, if a large quantity of the dye liquor is kept in store, there is a possibility of aging of the dye liquor. Therefore, the latter method is used only for trial dyeing, sample dyeing and small-quantity dyeing, etc. where a small quantity of a dye is taken out and used.

SUMMARY OF THE INVENTION

The present invention has been made in view of the above-mentioned circumstances in the prior art, and has for its object to provide a method of dispensing a powdered dye, which is almost completely free from bad influence by an error which occurs at the time of dispensing the powdered dye, and which enables the dye to be weighed and dispensed quickly and at a high accuracy regardless of the required quantity of the dye, thereby improving the efficiency of dyeing operation and achieving a satisfactory result of dyeing, and also an apparatus suitable for carrying out the method.

According to a first aspect of the invention there is provided a method of dispensing a required quantity (a) by weight of a dye, comprising: a first step of dispensing and then weighing a first quantity (b) of the dye, in powdered form, slightly less than the required quantity (a); a second step of dispensing and then weighing a second quantity (c) of the dye, in powdered form, slightly greater than the difference (d) between the required quantity (a) and said first quantity (b), and adding, to the second quantity (c) of dye in powdered form, a liquid such as water or a solvent or a dispersion medium, at a particular ratio to the weight of the second quantity (c) of dye, so as to prepare a solution or liquor having a known dye concentration; and a third step of dispensing a particular quantity of the solution or liquor and adding it to said first quantity (b) of dye so as to obtain the required quantity (a) of dye.

To achieve the above-mentioned object, according to a second aspect of the present invention, there is provided an apparatus for dispensing a powdered dye, comprising: a powdered dye storage tank, a relatively large quantity powdered dye discharge pipe and a relatively small quantity powdered dye discharge pipe, each being connected to the lower part of the storage tank and each having a fixed quantity delivery means associated therewith; a first dye container located below the relatively large quantity powdered dye discharge pipe and placed on a first weigh-

ing device; a second dye container located below the relatively small quantity powdered dye discharge pipe and placed on a second weighing device; a liquid supply pipe for supplying a liquid such as water or a solvent or a dispersion medium into the second dye container; and a pump piping system for transferring a predetermined quantity of a diluted solution having a particular dye concentration prepared in the second dye container into the first dye container, wherein the operations of the fixed quantity delivery means associated with the relatively large quantity powdered dye discharge pipe, the fixed quantity delivery means associated with the relatively small quantity powdered dye discharge pipe, the liquid supply pipe and a pump of the pump piping system are controlled by a computer in accordance with the weighed value or values obtained as a result of weighing by any one or both of the weighing devices.

To achieve the above-mentioned objects, in accordance with a third aspect of the present invention, there is provided an apparatus for dispensing a plurality of kinds of powdered dyes, comprising: a plurality of powdered dye storage tanks located substantially in a row; relatively large quantity powdered dye discharge pipes each having a fixed quantity delivery means associated therewith and being connected to the lower part of each storage tank so as to project on one side of the row of the storage tanks; relatively small quantity powdered dye discharge pipes each having a fixed quantity delivery means associated therewith and projecting on the other side of the row of the tanks; a first weighing device mounted so as to be movable on a path located below the relatively large quantity powdered dye discharge pipes of the storage tanks and extending in parallel with the row of the tanks; a first dye container resting on the first weighing device; a second weighing device mounted so as to be movable on a path located below the relatively small quantity powdered dye discharge pipes of the storage tanks and extending in parallel with the row of the tanks; second dye containers each being located below the relatively small quantity powdered dye discharge pipe of each storage tank and between the relatively small quantity powdered dye discharge pipe and the path on which the second weighing device is moved, each of the second dye containers being located on and supported by the second weighing device so as to be selectively weighed by the latter; liquid supply pipes each supplying a liquid such as water or a solvent or a dispersion medium into each of the second dye containers associated therewith; and pump piping systems provided separately for each of the second dye containers so as to transfer a diluted solution having a particular dye concentration prepared therein into the first dye container, wherein the movement of the first and second weighing devices to positions opposite to a particular one of the powdered storage tanks located in a row, and operations

of the fixed quantity delivery means associated with the relatively large quantity powdered dye discharge pipe and the relatively small quantity powdered dye discharge pipe, respectively, of the particular storage tank, the two weighing devices, the liquid supply pipe and a pump of the pump piping system associated with the particular storage tank are controlled by a computer in accordance with a particular program and the values obtained as a result of weighing by the two weighing devices.

According to the method of the present invention as set forth in the first aspect, powdered dye can be dispensed easily and with high accuracy by dispensing and weighing most of a required quantity of the powdered dye directly in a powdery state, and dispensing the remaining quantity of the powdered dye separately in a state of solution thereby eliminating any bad influence due to error in the discharge by the fixed quantity delivery means. Further, according to the first apparatus set forth in the second aspect of the present invention, the above-mentioned method for weighing and dispensing a single powdered dye can be carried out simply. Still further, according to the second apparatus as set forth in the third aspect, the above-mentioned method can be effected repeatedly to weigh and dispense several kinds of powdered dyes in turn and continuously in accordance with their respective required quantity. The use of the second apparatus is extremely advantageous in terms of costs of equipment and operation as compared with the case of using a plurality of the first apparatuses.

The above-mentioned and other objects, aspects and advantages of the present invention will become apparent to those skilled in the art by making reference to the following description and the accompanying drawings in which preferred embodiments incorporating the principles of the present invention are shown by way of example only.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a fragmentary front view showing the section of the principal parts of a first apparatus according to the present invention;

Fig. 2 is a horizontal sectional view of a powdered dye storage tank;

Figs. 3 and 4 are sectional views of the tank shown in fig. 2 taken along lines III - III and IV - IV, respectively, in Fig. 2;

Fig. 5 is a fragmentary front view showing the section of the principal parts of a second apparatus according to the present invention; and

Fig. 6 is a plan view of the second apparatus of the present invention shown in fig. 5.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The method and apparatus of the present invention will now be described below by way of embodiments thereof with reference to the accompanying drawings.

Fig. 1 is a fragmentary front view showing the section of the principal parts of the first apparatus according to the present invention.

In the drawings, reference numeral 1 denotes a storage tank for storing a powdered dye; 2 a relatively large quantity powdered dye discharge pipe projecting from the lower part of the storage tank 1 and provided with a fixed quantity delivery means; 3 a relatively small quantity powdered dye discharge pipe provided with a fixed quantity delivery means; 21 a first weighing device which is an electronic weigher located below the relatively large quantity powdered dye discharge pipe 2; 19 a first dye container placed on the first weighing device 21; 22 a second weighing device which is an electronic weigher located below the relatively small quantity powdered dye discharge pipe 3; and 20 a second dye container placed on the second weighing device 22.

Further, reference numeral 25 denotes a liquid supply pipe for supplying a liquid such as water or a solvent or a dispersion medium for dye into the second dye container 20; 26 a stirrer; and 30 a pump piping system which includes a pump 31, a suction pipe 32 connected to the suction side of the pump 31 and which is inserted into the second dye container 20, and a discharge pipe 33 whose leading end opens above the first dye container 19.

Reference numeral 40 denotes a bed; 41 a cover; 42 and 43 brackets for supporting rotating drive shafts 4, 5 adapted to actuate the fixed quantity delivery means associated with the above-mentioned relatively large quantity powdered dye discharge pipe 2 and relatively small quantity powdered dye discharge pipe 3, respectively; and 44 electrical wirings for the first and second weighing devices 21 and 22.

Figs. 2, 3 and 4 show the relatively large quantity powdered dye discharge pipe 2 and the relatively small quantity powdered dye discharge pipe 3, respectively, connected to the lower part of the storage tank 1, and the fixed quantity delivery means associated with the discharge pipes 2 and 3, respectively. The relatively large quantity dye discharge pipe 2 is a pipe having a large bore which extends outwardly from the tank wall and in which a helical or screw member 16 extends through the interior of the tank 1 and along the entire length of the large quantity powdered dye discharge pipe 2. The rear end of the helical or screw member 16 is fixedly secured to and supported by a rotating support shaft 8 which extends through the tank wall. Provided above the spiral or screw member 16 and the shaft 8 is a rotating shaft

6 which has a stirring blade mounted thereon and which passes through the tank wall and is supported so as to be slidably moved in the axial direction thereof. One end of the rotating shaft 6 is connected through a sliding-contact coupling to the operating end of a first air cylinder 14, whilst the other end thereof has fixedly secured thereto a bevel gear 12 fitted with a spur gear which meshes with the spur gear mounted on the above-mentioned rotating support shaft 8. With the piston rod within the first air cylinder 14 being extended outwardly, the bevel gear 12 having a spur gear mounted thereon is allowed to mesh with a bevel gear 10 mounted on the rotating drive shaft 5 so as to rotate the rotating shaft 6 fitted with a stirring blade, and also turn, through the intermeshing of the spur gears, the rotating support shaft 8 and the helical or screw member 16 fixedly secured thereto, so that the powdered dye stored in the storage tank 1 is subjected to a stirring action made by the stirring blade mounted on the rotating shaft 6 and also a quick powder delivery action caused by the turning of the helical or screw member 16 having a relatively large pitch within the powdered dye discharge pipe 2 having a relatively large bore thus discharging a large quantity of the powdered dye. Subsequently, when the piston rod in the first air cylinder 14 is withdrawn to its initial position, the bevel gear 12 is disengaged from the bevel gear 10 of the rotating drive shaft 5 to thereby stop the rotation of the shafts 6 and 8 and the turning of the helical or screw member 16.

The relatively small quantity powdered dye discharge pipe 3 is smaller in bore than the relatively large quantity powdered discharge pipe 2, and has a helical or screw member 17 inserted therein to cause powdered dye delivery action. With the exception that the helical or screw member 17 is smaller in diameter and pitch than the helical or screw member 16 and is capable of delivering powdered dye with a higher accuracy than the former, powdered dye delivery action and the stoppage thereof provided by connection and disconnection between a rotating shaft 7 having a stirring blade mounted thereon, and a rotating support shaft 9, and also that between a bevel gear 11 mounted on the rotating drive shaft 4 and a bevel gear 13 due to actuation of a second air cylinder 15 can be made entirely in the same manner as aforementioned.

One embodiment of the method of weighing and dispensing a powdered dye using the above-mentioned first apparatus will be described below.

The maximum error (P) on the accuracy of dispensing powdered dye from the relatively large quantity powdered dye discharge pipe 2 of this apparatus is ± 0.5 gr., the maximum error of the accuracy of taking out powdered dye from the relatively small quantity powdered dye discharge pipe 3 is ± 0.35 gr., the measuring accuracy of the two electronic weighers is ± 0.005 gr., and the maximum error of the liquid supply

accuracy of the pump piping system is ± 0.25 cc. The required quantity (a) of the powdered dye is input to a computer, not shown. If the value of required quantity of the dye is 9.36 gr., then the computer will output the value to the first weighing device 21, and at the same time command the fixed quantity delivery means associated with the relatively large quantity powdered dye discharge pipe 2 of the storage tank 1 to deliver the powdered dye by an amount of 8 gr. which is less by one than the figure at the units place of the value of required quantity. If the weighted value (b) of the powdered dye received in the first dye container 19 is 8.5 gr., then the value (c) of difference of 0.86 gr. between the required quantity (a) and the weighed value (b) which needs to be supplemented is stored by the computer. Whilst, to cover the error range of the accuracy, the computer will command the fixed quantity delivery means associated with the small quantity powdered dye discharge pipe 3 to deliver the powdered dye by an amount of 1.56 gr. which equals to the value (c) of difference plus 0.7 gr. Then, the powdered dye discharged into the second dye container 20 is weighed by the second weighing device 22, and the weighed value is assumed to be 1.5 gr.. Subsequently, the computer will command the liquid supply pipe 25 to supply 750 cc of water to prepare diluted solution of 0.2 %, and at the same time command the stirrer 26 to start to stir the solution, and then command the pump 31 in the pump piping system to transfer the diluted solution of 430 cc (including 0.86 gr. of the dye) into the first dye container 19 to thereby supplement the dye liquor with the accuracy of error range of ± 0.25 cc. As a result, a dye liquor containing the dye of 9.36 ± 0.0005 gr., error or deviation of which from the required quantity is extremely small, is obtained in the first dye container 19.

An embodiment of the second apparatus of the present invention will be described below with reference to Fig. 5 which is a fragmentary front view showing the section of the principal parts thereof, and Fig. 6 showing the plan view thereof.

This apparatus comprises a plurality of unit devices having nearly the same arrangement as those of the above-mentioned first apparatus. This apparatus comprises a plurality of storage tanks 1, in which different kinds of powdered dyes are stored, and is arranged such that the aforementioned operations are made in turn and continuously every storage tank 1. The component parts of this apparatus having the same function as those of the aforementioned first apparatus are indicated with the same reference numerals. As already mentioned, this apparatus comprises a plurality of storage tanks 1, located in a row, and each of the tanks 1 has a relatively large quantity powdered dye discharge pipe 2 projecting on one side of the row thereof and a relatively small quantity powdered dye discharge pipe 3 projecting on the other side of the row thereof. Two guide rails 38 and 39 are

mounted below the discharge pipes 2 and 3, respectively, and in parallel with the row of the storage tanks 1. Further, a first weighing device 21 which is an electronic weigher and a second weighing device 22 which is also an electronic weigher are arranged so that they may be moved on the guide rails 38 and 39, respectively. Both the weighing devices 21 and 22 are controlled such that they may be moved by transfer chains to positions opposite to a particular or any relevant storage tank 1 and stopped there.

The first weighing device 21 holds a first dye container 19 resting thereon, whilst the second weighing device 22 has a dish-shaped surface adapted to support and raise a second dye container 20 resting on a base 36 together the latter every dye storage tank 1. The base 36 is arranged to be moved up and down and loosely fitted in an opening formed in a rack 35. When the second weighing device is arranged to support and raise the container 20 together with the pedestal 36, it is ready for commencing its weighing operation.

A pump piping system 30 is provided independently for each of the dye storage tanks 1, and a liquid supply pipe 25 and a stirrer 26 are provided for each of the second dye containers 20.

By controlling the movement of the first and second weighing devices 21 and 22 to positions opposite to a particular one out of the powdered dye storage tanks 1 located in a row by a computer, and also by controlling the weighing and dispensing of the powdered dyes at respective tanks by the computer in the same manner as in the case of the aforementioned first apparatus, a required quantity of each of different kinds of powdered dyes stored in each of the storage tanks can be transferred or taken in the first dye container 19 with a minimum error or deviation.

It is a matter of course that in the case of the above operation the value of required quantity commanded by the computer to the first weighing device 21 is the total value of required quantities of different kinds of dyes.

Thus, the first dye container 19 in which the weighed and delivered dye is accommodated is transferred to a position where a diluted liquid supply pipe 45 and a dyeing aid supply pipe 46 are installed where the diluted liquid and the dyeing aid is added to the dye to prepare a desired dye liquor composition, which is then transported to a dyeing apparatus.

In the above-mentioned embodiment, if the conditions of the second apparatus controlled by the computer are changed, then a second method of the present invention can be carried out.

Claims

1. A method of dispensing a required quantity (a) by weight of a dye, comprising:



accuracy of the pump piping system is ± 0.25 cc. The required quantity (a) of the powdered dye is input to a computer, not shown. If the value of required quantity of the dye is 9.36 gr., then the computer will output the value to the first weighing device 21, and at the same time command the fixed quantity delivery means associated with the relatively large quantity powdered dye discharge pipe 2 of the storage tank 1 to deliver the powdered dye by an amount of 8 gr. which is less by one than the figure at the units place of the value of required quantity. If the weighted value (b) of the powdered dye received in the first dye container 19 is 8.5 gr., then the value (c) of difference of 0.86 gr. between the required quantity (a) and the weighed value (b) which needs to be supplemented is stored by the computer. Whilst, to cover the error range of the accuracy, the computer will command the fixed quantity delivery means associated with the small quantity powdered dye discharge pipe 3 to deliver the powdered dye by an amount of 1.56 gr. which equals to the value (c) of difference plus 0.7 gr. Then, the powdered dye discharged into the second dye container 20 is weighed by the second weighing device 22, and the weighed value is assumed to be 1.5 gr.. Subsequently, the computer will command the liquid supply pipe 25 to supply 750 cc of water to prepare diluted solution of 0.2 %, and at the same time command the stirrer 26 to start to stir the solution, and then command the pump 31 in the pump piping system to transfer the diluted solution of 430 cc (including 0.86 gr. of the dye) into the first dye container 19 to thereby supplement the dye liquor with the accuracy of error range of ± 0.25 cc. As a result, a dye liquor containing the dye of 9.36 ± 0.0005 gr., error or deviation of which from the required quantity is extremely small, is obtained in the first dye container 19.

An embodiment of the second apparatus of the present invention will be described below with reference to Fig. 5 which is a fragmentary front view showing the section of the principal parts thereof, and Fig. 6 showing the plan view thereof.

This apparatus comprises a plurality of unit devices having nearly the same arrangement as those of the above-mentioned first apparatus. This apparatus comprises a plurality of storage tanks 1, in which different kinds of powdered dyes are stored, and is arranged such that the aforementioned operations are made in turn and continuously every storage tank 1. The component parts of this apparatus having the same function as those of the aforementioned first apparatus are indicated with the same reference numerals. As already mentioned, this apparatus comprises a plurality of storage tanks 1, located in a row, and each of the tanks 1 has a relatively large quantity powdered dye discharge pipe 2 projecting on one side of the row thereof and a relatively small quantity powdered dye discharge pipe 3 projecting on the other side of the row thereof. Two guide rails 38 and 39 are

mounted below the discharge pipes 2 and 3, respectively, and in parallel with the row of the storage tanks 1. Further, a first weighing device 21 which is an electronic weigher and a second weighing device 22 which is also an electronic weigher are arranged so that they may be moved on the guide rails 38 and 39, respectively. Both the weighing devices 21 and 22 are controlled such that they may be moved by transfer chains to positions opposite to a particular or any relevant storage tank 1 and stopped there.

The first weighing device 21 holds a first dye container 19 resting thereon, whilst the second weighing device 22 has a dish-shaped surface adapted to support and raise a second dye container 20 resting on a base 36 together the latter every dye storage tank 1. The base 36 is arranged to be moved up and down and loosely fitted in an opening formed in a rack 35. When the second weighing device is arranged to support and raise the container 20 together with the pedestal 36, it is ready for commencing its weighing operation.

A pump piping system 30 is provided independently for each of the dye storage tanks 1, and a liquid supply pipe 25 and a stirrer 26 are provided for each of the second dye containers 20.

By controlling the movement of the first and second weighing devices 21 and 22 to positions opposite to a particular one out of the powdered dye storage tanks 1 located in a row by a computer, and also by controlling the weighing and dispensing of the powdered dyes at respective tanks by the computer in the same manner as in the case of the aforementioned first apparatus, a required quantity of each of different kinds of powdered dyes stored in each of the storage tanks can be transferred or taken in the first dye container 19 with a minimum error or deviation.

It is a matter of course that in the case of the above operation the value of required quantity commanded by the computer to the first weighing device 21 is the total value of required quantities of different kinds of dyes.

Thus, the first dye container 19 in which the weighed and delivered dye is accommodated is transferred to a position where a diluted liquid supply pipe 45 and a dyeing aid supply pipe 46 are installed where the diluted liquid and the dyeing aid is added to the dye to prepare a desired dye liquor composition, which is then transported to a dyeing apparatus.

In the above-mentioned embodiment, if the conditions of the second apparatus controlled by the computer are changed, then a second method of the present invention can be carried out.

Claims

1. A method of dispensing a required quantity (a) by weight of a dye, comprising:



- a first step of dispensing and then weighing a first quantity (b) of the dye, in powdered form, slightly less than the required quantity (a);
a second step of dispensing and then weighing a second quantity (c) of the dye, in powdered form, slightly greater than the difference (d) between the required quantity (a) and said first quantity (b), and adding, to the second quantity (c) of dye in powdered form, a liquid such as water or a solvent or a dispersion medium, at a particular ratio to the weight of the second quantity (c) of dye, so as to prepare a solution or liquor having a known dye concentration;
and a third step of dispensing a particular quantity of the solution or liquor and adding it to said first quantity (b) of dye so as to obtain the required quantity (a) of dye.
2. A method as claimed in claim 1, wherein said first step of dispensing and then weighing a first quantity (b) of the dye, in powdered form, is carried out by means of a dispenser having a known maximum error (P) and wherein said dispenser is set to dispense said first quantity (b) as an amount which is less than the required quantity (a) by at least the known maximum error (P).
3. An apparatus for dispensing a powdered dye, comprising: a powdered dye storage tank (1); a relatively large quantity powdered dye discharge pipe (2) and a relatively small quantity powdered dye discharge pipe (3), each being connected to the lower part of the storage tank (1) and each having a fixed quantity delivery means associated therewith; a first dye container (19) located below the relatively large quantity powdered dye discharge pipe (2) and placed on a first weighing device (21); a second dye container (20) located below the relatively small quantity powdered dye discharge pipe (3) and placed on a second weighing device (22); a liquid supply pipe (25) for supplying a liquid such as water or a solvent or a dispersion medium into the second dye container (20); and a pump piping system (30) for transferring a predetermined quantity of a diluted solution having a particular dye concentration prepared in the second dye container (20) into the first dye container (19), wherein the operations of the fixed quantity delivery means associated with said relatively large quantity powdered dye discharge pipe (2), the fixed quantity delivery means associated with said relatively small quantity powdered dye discharge pipe (3), the liquid supply pipe (25) and a pump (31) of the pump piping system (30) are controlled by a computer in accordance with the value or values obtained as a result of weighing by any one or both of the two weighing devices (21) and (22).
4. An apparatus for dispensing a plurality of kinds of powdered dyes, comprising: a plurality of powdered dye storage tanks (1) located substantially in a row; relatively large quantity powdered dye discharge pipes (2) each having a fixed quantity delivery means associated therewith and being connected to the lower part of each storage tank (1) so as to project on one side of the row of said storage tanks (1); relatively small quantity powdered dye discharge pipes (3) each having a fixed quantity delivery means associated therewith and projecting on the other side of the row of the tanks (1); a first weighing device (21) mounted so as to be movable on a path located below the relatively large quantity powdered dye discharge pipes (2) of the storage tanks (1) and extending in parallel with the row of the tanks; a first dye container (19) resting on the first weighing device (21); a second weighing device (22) mounted so as to be movable on a path located below the relatively small quantity powdered dye discharge pipes (3) of the storage tanks (1) and extending in parallel with the row of the tanks; second dye containers (20) each being located below the relatively small quantity powdered dye discharge pipe 3 of each storage tank (1) and between the relatively small quantity powdered dye discharge pipe (3) and the path on which the second weighing device (22) is moved, each of the second dye containers (20) being located on and supported by the second weighing device (22) so as to be selectively weighed by the latter; liquid supply pipes (25) each supplying a liquid such as water or a dye solvent or a dispersion medium into each of the second dye containers (20) associated therewith; and pump piping systems (30) provided separately for each of the second dye containers (20) so as to transfer a predetermined quantity of a diluted solution having a particular dye concentration prepared therein into the first dye container (19), wherein the movement of said first and second weighing devices (21) and (22) to positions opposite to a particular one of the powdered dye storage tanks 1 located in a row, and operations of the fixed quantity delivery means associated with the relatively large quantity powdered dye discharge pipe (2) and the relatively small quantity powdered dye discharge pipe (3), respectively, of the particular storage tank (1), the two weighing devices (21) and (22), the liquid supply pipe (25) and a pump (31) of the pump piping system (30) associated with the particular storage tank are controlled by a computer in accordance with a particular program and the values obtained as a result of weighing by the two weighing devices (21) and (22).



Patentansprüche

1. Verfahren zum Abgeben einer benötigten Gewichtsmenge (a) eines Farbstoffs, umfassend:
 - einen ersten Schritt des Abgebens und anschließenden Wiegens einer ersten Menge (b) des Farbstoffs in pulverförmiger Form, die geringfügig kleiner ist als die benötigte Menge (a);
 - einen zweiten Schritt des Abgebens und anschließenden Wiegens einer zweiten Menge (c) des Farbstoffs in pulverförmiger Form, die geringfügig größer ist als der Unterschied (d) zwischen der benötigten Menge (a) und der besagten ersten Menge (b), und Hinzufügen zu der zweiten Menge (c) des Farbstoffs in pulverförmiger Form einer Flüssigkeit, wie z.B. Wasser oder ein Lösungsmittel oder ein Dispersionsmedium, in einem bestimmten Verhältnis zum Gewicht der zweiten Menge (c) des Farbstoffs, um eine Lösung oder Lauge mit einer bekannten Farbstoffkonzentration bereitzustellen;
 - und einen dritten Schritt des Abgebens einer bestimmten Menge der Lösung oder der Lauge und Hinzufügen derselben zu der besagten ersten Menge (b) des Farbstoffs, um die benötigte Menge (a) des Farbstoffs zu erhalten.
2. Verfahren nach Anspruch 1, wobei der erste Schritt des Abgebens und anschließenden Wiegens einer ersten Menge (b) des Farbstoffs in pulverförmiger Form mit Hilfe einer Abgabeeinrichtung durchgeführt wird, die einen bekannten maximalen Fehler (P) hat, und wobei diese Abgabeeinrichtung so eingestellt wird, um die besagte erste Menge (b) als einen Betrag abzugeben, der mindestens um den bekannten maximalen Fehler (P) kleiner ist als die benötigte Menge (a).
3. Vorrichtung zum Abgeben eines pulverförmigen Farbstoffs, umfassend: einen Vorratsbehälter (1) für pulverförmigen Farbstoff; ein Austragrohr (2) für eine verhältnismäßig große Menge pulverförmigen Farbstoffs und ein Austragrohr (3) für eine verhältnismäßig kleine Menge pulverförmigen Farbstoffs, die jeweils mit dem unteren Teil des Vorratsbehälters (1) verbunden sind und denen jeweils eine Zuführeinrichtung für eine unveränderliche Menge zugeordnet ist; einen ersten Farbstoffbehälter (19), der unter dem Austragrohr (2) für die verhältnismäßig große Menge pulverförmigen Farbstoffs positioniert und auf einer ersten Waage (21) angeordnet ist; einen zweiten Farbstoffbehälter (20), der unter dem Austragrohr (3) für die verhältnismäßig kleine Menge pulverförmigen Farbstoffs positioniert und auf einer zweiten Waage (22) angeordnet ist; ein Flüssigkeitszuführrohr (25) zum Zuführen einer Flüssigkeit, wie z.B. Wasser oder ein Lösungsmittel oder ein Dispersionsmedium, in den zweiten Farbstoffbehälter (20); und ein Pumpenrohrleitungssystem (30) zum Überführen einer bestimmten Menge einer in dem zweiten Farbstoffbehälter (20) zubereiteten verdünnten Lösung mit einer bestimmten Farbstoffkonzentration in den ersten Farbstoffbehälter (19), wobei die Betriebsweise der dem Austragrohr (2) für eine verhältnismäßig große Menge pulverförmigen Farbstoffs zugeordneten Zuführeinrichtung für eine unveränderliche Menge, die dem Austragrohr (3) für eine verhältnismäßig kleine Menge pulverförmigen Farbstoffs zugeordneten Zuführeinrichtung für eine unveränderliche Menge, des Flüssigkeitszuführrohres (25) und einer Pumpe (31) des Pumpenrohrleitungssystems (30) von einem Computer entsprechend dem Wert oder den Werten gesteuert wird, die als Ergebnis des Wiegevorgangs einer oder beider Waagen (21 und 22) erhalten werden.
4. Vorrichtung zur Abgabe mehrerer Arten von pulverförmigen Farbstoffen, umfassend: mehrere Vorratsbehälter für pulverförmige Farbstoffe, die im wesentlichen in einer Reihe angeordnet sind; Austragrohre (2) für eine verhältnismäßig große Menge pulverförmigen Farbstoffs, denen jeweils eine Zuführeinrichtung für eine unveränderliche Menge zugeordnet ist und die mit dem unteren Teil jedes Vorratsbehälters (1) verbunden sind, so daß sie an einer Seite der Reihe von Vorratsbehältern (1) vorstehen; Austragrohre (3) für eine verhältnismäßig kleine Menge pulverförmigen Farbstoffs, denen jeweils eine Zuführeinrichtung für eine unveränderliche Menge zugeordnet ist und die auf der anderen Seite der Reihe von Vorratsbehältern (1) vorstehen; eine erste Waage (21), die so gelagert ist, daß sie auf einer Bahn bewegbar ist, die unter den Austragrohren (2) für die verhältnismäßig große Menge pulverförmigen Farbstoffs der Vorratsbehälter (1) angeordnet ist und parallel zu der Reihe von Vorratsbehältern verläuft; einen auf der ersten Waage (21) ruhenden ersten Farbstoffbehälter (19); eine zweite Waage (22), die so gelagert ist, daß sie auf einer Bahn bewegbar ist, die unter den Austragrohren (3) für verhältnismäßig kleine Mengen pulverförmigen Farbstoffs der Vorratsbehälter (1) angeordnet ist und parallel zu der Reihe von Vorratsbehältern verläuft; zweite Farbstoffbehälter (20), die jeweils unter dem Austragrohr (3) für eine verhältnismäßig kleine Menge pulverförmigen Farbstoffs jedes Vorratsbehälters (1) und zwischen dem Austragrohr (3) für eine verhältnismäßig kleine Menge pulverförmigen Farbstoffs und der Bahn angeordnet sind, auf der die zweite Waage (22) bewegt wird, wobei jeder der zweiten Farbstoffbehälter (20) auf der



zweiten Waage (22) angeordnet und durch diese abgestützt ist, so daß er wahlweise von dieser gewogen wird; Flüssigkeitszuführrohre (25), die jeweils eine Flüssigkeit, wie z.B. Wasser oder ein Farbstofflösungsmittel oder ein Dispersionsmedium in jeden der zugeordneten zweiten Farbstoffbehälter (20) zuführen; und ein Pumpenrohrleitungssystem (30), das für jeden der zweiten Farbstoffbehälter (20) getrennt vorgesehen ist, um eine darin zubereitete bestimmte Menge einer verdünnten Lösung mit einer bestimmten Farbstoffkonzentration in den ersten Farbstoffbehälter (19) zu überführen, wobei die Bewegung der ersten und zweiten Waage (21 und 22) in Positionen, die einem bestimmten der in einer Reihe angeordneten Vorratsbehälter (1) für pulverförmigen Farbstoff gegenüberliegen, und die Betriebsweise der dem Austragrohr (2) für eine verhältnismäßig große Menge pulverförmigen Farbstoffs und dem Austragrohr (3) für eine verhältnismäßig kleine Menge pulverförmigen Farbstoffs des betreffenden Vorratsbehälters (1) zugeordneten Zuführeinrichtungen für eine unveränderliche Menge, der beiden Waagen (21 und 22), des Flüssigkeitszuführrohres (25) und einer Pumpe (31) des dem betreffenden Vorratsbehälter zugeordneten Pumpenrohrleitungssystems von einem Computer gesteuert wird in Abhängigkeit von einem besonderen Programm und der Werte, die als Ergebnis des Wiegevorgangs der beiden Waagen (21 und 22) erhalten werden.

Revendications

1. Procédé pour distribuer une quantité requise (a) en poids d'un colorant, comprenant :
 - une première étape de distribution et ensuite le pesage d'une première quantité (b) du colorant, sous forme de poudre, légèrement inférieure à la quantité requise (a) ;
 - une seconde étape de distribution et ensuite le pesage d'une seconde quantité (c) du colorant, sous forme d'une poudre, légèrement supérieure à la différence (b) entre la quantité requise (a) et ladite première quantité (b), et l'addition, à la seconde quantité (c) de colorant sous forme de poudre, d'un liquide tel que de l'eau ou un solvant, ou un agent de dispersion, suivant un rapport particulier vis à vis du poids de la seconde quantité (c) de colorant, de manière à préparer une solution ou une liqueur ayant une concentration de colorant connue ; et
 - une troisième étape de distribution d'une quantité particulière de la solution ou de la liqueur et l'addition de cette quantité à ladite première quantité (b) de colorant afin d'obtenir la quantité requise (a) de colorant.
2. Procédé selon la revendication 1, dans lequel la première étape de distribution puis de pesage d'une première quantité (b) du colorant, sous forme de poudre, est effectuée au moyen d'un distributeur présentant une erreur maximale connue (P) et dans lequel le distributeur est réglé de manière à distribuer la première quantité (b) en une quantité qui est inférieure à la quantité requise (a) d'au moins l'erreur maximale connue (P).
3. Appareil pour distribuer un colorant en poudre comprenant :
 - un réservoir (1) de stockage de colorant en poudre ;
 - un conduit (2) de décharge de quantité relativement grande de colorant en poudre ; et
 - un conduit (3) de décharge de quantité relativement faible de colorant en poudre, chaque conduit étant raccordé à la partie inférieure du réservoir de stockage (1) et comportant chacun un moyen de fourniture de quantité déterminée associé à ce réservoir ;
 - un premier récipient (19) de colorant disposé en-dessous du conduit (2) de décharge de quantité relativement grande de colorant en poudre et placé sur un premier dispositif de pesage (21) ;
 - un second récipient (20) de colorant disposé en-dessous du conduit (3) de décharge de quantité relativement faible de colorant en poudre et placé sur un second dispositif de pesage (22) ;
 - un conduit (25) d'amenée de liquide pour l'amenée d'un liquide tel que de l'eau ou un solvant ou un agent de dispersion dans le second récipient (20) de colorant ; et un système (30) de tuyauteries et de pompe pour transférer dans le premier récipient (19) de colorant une quantité prédéterminée d'une solution diluée présentant une concentration de colorant particulière préparée dans le second récipient (20) de colorant, les opérations des moyens de fourniture de quantité déterminée associés au conduit (2) de décharge de quantité relativement grande de colorant en poudre, le moyen de fourniture de quantité déterminée associé au conduit (3) de décharge de quantité relativement faible de colorant en poudre, le conduit (25) d'amenée le liquide et une pompe (31) du système (30) de tuyauteries et de pompe étant commandés par un ordinateur en fonction de la valeur ou des valeurs obtenues par suite du pesage de l'un et/ou l'autre des deux dispositifs de pesage (21) et (22).
4. Appareil pour distribuer une pluralité de types de colorant en poudre, comprenant :
 - une pluralité de réservoirs (1) de stockage de colorant en poudre disposés sensiblement en une rangée ;



des conduits (2) de décharge de quantité relativement grande de colorant en poudre dont chacun comporte un moyen de fourniture de quantité déterminée qui lui est associé, et est raccordé à la partie inférieure de chaque réservoir de stockage (1) de manière à s'étendre sur un des côtés de la rangée desdits réservoirs de stockage (1) ;

des conduits (3) de décharge de quantité relativement faible de colorant en poudre dont chacun comporte un moyen de fourniture de quantité déterminée qui lui est associé et s'étend sur l'autre côté de la rangée des réservoirs (1) ;

un premier dispositif de pesage (21) monté de manière à pouvoir être déplacé sur un trajet situé en dessous des conduits (2) de décharge de quantité relativement grande de colorant en poudre des réservoirs de stockage (1) et s'étendant parallèlement à la rangée des réservoirs ;

un premier récipient (19) de colorant reposant sur le premier dispositif de pesage (21) ;

un second dispositif de pesage (22) monté de manière à pouvoir être déplacé sur un trajet situé en-dessous des conduits (3) de décharge de quantité relativement faible de colorant des réservoirs de stockage (1) et s'étendant parallèlement à la rangée des réservoirs ;

des seconds récipients (20) de colorant disposés chacun en-dessous du conduit (3) de décharge de quantité relativement faible de colorant en poudre de chaque réservoir de stockage (1) et entre le conduit (3) de décharge de quantité relativement faible de colorant en poudre et le trajet sur lequel le second dispositif de pesage (22) est déplacé, chacun des seconds récipients (20) de colorant étant disposé sur le second dispositif de pesage (22) est supporté par ce dispositif de manière à être pesé sélectivement par ce dernier ;

des conduits (25) d'amenée de liquide, amenant chacun un liquide tel que de l'eau ou un solvant de colorant ou un agent de dispersion dans chacun des seconds récipients (20) de colorant qui leur sont associés; et

des systèmes (30) de tuyauteries et de pompe prévus séparément pour chacun des seconds récipients (20) de colorant de manière à transférer dans le premier récipient (19) de colorant une quantité prédéterminée d'une solution diluée présentant une concentration de colorant particulière qui y est préparée, le déplacement des premier et second dispositifs de pesage (21) et (22) jusqu'à des positions se trouvant en face d'une position particulière des réservoirs (1) de stockage de colorant en poudre situé dans une rangée, et les opérations des moyens de fourniture de quantité déterminée associés au conduit (2) de décharge de quantité relativement grande

de colorant en poudre et au conduit (3) de décharge de quantité relativement faible de colorant, respectivement, du réservoir de stockage particulier (1), les deux dispositifs de pesage (21) et (22), le conduit (25) d'amenée de liquide et une pompe (31) du système (30) de tuyauteries et de pompe associé au réservoir de stockage particulier étant commandés par un ordinateur en fonction d'un programme particulier et des valeurs obtenues par suite du pesage par les deux dispositifs de pesage (21) et (22).

5

10

15

20

25

30

35

40

45

50

55