

(51) International Patent Classification:
H01L 21/02 (2006.01)(21) International Application Number:
PCT/US2015/026687(22) International Filing Date:
20 April 2015 (20.04.2015)

(25) Filing Language: English


(26) Publication Language: English

(30) Priority Data:
61/994,584 16 May 2014 (16.05.2014) US(71) Applicant: APPLIED MATERIALS, INC. [US/US];
3050 Bowers Avenue, Santa Clara, California 95054 (US).(72) Inventors: SHAH, Kartik; 583 Kiholo Terrace,
Sunnyvale, California 94089 (US). PRASAD, Chaitanya
A.; #4, 4th Cross, LIC Colony, 3Rd Block, E., Jayanagar,
Bangalore 560011 (IN). BAUTISTA, Kevin J.; 1454
Clemence Ave., San Jose, California 95122 (US). TOBIN,
Jeffrey; 668 Leona Lane, Mountain View, California
94040 (US). KELKAR, Umesh M.; 957 Pomeroy Avenue,
Santa Clara, California 95051 (US). HAWRYLCHAK,
Lara; 7090 Church Street, Gilroy, California 95020 (US).(74) Agents: PATTERSON, B. Todd et al.; Patterson &
Sheridan, L.L.P., 24 Greenway Plaza, Suite 1600, Houston,
Texas 77046 (US).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SHOWERHEAD DESIGN



(57) Abstract: Embodiments described herein relate to a showerhead having a reflector plate with a gas injection insert for radially distributing gas. In one embodiment, a showerhead assembly includes a reflector plate and a gas injection insert. The reflector plate includes at least one gas injection port. The gas injection insert is disposed in the reflector plate, and includes a plurality of apertures. The gas injection insert also includes a baffle plate disposed in the gas injection insert, wherein the baffle plate also includes a plurality of apertures. A first plenum is formed between a first portion of the baffle plate and the reflector plate, and a second plenum is formed between a second portion of the baffle plate and the reflector plate. The plurality of apertures of the gas injection insert and the plurality of apertures of the baffle plate are not axially aligned.