increases.

[0006] In view of this, it is an object of the present invention to provide a coating removing method and a coating removing equipment that, in order to obtain a base film with which a recycled film can be stably formed from a used coated film even when the film is remelted, can efficiently remove a coating from a surface of a coated film including a coating containing a water-soluble resin on at least one side of a base film by dissolving the water-soluble resin with a very small amount of a solvent.

Solution to Problem

[0007] ~~A coating removing method according to the present invention to solve the object is~~According to a first aspect of the present invention, there is provided a method for removing a coating from a coated film including a coating containing a water-soluble resin on at least one side of a base film. The method includes: supplying a cleaning liquid in a form of droplets to a surface of the coating, and retaining the cleaning liquid in the form of droplets on the surface of the coating; and c removing the coating containing the cleaning liquid from the coated film.

The coating removing method according to the above aspect of the present invention ~~is preferably~~has the following ~~methods~~embodiments.

The cleaning liquid is supplied to the surface of the coating while being heated to 40°C or higher.

The coated film is heated to 40°C or higher.

The coating film contains a curable silicone resin.

The cleaning liquid is water.

A diameter of the droplets of the cleaning liquid is 1 mm or less.

[0008] ~~A coating removing equipment according to the present invention to solve the object is~~ According to a second aspect of the present invention, there is provided an equipment for removing a coating from a coated film including a coating containing a water-soluble resin on at

least one side of a base film. The equipment includes: a cleaning-liquid applying mechanism configured to dispense a cleaning liquid in a form of droplets toward a surface of the coating film such that the cleaning liquid is able to be retained in the form of droplets on the surface of the coating; and a removing mechanism configured to remove the coating film containing the cleaning liquid from the coated film in which the cleaning liquid has been supplied to the surface of the coating.

The coating film removing equipment according to the above aspect of the present invention ~~preferably~~ has the following ~~aspects~~embodiments.

The cleaning-liquid supplying mechanism includes a unit configured to heat the cleaning liquid.

The coating film removing equipment further includes a unit configured to heat the coated film.

Advantageous Effects of Invention

[0009] By the method for removing a coating film and the equipment for removing a coating film according to the above aspects of the present invention, the coating film can be efficiently removed from the coated film including the coating film containing the water-soluble resin on at least one side of the base film with a small amount of the cleaning liquid.

Brief Description of Drawings

[0010] FIG. 1 is a schematic diagram of a removing equipment 101 according to a first embodiment of the present invention.

FIG. 2 is a schematic diagram of a removing equipment 201 according to a second embodiment of the present invention.

FIG. 3 is a schematic diagram of a removing equipment 301 according to a third embodiment of the present invention.

FIG. 4 is a schematic diagram of a conventional