

SYSTEM AND METHOD FOR TREATMENT OF WASTEWATER VIA ENHANCED ELECTROFLOTATION

TECHNICAL FIELD

[0001] The present invention relates to wastewater treatment and, in particular, to the oxidation and removal of wastewater contaminants, including, suspended solids, organics, heavy metals and bacteria using mechanically-induced electroflotation.

BACKGROUND

[0002] There are a few conventional processes for removal of solids/suspended impurities in water. However, each of these processes has associated disadvantages as described below.

[0003] Dissolved air flotation (DAF) is a water treatment process that clarifies wastewater by the removal of suspended matter such as oils and greases or solids. The removal is achieved by dissolving air in wastewater under pressure using either an external compressed air supply or an air supply from a blower unit and then releasing the air at atmospheric pressure in a flotation tank basin. The released air forms micro-bubbles which adhere to the suspended matter in the wastewater causing the suspended matter to float to the surface of the water where it may then be removed by a mechanical skimming device. However, it is difficult to produce the most optimum fine bubble size (bubble flux) to effectively float the suspended matter without specialized, costly diffusers and high pressure air feeds. Also, since bubble diffusers mounted in the bottom of a DAF tank cannot provide 100% coverage of the tank's surface area, allowing portions of the wastewater to ultimately bypass the DAF flotation process without being treated. Furthermore, since the floating solids mass remains on the surface of the water, mechanical skimming devices or pumps are required to effectively remove the solids from the tank. While DAF is more mechanically intensive, it is not suitable for locations such as offshore drilling platforms where equipment maintenance is likely to be neglected.

[0004] Electroflotation (EF), which involves flotation by electrically generated bubbles, is another process for removal of floating ions or solid solids, suspended or dissolved in a liquid phase. EF requires a cathode (that may be made of non-oxidizing material) and an anode (that may be made of iron or aluminum). Electrode plates or packs may be connected to an electric power source, and positioned within a flotation tank under the water surface. During electrolysis, the electrode plates/packs generate small gas bubbles (e.g., O₂, H₂) which are then attached to the pollutants (e.g., suspended solids) in the water before they begin to float upward in a flotation tank where they can be more easily collected and removed. However, producing the correct bubble size requires certain electrical power control over the submerged electrode plates/packs. Traditional EF process suffers the drawback of requiring continuous maintenance due to the layer of iron or aluminum hydrates and oxides that forms on the surface of the electrodes, without separating from them, so that over time the electric current decreases and therefore so does the formation of hydrates. Another drawback is that the electrodes are subjected to uneven wear, with the need to replace them often before they are completely worn. Also, maintenance on the electrode plates/packs requires either draining of the flotation tank or removal of the electrodes from the water volume to service. Since the electrode plates/packs mounted in the bottom of the tank often do not produce a 100% coverage of the tank's water surface area, allowing portions of the wastewater to ultimately bypass the flotation process and exit the treatment unit untreated. Furthermore, since the floating solids mass remains on the surface of the water column, similar to the DAF process, various mechanical skimming devices or pumps are required to effectively remove the solids from the tank.

[0005] For these reasons, the wastewater treatment industry especially marine sewage treatment industry is in need of a technically and economically viable system for efficient solids separation, organics and bacteria removals.

SUMMARY OF THE INVENTION

[0006] In accordance with one or more embodiments, the invention relates to a system and method for treating wastewater. In an embodiment, the invention relates to a method for treating wastewater or marine wastewater.

[0007] According to an embodiment, a system for treating wastewater (or “treatment system”) is comprised of a main batch sewage treatment tank with level control system, a locally mounted electrical control panel, a highly efficient electrolytic cell(s), blower for hydrogen dilution, and an on-skid automatic polymer blending/mixing system. The treatment system further includes a dechlorination unit comprising a ship-loose sodium sulfite/bisulfite storage/dechlorination (neutralization) tank and a chemical injection pump. The dechlorination unit ensures that chlorine-free International Maritime Organization (IMO)-compliant effluent is discharged to the sea. The treatment capacities of the treatment system range from 4.85 to 49.95 cubic meters per day, while utilizing small installation floor space. In one aspect, the treatment system is used in marine and offshore installations requiring permanent or long-term operation for the treatment of marine sewage.

[0008] The treatment system is designed to operate in an automatic mode with very little operator intervention. Based on sewage treatment demand of the platform or vessel, the treatment system initializes sewage transfer and begins treatment processing. A manual operation mode is provided for troubleshooting and emergency pump out and/or flushing of the treatment system.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The invention will be described in further detail below and with reference to the attached drawings all of which describe or relate to apparatus, systems and methods of the present invention. In the figures, which are not intended to be drawn to scale, each similar component that is illustrated in various figures is represented by a like numeral. In the figures:

[0010] Figures 1A and 1B illustrate multiple views of an exemplary system for treating wastewater according to an embodiment.

[0011] Figure 2A illustrates an electrolytic cell according to an embodiment.

[0012] Figure 2B illustrates an electrolytic cell according to another embodiment.

[0013] Figures 3A and 3B illustrate multiple views of an exemplary polymer mixing system according to an embodiment.

[0014] Figure 4 illustrates a block diagram of an exemplary system for treating

wastewater according to an embodiment.

[0015] Figure 5 illustrates a block diagram of an exemplary system for dewatering the sludge generated from treating wastewater for landfill disposal according to an embodiment.

DETAILED DESCRIPTION OF THE INVENTION

[0016] Depending on the context, all references below to the "invention" may in some cases refer to certain specific embodiments only. In other cases, it will be recognized that references to the "invention" will refer to subject matter recited in one or more, but not necessarily all, of the claims.

[0017] In an embodiment, the present invention relates to a system **100** for treatment of wastewater or marine wastewater containing suspended solids and other impurities (e.g., organic matter, bacteria, etc.). The system **100** is a batch treatment system that utilizes electrolytic cell(s) to generate an efficient oxidizer/micro-bubbles and uses polymer as a flocculation agent to create a "floating layer" of suspended solids which is effectively removed from the system at the end of each treatment cycle.

[0018] As used herein, the term "wastewater" includes any water to be treated such as black water and gray water from offshore platforms and marine vessels or a stream of wastewater from industrial, agricultural and municipal/ residential sources, having solid pollutants of biodegradable material. Marine wastewater streams generally include black water, gray water and combinations thereof. The term "black water" refers to water contaminated with human waste that comprises coliform and other bacilli. The term "gray water" refers to used water absent human waste, such as water from galley, laundry, sinks and showers. Generally, marine wastewater is composed of both toxic and non-toxic organic and inorganic contaminants, micro and macro suspended solid contaminants comprising cellulose, sand, grit, human biomass, and emulsions and gases. The pollution potential of combined black water and gray water is indicated by several wastewater parameters, biochemical oxygen demand (BOD), chemical oxygen demand (COD), coliform bacteria, and suspended solids (SS) being the major ones. TSS may be organic in nature and can serve as safe havens for harmful bacteria and other microorganisms. The terms "wastewater", "sewage" and "marine wastewater" are used

interchangeably in this document.

[0019] In another embodiment, the invention relates to a method and/or treatment cycle for treating wastewater. The method involves electrolysis and an enhanced/mechanically-induced electroflotation stage for efficiently separating suspended solids and for clarifying the water. In a first step, an electrolytic cell(s) can be used to generate disinfectant (e.g., sodium hypochlorite) which helps to oxidize organic matter and create micro-bubbles (hydrogen/ oxygen). These bubbles are able to lift any suspended solid matter in a batch tank water volume. In a second step, a small amount of polymer can be mixed in-situ within a mixing spool of piping in the system. The process flow through the mixing spool ensures good dispersion of the blended polymer in the wastewater stream. Polymer added coupled with micro bubbles from the first step create an electroflotation condition to facilitate solid agglomeration and flotation at the liquid surface. The method further involves treating wet polymerized solids waste/sludge generated during the treatment process to obtain a centrate and a compacted sludge for landfill disposal. The centrate may be used to supplement seawater or reduce the volume of seawater used during a subsequent wastewater treatment cycle.

[0020] **FIG. 1A** and **FIG. 1B** illustrate multiple views of a specific, non-limiting, embodiment exemplifying a system **100** for treating wastewater. The system **100** includes a single batch tank **105** for receiving wastewater to be treated. The batch tank **105** is also designed to contain seawater that is to be mixed with the wastewater. In an exemplary embodiment, the batch tank **105** is made of carbon steel, coated in a corrosion-resistant acrylic polyurethane coating. The batch tank is configured in such a way that allows to withdraw sludge and clarified effluent from the base of the tank. In conventional tanks, as you draw clarified effluent out from the base, the remaining sludge may plug/clog other devices in the tank (for example, electrolytic cells) causing maintenance problems. As such, in conventional tanks, solid waste would have to be removed from the top which would require another unit operation to the process. This adds to the operation cost by requiring the addition of paddles, skimmers and other mechanical devices.

[0021] The system components, including, the batch tank **105**, the electrolytic cell **110**, a polymer mixing device or system **130**, etc. are conveniently mounted on a skid **125**. The skid **125** may comprise a compact steel base frame. Other system components

are described with reference to **FIG. 4**. Additional process equipment, such as pumps, pipes, sensors or valves may be employed throughout the system **100**. The system **100** is configured to operate in an automatic batch mode with minimal operator intervention. The system **100** can initialize sewage transfer and commence treatment based on sewage treatment demand of the marine vessel.

[0022] The batch tank **105** is in fluid communication with an electrolytic cell **110**. As used herein, the term “electrolytic cell” can encompass one, two or multiple electrolytic cells (for example, for use on larger marine vessels or treatment units). The electrolytic cell **110** is intentionally positioned outside the batch tank **105**. This reduces the components/parts contained within the batch tank **105**. This also minimizes corrosion/wear and tear and makes it more convenient to service the electrolytic cell **110**. (If the cell were to be placed in the batch tank, the tank would have to be completely drained before conducting any maintenance work). A defoamer injection pump **442** is provided to inject a small amount of a diluted defoamer into an oxidized wastewater mixture leaving the electrolytic cell **110**. Blower **120** can be configured to start when the electrolytic cell **110** is energized. A recirculation pump **140** is configured to recirculate an oxidized wastewater stream through the in-line mixing spool/piping **135**.

[0023] The system **100** includes an electrical control panel **150**. The control panel **150** is simple and easy to operate. The control panel **150** utilizes a switching power supply and smart relay controllers as the basis for safe and effective operation of the system **100**. All system components may be pre-wired to the control panel **150**.

[0024] **FIGS. 2A** and **2B** illustrate isometric views of two exemplary embodiments of the electrolytic cell **110A**, **110B**. The electrolytic cell can have a substantially flat/book-shaped housing **110A** or a substantially cylindrical housing **110B**. Irrespective of the housing geometry (**110A**, **110B**), the electrolytic cell **110** is configured to function as a primary component for killing bacteria/pathogens in the wastewater by generating sodium hypochlorite and other mix oxidants from the seawater. The electrolytic cell **110** is equipped with one or more pairs of opposing electrodes (not shown) and means, for example, a DC power supply, for applying electrical current between the electrodes (not shown). The electrical polarity of the electrodes in the electrolytic cell **110** can be periodically (i.e., once every 24 hours when the treatment

system is operated continuously) reversed to minimize maintenance. This action allows the self-cleaning of the electrodes to remove hardness (calcium and magnesium) deposits. The treatment system **100** does not use electrolytic cell(s) that contain sacrificial electrodes which are typically subjected to uneven wear, with the need to replace them often before they are completely worn.

[0025] **FIGS. 3A and 3B** illustrate exemplary views of a polymer mixing system **130**. A polymer mixing system **130** is provided to mix neat polymer with a premeasured volume of water, typically utility or service water. Either potable or non-potable water, with the exception of seawater, may be used.

[0026] Now referring to **FIG. 3A**, the polymer mixing system **130** includes a polymer mixing chamber/column **310**. The polymer mixing chamber/column **310** includes an automatic high shear polymer mixer **320** for blending the neat polymer and non-potable water, with the exception of seawater to produce a diluted polymer solution. Due to the highly viscous nature of most polymers, proper mixing is essential to allow the polymer to disperse into the process flow effectively without polymer agglomerations and “fish eyes”. (Fish eyes are globular or partly hydrated polymer caused by poor dispersion during the mixing process). In one aspect, the mixer **320** comprises a square hole high shear head. The polymer mixing system **130** is provided with a motor **330** and a junction box for electrical connection to the motor **330**. The motor **330** is operably connected to the mixer **320** via a shaft – typically, a clear piece of pipe. The J-box **340** provides electrical connection for the polymer mixer motor.

[0027] Now referring to **FIG. 3B**, the polymer mixing chamber/column **130** includes two switches, a high liquid level switch **350A** and a low liquid level switch **350B**. The switches **350A** and **350B** are set at different heights to ensure that an optimal and accurate amount of diluted polymer is added upstream of the in-line static mixing spool/piping **135** in the recirculated oxidized wastewater even when the system **100** is tilted or is in an inclined position, for example, a 22.5 degrees inclination.

[0028] Referring back to **FIGS. 1A and 1B**, the diluted polymer is sent to the quelling chamber **115** through addition at upstream of the in-line static mixing spool/piping **135** by a diluted polymer injection pump **155**.

[0029] An exemplary method for treating wastewater using the system **100** is

described with reference to **FIG. 4**. A new batch treatment cycle commences with a fill cycle wherein a predetermined volume of seawater **405** is sent to the tank **105** by opening an automatic seawater inlet valve **407**. The seawater is transferred to the tank **105** by an internal seawater sprayer **410**. The sprayer **410** may be configured along a top portion of the tank **105**. Seawater is a critical component of the treatment process since electrolytic oxidation/disinfection depends on it to generate a required amount of sodium hypochlorite for effectively removing organics and killing fecal coliform. The tank **105** is filled to a predefined tank level based on measurements received from a level sensor **409**. It is understood that more than one level sensors can be used to detect the level of liquid in the batch tank **105**. Once the predefined seawater level in the batch tank **105** is reached, the actuated seawater supply valve **407** is configured to automatically close/de-energize.

[0030] At the same time that the seawater stream is added to the batch tank **105**, a stream of the neat polymer is pumped from the neat polymer storage tank **430** into the polymer mixing chamber/column **310** by the neat polymer injection pump **145**. A pre-measured volume of potable or non-potable water but excluding seawater **435** may be piped into the polymer mixing chamber/column **310** by opening valve **437**. The neat polymer and potable or non-potable water but excluding seawater is blended very well by a high shear mixer (as shown in **Figure 3A**) in the polymer mixing chamber/column **310** at a preset flow rate to establish a useable diluted/blended polymer solution for flocculation or agglomeration of solids suspended in the wastewater.

[0031] Once the predefined seawater level is reached, the level sensor **409** can transmit a signal to a sewage transfer pump to transfer wastewater **415**. A flow controlling ball valve (not shown), or another mechanism known in the art, may be set on a sewage transfer pump to ensure a desired or optimal flow rate into the tank **105**. Wastewater is filled in the batch tank **105** to a predefined level. When the predefined level is reached, the level sensor **409** can transmit a signal to terminate the wastewater transfer. The desired or optimal flow rates of the wastewater and seawater may be dependent on the treatment capacity of the system **100**.

[0032] A liquid level gauge/liquid level sight glass **420** may be connected to one side of the batch tank **105**. The level gauge **420** comprises a clear tube. The level gauge

420 provides a visual indication of an actual level of liquid in the batch tank **105** when the liquid level in the batch tank **105** changes. This provides a convenient mechanism for an operator to monitor and determine actual liquid levels in the batch tank **105**.

[0033] Macerator/grinder pump **425** is then energized. Valve **422** is opened and a stream of wastewater and seawater mixture from the bottom of the batch tank **105** is routed through the macerator **425**. The macerator **425** is configured to effectively grind or macerate solids found in the wastewater stream to a smaller particle size to provide numerous high surface areas to enhance treatment and to help the waste mixture to pass through the charged surfaces of the electrolytic cell **110** without fear of plugging/blinding the cell.

[0034] Diverter valve **427** is activated or energized to allow passage of the macerated wastewater mixture to the electrolytic cell **110**. The valve **427** may be a seal flush solenoid valve. The electrolytic cell **110** is energized and the macerated wastewater mixture is effectively electrolyzed between opposing electrodes to form mixed oxidants. The oxidants primarily include sodium hypochlorite. Sodium hypochlorite can effectively oxidize the wastewater mixture. Sodium hypochlorite removes a significant amount of organics and destroys fecal coliform. When in operation, the electrolytic cell **110** can generate fine gas bubbles for support of the particulates at the water surface interface level. Recirculation of the wastewater mixture can be continued for a predetermined time period. For example, the waste slurry can be recirculated through the electrolytic cell **110** for about 5 to 20 minutes. Oxidized/electrolyzed mixture is piped from the electrolytic cell to a quelling chamber **115** that is in fluid communication with the batch tank **105**. Blower **120** can be configured to start when the electrolytic cell **110** is energized. A regenerative blower **120** is used to force ambient air into the vent line.

[0035] A defoamer storage tank **440** is provided to store one or more diluted defoaming or antifoaming agents. In one aspect, the defoamer is an organic defoamer. The defoamer may be derived from naturally occurring tall oil fatty acids (TOFA) and polyols to form a polyol diester. During the oxidation/electrolysis cycle, a defoamer injection pump **442** is energized to inject a small amount of the diluted defoamer from the defoamer storage tank **440** into the oxidized wastewater mixture leaving the electrolytic cell **110**. The defoamer is used to manage any excessive foam buildup that occurs from

any gas entrained within the suspended solids and minimize foaming in the oxidized stream exiting the electrolytic cell **110**. Also, normally, smaller bubbles coalesce into larger bubbles as they often roll across the cathode surface of the electrodes in the electrolytic cell **110**. The inventors have discovered that the introduction of the defoamer discourages this coalescing action.

[0036] During electrolysis, small bubbles of hydrogen, oxygen and other residual gases are produced as by-products. These gases are entrained in the oxidized stream. Upon exiting the electrolytic cell **110**, the process/oxidized stream mixed with sodium hypochlorite and gases is routed to a quelling chamber **115**. The quelling chamber **115** is mounted over the batch tank **105**. As the process stream mixed with sodium hypochlorite and gases enters the quelling chamber **115**, the entrained gases produced during the electrolysis reaction, are diluted with ambient air to less than 25% of the lower explosive level or LEL of hydrogen in air. The diluted gases are positively vented out of the quelling chamber **115** to a safe location through a vent line **445**. This ensures that at least the larger process gas bubbles are exhausted to the atmosphere in a safe manner. Thus, the remaining process stream is substantially degasified with the exception of entrained micro/small gas bubbles.

[0037] The quelling chamber **115** further includes a distribution coalescing pack **450**. The coalescing pack comprises a plurality of integral flow diffuser or diverter plates contained within a box/container. The oxidized stream containing the micro bubbles is directed over the coalescing pack **450**. The stream is dispersed through the plates **450** from where it rains down/disperses onto the surface of water in the batch tank **105** as fine droplets instead of a continual stream or flow. The coalescing pack **450** increases the contact surface area of the stream to disperse it and remove its flow energy.

[0038] The bottom of the quelling chamber **115**, which contains the plates **450**, opens into the batch tank **105**. The quelling chamber **115** slows down the flow of the stream and ensures that any solid particles in the stream do not break apart. Sensor **409** controls fill volume and ensures that a predetermined air gap is maintained between the base of the coalescing pack **450** and the surface of the water in the batch tank **105**. This predetermined air gap is preset, for example, to about 2 inches to 8 inches, and preferably

between 3-6 inches. This preset gap ensures effective solids separation in the batch tank **105**.

[0039] Neat/concentrated polymer may be stored in a neat polymer storage tank/container **430**. The neat polymer storage tank **430** may also be mounted on a skid (such as, **125** shown in Figures 1A and 1B). Alternately, the polymer may be drawn from a stock container or pail (not shown). The polymer is a flocculant/dewatering polymer that promotes aggregation or agglomeration of solids suspended in wastewater. The polymer can be a cationic polymer. In one aspect, the cationic polymer is a cationic polyacrylamide. For example, the polymer is a copolymer of acrylamide and a quaternized cationic monomer (or a polyacrylamide inverse emulsion) having a high molecular weight. The cationic polymer is a water soluble flocculating agent that is effective over a wide pH range (4.0 – 9.0).

[0040] As described earlier, the polymer mixing chamber/column **310** includes two switches **350A** and **350B** for detecting a first or a high level of the polymer solution and second or a low level of the polymer solution. It is critical to monitor the polymer levels in the polymer mixing chamber/column **310** in order to meet IMO discharge standards. Two switches are essential to ensure that a right amount of polymer blend/mix is added to the batch tank **105**. Through experiments, the inventors discovered that when the treatment system was in an inclined position, having only a single switch was not sufficient to produce a desired amount of polymer mix in the batch solution. Therefore, the polymer mixing chamber/column **310** was configured with two switches as a safety feature to give a better control over the treatment process.

[0041] The recirculation pump **140** is energized and it starts recirculating the oxidized wastewater stream through the in-line mixing spool/piping **135** back to the quelling chamber **115**. The diluted polymer injection pump **155** is also energized. This blended polymer solution is then added is injected upstream of the in-line mixing spool/piping **135** by diluted polymer injection pump **155**. Similar to the substantially degasified process stream, the polymer solution is allowed to rain down the plates **450** into the batch tank **105**. After the oxidized wastewater stream recirculation and diluted polymer injection cycle is complete, a short, quiet residence time (for example, about 5-15 minutes, and preferably, around 10 minutes) is observed in the batch tank. The quiet

residence time facilitates the concentration of solids in the oxidized stream as a floating mass layer on the surface of the batch tank **105** liquid volume and separation of clear effluent from the floating layer.

[0042] The plates **450** located in the quelling chamber **115** are configured so that oxidized wastewater stream containing diluted polymer is dispersed into a calming shower onto the liquid surface interface of the tank's **105** volume. Subsequently, a very buoyant suspended solids mass is formed at the water surface, where micro bubbles are attached onto the agglomerated masses. The agglomerated particles form a floating layer on the top surface of the water in the batch tank **150**. This phenomenon is referred as "electroflotation". Thus, the solid particles in the original wastewater stream are now suspended by gas bubbles on the surface of the water in the batch tank as a floating layer while below this floating layer is substantially clear treated effluent which can be discharged to the sea.

[0043] The polymer serves two functions. First, it attracts solid impurities suspended in the wastewater and neutralizes their surface charge. The charge neutralization is a key to the electroflotation process. Secondly, it acts as a flocculent to begin agglomeration of the solid impurities contained in the oxidized wastewater stream. The entrained micro bubbles from the electrolysis process are impacted at the water surface interface and promote floating of the agglomerated particles found in the wastewater stream. The density of the agglomerated particles is such that it stays above the surface of a substantially clarified effluent.

[0044] After the quite residence time, valve **459** is actuated by solenoid to facilitate the passage of the clarified effluent. A recirculation pump **140** is energized to withdraw a clarified effluent through valve **457** and send to sea or to any designated site. Prior to discharge overboard, a clarified effluent stream is neutralized by adding sulfate-based chemical. A neutralized treated stream **485** is now substantially free of any residual chlorine. As the clarified effluent is removed, the slick agglomerated sludge layer rides down the walls of the batch tank **105** and sticks to the sides of the tank. In one aspect, a portion of one or more sidewalls of the batch tank **105** slopes inward to facilitate the falling of the sludge to the bottom of the batch tank **105**. The solids trap **455** is configured in proximity to the bottom of the batch tank **105**. The solids trap **455** comprises a piping

fixture having a substantially “mushroom” shaped cap. The solids trap **455** is configured to ensure that there is no cross contamination of the agglomerated sludge with the clarified effluent during pump out or discharge. In other embodiments, the cap may be bell, convex or umbrella-shaped. In another aspect, the solids trap **455** may be a “P-trap” piping fixture.

[0045] The solids trap **455** is further configured to prevent the pumping out of the sludge with clarified supernatant/effluent. A “stop level” may be set at the top surface of the solids trap **455**. When the sensor **409** detects that the effluent level has reached the stop level, the recirculation pump **140** is deenergized. This action stops the draining of the clarified effluent from the batch tank **105** so that the agglomerated mass does not get discharged along with the clarified effluent. Thus, the solids trap **455** acts as a trap for the agglomerated mass (because of the consistency/density of the agglomeration).

[0046] A small volume of clarified effluent may remain in the batch tank **105**. The batch tank **105** further includes a wash down sprayer **460**. The wash down sprayer **460** is located within the batch tank **105** beneath seawater sprayer **410** and above a solids trap **455**. Sprayer **460** promotes an internal washing of any solid particles or debris along the inside walls of the tank **105** at the beginning of each fill cycle. The wash down sprayer **460** can be used to mix the solids remaining in the batch tank **105** with the residual clarified effluent to create a slurry. This “tank wash” step allows proper cleaning of sidewalls of the tank **105** and facilitates proper mixing of slurry for ease of withdrawal from the tank **105** during solids discharge cycle. The slurry includes about 0.8-2.5 wt. % solids. Valve **422** is repositioned (or energized) to withdraw slurry through the bottom of the tank. solids trap **455**. The macerator **425** is energized to recirculate slurry through valves **427** and **462** and back to the batch tank **105**. This step is called “Rinse Step” to prepare the remaining wet solids for discharge. After a short period of time, valve **462** is then repositioned to allow for discharge to solids dewatering/handling system or customer’s solids storage tank. The macerator pump **425** transfers the wet solids until a low shutoff level measurement is detected by a level sensor **409** in the batch tank **105**. Upon reaching the low shutoff level, the macerator pump **425** is de-energized. Discharge valve **462** is de-energized and reverts back to its “normal” position. This essentially completes one complete batch treatment cycle. The batch tank **105** is now empty again,

and seawater can begin to fill the batch tank for the next treatment cycle. The automatic batch operation cycle can continue unless the system **100** is physically taken out of the automatic mode of operation or unless the system encounters a fault or alarm.

[0047] Referring again the neutralizing process, in one aspect, a dechlorination unit **480** is provided. The dechlorination unit **480** includes a chemical injection pump or a metering pump **475**. The substantially clarified treated effluent leaving the batch tank **105** may be dechlorinated by addition of optimal amounts of one or more dechlorination chemicals, such as, sodium bisulfite, sodium sulfite, sodium thiosulfate or sulfur dioxide prior to its discharge overboard. A start signal may be sent to the dechlorination unit **480** to inject dechlorination chemical into the clarified effluent discharge stream. The dechlorinated effluent is pumped overboard until a “low level” switch point is detected by sensor **409** in the batch tank **105**. This de-energizes the recirculation pump **140** and the dechlorination signal is removed. The effluent discharge valve **459** is de-energized back to its “normal” position.

[0048] The chlorine content of the discharged effluent (< 0.5 mg/L) is configured to meet the requirements of Resolution MEPC.227(64) of the IMO for effluent release to the marine environment without further processing. The dechlorinated effluent is environmentally safe and substantially free of residual chlorine.

[0049] The dechlorinated effluent **485** may be gravity drained overboard through piping. For example, the system **100** may comprise a stainless steel centrifugal overboard pump (not shown) to discharge the dechlorinated effluent overboard. The discharged effluent comprise fecal coliform less than 100 cfu/100 ml, BOD₅ less than 17 mg/L, COD less than 84 mg/L, TSS less than 23 mg/L, pH between 6 and 8.5, and total residual chlorine less than 0.5 mg/L.

[0050] In one aspect, an online turbidity sensor/transmitter **470** monitors the turbidity/total suspended solids levels in the clear treated effluent prior to it being dechlorinated and discharged to overboard. The online turbidity sensor **470** can be positioned such that it can detect turbidity (in Nephelometric Turbidity Unit (NTU)) in the discharge effluent either prior to and/or after the dechlorination chemical is injected into it.

[0051] In one aspect, the discharged 0.8 to 2.5 weight% wet solids/sludge **465** may be collected in an off-skid sewage collection/equalization tank. The sewage collection/equalization tank (not shown) may be provided by a customer/user of the system **100**.

[0052] In another aspect, the discharged 0.8 to 2.5 weight% wet solids/sludge **465** from the batch tank **105** can be subjected to further treatment, such as, dewatering treatment. **FIG. 5** illustrates an exemplary block diagram for a system **500** for dewatering or compacting the sludge generated during the wastewater treatment process described earlier with reference to **FIG. 4**. Dewatering system **500** is a centrifuge-based sludge dewatering system. The dewatering system **500** is configured to effectively dewater the sludge, which contains 0.8-2.5 weight% wet solids, to a point where the dewatered sludge contains 10-13 weight% solids. The dewatered sludge can be classified as a “Class B” type sanitary waste product that may be disposed of in an approved Class B Municipal Solid Waste Landfill Facility, without the need for further treatment ashore at a municipal treatment location. The operation of this dewatering system **500** can be automated. The dewatering system **500** can communicate with the treatment system **100** via a centrifuge system control panel (not shown).

[0053] The dewatering system **500** is operated in an automatic mode. The dewatering system **500** is configured to transmit a signal, namely, a “centrifuge ready to receive” signal when it is ready to commence dewatering operations on a sludge discharge received from the treatment system **100**.

[0054] Referring now to **FIG. 4** and **FIG. 5**, when sludge from the treatment system **100** is ready to be sent to the dewatering system **500**, the macerator pump **425** sends a 0.8 to 2.5 weight% wet solids/sludge stream **465** to sludge collection tank **510** along with a signal, such as, a “sludge transfer” signal to centrifuge unit **530** until the batch tank **105** is empty. During the sludge dewatering process, the sludge collection tank **510** is used as a surge tank.

[0055] In the absence of the dewatering system **500**, the customer would have to deal with the issue of storing a large mass and volume of sludge onboard a marine vessel. For instance, a large volume of sludge (containing 0.8 to 2.5 wt.% solids) is generated after the first treatment cycle. The customer would need a tank with an enormous

capacity to store this volume of sludge waste depending on duration of storage. By dewatering the 0.8-2.5 wt% wet solids, it is compacted to about 10 to 13 wt.% concentrated solids. The centrate obtained from the dewatering process can be reused by recirculating it back to the batch tank thereby reducing the volume of seawater usage. Thus, the customer would only have to store the small volume of compacted sludge onboard the vessel. Valve **555** is an actuated ball valve that is opened to allow centrate flow **560** to be routed back to the batch tank **105** at the treatment unit.

[0056] After the centrate **560** is sent back to treatment system **100**, the sludge collection tank **510** volume is transferred to the recirculation tank **520** via gravity flow through on/off valve **516**. This empties the sludge collection tank **510** and it is then ready to receive a next waste batch of sludge/wet solids from the treatment system **100**.

[0057] The dewatering system **500** can then send a signal, such as, a “centrifuge ready to receive” signal to treatment system **100** in preparation for the next sludge transfer batch from treatment system **100**. The dewatering system **500** begins operation when recirculation tank **520** is full.

[0058] The recirculation pump **526** withdraws sludge from recirculation tank **520**. Pump **526** passes the sludge stream through centrifuge **530**. In the centrifuge **530**, centrifugal force, which is generated by high speed rotations, is used to separate the entrained solids from the fluid. The centrifuge **530** includes an internal centrifuge bowl for receiving the fluid (not shown). In one aspect, as described in U.S. Pat. Nos. 6,224,532, 6,461,286, 6,478,724, 6,932,757 and 7,044,904, the contents of which are incorporated by reference herein, centrifuge **530** can include a spindle configured to rotate about an axis, wherein the internal centrifuge bowl is attached to the spindle to rotate therewith; a drive shaft; and a scraper blade attached to the drive shaft to rotate therewith, wherein the scraper blade can selectively remove solids accumulated on an internal surface of the centrifuge bowl; and a clutch mechanism. As the sludge enters the spinning centrifuge, it forms an annulus next to the walls of the centrifuge bowl. Due to the centrifugal force, the dewatered denser solid material moves outwardly toward the walls of the centrifuge bowl while at the same time, the liquid overflows from the bowl and is gravity drained into recirculation tank **520**. The liquid is relatively devoid of solids. The 10 to 13 wt. % solids is retained on the walls of the centrifuge. This continues for a

preset time interval while the fluid is separated from the entrained solids of the stream. After the preset time period expires, the spinning centrifuge bowl slows to a stop and the dewatered solids are scraped from the centrifuge bowl by internal scrapers. As these solids are scraped/dislodged from the bowl, they are allowed to fall by gravity into the dewatered solids collection container **540**. The dewatered solids collection container **540** may be positioned beneath the centrifuge **530**.

[0059] During this complete operation, level detectors **514** and **524** can monitor the levels in the associated tanks **510** and **520**. Tanks **510** and **520** are provided with atmospheric tank vents **512** and **522**, respectively. Any remaining centrate water **550** in the recirculation tank **520** can be discharged through valves **528** and **545** from the dewatering system **500**.

[0060] In one aspect, the dewatering system can compact sludge from 0.8-2.5 wt% to 10-13 wt% solids, thus reducing the mass and volume of sludge requiring disposal. The customer then only has to worry about disposing the 10-13 wt% solids. The dewatering system **500** operates concurrently with the batch treatment system **100**.

[0061] In one aspect, the treatment of wastewater may be carried onboard a marine vessel. This onboard treatment is generally utilized at those locations where there is limited access to a municipal water treatment plant or equivalent facility. Examples of such locations are ships and off-shore drilling platforms.

[0062] The one or more embodiments of the system have a reduced footprint and by reducing the number of components and the complexity to separate solids and liquids in wastewater (automatic valves, number of electrolytic cells, routine maintenance steel support structure, power supply, control systems), the system is easier to operate. This also reduces material costs and manufacturing man-hour costs.

[0063] Type Approval Certification Tests

[0064] Type Approval Certification tests were performed on Applicant's treatment system under the supervision of Bureau Veritas (BV) notified body. The treatment system was operated under "Guidelines for Performance Tests for Sewage Treatment Plants with respect to Effluent Standards" adopted by the Marine Environmental Protection Committee (MEPC) of the International Maritime Organization

(IMO) in resolution MEPC 2(VI) in 3 December 1976; and modifications adopted at MEPC 159(55) in 13 October 2006 and MEPC 227(64) in 5 October 2012.

[0065] Raw Sewage Characteristics for Type Tests: The raw sewage quality during entire type test period met the requirements stipulated in Section 5.2 of MEPC.227(64) resolution. Table 1 lists geometric mean, minimum, and maximum values of TSS, BOD₅, COD and Turbidity for raw sewage (influent).

Table 1 – Raw Sewage Characteristics during Type Testing of Treatment System

Parameter	Unit	MEPC.227(64) Requirement for Land-based Testing	Geometric Mean	Minimum	Maximum
TSS	mg/L	500 (minimum)	796	497	1,303
BOD ₅	mg/L	Not specified	211	127	281
COD	mg/L	Not specified	1,041	852	1,436
Turbidity	NTU	Not specified	427	190	590
pH	-	Not specified	7.1	6.7	7.4
FC	CFU/100 mL	Not specified	>17,222	9,200	>20,000

Notes: TSS – Total Suspended Solids, BOD₅ – 5-day Biochemical Oxygen Demand, COD – Chemical Oxygen Demand, FC – Fecal Coliform, TRC – Total Residual Chlorine, TN – Total Nitrogen, and TP – Total Phosphorus. For Geometric calculations, FC values analyzed as >20,000 CFU/100 mL are considered as 20,000 CFU/100 mL.

[0066] Dechlor Effluent Characteristics of Type Tests: This stream represents the overboard effluent exiting the treatment system. Table 2 lists geometric mean, minimum, and maximum values of TSS, BOD₅, COD and Turbidity for dechlor effluent.

Table 2 – Dechlor Effluent Characteristics achieved by Treatment System

Parameter	Unit	Effluent Limit per IMO MEPC.227(64)	Revised Effluent Limits for OMNIPURE™ Series 64 Gen II STPs (Dilution Factor: 0.67)	Geometric Mean	Min.	Max.
TSS	mg/L	35 x Q _i /Q _e	23 (35 x 0.67)	14	9	35
BOD ₅	mg/L	25 x Q _i /Q _e	17 (25 x 0.67)	13	2	23
COD	mg/L	125 x Q _i /Q _e	84 (125 x 0.67)	48	40	60
FC	CFU/ 100mL	100	100	23	1	609
pH	unit	6 to 8.5	6 to 8.5	7.0	6.7	7.4
TRC	mg/L	<0.5	<0.5	0.06	0.00	0.49
TN	mg/L	20 (or 70% reduction)	20 (or 70% reduction)	NA	NA	NA
TP	mg/L	1 (or 70% reduction)	1 (or 70% reduction)	NA	NA	NA

Notes: TSS – Total Suspended Solids, BOD₅ – 5-day Biochemical Oxygen Demand, COD – Chemical Oxygen Demand, FC – Fecal Coliform, TRC – Total Residual Chlorine, TN – Total Nitrogen, TP – Total Phosphorus, NA – Not analyzed. For Geometric calculations, TRC values recorded as 0.0 mg/L are considered as 0.001 mg/L, while BOD₅ values recorded as <2.0 mg/L are considered as 2.0 mg/L.

[0067] Therefore, the present invention is well adapted to attain the ends and advantages mentioned as well as those that are inherent therein. The previous description is not intended to limit the invention, which may be used according to different aspects or embodiments without departing from the scopes thereof, and whose extent is univocally defined by the appended claims. The discussion of documents, acts, materials, devices, articles and the like is included in this specification solely for the purpose of providing a context for the present invention. It is not suggested or represented that any or all of these matters formed part of the prior art base or were common general knowledge in the field relevant to the present invention before the priority date of each claim of this application.

[0068] Furthermore, the particular illustrative embodiments disclosed above may be altered or modified and all such variations are considered within the scope and spirit of the present invention. While systems and methods are described in terms of “comprising,” “containing,” or “including” various devices/components or steps, it is understood that the systems and methods also can “consist essentially of” or “consist of” the various components and steps. Whenever a numerical range with a lower limit and an upper limit is disclosed, any number and any included range falling within the range is specifically disclosed. In particular, every range of values (of the form, “from about a to about b,” or, equivalently, “from approximately a to b”) disclosed herein is to be understood to set forth every number and range encompassed within the broader range of values. Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee. Moreover, the indefinite articles “a” or “an”, as used in the claims, are defined herein to mean one or more than one of the element that it introduces. If there is any conflict in the usages of a word or term in this specification and one or more patent(s) or other documents that may be incorporated herein by reference, the definitions that are consistent with this specification should be adopted.

CLAIMS

1. A method for treating wastewater comprising:

filling a batch tank with seawater until it reaches a first predetermined level;

transferring the wastewater to the batch tank until a seawater and wastewater mix in the batch tank reaches a second predetermined level, wherein the wastewater comprises suspended solid particles;

subjecting a stream of the seawater and wastewater mix to electrolysis within an electrolytic cell, wherein the electrolytic cell is mounted outside the batch tank;

piping the electrolyzed stream to a quelling chamber, wherein the quelling chamber is mounted above the batch tank, wherein the quelling chamber comprises a coalescing pack having integral flow diffuser plates for dispersing the polymer solution and the electrolyzed stream, and wherein the electrolyzed stream comprises entrained micro/fine gas bubbles generated during the electrolysis;

injecting a diluted defoamer solution via a chemical injection pump from a defoamer storage chamber at the exit of the electrolytic cell;

injecting a diluted polymer solution at upstream of an in-line mixer piping, wherein the polymer solution is piped into the quelling chamber substantially concurrently with the electrolyzed stream;

enabling dispersion of the polymer solution and the electrolyzed stream as a fine shower over residual seawater and wastewater in the batch tank, wherein the polymer solution facilitates flocculation of the suspended solid particles;

creating a distinct buoyant layer of the flocculated solid particles attached with the micro bubbles;

separating a substantially clarified effluent from the flocculated layer;

spraying the batch tank with a stream of the clarified effluent to create a slurry with residual solid particles;

dewatering the slurry to compact the residual solids and generate a centrate; and

recirculating the centrate to the batch tank for use during a subsequent treatment cycle.

2. The method according to Claim 1, further comprising macerating the suspended solid particles prior to the electrolysis step.

3. The method according to Claim 1, wherein the defoamer solution manages excess foam buildup in the electrolyzed stream before it is piped to the quelling chamber.
4. The method according to Claim 1, further comprising blending, in an in-situ polymer mixing system, a cationic polymer with a predetermined volume of service water to produce the diluted polymer solution, wherein the polymer mixing system comprises a polymer mixing chamber/column.
5. The method according to Claim 4, wherein concurrently with the transferring of the seawater to the batch tank, pumping the cationic polymer into the polymer mixing chamber/column for the blending step.
6. The method according to Claim 4, further comprising providing the polymer mixing chamber/column with a first/upper switch and a second/lower switch to detect polymer solution levels in the polymer mixing chamber/column and thereby ensure an optimal amount of the polymer solution is added to the batch tank.
7. The method according to Claim 1, further comprising facilitating a settling time cycle to enable the separation of the substantially clarified effluent from the flocculated layer.
8. The method according to Claim 1, further comprising discharging the clarified effluent from the batch tank.
9. The method according to Claim 8, wherein the discharging of the clarified effluent is terminated when a third predetermined level is reached.
11. The method according to Claim 8, further comprising neutralizing residual chlorine in the clarified effluent with one or more chemicals prior to the discharge step.
12. The method according to Claim 11, further comprising measuring turbidity of the clarified effluent prior to and/or after the neutralization step.
13. The method according to Claim 8, further comprising substantially trapping the flocculated layer in the batch tank using a device such that it is prevented from being discharged with the clarified effluent.
14. The method according to Claim 13, further comprising pumping the flocculated layer from the batch tank into a sludge tank until a shutoff level is detected in the batch tank, wherein the shutoff level corresponds to a substantially empty batch tank.
15. The method according to Claim 14, further comprising resuming filling of the batch tank with seawater to commence a subsequent cycle for treating the wastewater.

18. The method according to Claim 1, wherein the centrate is added back to the batch tank prior to the addition of seawater during the subsequent treatment cycle, and wherein the centrate supplements the seawater.
19. A system for treating wastewater comprising:
- a batch tank for receiving wastewater and seawater, wherein the wastewater comprises suspended solid particles;
 - an electrolytic cell in operable communication with the batch water tank, wherein the electrolytic cell is mounted outside the batch tank, wherein the electrolytic cell is configured to electrolyze a stream of the seawater and wastewater mix, and wherein the electrolyzed stream comprises entrained micro/fine gas bubbles;
 - a chemical injection pump for injecting a diluted defoamer solution into the electrolyzed stream at an exit of the electrolytic cell,
 - a quelling chamber, wherein the quelling chamber is mounted above the batch tank and is in fluidic communication with the batch tank; and
 - an in-situ polymer mixing system, wherein the polymer mixing system comprises a polymer mixing chamber/column, wherein the polymer mixing chamber/column has a first/upper switch and a second/lower switch to detect polymer solution levels in the polymer mixing chamber/column,
 - wherein the batch tank comprises one or more sensors, wherein the one or more sensors are configured for detecting:
 - a first predetermined level, wherein the first predetermined level corresponds to a predetermined seawater fill level in the batch tank;
 - a second predetermined level, wherein the second predetermined level corresponds to a predetermined wastewater fill level in the batch tank;
 - wherein the quelling chamber comprises a coalescing pack having integral flow diffuser plates.
20. The system according to Claim 19, wherein the system is skid-mounted.
21. The system according to Claim 19, further comprising a defoamer injector, wherein the defoamer injector is located outside the batch tank and in proximity to the electrolytic cell.

22. The system according to Claim 19, further comprising a dechlorination injector for neutralizing the clarified effluent, wherein the dechlorination injector is located in proximity to a port for discharging the clarified effluent.

23. The system according to Claim 19, further comprising a dewatering system, wherein the dewatering system comprises a centrifuge for receiving the flocculated solid particles in a wet slurry form.

24. The system according to Claim 23, wherein the dewatering system further comprises piping for circulating a centrate generated from centrifugation/dewatering of the flocculated solid particles/wet slurry to the batch tank.