

Description

The present invention relates to control of a peripheral data storage subsystem, particularly to allocation and reallocation of allocatable segments of a random-access data buffer in such a storage subsystem.

Data buffers having allocatable data storage segments have been employed for enhancing the data transfer characteristics of a peripheral data storage system, including those employing magnetic tape recorders. U.S. patents 4423480, 4403286 and 4428064 illustrate such a system and are hereby incorporated in this specification. Patent 4,403,286, for example, indicates that total peripheral system performance can be enhanced by adjusting the peripheral system operation for balancing the workloads between various data buffers in the peripheral system. The performance, i.e., short access time, of the peripheral data storage system can be further enhanced by managing the operation of the data buffer in diverse ways.

For example, the Casey, et al article "Replacement Algorithms for Storage Management in Relational Data Bases" IEEE COMPUTER JOURNAL, November 1976, pp. 306-314 teaches that relations in a data base are variably sized. Each defined relation can have a plurality of allocatable memory units or segments. Each relation has but one entry in a replacement control, which includes a least-recently used (LRU) linked list. This reference shows grouping allocatable segments as a single unit on an LRU linked list.

The U. S. Patent 4,099,235, Hoschler, shows a telephone switching system having a plurality of control computers, which balance their loading based upon a "current measured utilization ratio". This ratio is a quotient of call waiting time divided by computer free or available time. Upon reaching predetermined thresholds, incoming calls are assigned to various control Computers (task reassignment, or reallocation). This patent therefore teaches that workloading is a factor in determining reconfiguration, or task reassignment. U. S. Patent 4,008,460 is an example of timestamping an LRU linked list for enabling early cast out, or deallocation of allocated data storage segments of a memory. Patent 3,898,624 shows varying the bandwidth of a data cache by varying the prefetching time so that more or less allocation in the cache depends on operator-inputted controls.

Patent 4,403,286 shows the use of counting channel command retries (CCRs) for the purpose of load balancing.

EP-A-0 059 829 discloses a data storage transfer system that uses a buffer for transfers between host processors and peripheral devices. Data transfers to/from devices are allocated to buffer seg-

ments and replacement of allocations is based on LRU-Scheme.

The present invention dynamically reallocates allocatable memory segments between a plurality of users on a normalized elapsed-time periodic basis. Reallocation, in one aspect of the invention, depends upon the activity of data transfers by a user and in another aspect, reallocation depends upon record size. In the context of the description, a user is a magnetic tape recorder and the data storage unit is the data buffer for all of the magnetic tape recorders.

In another aspect of the invention, the normalized elapsed time is indicated by the total number of accesses to all of the magnetic tape recorders, or users, in a peripheral system. In other words, elapsed time is normalized to total system activity. This time normalization enables dynamic reallocation in a more frequent basis in a busy tape system, which normally means higher performance; while in a slower tape system, the dynamic reallocation employs greater actual elapsed time. Normalized elapsed time is measured in two ways. First is an intensity measurement indicated by the number of channel command retries (CCRs), or processing delays incurred because of data storage unit (buffer) status. For example, when an allocated data storage segment is to receive data for storage, and it is full, then a channel command retry is sent to the requesting host; on the other hand, in a read operation, where data is transferred from the data buffer to a connected host processor, a time delay occurs when the allocated segment is empty. The more time delays, the greater the intensity of data transfer activity. The second indicator relates to whether any access at all has been made to the data buffer by a connected host processor during the normalized elapsed time period. This indicates whether there is any activity at all irrespective of intensity.

The foregoing and other objects, features, and advantages of the invention will be apparent from the following more particular description of preferred embodiments of the invention, as illustrated in the accompanying drawings.

Figure 1 is a simplified block diagram of a data processing system employing the present invention.

Figure 2 is a simplified flowchart illustrating operations of the Figure 1 illustrated system in determining whether the activity status of the peripheral system should be checked for possible data segment reallocation.

Figures 3 and 4 respectively show data structures used in practicing the present invention in a microprocessor controlled Figure 1 illustrated system.

Figure 5 is a flowchart showing allocation procedures for establishing a control input to the dynamic allocation operations of the Figure 1 illustrated system.

Figures 6 and 7 are flowcharts illustrating the operation of the Figure 1 illustrated system during activity checking and dynamic reallocation.

Referring now more particularly to the drawing, like numerals indicate like parts and structural features in the various diagrams. The invention is illustrated as being incorporated into storage system 10 having a pair of control units 11, also denominated as CU-0 and CU-1. Storage system 10 is connectable to a plurality of hosts 12 for receiving, storing and supplying data signals from and to the respective hosts under control of host operations, as is practiced in the data processing art. Storage system 10 stores data signals on behalf of the host in a plurality of data storage devices 13. Such data storage devices 13 include, without limitation, magnetic tape or optically sensed tape recorders, magnetic or optical disk recorders, magnetic or optical card recorders and unit record equipment. Communications between hosts 12 and storage system 10 are via a plurality of input/output channels 14, constructed generally in accordance with the input/output channels set forth in Amdahl, et al., U. S. Patent No. 3,400,371. For enhancing system 10 operations, each control unit 11 includes a data buffer 15, preferably constructed of semiconductive random-access memory elements. Buffers 15 are the prime conduits for data transfer between hosts 12 and devices 13; the arrangement is such that a host 12 can communicate with a given device 13 through either buffer 15 and via either control unit 11. Communications from input/output channels 14 to a buffer 15 are via channel adapter CXX 80 and bus 81 in CU-0 and via bus 96 to CU-1. It is understood that CU-1 is constructed identically to CU-0 with complementary connections (not shown) in CU-1. For example, bus 97 connects a channel adapter (not shown) of CU-1 to buffer 15 of CU-0 via channel data transfer circuits 16. Circuits 16 are known automatic data transfer circuits commonly used in the data processing art.

Since a plurality of devices 13 communicate through a single buffer 15 to a plurality of hosts 12, buffer 15 is dynamically managed as a plurality of allocatable data storage segments indicated by dashed lines 17. That is, when a given device 13 is communicating with a host 12, the given device 13 is assigned or allocated a data storage segment of buffer 15 for handling the data transfers. Devices 13 that are not currently transferring data need not be assigned such data storage segments; this freedom allows buffer 15 to be relatively small, such as 256,000 bytes of data storage. Buffer 15 allocations

to devices 13 are normally maintained between successive data transfers in each independent series of data transfers or chains of commands.

Communications between buffer 15 and devices 13 are conducted through an automatic data transfer circuit DX 83. Connections from DX 83 to devices 13 are via a pair of cables 90 and 94, as detailed in U. S. Patents 4,403,286 and 4,423,480. In a similar manner, CU-1 is connected to the devices 13 by another pair of cables 93, 95.

The control of storage system 10 resides jointly in the two control units 11. The showing in Figure 1 is simplified in that those control circuits not pertinent to an understanding of the present invention are not detailed. Each control unit 11 includes a control 33, preferably including a programmed digital computer or microprocessor as shown in patents 4403286 and 4423480. Miscellaneous controls are indicated by numeral 34. Since the control of storage system 10 is shared between CU-0 and CU-1, interconnecting bus 109 provides communications between the two control units 11 for exchanging control data necessary to the logical control of storage system 10. Miscellaneous control 34 also controls automatic data transfer circuits CX 16 and DX 83 and the operations of buffer 15. Connections 81, 35 and 36 represent these controls.

A first portion of the invention relates to separate measurements of data transfer activity in CU-0 and CU-1 to ensure that the work is efficiently performed by the two control units on a dynamic basis. Since the buffers 15 of CU-0 and CU-1 are the prime conduits for data transfers between hosts 12 and devices 13, the status of the two buffers 15 at the time of a request for data is an indication of the current ability of the respective control units 11 for efficiently satisfying hosts 12 requests. For example, whenever a host 12 requests data from storage system 10 and that data is not in the buffer 15, then that event is used as an indication of control unit work load and, hence, data transfer efficiency. In a similar manner, if a host 12 desires to record data on a device 13 and the buffer 15 data storage segment allocated to the device is full of data, that status is another indication of control unit 11 work load. Also, when a buffer 15 segment is not allocated to a device 13 when a host 12 requests the use of that device 13 which requires buffer operation is an indication of control unit work load. Such indications are determined by control 34 while responding to a host 12 supplied input/output channel commands determining that the command cannot be immediately performed. Control 34 then indicates the delay by supplying a channel command retry (CCR) signal over line 40 through CXX 80 to the requesting host 12. Such channel command retries are fully explained in R. L. Cormier, et

al., U. S. Pat. No. 3,688,274. According to this invention, each control unit 11 includes circuitry and controls for utilizing the CCR signals to maintain efficiency in each of the control units 11. The tally of CCR signals indicates intensity of operations for each of the devices 13 during each normalized elapsed time period.

For each allocated segment of a buffer 15, a separate tally "CCRK" is provided for the number of CCRs. The tallies, CCRK, are held in counter registers 41, 42. The CCR signal on line 40 also goes to respective counter registers 41, 42 for increasing the respective CCRK counts. Each CCR signal is associated with an addressed device 13 (the device to which the segment represented by registers 41, 42 is allocated); registers 41, 42 are addressed accordingly. In this manner, the activity intensity state for each of the allocated buffer segments is maintained in the separate CCR tallies. These separate tallies also indicate the relative responsiveness of the respective devices 13 and associated buffer 15 segments to hosts 12 requested operations.

All activities of the storage system 10 are based upon device 13 addresses. The combination of an allocated buffer 15 segment with a recorder or device 13 is termed a logical device, i.e., to hosts 12 the device 13 and allocated segment appear as a single unit. Each host 12 in its communications with storage system 10 always addresses a device 13; accordingly, the buffer 15 segments are not explicitly addressed by hosts 12 but are implicitly addressed by a device 13 address. Control 34 responds to the received input/output commands issued by hosts 12 as set forth in the incorporated documents. When a CCR is supplied to a host 12, as set forth above, control 34 supplies an address signal over bus 43 to select one of the registers 41, 42 representing the logical device being addressed and increments the count CCRK in the addressed counter register. To implement the invention in a preferred mode for measuring normalized elapsed time, each control unit 11 maintains a total device operations count in device operations counter 45. Each time a device 13 is accessed by a control unit 11, the counter 45 contents are incremented by unity. To check for expiration of a normalized elapsed time, each time counter 45 is incremented, the numerical contents therein after incrementing are compared by compare circuit 46 with a threshold or limit value stored in register 47. When the counter 45 contents equal or exceed the register 47 threshold, then data buffer 15 data transfer activity should be investigated.

The normalized elapsed time is generated by control 34 incrementing counter 45 by unity by supplying a signal over line 48 (in the programmed

embodiment, the equivalent program function is performed) each time an operation is started with a device 13. There is one counter 45 in each control unit 11. Register 47 stores the numerical limit value indicating the expiration of a normalized elapsed time. Compare circuit 46 compares the count value of counter 45 with limit value in register 47. Each time control 34 selects or activates a device 13 control 34 supplies a signal over line 49 for activating compare circuit 46. When compare circuit 46 detects that the numerical contents of counter 45 are less than the limit value in register 47, a signal travels over line 50 through OR circuit 51 to control 34 signifying that the normalized time period has not yet elapsed. When compare circuit 46 finds that the numerical contents of counter 45 are equal to, or greater than, the limit value of contents of register 47, an activity checking signal travels over line 54 for sampling AND circuit 55, as well as AND/NOT circuit 57. When there is a contention for the data storage segment of data buffer 15 to be used with the current data transfer, i.e., associated with the addressed device 13, then no activity checking is to ensue. Contend latch 56 is set, as later described, any time there is a contention for any of the buffer 15 data storage segments. AND circuit 55 responds to the contend latch 56 being set for passing a continue and no checking signal through OR circuit 51 to control 34. On the other hand, when contend latch 56 is not set (no buffer 15 contention), AND/NOT circuit 57 responds to the line 54 signal to reset the counter 45 for starting a new normalized time period. The AND/NOT circuit 57 output signal also goes to control 34 for initiating activity checking as later described and as illustrated in Figure 1 by reallocation control 65. Line 66 carries the AND/NOT circuit 57 output signal for actuating reallocation control 65.

Upon each activation, reallocation control 65 examines a buffer record table BRT 141, the buffer status table (BST) 137, and the logical device table (LDT) 133 for measuring the activity intensity for each of the logical devices during the just-expired, normalized elapsed time period.

Reallocation control 65 employs a plurality of registers for storing counts for creating an indication of the maximum intensity of the devices 13, and hence the data storage segments of data buffer 15. It also determines whether any of the devices 13 had activity at all and the data storage status in data buffer 15. FICOUNT 68 is set to unity whenever a data storage segment of buffer 15 is free or inactive during an activity check. Register FC 69 stores the maximum fault count (herein CCR count CCRK) for all of the data storage segments of data buffer 15. This maximum count is used for identifying which of the data storage segments had the most CCRs (greatest intensity of activity) dur-

ing the just-preceding normalized time period. Register SEG 70 stores the identification of the data storage segment of data buffer 15 which experienced the maximum count indicated in FC 69. Register S 71 identifies the data storage segment of the data buffer 15 currently being examined by reallocation control 65. Register DECCR 72 indicates whether a deallocate procedure should be invoked when the next channel command retry CCR is sent to a host 12. During the read mode, this bit indicates deallocation and purging data from data buffer 15 (as taught in patent 4,403,286) for enabling pairing buffer segments. Register ACT 262 contains a bit for each of the data storage segments of data buffer 15. The respective bits in ACT 262 are set by control 34 during the normalized time period whenever the respective data storage segments of data buffer 15 are accessed for any purpose at all. These bits indicate whether any activity has occurred at all for the respective data storage segments during the normalized time period. In the preferred embodiment, register ACT 262 is a portion of BST 137.

Turning now to Figure 2, the determination by control 34 whether a data buffer 15 activity check should occur is described. This figure corresponds to the flow of control by a microprocessor in control 34 in performing the functions represented by items 45 through 57 of Figure 1. The activity begins whenever a device 13 is selected such as a result of executing microprogram module termed "DM SDO". Numeral 543 represents the device 13 selection processes not pertinent to an understanding of the present invention. Assuming a device 13 is to be actuated for an ensuing data transfer operations, then control 34 at step 115 starts the device 13 operation. This step can follow known procedures for starting operations of peripheral devices. As soon as a device 13 has received a "start" signal from control 34, then control 34 at step 116 increments the counter 45 by unity. In step 117 control 34 actuates compare circuit 46 to compare the numerical contents of counter 45 with the numerical contents of register 47. If the count is not equal to, or greater than, the threshold represented by the numerical contents of register 47, then control 34 performs to other machine operations as indicated by numeral 503. Numeral 502 indicates that return to other operations may be effected by control 34 from other machine operations, not pertinent to an understanding of the present invention. In the event in step 117 the numerical contents of counter 45 are greater than, or equal to, the numerical contents of register 47, then in step 118 control 34 examines buffer contend latch 56. If there was contention for any of data buffers 15 storage segments, as later described, then the activity checking will not occur

because reallocation is inapt at this time. In other words, when there is a pending request for additional data storage space in buffer 15, dynamic reallocation should not go forward until that contention has been removed. In this regard, two alternatives can be used in practicing the present invention. The counter 45 may not be reset to zero whenever there is buffer contention. Accordingly, each time a device 13 is to be selected for an ensuing data transfer operation, the compare circuits 46 are activated as indicated at step 117. This occurs until the contention for data buffer 15 space is removed such that dynamic reallocation can be performed without interfering with the current buffer 15 data storage space contention. In an alternate embodiment, the activity checking for possible reallocation can be deferred until the end of the next ensuing normalized time period. In the preferred mode, the first described mode, the normalized elapsed time period is extended a small amount by any data buffer 15 contention.

Returning to Figure 2, if at step 118 buffer contention is detected, then other machine operations (not shown) are performed, as indicated at 503, by control 34. If there is no buffer contention at step 118, then control 34 in step 119 resets counter 45 to zero for starting a new normalized time period. Then control 34 proceeds to check the activity of data buffer 15 during the just-terminated, normalized time period and perform a dynamic buffer segment reallocation, as required.

The data structures for implementing the invention are described next. The logical devices are identified and controlled via LDT 133 (Fig. 4) while the data buffer 15 segments of the respective logical devices are controlled via PST 137 (Fig. 3). There is one entry register in BST 137 for each of the buffer 15 segments in the respective control units 11. Since all host processor 12 issued commands received by storage system 10 are based upon device 13 addresses and not upon buffer 15 segment addresses, LDT 133 provides an indirect address base for BST 137. In this regard, BSTP 253 in each of the registers of LDT 133 indicates the address of the corresponding entry in BST 137. Counter registers CCRK 41, 42 are in LDT 133. IRAH 225 is a bit indicating inhibit read ahead; that is, the storage system 10 will not transfer data from a device 13 to data buffer 15 without a command received by a host 12. DECCR 254 (came as DECCR 72) is a hit signifying to control unit 11 that when a CCR is sent for the addressed device 13 represented by the register in LDT 133, the corresponding data storage segment of data buffer 15 is to be deallocated. This bit is useful when dynamic reallocation involves a data storage segment storing data read from a device 13. Other LDT 133 fields, not pertinent to the present invention, relat-

ing to logical devices consisting of a device 13 and an allocated buffer 15 segment are indicated by ellipsis 256.

BST 137 (Fig. 3) relating to buffer 15 segment operations has a plurality of fields in each of its registers for the respective buffer 15 segments. DADDR 260 stores the address of a device 13 to which the data storage segment is allocated. This allocation is indicated by A bit 263 being set to unity. If the data storage segment is not allocated, then A bit 263 is zero. The contents of DADDR 260 are then ignored. Field LRU 261 relates to the LRU linked list used for managing data buffer 15. When the represented data storage segment is allocated with another data storage segment to one device 13, the corresponding LRU 261 entries are nulled; the other data storage segment LRU 251 entry represents both of the data storage segments for allocation and replacement control purposes. ACT bit 262 indicates that the represented data storage segment was accessed during the current normalized time period as indicated by selection of its corresponding device 13. E field 264 indicates that the buffer 15 segment currently is engaged; that is, a data processing operation is currently being performed involving the buffer 15 segment represented by the BST 137 entry. F field 265 indicates that the segment has been scheduled for freeing, i.e., deallocation. RANGE 268 indicates relative size of data records in blocks currently being transferred, i.e., small, medium, large or extra large. D (direction) field 267 indicates forward or backward magnetic tape operations. P bit 270, when set, indicates that the segment is paired with another segment. Ellipsis 269 indicates that, in a constructed embodiment, other fields not necessary for describing the present invention may be included in a typical BST 137. By convention, only even numbered data storage segments (0,2,4,...) of a pair of data storage segments will be on the LRU linked list while the odd numbered data storage segments (1,3,5,...), when paired, are omitted from the LRU linked list.

Setting contend bit 56 is achieved during allocation processing, as shown in Figure 5. Any requests for a data transfer received from a host processor 12 wherein no current allocation exists (indicated LDT 133 by its BSTP 253 equalling zero) causes the machine operations illustrated in Figure 5 to be performed. Activation of control 34 to perform the Figure 5 illustrated machine operations occurs at 274. Firstly, control 34 examines a pending allocation table (PAT 134) which identifies the addresses of all devices 13 requiring allocation of a data storage segment of data buffer 15. Pointers within PAT 134 indicate the beginning and end of the list of devices 13 using known table construction techniques. Each entry of PAT 134 includes

paired bit P 135 for indicating whether one or two data storage segments are to be allocated. When P=0, one data storage segment is allocated, when P=1 two data storage segments are allocated. The beginning of the allocation list device 13 addresses is indicated by the character "I" and the bottom of the list is indicated by the character "O".

At step 280, control 34 determines whether the pending allocation table (PAT) 134 is empty; if table pointers in control 34 (not shown) to the first entry and table pointers (not shown) to the last entry in PAT 134 are equal, then PAT 134 is empty. With PAT 134 empty, control 34 proceeds at 288 to other machine operations. On the other hand, if PAT 134 is not empty (an allocation of a data storage segment is pending), then at 281 control 34 checks the data contents of BSTP field 253 in LDT 133 for the addressed device 13. If that BSTP 253 is not zero, the logical device address has both a pending allocation and deallocation. Control 34 then proceeds to other machine operations via return point 288. If the examined BSTP 253 of LDT 133 is zero, then allocation of a data buffer 15 segment is appropriate. At 282 control 34 examines the P bit 135 for the pending allocation request. If P=0, then a single segment of data buffer 15 is to be allocated to the addressed device 13 for constituting a logical device. For a single segment to be allocated, control 34 at 283 activates logic module BM ASE (not shown) which allocates a free one of the data buffer 15 data storage segments using known allocation methods. A "free list" of free data storage segments is kept in the usual manner. Upon completion of an attempt to allocate a single segment in step 283, control 34 at step 284 checks the return code (RC) from logic module BM ASE. When RC=0, a data buffer 15 segment was successfully allocated to the addressed device 13. Then, in step 285, the output pointer O of PAT 134 is incremented by unity. At step 286, following step 285, control 34 alters the BST 137 corresponding entry to the just-allocated buffer segment by setting its bit A 263 and E bit 264 to unity for indicating that the indicated segment is allocated and engaged and resets P bit 270 to indicate allocation of a single data storage segment. Control 34 also sets DADDR 260 to the address of the addressed device 13. Control 34 then returns to the activating logic module (not shown) at 288 for performing other machine operations.

Returning to step 284, when the return code (RC) is not equal to zero, control 34 knows that the attempted allocation was unsuccessful. This means that there is contention for data storage segments of data buffer 15. Accordingly, at step 287 contend bit or latch 56 (Fig. 1) is set to unity. Then, control 34 proceeds to other machine activities via point

288.

When control 34 at step 282 finds the paired bit P 135 equals unity, then two data storage segments are allocated to the addressed device 13. This paired allocation can be initiated by several means, one of which is in accordance with the present invention during dynamic reallocation. The identification of the pairing bit will become apparent from Figures 6 and 7. When a pair of data storage segments are to be allocated, control 34 at 289 activates a logic module BM APR (not shown) which using known techniques allocate two of the data storage segments to the address device 13. In the constructed embodiment, an even numbered data storage segment is the lower numbered segment in each pair of data storage segments. As indicated with respect to BST 137 of Figure 3, when more than once data storage segment is allocated to a given device 13, only the even numbered data storage segment has an entry in LRU linked list 261. By convention, in the preferred embodiment, the segments of data buffer 15 are enumerated zero through N. The even numbered segments are always on the LRU list 261, while the odd numbered segments are on the LRU list only when they are singly allocated to an addressed device 13. Grouping of allocation segments with one of the allocation segments only being on an LRU replacement control list, such as list 261, is known and not described for that reason. Upon completion of attempting to allocate a buffer pair in step 289, control 34 proceeds to step 284 as previously described. With respect to step 286, PST 137 is amended in accordance with the paired allocation by setting both the A bit 263 and E bit 264 of both data storage segments to unity and the P bits 270 to unity for both data storage segments.

Figure 6 illustrates the machine operations of controls 65, which are preferably microprocessor executed and controlled, for examining the activity of data buffer 15 as to intensity of activity for (devices 13) a just-terminated, normalized elapsed time period. Controls 65 at step 290 initializes its registers of Figure 1 for performing the logical device activity examination. Initialization consists of setting registers S 71, FC 69, SEG 70 and FICOUNT 68 to zero (or other null value). Examination of the activity of all data storage segments of data buffer 15 is achieved within iterative loop 291 which serially examines the CCR-indicated activities of each of the data storage segments beginning with the segment designated by numeral zero and proceeding arithmetically to segment number N. Because of pairing, the number of loop iterations can vary from N/2 through N. At step 292, controls 65 access BST 137 to determine whether the data storage segment identified in register S 71 is inactive or free. If bit F 265 equals, then that

examined data storage segment designated by the contents of register S 71 is free. If ACT 262 is zero, the segment has been inactive for the entire normalized elapsed time period. For a free or inactive segment, controls 65 at step 293 set FICOUNT bit 68 to unity for indicating that at the end of the normalized elapsed time period, at least one of the data storage segments of data buffer 15 was free or inactive. From step 293, control 34 proceeds to index the loop as will be described.

When controls 65 find that the data storage segment being examined is not free or not inactive, then at step 294 controls 65 determine whether the data storage segment being examined is a candidate for reallocation. First, controls 65 examines RANGE 268 of BST 137 (Fig. 3) to determine the size of data being transferred through the data storage segment being examined. RANGE 268 stores a general indication of the size of data records or blocks being transferred. Length detector 75 (Fig. 1) counts the number of data bytes in each block or record being transferred either through CX 16 or DX 83. Four ranges are set up: small, medium, large and extra large.

To obtain the range, control 34 at the end of transferring a record or block of data receives the byte count from length detector 75. Control 34 then compares the received byte count with three thresholds (one threshold between two of the four ranges), and indicates the range. The RANGE 268 of BST 137 is updated. This action may occur once in each series of block or record transfers or once in a single chain of I/O commands.

By arbitrary definition, only the large and extra large block-sized transfers are eligible for reallocation in a first-constructed embodiment of the invention. The reason for this determination is that when small and medium size data blocks are being transferred, the possibility of needing more than one data storage segment of data buffer 15 for accommodating the data transfers is highly remote; there is no need to pair the current data storage segment being used with any other data storage segment. Therefore, for small sized data blocks, the segment indicated in S 71 is not a candidate for reallocation. Also, certain error conditions may make the respective data storage segments unavailable for dynamic reallocation.

Assuming that the examined data storage segment is a candidate for dynamic reallocation, then controls 65 in step 295 compare the numerical contents of FC 69 with the numerical contents of the CCRK register 41, 42 for the identified data storage segment. When the current fault count in FC 69 is greater than, or equal to, the fault count in the respective CCRK register, then the numerical contents of FC 69 are not altered. On the other hand, when the numerical count contents of FC 69

are less than the respective CCRK register contents, then at step 296 the count contents of the respective CCRK register are transferred to FC 69 for storing the largest fault count found in the intensity examinations to the present data storage segment being examined. Also, the contents of SEC 70 are set equal to the identification of the data storage segment associated with the CCRK count just-loaded into FC 69.

Controls 65 from either step 295 or 296 then access ACT 262 in the respective register of BST 137 for resetting that hit to zero. This primes BST 137 for the ensuing normalized elapsed time period as indicating no activity has occurred for the respective data storage segment.

Controls 65 from either step 293 or 297 then index the loop 291. In step 298 control 34 compares the contents of S 71 with the number N of data storage segments existing in data buffer 15. If the just-examined data storage segment is the Nth data storage segment, this means the last data storage segment has been examined. Accordingly, control 34 exits the loop as indicated by following line 305. When the just-examined data storage segment is not the last data storage segment, then in step 299 controls 65 examine the contents of register S 71 for odd-even value. If the examined S value is odd, then controls 65 in step 301 increment S by unity. If the examined S value is even, then P bit 270 in the corresponding entry of BST 137 is examined to determine whether the even numbered data storage segment is paired with an odd numbered segment. If it is not paired, then the odd numbered segment has to be examined; the value S is incremented by unity in step 301. If P bit 270 is unity, then the odd numbered segment is not to be examined. Controls 65 then increment S by two in step 300 for omitting the examination of the next high odd numbered segment. Following step 300 or 301, steps 292 through 297 are repeated until all necessary segments have been examined for intensity of activity as indicated by the respective CCRK counts.

Upon completion of examination loop 291, controls 65 then determine whether dynamic reallocation should be initiated. Firstly, from line 305 at step 306, controls 65 examine the numerical content of registers FC 69 and FICOUNT 68. If the data contents of both registers are nonzero, then at least one CCR has been sent to a host 12 during the immediately preceding normalized elapsed time period, and at least one data storage segment is either free or inactive for permitting a possible dynamic reallocation. If either of the registers FC 69 or FICOUNT 68 are zero, then a dynamic reallocation should not be performed. Controls 65 then indicate to control 34 over line 67 (Fig. 1) to return from step 306 via point 503 (Fig. 6) to other ma-

chine activities not pertinent to the present invention.

When dynamic reallocation is possible, then controls 65 in step 307 examine R bit 266 of BST 137 for the data storage segment identified in SEG register 70 to determine whether that data storage segment is in the read or write mode. When R bit 266 is unity, the read mode is indicated; this causes controls 65 in step 308 to inhibit read ahead by setting IRAH bit 225 and DECCR bit 254 of LDT 133 for the logical device having the SEG 70 identified storage segment to unity. The operative effect on storage system 10 is to inhibit further reading of data into the SEG 70 identified data storage segment and primes the control unit 11 to lock for a deallocation when the next CCR is sent to host 12 for the related logical device. The practical effect is that the host 12, which has a read operation pending with the device 13 associated with the SEG 70 identified data storage segment will read data from that data storage segment of buffer 15 until a channel command retry (CCR) is required, as described with respect to Figure 7; then, that segment will be deallocated for permitting a later paired allocation of data storage segments to the corresponding device 13, as fully explained with respect to Figure 7. When the mode of operation for the SEG 70 identified data storage segments is not the read mode, then controls 65 at step 309 proceed with deallocation by activating a logic module (not shown) termed "BM DBS" which causes controls 65 to deallocate the SEG 70 identified data storage segment. Deallocation follows normal and known procedures; such deallocation can include writing data from the SEG 70 identified data storage segment to the corresponding device 13.

Then controls 65 in step 310 examine the other data storage segment in the segment pair that corresponds to the data storage segment just deallocated in step 309. When the just-deallocated segment is an odd numbered segment, then the next lower numbered even segment is the other segment. When the just-deallocated segment is an even numbered segment, then the next higher odd numbered segment is the other segment. If such other segment is allocated, then it must be deallocated for permitting dynamic reallocation with the just-deallocated data storage segment. Accordingly, in step 311, controls 65 again activate logic module BM DBS for deallocating the identified other segment. Upon completion of step 311, or if the other segment was not allocated at step 310 (bit D 267 of BST 137 equalled zero), there are two data storage segments which are pairable and deallocated. These two data storage segments are now available for allocation as a pair for the device 13 which formerly had the SEG 70 identified data

storage segment for completing its logical device. On the other hand, if in step 310 the identified other segment is free, then no deallocation is required. Then controls 65 in step 312 adds the SEG 70 identified device 13 address (DADDR) into PAT 134 of Figure 5 and sets the corresponding P bit 135 to unity. This primes the allocation procedures of control 34 for allocating a pair of data storage, segment of data buffer 15 to the SEG 70 identified device 13. The actual allocation occurs as described with respect to Figure 7 and does not occur until a host 12 requires further data transfer activity with such identified device 13. Then controls 65 at 503 enables control 34 to perform other machine activities pending receipt of the next data transfer command from a host 12.

Figure 7 illustrates how the dynamic reallocation is completed upon receipt of a host-issued command after the above-described deallocation operations. Certain functions are performed in decoding the received host-issued command as indicated by the legend CS DCD. At step 400 the mode of operation identified in BST 137 for the addressed device 13 is examined. If it is in the read mode, as indicated by R bit 266, then at 404 control 34 examines BST 137 to determine whether the corresponding data storage segment is empty (MT) by examining the corresponding buffer record table as referred to earlier. If the buffer record table shows data stored in the data storage segment of the addressed logical device (as by having an entry identify a data record) then at step 405 ACT bit 262 of the corresponding BST 137 register is set to unity. Then at 407-411 further machine operations with respect to command execution, not pertinent to an understanding of the present invention, are performed.

Returning to step 400, when the write mode is indicated in BST 137 by R bit 266 being equal to zero, control 34 in step 401 determines whether data is stored within the data storage segment corresponding to the addressed device 13. If the data storage segment is full, it cannot receive any additional data. Accordingly, a channel command retry is sent to the command-issuing host 12 at step 402. When the host 12 accepts the CCR, CCR bit 245 of command status table 131 is set to unity. See patent 4403286 for more detail.

In some instances, channel adapter CXX 80 may have sent a CCR without involving control 34 (a normal known practice of IBM control units). In such a case, no additional CCR is sent at step 402. When CXX 80 sends a CCR, it notifies control 34 such that CCR bit 245 of command status table CST 131 is set. Control 34 before sending a CCR to CXX 80 examines the CST 131 CCR bit 245; if set, a CCR has been sent and no additional CCR will be sent in step 402.

If the examined data storage segment is not full, then at 403 ACT bit 262 of BST 137 is set to unity. Then at 416, control 34 determines whether a CCR has been sent, such as at step 402 and CCR bit 245 of CST 131. When a CCR is sent, the logic module BM IDF (not shown) is activated at step 337 for incrementing the respective CCRK count 41, 42 using known data processing counting techniques. At 420, additional functions of the command decoding are performed not pertinent to an understanding of the present invention. Then control 34 in step 421 examines BSTP 253 for the addressed device 13. If BSTP 253 is equal to zero, then no data storage segment of data buffer 15 is currently allocated to the addressed device. At 430, control 34 activates logic module BM ABS which performs the functions described with respect to Figure 5. Upon completion of the allocation, which will include a paired allocation during dynamic reallocation, a DEVICE END (DE) is sent to host 12 using the channel command retry procedure described in U. S. Patent 3,688,274. Then control 34 proceeds to other machine activities at 503 awaiting retransmission of the same command received as indicated at the beginning of the description of Figure 7. Then the steps are repeated, however, the next iteration of the command execution finds the allocation completed through step 430 and the requested data transfer ensues.

Returning to step 421, when BSTP has a non-zero value in it, the ACT 262 corresponding to the addressed device 13 is set to unity for showing activity during a normalized elapsed time period. Then at 423, bit DECCR 254 of LDT 133 is examined. If it is zero, then no additional control activity is needed; the addressed device 13 is started in step 424. Then control 34 proceeds to other machine activity pending the device 13 bringing the magnetic tape (not shown) up to speed across its transducer. At step 423, when DECCR bit 423 is set to unity and a CCR was sent at step 402, or earlier, with respect to the data storage segment (the CCR was actually sent with respect to the logical device to which the data storage segment is allocated); then the currently allocated data storage segment is deallocated at step 425 and at 426 DECCR bit 254 is reset to zero. Steps 430 and 427 are performed when either BSTP 253 for the addressed device 13 equals zero or null at step 421, or upon the completion of step 426. In step 427, control 34 allocates a pair of the data storage segments of buffer 15, such as the data storage segments which have been deallocated, to the addressed device 13. Figure 5 illustrates the allocation procedure. The allocation of the segments completes the dynamic reallocation procedures enabling storage system 10 to proceed with the requested data transfer with a buffer allocation which

now can handle ensuing data transfers for the addressed device 13 more efficiently. This fact is signalled to the requesting host 12 by storage system 10 sending a DEVICE END (DE) at step 430 via CXX 80. While the storage system 10 proceeds to other machine activity by control 34 exiting the illustrating procedures at 503, the requesting host 12 responds to the DE by retransmitting the data transfer requesting command to storage system 10.

Claims

1. A data storage system (10) for handling a plurality of independent data transfers between a host processor (12) and a plurality of addressable data storage devices (13), each of said data transfers including the transfer of a predetermined succession of data blocks to or from one of said addressable data storage devices, said data storage system including:

a data buffer (15) having a plurality of allocatable data storage segments (17), each of said segments having a plurality of addressable data storage registers and being capable of storing one or more data blocks;

and transfer means (16, 83) coupled to the data buffer for transferring said data blocks into and out of said data buffer in said plurality of independent data transfers;

and characterised by:

system means (34, 45, 46, 47) for indicating a predetermined elapsed time;

intensity means (34, 41, 42), connected to said transfer means and to said data buffer, for sensing and recording the intensity of activity of each individual data storage segment during said predetermined elapsed time;

block length means (137, 268), connected to said data buffer and to said transfer means, for indicating for each individual data storage segment the length of the data blocks currently being stored therein;

checking means (34, 65), connected to said block length means, said system means, and to said intensity means, responsive to said system means indicating a predetermined elapsed time, for identifying a data storage segment for reallocation that has the greatest recorded intensity of activity during said predetermined elapsed time and that also has stored data blocks exceeding a predetermined block length;

and allocation control means (34, 45), connected to said checking means and to said data buffer, responsive to the identification of the data storage segment for reallocation, for allocating an additional data storage segment

to said data storage segment identified for reallocation.

2. The data storage system set forth in claim 1, further including:

reset means in said checking means, connected to said system means and to said intensity means, for responding to said indication of said predetermined elapsed time to initiate measurement of another predetermined elapsed time and to reset said intensity means to restart said intensity measurements.

3. The data storage system set forth in claim 2, further including:

buffer status table means (137), connected to said buffer, for storing indications of: the status of each of said data storage segments wherein said status shows the allocation of said data storage segments to respective independent data transfers; the availability of each data storage segment for allocation; and whether a data storage segment is allocated with another data storage segment to one independent data transfer as a paired allocation, said buffer storage table means being connected to said allocation control means for receiving and storing allocation changes;

availability means in said checking means, connected to said buffer status table means and to said reset means, for indicating that none of said data storage segments are available for allocation and to inhibit said reset means and said allocation means from allocating any of said data storage segments while said none indication is active; and

deallocation means, connected to said buffer and to said availability means, for deallocating data storage segments from said respective independent data transfers and then activating said availability means to remove said none indication.

4. The data storage system set forth in any preceding claim, further including:

attachment means (80) for connecting said data storage system to said host processor, and connected to said transfer means for transferring data between said data buffer and said host processor;

said system means being connected to said transfer means and having counting means (45) for counting the number of accesses to any of said data storage devices;

limit value means (47) in said system means for storing a limit value indicating expiration of the normalized predetermined elapsed time period, compare means (46) in



now can handle ensuing data transfers for the addressed device 13 more efficiently. This fact is signalled to the requesting host 12 by storage system 10 sending a DEVICE END (DE) at step 430 via CXX 80. While the storage system 10 proceeds to other machine activity by control 34 exiting the illustrating procedures at 503, the requesting host 12 responds to the DE by retransmitting the data transfer requesting command to storage system 10.

Claims

1. A data storage system (10) for handling a plurality of independent data transfers between a host processor (12) and a plurality of addressable data storage devices (13), each of said data transfers including the transfer of a predetermined succession of data blocks to or from one of said addressable data storage devices, said data storage system including:

a data buffer (15) having a plurality of allocatable data storage segments (17), each of said segments having a plurality of addressable data storage registers and being capable of storing one or more data blocks;

and transfer means (16, 83) coupled to the data buffer for transferring said data blocks into and out of said data buffer in said plurality of independent data transfers;

and characterised by:

system means (34, 45, 46, 47) for indicating a predetermined elapsed time;

intensity means (34, 41, 42), connected to said transfer means and to said data buffer, for sensing and recording the intensity of activity of each individual data storage segment during said predetermined elapsed time;

block length means (137, 268), connected to said data buffer and to said transfer means, for indicating for each individual data storage segment the length of the data blocks currently being stored therein;

checking means (34, 65), connected to said block length means, said system means, and to said intensity means, responsive to said system means indicating a predetermined elapsed time, for identifying a data storage segment for reallocation that has the greatest recorded intensity of activity during said predetermined elapsed time and that also has stored data blocks exceeding a predetermined block length;

and allocation control means (34, 45), connected to said checking means and to said data buffer, responsive to the identification of the data storage segment for reallocation, for allocating an additional data storage segment

to said data storage segment identified for reallocation.

2. The data storage system set forth in claim 1, further including:

reset means in said checking means, connected to said system means and to said intensity means, for responding to said indication of said predetermined elapsed time to initiate measurement of another predetermined elapsed time and to reset said intensity means to restart said intensity measurements.

3. The data storage system set forth in claim 2, further including:

buffer status table means (137), connected to said buffer, for storing indications of: the status of each of said data storage segments wherein said status shows the allocation of said data storage segments to respective independent data transfers; the availability of each data storage segment for allocation; and whether a data storage segment is allocated with another data storage segment to one independent data transfer as a paired allocation, said buffer storage table means being connected to said allocation control means for receiving and storing allocation changes;

availability means in said checking means, connected to said buffer status table means and to said reset means, for indicating that none of said data storage segments are available for allocation and to inhibit said reset means and said allocation means from allocating any of said data storage segments while said none indication is active; and

deallocation means, connected to said buffer and to said availability means, for deallocating data storage segments from said respective independent data transfers and then activating said availability means to remove said none indication.

4. The data storage system set forth in any preceding claim, further including:

attachment means (80) for connecting said data storage system to said host processor, and connected to said transfer means for transferring data between said data buffer and said host processor;

said system means being connected to said transfer means and having counting means (45) for counting the number of accesses to any of said data storage devices;

limit value means (47) in said system means for storing a limit value indicating expiration of the normalized predetermined elapsed time period, compare means (46) in



said system means and connected to said counting means and said limit value means for comparing said counted number of accesses with said limit value, and when said counted number of accesses equals or exceeds said limit value supplying said elapsed time indication.

5. The data storage system set forth in any preceding claim, further including:

activity indicating means (262), connected to said transfer means, for recording whether or not any activity has occurred with respect to respective ones of said data storage segments; and

deallocation means, connected to said activity indicating means and to said checking means, for indicating said data storage segments not having any activity recorded by said activity indicating means as eligible for allocation as said additional storage segment to said data storage segment having the greatest recorded intensity of activity.

6. The data storage system set forth in any preceding claim, further including:

contend means (56), connected to said allocation control means and to said data buffer, for sensing attempted allocations of said data storage segments that fail and for indicating a sensed failed allocation as a contention indication;

inhibit means in said checking means, connected to said contend means, and responsive to said contention indication to inhibit said checking means from responding to said system means indicating a predetermined elapsed time so long as said contention indication is indicating a failed allocation; and

means connected to said contend means for resetting said contention indication for permitting said checking means to respond to said system means.

7. A method of operating a data storage system (10) for handling a plurality of independent data transfers between a host processor (12) and a plurality of addressable data storage devices (13), said data storage system including a data buffer (15) having a plurality of allocatable data storage segments (17), each of said segments having a plurality of addressable data storage registers and being capable of storing one or more data blocks;

said method including the steps of:

allocating predetermined ones of said data storage segments for respective independent data transfers;

transferring data by said independent data transfers in data blocks;

measuring the length of data blocks being transferred in said respective independent data transfers;

memorizing the amount of data stored and the free space available for data storage in each of said data storage segments as data storage status;

respectively counting the number of data transfer delays encountered by each of said independent data transfers due to the data storage requirements of any given data transfer not being met;

establishing a time period normalized relative to the activity of said data buffer for all of said independent data transfers;

measuring elapsed time in a normalized manner;

comparing said measured time with said established time period, and when said measured time exceeds or equals said established time, comparing the number of delays counted for each of said data storage segments, and allocating an additional data storage segment to the independent data transfer allocated to the data storage segment with the greatest number of delays that also has stored data blocks exceeding a predetermined block length, when said measured time is less than said established time, continuing the transfer of data.

8. The method set forth in claim 7, further including the steps of:

in said measuring elapsed time step, counting the number of accesses to said data storage segments as an indication of normalized elapsed time;

in said establishing step, setting a count value as representing said normalized elapsed time period; and

in said comparing step, comparing said set count value with said access count as representing the comparison of said measured time with said established time period.

9. The method set forth in claim 7 or 8, further including the steps of:

when attempting to allocate said additional data storage segment to an independent data transfer and detecting that none of said data storage segments are available to be said additional data storage segment, setting a contention indication signifying contention for allocation;

deallocating one of said allocated data storage segments and removing said conten-



tion indication;

and delaying said comparing step until after said contention indication has been removed so that said deal location step is completed before any reallocation steps are performed.

Patentansprüche

1. Ein Datenspeichersystem (10) zur Durchführung einer Mehrzahl an unabhängigen Datenübertragungen zwischen einem Host-Prozessor (12) und einer Mehrzahl an adressierbaren Datenspeichereinrichtungen (13), wobei jede der Datenübertragungen die Übertragung einer vorbestimmten Folge von Datenblöcken zu oder von einer der adressierbaren Datenspeichereinrichtungen mit einschließt, wobei dieses Datenspeichersystem folgendes umfaßt:

einen Datenpuffer (15) mit einer Mehrzahl an zuteilbaren Datenspeichersegmenten (17), wobei jedes dieser Segmente mit einer Mehrzahl an adressierbaren Datenspeicherregistern ausgestattet und zur Speicherung eines oder mehrerer Datenblöcke in der Lage ist;

Ein Übertragungsmittel (16, 83), das an den Datenpuffer gekoppelt ist, um die Datenblöcke in dieser Mehrzahl an unabhängigen Datenübertragungen in den und aus dem Datenpuffer zu übertragen,

dadurch gekennzeichnet, daß folgende Mittel vorhanden sind:

Ein Systemmittel (34, 45, 46, 47) zur Anzeige einer vorbestimmten durchlaufenen Zeit;

Ein Intensitätsmittel (34, 41, 42), das an dieses Übertragungsmittel und an den Datenpuffer angeschlossen ist, um die Aktivitätsintensität jedes einzelnen Datenspeichersegments während der vorbestimmten durchlaufenen Zeit zu messen und aufzuzeichnen;

Ein Blocklängenmittel (137, 268), das an diesen Datenpuffer und an die Übertragungsmittel angeschlossen ist, um für jedes einzelne Datenspeichersegment die Länge des derzeit gespeicherten Datenblocks anzuzeigen;

Ein Prüfmittel (34, 65), das an das Blocklängenmittel, an das Systemmittel und an das Systemmittel angeschlossen ist und auf das Systemmittel reagiert und eine vorbestimmte durchlaufene Zeit anzeigt, um ein Datenspeichersegment für die Neuordnung zu identifizieren, welches die größte aufgezeichnete Aktivitätsintensität während der vorbestimmten durchlaufenen Zeit aufweist und welches gespeicherte Datenblöcke aufweist, die eine vorbestimmte Blocklänge überschreiten;

Ein Zuordnungssteuermittel (34, 45), das an das Prüfmittel und an den Datenpuffer an-

geschlossen ist und auf die Identifikation des Datenspeichersegments für die Neuordnung reagiert, um dem für die Neuordnung identifizierten Datenspeichersegment ein neues Datenspeichersegment zuzuordnen.

2. Das in Anspruch 1 beschriebene Datenspeichersystem, einschließlich:

Einstellungsmittel in diesem Prüfmittel, das an das Systemmittel und an das Intensitätsmittel angeschlossen ist, um auf die Anzeige der vorbestimmten durchlaufenen Zeit zu reagieren, um eine Messung einer anderen vorbestimmten durchlaufenen Zeit zu bewirken und um das Intensitätsmittel neu einzustellen, um die Intensitätsmessungen neu zu starten.

3. Das in Anspruch 2 beschriebene Datenspeichersystem, einschließlich:

Pufferstatusabellenmittel (137), das an den Puffer angeschlossen ist, um folgende Anzeigen zu speichern: den Status jedes Datenspeichersegments, wobei der Status die Zuordnung der Datenspeichersegmente zu den entsprechenden unabhängigen Datenübertragungen, die Verfügbarkeit jedes Datenspeichersegments für die Zuordnung und die Tatsache, ob ein Datenspeichersegment einem anderen Datenspeichersegment für eine einzige unabhängige Datenübertragung als gepaarte Zuordnung zugeordnet ist, zeigt, wobei das Pufferspeichertabellenmittel an das Zuordnungssteuermittel angeschlossen ist, um Zuordnungsänderungen zu empfangen und zu speichern;

Verfügbarkeitsmittel im Prüfmittel, das an das Pufferstatusabellenmittel und an das Neueinstellungsmittel angeschlossen ist, um anzuzeigen, daß keines der Datenspeichersegmente für die Zuordnung verfügbar ist und um das Neueinstellungsmittel und das Zuordnungsmittel davon abzuhalten, eines der Datenspeichersegmente zuzuordnen, während eine Nichtanzeige aktiv ist; und

Zuordnungsauflösungsmittel, das an den Puffer und an das Verfügbarkeitsmittel angeschlossen ist, um eine Zuordnungsauflösung der Datenspeichersegmente in den entsprechenden unabhängigen Datenübertragungen durchzuführen und dann dieses Verfügbarkeitsmittel aktiviert, um die Nichtanzeige zu entfernen.

4. Das Datenspeichersystem, wie es in allen bisher aufgeführten Ansprüchen beschrieben wurde, einschließlich:

Zusatzmittel (80) für das Anschließen des Datenspeichersystems an den Host-Prozessor



und angeschlossen an das Übertragungsmittel für die Datenübertragung zwischen dem Datenpuffer und dem Host-Prozessor;

das Systemmittel ist an das Übertragungsmittel angeschlossen und besitzt ein Zählmittel (45) zur Zählung der Anzahl an Zugriffen auf ein beliebiges Datenspeicher-Device;

Grenzwertmittel (47) im Systemmittel für die Speicherung eines Grenzwerts, der den Ablauf der normalisierten vorbestimmten durchlaufenen Zeitperiode anzeigt, ein Vergleichsmittel (46) im Systemmittel, welches an das Zählmittel und an das Grenzwertmittel angeschlossen ist, um die gezählte Anzahl an Zugriffen mit dem Grenzwert zu vergleichen und welches, wenn die gezählte Anzahl an Zugriffen den Grenzwert erreicht oder überschreitet, die Anzeige der durchlaufenen Zeit liefert.

5. Das Datenspeichersystem, wie es in allen bisher aufgeführten Ansprüchen beschrieben wurde, einschließlich:

Ein aktivitätsanzeigendes Mittel (262), das an das Übertragungsmittel angeschlossen ist, um aufzuzeichnen, ob eine Aktivität in bezug auf entsprechende Aktivitäten der Datenspeichersegmente aufgetreten ist;

ein Zuordnungsauflösmittel, das an das aktivitätsanzeigende Mittel und an das Prüfmittel angeschlossen ist, um Datenspeichersegmente, die keine durch ein aktivitätsanzeigendes Mittel aufgezeichnete Aktivität aufweisen, als bereit für die Zuordnung als zusätzliches Speichersegment zum Datenspeichersegment mit der größten aufgezeichneten Aktivitätsintensität zu kennzeichnen.

6. Das Datenspeichersystem, wie es in allen bisher aufgeführten Ansprüchen beschrieben wurde, einschließlich:

ein Konkurrenzmittel (56), das an das Zuordnungssteuermittel und an den Datenpuffer angeschlossen ist, um versuchte Zuordnungen von Datenspeichersegmenten zu registrieren, die gescheitert sind und zur Anzeige von registrierten gescheiterten Zuordnungen als Konkurrenzanzeige;

ein Verhinderungsmittel im Prüfmittel, das mit dem Konkurrenzmittel verbunden ist und auf diese Konkurrenzanzeige reagiert, um zu verhindern, daß das Prüfmittel auf das Systemmittel reagiert und eine vorbestimmte durchlaufene Zeit solange anzeigt, wie diese Konkurrenzanzeige eine gescheiterte Zuordnung anzeigt;

ein Mittel, das an das Konkurrenzmittel angeschlossen ist, um die Konkurrenzanzeige

neu einzustellen, um dem Prüfmittel zu ermöglichen, auf das Systemmittel anzusprechen.

7. Eine Methode zum Betreiben eines Datenspeichersystems (10) für den Umgang mit einer Mehrzahl an unabhängigen Datenübertragungen zwischen einem Host-Prozessor (12) und einer Mehrzahl an adressierbaren Datenspeicher-Devices (13), wobei das Datenspeichersystem einen Datenpuffer (15) mit einer Mehrzahl an einteilbaren Datenspeichersegmenten (17) enthält, wobei jedes der Segmente mit einer Mehrzahl an adressierbaren Datenspeicherregistern ausgestattet ist und einen oder mehrere Datenblöcke speichern kann;

wobei diese Methode die folgenden Schritte enthält:

Zuordnung von vorbestimmten Datenspeichersegmenten für entsprechende unabhängige Datenübertragungen;

Übertragung von Daten durch unabhängige Datenübertragungen in Datenblöcken;

Messung der Länge der Datenblöcke, die durch die entsprechenden unabhängigen Datenübertragungen übertragen werden;

Aufzeichnung der Menge an gespeicherten Daten und verfügbarer freier Speicherplatz für die Datenspeicherung in jedem der Datenspeichersegmente als Datenspeicherstatus;

Zählung der Anzahl an Datenübertragungsverzögerungen, die bei Jeder unabhängigen Datenübertragung aufgetreten sind, weil die Datenspeicherungsanforderungen einer gegebenen Datenübertragung nicht erfüllt wurden;

Festlegung einer relativ zur Aktivität des Datenpuffers normalisierten Zeitperiode für alle unabhängigen Datenübertragungen;

Messung der durchlaufenen Zeit in einer normalisierten Weise;

Vergleich der gemessenen Zeit mit der festgelegten Zeitperiode, und, wenn die gemessene Zeit die festgelegte Zeitperiode erreicht oder überschreitet, Vergleich der Anzahl an gezählten Verzögerungen für Jedes der Datenspeichersegmente und Zuordnung eines zusätzlichen Datenspeichersegments zur unabhängigen Datenübertragung, die dem Datenspeichersegment mit der größten Anzahl an Verzögerungen zugeordnet ist und die ebenfalls gespeicherte Datenblöcke aufweist, die eine vorbestimmte Blocklänge überschreiten; wenn die gemessene Zeit unterhalb der festgelegten Zeit liegt, folgt eine Fortsetzung der Datenübertragung.



8. Die in Anspruch 7 beschriebene Methode, einschließlich folgender Schritte:

Im Schritt der Messung der durchlaufenen Zeit Zählung der Anzahl an Zugriffen auf die Datenspeichersegmente als Anzeige der normalisierten durchlaufenen Zeit;

Im Zeitfestlegungsschritt Einstellung eines Zählwerts zur Darstellung der normalisierten durchlaufenen Zeitperiode;

Im Vergleichsschritt Vergleich des eingestellten Zählwerts mit der Zählung der Zugriffe zur Darstellung des Vergleichs der gemessenen Zeit mit der festgelegten Zeitperiode.

9. Die in Anspruch 7 oder 8 beschriebene Methode, einschließlich folgender Schritte:

Beim Versuch der Zuordnung des zusätzlichen Datenspeichersegments zu einer unabhängigen Datenübertragung und bei der Feststellung, daß keines der Datenspeichersegmente verfügbar ist, um dieses Datenspeichersegment darzustellen, Einstellung einer Konkurrenzanzeige, die der Zuordnung einen Konkurrenzzustand anzeigt;

Zuordnungsauflösung eines der zugeordneten Datenspeichersegmente und Entfernen der Konkurrenzanzeige;

Verzögerung des Vergleichsschrittes, bis die Konkurrenzanzeige entfernt ist, so daß der Verzögerungsvergleichsschritt beendet ist, bevor jegliche Neuordnungsschritte ausgeführt werden.

Revendications

1. Système de mémorisation de données (10) pour traiter une pluralité de transferts de données indépendants entre un processeur central (12) et une pluralité de dispositifs de mémorisation de données adressables (13), chacun desdits transferts de données comportant le transfert d'une suite prédéterminée de blocs de données vers ou depuis un desdits dispositifs de mémorisation de données adressables, ledit système de mémorisation de données comportant :

une mémoire tampon de données (15) comportant une pluralité de segments de mémorisation de données attribuables (17), chacun desdits segments comportant une pluralité de registres de mémorisation de données adressables et pouvant mémoriser un ou plusieurs blocs de données ;

et un moyen de transfert (16, 83) couplé à la mémoire tampon de données pour transférer lesdits blocs de données dans et hors la mémoire tampon de données dans ladite pluralité de transferts de données indépendants ;

et caractérisé par :

un moyen de système (34,45 , 46, 47) pour indiquer un temps d'exécution prédéterminé ;

un moyen d'intensité (34, 41, 42) connecté audit moyen de transfert et à ladite mémoire tampon de données, pour détecter et enregistrer l'intensité de l'activité de chaque segment de mémorisation de données individuel pendant le temps d'exécution prédéterminé ;

un moyen de longueur de bloc (137, 268) connecté à la mémoire tampon de données et audit moyen de transfert, pour indiquer pour chaque segment de mémorisation de données la longueur des blocs de données qui sont actuellement mémorisés dans celui-ci ;

un moyen de vérification (34, 65) connecté audit moyen de longueur de bloc, audit moyen de système et audit moyen d'intensité, répondant audit moyen de système indiquant un temps d'exécution prédéterminé, pour identifier un segment de mémorisation de données pour réattribution qui présente l'intensité d'activité enregistrée la plus grande pendant ledit temps d'exécution prédéterminé, et qui également comporte des blocs de données mémorisés dépassant une longueur de bloc prédéterminée ;

et un moyen de commande d'attribution (34, 45), connecté audit moyen de vérification et à ladite mémoire tampon de données, répondant à l'identification du segment de mémorisation de données pour réattribution, pour attribuer un segment de mémorisation de données supplémentaire audit segment de mémorisation de données identifié pour réattribution.

2. Système de mémorisation de données selon la revendication 1, comportant de plus :

un moyen de remise à zéro dans ledit moyen de vérification, connecté audit moyen de système et audit moyen d'intensité, pour répondre à ladite indication dudit temps d'exécution prédéterminé pour lancer la mesure d'un autre temps d'exécution prédéterminé et pour remettre à zéro ledit moyen d'intensité pour recommencer lesdites mesures d'intensité.

3. Système de mémorisation de données selon la revendication 2, comportant de plus :

un moyen de table d'états de mémoire tampon (137) connecté à ladite mémoire tampon, pour mémoriser des indications se rapportant à : l'état de chacun des segments de mémorisation de données, dans lequel ledit état représente l'attribution desdits segments de mémorisation de données aux transferts de



données indépendant respectifs ; la disponibilité de chaque segment de mémorisation de données pour attribution ; et si un segment de mémorisation de données est attribué avec un autre segment de mémorisation de données à un transfert de données indépendant comme attribution appariée, ledit moyen de table d'état de mémoire tampon étant connecté au moyen de commande d'attribution pour recevoir et mémoriser les changements d'attribution ;

un moyen de disponibilité dans ledit moyen de vérification, connecté audit moyen de table d'états de mémoire tampon et audit moyen de remise à zéro pour indiquer qu'aucun desdits segments de mémorisation de données n'est disponible pour attribution et pour interdire audit moyen de remise à zéro et audit moyen d'attribution d'attribuer l'un quelconque desdits moyens de mémorisation de données tant que ladite indication de ne rien faire est active, et

un moyen de désattribution, connecté à ladite mémoire tampon et audit moyen de disponibilité, pour désattribuer les segments de mémorisation de données à partir desdits transferts de données indépendants respectifs et activer ensuite ledit moyen de disponibilité pour supprimer ladite indication de ne rien faire.

4. Système de mémorisation de données selon l'une quelconque des revendications précédentes, comportant de plus :

un moyen de connexion (80) pour connecter ledit système de mémorisation de données audit processeur central, et connecté audit moyen de transfert pour transférer les données entre ladite mémoire tampon de données et ledit processeur central ;

ledit moyen de système étant connecté audit moyen de transfert et comportant un moyen de comptage (45) pour compter le nombre d'accès à l'un quelconque desdits dispositifs de mémorisation de données ;

un moyen de valeur limite (47) dans ledit moyen de système pour mémoriser une valeur limite indiquant la fin de l'intervalle de temps d'exécution prédéterminé normalisé, un moyen de comparaison (46) dans ledit moyen de système, et connecté audit moyen de comptage et audit moyen de valeur limite pour comparer le nombre compté d'accès à ladite valeur limite, et lorsque ledit nombre compté d'accès égal ou dépasse ladite valeur limite, délivrer ladite indication de temps d'exécution.

5. Système de mémorisation de données selon l'une quelconque des revendications précédentes, comportant de plus :

un moyen d'indication d'activité (262), connecté audit moyen de transfert, pour enregistrer si oui ou non une activité quelconque s'est produite par rapport aux segments de mémorisation respectifs parmi lesdits segments de mémorisation de données, et

un moyen de désattribution, connecté audit moyen d'indication d'activité et audit moyen de vérification, pour indiquer lesdits segments de mémorisation de données n'ayant aucune activité enregistrée par ledit moyen d'indication d'activité comme pouvant être choisi pour attribution comme dit segment de mémorisation supplémentaire audit segment de mémorisation de données ayant l'intensité d'activité enregistrée la plus grande.

6. Système de mémorisation de données selon l'une quelconque des revendications précédentes, comportant de plus :

un moyen de conflit (56), connecté audit moyen de commande d'attribution et à ladite mémoire tampon de données, pour détecter des essais d'attribution desdits segments de mémorisation de données qui échouent et pour indiquer une attribution échouée détectée comme indication de conflit ;

un moyen d'interdiction dans ledit moyen de vérification, connecté audit moyen de conflit et répondant à l'indication de conflit pour interdire audit moyen de vérification de répondre audit moyen de système indiquant un temps d'exécution prédéterminé tant que ladite indication de conflit indique une attribution qui a échoué, et

un moyen connecté audit moyen de conflit pour remettre à zéro l'indication de conflit pour permettre audit moyen de vérification de répondre audit moyen de système.

7. Procédé pour mettre en oeuvre un système de mémorisation de données (10) pour traiter une pluralité de transferts de données indépendants entre un processeur central (12) et une pluralité de dispositifs de mémorisation de données adressables (13), ledit système de mémorisation de données comportant une mémoire tampon de données (15) comportant une pluralité de segments de mémorisation de données attribuables (17), chacun desdits segments comportant une pluralité de registres de mémorisation de données adressables et pouvant mémoriser un ou plusieurs blocs de données ;

ledit procédé comportant les étapes consistant à :

attribuer un des segments de mémorisation



tion prédéterminé parmi les segments de mémorisation de données pour transferts de données indépendants respectifs ;

transférer les données par lesdits transferts de données indépendants en blocs de données ;

mesurer la longueur des blocs de données qui sont transférés dans lesdits transferts de données indépendants respectifs ;

mémoriser la quantité de données stockées et l'espace libre disponible pour mémorisation de données dans chacun desdits segments de mémorisation de données en tant qu'état de mémorisation de données ;

compter respectivement le nombre de retards de transfert de données rencontrés par chacun desdits transferts de données indépendants dû aux exigences de mémorisation de données de tout transfert de données donné qui n'est pas satisfait ;

établir un intervalle de temps normalisé par rapport à l'activité de ladite mémoire tampon de données pour la totalité desdits transferts de données indépendants ;

mesurer le temps d'exécution d'une manière normalisée ;

comparer ledit temps mesuré audit intervalle de temps établi, et lorsque ledit temps mesuré dépasse ou est égal audit temps établi, comparer le nombre de retards comptés pour chacun desdits segments de mémorisation de données, et attribuer un segment de mémorisation de données supplémentaire au transfert de données indépendant attribué au segment de mémorisation de données ayant le nombre de retards le plus important, qui a également mémorisé des blocs de données dépassant une longueur de bloc déterminée, et lorsque ledit temps mesuré est inférieur audit temps établi, poursuivre le transfert de données.

8. Procédé selon la revendication 7, comportant de plus les étapes consistant à :

dans ladite étape de mesure du temps d'exécution, compter le nombre d'accès auxdits segments de mémorisation de données comme une indication du temps d'exécution normalisé ;

dans ladite étape d'établissement, établir une valeur de compte comme représentant ledit intervalle de temps d'exécution normalisé, et

dans ladite étape de comparaison, comparer ladite valeur de compte établie audit compte d'accès comme représentant la comparaison dudit temps mesuré audit intervalle de temps établi.

9. Procédé selon la revendication 7 ou 8, comportant de plus les étapes consistant à :

lorsqu'on essaie d'attribuer ledit segment de mémorisation de données supplémentaire à un transfert de données indépendant et lorsqu'on essaie de détecter qu'aucun des segments de mémorisation de données n'est disponible pour être le segment de mémorisation de données supplémentaire, établir une indication de conflit signifiant le conflit pour attribution ;

désattribuer un desdits segments de mémorisation de données attribués et supprimer ladite indication du conflit ;

et retarder ladite étape de comparaison jusqu'au moment où l'indication de conflit a été enlevée, de sorte que ladite étape de désattribution est achevée avant que toute étape de réattribution quelconque ne soit effectuée.